

Schedule for PR-0138526673 dated 16-12-2024

PR Item No			Vendor Confirmation
10	Short Description	SELF ADHESIVE PVC INSULATION TAPE - RED	-
	Technical Parameters		
	Width	18 mm	
	Length	8.0 meters	
	Colour	Red	
	Thickness of tape	0.1 to 0.15 mm	
	Adhesion to steel	1.6N/ 10mm width (min)	
	Adhesion to backing	1.3N/ 10mm width (min)	
	Tensile Strength	150N/ 10mm width per mm thickness (min)	
	Electrical Strength at room temperature	40kV/ mm thickness (min)	
	Electrical Strength at humid condition at 27°C+2%RH	35kV/ mm (min)	
	Make	M/s Steel grip or Equivalent	
	Confirming to	IS 7809: Part 3: Sec 1:1986(BIS Certification shall be submitted)	
	Flammability	Self extinguishing	
	Voltage	Suitable for primary insulation upto 440V	
	Storage Life	6 months(min) from dispatch	

PARIMI NAGA
 VENKATA SAI
 SURYATEJA

Digitally signed by
 PARIMI NAGA VENKATA
 SAI SURYATEJA
 Date: 2024.12.30
 15:18:01 +05'30'

Schedule for PR-0138526673 dated 16-12-2024

PR Item No			Vendor Confirmation
20	Short Description	SELF ADHESIVE PVC INSULATION TAPE - YELLOW	-
	Technical Parameters		
	Width	18 mm	
	Length	8.0 meters	
	Colour	Yellow	
	Thickness of tape	0.1 to 0.15 mm	
	Adhesion to steel	1.6N/ 10mm width (min)	
	Adhesion to backing	1.3N/ 10mm width (min)	
	Tensile Strength	150N/ 10mm width per mm thickness (min)	
	Electrical Strength at room temperature	40kV/ mm thickness (min)	
	Electrical Strength at humid condition at 27°C+2%RH	35kV/ mm (min)	
	Make	M/s Steel grip or Equivalent	
	Confirming to	IS 7809: Part 3: Sec 1:1986(BIS Certification shall be submitted)	
	Flammability	Self extinguishing	
	Voltage	Suitable for primary insulation upto 440V	
	Storage Life	6 months(min) from dispatch	

PARIMI NAGA
VENKATA SAI
SURYATEJA

Digitally signed by
PARIMI NAGA VENKATA
SAI SURYATEJA
Date: 2024.12.30
15:17:49 +05'30'

Schedule for PR-0138526673 dated 16-12-2024

PR Item No			Vendor Confirmation
30	Short Description	SELF ADHESIVE PVC INSULATION TAPE - BLUE	-
	Technical Parameters		
	Width	18 mm	
	Length	8.0 meters	
	Colour	Blue	
	Thickness of tape	0.1 to 0.15 mm	
	Adhesion to steel	1.6N/ 10mm width (min)	
	Adhesion to backing	1.3N/ 10mm width (min)	
	Tensile Strength	150N/ 10mm width per mm thickness (min)	
	Electrical Strength at room temperature	40kV/ mm thickness (min)	
	Electrical Strength at humid condition at 27°C+2%RH	35kV/ mm (min)	
	Make	M/s Steel grip or Equivalent	
	Confirming to	IS 7809: Part 3: Sec 1:1986(BIS Certification shall be submitted)	
	Flammability	Self extinguishing	
	Voltage	Suitable for primary insulation upto 440V	
	Storage Life	6 months(min) from dispatch	

PARIMI NAGA
 VENKATA SAI
 SURYATEJA

Digitally signed by
 PARIMI NAGA VENKATA
 SAI SURYATEJA
 Date: 2024.12.30
 15:17:38 +05'30'

Schedule for PR-0138526673 dated 16-12-2024

PR Item No			Vendor Confirmation
40	Short Description	SELF ADHESIVE PVC INSULATION TAPE - BLACK	-
	Technical Parameters		
	Width	18 mm	
	Length	8.0 meters	
	Colour	Black	
	Thickness of tape	0.1 to 0.15 mm	
	Adhesion to steel	1.6N/ 10mm width (min)	
	Adhesion to backing	1.3N/ 10mm width (min)	
	Tensile Strength	150N/ 10mm width per mm thickness (min)	
	Electrical Strength at room temperature	40kV/ mm thickness (min)	
	Electrical Strength at humid condition at 27°C+2%RH	35kV/ mm (min)	
	Make	M/s Steel grip or Equivalent	
	Confirming to	IS 7809: Part 3: Sec 1:1986 (BIS Certification shall be submitted)	
	Flammability	Self extinguishing	
	Voltage	Suitable for primary insulation upto 440V	
	Storage Life	6 months(min) from dispatch	

PARIMI NAGA
VENKATA SAI
SURYATEJA

Digitally signed by
 PARIMI NAGA VENKATA
 SAI SURYATEJA
 Date: 2024.12.30
 15:17:21 +05'30'

Schedule for PR-0138526673 dated 16-12-2024

PR Item No			Vendor Confirmation
50	Short Description	SELF ADHESIVE PVC INSULATION TAPE - GREEN	-
	Technical Parameters		
	Width	18 mm	
	Length	8.0 meters	
	Colour	Green	
	Thickness of tape	0.1 to 0.15 mm	
	Adhesion to steel	1.6N/ 10mm width (min)	
	Adhesion to backing	1.3N/ 10mm width (min)	
	Tensile Strength	150N/ 10mm width per mm thickness (min)	
	Electrical Strength at room temperature	40kV/ mm thickness (min)	
	Electrical Strength at humid condition at 27°C+2%RH	35kV/ mm (min)	
	Make	M/s Steel grip or Equivalent	
	Confirming to	IS 7809: Part 3: Sec 1:1986 (BIS Certification shall be submitted)	
	Flammability	Self extinguishing	
	Voltage	Suitable for primary insulation upto 440V	
	Storage Life	6 months (min) from dispatch	

PARIMI NAGA
VENKATA SAI
SURYATEJA

Digitally signed by
PARIMI NAGA VENKATA
SAI SURYATEJA
Date: 2024.12.30
15:17:02 +05'30'