



A Maharatna Company

एन टी पी सी लिमिटेड

(भारत सरकार का उद्यम)

NTPC Limited

(A Govt. of India Enterprise)

(Formerly National Thermal Power Corporation Ltd.)

(केंद्रीय कार्यालय नोएडा)

Corporate Center NOIDA

Reference : CC-ENGG-4540-001-201-PVE-B-175

Date : 07/04/2023

From : Subodh Pandit
ADDL. GENERAL MANAGER

To : BHARAT HEAVY ELECTRICALS LTD
NEW DELHI
110049
IN

Cc : sisodia@bhel.in

Subject : EPC TTPP3 (2x660MW)

Please find enclosed following drawings/ documents for necessary action at your end.

Vendor Drg. No. : 34690002296

Orgn. Drg. No. : 4540-001-201-PVE-B-175

Revision No. : 01

Drg. Title : 420 KV SHUNT REACTOR- OUTLINE GENERAL ARRANGEMENT

App. Category : CATREL

Release Date : 07/04/2023



Scan to verify

Comments : AUTO ARCHIVED IN NTPC REPOSITORY.



Engineering Division
ISO 9001:2008 Certified



अभियंत्रिकी कार्यालय परिसर, प्लॉट नं.- ए 8ए, सेक्टर-24, पोस्ट बॉक्स नं.- 13, नोएडा (उ.प्र.) पिन-201 307

टेलिफोन नं.- 0120-2410333, 2410116 फैक्स-0120-2410136, 2410137

पंजीकृत कार्यालय: एनटीपीसी भवन, स्कोप कॉम्प्लेक्स, 7 इंस्टीट्यूशनल एरिया, लोधी रोड, नई दिल्ली-110 003

टेलिफोन नं.- 011-24361018 फैक्स-011-24361018, वेबसाइट: www.ntpc.co.in

ENGINEERING OFFICE COMPLEX, Plot No: A-8A, Sector-24, Post Box No: 13, Noida (UP), Pin-201 307





Telephone No: 0120-2410333, 2410116 Fax-0120-2410136, 2410137

Registered Office: NTPC Bhawan, Scope Complex, 7 Institutional Area, Lodhi Road, New Delhi-110 003

Telephone No: 011 2436100 Fax: 011 24361018, Website: www.ntpc.co.in

FIRST ANGLE PROJECTION

(All dimensions are in mm)

	REV.	DATE	ALT.		REV.	DATE	ALT.		ADDITIONAL INFORMATION	W.O. 62213-A-517-01	
			CHD.		01	04.04.23		CHD.		STATUS OF DRAWING	
						NTPC Comments incorporated			DISTRIBUTION OF PRINTS		
THE INFORMATION ON THIS DOCUMENT IS THE PROPERTY OF BHARAT HEAVY ELECTRICALS LIMITED. IT MUST NOT BE USED DIRECTLY OR INDIRECTLY IN ANY WAY DETRIMENTAL TO COMPANY.	<div>Note:- It is hereby confirmed that this document meets all the contract requirements including safety and statutory requirements and facilitate ease of operation and maintenance. In case any deviation is found, BHEL shall carry out all required changes/modifications without any cost implications to NTPC. In addition, Penalty on account of noncompliance of contract specification as deemed fit by NTPC shall be recovered</div>										
	Client		N T P C LIMITED								
	PROJECT	TALCHER THERMAL POWER PROJECT STAGE-III (2x660MW) EPC PACKAGE									
REF.DRG. NO.	PRODUCT		125 MVar, 420 KV, 3-PHASE SHUNT REACTOR								
	PO NO.		CS-4540-001A-2-FC-NOA-7227 DTD. 27/09/2022								
SIGN & DATE		BHARAT HEAVY ELECTRICALS LIMITED BHOPAL					NAME		SIGN	DATE	
						PREP.	SAMRENDRA KUMAR		--SD--	31.03.23	
						CKD.	AKSHAY DAVE		--SD--	31.03.23	
INVENTORY NO.	DEPT. CODE	TRE 406	CARD CODE	GRADE	SCALE NTS	WEIGHT (KG)		REF. TO ASSY. DRG.		ITEM NO.	NO. OF ITEMS
	TITLE						CARD CODE	BHEL DRAWING NO.			REV 01
	420 KV SHUNT REACTOR- OUTLINE GENERAL ARRANGEMENT							34690002296			
	NTPC DRAWING NO.						4540-001-201-PVE-B-175				

FIRST ANGLE PROJECTION

(ALL DIMENSIONS ARE IN mm)

96220 00 697 3 ON GRD

102

103

104

105

106

107

108

THE INFORMATION ON THIS DOCUMENT IS THE PROPERTY OF BHARAT HEAVY ELECTRICALS LTD. IT MUST NOT BE USED DIRECTLY OR INDIRECTLY IN ANY WAY DETRIMENTAL TO THE INTEREST OF THE COMPANY.


NOTES :-

1. WHEN REFERRING THIS DRAWING PLEASE QUOTE MVAR & W.O. NO.
2. 320 DIA. TWIN BI-DIRECTIONAL ROLLERS MOUNTED AT 1676 mm RAIL GAUGE IN BOTH DIRECTION ARE PROVIDED FOR MOVEMENT OF REACTOR AT SITE AND ROLLERS ARE TO BE REMOVED BEFORE ERECTION .
3. PAINT SHADE SHALL BE RAL 5012 BLUE.
4. WIRING FROM INSTRUMENT CTS. ETC. ARE NOT SHOWN FOR CLARITY.
5. FOUNDATION BOLTS ARE IN THE SCOPE OF BHEL SUPPLY.
6. FOR PART LIST OF OUTLINE GENERAL ARRANGEMENT REFER DRAWING NO. 3 469 00 02296.
7. DIMENSIONS SHOWN THUS ARE OVERALL SHIPPING DIMENSIONS EXCLUSIVE OF PACKING.
8. DIMENSIONS SHOWN ARE WITH REF.TO PLINTH LEVEL.
9. FOR TANK COVER BOLTED REFER DETAIL 'B' SHEET NO. 03.
10. HV, HVN BUSHING ARE BOUGHT OUT ITEM. HENCE, DIMENSION / WEIGHT RELATED TO THESE BUSHINGS ARE TENTATIVE. IT WILL BE FINALIZED (IF REQUIRED) AFTER VENDOR FINALIZATION.
11. FOR CRITICAL DIMENSIONS TOLERANCES ARE INDICATED IN THE DRAWING. FOR OTHER DIMENSION, GENERAL TOLERANCE MAY BE TREATED AS ±3%.

IMPORTANT NOTE :-

1. THE DESIGN FEATURES SHOWN ON THIS DRAWING (GENERALLY INLINE WITH IS:5553/IEC: 60076-6 APPLICABLE STANDARD & AGREED CUSTOMER SPECIFICATION) MEETS THE STATUTORY, REGULATORY & SAFETY REQUIREMENTS WITH RESPECT TO EARTHING ARRANGEMENT, DANGER & OTHER LABELS, CLEARANCES IN AIR PROVISION FOR PRESSURE RELIEF DEVICE, BUCHHOLZ RELAY AND ANTI-EARTHQUAKE CLAMPING ARRANGEMENT.

MIN. AIR CLEARANCES	
420 KV	145 KV
PHASE TO PHASE	4000
PHASE TO EARTH	3500
1050	



INVENTORY NO.		SIGN.DATE		REF.DRG.NO.	
F		E		D	
REV		DATE		ALT.	
CKD.		CKD.		KDSK	
APPD		APPD		KDSK	
ZONE		ZONE		CUSTOMER COMMENTS	
101		102		103	
104		105		106	
107		108		109	
110		111		112	
113		114		115	
116		117		118	
119		120		121	
122		123		124	
125		126		127	
128		129		130	
131		132		133	
134		135		136	
137		138		139	
140		141		142	
143		144		145	
146		147		148	
149		150		151	
152		153		154	
155		156		157	
158		159		160	
161		162		163	
164		165		166	
167		168		169	
170		171		172	
173		174		175	
176		177		178	
179		180		181	
182		183		184	
185		186		187	
188		189		190	
191		192		193	
194		195		196	
197		198		199	
200		201		202	
203		204		205	
206		207		208	
209		210		211	
212		213		214	
215		216		217	
218		219		220	
221		222		223	
224		225		226	
227		228		229	
230		231		232	
233		234		235	
236		237		238	
239		240		241	
242		243		244	
245		246		247	
248		249		250	
251		252		253	
254		255		256	
257		258		259	
260		261		262	
263		264		265	
266		267		268	
269		270		271	
272		273		274	
275		276		277	
278		279		280	
281		282		283	
284		285		286	
287		288		289	
290		291		292	
293		294		295	
296		297		298	
299		300		301	
302		303		304	
305		306		307	
308		309		310	
311		312		313	
314		315		316	
317		318		319	
320		321		322	
323		324		325	
326		327		328	
329		330		331	
332		333		334	
335		336		337	
338		339		340	
341		342		343	
344		345		346	
347		348		349	
350		351		352	
353		354		355	
356		357		358	
359		360		361	
362		363		364	
365		366		367	
368		369		370	
371		372		373	
374		375		376	
377		378		379	
380		381		382	
383		384		385	
386		387		388	
389		390		391	
392		393		394	
395		396		397	
398		399		400	
401		402		403	
404		405		406	
407		408		409	
410		411		412	
413		414		415	
416		417		418	
419		420		421	
422		423		424	
425		426		427	
428		429		430	
431		432		433	
434		435		436	
437		438		439	
440		441		442	
443		444		445	
446		447		448	
449		450		451	
452		453		454	
455		456		457	
458		459		460	
461		462		463	
464		465		466	
467		468		469	
470		471		472	
473		474		475	
476		477		478	
479		480		481	
482		483		484	
485		486		487	
488		489		490	
491		492		493	
494		495		496	
497		498		499	
500		501		502	
503		504		505	
506		507		508	
509		510		511	
512		513		514	
515		516		517	
518		519		520	
521		522		523	
524		525		526	
527		528		529	
530		531		532	
533		534		535	
536		537		538	
539		540		541	
542		543		544	
545		546		547	
548		549		550	
551		552		553	
554		555		556	
557		558		559	
560		561		562	
563		564		565	
566		567		568	
569		570		571	
572		573		574	
575		576		577	
578		579		580	
581		582		583	
584		585		586	
587		588		589	
590		591		592	
593		594		595	
596		597		598	
599		600		601	
602		603		604	
605		606		607	
608		609		610	
611		612		613	
614		615		616	
617		618		619	
620		621		622	
623		624		625	
626		627		628	
629		630		631	
632		633		634	
635		636		637	
638		639		640	
641		642		643	
644		645		646	
647		648		649	
650		651		652	
653		654		655	
656		657		658	
659		660		661	
662		663		664	
665		666		667	
668		669		670	
671		672		673	
674		675		676	
677		678		679	
680		681		682	
683		684		685	
686		687		688	
689		690		691	
692		693		694	
695		696		697	
698		699		700	
701		702		703	
704		705		706	
707		708		709	
710		711		712	
713		714		715	
716		717		718	
719		720		721	
722		723		724	
725		726		727	
728		729		730	
731		732		733	
734		735		736	
737		738		739	
740		741		742	
743		744		745	
746		747		748	
749		750		751	
752		753		754	
755		756		757	
758		759		760	
761		762		763	
764		765		766	
767		768		769	
770		771		772	
773		774		775	
776		777		778	
779		780		781	
782		783		784	
785		786		787	
788		789		790	
791		792		793	
794		795		796	
797		798		799	
800		801		802	
803		804		805	
806		807		808	
809		810		811	
812		813		814	
815		816		817	
818		819		820	
821		822		823	
824		825		826	
827		828		829	
830		831		832	
833		834		835	
836		837		838	
839		840		841	
842		843		844	
845		846		847	
848		849		850	
851		852		853	
854		855		856	
857		858		859	
860		861		862	
863		864		865	
866		867		868	
869		870		871	
872		873		874	
875		876		877	
878		879		880	
881		882		883	
884		885		886	
887		888		889	
890		891		892	
893		894		895	
896		897		898	
899		900		901	
902		903		904	
905		906		907	
908		909		910	
911		912		913	
914		915		916	
917		918		919	
920		921		922	
923		924		925	
926		927		928	
929		930		931	
932		933		934	
935		936		937	
938		939		940	
941		942		943	
944		945		946	
947		948		949	
950		951		952	
953		954		955	
956		957		958	
959		960		961	
962		963		964	
965		966		967	

FIRST ANGLE PROJECTION

96220 00 694 3 ON GRD

502

503

504

505

506

507

508

THE INFORMATION ON THIS DOCUMENT IS THE PROPERTY OF BHARAT HEAVY ELECTRICALS LTD.
IT MUST NOT BE USED DIRECTLY OR INDIRECTLY IN ANY WAY DETRIMENTAL TO THE INTEREST OF THE COMPANY.

REF.DRG.NO.

SIGN.DATE

INVENTORY NO.

APPROXIMATE WEIGHT & OIL QTY.	
DESCRIPTION	WT. IN KG
CORE AND WINDING	97270
TANK & FITTINGS	28000
BUSHINGS	2100
RADIATOR & CONSERVATOR PIPE WORK	15680
CONTROL CABINET	350
TOTAL OIL	44800
TOTAL WEIGHT	188200

NOTES:-
1. CABLE TRAY ON REACTOR TANK PROVIDED FOR CABLING OF INSTRUMENT.

COOLING SYSTEM

ITEM NO	DESCRIPTION	QTY	ZONE
30	LIFTING LUGS FOR RADIATORS (LIFTING CAPACITY 1100 KG EACH)	24	405-C
60	RADIATOR BANK	12	405-C
86C	AIR RELEASE PLUGS (3/4" BSP)	12	405-C
114	DRAIN PLUGS (3/4" BSP)	12	405-E
119	ISOLATING VALVES FOR RADIATORS (80 NB BUTTERFLY)	24	405-E
161	GAS COLLECTING DEVICE PIPE (6 NB)	2	407-C
163	EQUALISING PIPE (50NB)	1	304-C
163a	EQUALISING PIPE (25NB) FOR TURRETS	4	304-C

CONSERVATOR AND PIPE WORK

10a	INSPECTION COVER FOR OIL CONSERVATOR (BOLTED) (20 KG)	1	402-B
12	OIL GAUGE MAGNETIC TYPE WITH LOLA & HOLA	1	304-E
12a	PRISMATIC OIL LEVEL GAUGE (OVER LAPPED)	1	408-B
14a	50 NB DRAIN GATE VALVE FOR OIL CONSERVATOR	1	407-D
15	OIL CONSERVATOR 1300 DIA (ATMOSEAL TYPE)	1	402-B
17	MAINTENANCE FREE BREATHER	1	307-D
26	BUCHHOLZ RELAY (80 NB) (PLUG AND SOCKET TYPE)	2	403-C
27a	CANOPY FOR MOG. PRV. SPR & BUCHHOLZ RELAY	6	204-C
86a	AIR RELEASE PLUG (3/4" BSP) ON CONSERVATOR	2	204-B
86b	AIR RELEASE PLUG (1/4" BSP) FOR CONSERVATOR.	1	204-B
119a	ISOLATING GATE VALVE FOR BUCHHOLZ RELAY (80 NB)	2	403-C
119b	50 NB GATE VALVE FOR VACUUMING	1	205-B
119c	15 NB GATE VALVE FOR BREATHER/VACUUMING	1	205-B
125	GAS COLLECTING DEVICE.	2	402-E
153	CONSERVATOR SUPPORTS	2	204-C
164	BREATHER PIPE (25 NB)	1	206-C
168	CONSERVATOR PIPE (80 NB)	1	205-C
185	FLOW SENSITIVE CONSERVATOR ISOLATION VALVE	1	306-D
206	BHEL MONOGRAM	1	205-B
211	ATMOSEAL ARRANGEMENT (INSIDE THE CONSERVATOR)	1	206-C
211a	AIR CELL RUPTURE RELAY	1	203-B
213	CONSERVATOR DRAIN PIPE (60 NB)	1	304-D

TURRETS & BUSHINGS

ITEM NO	DESCRIPTION	QTY	ZONE
6	420KV, 1250AMP, H V LINE BUSHINGS	3	202-B
6X	145KV, 1250AMP, H V NEUTRAL BUSHING	1	203-C
122	CONNECTION BOX FOR C T TERMINAL (H V)	3	203-C
122a	CONNECTION BOX FOR C T TERMINAL (H V N) ON COVER	4	304-C
122b	CONNECTION BOX FOR C T TERMINAL (H V N)	1	303-D
148	NEUTRAL TURRET	1	203-C
150	H V TURRETS	3	202-C
157	NEUTRAL GROUNDING STRIPS	1 SET	203-D
157a	22KV POST INSULATOR	3	203-D
180	TERMINAL MARKING PLATE	4	204-C

REACTOR

ITEM NO	DESCRIPTION	QTY	ZONE
2	RATING AND DIAGRAM PLATE	1	203-D
2a	DOS & DONT'S INSTRUCTION PLATE	1	203-E
2b	VALVE SCHEDULE PLATE	1	204-D
2c	OIL FILLING INSTRUCTION PLATE	1	204-E
3	LIFTING BOLLARD (60000 KG. EACH)	4	407-D
3a	LIFTING LUGS FOR TANK COVER	6	304-C
3b	LASHING LUG	8	205-D
3c	INSTRUCTION PLATE FOR LIFTING	4	204-D
4	EARTHING TERMINAL DIAGONALLY OPPOSITE (SIZE 20 TK X 50X 120 LG.) (STAINLESS STEEL)	2	206-E
8	NAME PLATES (ENGLISH & HINDI)	1+1	204-D
10	INSPECTION COVERS (6 NOS. ON TANK COVER, 1 NO. ON TANK)	6+1	203-D 305-C
13	DRAIN PLUGS ON TANK 1" BSP	2	202-E
14	100 NB DRAIN GATE VALVE	1	204-E
18	POCKET FOR OTI	1	305-D
18a	POCKET FOR WTI	1	306-D
18b	ORDINARY THERMOMETER WITH POCKET (1 NO ON TANK COVER)	1	306-C
18c	RTD WITH POCKET FOR OTI	1	305-C
18d	RTD WITH POCKET FOR WTI	1	305-C
18e	SPARE POCKET FOR OTI	1	306-C
18f	SPARE POCKET FOR WTI	1	306-C
19	JACKING PADS 70000 KG EACH	4	205-E
21	OIL TEMPERATURE INDICATOR.	1	205-D
22	WINDING TEMPERATURE INDICATOR	1	205-D
25	50 NB GATE VALVE ON TANK AND COVER	2+1	303-C 402-D 406-D
27	PRESSURE RELIEF DEVICE (PLUG AND SOCKET TYPE)	2	303-C 306-D
28	15 NB GLOBE VALVE FOR OIL SAMPLING (1SET= 2 IN SERIES)	2 SET	204-E
29	PLATFORM FOR MARSHALLING BOX	1	402-E
34	MARSHALLING BOX (TANK MOUNTED)	1	305-D
41	OIL COLLECTING ARRGT. FOR PRV WITH PIPE WORK	2	306-C
79	LADDER WITH LOCKING DEVICE	1	304-D
86	AIR RELEASE PLUG 1/2" BSP.	1	305-C
109	PULLING HOLE DIA 64	8	203-E
212	COVER EARTHING OF CORE AND CORE CLAMPS.	1	306-C
215	EARTHING STRIP 30SOMM FOR TURRET	16	304-C
216	SUDDEN PRESSURE RELAY	1	204-D
216a	40 NB GATE VALVE FOR SUDDEN PRESSURE RELAY	1	204-D

TABLE OF FITTINGS

ITEM NO	DESCRIPTION	QTY	ZONE
6	420KV, 1250AMP, H V LINE BUSHINGS	3	202-B
6X	145KV, 1250AMP, H V NEUTRAL BUSHING	1	203-C
122	CONNECTION BOX FOR C T TERMINAL (H V)	3	203-C
122a	CONNECTION BOX FOR C T TERMINAL (H V N) ON COVER	4	304-C
122b	CONNECTION BOX FOR C T TERMINAL (H V N)	1	303-D
148	NEUTRAL TURRET	1	203-C
150	H V TURRETS	3	202-C
157	NEUTRAL GROUNDING STRIPS	1 SET	203-D
157a	22KV POST INSULATOR	3	203-D
180	TERMINAL MARKING PLATE	4	204-C

TABLE OF FITTINGS

ITEM NO	DESCRIPTION	QTY	ZONE
2	RATING AND DIAGRAM PLATE	1	203-D
2a	DOS & DONT'S INSTRUCTION PLATE	1	203-E
2b	VALVE SCHEDULE PLATE	1	204-D
2c	OIL FILLING INSTRUCTION PLATE	1	204-E
3	LIFTING BOLLARD (60000 KG. EACH)	4	407-D
3a	LIFTING LUGS FOR TANK COVER	6	304-C
3b	LASHING LUG	8	205-D
3c	INSTRUCTION PLATE FOR LIFTING	4	204-D
4	EARTHING TERMINAL DIAGONALLY OPPOSITE (SIZE 20 TK X 50X 120 LG.) (STAINLESS STEEL)	2	206-E
8	NAME PLATES (ENGLISH & HINDI)	1+1	204-D
10	INSPECTION COVERS (6 NOS. ON TANK COVER, 1 NO. ON TANK)	6+1	203-D 305-C
13	DRAIN PLUGS ON TANK 1" BSP	2	202-E
14	100 NB DRAIN GATE VALVE	1	204-E
18	POCKET FOR OTI	1	305-D
18a	POCKET FOR WTI	1	306-D
18b	ORDINARY THERMOMETER WITH POCKET (1 NO ON TANK COVER)	1	306-C
18c	RTD WITH POCKET FOR OTI	1	305-C
18d	RTD WITH POCKET FOR WTI	1	305-C
18e	SPARE POCKET FOR OTI	1	306-C
18f	SPARE POCKET FOR WTI	1	306-C
19	JACKING PADS 70000 KG EACH	4	205-E
21	OIL TEMPERATURE INDICATOR.	1	205-D
22	WINDING TEMPERATURE INDICATOR	1	205-D
25	50 NB GATE VALVE ON TANK AND COVER	2+1	303-C 402-D 406-D
27	PRESSURE RELIEF DEVICE (PLUG AND SOCKET TYPE)	2	303-C 306-D
28	15 NB GLOBE VALVE FOR OIL SAMPLING (1SET= 2 IN SERIES)	2 SET	204-E
29	PLATFORM FOR MARSHALLING BOX	1	402-E
34	MARSHALLING BOX (TANK MOUNTED)	1	305-D
41	OIL COLLECTING ARRGT. FOR PRV WITH PIPE WORK	2	306-C
79	LADDER WITH LOCKING DEVICE	1	304-D
86	AIR RELEASE PLUG 1/2" BSP.	1	305-C
109	PULLING HOLE DIA 64	8	203-E
212	COVER EARTHING OF CORE AND CORE CLAMPS.	1	306-C
215	EARTHING STRIP 30SOMM FOR TURRET	16	304-C
216	SUDDEN PRESSURE RELAY	1	204-D
216a	40 NB GATE VALVE FOR SUDDEN PRESSURE RELAY	1	204-D

भारत भारती NTPC	एन टी पी सी लिमिटेड NTPC LIMITED
----------------------------------	--

PROJECT TANCHER थर्मल पावर प्रोजेक्ट STAGE-III (2 X 660 MW) EPC PACKAGE.

W.O.- 62213-A-517-01	भारत भारती इंजीनियरिंग लिमिटेड, गंगोत्री	DRN.	MRP	DATE
STATUS OF DRAWING "PR"	BHARAT HEAVY ELECTRICALS LTD, BHOPAL	CHD.	MRP	10.03.2023
DISTRIBUTION OF PRINTS	DEPT CODE WEIGHT(Kg) SCALE	APPD.	KD/SK	20.03.2023
TRE-1, TRM-3	TRE 406 ----- COMP.SCALE-1:1	APPD.	KD/SK	31.03.2023

LIST OF FITTING & ACCESSORIES

DRG. NO 3 469 00 02296 REV. 01

501

502

503

504


505

506







507

508

Handwritten signature



SL. NO.	SIZE OF POWER CABLE	TYPE OF CABLE
1.	3.5CX300SQ.MM	AL/XLPE
2.	1CX150SQ.MM	AL/XLPE
3.	3.5CX70SQ.MM	AL/PVC
4.	3.5CX35SQ.MM	AL/PVC
5.	4CX16SQ.MM	AL/PVC
6.	4CX6SQ.MM	AL/PVC
7.	2CX6SQ.MM	AL/PVC

SYMBOL	NOMENCLATURE	DESCRIPTION
	ACB	AIR CIRCUIT BREAKER (DRAWOUT TYPE)
	MCCB	MOULDED CASE CIRCUIT BREAKER
	SFU	POLE SWITCH FUSE UNIT (SFU)
	DP AB SWITCH	DOUBLE POLE AIR BREAK SWITCH
	INTERLOCKING	INTERLOCKING THROUGH CONTACTORS
	MCB	MINIATURE CIRCUIT BREAKER

1. BOARD SHALL BE EXTENDABLE ON BOTH SIDES, BY ADDITION OF VERTICAL SECTION AFTER REMOVING END COVERS.
2. BOARD SHALL BE OF UNIFORM HEIGHT NOT EXCEEDING 2450MM.
3. BOARD SHALL BE DUST AND VERMIN PROOF WITH IP-52.
4. NO TWO AC SOURCES SHALL BE PARALLEL AT ANY STAGE. INTERLOCK (ELECTRICAL) TO BE PROVIDED BETWEEN INCOMERS (INTERLOCK SCHEME FOR DETAIL SHALL BE FURNISHED ALONG WITH VENDOR DRAWINGS).
5. ORIENTATION OF FEEDERS SHOULD BE VERIFIED TO AVOID CROSS CABLING.
6. PHASOR SEQUENCE OF INCOMER SHOULD BE VERIFIED TO AVOID CHANGE OVER PHASE EQUIPMENT.
7. LOADING OF EACH FEEDER SHOULD BE SUCH THAT AMPACITY OF CABLE IS WITHIN THE LIMITS AND ACCORDINGLY VOLTAGE DROPS SHOULD BE CHECKED .
8. METERING AND PROTECTION REQUIREMENT SHALL BE AS PER TECHNICAL SPECIFICATION .
9. FOR CABLE INTERCONNECTION REFER CABLE SCHEDULE DRAWING.
10. CABLE DETAIL INDICATED ARE TENTATIVE ONLY (INFORMATION PURPOSE)
11. FOR AUTO-CHANGEOVER SCHEME REFER VENDOR SCHEME DETAIL DRAWING(S)
12. FOR OUTGOING FEEDER DETAILS REFER OGA OF RESPECTIVE BOARDS .
13. TRANSducer FOR MEASUREMENT OF DC CURRENT AND DC VOLTAGE SHALL BE LOCATED IN RESPECTIVE CHARGER & SAME SHALL BE INTEGRATED TO SAS.
14. IN NORMAL CONDITION WHEN TWO INCOMERS OF DC BOARD IS ON THEN BUS COUPLER AIR BREAK SWITCH SHALL BE OFF CONDITION .
15. IN THE CASE OF COMPLETE OUTAGE OF ANY ONE SECTION BATTERY AND CHARGER OUTPUT, BUS COUPLER AIR BREAK SWITCH SHALL BE IN ON CONDITION MANUALLY.
16. THE OFFERED RELAYS SHALL BE NUMERICAL AS PER TECHNICAL SPECIFICATION.
17. OIL FILTRATION RECEPTACLES ARE LOOP IN LOOP OUT TYPE & WILL BE LOCATED IN OUTDOOR YARD.
18. AVCS AND GIS HALL VENTILATION DISTRIBUTION BOARD SHALL BE IN THE RESPECTIVE VENDOR'S SCOPE.
19. ILLUMINATION FEEDERS ARE AS PER FINAL ILLUMINATION DESIGN.
20. MINIMUM INDICATIVE REQUIREMENT OF ANALOG SIGNALS, POTENTIAL FREE CONTACTS AND COMMAND SIGNALS WHICH SHOULD BE AVAILABLE AT RESPECTIVE EQUIPMENT FOR REMOTE INDICATION & CONTROL FROM AUXILIARY ECU LOCATED IN SWD CONTROL ROOM - SHALL BE PROVIDED AS PER TS.

<u>DESIGN PARTICULARS</u>	
1. AMBIENT TEMPERATURE	: 50° C
2. ONE MIN. POWER FREQ. WITHSTAND VOLTAGE	: 2.5 kV(rms)
3. POWER SUPPLY DETAIL	
a. AC SYSTEM	: 3 PHASE , 4 WIRE, SOLIDLY EARTHED, 415V±10%, 50HZ
b. DC SYSTEM	: 2WIRE, UNEARTHED, 220V±10%
4. WIRING	: 650/1100V GRADE PVC INSULATED WIRE OF 1.5 SQ MM CU. FOR CONTROL AND 2.5 SQ.MM.FOR CT CIRCUIT
5. POWER SUPPLY DETAIL	
a. TRIP AND CLOSING COILS	220V DC UNEARTHED
b. SPRING CHARGING	220V DC UNEARTHED
6. ALL METALLIC CASE LIKE RELAYS, INSTRUMENT & OTHER EQUIPMENT SHALL BE CONNECTED TO EARTH WITH 2.5 SQ.MM. CU WIRE, GREEN COLOUR	

S.NO	MIN. CLERANCE (EXCEPT AT TERMINATION)	
1	PHASE TO PHASE	25 MM
2	PHASE TO NEUTRAL	25 MM
3	PHASE TO EARTH	25 MM
4	NEURAL TO EARTH	25 MM

version REV.	Issue DATE	Modified ALTO	Issue CHD	applied APPO	version REV.	Issue DATE	Modified ALTO	Issue CHD	applied APPO
6					5				

ग्राहक ड्राइंग NO. CUSTOMER DRAWING NO.		PE-DG-497-565-E001A	
<div>एन टी पी सी NTPC</div>		अर्थक/CUSTOMER एन टी पी सी लिमिटेड N T P C LIMITED	
कार्य संख्या: JOB NO. 419 विभाग DEPT. CONTRACT प्रमुख CHIEF प्रमुख CHIEF		TALCHER THERMAL POWER PROJECT STAGE-III (2X660MW)	
भारत हेवी इलेक्ट्रिकल्स लिमिटेड BHARAT HEAVY ELECTRICALS LTD TRANSMISSION BUSINESS GROUP नोएडा (उ.प्र.)/NOIDA (U.P.)		ड्राफ्ट DRAFT M	जमा SUBMITTED प्रमाणित CERTIFIED दिनांक DATE 10.02.2023 10.02.2023 10.02.2023
0144410 0 10 20 30 40 50 60 70 80 90 100 110 120 130 140 150 160 170 180 190 200 210 220 230 240 250 260 270 280 290 300 310 320 330 340 350 360 370 380 390 400 410 420 430 440 450 460 470 480 490 500 510 520 530 540 550 560 570 580 590 600 610 620 630 640 650 660 670 680 690 700 710 720 730 740 750 760 770 780 790 800 810 820 830 840 850 860 870 880 890 900 910 920 930 940 950 960 970 980 990 1000 1010 1020 1030 1040 1050 1060 1070 1080 1090 1100 1110 1120 1130 1140 1150 1160 1170 1180 1190 1200 1210 1220 1230 1240 1250 1260 1270 1280 1290 1300 1310 1320 1330 1340 1350 1360 1370 1380 1390 1400 1410 1420 1430 1440 1450 1460 1470 1480 1490 1500 1510 1520 1530 1540 1550 1560 1570 1580 1590 1600 1610 1620 1630 1640 1650 1660 1670 1680 1690 1700 1710 1720 1730 1740 1750 1760 1770 1780 1790 1800 1810 1820 1830 1840 1850 1860 1870 1880 1890 1900 1910 1920 1930 1940 1950 1960 1970 1980 1990 2000 2010 2020 2030 2040 2050 2060 2070 2080 2090 2100 2110 2120 2130 2140 2150 2160 2170 2180 2190 2200 2210 2220 2230 2240 2250 2260 2270 2280 2290 2300 2310 2320 2330 2340 2350 2360 2370 2380 2390 2400 2410 2420 2430 2440 2450 2460 2470 2480 2490 2500 2510 2520 2530 2540 2550 2560 2570 2580 2590 2600 2610 2620 2630 2640 2650 2660 2670 2680 2690 2700 2710 2720 2730 2740 2750 2760 2770 2780 2790 2800 2810 2820 2830 2840 2850 2860 2870 2880 2890 2900 2910 2920 2930 2940 2950 2960 2970 2980 2990 3000 3010 3020 3030 3040 3050 3060 3070 3080 3090 3100 3110 3120 3130 3140 3150 3160 3170 3180 3190 3200 3210 3220 3230 3240 3250 3260 3270 3280 3290 3300 3310 3320 3330 3340 3350 3360 3370 3380 3390 3400 3410 3420 3430 3440 3450 3460 3470 3480 3490 3500 3510 3520 3530 3540 3550 3560 3570 3580 3590 3600 3610 3620 3630 3640 3650 3660 3670 3680 3690 3700 3710 3720 3730 3740 3750 3760 3770 3780 3790 3800 3810 3820 3830 3840 3850 3860 3870 3880 3890 3900 3910 3920 3930 3940 3950 3960 3970 3980 3990 4000 4010 4020 4030 4040 4050 4060 4070 4080 4090 4100 4110 4120 4130 4140 4150 4160 4170 4180 4190 4200 4210 4220 4230 4240 4250 4260 4270 4280 4290 4300 4310 4320 4330 4340 4350 4360 4370 4380 4390 4400 4410 4420 4430 4440 4450 4460 4470 4480 4490 4500 4510 4520 4530 4540 4550 4560 4570 4580 4590 4600 4610 4620 4630 4640 4650 4660 4670 4680 4690 4700 4710 4720 4730 4740 4750 4760 4770 4780 4790 4800 4810 4820 4830 4840 4850 4860 4870 4880 4890 4900 4910 4920 4930 4940 4950 4960 4970 4980 4990 5000 5010 5020 5030 5040 5050 5060 5070 5080 5090 5100 5110 5120 5130 5140 5150 5160 5170 5180 5190 5200 5210 5220 5230 5240 5250 5260 5270 5280 5290 5300 5310 5320 5330 5340 5350 5360 5370 5380 5390 5400 5410 5420 5430 5440 5450 5460 5470 5480 5490 5500 5510 5520 5530 5540 5550 5560 5570 5580 5590 5600 5610 5620 5630 5640 5650 5660 5670 5680 5690 5700 5710 5720 5730 5740 5750 5760 5770 5780 5790 5800 5810 5820 5830 5840 5850 5860 5870 5880 5890 5900 5910 5920 5930 5940 5950 5960 5970 5980 5990 6000 6010 6020 6030 6040 6050 6060 6070 6080 6090 6100 6110 6120 6130 6140 6150 6160 6170 6180 6190 6200 6210 6220 6230 6240 6250 6260 6270 6280 6290 6300 6310 6320 6330 6340 6350 6360 6370 6380 6390 6400 6410 6420 6430 6440 6450 6460 6470 6480 6490 6500 6510 6520 6530 6540 6550 6560 6570 6580 6590 6600 6610 6620 6630 6640 6650 6660 6670 6680 6690 6700 6710 6720 6730 6740 6750 6760 6770 6780 6790 6800 6810 6820 6830 6840 6850 6860 6870 6880 6890 6900 6910 6920 6930 6940 6950 6960 6970 6980 6990 7000 7010 7020 7030 7040 7050 7060 7070 7080 7090 7100 7110 7120 7130 7140 7150 7160 7170 7180 7190 7200 7210 7220 7230 7240 7250 7260 7270 7280 7290 7300 7310 7320 7330 7340 7350 7360 7370 7380 7390 7400 7410 7420 7430 7440 7450 7460 7470 7480 7490 7500 7510 7520 7530 7540 7550 7560 7570 7580 7590 7600 7610 7620 7630 7640 7650 7660 7670 7680 7690 7700 7710 7720 7730 7740 7750 7760 7770 7780 7790 7800 7810 7820 7830 7840 7850 7860 7870 7880 7890 7900 7910 7920 7930 7940 7950 7960 7970 7980 7990 8000 8010 8020 8030 8040 8050 8060 8070 8080 8090 8100 8110 8120 8130 8140 8150 8160 8170 8180 8190 8200 8210 8220 8230 8240 8250 8260 8270 8280 8290 8300 8310 8320 8330 8340 8350 8360 8370 8380 8390 8400 8410 8420 8430 8440 8450 8460 8470 8480 8490 8500 8510 8520 8530 8540 8550 8560 8570 8580 8590 8600 8610 8620 8630 8640 8650 8660 8670 8680 8690 8700 8710 8720 8730 8740 8750 8760 8770 8780 8790 8800 8810 8820 8830 8840 8850 8860 8870 8880 8890 8900 8910 8920 8930 8940 8950 8960 8970 8980 8990 9000 9010 9020 9030 9040 9050 9060 9070 9080 9090 9100 9110 9120 9130 9140 9150 9160 9170 9180 9190 9200 9210 9220 9230 9240 9250 9260 9270 9280 9290 9300 9310 9320 9330 9340 9350 9360 9370 9380 9390 9400 9410 9420 9430 9440 9450 9460 9470 9480 9490 9500 9510 9520 9530 9540 9550 9560 9570 9580 9590 9600 9610 9620 9630 9640 9650 9660 9670 9680 9690 9700 9710 9720 9730 9740 9750 9760 9770 9780 9790 9800 9810 9820 9830 9840 9850 9860 9870 9880 9890 9900 9910 9920 9930 9940 9950 9960 9970 9980 9990 10000 10010 10020 10030 10040 10050 10060 10070 10080 10090 10100 10110 10120 10130 10140 10150 10160 10170 10180 10190 10200 10210 10220 10230 10240 10250 10260 10270 10280 10290 10300 10310 10320 10330 10340 10350 10360 10370 10380 10390 10400 10410 10420 10430 10440 10450 10460 10470 10480 10490 10500 10510 10520 10530 10540 10550 10560 10570 10580 10590 10600 10610 10620 10630 10640 10650 10660 10670 10680 10690 10700 10710 10720 10730 10740 10750 10760 10770 10780 10790 10800 10810 10820 10830 10840 10850 10860 10870 10880 10890 10900 10910 10920 10930 10940 10950 10960 10970 10980 10990 11000 11010 11020 11030 11040 11050 11060 11070 11080 11090 11100 11110 11120 11130 11140 11150 11160 11170 11180 11190 11200 11210 11220 11230 11240 11250 11260 11270 11280 11290 11300 11310 11320 11330 11340 11350 11360 11370 11380 11390 11400 11410 11420 11430 11440 11450 11460 11470 11480 11490 11500 11510 11520 11530 11540 11550 11560 11570 11580 11590 11600 11610 11620 11630 11640 11650 11660 11670 11680 11690 11700 11710 11720 11730 11740 11750 11760 11770 11780 11790 11800 11810 11820 11830 11840 11850 11860 11870 11880 11890 11900 11910 11920 11930 11940 11950 11960 11970 11980 11990 12000 12010 12020 12030 12040 12050 12060 12070 12080 12090 12100 12110 12120 12130 12140 12150 12160 12170 12180 12190 12200 12210 12220 12230 12240 12250 12260 12270 12280 12290 12300 12310 12320 12330 12340 12350 12360 12370 12380 12390 12400 12410 12420 12430 12440 12450 12460 12470 12480 12490 12500 12510 12520 12530 12540 12550 12560 12570 12580 12590 12600 12610 12620 12630 12640 12650 12660 12670 12680 12690 12700 12710 12720 12730 12740 12750 12760 12770 12780 12790 12800 12810 12820 12830 12840 12850 12860 12870 12880 12890 12900 12910 12920 12930 12940 12950 12960 12970 12980 12990 13000 13010 13020 13030 13040 13050 13060 13070 13080 13090 13100 13110 13120 13130 13140 13150 13160 13170 13180 13190 13200 13210 13220 13230 13240 13250 13260 13270 13280 13290 13300 13310 13320 13330 13340 13350 13360 13370 13380 13390 13400 13410 13420 13430 13440 13450 13460 13470 13480 13490 13500 13510 13520 13530 13540 13550 13560 13570 13580 13590 13600 13610 13620 13630 13640 13650 13660 13670 13680 13690 13700 13710 13720 13730 13740 13750 13760 13770 13780 13790 13800 13810 13820 13830 13840 13850 13860 13870 13880 13890 13900 13910 13920 13930 13940 13950 13960 13970 13980 13990 14000 14010 14020 14030 14040 14050 14060 14070 14080 14090 14100 14110 14120 14130 14140 14150 14160 14170 14180 14190 14200 14210 14220 14230 14240 14250 14260 14270 14280 14290 14300 14310 14320 14330 14340 14350 14360 14370 14380 14390 14400 14410 14420 14430 14440 14450 14460 14470 14480 14490 14500 14510 14520 14530 14540 14550 14560 14570 14580 14590 14600 14610 14620 14630 14640 14650 14660 14670 14680 14690 14700 14710 14720 14730 14740 14750 14760 14770 14780 14790 14800 14810 14820 14830 14840 14850 14860 14870 14880 14890 14900 14910 14920 14930 14940 14950 14960 14970 14980 14990 15000 15010 15020 15030 15040 15050 15060 15070 15080 15090 15100 15110 15120 15130 15140 15150 15160 15170 15180 15190 15200 15210 15220 15230 15240 15250 15260 15270 15280 15290 15300 15310 15320 15330 15340 15350 15360 15370 15380 15390 15400 15410 15420 15430 15440 15450 15460 15470 15480 15490 15500 15510 15520 15530 15540 15550 15560 15570 15580 15590 15600 15610 15620 15630 15640 15650 15660 15670 15680 15690 15700 15710 15720 15730 15740 15750 15760 15770 15780 15790 15800 15810 15820 15830 15840 15850 15860 15870 15880 15890 15900 15910 15920 15930 15940 15950 15960 15970 15980 15990 16000 16010 16020 16030 16040 16050 16060 16070 16080 16090 16100 16110 16120 16130 16140 16150 16160 16170 16180 16190 16200 16210 16220 16230 16240 16250 16260 16270 16280 16290 16300 16310 16320 16330 16340 16350 16360 16370 16380 16390 16400 16410 16420 16430 16440 16450 16460 16470 16480 16490 16500 16510 16520 16530 16540 16550 16560 16570 16580 16590 16600 16610 16620 16630 16640 16650 16660 16670 16680 16690 16700 16710 16720 16730 16740 16750 16760 16770 16780 16790 16800 16810 16820 16830 16840 16850 16860 16870 16880 16890 16900 16910 16920 16930 16940 16950 16960 16970 16980 16990 17000 17010 17020 17030 17040 17050 17060 17070 17080 17090 17100 17110 17120 17130 17140 17150 17160 17170 17180 17190 17200 17210 17220 17230 17240 17250 17260 17270 17280 17290 17300 17310 17320 17330 17340 17350 17360 17370 17380 17390 17400 17410 17420 17430 17440 17450 17460 17470 17480 17490 17500 17510 17520 17530 17540 17550 17560 17570 17580 17590 17600 17610 17620 17630 17640 17650 17660 17670 17680 17690 17700 17710 17720 17730 17740 17750 17760 17770 17780 17790 17800 17810 17820 17830 17840 17850 17860 17870 17880 17890 17900 17910 17920 17930 17940 17950 17960 17970 17980 17990 18000 18010 18020 18030 18040 18050 18060 18070 18080 18090 18100 18110 18120 18130 18140 18150 18160 18170 18180 18190 18200 18210 18220 18230 18240 18250 18260 18270 18280 18290 18300 18310 18320 18330 18340 18350 18360 18370 18380 18390 18400 18410 18420 18430 18440 18450 18460 18470 18480 18490 18500 18510 18520 18530 18540 18550 18560 18570 18580 18590 18600 18610 18620 18630 18640 18650 18660 18670 18680 18690 18700 18710 18720 18730 18740 18750 18760 18770 18780 18790 18800 18810 18820 18830 18840 18850 18860 18870 18880 18890 18900 18910 18920 18930 18940 18950 18960 18970 18980 18990 19000 19010 19020 19030 19040 19050 19060 19070 19080 19090 19100 19110 19120 19130 19140 19150 19160 19170 19180 19190 19200 19210 19220 19230 19240 19250 19260 19270 19280 19290 19300 19310 19320 19330 19340 19350 19360 19370 19380 19390 19400 19410 19420 19430 19440 19450 19460 19470 19480 19490 19500 19510 19520 19530 19540 19550 19560 19570 19580 19590 19600 19610 19620 19630 19640 19650 19660 19670 19680 19690 19700 19710 19720 19730 19740 19750 19760 19770 19780 19790 19800 19810 19820 19830 19840 19850 19860 19870 19880 19890 19900 19910 19920 19930 19940 19950 19960 19970 19980 19990 20000 20010 20020 20030 20040 20050 20060 20070 20080 20090 20100 20110 20120 20130 20140 20150 20160 20170 20180 20190 20200 20210 20220 20230 20240 20250 20260 20270 20280 20290 20300 20310 20320 20330 20340 20350 20360 20370 20380 20390 20400 20410 20420 20430 20440 20450 20460 20470 20480 20490 20500 20510 20520 20530 20540 20550 20560 20570 20580 20590 20600 20610 20620 20630 20640 20650 20660 20670 20680 20690 20700 20710 20720 20730 20740 20750 20760 20770 20780 20790 20800 20810 20820 20830 20840 20850 20860 20870 20880 20890 20900 20910 20920 20930 20940 20950 20960 20970 20980 20990 21000 21010 21020 21030 21040 21050 21060 21070 21080 21090 21100 21110 21120 21130 21140 21150 21160 21170 21180 21190 21200 21210 21220 21230 21240 21250 21260 21270 21280 21290 21300 21310 21320 21330 21340 21350 21360 21370 21380 21390 21400 21410 21420 21430 21440 21450 21460 21470 21480 21490 21500 21510 21520 21530 21540 21550 21560 21570 21580 21590 21600 21610 21620 21630 21640 21650 21660 21670 21680 21690 21700 21710 21720 21730 21740 21750 21760 21770 21780 21790 21800 21810 21820 21830 21840 21850 21860 21870 21880 218			

Annexure CTM

Cable Trench Material - work for BOLTED and Welded TYPE (As applicable) GI Rack / Tray for cable trenches in Switchyard, GIS Hall & Control Room Building as per doc. no. TB-419-316-019 Rev00.

Following works deemed included in the scope and not being payable separately - Welding of racks, installation of cantilever arms, back plate, angle fitting, clamp for single / double channel, cutting of vertical supports C1 and C2 as per requirement, base plate for single / double channel, beam clamp, tray fixing clamp, screw, nut bolt, anchor bolt, floor / ceiling / beam / columns support, Side runner for cable tray, side coupler, pvc end cap, earthing clamp, tray clamp etc. complete in all respect are deemed included in the scope. Cable rack assembly will be of 1/2/3/4 tier. (Bolted and Welded type Cable Rack/Tray material/Hardware, Nut Bolt, fasteners shall be free issued by BHEL.) Cutting, drilling, punching, minor civil works also included in the scope. Minor welding and application of protective / zinc rich paint on welded surface is also included in the scope.



1.2 Bill of Quantities

SN	Item Description	Qty (Nos.)	Remarks
1.	4 Tier Double Side Galvanized Cable Rack Assembly With 50X50X6 thick MS Angle as per Section 1-1 – Welded Type.	210	As per Annexure 1 of section 1.
2.	4 Tier Single Side Galvanized Cable Rack Assembly With 50X50X6 thick MS Angle as per Section 2-2 – Welded Type.	189	As per Annexure 1 of section 1.
3.	2 Tier Galvanized Cable Rack Assembly With 50X50X6 thick MS Angle as per Section 4-4 – Welded Type.	680	As per Annexure 1 of section 1.
4.	1 Tier Galvanized Cable Rack Assembly With 50X50X6 thick MS Angle as per Section 5-5 – Welded Type.	161	As per Annexure 1 of section 1.
5.	Vertical support of Single Channel (C1) of standard length 6.0 m – Bolted Type	5	As per Drawing: PE-DG-497-507-E006 Rev00 -Sheet 02 Of 37
6.	Vertical support of Double Channel (C2) of standard length 6.0 m - Bolted Type	8	As per Drawing: PE-DG-497-507-E006 Rev00 -Sheet 02 Of 37
7.	Horizontal support of cantilever arm CA1 each with 2 nos. 12 mm dia (M12) bolts with spring nuts and washers as well as 2 nos. 6 mm dia (M6) pan head screws with long spring nuts and washers for fixing on vertical support single/double (C1/C2) suitable for ladder type cable tray 600 mm wide – Bolted Type.	147	As per Drawing: PE-DG-497-507-E006 Rev00 -Sheet 03 Of 37 and PE-DG-497-507-E006 Rev00 -Sheet 11 Of 37
8.	Ladder type cable tray 600 mm wide, 100 mm high, 2 mm thick (min.) galvanised iron slotted rung 2.5 m long each with 2 Nos. coupler plate, 3 mm thick (min.) along with 8 mm dia (M8) bolts with nuts and washers for coupling two trays – Bolted Type	375	As per Drawing: PE-DG-497-507-E041 Rev01- Sheet 02 Of 14
9.	Ladder type cable tray 150 mm wide, 100 mm high, 2 mm thick (min.) galvanised iron slotted rung 2.5 m long each with 2 Nos. coupler plate, 3 mm thick (min.) along with 8 mm dia (M8) bolts with nuts and washers for coupling two trays – Bolted Type	40	As per Drawing: PE-DG-497-507-E041 Rev01 -Sheet 02 Of 14
10.	Horizontal TEE For Ladder type cable tray 2.5 m long, 600 mm wide, 100 mm high, 2 mm thick, having slotted rung - Bolted Type	20	As per Drawing: PE-DG-497-507-E041 Rev01 -Sheet 06 Of 14
11.	Horizontal TEE For Ladder type cable tray 2.5 m long, 150 mm wide, 100 mm high, 2 mm thick, having slotted rung - Bolted Type	10	As per Drawing: PE-DG-497-507-E041 Rev01 -Sheet 06 Of 14
12.	Horizontal Elbow(90 deg Bend) for Ladder type cable tray 2.5 m long, 600 mm wide, 100 mm high, 2 mm thick, having slotted rung – Bolted Type	15	As per Drawing: PE-DG-497-507-E041 Rev01 -Sheet 08 Of 14



SN	Item Description	Qty (Nos.)	Remarks
13.	Vertical Elbow(90 deg Bend) for Ladder type cable tray 2.5 m long, 600 mm wide, 100 mm high, 2 mm thick, having slotted rung - Bolted Type	10	As per Drawing: PE-DG-497-507-E041 Rev01 -Sheet 08 Of 14
14.	Left Hand Reducer for Ladder type cable tray 600 mm wide To 150 mm Wide, 100 mm high, 2 mm thick, having slotted rung - Bolted Type	15	As per Drawing: PE-DG-497-507-E041 Rev01 -Sheet 06 Of 14
15.	Right Hand Reducer for Ladder type cable tray 600 mm wide To 150 mm Wide, 100 mm high, 2 mm thick, having slotted rung - Bolted Type	15	As per Drawing: PE-DG-497-507-E041 Rev01 -Sheet 06 Of 14
16.	Base Plate For Single Channel (BP1) with 1 No. 10 mm dia (M10) anchor bolts – Bolted Type	9	As per Drawing: PE-DG-497-507-E006 Rev00 -Sheet 06 Of 37 and PE-DG-497-507-E006 Rev00 -Sheet 11 Of 37
17.	Base Plate For Double Channel (BP2) with 2 No. 10 mm dia (M10) anchor bolts – Bolted Type	17	As per Drawing: PE-DG-497-507-E006 Rev00 -Sheet 07 Of 37 and PE-DG-497-507-E006 Rev00 -Sheet 11 Of 37
18.	Tray Fixing Clamp (TC1) – Bolted Type	381	As per Drawing: PE-DG-497-507-E006 Rev00 -Sheet 09 Of 37
19.	PVC End Cap	167	As per Drawing: 0350-215-PVE-B-001 Rev00- Sheet 20 Of 21
20.	Earth Flat Fixing Clamp (Z) – Bolted Type	26	As per Drawing: 0350-215-PVE-B-001 Rev00- Sheet 18 Of 21
21.	90 deg Angle Fitting LA1	26	As per Drawing: PE-DG-497-507-E006 Rev00 -Sheet 10 Of 37
22.	90 deg Angle Fitting HL1	44	As per Drawing: PE-DG-497-507-E006 Rev00 -Sheet 04 Of 37

Note:






1. The quantity for individual items may vary up to any extent, however total quantity may vary $\pm 40\%$ during contract execution stage.
2. All items mentioned above shall be as per NTPC specification drawings attached in Section-2.
3. Minor fabrication detail changes which do not affect the material/dimensional aspect of the equipment, shall be subject to BHEL's/Owner's approval without any commercial implication.
4. 2% Extra Hardware shall be supplied along with all the applicable items in the BOQ.



TYP. CABLE SUPPORT EARTH CONDUCTOR
'E' RUNS ON TOP TIERS ONLY

[illegible]





ANNEXURE-I







W.D. NO. 419		PROJECT TALCHER THERMAL POWER PROJECT STAGE-III (2X660MW)	
STATUS CONTRACT		OWNER NTPC Limited (A GOVERNMENT OF INDIA ENTERPRISE)	
DISTRIBUTION		BHARAT HEAVY ELECTRICALS LTD TRANSMISSION BUSINESS GROUP NOIDA	
TO		DEPT CODE	NAME
No. OF		DRN	PC
REV. 02	DATE 23.11.23	CHD	RD
	ALTD PC	APPD	VK
	CHD RD		
	APPD VK		
DRAWINGS REVISED IN LINE WITH NTPC COMMENTS DT 25.08.23		TITLE INDOOR CABLE TRENCH LAYOUT FOR SWITCHYARD CONTROL ROOM BUILDING (ELECTRICAL DRAWING)	
		DEPT. SCALE NTS	DRAWING NO. 4540-001-230-PVE-F-001
		SIGN DATE	SHEET 02 OF 02 REV. 02

"We confirm that this document meets all the contract requirements including safety and statutory requirements and facilitate ease of operation and maintenance. In case any deviation is found, the Contractor shall carry out all required changes/modifications without any cost implications to NTPC. In addition, Penalty on account of noncompliance of contract specification as deemed fit by the Employer shall be recovered.



TYPICAL DETAILS OF CABLE TRAYS AND ACCESSORIES

REV	ALTD	CHD	APPD	DATE	NTPC DOCUMENT NO: 4540-001-215-PVE-B-045													
01	VKS	AnA	SL	04.01.2023														
DRAWING IS REVISE AS PER CUSTOMER COMMENTS DATED 31.12.2022. HOLE LOCATION ON SIDE RUNNER UPDATED. CHANGES ARE MARKED AS 					CUSTOMER		<div> एन टी पी सी लिमिटेड N T P C LIMITED</div>											
					PROJECT		2X660MW TALCHER THERMAL POWER PROJECT LTD. STAGE-III											
					JOB NO. 497		<div> भारत हेवी इलेक्ट्रिकल्स लिमिटेड POWER SECTOR PROJECT ENGINEERING MANAGEMENT NOIDA(U.P) INDIA</div>						DPT CODE-E		DRN	NAME	SIGN	DATE
					DSN	SKS									-sd-	13.12.22		
					<div></div>		CHD	AS	-sd-	13.12.22								
							APP	SL	-sd-	13.12.22								
							DWG. NO. PE-DG-497-507-E041											
							SHT. 01 OF 14 REV.01											

ANNEXURE-II



(TO SUIT TRAY WIDTH)



W	150	300	600
L	145	295	595
T	2	2	2
t	2	2	2

FOR GENERAL NOTES REFER SHEET 14 OF 14




TYPICAL DETAILS OF CABLE TRAYS AND ACCESSORIES

NTPC DOCUMENT NO:
4540-001-215-PVE-B-045

BHEL DWG. NO.
PE-DG-497-507-E041



SHT. 02 OF 14

REV.01



**SIDE COUPLER PLATE FOR
LADDER/PERFORATED TYPE TRAYS**
(600/300/150W TRAYS)


QTY. REQUIRED/TRAY SECTION : 4 NOS.



QTY. REQD/TRAY SECTION

- A) 16 NOS. M8 BOLTS
- B) 16 NOS. NUTS
- C) 32 NOS. WASHERS

(2 NOS. COUPLER PLATES
OF 3 MM THICKNESS TO
BE SUPPLIED PER JOINT)



SEQUENCE OF M8 BOLT, WASHER, NUT, COUPLER PLATE & CABLE TRAY
FOR TYPICAL CABLE TRAY JOINT

FOR GENERAL NOTES REFER SHEET 14 OF 14




**TYPICAL DETAILS OF CABLE TRAYS AND
ACCESSORIES**

NTPC DOCUMENT NO:
4540-001-215-PVE-B-045

BHEL DWG. NO.
PE-DG-497-507-E041



SHT. 03 OF 14

REV.01



SIDE COUPLER PLATE FOR PERFORATED TYPE TRAYS (100/50W TRAYS)


QTY. REQUIRED/TRAY SECTION : 4 NOS.



QTY. REQD/TRAY SECTION

- A) 16 NOS. M6 BOLTS
- B) 16 NOS. NUTS
- C) 32 NOS. WASHERS

(2 NOS. COUPLER PLATES
OF 3 MM THICKNESS TO
BE SUPPLIED PER JOINT)



SEQUENCE OF M6 BOLT, WASHER, NUT, COUPLER PLATE & CABLE TRAY
FOR TYPICAL CABLE TRAY JOINT

FOR GENERAL NOTES REFER SHEET 14 OF 14






TYPICAL DETAILS OF CABLE TRAYS AND
ACCESSORIES

NTPC DOCUMENT NO:
4540-001-215-PVE-B-045

BHEL DWG. NO.
PE-DG-497-507-E041

SHT. 04 OF 14 REV.01

ANNEXURE-II

COVER FIXING (TYP.)DETAIL-XCABLE TRAY COVER

FOR GENERAL NOTES REFER SHEET 14 OF 14




TYPICAL DETAILS OF CABLE TRAYS AND ACCESSORIES

NTPC DOCUMENT NO:
4540-001-215-PVE-B-045BHEL DWG. NO.
PE-DG-497-507-E041


SHT. 05 OF 14

REV.01

ANNEXURE-II




LEFT HAND REDUCER




RIGHT HAND REDUCER

WW	W	DEPTH
600	300	100
600	150	100
300	150	100

LADDER TYPE

10mm DIA. HOLES



WIDTH W	BENDING RADIUS R	DEPTH	A		
			W		
			150	300	600
150, 300, 450 & 600	600	100	1354	1504	1804

LADDER TYPE

FOR GENERAL NOTES REFER SHEET 14 OF 14




TYPICAL DETAILS OF CABLE TRAYS AND ACCESSORIES

NTPC DOCUMENT NO:
4540-001-215-PVE-B-045BHEL DWG. NO.
PE-DG-497-507-E041

SHT. 06 OF 14 REV.01

Solt

HORIZONTAL CROSS-PLAN

WIDTH W	BENDING RADIUS R	$A=R+W/2+100$
600	600	1000
300	600	850

FOR GENERAL NOTES REFER SHEET 14 OF 14




TYPICAL DETAILS OF CABLE TRAYS AND ACCESSORIES

NTPC DOCUMENT NO:
4540-001-215-PVE-B-045BHEL DWG. NO.
PE-DG-497-507-E041


SHT. 07 OF 14

REV.01


ANNEXURE-II



INSIDE TYPE



OUTSIDE TYPE




ENLARGED VIEW OF "X"

VERTICAL ELBOW 90 DEG UP/DOWN

INSIDE WIDTH W	BENDING RADIUS R	DEPTH	A
600, 300 & 150	600	100	700

90° VERTICAL BEND - LADDER TYPE



LADDER TYPE

X (AS ABOVE)

HORIZONTAL ELBOW 90 DEG

INSIDE WIDTH W	BENDING RADIUS R	DEPTH	A		
			W		
			150	300	600
600, 300 & 150	600	100	854	1004	1304

90° HORIZONTAL BEND - LADDER TYPE

LADDER TYPE ACCESSORIES



FOR GENERAL NOTES REFER SHEET 14 OF 14



TYPICAL DETAILS OF CABLE TRAYS AND ACCESSORIES


NTPC DOCUMENT NO:
4540-001-215-PVE-B-045BHEL DWG. NO.
PE-DG-497-507-E041

SHT. 08 OF 14 REV.01




SECTION-CC

600/300/150 TRAYS




SECTION-DD

600/300/150 TRAYS



SECTION-DD

100/50 TRAYS



SECTION-CC

(100/50 TRAYS)

TRAY WIDTH W (mm)	600	300	150	100	50
TRAY DEPTH D (mm)	100	100	100	50	50
T (mm)	2	2	2	2	2

PERFORATED TYPE TRAY

FOR GENERAL NOTES REFER SHEET 14 OF 14




TYPICAL DETAILS OF CABLE TRAYS AND ACCESSORIES

NTPC DOCUMENT NO:
4540-001-215-PVE-B-045

BHEL DWG. NO.
PE-DG-497-507-E041

SHT. 09 OF 14 REV.01

ANNEXURE-II




LEFT HAND REDUCER


RIGHT HAND REDUCER

PERFORATED TYPE

WW	W	DEPTH
600	300	100
600	150	100
300	150	100



SECTION-EE



TEE

WIDTH W	BENDING RADIUS R	DEPTH	A		
			W		
			150	300	600
150, 300 & 600	600	100	1354	1504	1804

PERFORATED TYPE

FOR GENERAL NOTES REFER SHEET 14 OF 14




TYPICAL DETAILS OF CABLE TRAYS AND ACCESSORIES

NTPC DOCUMENT NO:
4540-001-215-PVE-B-045BHEL DWG. NO.
PE-DG-497-507-E041

SHT. 10 OF 14 REV.01

ANNEXURE-II

Sht



CROSS

WIDTH W	BENDING RADIUS R	$A=R+W/2+100$
600	600	1000
300	600	850



FOR GENERAL NOTES REFER SHEET 14 OF 14



TYPICAL DETAILS OF CABLE TRAYS AND ACCESSORIES

NTPC DOCUMENT NO:
4540-001-215-PVE-B-045BHEL DWG. NO.
PE-DG-497-507-E041

SHT. 11 OF 14 REV.01




90° VERTICAL BEND - PERFORATED TYPE

VERTICAL ELBOW 90 DEG UP/DOWN

INSIDE WIDTH W	BENDING RADIUS R	DEPTH	A
600, 300 & 150	600	100	700

HORIZONTAL ELBOW 90 DEG



90° HORIZONTAL BEND - PERFORATED TYPE

INSIDE WIDTH W	BENDING RADIUS R	DEPTH	A		
			W		
150, 300 & 600	600	100	150	300	600
			854	1004	1304

FOR GENERAL NOTES REFER SHEET 14 OF 14



TYPICAL DETAILS OF CABLE TRAYS AND ACCESSORIES


NTPC DOCUMENT NO:
4540-001-215-PVE-B-045

BHEL DWG. NO.
PE-DG-497-507-E041

SHT. 12 OF 14 REV.01

ANNEXURE-II

Sht



SECTION S-S

CABLE TROUGHS

FOR GENERAL NOTES REFER SHEET 14 OF 14



TYPICAL DETAILS OF CABLE TRAYS AND ACCESSORIES

NTPC DOCUMENT NO:
4540-001-215-PVE-B-045BHEL DWG. NO.
PE-DG-497-507-E041

SHT. 13 OF 14 REV.01

NOTES:—

1. THE CABLE TRAYS AND ACCESSORIES SHALL BE MADE OF 2mm HOT ROLLED M.S.SHEET CONFIRMING TO IS:1079. ALL THE COUPLER PLATE SHALL BE OF 3 MM THICK.
2. THE CABLE TRAYS AND ACCESSORIES SHALL BE HOT DIP GALVANISED AS PER IS 2629. THE MASS OF ZINC COATING SHALL BE 610 gm/sqm FOR 2MM THICK PRODUCT AND 460 gm/sqm FOR 1.7 MM THICK PRODUCT. THICKNESS SHALL BE 75 MICRONS (MINIMUM), 86 MICRONS (AVERAGE) FOR 2.0 MM THICK PRODUCT AND 55 MICRONS (MINIMUM), 65 MICRONS (AVERAGE) FOR 1.7 MM THICK PRODUCT .
3. FOR LADDER TYPE CABLE TRAYS AND ACCESSORIES, ALL RUNGS SHALL BE SLOTTED.
4. PERFORATED TRAYS SHALL BE FABRICATED OUT OF A SINGLE M.S. SHEET.
5. THE DIMENSIONS OF ALL BENDS, TEES, CROSSES, ETC. FOR PERFORATED CABLE TRAYS SHALL BE THE SAME AS FOR LADDER TYPE TRAY FITTINGS.
6. SIDE CHANNELS OF PERFORATED TRAY ACCESSORIES SHALL BE WELDED WITH THE PERFORATED SHEET AT INTERVALS OF 100mm.
7. LENGTH OF WELDING SHALL NOT BE LESS THAN 25mm. WELDING SHALL BE AS PER IS 9595.
8. PREFERABLY SINGLE MS PERFORATED SHEET SHALL BE USED AS BASE OF ALL PERFORATED TYPE TRAY ACCESSORIES. HOWEVER, IF USE OF PIECES OF PERFORATED SHEET IS UNAVOIDABLE FOR BASE, PIECES SHALL BE WELDED WITH EACH OTHER IN LINE WITH THE ABOVE.
9. ALL TRAY CORNERS SHALL BE FREE OF SHARP EDGES & SMOOTH.
10. THE DEPTH, WIDTH AND LENGTH OF TRAYS AND ACCESSORIES SHALL BE WITHIN A TOLERANCE AS PER RELEVANT IS
11. TO FACILITATE ASSEMBLY, ALL ACCESSORIES AT ENDS SHALL HAVE 100mm STRAIGHT PORTION.
12. ALL NUTS, BOLTS, WASHERS ETC., SHALL BE HOT DIP GALVANISED AS PER IS 1367 FOR SIZES ABOVE 12MM AND ELECTROPLATED/ELECTROGALVANISED FROM SIZE BELOW 12MM.
13. ALL DIMENSIONS ARE IN mm UNLESS NOTED OTHERWISE.
14. TRAY ACCESSORIES SHOWN IN THIS DRAWING SHALL BE FACTORY FABRICATED FOR USE AT SITE AS PER APPROVED LAYOUT DRAWINGS. FOR SPECIFIC SITE REQUIREMENTS (E.G. IRREGULAR ANGLE BENDS SUCH AS 30°/60° BENDS, ETC) AS PER SITE LAYOUT CONDITIONS, TRAY ACCESSORIES SHALL BE FABRICATED AT SITE FROM THE STRAIGHT LENGTH OF RESPECTIVE SIZES AS REQUIRED. GALVANISATION DAMAGED DURING CUTTING/WELDING OPERATIONS SHALL BE BRUSHED AND RED LEAD PRIMER, OIL PRIMER AND ALUMINIUM PAINT SHALL BE APPLIED BEFORE INSTALLATION OF THE ACCESSORIES.
15. WIDTH OF CABLE TRAYS PROPOSED TO BE USED FOR PROJECT ARE AS UNDER :
LADDER TYPE CABLE TRAY (MM) : 600, 300 & 150.
PERFORATED TYPE CABLE TRAY (MM) : 600, 300, 150, 100 & 50.
16. 600MM WIDE CABLE TRAY SHALL BE SUITABLE FOR WEIGHT OF 100KG/M INCLUDING LIVE LOAD OF RUNNING LENGTH OF CABLE TRAY.
17. CABLE TROUGHS OR 50/100MM WIDE PERFORATED TYPE TRAY SHALL BE USED FOR LOCAL CABLING/BRANCHING OUT FEW CABLES FROM MAIN ROUTE.



**TYPICAL DETAILS OF CABLE TRAYS AND
ACCESSORIES**

NTPC DOCUMENT NO:
4540-001-215-PVE-B-045

BHEL DWG. NO.
PE-DG-497-507-E041

SHT. 14 OF 14 REV.01




"We confirm that this document meets all the contract requirements including safety and statutory requirements and facilitate ease of operation and maintenance. In case any deviation is found, the Contractor shall carry out all required changes/ modifications without any cost implications to NTPC. In addition, Penalty on account of noncompliance of contract specification as deemed fit by the Employer shall be recovered.


TYPICAL INSTALLATION DETAILS FOR CABLE TRAY SUPPORT SYSTEM

NTPC DOCUMENT NO: 4540-001-215-PVE-C-046

CUSTOMER	<div><div><div>एन टी पी सी</div><div>NTPC</div></div><div>एन टी पी सी लिमिटेड</div><div>N T P C LIMITED</div></div>					
PROJECT	TALCHER THERMAL POWER PROJECT STAGE-III (2x660MW) EPC PACKAGE					
JOB NO. 497	<div><div><div>बी एच ई एल</div><div>BHEL</div></div><div>BHARAT HEAVY ELECTRICALS LIMITED</div><div>POWER SECTOR</div><div>PROJECT ENGINEERING MANAGEMENT</div><div>NOIDA(U.P) INDIA</div></div>	DPT CODE-E	DRN	NAME	SIGN	DATE
			DSN	VKS	-sd-	17.01.23
			CHD	AnA/AS	-sd-	17.01.23
			APP	SL	-sd-	17.01.23
		DWG. NO. PE-DG-497-507-E006				
		SHT. 01 OF 37 REV.0				



SINGLE CHANNEL SC1



DOUBLE CHANNEL DC1

TWO LENGTHS OF SINGLE CHANNEL

SPOT WELDED BACK TO BACK

NOTE:

AT 75MM C/C

1. ALL DIMENSIONS ARE IN mm.
2. MATERIAL : 2.5MM THICK HOT/ COLD ROLLED M.S. AS PER IS:1079.
3. FINISH : HOT DIP GALVANISED AS PER IS 2629
4. TOLERANCE ON THICKNESS IS AS PER IS 1852
5. ALL FABRICATION TOLERANCE AS PER RELEVANT IS.
6. ZINC COATING SHALL BE MIN. 75 MICRONS/ 610 G/SQ. M.




**TITLE: TYPICAL INSTALLATION DETAILS
FOR CABLE TRAY SUPPORT
SYSTEM**

NTPC DOC. NO: 4540-001-215-PVE-C-046

BHEL DRWG NO: PE-DG-497-507-E006


REV.0

SH 02 OF 37



CANTILEVER ARMS

TRAY WIDTH IN MM	CANTILEVER ARM LENGTH (L) IN MM
150	170 (FOR OVERHEAD TRAYS)
300	320 (FOR OVERHEAD TRAYS)
600	620 (FOR OVERHEAD TRAYS)
600	750 (FOR TRENCH)



TYPICAL ASSEMBLY OF CHANNEL SUPPORTS AND CABLE TRAY

M12 HEX BOLT & WASHER-2Nos.
M12 SPRING NUTS-2Nos.
M6 PAN HEAD SCREWS & WASHER-2Nos.
M6 SPRING NUTS-2Nos.

NOTES :

1. ALL DIMENSIONS ARE IN mm.
2. ITEM NO.1 MATERIAL : HOT/ COLD ROLLED M.S. AS PER RELEVANT IS.
3. ITEM NO.2 MATERIAL : M.S AS PER IS-2062
4. FINISH : HOT DIP GALVANISED AS PER IS:2629
5. TOLERANCE ON THICKNESS IS AS PER IS:1852
6. ALL FABRICATION TOLERANCE AS PER RELEVANT IS.
7. ZINC COATING SHALL BE MIN. 75 MICRONS/ 610 G/SQ. M.




**TITLE: TYPICAL INSTALLATION DETAILS
FOR CABLE TRAY SUPPORT
SYSTEM**

NTPC DOC. NO: 4540-001-215-PVE-C-046

BHEL DRWG NO: PE-DG-497-507-E006

REV.0

SH 03 OF 37



90 ANGLE FITTING HL1 (HEAVY DUTY TYPE)

**ANCHOR FASTENER-2Nos.
SPRING NUT & WASHER-2Nos.**

NOTES :

1. ALL DIMENSIONS ARE IN mm.
2. MATERIAL :MILD STEEL AS PER IS-2062
3. FINISH : HOT DIP GALVANISED AS PER IS:2629
4. TOLERANCE ON THICKNESS AS PER IS:1852
5. ALL FABRICATION TOLERANCE AS PER RELEVANT IS.
6. ZINC COATING SHALL BE MIN. 75 MICRONS/ 610 G/SQ. M.



**TITLE: TYPICAL INSTALLATION DETAILS
FOR CABLE TRAY SUPPORT
SYSTEM**







NTPC DOC. NO: 4540-001-215-PVE-C-046

BHEL DRWG NO: PE-DG-497-507-E006

REV.0

SH 04 OF 37

Sgt

CLAMP FOR SINGLE CHANNEL CC1CLAMP FOR DOUBLE CHANNEL CC2NOTES

1. ALL DIMENSIONS ARE IN mm.
2. MATERIAL :MILD STEEL AS PER IS-2062
3. FINISH : HOT DIP GALVANISED AS PER IS:2629
4. TOLERANCE ON THICKNESS AS PER IS:1852
5. ALL FABRICATION TOLERANCE AS PER RELEVANT IS.
6. ZINC COATING SHALL BE MIN. 75 MICRONS/ 610 G/SQ. M.

ANCHOR FASTENER-2N0s.
SPRING NUT & WASHER-1N0.



**TITLE: TYPICAL INSTALLATION DETAILS
FOR CABLE TRAY SUPPORT
SYSTEM**



NTPC DOC. NO: 4540-001-215-PVE-C-046

BHEL DRWG NO: PE-DG-497-507-E006

REV.0

SH 05 OF 37

Solit



BASE PLATE FOR SINGLE CHANNEL BP1

NOTE

1. ALL DIMENSIONS ARE IN mm.
2. MATERIAL :MILD STEEL AS PER IS-2062
3. FINISH : HOT DIP GALVANISED AS PER IS:2629
4. TOLERANCE ON THICKNESS AS PER IS:1852
5. ALL FABRICATION TOLERANCE AS PER RELEVANT IS.
6. ZINC COATING SHALL BE MIN. 75 MICRONS/ 610 G/SQ. M.

**ANCHOR FASTENER-1NO.
SPRING NUT & WASHER-1NO.**





**TITLE: TYPICAL INSTALLATION DETAILS
FOR CABLE TRAY SUPPORT
SYSTEM**

NTPC DOC. NO: 4540-001-215-PVE-C-046

BHEL DRWG NO: PE-DG-497-507-E006

REV.0

SH 06 OF 37



**ANCHOR FASTENER-2NOS.
SPRING NUT & WASHER-2NOS.**

BASE PLATE FOR DOUBLE CHANNEL BP2

NOTE

1. ALL DIMENSIONS ARE IN mm.
2. MATERIAL :MILD STEEL AS PER IS-2062
3. FINISH : HOT DIP GALVANISED AS PER IS:2629
4. TOLERANCE ON THICKNESS AS PER IS:1852
5. ALL FABRICATION TOLERANCE AS PER RELEVANT IS.
6. ZINC COATING SHALL BE MIN. 75 MICRONS/ 610 G/SQ. M.



**TITLE: TYPICAL INSTALLATION DETAILS
FOR CABLE TRAY SUPPORT
SYSTEM**


NTPC DOC. NO: 4540-001-215-PVE-C-046

BHEL DRWG NO: PE-DG-497-507-E006

REV.0

SH 07 OF 37

S. P. T.





**TITLE: TYPICAL INSTALLATION DETAILS
FOR CABLE TRAY SUPPORT
SYSTEM**

NTPC DOC. NO: 4540-001-215-PVE-C-046

BHEL DRWG NO: PE-DG-497-507-E006

REV.0

SH 08 OF 37



TRAY FIXING CLAMP - TC1

NOTES

1. ALL DIMENSIONS ARE IN mm.
2. MATERIAL :MILD STEEL AS PER IS-2062
3. FINISH : HOT DIP GALVANISED AS PER IS:2629
4. TOLERANCE ON THICKNESS AS PER IS:1852
5. ALL FABRICATION TOLERANCE AS PER RELEVANT IS.
6. ZINC COATING SHALL BE MIN. 75 MICRONS/ 610 G/SQ. M.

SPRING NUT & WASHER-1NO.

*** :-2MM FOR TRAY FIXING CLAMP TC1
4MM FOR FRP-TRAY FIXING CLAMP**






**TITLE: TYPICAL INSTALLATION DETAILS
FOR CABLE TRAY SUPPORT
SYSTEM**

NTPC DOC. NO: 4540-001-215-PVE-C-046

BHEL DRWG NO: PE-DG-497-507-E006

REV.0

SH 09 OF 37

**SPRING NUT & WASHER-4Nos.****FLAT PLATE STRAIGHT FITTING PF2****SPRING NUT & WASHER-3Nos.****FLAT PLATE TEE FITTING PF1****SPRING NUT & WASHER-2Nos.****NOTES****90° ANGLE FITTING LA1**

1. ALL DIMENSIONS ARE IN mm.
2. MATERIAL :MILD STEEL AS PER IS-2062
3. FINISH : HOT DIP GALVANISED AS PER IS:2629
4. TOLERANCE ON THICKNESS AS PER IS:1852
5. ALL FABRICATION TOLERANCE AS PER RELEVANT IS.
6. ZINC COATING SHALL BE MIN. 75 MICRONS/ 610 G/SQ. M.




**TITLE: TYPICAL INSTALLATION DETAILS
FOR CABLE TRAY SUPPORT
SYSTEM**

NTPC DOC. NO: 4540-001-215-PVE-C-046

BHEL DRWG NO: PE-DG-497-507-E006

REV.0


SH 10 OF 37




SPRING NUT ASSEMBLY TYPICAL DETAILS OF WASHER

WASHER SIZE DETAILS


Sl.No.	BOLT/SCREW SIZE	HOLE DIA (IN MM)	OUTER DIA (IN MM)	WASHER THICKNESS (IN MM)
1	M6 PAN HEAD SCREW	6.4	12	1.6
2	M12 HEXA BOLT	13	24	2.5



PAN HEAD SCREW



HEX BOLT



ANCHOR BOLT M10

1. MATERIAL - MS AS PER IS - 2062.
2. M6 CHANNEL NUT DIMENSIONAL SIMILAR TO M12.
EXCEPT HOLE DRILLED AND TAPPED TO M6 PAN HEAD SCREWS.
3. TAPPED HOLE THREADING TO MATCH WITH THREADING OF BOLTS.
4. SURFACE PROTECTION ELECTROGALVANISED / CADMIUM PLATED.
5. ALL DIMENSIONS ARE IN MM.
6. ZINC COATING SHALL BE MIN. 75 MICRONS/ 610 G/SQ. M.




TITLE: TYPICAL INSTALLATION DETAILS FOR CABLE TRAY SUPPORT SYSTEM

NTPC DOC. NO: 4540-001-215-PVE-C-046


BHEL DRWG NO: PE-DG-497-507-E006

REV.0

SH 11 OF 37



TRESTLE BRAKET



FIXING ARRANGMENT OF TRESTLE BRACKET

NOTES

1. ALL DIMENSIONS ARE IN mm.
2. MATERIAL :MILD STEEL AS PER IS-2062
3. FINISH : HOT DIP GALVANISED AS PER IS:2629
4. TOLERANCE ON THICKNESS AS PER IS:1852
5. ALL FABRICATION TOLERANCE AS PER RELEVANT IS.
6. ZINC COATING SHALL BE MIN. 75 MICRONS/ 610 G/SQ. M.



**TITLE: TYPICAL INSTALLATION DETAILS
FOR CABLE TRAY SUPPORT
SYSTEM**

NTPC DOC. NO: 4540-001-215-PVE-C-046

BHEL DRWG NO: PE-DG-497-507-E006

REV.0

SH 12 OF 37

INDEX

SHEET NO	INSTALLATION DETAIL TYPE	DESCRIPTION OF INSTALLATION DETAIL
13	-	INDEX
14	-	TYPICAL SUPPORT SYSTEM ELEMENTS
15	-	TYPICAL SUPPORT SYSTEM ELEMENTS
16	SB1, SB2, SS1, SS2	SINGLE CHANNEL SUPPORT INSTALLATION, TRAYS ON SINGLE SIDE, BOTH ENDS FIXED / ONLY TOP END FIXED
17	SS3, SS4, SS5, SB3	SINGLE CHANNEL SUPPORT INSTALLATION, TRAYS ON SINGLE SIDE, ONLY BOTTOM END FIXED / BOTH ENDS FIXED
18	DB1, DB2, DB3, DB4	DOUBLE CHANNEL SUPPORT INSTALLATION, TRAYS ON BOTH SIDE, BOTH ENDS FIXED
19	DS1, DS2, DS3, DS4	DOUBLE CHANNEL SUPPORT INSTALLATION, TRAYS ON SINGLE/BOTH SIDE, ONLY TOP END FIXED
20	DS5, DS6, DS7, DS8	DOUBLE CHANNEL SUPPORT INSTALLATION, TRAYS ON SINGLE/BOTH SIDE, ONLY BOTTOM END FIXED
21	OH1	TYPICAL TRAY SUPPORT ARRANGEMENT ALONG PIPERACK UPTO 3 TRAYS
22	OH2	TYPICAL TRAY SUPPORT ARRANGEMENT ALONG PIPERACK MORE THAN 3 TRAYS
23	OV1	TYPICAL VERTICALLY ORIENTED TRAY SUPPORT ARRANGEMENT ALONG PIPERACK TRAYS SUPPORTED FROM TOP
24	OV2	TYPICAL VERTICALLY ORIENTED TRAY SUPPORT ARRANGEMENT ALONG PIPERACK TRAYS SUPPORTED FROM SIDE
25	CT1, CT2	TYPICAL DETAILS FOR CROSS TRAYS OVER TRESTLE
26	PM1, PM2	TYPICAL TRAY INSTALLATION AROUND PORTAL MEMBER ON PIPERACK
27	CR1, CR2	RISER ALONG STRUCTURAL STEEL, CHANNEL FRAME WORK FOR RISER UPTO 3 TRAYS. DETAIL FOR ADDITIONAL SUPPORT TO RISER COLUMN
28	CR3	TYPICAL CHANNEL FRAME WORK FOR CABLE TRAY RISER UPTO 3 TRAYS, DETAIL FOR ADDITIONAL SUPPORT TO RISER COLUMN
29	CR4	TYPICAL CHANNEL FRAME WORK FOR CABLE TRAY RISER MORE THAN 3 TRAYS
30	BB1, BB2, BB3, BB4	SUPPORTING ARRANGEMENT BELOW I-BEAMS/ W. BOX/ WELDED BEAMS
31	TR1, TR2	SUPPORTING ARRANGEMENT IN CABLE TRENCH
32	-	ROUTE MARKER DETAILS
33	-	BURIED CABLE DETAILS
34	-	ROAD CROSSING OF BURIED CABLE, CABLE TRAY ENTRY TO BDG/TRENCH
35	-	CABLE TRAY/RACK ENTRY TO BUILDING
36	-	CABLE CLAMPING ARRANGEMENT
37	-	GENERAL NOTES



**TITLE: TYPICAL INSTALLATION DETAILS
FOR CABLE TRAY SUPPORT
SYSTEM**


NTPC DOC. NO: 4540-001-215-PVE-C-046

BHEL DRWG NO: PE-DG-497-507-E006

REV.0


SH 13 OF 37

Set




TYPICAL ASSEMBLY OF CHANNEL SUPPORTS AND CABLE TRAY


- 1) 600mm TRAY-1 TO 6 TIER -C2
- 2) 300mm TRAY-1 TO 3 TIER -C1
- 3) 300mm TRAY-4 TO 6 TIER -C2
- 4) 150mm TRAY-1 TO 6 TIER -C1




END VIEW OF CANTILEVER ARM




BASE PLATE FOR SINGLE CHANNEL (BP1)




C1 CHANNEL CLAMP (CC1)





BASE PLATE FOR DOUBLE CHANNEL (BP2)




SECTION OF C1 (SINGLE CHANNEL)



C2 CHANNEL CLAMP (CC2)



SECTION OF C2 (DOUBLE CHANNEL)



TRAY CLAMP (TC1) (SEE NOTE VI)

TYPICAL SUPPORT SYSTEM ELEMENTS



TITLE: TYPICAL INSTALLATION DETAILS FOR CABLE TRAY SUPPORT SYSTEM


NTPC DOC. NO: 4540-001-215-PVE-C-046

BHEL DRWG NO: PE-DG-497-507-E006


REV.0

SH 14 OF 37


Solit




BEAM CLAMP (BC1)
(SEE FIXING DETAIL ON SHEET 30)




ANGLE FITTING (LA1)



FLAT PLATE TEE FITTING (PF1)



HEAVY DUTY RIGHT ANGLE FITTING HL1



FLAT PLATE STRAIGHT FITTING PF2

TYPICAL SUPPORT SYSTEM ELEMENTS



**TITLE: TYPICAL INSTALLATION DETAILS
FOR CABLE TRAY SUPPORT
SYSTEM**

NTPC DOC. NO: 4540-001-215-PVE-C-046


BHEL DRWG NO: PE-DG-497-507-E006

REV.0

SH 15 OF 37


ANNEXURE-II

Solit




INSTALLATION DETAIL TYPE SB1:
SINGLE CHANNEL SUPPORT INSTALLATION
BOTH ENDS FIXED, TRAYS ON SINGLE SIDE
WITH BP1 AT TOP BOTTOM
APPLICABLE FOR THREE TRAYS AND MORE

(SEE NOTE IX)




INSTALLATION DETAIL TYPE SB2:
SINGLE CHANNEL SUPPORT INSTALLATION
BOTH ENDS FIXED, TRAYS ON SINGLE SIDE
WITH HL1 AT TOP & BP1 AT BOTTOM
APPLICABLE FOR THREE TRAYS AND MORE

(SEE NOTE IX)



INSTALLATION DETAIL TYPE SS1:
SINGLE CHANNEL SUPPORT INSTALLATION
ONLY TOP END FIXED, TRAYS ON SINGLE SIDE
WITH BASEPLATE BP1 AT TOP
APPLICABLE FOR UPTO & INCLUDING TWO TRAYS

(SEE NOTE IX)



INSTALLATION DETAIL TYPE SS2:
SINGLE CHANNEL SUPPORT INSTALLATION
ONLY TOP END FIXED, TRAYS ON SINGLE SIDE
WITH ANGLE FITTING HL1 AT TOP
APPLICABLE FOR UPTO & INCLUDING TWO TRAYS

(SEE NOTE IX)



**TITLE: TYPICAL INSTALLATION DETAILS
 FOR CABLE TRAY SUPPORT
 SYSTEM**


NTPC DOC. NO: 4540-001-215-PVE-C-046

BHEL DRWG NO: PE-DG-497-507-E006


REV.0

SH 16 OF 37


501




INSTALLATION DETAIL TYPE SS3:
SINGLE CHANNEL SUPPORT INSTALLATION
ONLY BOTTOM END FIXED TRAYS ON SINGLE SIDE
BASEPLATE BP1 AT BOTTOM
APPLICABLE FOR UPTO & INCLUDING TWO TRAYS



INSTALLATION DETAIL TYPE SS4:
SINGLE CHANNEL SUPPORT INSTALLATION
ONLY BOTTOM END FIXED TRAYS ON SINGLE SIDE
WITH ANGLE FITTING HL1 AT BOTTOM
APPLICABLE FOR UPTO & INCLUDING TWO TRAYS



INSTALLATION DETAIL TYPE SS5:
SINGLE CHANNEL SUPPORT INSTALLATION
ONLY BOTTOM END FIXED,
TRAYS ORIENTED VERTICALLY
BASEPLATE AT BOTTOM
APPLICABLE FOR UPTO &
INCLUDING TWO TRAYS



INSTALLATION DETAIL TYPE SB3:
SINGLE CHANNEL SUPPORT INSTALLATION, BOTH ENDS FIXED
TRAYS ON SINGLE SIDE, APPLICABLE FOR SUPPORTING TRAYS
IN VERTICAL ORIENTATION ALONG BUILDING WALLS



TITLE: TYPICAL INSTALLATION DETAILS FOR CABLE TRAY SUPPORT SYSTEM

NTPC DOC. NO: 4540-001-215-PVE-C-046


BHEL DRWG NO: PE-DG-497-507-E006

REV.0


SH 17 OF 37

ANNEXURE-II


Solit




INSTALLATION DETAIL TYPE DB1:
DOUBLE CHANNEL SUPPORT INSTALLATION
BOTH ENDS FIXED, TRAYS ON SINGLE SIDE
WITH BASEPLATE BP2 AT TOP & BOTTOM
APPLICABLE FOR MORE THAN THREE TRAYS
(SEE NOTE IX)



INSTALLATION DETAIL TYPE DB2:
DOUBLE CHANNEL SUPPORT INSTALLATION
BOTH ENDS FIXED, TRAYS ON SINGLE SIDE
WITH HL1 AT TOP & BP2 AT BOTTOM
APPLICABLE FOR MORE THAN THREE TRAYS
(SEE NOTE IX)



INSTALLATION DETAIL TYPE DB3:
DOUBLE CHANNEL SUPPORT INSTALLATION
BOTH ENDS FIXED, TRAYS ON BOTH SIDES
WITH BASEPLATE BP2 AT TOP & BOTTOM
(SEE NOTE IX)



INSTALLATION DETAIL TYPE DB4:
DOUBLE CHANNEL SUPPORT INSTALLATION
BOTH ENDS FIXED, TRAYS ON BOTH SIDES
WITH HL1 AT TOP & BP2 AT BOTTOM
(SEE NOTE IX)



**TITLE: TYPICAL INSTALLATION DETAILS
 FOR CABLE TRAY SUPPORT
 SYSTEM**


NTPC DOC. NO: 4540-001-215-PVE-C-046

BHEL DRWG NO: PE-DG-497-507-E006


REV.0

SH 18 OF 37


ANNEXURE-II




INSTALLATION DETAIL TYPE DS1:
DOUBLE CHANNEL SUPPORT INSTALLATION
ONLY TOP END FIXED
BASEPLATE AT TOP
APPLICABLE FOR THREE TRAYS ON SINGLE SIDE
(SEE NOTE IX)



INSTALLATION DETAIL TYPE DS2:
DOUBLE CHANNEL SUPPORT INSTALLATION
ONLY TOP END FIXED
BASEPLATE AT TOP
APPLICABLE FOR UPTO THREE TRAYS ON BOTH SIDES
(SEE NOTE IX)



INSTALLATION DETAIL TYPE DS3:
DOUBLE CHANNEL SUPPORT INSTALLATION
ONLY TOP END FIXED
WITH ANGLE FITTING HL1 AT TOP
APPLICABLE FOR MORE THAN TWO TRAYS
ON SINGLE SIDE
(SEE NOTE IX)



INSTALLATION DETAIL TYPE DS4:
DOUBLE CHANNEL SUPPORT INSTALLATION
ONLY TOP END FIXED
WITH ANGLE FITTING HL1 AT TOP
APPLICABLE FOR UPTO THREE TRAYS ON BOTH SIDES
(SEE NOTE IX)



**TITLE: TYPICAL INSTALLATION DETAILS
 FOR CABLE TRAY SUPPORT
 SYSTEM**


NTPC DOC. NO: 4540-001-215-PVE-C-046

BHEL DRWG NO: PE-DG-497-507-E006


REV.0

SH 19 OF 37


Solit




INSTALLATION DETAIL TYPE DS5:
DOUBLE CHANNEL SUPPORT INSTALLATION
ONLY BOTTOM END FIXED TRAYS ON SINGLE SIDE
BASEPLATE AT BOTTOM



INSTALLATION DETAIL TYPE DS6:
DOUBLE CHANNEL SUPPORT INSTALLATION
ONLY BOTTOM END FIXED
UPTO THREE TRAYS ON BOTH SIDES
BASEPLATE AT BOTTOM



INSTALLATION DETAIL TYPE DS7:
DOUBLE CHANNEL SUPPORT INSTALLATION
ONLY BOTTOM END FIXED TRAYS ON SINGLE SIDE
WITH ANGLE FITTING HL1 AT BOTTOM



INSTALLATION DETAIL TYPE DS8:
DOUBLE CHANNEL SUPPORT INSTALLATION
ONLY BOTTOM END FIXED
UPTO THREE TRAYS ON BOTH SIDES
WITH ANGLE FITTING HL1 AT BOTTOM



**TITLE: TYPICAL INSTALLATION DETAILS
 FOR CABLE TRAY SUPPORT
 SYSTEM**

NTPC DOC. NO: 4540-001-215-PVE-C-046



BHEL DRWG NO: PE-DG-497-507-E006

REV.0

SH 20 OF 37

ANNEXURE-II

501t



**INSTALLATION DETAIL TYPE OH1:
TYPICAL TRAY SUPPORT ARRANGEMENT ALONG PIPERACK
(UPTO AND INCLUDING THREE TRAYS) (SEE NOTE IX)**



**TITLE: TYPICAL INSTALLATION DETAILS
FOR CABLE TRAY SUPPORT
SYSTEM**



NTPC DOC. NO: 4540-001-215-PVE-C-046

BHEL DRWG NO: PE-DG-497-507-E006

REV.0

SH 21 OF 37

Set



INSTALLATION DETAIL TYPE OH2:
TYPICAL TRAY SUPPORT ARRANGEMENT ALONG PIPERACK
(MORE THAN THREE TRAYS)
(SEE NOTE IX)



**TITLE: TYPICAL INSTALLATION DETAILS
FOR CABLE TRAY SUPPORT
SYSTEM**


NTPC DOC. NO: 4540-001-215-PVE-C-046

BHEL DRWG NO: PE-DG-497-507-E006

REV.0

SH 22 OF 37

Solit



INSTALLATION DETAIL TYPE OV1
TYPICAL VERTICALLY ORIENTED TRAY SUPPORT ARRANGEMENT ALONG PIPERACK



**TITLE: TYPICAL INSTALLATION DETAILS
FOR CABLE TRAY SUPPORT
SYSTEM**


NTPC DOC. NO: 4540-001-215-PVE-C-046

BHEL DRWG NO: PE-DG-497-507-E006

REV.0

SH 23 OF 37

ANNEXURE-II



INSTALLATION DETAIL TYPE OV2:
VERTICALLY ORIENTED TRAY SUPPORT ARRANGEMENT ALONG PIPERACK (USING BP1)
 (SEE NOTE IX)



**TITLE: TYPICAL INSTALLATION DETAILS
FOR CABLE TRAY SUPPORT
SYSTEM**


NTPC DOC. NO: 4540-001-215-PVE-C-046

BHEL DRWG NO: PE-DG-497-507-E006



REV.0

SH 24 OF 37


Solit



INSTALLATION DETAIL TYPE CT1:
CROSS TRAYS OVER TRESTLE



INSTALLATION DETAIL TYPE CT2:
CROSS TRAYS OVER TRESTLE



TITLE: TYPICAL INSTALLATION DETAILS FOR CABLE TRAY SUPPORT SYSTEM


NTPC DOC. NO: 4540-001-215-PVE-C-046

BHEL DRWG NO: PE-DG-497-507-E006


REV.0

SH 25 OF 37

Solit



INSTALLATION DETAIL TYPE PM1:
CABLE TRAYS ROUTED AROUND PORTAL MEMBER
FOR VERTICALLY ORIENTED TRAYS
(SEE NOTE-III(3))



INSTALLATION DETAIL TYPE PM2:
CABLE TRAYS ROUTED AROUND PORTAL MEMBER
FOR HORIZONTALLY ORIENTED TRAYS
(SEE NOTE-III(3))




**TITLE: TYPICAL INSTALLATION DETAILS
 FOR CABLE TRAY SUPPORT
 SYSTEM**

NTPC DOC. NO: 4540-001-215-PVE-C-046


BHEL DRWG NO: PE-DG-497-507-E006

REV.0

SH 26 OF 37



**INSTALLATION DETAIL TYPE CR1:
RISER ALONG STRUCTURAL STEEL**



**INSTALLATION DETAIL TYPE CR2:
(USING CC1 CLAMPS UPTO 3 TRAYS)**

**(TYPICAL CHANNEL FRAME WORK FOR CABLE TRAY RISER
UPTO & INCLUDING THREE CABLE TRAYS)**




**TITLE: TYPICAL INSTALLATION DETAILS
FOR CABLE TRAY SUPPORT
SYSTEM**

NTPC DOC. NO: 4540-001-215-PVE-C-046

BHEL DRWG NO: PE-DG-497-507-E006



REV.0

SH 27 OF 37



INSTALLATION DETAIL TYPE CR3:
(USING FITTINGS PF1/PF2)

(TYPICAL CHANNEL FRAME WORK FOR CABLE TRAY RISER
UPTO & INCLUDING THREE CABLE TRAYS)



TITLE: TYPICAL INSTALLATION DETAILS FOR CABLE TRAY SUPPORT SYSTEM



NTPC DOC. NO: 4540-001-215-PVE-C-046

BHEL DRWG NO: PE-DG-497-507-E006

REV.0

SH 28 OF 37

Solit



INSTALLATION DETAIL TYPE CR4:
TYPICAL CHANNEL FRAME WORK FOR CABLE TRAY RSIER
(FOR MORE THAN THREE CABLE TRAYS)



**TITLE: TYPICAL INSTALLATION DETAILS
FOR CABLE TRAY SUPPORT
SYSTEM**

NTPC DOC. NO: 4540-001-215-PVE-C-046


BHEL DRWG NO: PE-DG-497-507-E006

REV.0


SH 29 OF 37

ANNEXURE-II


Solit




INSTALLATION DETAIL TYPE BB1:
CABLE TRAYS BELOW I-BEAMS
(UPTO & INCLUDING THREE TRAYS)



INSTALLATION DETAIL TYPE BB2:
CABLE TRAYS BELOW I-BEAMS
(MORE THAN THREE TRAYS)



INSTALLATION DETAIL TYPE BB3:
CABLE TRAYS BELOW W. BOX/
WELDED BEAM'S (APPLICABLE FOR
UPTO & INCLUDING THREE TRAYS)



INSTALLATION DETAIL TYPE BB4:
CABLE TRAYS BELOW W. BOX/
WELDED BEAM'S (APPLICABLE FOR
MORE THAN THREE TRAYS)



TITLE: TYPICAL INSTALLATION DETAILS
FOR CABLE TRAY SUPPORT
SYSTEM


NTPC DOC. NO: 4540-001-215-PVE-C-046

BHEL DRWG NO: PE-DG-497-507-E006

REV.0


SH 30 OF 37

Soit




* A : MIN. 300 FOR POWER CABLES
MIN. 250 FOR CONTROL & SCREENED CABLES

** X=100 : CLEAR GAP BETWEEN TRENCH WALL & TRAY
FOR PASSAGE OF CABLES APPLICABLE BELOW
SWITCHGEAR/ CONTROL PANELS ONLY.



DETAIL-B

INSTALLATION DETAIL TYPE TR1:
SUPPORTING ARRANGEMENT IN CABLE TRENCH, TRAYS ON SINGLE SIDE



* A : MIN. 300 FOR POWER CABLES
MIN. 250 FOR CONTROL & SCREENED CABLES

** X=100 : CLEAR GAP BETWEEN TRENCH WALL & TRAY
FOR PASSAGE OF CABLES APPLICABLE BELOW
SWITCHGEAR/ CONTROL PANELS ONLY.

TRAY WIDTH	W (MM)
600MM	750
300MM	320
150MM	170

INSTALLATION DETAIL TYPE TR2:
SUPPORTING ARRANGEMENT IN CABLE TRENCH
TRAYS ON BOTH SIDE



**TITLE: TYPICAL INSTALLATION DETAILS
FOR CABLE TRAY SUPPORT
SYSTEM**


NTPC DOC. NO: 4540-001-215-PVE-C-046

BHEL DRWG NO: PE-DG-497-507-E006

REV.0

SH 31 OF 37

Solit

**NOTES:**

1. ALL DIMENSION ARE IN mm.
2. ROUTE MARKERS SHALL BE CONSTRUCTED OF CONCRETE WITH CAST IRON PLATE, WITH THE ROUTE INFORMATION ENGRAVED ON IT, BOLTED ON TOP OF THE CONCRETE BLOCK AS SHOWN.
3. CAST IRON PLATE SHALL BE OF MIN 6.0mm THICKNESS.



**TITLE: TYPICAL INSTALLATION DETAILS
FOR CABLE TRAY SUPPORT
SYSTEM**

NTPC DOC. NO: 4540-001-215-PVE-C-046


BHEL DRWG NO: PE-DG-497-507-E006

REV.0


SH 32 OF 37

ANNEXURE-II

Sait



DIRECTLY BURIED CABLES
IN SINGLE LAYER



DIRECTLY BURIED CABLES
IN TWO LAYER

LEGEND

- ① CABLE ROUTE MARKER
- ② EARTH BACK FILLED & RAMMED
- ③ PROTECTIVE COVERS
 - a.) BRICK FOR LOW VOLTAGE CABLES
 - b.) RCC FOR HIGH VOLTAGE CABLES WITH HOLE AT EACH END TO TIE EACH OTHER WITH G.S. WIRE
- ④ ARMoured POWER CABLE
- ⑤ ARMoured CONTROL CABLE
- ⑥ FINE SAND/RIDDLLED SOIL COMPACTED

DIMENSION MIN	1100V GRADE CABLES	FOR 3.3 KV TO 11KV	ABOVE 11KV & UPTO 33KV
D1	750	900	1050
S	= d BETWEEN CABLES OF SAME CLASS = *300MM BETWEEN CABLES OF DIFFERENT CLASS = *400MM BETWEEN 1/C POWER CABLE AND COMMUNICATION CABLE = *300MM BETWEEN MULTICORE POWER CABLE & COMMUNICATION CABLE		

d= OVERALL DIAMETER OF THE BIGGER OF THE TWO CABLES

D1= MINIMUM DEPTH OF LAYING FROM GROUND SURFACE
TO TOP OF CABLES.

* = SPACING SHALL BE TAKEN BOTH HORIZONTALLY AND VERTICALLY

NOTE

- SINGLE CORE CABLES SHALL BE RUN IN TREFOIL FORMATION AND SHALL BE BOUND BY SELFLOCKING CABLE TIES AT EVERY 750 MM.
- CABLE IDENTIFICATION TAG SHALL BE TIED AT BOTH ENDS OF THE CABLE
- IF THE MINIMUM CLARENCE AS INDICATED IN THE ABOVE TABLE FOR CABLES OF DIFFERENT CLASSES ARE NOT FEASIBLE BRICK BARRIERS SHALL BE USED BETWEEN ADJACENT CABLES.
- G.I/HUME /HDPE PIPES SHALL BE PROVIDED FOR ROAD CROSSING AT A MINIMUM DEPTH OF 600 FROM THE GRADE LEVEL AS DECIDED FRO THE PROJECT.
- ALL DIMENSION ARE IN MM.



**TITLE: TYPICAL INSTALLATION DETAILS
FOR CABLE TRAY SUPPORT
SYSTEM**


NTPC DOC. NO: 4540-001-215-PVE-C-046

BHEL DRWG NO: PE-DG-497-507-E006


REV.0

SH 33 OF 37


Solit




ROAD CROSSING OF BURIED CABLE



TYP. DETAILS OF BURIED CABLE ENTRY TO BLDG. OR CABLE TRENCH



CABLE TAG CONTROL CABLE



CABLE TAG POWER CABLE

NOTE:

1. ALL DIMENSIONS ARE IN 'MM'.
2. BURIED CABLE DETAILS ARE SUBJECT TO CHANGE AS PER LAYOUT OF RESPECTIVE AREA.



**TITLE: TYPICAL INSTALLATION DETAILS
FOR CABLE TRAY SUPPORT
SYSTEM**

NTPC DOC. NO: 4540-001-215-PVE-C-046



BHEL DRWG NO: PE-DG-497-507-E006

REV.0

SH 34 OF 37

Solt

Scanned with CamScanner



CABLE LAYING IN SHALLOW TRENCH (INDOOR)

NOTE:

1. ALL DIMENSIONS ARE IN 'MM'.
2. ABOVE DETAILS ARE SUBJECT TO CHANGE AS PER LAYOUT OF RESPECTIVE AREA.
3. THE PORTION OF FLOOR ABOVE THE TRENCH MARKED '*' SHALL BE FINISHED WITH WEAK MORTER.



TITLE: TYPICAL INSTALLATION DETAILS FOR CABLE TRAY SUPPORT SYSTEM

NTPC DOC. NO: 4540-001-215-PVE-C-046







BHEL DRWG NO: PE-DG-497-507-E006

REV.0

SH 35 OF 37

ANNEXURE-II

Solt

VERTICAL
SUPPORT SC1SUPPORTING ARRANGEMENT FOR BRICK OR CONCRETE WALL/COLUMNCABLE CLAMPS IN TREFOIL FORMATION
FOR SINGLE CORE POWER CABLESCABLE CLAMPS FOR
MULTICORE POWER CABLES
(NOT TOUCHING EACHOTHER)CLAMPING ARRANGEMENT
OF CONTROL CABLESCABLE CLAMPS FOR
MULTICORE POWER CABLES
(TOUCHING EACHOTHER)

NOTE:

For horizontal trays arrangements, multicore power cables and control cables shall be secured at every five meter interval. For vertical tray arrangement, individual multicore power cables and control cables shall be secured at every one meter by nylon cable strap.

After completion of cable laying work in the particular vertical tray, all the control cables shall be binded to trays/supports by aluminium strips at every five meter interval and at every bend.



TITLE: TYPICAL INSTALLATION DETAILS
FOR CABLE TRAY SUPPORT
SYSTEM

NTPC DOC. NO: 4540-001-215-PVE-C-046

BHEL DRWG NO: PE-DG-497-507-E006

REV.0

SH 36 OF 37

NOTES:-

- I.** THIS DRAWING SHALL BE REFERRED ONLY FOR INSTALLATION OF CABLE TRAY SUPPORT SYSTEM.
- II. SUPPORTING ARRANGEMENT IN CABLE VAULTS**
1. BASEPLATES/ANGLE FITTINGS SHALL BE CONTINUOUSLY WELDED ALL ROUND TO STEEL MEMBERS/ PLATE INSERTS PROVIDED. BRACKETS/ CLAMPS SHALL BE WELDED TO STEEL SURFACE WITH CHANNEL SC1/DC1 (AS APPLICABLE) IN POSITION TO ENSURE ALIGNMENT OF CLAMPS/CHANNEL. WELD THICKNESS SHALL BE 6MM MINIMUM. IN CASE STEEL SURFACE IS NOT AVAILABLE FOR WELDING, ANCHOR BOLTS SHALL BE USED FOR FIXING THE BASEPLATE/ANGLE FITTING.
 2. MAIN SUPPORTS FOR ALL LONGITUDINAL CABLE TRAY RUNS IN THE CABLE VAULTS SHALL BE FIXED AT BOTH ENDS AT THE TOP AS WELL AS AT THE BOTTOM AS OUTLINED ABOVE, FOR MORE THAN THREE TRAYS.
 3. SINGLE CHANNEL SUPPORT SC1 WHEREVER SUPPORTED FROM TOP ONLY SHALL BE USED FOR UPTO AND INCLUDING TWO TRAYS ONLY. WHEREVER MORE THAN TWO TRAYS ARE TO BE SUPPORTED IN THIS FASHION, DOUBLE CHANNEL DC1 SHALL BE USED.
 4. GALVANISATION DAMAGED DUE TO WELDING/CUTTING SHALL BE BRUSHED & RED LEAD PRIMER, OIL PRIMER AND ALUMINIUM PAINT SHALL BE APPLIED.
- III. SUPPORTING ARRANGEMENT ALONG PIPERACK**
1. BRACKETS/CLAMPS SHALL BE WELDED TO STEEL SURFACE WITH CHANNEL C1/C2 (AS APPLICABLE) IN POSITION TO ENSURE ALIGNMENT OF CLAMPS/CHANNEL. WELD THICKNESS SHALL BE 6MM MINIMUM.
 2. GALVANISATION DAMAGED DUE TO WELDING/CUTTING SHALL BE REPAIRED WITH COLD GALVANISING PAINT.
 3. WHEREVER PORTAL MEMBERS ARE ENCOUNTERED IN THE PATH OF THE TRAYS, THE TRAYS SHALL BE BENT INWARDS SUFFICIENTLY TO CLEAR THE OBSTRUCTION. FOR THIS PURPOSE, THE CANTILEVER ARMS PRECEDING & SUCCEEDING IMMEDIATELY THE PORTAL MEMBERS SHALL BE REPLACED BY SUITABLE LENGTHS OF HORIZONTAL SC1 CHANNEL FIXED TO THE VERTICAL SUPPORT BY MEANS OF ANGLE FITTING LA1. ADDITIONAL SUPPORT ALONG PORTAL MEMBER CAN SIMILARLY BE PROVIDED USING THE SC1 CHANNEL & LA1 COMBINATION.
 4. ALONG OVERHEAD CABLE TRAY ROUTES TRAYS SHALL BE ORIENTED VERTICALLY IN AREAS PRONE TO COAL DUST/ ASH (E.G. BOILER AREA & ESP AREA). ALONG OTHER ROUTES TRAYS SHALL GENERALLY BE ORIENTED HORIZONTALLY. HOWEVER IF SO REQUIRED DUE TO LAYOUT/ AESTHETIC CONSIDERATIONS, TRAYS MAY BE ORIENTED VERTICALLY IN OTHER AREAS ALSO. EXACT ORIENTATION SHALL BE AS PER APPROVED LAYOUT DRAWINGS.
- IV. SUPPORTING ARRANGEMENT IN TRENCHES**
1. CHANNEL SUPPORT SHALL BE PROVIDED AT 2.0M SPACING & SHALL BE FIXED AGAINST TRENCH WALL FOR EVERY TWO TRAYS USING CLAMPS (SPACED AT 600MM MAX.) AS SHOWN.
 2. 2NOS.-M12, ANCHOR BOLTS & 1NO.- SPRING NUT SHALL BE USED WITH EACH CLAMP FOR THE ARRANGEMENT SHOWN.
 3. ARRANGEMENT TR1 & TR2 SHALL BE USED
- V. CHANNEL FRAME WORK FOR RISERS**
- IN ADDITION TO THE SUPPORT FROM GROUND, THE RISER FRAMEWORK SHALL BE CONNECTED TO THE AVAILABLE BUILDING STEEL AT HIGHER ELEVATIONS WHEREVER AVAILABLE. THIS SHALL BE DONE BY USING ANGLE FITTINGS BOLTED TO THE RISER STRUCTURE ON ONE END & WELDED WITH SUITABLE STRUCTURAL STEEL MEMBER ON THE OTHER WHICH IN TURN SHALL BE WELDED TO BUILDING STEEL. IN CASE CONCRETE SURFACE IS AVAILABLE IN PLACE OF STEEL NECESSARY CONNECTION WILL BE REALISED BY USE OF BRACKETS/ CLAMPS FIXED TO CONCRETE SURFACE WITH ANCHOR FASTENERS.
- VI.** CABLE TRAYS SHALL NORMALLY BE FIXED TO CANTILEVER ARMS BY MEANS OF PAN HEAD SCREW & NUT SUPPLIED AS PART OF CANTILEVER ARMS. TRAY CLAMP TC1 SHALL BE USED FOR CLAMPING THE TRAY TO CANTILEVER ARM WHEREVER DUE TO MANUFACTURING/ERECTION/SITE LIMITATIONS, THE CENTER LINES OF CANTILEVER ARM AND THE HOLES IN TRAY BOTTOMS ARE NOT MATCHED.
- VII.** WHEREVER DIFFERENT ALTERNATIVES FOR SIMILAR SUPPORT ARRANGEMENT ARE SHOWN, SITE SHALL DECIDE THE EXACT ALTERNATIVE TO BE USED DEPENDING UPON SITE CONDITIONS.
- VIII.** WHEREVER CANTILEVER ARM CANNOT BE USED FOR DIRECT SUPPORTING OF TRAYS DUE TO LAYOUT CONSTRAINTS (E.G. BENDING OF TRAYS TO AVOID OBSTRUCTION), SUFFICIENT LENGTHS OF SC1 SHALL BE USED AS DIRECT SUPPORT IN PLACE. THESE SHALL BE FIXED BY MEANS OF ANGLE FITTING LA1.
- IX.** BEAM CLAMP SHALL BE USED WHEREVER STRUCTURAL BEAM OF SUITABLE SECTION & ORIENTATION IS AVAILABLE.
- X.** FOR INSTALLATION DETAIL TYPE DB3, DB4, DS2, DS4, DS6 & DS8 WHEREVER DISSIMILAR TYPE OF CABLES ARE INSTALLED AT THE SAME LEVEL ON EITHER SIDE OF THE MAIN SUPPORT (e.g. LTP & HTP, LTP & CONTROL, CONTROL & SCREENED CABLE), MINIMUM 300MM OF HORIZONTAL CLEARANCE SHALL BE ENSURED BETWEEN SUCH TRAYS BY USING LOWER SIZE TRAYS.
- XI.** TRAY SUPPORTS SHALL BE PROVIDED @2.0M SPACING FOR HORIZONTAL RUNS AND @1.0M FOR CABLE SHAFTS/ RISERS.



**TITLE: TYPICAL INSTALLATION DETAILS
FOR CABLE TRAY SUPPORT
SYSTEM**

NTPC DOC. NO: 4540-001-215-PVE-C-046

BHEL DRWG NO: PE-DG-497-507-E006

REV.0

SH 37 OF 37

CLAUSE NO.	TECHNICAL REQUIREMENTS	एनटीपीसी NTPC		
10.05.02	Lightning protection System down conductors shall not be connected to other conductors above ground level. Also no intermediate earthing connection shall be made to Surge arrester, Voltage Transformer, earthing leads for which shall be directly connected to rod electrode. Every down conductor shall be provided with a test joint at about 150mm above ground level. The test joint shall be directly connected to the earthing system. The lightning protection system shall not be in direct contact with underground metallic service ducts and cables.			
10.06.00	EQUIPMENT ERECTION NOTES a) All support insulators, circuit breaker interrupters and other fragile equipment shall be handled with cranes with suitable booms and handling capacity. The contractor shall strictly follow manufacturer's recommendations for handling and erection of equipment. b) The slings shall be of sufficient length to avoid any damage to insulator due to excessive swing, scratching by sling ropes etc. Handling equipment, sling ropes etc. should be tested before erection and periodically thereafter for strength. c) Bending of piping should be done by a bending machine and through cold bending only. Bending shall be such that inner diameter of pipe is not reduced. The pipes shall be thoroughly cleaned before installation.			
10.07.00	CABLING			
10.07.01	Cabling shall be on cable racks, in trenches, vertical shafts, excavated trenches for direct burial, pulled through pipes and conduits run clamped on steel structures etc. in accordance with the requirements specified elsewhere in the specification.			
10.07.02	Cables inside the switchyard shall be laid on bolted GI angle supports at 600mm spacing with separate tiers for control and power cables. The GI angles shall be bolted / welded to galvanized insert plates inside RCC trenches.			
10.07.03	Cabling in the control room shall be done on ladder type cable trays with supports at an interval of 2000mm. All interpole cables (both power & control circuit) for equipments shall be laid in cable trenches/G.I. Conduit Pipe of NB 50/100mm which shall be buried in the ground at a depth of 300mm.			
a)	EARTHING NOTES FOR SWITCHYARD			
	GENERAL			
	i) Earthing of operating boxes, cubicles shall be done by 50 X 6 mm GS flat while cable trenches and structure by 75 X 12 mm GS flat. Neutral points of systems of different voltages, metallic enclosures and frame works associated with all current carrying equipments and extraneous metal works associated with electric system shall be connected to a single earthing system unless stipulated otherwise. i. Earthing system installation shall be in strict accordance with the latest editions of Indian Electricity Rules, relevant Indian Standards and Codes of practice and Regulations existing in the locality where the system is installed.			
	b) EARTHING OF GIS			
	i) The grounding system shall be designed and provided as per IEEE 80-2000 and CIGRE 44 to protect operating staff against any hazardous touch voltages and electro-mechanical interferences.			
	ii-) The GIS contractor shall define clearly what constitutes the main grounding bus of the GIS. The GIS contractor must supply, commission the entire grounding work of GIS viz conductor, clamps, joints, bimetallic strips (for connection between different type of earthing materials), operating and safety platforms etc.			
TALCHER THERMAL POWER PROJECT STAGE-III (2X660 MW) EPC PACKAGE		TECHNICAL SPECIFICATION SECTION – VI, PART-B BID DOC. NO -CS-4540-001A-2		SUB-SECTION-B-17 SWITCHYARD Page 33 of 60

SUB-SECTION-B – 10

CABLING EARTHING AND LIGHTNING PROTECTION

CLAUSE NO.	TECHNICAL REQUIREMENTS																																																						
1.00.00	CODES AND STANDARDS																																																						
1.01.00	<p>All standards, specifications and codes of practice referred to herein shall be the latest editions including all applicable official amendments and revisions as on date of opening of bid. In case of conflict between this specification and those (IS codes, standards, etc.) referred to herein, the former shall prevail. All work shall be carried out as per the following standards/ codes as applicable .</p> <table><tr><td>IS:513</td><td>Cold rolled low carbon steel sheets and strips.</td></tr><tr><td>IS:802</td><td>Code of practice for the use of Structural Steel in Overhead Transmission Line Towers.</td></tr><tr><td>IS:1079</td><td>Hot Rolled carbon steel sheet & strips</td></tr><tr><td>IS:1239</td><td>Mild steel tubes, tubulars and other wrought steel fittings</td></tr><tr><td>IS:1255</td><td>Code of practice for installation and maintenance of power cables upto and including 33 KV rating</td></tr><tr><td>IS:1367 Part-13</td><td>Technical supply conditions for threaded Steel fasteners. (Hot dip galvanized coatings on threaded fasteners).</td></tr><tr><td>IS:2147</td><td>Degree of protection provided by enclosures for low voltage switchgear and control gear</td></tr><tr><td>IS:2309</td><td>Code of Practice for the protection of building and allied structures against lightning.</td></tr><tr><td>IS:2629</td><td>Recommended practice for hot dip galvanising of iron & steel</td></tr><tr><td>IS:2633</td><td>Method for testing uniformity of coating on zinc coated articles.</td></tr><tr><td>IS:3043</td><td>Code of practice for Earthing</td></tr><tr><td>IS:3063</td><td>Fasteners single coil rectangular section spring washers.</td></tr><tr><td>IS:6745</td><td>Methods for determination of mass of zinc coating on zinc coated iron & steel articles.</td></tr><tr><td>IS:8308</td><td>Compression type tubular in- line connectors for aluminium conductors of insulated cables</td></tr><tr><td>IS:8309</td><td>Compression type tubular terminal ends for aluminium conductors of insulated cables.</td></tr><tr><td>IS:9537</td><td>Conduits for electrical installation.</td></tr><tr><td>IS:9595</td><td>Metal - arc welding of carbon and carbon manganese steels - recommendations.</td></tr><tr><td>IS:13573</td><td>Joints and terminations for polymeric cables.</td></tr><tr><td>BS:476</td><td>Fire tests on building materials and structures</td></tr><tr><td>IEEE:80</td><td>IEEE guide for safety in AC substation grounding</td></tr><tr><td>IEEE:142</td><td>Grounding of Industrial & commercial power systems</td></tr><tr><td>DIN 46267 (Part-II)</td><td>Non tension proof compression joints for Aluminium conductors.</td></tr><tr><td>DIN 46329</td><td>Cable lugs for compression connections, ring type ,for Aluminium conductors</td></tr><tr><td>BS:6121</td><td>Specification for mechanical Cable glands for elastomers and plastic insulated cables.</td></tr><tr><td></td><td>Indian Electricity Act.</td></tr><tr><td></td><td>Indian Electricity Rules.</td></tr></table>			IS:513	Cold rolled low carbon steel sheets and strips.	IS:802	Code of practice for the use of Structural Steel in Overhead Transmission Line Towers.	IS:1079	Hot Rolled carbon steel sheet & strips	IS:1239	Mild steel tubes, tubulars and other wrought steel fittings	IS:1255	Code of practice for installation and maintenance of power cables upto and including 33 KV rating	IS:1367 Part-13	Technical supply conditions for threaded Steel fasteners. (Hot dip galvanized coatings on threaded fasteners).	IS:2147	Degree of protection provided by enclosures for low voltage switchgear and control gear	IS:2309	Code of Practice for the protection of building and allied structures against lightning.	IS:2629	Recommended practice for hot dip galvanising of iron & steel	IS:2633	Method for testing uniformity of coating on zinc coated articles.	IS:3043	Code of practice for Earthing	IS:3063	Fasteners single coil rectangular section spring washers.	IS:6745	Methods for determination of mass of zinc coating on zinc coated iron & steel articles.	IS:8308	Compression type tubular in- line connectors for aluminium conductors of insulated cables	IS:8309	Compression type tubular terminal ends for aluminium conductors of insulated cables.	IS:9537	Conduits for electrical installation.	IS:9595	Metal - arc welding of carbon and carbon manganese steels - recommendations.	IS:13573	Joints and terminations for polymeric cables.	BS:476	Fire tests on building materials and structures	IEEE:80	IEEE guide for safety in AC substation grounding	IEEE:142	Grounding of Industrial & commercial power systems	DIN 46267 (Part-II)	Non tension proof compression joints for Aluminium conductors.	DIN 46329	Cable lugs for compression connections, ring type ,for Aluminium conductors	BS:6121	Specification for mechanical Cable glands for elastomers and plastic insulated cables.		Indian Electricity Act.		Indian Electricity Rules.
IS:513	Cold rolled low carbon steel sheets and strips.																																																						
IS:802	Code of practice for the use of Structural Steel in Overhead Transmission Line Towers.																																																						
IS:1079	Hot Rolled carbon steel sheet & strips																																																						
IS:1239	Mild steel tubes, tubulars and other wrought steel fittings																																																						
IS:1255	Code of practice for installation and maintenance of power cables upto and including 33 KV rating																																																						
IS:1367 Part-13	Technical supply conditions for threaded Steel fasteners. (Hot dip galvanized coatings on threaded fasteners).																																																						
IS:2147	Degree of protection provided by enclosures for low voltage switchgear and control gear																																																						
IS:2309	Code of Practice for the protection of building and allied structures against lightning.																																																						
IS:2629	Recommended practice for hot dip galvanising of iron & steel																																																						
IS:2633	Method for testing uniformity of coating on zinc coated articles.																																																						
IS:3043	Code of practice for Earthing																																																						
IS:3063	Fasteners single coil rectangular section spring washers.																																																						
IS:6745	Methods for determination of mass of zinc coating on zinc coated iron & steel articles.																																																						
IS:8308	Compression type tubular in- line connectors for aluminium conductors of insulated cables																																																						
IS:8309	Compression type tubular terminal ends for aluminium conductors of insulated cables.																																																						
IS:9537	Conduits for electrical installation.																																																						
IS:9595	Metal - arc welding of carbon and carbon manganese steels - recommendations.																																																						
IS:13573	Joints and terminations for polymeric cables.																																																						
BS:476	Fire tests on building materials and structures																																																						
IEEE:80	IEEE guide for safety in AC substation grounding																																																						
IEEE:142	Grounding of Industrial & commercial power systems																																																						
DIN 46267 (Part-II)	Non tension proof compression joints for Aluminium conductors.																																																						
DIN 46329	Cable lugs for compression connections, ring type ,for Aluminium conductors																																																						
BS:6121	Specification for mechanical Cable glands for elastomers and plastic insulated cables.																																																						
	Indian Electricity Act.																																																						
	Indian Electricity Rules.																																																						
1.02.00	<p>Equipment complying with other internationally accepted standards such as IEC, BS, DIN, USA, VDE, NEMA etc. will also be considered if they ensure performance and constructional features equivalent or superior to standards listed above. In such a case, the Bidder shall clearly indicate the standard(s) adopted, furnish a copy in English of the latest revision of the standards alongwith copies of all official amendments and revisions in force as on date of opening of bid and shall clearly bring out the salient features for comparison.</p>																																																						
TALCHER THERMAL POWER PROJECT STAGE-III (2X660 MW) EPC PACKAGE		TECHNICAL SPECIFICATION SECTION – VI, PART-B BID DOC NO : CS-4540-001A-2	SUB SECTION-B-10 CABLING, EARTHING & LIGHTNING PROTECTION																																																				
			Page 1 of 21																																																				

CLAUSE NO.	TECHNICAL REQUIREMENTS	
2.00.00	DESIGN AND CONSTRUCTIONAL FEATURE	
2.01.00	Inter Plant Cabling	
2.01.01	Interplant cabling for main routes shall be laid along overhead trestles/duct banks. Cables from main plant to switchyard control room shall be laid in overhead trestles or duct bank. In case of Duct banks, pull-pits shall be filled with sand and provided with a PCC covering. Directly buried cables, if essential, shall not have concentration of more than 4 cables in one route. Cables crossing Railway line (if applicable) shall be laid underground through nearest culvert. Necessary statutory clearance if required shall be taken by Bidder. All HT, LT and control cable shall be armoured.	
2.01.02	Transformer yard In transformer yard cables shall be laid in overhead trestle. The main cable routes coming out from Main plant building and crossing the Transformer yard shall be laid in overhead trestles. In transformer yard, trestle height for rail/road crossing shall be suitable for movement of Generator Transformer with bushing.	
2.01.03	Trenches PCC flooring of built up trenches shall be sloped for effective drainage with sump pits and sump pumps.	
2.01.04	No sub zero level cable vault/trenches shall be provided below control building/switchgear rooms in main plant.	
2.01.05	Cable Vault The cable vault/ / cable spreader room space below the HT / LT switchgear room, Control Rooms, unit control equipment room, Programmer room, UPS, Charger & Battery Rooms, shall have 800 mm wide and 2.1 m high movement passage all around the cable trays in the cable vault/ cable spreader room for easy laying/maintenance of cables Cable vaults shall be provided with adequate drainage facilities for drainage of fire water. Each cable vault should have at least two doors. Exit signs shall be provided near doors for personnel escape in case of emergency	
2.01.06	Boiler Area Cable trays in boiler & ESP area shall be supported from the boiler and ESP structures. The same shall be coordinated with SG/ESP contractor. Cable trays in these areas shall be in vertical formation to avoid dust accumulation. No cable trenches shall be provided in boiler/ESP area.	
2.01.07	Two separate cable routes shall be provided for cable routing of working and standby drives or different set/group (say 50% capacity) of auxiliaries.	
2.01.08	OffSite Area For feeder in bidder's scope for offsite areas, overhead cable tray arrangement shall be followed. However cable trenches/slit may also be acceptable, for some areas, if found to be required during detailed engineering. Cable trenches provided shall be separated from fuel oil area to avoid oil accumulation.	
2.01.09	The cable slits to be used for motor/equipment power/control supply shall be sand filled & covered with PCC after cabling.	
2.01.10	Sizing criteria, derating factors for the cables shall be met as per respective chapters. However for the power cables, the minimum conductor size shall be 6 sq.mm. for aluminium conductor and 2.5 sq.mm. for copper conductor cable.	
TALCHER THERMAL POWER PROJECT STAGE-III (2X660 MW) EPC PACKAGE	TECHNICAL SPECIFICATION SECTION – VI, PART-B BID DOC NO : CS-4540-001A-2	SUB SECTION-B-10 CABLING, EARTHING & LIGHTNING PROTECTION Page 2 of 21

CLAUSE NO.	TECHNICAL REQUIREMENTS	
2.01.11	<p>Conscious exceptions to the above guidelines may be accepted under special conditions but suitable measures should be taken at such location to:</p> <ul style="list-style-type: none"> • Meet all safety requirements • Safeguard against fire hazards, mechanical damage, flooding of water, oil accumulation, electrical faults/interferences, etc 	
3.00.00	EQUIPMENT DESCRIPTION	
3.01.00	Cable trays, Fittings & Accessories	
3.01.01	Cable trays shall be ladder/perforated type as specified complete with matching fittings (like brackets, elbows, bends, reducers, tees, crosses, etc.) accessories (like side coupler plates, etc. and hardware (like bolts, nuts, washers, G.I. strap, hook etc.) as required. Cable tray shall be ladder type for power & control cables and perforated for instrumentation cables.	
3.01.02	Cable trays, fittings and accessories shall be fabricated out of rolled mild steel sheets free from flaws such as laminations, rolling marks, pitting etc. These (including hardware) shall be hot dip galvanized as per Clause No. 3.13.00 of this chapter.	
3.01.03	Cable trays shall have standard width of 150 mm, 300 mm & 600 mm and standard lengths of 2.5 metre. Thickness of mild steel sheets used for fabrication of cable trays and fittings shall be 2 mm. The thickness of side coupler plates shall be 3 mm.	
3.01.04	Cable troughs shall be required for branching out few cables from main cable route. These shall be U-shaped, fabricated of mild steel sheets of thickness 2 mm and shall be hot dip galvanised as per Clause No. 3.13.00 of this chapter. Troughs shall be standard width of 50 mm & 75 mm with depth of 25 mm.	
3.01.05	The tolerance for cable tray and accessories shall be as per IS 2102 (Part-1). Tolerance Class: - Coarse	
3.02.00	Support System for Cable Trays	
3.02.01	Cable tray support system shall be pre-fabricated out of single sheet as per enclosed tender drawings.	
3.02.02	<p>Support system for cable trays shall essentially comprise of the two components i.e. main support channel and cantilever arms. The main support channel shall be of two types : (i) C1:- having provision of supporting cable trays on one side and (ii) C2:-having provision of supporting cable trays on both sides. The support system shall be the type described hereunder</p> <ol style="list-style-type: none"> Cable supporting steel work for cable racks/cables shall comprise of various channel sections, cantilever arms, various brackets, clamps, floor plates, all hardwares such as lock washers, hexagon nuts, hexagon head bolt, support hooks, stud nuts, hexagon head screw, channel nut, channel nut with springs, fixing studs, etc. The system shall be designed such that it allows easy assembly at site by using bolting. All cable supporting steel work, hardwares fittings and accessories shall be prefabricated factory galvanised. The main support and cantilever arms shall be fixed at site using necessary brackets, clamps, fittings, bolts, nuts and other hardware etc. to form various arrangements required to support the cable trays. Welding of the components shall not be allowed. However, welding of the bracket (to which the main support channel is bolted) to the overhead beams, structural steel, insert plates or reinforcement bars will be permitted. Any cutting or welding of the galvanised surface shall be brushed and red lead primer, oil primer & aluminium paint shall be applied 	
TALCHER THERMAL POWER PROJECT STAGE-III (2X660 MW) EPC PACKAGE	TECHNICAL SPECIFICATION SECTION – VI, PART-B BID DOC NO : CS-4540-001A-2	SUB SECTION-B-10 CABLING, EARTHING & LIGHTNING PROTECTION Page 3 of 21

CLAUSE NO.	TECHNICAL REQUIREMENTS	
	<p>d. All steel components, accessories, fittings and hardware shall be hot dip galvanised after completing welding, cutting, drilling and other machining operation.</p> <p>e. The typical arrangement of flexible support system is shown in the enclosed drawings and described briefly below: The main support channel and cantilever arms shall be fabricated out of 2.5 thick rolled steel sheet conforming to IS 1079.</p> <p>f. Cantilever arms of 320 mm, 620mm and 750 mm in length are required, and shall be as shown in the enclosed drawing. The arm portion shall be suitable for assembling the complete arm assembly on to component constructed of standard channel section. The back plate shall allow sufficient clearance for fixing bolt to be tightened with tray in position.</p> <p>g. Support system shall be able to withstand</p> <ul style="list-style-type: none"> • weight of the cable trays • weight of the cables (75 Kg/Metre run of each cable tray) • Concentrated load of 75 Kg between every support span. • Factor of safety of minimum 1.5 shall be considered. 	
3.02.03	The size of structural steel members or thickness of sheet steel of main support channel and cantilever arms and other accessories as indicated above or in the enclosed drawings are indicative only. Nevertheless, the support system shall be designed by the bidder to fully meet the requirements of type tests as specified. In case the system fails in the tests, the components design modification shall be done by the Bidder without any additional cost to the Employer. The bidder shall submit the detailed drawings of the system offered by him alongwith the bid.	
3.02.04	Four legged structure shall be provided wherever there is change in elevation and change in direction	
3.02.05	<p>FOR COAL HANDLING PLANT/FGD PLANT/ ESP AREA THE FOLLOWING SHALL ALSO BE APPLICABLE:</p> <p>a) All overhead cable routes shall be along the route of the conveyor gallery on separate supporting structures and cables shall be laid in vertical trays. The bottom of the steel shall be such that the existing facilities, movement of trucks/human beings etc. does not get affected. The cable trestle shall have a minimum 600mm clear walk way and shall have maintenance platforms as required. The bottom of the steel supporting structure shall be generally at 3.0M above the grade level except for rail/road crossings where it shall be at 8.0M above grade level. Tap offs from the overhead cable trestle can be through shallow trenches with prior approval of the Employer. Directly buried cable, if essential, shall not have concentration of more than 4 cables on one route.</p> <p>b) Cable trenches shall be provided only in Switchgear/MCC rooms.</p> <p>c) Cables shall not be routed through the conveyor galleries except for the equipment located in the conveyor galleries for a particular conveyor i.e. protection switches, receptacles etc.</p> <p>d) Cables for PCS and BSS shall be routed along the conveyors through GI conduits.</p>	
3.03.00	Pipes, Fittings & Accessories	
3.03.01	Pipes offered shall be complete with fittings and accessories (like tees, elbows, bends, check nuts, bushings, reducers, enlargers, coupling caps, nipples etc.) The size of the pipe shall be selected on the basis of maximum 40% fill criteria	
TALCHER THERMAL POWER PROJECT STAGE-III (2X660 MW) EPC PACKAGE	TECHNICAL SPECIFICATION SECTION – VI, PART-B BID DOC NO : CS-4540-001A-2	SUB SECTION-B-10 CABLING, EARTHING & LIGHTNING PROTECTION Page 4 of 21

CLAUSE NO.	TECHNICAL REQUIREMENTS	
3.03.02	GI Pipes shall be of medium duty as per IS: 1239	
3.03.03	Duct banks shall be High Density PE pipes encased in PCC (10% spare of each size, subject to minimum one) with suitable water-proof manholes.	
3.03.04	Hume pipes shall be NP3 type as per IS 458.	
3.03.05	TERNE Coated Flexible Steel Conduits shall be water proof and rust proof made of heat resistant lead coated steel. Conduit diameter shall be uniform throughout its length. Internal surface of the conduit shall be free from burrs and sharp edges. Conduits shall be complete with necessary accessories for proper termination of the conduit with junction boxes and lighting fixtures	
3.03.06	HDPE pipes and conduits shall be PE-80, PN-10 type as per IS 4984/IS 8008 part-I.	
3.04.00	Junction Boxes	
3.04.01	<p>Junction box shall be made of Fire retardant material. Material of JB shall be Thermoplastic or thermosetting or FRP type. The box shall be provided with the terminal blocks, mounting bracket and screws etc. The cable entry shall be through galvanized steel conduits of suitable diameter. The JB shall have suitable for installing glands of suitable size on the bottom of the box. The JB shall be suitable for surface mounting on ceiling/structures. The JB shall be of grey color RAL 7035. All the metal parts shall be corrosion protected. Junction box surface should be such that it is free from crazings, blisterings, wrinkling, colour blots/striations. There should not be any mending or repair of surface. JB's will be provided with captive screws so that screws don't fall off when cover is opened. JB's mounting brackets should be of powder coated MS. Type test reports for the following tests shall be furnished:-</p> <p>(a) Impact resistance for impact energy of 2 Joules (IK07) as per BS EN50102</p> <p>(b) Thermal ageing at 70deg C for 96 hours as per IEC60068-2-2Bb.</p> <p>(c) Class of protection shall be IP 55.</p> <p>(d) HV test.</p>	
3.04.02	Terminal blocks shall be 1100V grade, of suitable current rating, made up of unbreakable polyamide 6.6 grade. The terminals shall be screw type or screw less (spring loaded) / cage clamp type with lugs. Marking on terminal strips shall correspond to the terminal numbering in wiring diagrams. All metal parts shall be of non ferrous material. In case of screw type terminals the screw shall be captive, preferably with screw locking design. All terminal blocks shall be suitable for terminating on each side the required cables/wire size. All internal wiring shall be of cu. Conductor PVC wire.	
3.05.00	Terminations & Straight Through Joints	
3.05.01	<p>Termination and jointing kits for 33kV, 11 kV, 6.6 KV and 3.3 kV grade XLPE insulated cables shall be of proven design and make which have already been extensively used and type tested. Termination kits and jointing kits shall be Pre-moulded type or heat shrinkable type. Further Cold shrinkable type termination and jointing kits are also acceptable. The Cold shrinkable type kits shall be type tested as per relevant standards. Calculation to withstand the required fault level shall also be furnished in case of cold shrinkable type kits. 33 kV, 11 kV, 6.6 KV and 3.3kV grade joints and terminations shall be type tested and Type test reports as per IS:13573 Part II and IEC60502 shall be furnished. Also, heat shrink material shall comply with requirements of ESI 09-13 (external tests). Critical components used in cable accessories shall be of tested and proven quality as per relevant product specification/ESI specification. Cable joints and terminations should be with FRLS properties as per IEC 60754 1&2. Kit contents shall be supplied from the same source as were used for type testing. The kit shall be complete with the tinned copper solderless</p>	
TALCHER THERMAL POWER PROJECT STAGE-III (2X660 MW) EPC PACKAGE	TECHNICAL SPECIFICATION SECTION – VI, PART-B BID DOC NO : CS-4540-001A-2	SUB SECTION-B-10 CABLING, EARTHING & LIGHTNING PROTECTION Page 5 of 21

CLAUSE NO.	TECHNICAL REQUIREMENTS	
	<p>crimping type cable lugs & ferrule or mechanical connectors (wherein bolts are tightened that shear off at an appropriate torque) as per DIN standard suitable for aluminium compacted conductor cables.</p> <p>3.05.02 Straight through joint and termination shall be capable of withstanding the fault level of 21 KA for 0.12 Sec. with dynamic peak of 52 KA for 33 KV system & of 40 kA for 0.12 sec with a dynamic peak of 100 kA for 11 kV, 6.6 KV & 3.3 KV system. Straight through joints shall have provisions for shield connection and earthing wherever required and complete with all accessories and consumables suitable for storage without deterioration at a temperature of 50 deg. C with shelf life of more than five years. 1.1 kV grade straight through joints shall also be of proven design</p> <p>3.05.03 1.1 KV grade Straight Through Joint shall be of proven design.</p> <p>3.06.00 Cable glands</p> <p>3.06.01 Cable shall be terminated using double compression type cable glands. Testing requirements of Cable glands shall conform to BS:6121 and gland shall be of robust construction capable of clamping cable and cable armour (for armoured cables) firmly without injury to insulation. Cable glands shall be made of heavy duty brass machine finished and nickel chrome plated. Thickness of plating shall not be less than 10 micron. All washers and hardware shall also be made of brass with nickel chrome plating. Rubber components shall be of neoprene or better synthetic material and of tested quality. Cable glands shall be suitable for the sizes of cable supplied/erected.</p> <p>3.07.00 Cable lugs/ferrules</p> <p>3.07.01 Cable lugs/ferrules shall be solderless crimping type suitable for power and control cables as per the DIN 46239. Aluminium solderless crimping lugs/ ferrules shall be used for Aluminium cables and Copper lugs/ferrules shall be used for Copper cables. Bimetallic washers or bimetallic type lugs shall be used for bimetallic connections.</p> <p>Crimping tool for crimping (from 1.5sqmm cable to 630sqmm cables) above mentioned lugs shall be of Hexagonal Type crimp profile, with suitable die of crimp match code.</p> <p>Characteristics of crimping tool:</p> <ol style="list-style-type: none"> 1) To should generate enough pressure to pass pull out test as per IEC 61238 1. Relevant type test to be produced for the sizes specified in the tender. 2) Tool die shall be replaceable for assorted sizes and crimp code to be mentioned on both part the die. 3) Tool should be compliant of testing according to IEC, UL and GS standards. <p>Tool shall have features such as:</p> <ul style="list-style-type: none"> • Auto retraction system • Manual retraction stop. • Feedback signals for improper pressure • Better battery capacity and with status display • Flexible and rotating head for easy crimping. <p>3.08.00 Trefoil clamps</p> <p>3.08.01 Trefoil clamps for single core cables shall be pressure die cast aluminum or fibre glass or nylon and shall include necessary fixing accessories like G.I. nuts, bolts, washers, etc. Trefoil clamps shall have adequate mechanical strength, when installed at 1 mtr intervals, to withstand the forces generated by the peak value of maximum system short circuit current.</p> <p>3.09.00 Cable Clamps & Ties</p> <p>3.09.01 The cable clamps/ties required to clamp multicore cables shall be of SS 316 material, 12mm wide, polyester coated ladder lock type. The clamps/ties shall have self locking arrangement</p>	
TALCHER THERMAL POWER PROJECT STAGE-III (2X660 MW) EPC PACKAGE	TECHNICAL SPECIFICATION SECTION – VI, PART-B BID DOC NO : CS-4540-001A-2	SUB SECTION-B-10 CABLING, EARTHING & LIGHTNING PROTECTION Page 6 of 21

CLAUSE NO.	TECHNICAL REQUIREMENTS	
	<p>& shall have sufficient strength. The cable clamps/ties shall be supplied in finished individual pieces of suitable length to meet the site requirements.</p> <p>3.10.00 Receptacles</p> <p>3.10.01 Receptacles boxes shall be fabricated out of MS sheet of 2mm thickness and hot dipped gavanised or of die cast aluminium alloy of thickness not less than 2.5 mm. The boxes shall be provided with two nos. earthing terminals, gasket to achieve IP55 degree of protection, terminal blocks for loop in-loop out for cable of specified sizes, mounting brackets suitable for surface mounting on wall/column/structure, gland plate etc. The ON-OFF switch shall be rotary type heavy duty, double break, AC23 category, suitable for AC supply. Plug and Socket shall be shrouded Die cast aluminium. Socket shall be provided with lid safety cover. Robust mechanical interlock shall be provided such that the switch can be put ON only when the plug is fully engaged and plug can be withdrawn only when the switch is in OFF position. Also cover can be opened only when the switch is in OFF position. Wiring shall be carried out with 1100 V grade PVC insulated stranded aluminium/copper wire of adequate size. The Terminal blocks shall be of 1100 V grade. The Terminal blocks shall be of 1100 V grade made up of unbreakable polyimide 6.6 grade with adequate current rating and size. The welding receptacles shall be provided with RCCB/RCD of 30mA sensitivity having facility for manual testing/checking of operation of RCCB/RCD. Location and Minimum no of RC type receptacle TG and SG area shall be provided as per Annex I attached.</p> <p>3.11.00 Cable Drum Lifting Jack</p> <p>The jack for cable drum lifting shall be of screw type with 10 ton capacity. The cable drum jacks shall be manufactured from fabricated steel. The spindles supplied with the cable drum jack shall be manufactured using BSEN 24 grade steel bar with locking collars. Jack nests shall be of SG cast steel. Cable drum jack supplied shall have undergone load testing and reports for the same shall be submitted. At least Two Nos. of jacks shall be supplied for NTPC use. Contractor has to make arrangements for his own jacks for cable reeling/unreeling under his scope of installation.</p> <p>3.12.00 Galvanising</p> <p>3.12.01 Galvanising of steel components and accessories shall conform to IS:2629 , IS4759 & IS:2633. Additionally galvanising shall be uniform, clean smooth, continuous and free from acid spots.</p> <p>3.12.02 The amount of zinc deposit over threaded portion of bolts, nuts, screws and washers shall be as per IS:1367 . The removal of extra zinc on threaded portion of components shall be carefully done to ensure that the threads shall have the required zinc coating on them as specified</p> <p>3.13.00 Welding</p> <p>3.13.01 The welding shall be carried out in accordance with IS:9595. All welding procedures and welders qualification shall also be followed strictly in line with IS:9595</p> <p>4.00.00 INSTALLATION</p> <p>4.01.00 Cable tray and Support System Installation</p> <p>4.01.01 Cables shall run in cable trays mounted horizontally or vertically on cable tray support system which in turn shall be supported from floor, ceiling, overhead structures, trestles, pipe racks, trenches or other building structures.</p> <p>4.01.02 Horizontally running cable trays shall be clamped by bolting to cantilever arms and vertically running cable trays shall be bolted to main support channel by suitable bracket/clamps on both top and bottom side rails at an interval of 2000 mm in general. For vertical cable risers/shafts cable trays shall be supported at an interval of 1000mm in general. Fixing of cable trays to cantilever arms or main support channel by welding shall not be accepted.</p>	
TALCHER THERMAL POWER PROJECT STAGE-III (2X660 MW) EPC PACKAGE	TECHNICAL SPECIFICATION SECTION – VI, PART-B BID DOC NO : CS-4540-001A-2	SUB SECTION-B-10 CABLING, EARTHING & LIGHTNING PROTECTION Page 7 of 21

CLAUSE NO.	TECHNICAL REQUIREMENTS												
	<p>Cable tray installation shall generally be carried out as per the approved guidelines/ drawings. Vendor shall design the support system along with tray, spacing etc in line with tray loadings/drawings.</p>												
4.01.03	<p>The cantilever arms shall be positioned on the main support channel with a minimum vertical spacing of 300 mm unless otherwise indicated.</p>												
4.01.04	<p>The contractor shall fix the brackets/ clamps/ insert plates using anchor fasteners. Minimum size of anchor fasteners shall be M 8 X 50 and material shall be stainless steel grade 316 or better. Anchor fastener shall be fixed as recommended by manufacturer and as approved by site engineer. For brick wall suitable anchor fasteners shall be used as per the recommendations of manufacturer. Make of anchor fasteners subject to QA approval and the same shall be finalized at pre-award stage.</p>												
4.01.05	<p>All cable way sections shall have identification, designations as per cable way layout drawings and painted/stenciled at each end of cable way and where there is a branch connection to another cable way. Minimum height of letter shall be not less than 75 mm. For long lengths of trays, the identification shall be painted at every 10 meter. Risers shall additionally be painted/stenciled with identification numbers at every floor.</p>												
4.01.06	<p>In certain cases it may be necessary to site fabricate portions of trays, supports and other non standard bends where the normal prefabricated trays, supports and accessories may not be suitable. Fabricated sections of trays, supports and accessories to make the installation complete at site shall be neat in appearance and shall match with the prefabricated sections in the dimensions. They shall be applied with one coat of red lead primer, one coat of oil primer followed by two finishing coats of aluminium paint.</p>												
4.01.07	<p>In fire prone areas, like Boiler, TG, fuel oil area and any other strategic location etc, fire retardant paint to be applied after installation cables.</p>												
4.02.00	<p>Conduits/Pipes/Ducts Installation</p>												
4.02.01	<p>The Contractor shall ensure for properly embedding conduit pipe sleeves wherever necessary for cabling work. All openings in the floor/roof/wall / cable tunnel/cable trenches made for conduit installation shall be sealed and made water proof by the Contractor.</p>												
4.02.02	<p>GI pull wire of adequate size shall be laid in all conduits before installation. Metallic conduit runs at termination shall have two lock nuts wherever required for junction boxes etc.</p>												
4.02.03	<p>Conduit runs/sleeves shall be provided with PVC bushings having round edge at each end. All conduits/pipes shall have their ends closed by caps until cables are pulled. After cables are pulled, the ends of conduits/pipes shall be sealed with Glass wool/Cement Mortar/Putty to prevent entrance of moisture and foreign material</p>												
4.02.04	<p>Exposed conduit/pipe shall be adequately supported by racks, clamps, straps or by other approved means. Conduits /pipe support shall be installed square and true to line and grade with an average spacing between the supports as given below, unless specified otherwise</p> <table><tr><td>Conduit /pipe size (dia).</td><td>Spacing</td></tr><tr><td>Upto 40 mm</td><td>1 M</td></tr><tr><td>50 mm</td><td>2.0 M</td></tr><tr><td>65-85 mm</td><td>2.5 M</td></tr><tr><td>100 mm and above</td><td>3.0 M</td></tr></table>			Conduit /pipe size (dia).	Spacing	Upto 40 mm	1 M	50 mm	2.0 M	65-85 mm	2.5 M	100 mm and above	3.0 M
Conduit /pipe size (dia).	Spacing												
Upto 40 mm	1 M												
50 mm	2.0 M												
65-85 mm	2.5 M												
100 mm and above	3.0 M												
4.02.05	<p>For bending of conduits, bending machine shall be arranged at site by the contractor to facilitate cold bending. The bends formed shall be smooth.</p>												
TALCHER THERMAL POWER PROJECT STAGE-III (2X660 MW) EPC PACKAGE	TECHNICAL SPECIFICATION SECTION – VI, PART-B BID DOC NO : CS-4540-001A-2	SUB SECTION-B-10 CABLING, EARTHING & LIGHTNING PROTECTION	Page 8 of 21										

CLAUSE NO.	TECHNICAL REQUIREMENTS	
4.03.00	Junction Boxes Installation	
4.03.01	Junction boxes shall be mounted at a height of 1200mm above floor level or as specified in the drawings and shall be adequately supported/mounted on masonry wall by means of anchor fasteners/ expandable bolts or shall be mounted on an angle, plate or other structural supports fixed to floor, wall, ceiling or equipment foundations.	
4.04.00	Cable Installation	
4.04.01	Cable installation shall be carried out as per IS:1255 and other applicable standards.	
4.04.02	For Cable unloading, pulling etc following guidelines shall be followed in general:	
	a) Cable drums shall be unloaded, handled and stored in an approved manner on hard and well drained surface so that they may not sink. In no case shall be drum be stored flat i.e. with flange horizontal. Rolling of drums shall be avoided as far as possible. For short distances, the drums may be rolled provided they are rolled slowly and in proper direction as marked on the drum. In absence of any indication, the drums may be rolled in the same direction as it was rolled during taking up the cables. For unreeling the cable, the drum shall be mounted on suitable jacks or on cable wheels and shall be rolled slowly so that cable comes out over the drum and not from below. All possible care shall be taken during unreeling and laying to avoid damage due to twist, kink or sharp bends. Cable ends shall be provided with sealed plastic caps to prevent damage and ingress of moisture. b) While laying cable, ground rollers shall be used at every 2 meter interval to avoid cable touching ground. The cables shall be pushed over the rollers by a gang of people positioned in between the rollers. Cables shall not be pulled from the end without having intermediate pushing arrangements. Pulling tension shall not exceed the values recommended by cable manufacturer. Selection of cable drums for each run shall be so planned so as to avoid using straight through joints. Care should be taken while laying the cables so as to avoid damage to cables. If any particular cable is damaged, the same shall be repaired or changed to the satisfaction of Project Manager.	
4.04.03	Cables shall be laid on cable trays strictly in line with cable schedule	
4.04.04	Power and control cables shall be laid on separate tiers inline with the approved guidelines/drawings. The laying of different voltage grade cables shall be on different tiers according to the voltage grade of the cables. In horizontal tray stacks, H.T. cables shall be laid on top most tier and cables of subsequent lower voltage grades on lower tiers of trays. Single core cable in trefoil formation shall be laid with a distance of four times the diameter of cable between trefoil center lines and clamped at every one metre. All multicore cables shall be laid in touching formation. Power and control cables shall be secured fixed to trays/support with cable clamps/ties with self locking arrangement. For horizontal trays arrangements, multicore power cables and control cables shall be secured at every five meter interval. For vertical tray arrangement, individual multicore power cables and control cables shall be secured at every one meter. After completion of cable laying work in the particular vertical tray, all the control cables shall be binded to trays/supports by cable clamps/ties with self locking arrangement at every five meter interval and at every bend. Fibre Optical cable shall be laid in trenches/trays or as decided by Employer.	
4.04.05	Bending radii for cables shall be as per manufacturer's recommendations and IS:1255.	
4.04.06	Where cables cross roads/rail tracks, the cables shall be laid in hume pipe/ HDPE pipe.	
4.04.07	No joints shall be allowed in trip circuits, protection circuits and CT/PT circuits. Also joints in critical equipment in main plant area shall not be permitted. Vendor shall identify and accordingly procure the cable drum length.	
TALCHER THERMAL POWER PROJECT STAGE-III (2X660 MW) EPC PACKAGE	TECHNICAL SPECIFICATION SECTION – VI, PART-B BID DOC NO : CS-4540-001A-2	SUB SECTION-B-10 CABLING, EARTHING & LIGHTNING PROTECTION Page 9 of 21

CLAUSE NO.	TECHNICAL REQUIREMENTS												
4.04.08	In each cable run some extra length shall be kept at suitable point to enable one LT/two HT straight through joints to made, should the cable develop fault at a later stage. Control cable termination inside equipment enclosure shall have sufficient lengths so that shifting of termination in terminal blocks can be done without requiring any splicing.												
4.04.09	Wherever few cables are branching out from main trunk route troughs shall be used.												
4.04.10	Wind loading shall be considered for designing support as well Cable trays wherever required.												
4.04.11	Where there is a considerable risk of steam, hot oil or mechanical damage cable routes shall be protected by barriers or enclosures.												
4.04.12	The installation work shall be carried out in a neat workman like manner & areas of work shall be cleaned of all scraps, water, etc. after the completion of work in each area every day. Contractor shall replace RGC/Steel trench covers after the Installation work in that particular area is completed or when further work is not likely to be taken up for some time.												
4.04.13	Separation At least 300mm clearance shall be provided between: <ul style="list-style-type: none">HT power & LT power cables,LT power & LT control/instrumentation cables,												
4.04.14	Segregation <ul style="list-style-type: none">1) Segregation means physical isolation to prevent fire jumping.2) All cables associated with the unit shall be segregated from cables of other units.3) Interplant cables of station auxiliaries and unit critical drives shall be segregated in such a way that not more than half of the drives are lost in case of single incident of fire. Power and control cables for AC drives and corresponding emergency AC or DC drives shall be laid in segregated routes. Cable routes for one set of auxiliaries of same unit shall be segregated from the other set.4) In switchyard, control cables of each bay shall be laid on separate racks/trays.												
4.04.15	Minimum number of spare cores required to be left for interconnection in control cables shall be as follows: Minimum number of spare cores required to be left for interconnection in control cables shall be as follows: <table><tr><th>No. of cores in cable</th><th>No. of spare cores</th></tr><tr><td>2C,3C</td><td>NIL</td></tr><tr><td>5C</td><td>1</td></tr><tr><td>7C-10C</td><td>2</td></tr><tr><td>14C and above</td><td>3</td></tr></table>	No. of cores in cable	No. of spare cores	2C,3C	NIL	5C	1	7C-10C	2	14C and above	3		
No. of cores in cable	No. of spare cores												
2C,3C	NIL												
5C	1												
7C-10C	2												
14C and above	3												
4.04.16	Directly Buried Cables <ul style="list-style-type: none">a) Cable trenches shall be constructed for directly buried cables. Construction of cable trench for cables shall include excavation, preparation of sieved sand bedding, riddled soil cover, supply and installation of brick or concrete protective covers, back filling and compacting, supply and installation of route markers and joint markers. Laying of cables and providing protective covering shall be as per IS:1255 and the enclosed drawings showing cabling details.b) RCC cable route and RCC joint markers shall be provided wherever required. The voltage grade of the higher voltage cables in route shall be engraved on the marker. Location of underground cable joints shall be indicated with cable marker with an additional inscription "Cable Joint". The marker shall project 150 mm above ground												
TALCHER THERMAL POWER PROJECT STAGE-III (2X660 MW) EPC PACKAGE		TECHNICAL SPECIFICATION SECTION – VI, PART-B BID DOC NO : CS-4540-001A-2	SUB SECTION-B-10 CABLING, EARTHING & LIGHTNING PROTECTION										
			Page 10 of 21										

CLAUSE NO.	TECHNICAL REQUIREMENTS	
	<p>and shall be spaced at an interval of 30 meters and at every change in direction. They shall be located on both sides of road crossings and drain crossings. Top of cable marker/joint marker shall be sloped to avoid accumulation of water/dust on marker.</p> <p>4.04.17 Cable tags shall be provided on all cables at each end (just before entering the equipment enclosure), on both sides of a wall or floor crossing, on each duct/conduit entry, and at every 20 meters in cable tray/trench runs. Cable tags shall also be provided inside the switchgear, motor control centers, control and relay panels etc. where a number of cables enter together through a gland plate. Cable tag shall be of rectangular shape for power cables and control cables. Cable tag shall be of 2 mm thick aluminum with number punched on it and securely attached to the cable by not less than two turns of 20 SWG GI wire conforming to IS:280. Alternatively, the Contractor may also provide cable tags made of nylon, cable marking ties with cable number heat stamped on the cable tags. The cable tag requirements mentioned above shall prevail over Tag requirements mentioned elsewhere in this document for HT power, LT power & control cables.</p> <p>4.04.18 While crossing the floors, unarmoured cables shall be protected in conduits upto a height of 500 mm from floor level if not laid in tray.</p> <p>4.05.00 Cable Terminations & Connections</p> <p>4.05.01 The termination and connection of cables shall be done strictly in accordance with cable termination kit manufacturer" instructions, drawings and/or as directed by Project Manager. Cable jointer shall be qualified to carryout satisfactory cable jointing/termination. Contractor shall furnish for review documentary evidence/experience reports of the jointers to be deployed at site.</p> <p>4.05.02 Work shall include all clamps, fittings etc. and clamping, fitting, fixing, plumbing, soldering, drilling, cutting, taping, preparation of cable end, crimping of lug, insulated sleeving over control cable lugs, heat shrinking (where applicable), connecting to cable terminal, shorting and grounding as required to complete the job to the satisfaction of the Project Manager.</p> <p>4.05.03 The equipment will be generally provided with undrilled gland plates for cables/conduit entry. The Contractor shall be responsible for punching of gland plates, painting and touching up. Holes shall not be made by gas cutting. The holes shall be true in shape. All cable entry points shall be sealed and made vermin and dust proof. Unused openings shall be effectively sealed by 2mm thick aluminium sheets.</p> <p>4.05.04 Control cable cores entering control panel/switchgear/MCC/miscellaneous panels shall be neatly bunched, clamped and tied with self locking type nylon cable ties with de interlocking facility to keep them in position.</p> <p>4.05.05 All the cores of the control cable to be terminated shall have identification by providing ferrules at either end of the core, each ferrule shall be indelible, printed single tube ferrule and shall include the complete wire number and TB number as per the drawings. The ferrule shall fit tightly on the core. Spare cores shall have similar ferrules with suffix sp1, sp2, etc along with cable numbers and coiled up after end sealing.</p> <p>4.05.06 All cable terminations shall be appropriately tightened to ensure secure and reliable connections.</p> <p>5.00.00 EARTHING SYSTEM</p> <p>5.01.00 Earthing system shall be in strict accordance with IS:3043 and Indian Electricity Rules/Acts</p>	
TALCHER THERMAL POWER PROJECT STAGE-III (2X660 MW) EPC PACKAGE	TECHNICAL SPECIFICATION SECTION – VI, PART-B BID DOC NO : CS-4540-001A-2	SUB SECTION-B-10 CABLING, EARTHING & LIGHTNING PROTECTION Page 11 of 21

CLAUSE NO.	TECHNICAL REQUIREMENTS		
	<p>The earthing system shall be designed for a life expectancy of at least forty (40) years, for a system fault current of 63 kA for 1.0 sec. The minimum rate of corrosion of steel for selection of earthing conductor shall be 0.12mm per year.</p> <p>Earthing system network/earthmat shall be interconnected mesh of mild steel rods buried in ground in the plant. All areas under contractor scope of supply shall be interconnected together by minimum two parallel conductors. The Contractor shall furnish the detailed design and calculations for Employer's approval. Contractor shall obtain all necessary statutory approvals for the system. All the columns shall be earthed by nearby risers and earthmat grid spacing shall be maximum 10 mts. Minimum two nos of risers shall be provided for each equipment in SG area. Separate dedicated riser shall be provided for C&I earthing purpose and also for Lightning down conductor connection purpose. Sufficient nos of risers near the equipment shall be provided as per the system requirement. Ring type earthing around the offsite building shall be provided with interconnection of with main grid at minimum two points.</p>		
5.02.00	The earth conductors shall be free from pitting, laminations, rust, scale and other electrical, mechanical defects		
5.03.00	The material of the earthing conductors shall be as follows:		
	1)	Conductors above ground level and in built up trenches.	- Galvanized steel
	2)	Conductors buried in earth	- Mild steel
	3)	Earth electrodes	- Mild steel rod
5.04.00	The sizes of earthing conductors for various electrical equipments shall be as below:		
	Equipment	Earth conductor buried in earth	Earth conductor above ground level & in built up trenches
	a)	Main earth grid	Min 40 mm dia. MS rod or as per actual calculation whichever is more
	b)	33kV/11kV/6.6kV/3.3 kV/ switchgear equipment and 415V switchgear	65 x 8mm GS flat
	c)	415 V MCC/ Distribution boards / Transformers	50 x 6mm GS flat
	d)	LT Motors above 125 KW	50 x 6mm GS flat
		25 KW to 125 KW	25 x 6mm GS flat
		1KW to 25 KW	25 x 3mm GS flat
		Fractional House power motor	8 SWG GS wire
	e)	Control panel & control desk	25 x 3 mm GS flat
	f)	Push button station / Junction Box	8 SWG GI wire
	g)	Columns, structures, cable trays and bus ducts enclosures	50 x 6mm GS flat
	h)	Crane, rails, rail tracks & other non current carrying metal parts	25 x 6mm GS flat
5.05.00	Metallic frame of all electrical equipment shall be earthed by two separate and distinct connections to earthing system, each of 100% capacity, Crane rails, tracks, metal pipes and conduits shall also be effectively earthed at two points. Steel RCC columns, metallic stairs,		
TALCHER THERMAL POWER PROJECT STAGE-III (2X660 MW) EPC PACKAGE		TECHNICAL SPECIFICATION SECTION – VI, PART-B BID DOC NO : CS-4540-001A-2	SUB SECTION-B-10 CABLING, EARTHING & LIGHTNING PROTECTION Page 12 of 21

CLAUSE NO.	TECHNICAL REQUIREMENTS	
	<p>and rails etc. of the building housing electrical equipment shall be connected to the nearby earthing grid conductor by one earthing ensured by bonding the different sections of hand rails and metallic stairs. Metallic sheaths/screens, and armour of multi-core cables shall be earthed at both ends. Metallic Sheaths and armour of single core cables shall be earthed at switchgear end only unless otherwise approved. Every alternate post of the switchyard fence shall be connected to earthing grid by one GS flat and gates by flexible lead to the earthed post. Railway tracks within the plant area shall be bonded across fish plates and connected to earthing grid at several locations. Portable tools, appliances and welding equipment shall be earthed by flexible insulated cable.</p> <p>5.06.00 Each continuous laid lengths of cable tray shall be earthed at minimum two places by G.S. flats to earthing system, the distance between earthing points shall not exceed 30 meter. Wherever earth mat is not available, necessary connections shall be done by driving an earth electrode in the ground</p> <p>5.07.00 Neutral points of HT transformer shall be earthed through NG resistors. The Contractor shall connect the NGR earthing point to earth electrodes by suitable earth conductors.</p> <p>5.08.00 Neutral connections and metallic conduits/pipes shall not be used for the equipment earthing. Lightning protection system down conductors shall not be connected to other earthing conductors above the ground level.</p> <p>5.09.00 Connections between earth leads and equipment shall normally be of bolted type. Contact surfaces shall be thoroughly cleaned before connections. Equipment bolted connections after being tested and checked shall be painted with anti corrosive paint/compound.</p> <p>5.10.00 Suitable earth risers as approved shall be provided above finished floor/ground level, if the equipment is not available at the time of laying of main earth conductor.</p> <p>5.11.00 Connections between equipment earthing leads and between main earthing conductors shall be of welded type. For rust protection the welds should be treated with red lead compound and afterwards thickly coated with bitumen compound. All welded connections shall be made by electric arc welding.</p> <p>5.12.00 Resistance of the joint shall not be more than the resistance of the equivalent length of conductors.</p> <p>5.13.00 Earthing conductors buried in ground shall be laid minimum 600 mm below grade level unless otherwise indicated in the drawing. Back filling material to be placed over buried conductors shall be free from stones and harmful mixtures. Back filling shall be placed in layers of 150 mm.</p> <p>5.14.00 Earthing conductors embedded in the concrete floor of the building shall have approximately 50 mm concrete cover.</p> <p>5.15.00 A minimum earth coverage of 300 mm shall be provided between earth conductor and the bottom of trench/foundation/underground pipes at crossings. Earthing conductors crossings the road can be installed in pipes. Wherever earthing conductor crosses or runs at less than 300 mm distance along metallic structures such as gas, water, steam pipe lines, steel reinforcement in concrete, it shall be bonded to the same.</p> <p>5.16.00 Earthing conductors along their run on columns, walls, etc. shall be supported by suitable welding / cleating at interval of 1000mm and 750mm respectively.</p> <p>5.17.00 Earth pit shall be of treated type & shall be constructed as per IS:3043. Electrodes shall be embedded below permanent moisture level. Minimum spacing between electrodes shall be 600mm. Earth pits shall be treated with salt and charcoal as per IS:3043. Test links shall be</p>	
TALCHER THERMAL POWER PROJECT STAGE-III (2X660 MW) EPC PACKAGE	TECHNICAL SPECIFICATION SECTION – VI, PART-B BID DOC NO : CS-4540-001A-2	SUB SECTION-B-10 CABLING, EARTHING & LIGHTNING PROTECTION Page 13 of 21

CLAUSE NO.	TECHNICAL REQUIREMENTS		
	provided with bolted arrangement alongwith each earth pit, in order to facilitate measurement of earth resistance as & when required.		
5.18.00	On completion of installation continuity of earth conductors and efficiency of all bonds and joints shall be checked. Earth resistance at earth terminations shall be measured and recorded. All equipment required for testing shall be furnished by contractor.		
5.19.00	Earthing conductor shall be buried at least 2000mm outside the fence of electrical installations. Every alternate post of the fences and all gates shall be connected to earthing grid by one lead.		
5.20.00	Other Requirements of Earthing System:		
	Standard/Code	IEEE 80, IS 3043	
	Earthing System		
	Life expectancy	40 Years	
	System Fault Level	System Fault Level 63 KA for 1 sec	
	Soil resistivity	Actual as per site conditions.	
	Min. Steel corrosion	0.12mm/year	
	Depth of burial of main earth conductor	600mm below grade level; where it crosses trenches, pipes, ducts, tunnels, rail tracks, etc., it shall be at least 300mm below them.	
	Conductor joints	By electric arc welding, with resistance of joint not more than that of the conductor.	
	Welds to be treated with red lead for rust protection and then coated with bitumen compound for corrosion protection.		
	Surface resistivity	-Gravel	3000 ohm-meter
		-Concrete	500 ohm-meter
6.00.00	LIGHTNING PROTECTION SYSTEM		
6.01.01	Lightning protection system shall be in strict accordance with IEC : 62305 and latest IS standards.		
6.01.02	Lightning conductor shall be of 25x6mm GS strip when used above ground level and shall be connected through test link with earth electrode/earthing system		
6.01.03	Lightning system shall comprise of air terminations, down conductors, test links, earth electrode etc. as per approved drawings.		
6.02.00	Down Conductors		
	1.	Down conductors shall be as short and straight as practicable and shall follow a direct path to earth electrode.	
	2.	Each down conductor shall be provided with a test link at 1000 mm above ground level for testing but it shall be in accessible to interference. No connections other than the one direct to an earth electrode shall be made below a test point.	
	3.	All joints in the down conductors shall be welded type.	
	4.	Down conductors shall be cleated on outer side of building wall, at 750 mm interval or welded to outside building columns at 1000 mm interval.	
	5.	Lightning conductor on roof shall not be directly cleated on surface of roof. Supporting blocks of PCC/insulating compound shall be used for conductor fixing at an interval of 1500 mm.	
	6.	All metallic structures within a vicinity of two meters of the conductors shall be bonded to conductors of lightning protection system.	
	7.	Lightning conductors shall not pass through or run inside GI Conduits.	
	8.	Testing link shall be made of galvanized steel of size 25x 6mm.	
	9.	Pulser system for lightning shall not be accepted.	
	10.	Hazardous areas handling inflammable/explosive materials and associated storage areas shall be protected by a system of aerial earths.	
TALCHER THERMAL POWER PROJECT STAGE-III (2X660 MW) EPC PACKAGE		TECHNICAL SPECIFICATION SECTION – VI, PART-B BID DOC NO : CS-4540-001A-2	SUB SECTION-B-10 CABLING, EARTHING & LIGHTNING PROTECTION Page 14 of 21

CLAUSE NO.	TECHNICAL REQUIREMENTS	
<p>7.00.00</p> <p>7.02.00</p> <p>7.02.01</p>	<p>TESTS</p> <p>Type Test reports shall be furnished for the following</p> <p>Type tests on Cable Trays support system</p> <p>a) Test 1A:</p> <p>On main support channel type-C2 for cantilever arms fixed on one side only. A 3.5 meter length of main support channel shall be fixed vertically at each end to a rigid structure as per the fixing arrangement as shown in the enclosed drawing. Eight (8) nos. 750 mm cantilever arms shall be fixed to the main channel and each arm shall be loaded over the outboard 600 mm with a uniform working load of 100 kg. Subsequently a point load of 100 kg shall be applied on arm 2. A uniform proof load on all the arms equal to twice the working load shall be then be applied. Deflections shall be measured at the points shown in the enclosed drawings and at the following load intervals:</p> <ul style="list-style-type: none"> i) Working load ii) Working load + point load iii) Off load iv) Proof load + point load v) Off load <p>The deflection measured at working loads shall not exceed 16mm. The permanent deflection after removing the combination of working load and point load shall not exceed 10 mm at the arm tips and 6 mm on the channel. No collapse of the structure shall occur with a combination of proof load and point load applied.</p> <p>B) Test 1B:</p> <p>Test 1A shall be repeated with Eight Cantilever arms uniformly loaded and with the same point load on arm 2</p> <p>Test 2: On Main support channel type -C2 for cantilever arms fixed on both sides</p> <p>a) Test 2A: A 3.5 m length of main support channel C2 for cantilever arms fixing on both sides shall be fixed at each end to rigid structure as per the fixing arrangement as shown in the enclosed drawing. Six (6), 750 mm cantilever arms shall be attached to each sides and each arm uniformly loaded to a working load of 100 kg over the out board 600 mm. A point load of 100 kg shall than be applied to arm 2, followed by a uniform proof load of twice the working load on all the arms; deflection shall be measured at points shown in the enclosed drawings at the following load intervals.</p> <ul style="list-style-type: none"> i) Working load ii) Working load + Point load iii) Off load iv) Proof load + Point load v) Off load <p>The deflection measured at working loads shall not exceed 16mm. The permanent deflection after removing the combination of working load and point load shall not exceed 10 mm at the arm tips and 6 mm on the channel. No collapse of the structure shall occur with a combination of proof load and point load applied</p> <p>b) Test 2 B: The test 2 A shall be repeated with the assembly but with an asymmetrical load on the C2 column and point load applied to arm 8. The 100 kg and 200 kg uniformly distributed loads shall be applied to the upper three arms on one side and the lower three arms on the opposite side.</p> <p>Test 3 : Tests on Channel Fixed on Beam/Floor</p>	
<p>TALCHER THERMAL POWER PROJECT</p> <p>STAGE-III (2X660 MW)</p> <p>EPC PACKAGE</p>	<p>TECHNICAL SPECIFICATION</p> <p>SECTION – VI, PART-B</p> <p>BID DOC NO : CS-4540-001A-2</p>	<p>SUB SECTION-B-10</p> <p>CABLING, EARTHING & LIGHTNING PROTECTION</p> <p>Page 15 of 21</p>

CLAUSE NO.	TECHNICAL REQUIREMENTS	
	<p>A length of main support channel section shall be fixed to steel structure/floor and have loads applied as shown in the drawing enclosed and as detailed below</p> <p>a) Test 3A : A length of steel structure shall be rigidly supported. It should be fitted on a meter length of channel section using beam clamps welded/bolted. A point load of 1200 kg shall be applied to the centre point via two brackets. No distortion or pulling of the components shall take place.</p> <p>b) Test 3B: With the components assembled as in Test 3A, two perpendicular point loads of 600 kg shall be simultaneously applied at positions 150 mm either side of the centre line, no distortion or pulling of the components shall take place.</p> <p>c) Test 3C: With the components assembled as in Test 3A, a perpendicular point load shall be applied at a point 150 mm on one side of the centre line.</p> <p>The load shall be gradually increased to the maximum value that can be applied without causing distortion or pulling of the components. This value shall be recorded.</p> <p>Test 4 : Channel Insert Test</p> <p>A 2.5 m length of C1 channel fixed to the concrete wall/ steel structure as per actual site installation conditions. 6 nos. of 750 mm cantilever arms shall be attached to C1 channel as shown in enclosed drawing. Each arm uniformly loaded to a working load of 100 kg over the out board 600 mm. A point load of 100 kg shall then be applied to arm 2, followed by a uniform proof load of twice the working load on all the arms; deflection shall be measured at points shown in the enclosed drawings at the following load intervals.</p> <ul style="list-style-type: none"> i) Working Load ii) Working Load + Point Load iii) Off Load iv) Proof Load + Point Load v) Off load <p>The deflection measured at working loads shall not exceed 16mm. The permanent deflection after removing the combination of working load and point load shall not exceed 10 mm at the arm tips and 6 mm on the channel. No collapse of the structure shall occur with a combination of proof load and point load applied</p> <p>Test 5 : Channel nut slip characteristics (what ever applicable)</p> <p>Tests 5A1,5A2,5A3 : A length of channel C1 section 200mm long shall have fitted bracket with the two bolt fixing as shown in drawing enclosed. With loads applied at the position shown in drawing enclosed nut slip shall be determined with bolt torque of 30NM, 50 NM and 65 NM No fewer than three measurements shall be made for each torque setting.</p> <p>A minimum loading of 720 kg shall be obtained before nut slip with bolt torque of 65 NM.</p> <p>Tests 5B1,5B2,5B3: The length of channel C1 section 200 mm long shall have fitted bracket with the one bolt fixing as shown in drawing enclosed. With loads applied at the position shown in drawing, nut slip shall be determined with bolt torques of 30 NM, 50 NM and 65 NM. No fewer than three measurements shall be made for each torque setting.</p>	
TALCHER THERMAL POWER PROJECT STAGE-III (2X660 MW) EPC PACKAGE	TECHNICAL SPECIFICATION SECTION – VI, PART-B BID DOC NO : CS-4540-001A-2	SUB SECTION-B-10 CABLING, EARTHING & LIGHTNING PROTECTION Page 16 of 21

CLAUSE NO.	TECHNICAL REQUIREMENTS	
	<p>A minimum loading of 350 kg shall be obtained before nut slip with a bolt torque of 65 NM.</p> <p>Test 6 Weld Integrity Test</p> <p>After deflection test as per test 1A, 1B, 2, 3 & 4 weld integrity shall be checked by magnetic particle inspection to detect sub-surface cracks developed, if any.</p> <p>7.02.02 Cable termination kit and straight through joints should have been tested as per IS:13573 for 3.3kV grade & above.</p> <p>7.03.00 Routine/ Acceptance Tests</p> <p>7.03.01 Routine Tests</p> <ul style="list-style-type: none"> a) Routine tests as per specification and applicable standards shall be carried out on all requirements/items covered in the specification. b) Physical & dimensional check on all equipments as per approved drawings/standards c) HV/IR as applicable. d) Check/measurement of thickness of paint/zinc coating/nickel-chrome plating as per specification & applicable standard. <p>7.03.02 Acceptance Test</p> <ul style="list-style-type: none"> a) Galvanising Tests as per applicable standards b) Welding checks c) Deflection tests on cable trays: One piece each of 2.5m length of cable tray of 300mm & above shall be taken as sample from each offered lot. It shall be supported at both end & loaded with uniform load of 76 kg/meter along the length of cable tray. The maximum deflection at the mid-span of each size shall not exceed 7mm. d) Proof load tests on cable tray support system i) Tests on Main Support Channel shall be done if only C1 Channel are in scope of supply and cantilever arms shall be fitted on one side. This test shall be same as test 4 of type test. ii) Test on Main Support Channel shall be done with C2 channel and cantilever arms fitted on both sides, if C2 channels are in scope of supply. This test shall be same as test 2A of type test. Then test (i) above shall not be done. iii) Nut slip characteristic test (it shall support minimum load of 350kg before nut slips with a bolt torque of 65 NM). This test shall be same as test 5B3 of type test. The procedure for carrying out tests at "d" above shall be as per details given in Type Tests in specification thereafter Die-Penetration test shall be carried out to check weld integrity. e) The above acceptance tests shall be done only on one sample from each offered lot. <p>8.00.00 COMMISSIONING</p> <p>8.01.01 The Contractor shall carry out the following commissioning tests and checks after installation at site. In addition the Contractor shall carry out all other checks and tests as recommended by the Manufacturers or else required for satisfactory performance..</p> <p>8.01.02 Cables</p> <ul style="list-style-type: none"> a) Check for physical damage b) Check for insulation resistance before and after termination/jointing. 	
TALCHER THERMAL POWER PROJECT STAGE-III (2X660 MW) EPC PACKAGE	TECHNICAL SPECIFICATION SECTION – VI, PART-B BID DOC NO : CS-4540-001A-2	SUB SECTION-B-10 CABLING, EARTHING & LIGHTNING PROTECTION Page 17 of 21




CLAUSE NO.	TECHNICAL REQUIREMENTS		
	<div><div>c)</div><div>HT cables shall be pressure tested (test voltage as per IS:7098) before commissioning.</div></div> <div><div>d)</div><div>Check of continuity of all cores of the cables.</div></div> <div><div>e)</div><div>Check for correctness of all connections as per relevant wiring diagrams. Any minor modification to the panel wiring like removing/inserting, shorting, change in terminal connections, etc., shall be carried out by the Contractor.</div></div> <div><div>f)</div><div>Check for correct polarity and phasing of cable connections.</div></div> <div><div>g)</div><div>Check for proper earth connections for cable glands, cable boxes, cable armour, screens, etc.</div></div> <div><div>h)</div><div>Check for provision of correct cable tags, core ferrules, tightness of connections.</div></div>		
8.02.00	Cable trays / supports and accessories <div><div>1)</div><div>Check for proper galvanizing/painting and identification number of the cable trays/supports and accessories.</div></div> <div><div>2)</div><div>Check for continuity of cable trays over the entire route.</div></div> <div><div>3)</div><div>Check that all sharp corners, burrs, and waste materials have been removed from the trays supports.</div></div> <div><div>4)</div><div>Check for earth continuity and earth connection of cable trays.</div></div>		
8.03.00	Earthing and Lightning protection system <div><div>1)</div><div>Earth continuity checks.</div></div> <div><div>2)</div><div>Earth resistance of the complete system as well as sub-system.</div></div>		
9.00.00	ELECTRICAL LAYOUT PHILOSOPHY: <p>While developing the layout the bidder must give due consideration to the following requirements:</p> <div><div>a)</div><div>Adequate distance shall be maintained between the transformers. As basic guidelines following norms will be adhered to:</div></div> <div><div>1)</div><div>Transformers shall be separated from the adjacent building/structures and from each other by a minimum distance as defined below or by a fire wall of two hours of fire resisting of height at least 600 mm above bushing / pressure relief vent whichever is higher.</div></div> <div><div></div><div><div>Oil capacity of individual transformer (in liters)</div><div>5,000 to 10,000</div><div>10,001 to 20,000</div><div>20,001 to 30,000</div><div>Over 30,001</div></div><div><div>Clear separating distance (in meters)</div><div>8.0</div><div>10.0</div><div>12.5</div><div>15.0</div></div></div> <div><div>2)</div><div>In case of auxiliary transformers having an aggregate oil capacity in excess of 2300 liters but individual oil capacity of less than 5000 liters, the maximum separating distance between transformers and surrounding building shall be at least 6M unless they are separated by fire separating walls or are protected by high velocity spray system.</div></div> <div><div>3.)</div><div>Rail track shall be provided in Transformer yard for movement of each transformer. The rail track in Transformer yard shall be connected with TG area rail track The Foundation top of transformer & rail top shall be at EL +/- 0.0M. Bus duct support or Transformer body shall be at least 8.0M from A-Row of TG building to clear the movement of GT/ Stator/UT/ST/UAT on rail line. Jacking pads shall be provided where the rail track changes the direction. Mooring post shall be provided on rail track for handling the transformers.</div></div>		
TALCHER THERMAL POWER PROJECT STAGE-III (2X660 MW) EPC PACKAGE		TECHNICAL SPECIFICATION SECTION – VI, PART-B BID DOC NO : CS-4540-001A-2	SUB SECTION-B-10 CABLING, EARTHING & LIGHTNING PROTECTION
			Page 18 of 21

CLAUSE NO.	TECHNICAL REQUIREMENTS																			
	<p>4) For each transformer a pit shall be provided all around at a distance of 1.5 m (minimum) from transformer outer edge. A sump pit shall be provided for each pit. A common oil retention pit per unit shall be provided to hold oil quantity of the largest transformer (by volume) & 10 minutes of water quantity of HVW spray system for the largest transformer. Sump pit of individual transformer shall be connected to common oil retention pit of that unit.</p> <p>5) Rail track shall be provided for all outdoor transformers up to road for movement of each transformer of size more than or equal to 7.5MVA Transformer. Jacking pads shall be provided where the rail track changes the direction. Jacking pad shall also be provided at the location of installation of transformer and mooring post shall be provided on rail track for handling the transformers.</p> <p>6.) The Transformer fencing shall be at 1.0 M (minimum) distance from the pit wall. The Height of fencing shall be 2.5 M (minimum) and fencing shall have personal entry gate and removable type fencing/gate for transformer withdrawal.</p> <p>7) The transformer firewall, pit sizing and clearances from adjacent building/structures etc. shall be as per IS 1646/CBIP manual on Transformer</p> <p>8) However, for all outdoor transformers of oil capacity less than 2000 litre, a trench of suitable size shall be provided all around at a distance of 1.0 m (minimum) from transformer outer edge. A sump pit shall be provided for each trench.</p> <p>b) Layout requirements for Electrical MCC/switchgear rooms</p> <p>1. Separate Switchgear Rooms shall be provided for each unit. For TG building, all HT boards shall be provided in HT switchgear room at only one floor and all LT boards shall be provided in LT switchgear room at only one floor</p> <p>2. The following clearances shall be maintained for HT Switchboard.</p> <p>a.) Front Clearance</p> <table border="0"> <tr> <td>i) For one Row of Swgr.</td> <td>-</td> <td>2.0 M (Min)</td> </tr> <tr> <td>ii) For two Rows of Swgr.</td> <td>-</td> <td>2.5 M (Min)</td> </tr> </table> <p>b.) Back Clearance - 1.5 M (Min.)</p> <p>c.) Side Clearance</p> <p>Min. 800 mm, however provision to be made for any additional panel in future at both ends. Therefore end clearance shall be 800+width of panel (including spare panels/dummy panels etc.)</p> <p>3. The following clearances shall be maintained for LT Switchboard.</p> <p>a.) Front Clearance</p> <table border="0"> <tr> <td>i) For one Row of Swgr</td> <td>-</td> <td>1.5M (Min)</td> </tr> <tr> <td>ii) For two Rows of Swgr</td> <td>-</td> <td>1.5/1.75M depending upon the depth of panels etc</td> </tr> </table> <p>b.) Back Clearance</p> <table border="0"> <tr> <td>i) For single front</td> <td>-</td> <td>1.0M (Min)</td> </tr> <tr> <td>ii) For double front</td> <td>-</td> <td>1.5M (Min)</td> </tr> </table>	i) For one Row of Swgr.	-	2.0 M (Min)	ii) For two Rows of Swgr.	-	2.5 M (Min)	i) For one Row of Swgr	-	1.5M (Min)	ii) For two Rows of Swgr	-	1.5/1.75M depending upon the depth of panels etc	i) For single front	-	1.0M (Min)	ii) For double front	-	1.5M (Min)	
i) For one Row of Swgr.	-	2.0 M (Min)																		
ii) For two Rows of Swgr.	-	2.5 M (Min)																		
i) For one Row of Swgr	-	1.5M (Min)																		
ii) For two Rows of Swgr	-	1.5/1.75M depending upon the depth of panels etc																		
i) For single front	-	1.0M (Min)																		
ii) For double front	-	1.5M (Min)																		
TALCHER THERMAL POWER PROJECT STAGE-III (2X660 MW) EPC PACKAGE	TECHNICAL SPECIFICATION SECTION – VI, PART-B BID DOC NO : CS-4540-001A-2	SUB SECTION-B-10 CABLING, EARTHING & LIGHTNING PROTECTION Page 19 of 21																		


CLAUSE NO.	TECHNICAL REQUIREMENTS																																																		
	<p>c.) Side Clearance:Min. 800 mm, however provision to be made for any additional panel in future at both ends. Therefore end clearance shall be 800 mm + width of panel.</p> <p>For offsite areas, HT Switchboard clearances shall be followed wherever both LT & HT switch boards are in the same MCC room.</p> <p>4. Height of HT/LT Switchgear Room and Boiler MCC room</p> <p>i) With Bus Duct – 4.5 m (min)</p> <p>ii) Without Bus Duct – 4.0 m (min)</p> <p>Further no vertical bracings shall be envisaged in HT/LT switchgear room and associated cable vault area.</p> <p>5. Cable trench/Cable vault</p> <p>For LT switchgear/MCC room at EL 0.0M, 1400 wide x 1400 deep cable trench shall be provided to route the cables. Horizontal cable trays shall be routed in cable trenches.</p> <p>c) Minimum clear working space around the equipment 1200mm</p> <p>d) In buildings having MCC, minimum 2 fire door along with one rolling shutter of adequate size/capacity shall be provided.</p> <p>e) The cable entry and exit from switchgear room shall be from 1.5 mtr (minimum) above FGL.</p> <p>f) Wash basin with mirror shall be provided in battery room.</p> <p style="text-align: right;">Annexure-I</p> <p>1.0 LOCATION OF LP3 :-</p> <p>One number LP3 to be located in boiler MCC room at 28.0m in BC bay to supply RC receptacles in TG area.</p> <p style="text-align: center;">Location of RC Receptacles in Turbine hall</p> <table><tr><th>Sl. No.</th><th>Name</th><th>Location of RC</th><th>No. of RC</th></tr><tr><td>1</td><td>Hot Well</td><td>0m (Near CEP)</td><td>2</td></tr><tr><td>2</td><td>Main Oil Tank</td><td>8.5m (AB Bay)</td><td>1</td></tr><tr><td>3</td><td>NGT Cubicle/ Gen Bushing</td><td>8.5m (AB Bay)</td><td>2</td></tr><tr><td>4</td><td>LAVT</td><td>7.5m (AB Bay)</td><td>2</td></tr><tr><td>5</td><td>HP-IP Turbine</td><td>17.0m (AB Bay)</td><td>2</td></tr><tr><td>6</td><td>LP Turbine</td><td>17.0m (AB Bay)</td><td>1</td></tr><tr><td>7</td><td>TD BFP</td><td>17.0m (AB Bay)</td><td>1</td></tr><tr><td>8</td><td>HP Heater - 5</td><td>17.0m (BC Bay)</td><td>2</td></tr><tr><td>9</td><td>Deaerator</td><td>38.0m (BC Bay)</td><td>2</td></tr><tr><td>10</td><td>LP Heater- 2</td><td>8.5m (BC Bay)</td><td>1</td></tr><tr><td>11</td><td>Valve Room</td><td>8.5m (AB Bay)</td><td>2</td></tr></table> <p style="text-align: center;">Total - 18 nos. RC Receptacles in Turbine Hall.</p> <p>2.0 LOCATION OF RC RECEPTACLES</p>			Sl. No.	Name	Location of RC	No. of RC	1	Hot Well	0m (Near CEP)	2	2	Main Oil Tank	8.5m (AB Bay)	1	3	NGT Cubicle/ Gen Bushing	8.5m (AB Bay)	2	4	LAVT	7.5m (AB Bay)	2	5	HP-IP Turbine	17.0m (AB Bay)	2	6	LP Turbine	17.0m (AB Bay)	1	7	TD BFP	17.0m (AB Bay)	1	8	HP Heater - 5	17.0m (BC Bay)	2	9	Deaerator	38.0m (BC Bay)	2	10	LP Heater- 2	8.5m (BC Bay)	1	11	Valve Room	8.5m (AB Bay)	2
Sl. No.	Name	Location of RC	No. of RC																																																
1	Hot Well	0m (Near CEP)	2																																																
2	Main Oil Tank	8.5m (AB Bay)	1																																																
3	NGT Cubicle/ Gen Bushing	8.5m (AB Bay)	2																																																
4	LAVT	7.5m (AB Bay)	2																																																
5	HP-IP Turbine	17.0m (AB Bay)	2																																																
6	LP Turbine	17.0m (AB Bay)	1																																																
7	TD BFP	17.0m (AB Bay)	1																																																
8	HP Heater - 5	17.0m (BC Bay)	2																																																
9	Deaerator	38.0m (BC Bay)	2																																																
10	LP Heater- 2	8.5m (BC Bay)	1																																																
11	Valve Room	8.5m (AB Bay)	2																																																
TALCHER THERMAL POWER PROJECT STAGE-III (2X660 MW) EPC PACKAGE	TECHNICAL SPECIFICATION SECTION – VI, PART-B BID DOC NO : CS-4540-001A-2	SUB SECTION-B-10 CABLING, EARTHING & LIGHTNING PROTECTION	Page 20 of 21																																																

TECHNICAL REQUIREMENTS

Location of Receptacles and Socket in Boiler area

FLOOR	63A WELDING RECEPTACLES		20A, 240V AC INDUSTRIAL SOCKET		20A, 24V AC INDUSTRIAL SOCKET	
			RA 		RC 	
	PROPOSED		PROPOSED		PROPOSED	
	QTY	LOCATION	QTY	LOCATION	QTY	LOCATION
GL-200	10	S7L,R MILL-B,E,G S17 ID-A,B P3L,R	7	S8L,R S21L, P3L,R ID-A,B	4	P2L,R ID-A,B
4710	3	MILL-A,D,J	3	MILL-A,D, MILL-J	8	MILL-A,B,C,D,F,G,H,J
8900	1	S18	1	S18, S14R	1	S12L
9700	2	S7L,R	2	S8L,R	2	S8L,R
11450	2	S8L,R	3	S8L,R S21	4	S10L,R S22L,R
17600					1	F1L
20500(APH BOTTOM), 21850	4	S18(2) S19L,R	7	S8L,R S17, S19L,R S6L,R	7	S9L,R S12L,R S18, S20L,R
21700(FEEDER FLOOR)	2	FEEDER A,J	4	FEEDER-A,C,F,J	4	FEEDER-A,C,F,J
23000	1	S17	2	S13L, S19		
25000(BURNNER BOTTOM, SPRAY STATION)	4	S3L,R S11L,R	5	S1L,R S11L,R S17	5	S1L,R S11L,R S17
28000(APH)	2	S19L,R	2	S19L,R	2	S19L,R
29200(APH, WIND BOX)	4	S20L,R S9L,R	4	S8L,R S20L,R	4	S8L,R S10L,R
32200	2	S9L,R	2	S8L,R		
33400	2	S12L,R	2	S8L,R S19L,R	2	S19L,R
38500	2	S3R, S10L				
42500	2	S10L,R	3	S8L,R S17	3	S9L,R S17
45300	2	S10L,R	4	S8L,R S11L,R	4	S8L,R S10L,R
48000	1	S1R	2	S14R S15L	2	S9L,R
48900	4	S18(2) S12L,R	4	S11L,R S12L,R	2	S11L,R
53600	2	S5L,R	3	S14R S10L,R	2	S5L,R
58000	4	S11L,R S14L S15R	4	S14R S15L S11L,R	2	S11L,R
59200(TRIPPER FLOOR)	2	LEFT, RIGHT	2	L,R		
61400	4	S11L,R S14L S15R	3	S14R S11L,R	2	S11L,R
68100	2	S11L,R	2	S9L,R		
77300	2	S10L,R	4	S9L,R S11L,R	2	S4L,R
83500	2	S10L,R	2	S12L,R		
86700	2	S3L,R	2	S11L,R	2	S11L,R
88600	1	S11L	2	S8L,R	2	S8L,R
95900	1	S1R	1	S1L		
ESP/FG IL DUCT	4		2		4	
ESP/FG OL DUCT	2		1		2	
ESP AT MANHOLE DOOR FLOOR	4	IN BETWEEN TWO PASS	4		4	
ESP AT TOP	2		1			
ESP AT -200	2	AT FRONT SIDE BOTH L&R	2			
TOTAL	86		92		77	

Annexure-ETP



The Tentative BoQ of the system shall be as below:

- 1.Horizontal Centrifugal Pump (10m³/hr)-2Nos.
- 2.Butterfly valve/gate valve -4nos.
- 2.Three-way valve-3nos.
- 3.NRV/check valve -2nos.
- 4.Pressure gauge-2nos.
- 5.Pressure transmitter/ switch-1No.
6. Level gauge-2nos.,
- 7.Level transmitter/
switch-2nos.
- 8.Piping works (65NB as per IS 1239)-20Mtrs

Any other item for the completeness of the system as shown in the schematic may be considered by the bidder.



TITLE :
2 X 660 MW TALCHER THERMAL POWER
PROJECT STAGE-III

SPECIFICATION NO. PE-TS-497-164-W001

VOLUME – IIB

TECHNICAL SPECIFICATION FOR EFFLUENT
TREATMENT PLANT

SECTION - IA

REV. No. 00

DATE : 18.12.2023

DATASHEET A

1.	TG UNIT-1A FLOOR WASH WATER SUMP (E1A)	
a)	Number required	One (1) nos.
b)	Effective Capacity, m3	12 m3
c)	Material of Construction	RCC (IN BHEL SCOPE)
d)	Type	Underground, Rectangular with Flat bottom
e)	Type of fluid to be handled	1. Floor wash from TG UNIT 1 containing oil traces 2. Oily effluent from TDBFP-A Unit-1 & MDBFP Unit-1 area
2.	TG UNIT-1A FLOOR WASH WATER TRANSFER PUMPS	
a)	Number required	Two (1W+1S) nos.
b)	Type	Vertical Screw type
c)	Location	Outdoor
d)	Fluid to be handled	1. Floor wash from TG UNIT 1 containing oil traces 2. Oily effluent from TDBFP-A Unit-1 & MDBFP Unit-1 area
e)	Duty	Intermittent
f)	Rated capacity, each m3/ hr.	25
g)	Pump Speed, RPM (max.)	1500
h)	Minimum Head to be developed at rated capacity, MLC	As per System Requirements
i)	Material of Construction	
	• Casing	2.5% Ni Cl IS:210 GR. FG 260
	• Impeller/Rotor	ASTM A351 CF8M
	• Shaft	SS 316
3.	TG UNIT-1B FLOOR WASH WATER SUMP (E1B)	
a)	Number required	One (1) nos.
b)	Effective Capacity, m3	12 m3
c)	Material of Construction	RCC (IN BHEL SCOPE)
d)	Type	Underground, Rectangular with Flat bottom
e)	Type of fluid to be handled	1. Floor wash from TG UNIT 1 containing oil traces 2. Oily effluent from TDBFP-A Unit-1 & MDBFP Unit-1 area 3. Oily effluent from COT/DOT area
4.	TG UNIT-1B FLOOR WASH WATER TRANSFER PUMPS	
a)	Number required	Two (1W+1S) nos.
b)	Type	Vertical Screw type
c)	Location	Outdoor
d)	Fluid to be handled	1. Floor wash from TG UNIT 1 containing oil traces 2. Oily effluent from TDBFP-B Unit-1 & MDBFP Unit-1 area 3. Oily effluent from COT/DOT area
e)	Duty	Intermittent
f)	Rated capacity, each m3/ hr.	25
g)	Pump Speed, RPM (max.)	1500
h)	Minimum Head to be developed at rated capacity, MLC	As per System Requirements
i)	Material of Construction	
	• Casing	2.5% Ni Cl IS:210 GR. FG 260
	• Impeller/Rotor	ASTM A351 CF8M
	• Shaft	SS 316



TITLE :
2 X 660 MW TALCHER THERMAL POWER
PROJECT STAGE-III

SPECIFICATION NO. PE-TS-497-164-W001

VOLUME – IIB

TECHNICAL SPECIFICATION FOR EFFLUENT
TREATMENT PLANT

SECTION - IA

REV. No. 00

DATE : 18.12.2023

5.	COT/DOT WASTE WATER COLLECTION SUMP (E1C)	
a)	Number required	One (1) nos.
b)	Effective Capacity, m3	1 m3
c)	Material of Construction	RCC (IN BHEL SCOPE)
d)	Type	Underground, Rectangular with Flat bottom
e)	Type of fluid to be handled	1. Oily effluent from COT/DOT area
6.	COT/DOT WASTE WATER TRANSFER PUMPS	
a)	Number required	Two (1W+1S) nos.
b)	Type	Horizontal Screw type
c)	Location	Outdoor
d)	Fluid to be handled	1. Oily effluent from COT/DOT area
e)	Duty	Intermittent
f)	Rated capacity, each m3/ hr.	2
g)	Pump Speed, RPM (max.)	1500
h)	Minimum Head to be developed at rated capacity, MLC	As per System Requirements
i)	Material of Construction	
	• Casing	2.5% Ni Cl IS:210 GR. FG 260
	• Impeller/Rotor	ASTM A351 CF8M
	• Shaft	SS 316
7.	TG UNIT-2A FLOOR WASH WATER SUMP (E2A)	
a)	Number required	One (1) nos.
b)	Effective Capacity, m3	12 m3
c)	Material of Construction	RCC (IN BHEL SCOPE)
d)	Type	Underground, Rectangular with Flat bottom
e)	Type of fluid to be handled	1. Floor wash from TG UNIT 2 containing oil traces 2. Oily effluent from TDBFP-A Unit-2 & MDBFP Unit-2 area
8.	TG UNIT-2A FLOOR WASH WATER TRANSFER PUMPS	
a)	Number required	Two (1W+1S) nos.
b)	Type	Vertical Screw type
c)	Location	Outdoor
d)	Fluid to be handled	1. Floor wash from TG UNIT 2 containing oil traces 2. Oily effluent from TDBFP-A Unit-2 & MDBFP Unit-2 area
e)	Duty	Intermittent
f)	Rated capacity, each m3/ hr.	25
g)	Pump Speed, RPM (max.)	1500
h)	Minimum Head to be developed at rated capacity, MLC	As per System Requirements
i)	Material of Construction	
	• Casing	2.5% Ni Cl IS:210 GR. FG 260
	• Impeller/Rotor	ASTM A351 CF8M
	• Shaft	SS 316
9.	TG UNIT-2B FLOOR WASH WATER SUMP (E2B)	
a)	Number required	One (1) nos.
b)	Effective Capacity, m3	12 m3
c)	Material of Construction	RCC (IN BHEL SCOPE)
d)	Type	Underground, Rectangular with Flat bottom



TITLE :
2 X 660 MW TALCHER THERMAL POWER
PROJECT STAGE-III

SPECIFICATION NO. PE-TS-497-164-W001

VOLUME – IIB

TECHNICAL SPECIFICATION FOR EFFLUENT
TREATMENT PLANT

SECTION - IA

REV. No. 00

DATE : 18.12.2023

e)	Type of fluid to be handled	1. Floor wash from TG UNIT 1 containing oil traces 2. Oily effluent from TDBFP-B Unit-2 & MDBFP Unit-2 area
10.	TG UNIT-2B FLOOR WASH WATER TRANSFER PUMPS	
a)	Number required	Two (1W+1S) nos..
b)	Type	Vertical Screw type
c)	Location	Outdoor
d)	Fluid to be handled	1. Floor wash from TG UNIT 1 containing oil traces 2. Oily effluent from TDBFP-B Unit-2 & MDBFP Unit-2 area
e)	Duty	Intermittent
f)	Rated capacity, each m3/ hr.	25
g)	Pump Speed, RPM (max.)	1500
h)	Minimum Head to be developed at rated capacity, MLC	As per System Requirements
i)	Material of Construction	
	• Casing	2.5% Ni Cl IS:210 GR. FG 260
	• Impeller/Rotor	ASTM A351 CF8M
	• Shaft	SS 316
11.	FUEL OIL HANDLING AREA OILY WASTE SUMP (E3)	
a)	Number required	One (1) nos.
b)	Effective Capacity, m3	As specified in FOHS area
c)	Material of Construction	RCC (IN BHEL SCOPE)
d)	Type	Underground, Rectangular with Flat bottom
e)	Type of fluid to be handled	Oily effluent from FOHS area
12.	FUEL OIL AREA WASTE TRANSFER PUMPS	
a)	Number required	Two (1W+1S) nos.
b)	Type	Vertical Screw type
c)	Location	Outdoor
d)	Fluid to be handled	Oily effluent from FOHS area
e)	Duty	Intermittent
f)	Rated capacity, each m3/ hr.	10
g)	Pump Speed, RPM (max.)	1500
h)	Minimum Head to be developed at rated capacity, MLC	As per System Requirements
i)	Material of Construction	
	• Casing	2.5% Ni Cl IS:210 GR. FG 260
	• Impeller/Rotor	ASTM A351 CF8M
	• Shaft	SS 316
13.	TRANSFORMER YARD OILY WASTE SUMP UNIT-1 (E4)	
a)	Number required	One (1) nos.
b)	Effective Capacity, m3	As specified in Transformer area Oil Water Separator
c)	Material of Construction	RCC (IN BHEL SCOPE)
d)	Type	Underground, Rectangular with Flat bottom
e)	Type of fluid to be handled	Oily effluent from Transformer area Oil Water Separator
14.	TRANSFORMER YARD UNIT-1 OILY WASTE TRANSFER PUMPS	
a)	Number required	Two (1W+1S) nos.
b)	Type	Vertical Screw type
c)	Location	Outdoor



TITLE :
2 X 660 MW TALCHER THERMAL POWER
PROJECT STAGE-III

SPECIFICATION NO. PE-TS-497-164-W001

VOLUME – IIB

TECHNICAL SPECIFICATION FOR EFFLUENT
TREATMENT PLANT

SECTION - IA

REV. No. 00

DATE : 18.12.2023

d)	Fluid to be handled	Oily effluent from Transformer area Oil Water Separator
e)	Duty	Intermittent
f)	Rated capacity, each m3/ hr.	10
g)	Pump Speed, RPM (max.)	1500
h)	Minimum Head to be developed at rated capacity, MLC	As per System Requirements
i)	Material of Construction	
	• Casing	2.5% Ni Cl IS:210 GR. FG 260
	• Impeller/Rotor	ASTM A351 CF8M
	• Shaft	SS 316
15.	TRANSFORMER YARD OILY WASTE SUMP UNIT-2 (E5)	
a)	Number required	One (1) nos.
b)	Effective Capacity, m3	As specified in Transformer area Oil Water Separator
c)	Material of Construction	RCC (IN BHEL SCOPE)
d)	Type	Underground, Rectangular with Flat bottom
e)	Type of fluid to be handled	Oily effluent from Transformer area Oil Water Separator
16.	TRANSFORMER YARD UNIT-2 OILY WASTE TRANSFER PUMPS	
a)	Number required	Two (1W+1S) nos.
b)	Type	Vertical Screw type
c)	Location	Outdoor
d)	Fluid to be handled	Oily effluent from Transformer area Oil Water Separator
e)	Duty	Intermittent
f)	Rated capacity, each m3/ hr.	10
g)	Pump Speed, RPM (max.)	1500
h)	Minimum Head to be developed at rated capacity, MLC	As per System Requirements
i)	Material of Construction	
	• Casing	2.5% Ni Cl IS:210 GR. FG 260
	• Impeller/Rotor	ASTM A351 CF8M
	• Shaft	SS 316
17.	MRS WASTE WATER SUMP UNIT-1 (E6)	
a)	Number required	One (1) nos.
b)	Effective Capacity, m3	10 m3
c)	Material of Construction	RCC (IN BHEL SCOPE)
d)	Type	Underground, Rectangular with Flat bottom
e)	Type of fluid to be handled	1. Floor wash waste (containing coal laden particles) from MRS area Unit-1 2. Waste water (containing coal laden particles) from Feeder and Tripper Floor Unit-1
18.	MRS UNIT-1 OILY WASTE WATER TRANSFER PUMPS	
a)	Number required	Two (1W+1S) nos.
b)	Type	Vertical Centrifugal type
c)	Location	Outdoor
d)	Fluid to be handled	1. Floor wash waste (containing coal laden particles) from MRS area Unit-1 2. Waste water (containing coal laden particles) from Feeder and Tripper Floor Unit-1
e)	Duty	Intermittent



TITLE :
2 X 660 MW TALCHER THERMAL POWER
PROJECT STAGE-III

SPECIFICATION NO. PE-TS-497-164-W001

VOLUME – IIB

TECHNICAL SPECIFICATION FOR EFFLUENT
TREATMENT PLANT

SECTION - IA

REV. No. 00

DATE : 18.12.2023

f)	Rated capacity, each m3/ hr.	10
g)	Pump Speed, RPM (max.)	1500
h)	Minimum Head to be developed at rated capacity, MLC	As per System Requirements
i)	Material of Construction	
	• Casing	2.5% Ni Cl IS:210 GR. FG 260, S-0.1 (max.) P-0.15 (max.)
	• Stuffing box, Gland	2.5% Ni Cl IS:210 GR. FG 260
	• Impeller	ASTM A351 CF8M
	• Shaft, Shaft coupling, shaft sleeves	SS 410
	• Column pipe & discharge pipe, shaft enclosing	CS as per IS:2062 or eq.
	• Gland packing	TIWA
	• Gasket	Neoprene Rubber
	• Bolts & nuts	SS
	• Base plate and soleplate	CS (min. 10 thick)
19.	MRS WASTE WATER SUMP UNIT-2 (E7)	
a)	Number required	One (1) nos.
b)	Effective Capacity, m3	10 m3
c)	Material of Construction	RCC (IN BHEL SCOPE)
d)	Type	Underground, Rectangular with Flat bottom
e)	Type of fluid to be handled	1. Floor wash waste (containing coal laden particles) from MRS area Unit-2 2. Waste water (containing coal laden particles) from Feeder and Tripper Floor Unit-2
20.	MRS UNIT-2 OILY WASTE WATER TRANSFER PUMPS	
a)	Number required	Two (1W+1S) nos.
b)	Type	Vertical Centrifugal type
c)	Location	Outdoor
d)	Fluid to be handled	1. Floor wash waste (containing coal laden particles) from MRS area Unit-1 2. Waste water (containing coal laden particles) from Feeder and Tripper Floor Unit-1
e)	Duty	Intermittent
f)	Rated capacity, each m3/ hr.	10
g)	Pump Speed, RPM (max.)	1500
h)	Minimum Head to be developed at rated capacity, MLC	As per System Requirements
i)	Material of Construction	
	• Casing	2.5% Ni Cl IS:210 GR. FG 260, S-0.1 (max.) P-0.15 (max.)
	• Stuffing box, Gland	2.5% Ni Cl IS:210 GR. FG 260
	• Impeller	ASTM A351 CF8M
	• Shaft, Shaft coupling, shaft sleeves	SS 410
	• Column pipe & discharge pipe, shaft enclosing	CS as per IS:2062 or eq.
	• Gland packing	TIWA



TITLE :
2 X 660 MW TALCHER THERMAL POWER
PROJECT STAGE-III

SPECIFICATION NO. PE-TS-497-164-W001

VOLUME – IIB

TECHNICAL SPECIFICATION FOR EFFLUENT
TREATMENT PLANT

SECTION - IA

REV. No. 00

DATE : 18.12.2023

	<ul style="list-style-type: none"> Gasket 	Neoprene Rubber
	<ul style="list-style-type: none"> Bolts & nuts 	SS
	<ul style="list-style-type: none"> Base plate and soleplate 	CS (min. 10 thick)
21.	SG UNIT-1 FLOOR WASH WATER SUMP (E8)	
a)	Number required	One (1) nos.
b)	Effective Capacity, m3	100 M3
c)	Material of Construction	RCC (IN BHEL SCOPE)
d)	Type	Underground, Rectangular with Flat bottom
e)	Type of fluid to be handled	1. Floor wash from SG UNIT 1 containing oil traces 2. Floor wash from APH UNIT 1 containing ash traces
22.	SG UNIT-1 FLOOR WASH WATER TRANSFER PUMPS	
a)	Number required	Two (2W) nos.
b)	Type	Vertical Screw type
c)	Location	Outdoor
d)	Fluid to be handled	1. Floor wash from SG UNIT 1 containing oil traces 2. Floor wash from APH UNIT 1 containing ash traces
e)	Duty	Intermittent
f)	Rated capacity, each m3/ hr.	100
g)	Pump Speed, RPM (max.)	1500
h)	Minimum Head to be developed at rated capacity, MLC	As per System Requirements
i)	Material of Construction	
	<ul style="list-style-type: none"> Casing 	2.5% Ni CI IS:210 GR. FG 260
	<ul style="list-style-type: none"> Impeller/Rotor 	ASTM A351 CF8M
	<ul style="list-style-type: none"> Shaft 	SS 316
23.	SG UNIT-2 FLOOR WASH WATER SUMP (E9)	
a)	Number required	One (1) nos.
b)	Effective Capacity, m3	100 M3
c)	Material of Construction	RCC (IN BHEL SCOPE)
d)	Type	Underground, Rectangular with Flat bottom
e)	Type of fluid to be handled	1. Floor wash from SG UNIT 1 containing oil traces 2. Floor wash from APH UNIT 1 containing ash traces
24.	SG UNIT-2 FLOOR WASH WATER TRANSFER PUMPS	
a)	Number required	Two (2W) nos.
b)	Type	Vertical Screw type
c)	Location	Outdoor
d)	Fluid to be handled	1. Floor wash from SG UNIT 1 containing oil traces 2. Floor wash from APH UNIT 1 containing ash traces
e)	Duty	Intermittent
f)	Rated capacity, each m3/ hr.	100
g)	Pump Speed, RPM (max.)	1500
h)	Minimum Head to be developed at rated capacity, MLC	As per System Requirements
i)	Material of Construction	
	<ul style="list-style-type: none"> Casing 	2.5% Ni CI IS:210 GR. FG 260
	<ul style="list-style-type: none"> Impeller/Rotor 	ASTM A351 CF8M
	<ul style="list-style-type: none"> Shaft 	SS 316



TITLE :
2 X 660 MW TALCHER THERMAL POWER
PROJECT STAGE-III

SPECIFICATION NO. PE-TS-497-164-W001

VOLUME – IIB

TECHNICAL SPECIFICATION FOR EFFLUENT
TREATMENT PLANT

SECTION - IA

REV. No. 00

DATE : 18.12.2023

25.	ESP UNIT-1 FLOOR WASH WATER SUMP (E10)	
f)	Number required	One (1) nos.
g)	Effective Capacity, m3	50 M3
h)	Material of Construction	RCC (IN BHEL SCOPE)
i)	Type	Underground, Rectangular with Flat bottom
j)	Type of fluid to be handled	Floor wash from ESP UNIT 1 containing ash traces
26.	ESP UNIT-1 FLOOR WASH WATER TRANSFER PUMPS	
a)	Number required	Two (1W+1S) nos.
b)	Type	Vertical Screw type
c)	Location	Outdoor
d)	Fluid to be handled	Floor wash from ESP UNIT 1 containing ash traces
e)	Duty	Intermittent
f)	Rated capacity, each m3/ hr.	50
g)	Pump Speed, RPM (max.)	1500
h)	Minimum Head to be developed at rated capacity, MLC	As per System Requirements
i)	Material of Construction	
	• Casing	2.5% Ni Cl IS:210 GR. FG 260
	• Impeller/Rotor	ASTM A351 CF8M
	• Shaft	SS 316
27.	ESP UNIT-2 FLOOR WASH WATER SUMP (E11)	
a)	Number required	One (1) nos.
b)	Effective Capacity, m3	50 M3
c)	Material of Construction	RCC (IN BHEL SCOPE)
d)	Type	Underground, Rectangular with Flat bottom
e)	Type of fluid to be handled	Floor wash from ESP UNIT 2 containing ash traces
28.	ESP UNIT-2 FLOOR WASH WATER TRANSFER PUMPS	
a)	Number required	Two (1W+1S) nos.
b)	Type	Vertical Screw type
c)	Location	Outdoor
d)	Fluid to be handled	1. Floor wash from ESP UNIT 2 containing ash traces
e)	Duty	Intermittent
f)	Rated capacity, each m3/ hr.	50
g)	Pump Speed, RPM (max.)	1500
h)	Minimum Head to be developed at rated capacity, MLC	As per System Requirements
i)	Material of Construction	
	• Casing	2.5% Ni Cl IS:210 GR. FG 260
	• Impeller/Rotor	ASTM A351 CF8M
	• Shaft	SS 316
29.	WASTE SERVICE WATER SUMP (WSWS) (E12)	
a)	Number required	One (1) nos. (In two compartments)
b)	Effective Capacity (each compartment), m3	250m3
c)	Material of Construction	RCC (IN BHEL SCOPE)
d)	Type	Rectangular with Flat bottom, under ground
e)	Inlet arrangement	Inlet & Outlet chamber with interconnecting gates



TITLE :
2 X 660 MW TALCHER THERMAL POWER
PROJECT STAGE-III

SPECIFICATION NO. PE-TS-497-164-W001

VOLUME – IIB

TECHNICAL SPECIFICATION FOR EFFLUENT
TREATMENT PLANT

SECTION - IA

REV. No. 00

DATE : 18.12.2023

f)	Oil removal arrangement	Two (2x100%) numbers Drum Type Oil skimmers and Two (2x100%) numbers trolley mounted Portable Oil Centrifuge.
g)	Oil collection drum (type/ capacity)	One (1) nos. MS Oil Drum (capacity: 200 litre)
h)	Oil Skimmer (each to be installed in each compartment of WWS)	Type: Drum Capacity: As per system requirements Inlet Oil Level: 50ppm Oil Outlet guarantee: <5ppm MOC: As per system requirements Accessories: Power pack, motor, valves, control panel as required.
i)	Portable Oil Centrifuge	Type: Trolley Mounted Portable Oil Centrifuge Capacity: As per system requirements MOC: As per system requirements Accessories: motor, valves, control panel as required. Purpose: To collect and purify the oil of the WWS
30.	WSWS TRANSFER PUMPS	
a)	Number required	Three (2W+1S) nos.
b)	Type	Vertical Centrifugal type
c)	Location	Outdoor
d)	Fluid to be handled	Effluent from WWS
e)	Duty	Intermittent
f)	Rated capacity, each m3/ hr.	125
g)	Pump Speed, RPM (max.)	1500
h)	Minimum Head to be developed at rated capacity, MLC	As per System Requirements
i)	Material of Construction	
	• Casing	2.5% Ni Cl IS:210 GR. FG 260, S-0.1 (max.) P-0.15 (max.)
	• Stuffing box, Gland	2.5% Ni Cl IS:210 GR. FG 260
	• Impeller	ASTM A351 CF8M
	• Shaft, Shaft coupling, shaft sleeves	SS 410
	• Column pipe & discharge pipe, shaft enclosing tube	CS as per IS:2062 or eq. (Min. Thickness 8 mm)
	• Gland packing	TIWA
	• Gasket	Neoprene Rubber
	• Bolts & nuts	SS
	• Base plate and soleplate	CS (min. 10 thick)
31.	LAMELLA CLARIFIER/ TUBE SETTLER	
a)	Number required	Two (1W+1S) nos.
b)	Material of Construction	RCC (IN BHEL SCOPE)
c)	Design Flow (Net Output of each clarifier), m3/hr	250
d)	Basis design and components	As per manufacturer standard
e)	Sludge Consistency	2% (minimum)
f)	Type	Counter Flow / Cross Flow
g)	Design Flow velocity	Not more than 5m3/hr/m2
h)	Flash Mixer tank & Flocculator tank	1x100% Flash Mixer Tank and 1x100% flocculation tank (for each Lamella Clarifier/ Tube Settler)
i)	No. of Flash Mixer (for each Lamella Clarifier/ Tube Settler)	One (1) number with required agitator Min. 1-minute storage for Flash Mixer Tank
j)	MOC of Agitator	SS 316



TITLE :
2 X 660 MW TALCHER THERMAL POWER
PROJECT STAGE-III

SPECIFICATION NO. PE-TS-497-164-W001

VOLUME – IIB

TECHNICAL SPECIFICATION FOR EFFLUENT
TREATMENT PLANT

SECTION - IA

REV. No. 00

DATE : 18.12.2023

k)	No. of Flocculation Chamber (for each Lamella Clarifier/ Tube Settler)	One (1) number with required Flocculator Min. 10-minute storage for Flocculation Chamber
l)	MOC of Flocculator	SS 316
m)	Type of Fluid to be handled	Wastewater containing traces of oil, suspended solids.
n)	Accessories	Suitable sampling lines for performance monitoring
32.	CENTRAL MONITORING BASIN (CMB) (E13)	
a)	Number required	One (1) nos. (In two compartments)
b)	Effective Capacity (each compartment), m3	250m3
c)	Material of Construction	RCC (IN BHEL SCOPE)
d)	Type	Rectangular with Flat bottom, Above ground
e)	Inlet arrangement	Inlet & Outlet chamber with interconnecting gates
33.	CENTRAL MONITORING BASIN TRANSFER PUMPS	
a)	Number required	Three (2W+1S) nos.
b)	Type	Horizontal Centrifugal type
c)	Location	Outdoor
d)	Fluid to be handled	Effluent from WSWs
e)	Duty	Intermittent
f)	Rated capacity, each m3/ hr.	125
g)	Pump Speed, RPM (max.)	1500
h)	Minimum Head to be developed at rated capacity, MLC	As per System Requirements
i)	Material of Construction	
	• Casing	2.5% Ni CI IS:210 GR. FG 260, S-0.1 (max.) P-0.15 (max.)
	• Stuffing box, Gland	2.5% Ni CI IS:210 GR. FG 260
	• Impeller	ASTM A351 CF8M
	• Shaft, Shaft coupling, shaft sleeves	SS 410
	• Column pipe & discharge pipe, shaft enclosing tube	CS as per IS:2062 or eq. (Min. Thickness 8 mm)
	• Gland packing	TIWA
	• Gasket	Neoprene Rubber
	• Bolts & nuts	SS
	• Base plate and soleplate	CS (min. 10 thick)
34.	TROLLEY MOUNTED SCREW PUMPS WITH SLOPE OIL TANK	
a)	Number required	Two (2W) nos. (1 Set for each unit)
b)	Type	Trolley Mounted Screw type with Slope oil tank and Power station
c)	Location	Outdoor
d)	Fluid to be handled	Oily effluent from Transformers
e)	Duty	Intermittent
f)	Rated capacity, each m3/ hr.	10
g)	Pump Speed, RPM (max.)	1500
h)	Minimum Head to be developed at rated capacity, MLC	15 mwc
i)	Material of Construction	
	• Casing	2.5% Ni CI IS:210 GR. FG 260
	• Impeller/Rotor	ASTM A351 CF8M
	• Shaft	SS 316



TITLE :
2 X 660 MW TALCHER THERMAL POWER
PROJECT STAGE-III

SPECIFICATION NO. PE-TS-497-164-W001

VOLUME – IIB

TECHNICAL SPECIFICATION FOR EFFLUENT
TREATMENT PLANT

SECTION - IA

REV. No. 00

DATE : 18.12.2023

j)	Slope Oil Tank	Capacity: 1m3 MOC: MSEP
35.	SLUDGE SUMP (E14)	
a)	Number required	One (1) nos. (In two compartments).
b)	Effective Capacity, m3 (each compartment)	6.25m3
c)	Material of Construction	RCC (IN BHEL SCOPE)
d)	Type	Rectangular with Flat bottom, under ground
e)	Inlet arrangement	Inlet & Outlet chamber with interconnecting gates
36.	SLUDGE SUMP TRANSFER PUMPS	
a)	Number required	Two (1W+1S) nos.
b)	Type	Vertical sump type (Open Impeller, Non-clog type)
c)	Location	Outdoor
d)	Fluid to be handled	Effluent from WSWs
e)	Duty	Intermittent
f)	Rated capacity, each m3/ hr.	12.5
g)	Pump Speed, RPM (max.)	1500
h)	Minimum Head to be developed at rated capacity, MLC	As per System Requirements
i)	Material of Construction	
	• Casing	2.5% Ni Cl IS:210 GR. FG 260, S-0.1 (max.) P-0.15 (max.)
	• Stuffing box, Gland	2.5% Ni Cl IS:210 GR. FG 260
	• Impeller	ASTM A351 CF8M
	• Shaft, Shaft coupling, shaft sleeves	SS 410
	• Column pipe & discharge pipe, shaft enclosing tube	CS as per IS:2062 or eq. (Min. Thickness 8 mm)
	• Gland packing	TIWA
	• Gasket	Neoprene Rubber
	• Bolts & nuts	SS
	• Base plate and soleplate	CS (min. 10 thick)
37.	CHEMICAL DOSING FOR LAMELLA CLARIFIER/ TUBE SETTLER	
48.1	ALUM DOSING SYSTEM (DOSING RATE = 70 PPM)	
A.	ALUM DOSING TANK	
a)	Numbers required	Two (2) nos.
b)	Type	Vertical rectangular with flat bottom
c)	Type of fluid to be handled	10 % w/w Alum Solution.
d)	Effective capacity of each tank, m ³	Adequate to hold the quantity required for twelve (12) hours of operation for treatment of overall waste in LAMELLA CLARIFIER/ TUBE SETTLER + 20% margin excluding free board
e)	Design Pressure, Kg/sq. cm (g)	Atmospheric
f)	Material of Construction	RCC (IN BHEL SCOPE).
g)	Protection	
	• Internal	Acid Proof Tile Lining
	• External	Not applicable
h)	Agitator along with drive motor and all other accessories	
	• Number	One (1) per Tank
	• Material of Construction	SS 316



TITLE :
2 X 660 MW TALCHER THERMAL POWER
PROJECT STAGE-III

SPECIFICATION NO. PE-TS-497-164-W001

VOLUME – IIB

TECHNICAL SPECIFICATION FOR EFFLUENT
TREATMENT PLANT

SECTION - IA

REV. No. 00

DATE : 18.12.2023

i)	Dissolving Basket	
	• Number	One (1) per Tank
	• Material of Construction	SS 316
B.	ALUM SOLUTION DOSING PUMPS	
a)	Number	Two (2) Number [1W+1S] for LAMELLA CLARIFIER/ TUBE SETTLER.
b)	Type of Pump	Positive displacement and Simplex Hydraulically operated diaphragm type with auto stroke adjustment.
c)	Location	Outdoor
d)	Fluid to be handled	10 % w/w Alum Solution.
e)	Service	To dose Alum solution to LAMELLA CLARIFIER/ TUBE SETTLER.
f)	Duty	Continuous and suitable for parallel operation
g)	Suction Condition	Flooded
h)	Rated Capacity, m ³ /hr	100 % requirement at full load condition of the plant
i)	Range of Operation (%)	10 – 100
j)	Pump Speed, (RPM)	1500 (max.)
k)	Pump Stroke speed per minute	100 (max.)
l)	Material of construction	
	• Liquid end (Pump head Valve, valve spring, Housing, etc.)	AISI 316
	• Diaphragm, Packing	PTFE
	• Shaft	Hardened steel (EN8-BS-970)/ AISI-316
m)	Accessories	Pumps shall be provided with accessories such as Y-type suction strainers, check valves, pressure dampeners, Pressure Gauge, safety relief valves along with recirculation to tank etc
n)	Type of drive	Electrical Motor
48.2	LIME DOSING SYSTEM (DOSING RATE = 30 PPM)	
A.	LIME DOSING TANK	
a)	Numbers required	Two (2) nos.
b)	Type	Vertical rectangular with flat bottom
c)	Type of fluid to be handled	6 % w/w Lime Solution.
d)	Effective capacity of each tank, m ³	Adequate to hold the quantity required for twelve (12) hours of operation for treatment of overall waste in LAMELLA CLARIFIER/ TUBE SETTLER + 20% margin excluding free board
e)	Design Pressure, Kg/sq. cm (g)	Atmospheric
f)	Design Temperature, 0C	80
g)	Material of Construction	RCC (IN BHEL SCOPE) with 2 coats of Bitumastic paint over 2 coats of primer.
h)	Protection	
	• Internal	Acid Proof Tile Lining
	• External	Not applicable
i)	Agitator along with drive motor and all other accessories	
	• Number	One (1) per Tank
	• Material of Construction	SS 316
j)	Dissolving Basket	
	• Number	One (1) per Tank
	• Material of Construction	SS 316
B.	LIME SOLUTION DOSING PUMPS	
a)	Number	Two (2) Number [1W+1S] for LAMELLA CLARIFIER/ TUBE SETTLER.



TITLE :
2 X 660 MW TALCHER THERMAL POWER
PROJECT STAGE-III

SPECIFICATION NO. PE-TS-497-164-W001

VOLUME – IIB

TECHNICAL SPECIFICATION FOR EFFLUENT
TREATMENT PLANT

SECTION - IA

REV. No. 00

DATE : 18.12.2023

b)	Type of Pump	Screw type
c)	Location	Outdoor
d)	Fluid to be handled	6 % w/w Lime Solution.
e)	Service	To dose Lime solution to LAMELLA CLARIFIER/ TUBE SETTLER.
f)	Duty	Continuous and suitable for parallel operation
g)	Suction Condition	Flooded
h)	Rated Capacity, m ³ /hr	100 % requirement at full load condition of the plant
i)	Range of Operation (%)	10 – 100
j)	Pump Speed, (RPM)	1500 (max.)
k)	Material of construction	
	Pump casing	2.5% Ni-Cast Iron to IS 210 FG 260
	Stator	EPDM rubber
	Impeller/Rotor	CF8M
	Shaft and shaft sleeve	SS 410
l)	Accessories	Pumps shall be provided with accessories such as Y-type suction strainers, check valves, pressure dampeners, Pressure Gauge, safety relief valves along with recirculation to tank etc
m)	Type of drive	Electrical Motor
38.	AIR BLOWER FOR SLUDGE SUMP	
a)	Number	Two (2) (2X100 %) for Sludge Sump
b)	Type	Rotary Twin Lobe Type
c)	Duty	Intermittent
d)	Capacity & Head	As required
e)	MOC of casing, cover, stator	CI as per IS 210 FG 260
f)	MOC of shaft	Carbon steel to BS-970 En-8/ANSI-I045
g)	Impeller/Lobes	Carbon steel to BS-970, EN9 Forged
h)	Accessories Required	Acoustic Enclosures, Suction Filter, Silencer, relief Valve etc
i)	Location	Outdoor
39.	CHEMICAL STORAGE SPACE (In industrial shed)	
48.1	STORAGE AREA OF CHEMICALS	15 days
48.2	WEIGHING SCALE	
a)	Type	Platform & dial type/Electronic Type
b)	Number	One (1)
c)	Capacity	0-500 Kgs
48.3	ELECTRIC HOIST	
a)	Type	Electric monorail in chemical dosing area
b)	Number	One (1)
c)	Capacity	1 Ton
48.4	Safety arrangement	
a)	Safety shower and Eye wash fountain	One (1) number safety shower and two (2) numbers eye wash fountain shall be provided by bidder
b)	Personal protection	Two sets of safety equipment each comprising PVC protection suits with hoods, rubber boots, face visors and thick PVC gauntlets shall be provided by the bidder.
40.	OVERHEAD SERVICE WATER (E15)	
a)	Number required	One (1) nos.
b)	Effective Capacity, m3	To cater the requirement of chemical preparation for Alum and Lime dosing for 24 hrs and flushing requirement of equipment.
c)	Material of Construction	RCC (IN BHEL SCOPE)
d)	Type	Rectangular with Flat bottom, Over head on EQMS Room
41.	FLUSHING PUMPS	



TITLE :
2 X 660 MW TALCHER THERMAL POWER
PROJECT STAGE-III

SPECIFICATION NO. PE-TS-497-164-W001

VOLUME – IIB

TECHNICAL SPECIFICATION FOR EFFLUENT
TREATMENT PLANT

SECTION - IA

REV. No. 00

DATE : 18.12.2023

a)	Number required	Two (1W+1S) nos.
b)	Type	Horizontal Centrifugal type
c)	Location	Outdoor
d)	Fluid to be handled	Service Water
e)	Duty	Intermittent
f)	Rated capacity, each m3/ hr.	10
g)	Pump Speed, RPM (max.)	1500
h)	Minimum Head to be developed at rated capacity, MLC	As per System Requirements
i)	Material of Construction	
	• Casing	2.5% Ni Cl IS:210 GR. FG 260, S-0.1 (max.) P-0.15 (max.)
	• Stuffing box, Gland	2.5% Ni Cl IS:210 GR. FG 260
	• Impeller	ASTM A351 CF8M
	• Shaft, Shaft coupling, shaft sleeves	SS 410
	• Column pipe & discharge pipe, shaft enclosing tube	CS as per IS:2062 or eq. (Min. Thickness 8 mm)
	• Gland packing	TIWA
	• Gasket	Neoprene Rubber
	• Bolts & nuts	SS for coming in water contact else CS
	• Base plate and soleplate	CS (min. 10 thick)
42.	BELT TYPE OIL SKIMMER	
a)	Type	Portable Belt Type Oil Skimmer
b)	Location	To be used portably in TG Area sumps E1A, E1B, E2A, E2B
c)	Capacity	To Cater the requirements for either above mentioned TG Area sumps
d)	MOC	As per system requirements
43.	PRE-FILTER BACKWASH WATER SUMP UNIT-1	
a)	Number required	One (1) nos.
b)	Effective Capacity, m3	30 m3
c)	Material of Construction	RCC (IN BHEL SCOPE)
d)	Type	Underground, Rectangular with Flat bottom
e)	Type of fluid to be handled	Pre-Filter Backwash Water (DM Waste water) form CPU Unit-1
44.	PRE FILTER BACKWASH WATER PUMPS UNIT-1	
a)	Number required	Two (1W+1S) nos.
b)	Type	Vertical sump type (Open Impeller)
c)	Location	Outdoor
d)	Fluid to be handled	Pre-Filter Backwash Water (DM Waste water) form CPU Unit-1
e)	Duty	Intermittent
f)	Rated capacity, each m3/ hr.	12.5
g)	Pump Speed, RPM (max.)	1500
h)	Minimum Head to be developed at rated capacity, MLC	As per System Requirements
i)	Material of Construction	
	• Casing	ASTM A743 CF3M (SS316L)
	• Discharge /Column Pipe	ASTM A743 CF3M (SS316L)
	• Impeller / Shaft	ASTM A743 CF3M (SS316L)
	• Shaft coupling, shaft	SS 410



TITLE :
2 X 660 MW TALCHER THERMAL POWER
PROJECT STAGE-III

SPECIFICATION NO. PE-TS-497-164-W001

VOLUME – IIB

TECHNICAL SPECIFICATION FOR EFFLUENT
TREATMENT PLANT

SECTION - IA

REV. No. 00

DATE : 18.12.2023

	sleeves	
	<ul style="list-style-type: none"> Bolts & nuts 	SS 316L (wetted)
	<ul style="list-style-type: none"> Base plate and soleplate 	CS (min. 10mm thick)
45.	PRE-FILTER BACKWASH WATER SUMP UNIT-2	
a)	Number required	One (1) nos.
b)	Effective Capacity, m3	30 m3
c)	Material of Construction	RCC (IN BHEL SCOPE)
d)	Type	Underground, Rectangular with Flat bottom
e)	Type of fluid to be handled	Pre-Filter Backwash Water (DM Waste water) form CPU Unit-2
46.	PRE FILTER BACKWASH WATER PUMPS UNIT-2	
a)	Number required	Two (1W+1S) nos.
b)	Type	Vertical sump type (Open Impeller)
c)	Location	Outdoor
d)	Fluid to be handled	Pre-Filter Backwash Water (DM Waste water) form CPU Unit-2
e)	Duty	Intermittent
f)	Rated capacity, each m3/ hr.	12.5
g)	Pump Speed, RPM (max.)	1500
h)	Minimum Head to be developed at rated capacity, MLC	As per System Requirements
i)	Material of Construction	
	<ul style="list-style-type: none"> Casing 	ASTM A743 CF3M (SS316L)
	<ul style="list-style-type: none"> Discharge /Column Pipe 	ASTM A743 CF3M (SS316L)
	<ul style="list-style-type: none"> Impeller / Shaft 	ASTM A743 CF3M (SS316L)
	<ul style="list-style-type: none"> Shaft coupling, shaft sleeves 	SS 410
	<ul style="list-style-type: none"> Bolts & nuts 	SS 316L (wetted)
	<ul style="list-style-type: none"> Base plate and soleplate 	CS (min. 10mm thick)
47.	PIPING	All the piping shall generally be conforming to the requirements specified in the Chapter titled "General Technical Requirement Of Low Pressure Piping" considering the following aspects as minimum requirement:
	Raw water & Clarified water	Carbon Steel: IS: 1239 Part-I (Heavy grade-Black), ASTM-A-53 Type-E Grade B / ASTM A 36 /IS: 3589 - Grade 410; / IS-2062 Gr.-B (for fabricated from plates) / Equivalent
	Coagulant (Alum)	CPVC as per ASTM F441 CPVC 4120 Schedule 80
	Lime slurry/Solution/ Suspensions	CPVC as per ASTM F441 CPVC 4120 Sch. 80
	Sludge	1) GRP as per ASTM D3517/ AWWA C950-88/AWWA M45 2) HDPE as per ASTM D3350 CL 34543C, FM Class 150/ IS:4984 or Equivalent for buried portion 3) Cast Iron Class A as per IS 1536 (for only from Lamella Clarifier/Tube Settler to Sludge Sump)
	Chemical Waste from vessels and tanks	1) HDPE as per ASTM D3350 CL 34543C, FM Class 150/ IS: 4984 or Equivalent for buried portion.
	Demineralised Water (Pre-Filter Backwash Water)	Stainless Steel: Stainless steel to ASTM A312, Gr. 304 Sch.40s.



TITLE :
2 X 660 MW TALCHER THERMAL POWER
PROJECT STAGE-III

SPECIFICATION NO. PE-TS-497-164-W001

VOLUME – IIB

TECHNICAL SPECIFICATION FOR EFFLUENT
TREATMENT PLANT

SECTION - IA

REV. No. 00

DATE : 18.12.2023

48.	VALVES	All the valves shall generally be conforming to the requirements specified in the Chapter titled “General Technical Requirement of Low-Pressure Piping” considering the following aspects as minimum requirement:
48.1	Coagulant (Alum) Services	<p>i. Type of Valves</p> <p><u>For Isolation</u></p> <p>a) Saunder’s Patented Diaphragm Valves</p> <p>b) Ball Valves in CPVC pipes</p> <p><u>For non-return / Check</u></p> <p>Swing Check type /Dual Plate type</p> <p>ii. Material of Construction Valves</p> <p><u>Diaphragm Valves</u></p> <p>a) Body shall be Cast Iron to IS: 210 Gr FG 260/ ASTM A 48 Cl.40; BS: 1452 Gr.220/Equivalent. OR Cast Steel to ASTM. A 216GR. WCB and Body shall be internally lined with Soft Natural rubber, Ebonite or Polypropylene</p> <p>b) Diaphragm shall be shall be of reinforced rubber /Hypalon/ approved equivalent</p> <p>c) Stem, Compressor & Bush shall be Stainless steel Construction</p> <p>Ball Valves in CPVC Pipe lines</p> <p>a) Body, Ball & stem shall be of CPVC</p> <p>b) Seat ring & Packing shall be EPDM / or equivalent</p> <p><u>Check Valves</u></p> <p>a) Body & Cover, Hinge Disk/Door shall be Cast Iron to IS: 210 Gr FG 260/ ASTM A 48 Cl.40; BS: 1452 Gr.220 or Eqvt and shall be lined with natural Rubber, PTFE or Viton or Stainless Steel – 316</p> <p>b) Hinge Pin and Door/Disc Pin shall be of Cast steel ASTM A 216 Gr. WCB and shall be coated with PVDF, or suitable elastomer or Stainless Steel – 316</p> <p>c) Disc facing ring and Body Seat rings shall be Stainless Steel</p> <p>d) Bearing bushes shall be SS – 316</p> <p>e) Material of construction of spring in dual type valve shall be of INCONEL or better</p>
48.2	Lime slurry/Solution/ Suspensions	<p>i. Type of Valves</p> <p><u>For Isolation</u></p> <p>Non-lubricated Plug Valves</p> <p><u>For non-return / Check</u></p> <p>Swing Check type /Dual Plate type</p> <p>ii. Material of Construction Valves</p> <p><u>Plug Valves</u></p> <p>a) Body shall be Cast Iron to IS: 210 Gr FG 260 / ASTM A 48 Cl.40; BS: 1452 Gr.220 or Eqvt</p> <p>b) Plug shall be Stainless steel to AISI 316</p> <p>c) Body Sleeve & Seat shall be PTFE</p> <p>d) Gland & Gland nut shall be SS 304/316</p> <p>e) Cover shall be of Cast Steel to ASTM A 216 Gr WCB</p> <p><u>Check Valves</u></p> <p>a) Body & Cover, Hinge Disk/Door shall be Cast Iron to IS: 210 Gr FG 260 / ASTM A 48 Cl.40; BS: 1452 Gr.220 or Eqvt and shall be lined</p>



TITLE :
2 X 660 MW TALCHER THERMAL POWER
PROJECT STAGE-III

SPECIFICATION NO. PE-TS-497-164-W001

VOLUME – IIB

TECHNICAL SPECIFICATION FOR EFFLUENT
TREATMENT PLANT

SECTION - IA

REV. No. 00

DATE : 18.12.2023

		<p>with natural Rubber, PTFE or Viton or Stainless Steel – 316</p> <p>b) Hinge Pin and Door/Disc Pin shall be of Cast steel ASTM A 216 Gr. WCB and shall be coated with PVDF, or suitable elastomer or Stainless Steel – 316</p> <p>c) Disc facing ring and Body Seat rings shall be Stainless Steel</p> <p>d) Bearing bushes shall be SS-316</p> <p>e) Material of construction of spring in dual type valve shall be of INCONEL or better</p>
48.3	Sludge	<p>i. Type of Valves</p> <p><u>For Isolation</u> Gate or Sluice or Knife edge type Slide Valves</p> <p><u>For non-return / Check</u> Swing Check type /Dual Plate type</p> <p>ii. Material of Construction</p> <p><u>Gate / Sluice / Knife Edge Slide Valve</u></p> <p>a) Body,Disc : Cast Iron</p> <p>b) Stem : Stainless Steel AISI 420</p> <p>d) Packing : PTFE</p> <p>e) Gland & Gland nut : AISI 420</p> <p>f) Hand wheel : Cast Iron</p> <p><u>Check Valves</u></p> <p>a) Body & Cover, Hinge Disk/Door shall be Cast Iron BS:1452 Gr.220 or Eqvt</p> <p>b) Hinge Pin and Door/Disc Pin shall be of Cast steel ASTM A 216 Gr. WCB / High tensile Brass or BS: 2872 equivalent.</p> <p>c) Disc facing ring and Body Seat rings shall be Stainless Steel.</p> <p>d) Bearing bushes shall be Leaded tin Bronze.</p> <p>e) Material of construction of spring in dual type valve shall be of INCONEL or better</p>
48.4	Demineralised Water (Pre-Filter Backwash Water)	<p>i. Type of Valves</p> <p><u>For Isolation</u> a) Butterfly type</p> <p><u>For non-return / Check</u> a) Lift Check type/Swing Check /Dual Plate type for sizes upto 40 mm NB b) Swing Check or Dual Plate type valve for sizes 50 mm NB & above</p> <p>ii. Material of Construction Valves</p> <p><u>Butterfly Valves</u></p> <p>a) Body shall be of Stainless Steel-316</p> <p>b) Disc shall be of Stainless Steel-316.</p> <p>c) Shaft shall be of Stainless steel to ASTM. A 296 Gr. CF8M/AISI 316/ AISI 420 /BS:970 Gr.316; BS: 970 Gr.420 S45.</p> <p>d) Seat rings shall be Nitrile rubber /Hypalon/Eqvt.</p> <p><u>Check Valves</u></p> <p>a) Body & Cover, Hinge Disk/Door -Stainless Steel – 316</p> <p>b) Hinge Pin and Door/Disc Pin shall be of Stainless Steel – 316</p> <p>c) Disc facing ring and Body Seat rings shall be Stainless Steel</p>



TITLE :
2 X 660 MW TALCHER THERMAL POWER
PROJECT STAGE-III

SPECIFICATION NO. PE-TS-497-164-W001

VOLUME – IIB

TECHNICAL SPECIFICATION FOR EFFLUENT
TREATMENT PLANT

SECTION - IA

REV. No. 00

DATE : 18.12.2023

		<p>d) Bearing bushes shall be SS – 316.</p> <p>e) Material of construction of spring in dual type valve shall be of INCONEL or better</p>
48.5	<p>For normal water (portable/service water) & Waste Water</p>	<p>i. Type of Valves</p> <p>For Isolation</p> <p>a) Butterfly or Saunder's Patented Diaphragm Valves upto 200 mm NB</p> <p>b) Butterfly type for Sizes 250 mm NB & above</p> <p>For non-return / Check</p> <p>a) Lift Check type/Swing Check /Dual Plate type for sizes upto 40 mm NB</p> <p>b) Swing Check or Dual Plate type valve for sizes 50 mm NB & above</p> <p>ii. Material of Construction Valves</p> <p><u>Diaphragm Valves</u></p> <p>The Diaphragm shall conform to following requirement i) Design standard: BS: 5156 or equivalent of required rating/class. (Minimum rating of valves shall be PN 10). Type: Flanged and lined body ends, sealed bonnet, weir pattern, tight shut off type.</p> <p>a) Body , Bonnet: Cast iron IS 210 Gr. FG 260 or equivalent or Cast steel ASTM A-216 Gr. WCB</p> <p>b) Body lining : Soft natural rubber, ebonite , Polypropylene</p> <p>c) Hand wheel : Cast Iron</p> <p>d) Compressor : Stainless Steel</p> <p>e) Stem and Bush : Stainless Steel</p> <p><u>Butterfly Valves</u></p> <p>Butterfly valves shall be of Lugged-wafer type of low leakage rate confirming to AWWA-C-504 class 150 (min.) or BS:5155 PN 10 (min.)</p> <p>a) Body: ASTM A48, Gr. 40 with 2% Ni / IS: 210. Gr. FG-260, with 2% Ni / SG iron BSEN 1563, Gr EN GJS-400-15 with 2%Ni and epoxy coated.</p> <p>b) Disc: SS 316.</p> <p>c) Shaft: BS 970 431 S: 291 / EN 57, or AISI-410 or AWWA-permitted shaft material equivalent to EN-57/AISI-410 or better.</p> <p>d) Seat rings: 18-8 Stainless steel</p> <p>e) Seal: Nitrile rubber, EPDM, Hypalon</p> <p>All the butterfly valves shall be provided with Hand wheel or lever as per the requirements. All the butterfly valves shall be provided with an indicator to show the position of the disc. Flanges shall conform to ANSI B 16.5 Cl.150 (min).</p> <p><u>Ball Valves</u></p> <p>a) Type :Full bore</p> <p>b) Rating: PN 10 (min).</p> <p>c) Body: ASTM A216 Gr. WCB</p> <p>d) Ball: ASTM A276 TYPE 316</p> <p>e) Seat ring: PTFE</p>



TITLE :
**2 X 660 MW TALCHER THERMAL POWER
PROJECT STAGE-III**

SPECIFICATION NO. PE-TS-497-164-W001

VOLUME – IIB

**TECHNICAL SPECIFICATION FOR EFFLUENT
TREATMENT PLANT**

SECTION - IA

REV. No. 00

DATE : 18.12.2023

f) Stem: ASTM A276 TYPE 316

g) Seat: Nitrile rubber, PTFE

Check Valves

Body – Cast iron IS 210 Gr. FG 260 or equivalent

Disc/ door –ASTM A351 Gr. CF8

Hinged pin – SS 316

Piston – SS 316

Other Requirements:

- 1) Butterfly valves shall conform to design standard latest revision of AWWA C-504/EN 593/equivalent standard of required class/rating.
- 2) Plug valves shall be designed as per BS: 5353 Cl.150 or equivalent.
- 3) Valves for alum solution shall be Saunders's patented Diaphragm type designed as per BS: 5156 or approved equivalent standard.
- 4) Sluice/Gate Valves shall conform to BS: 5150 (BS: 5163 PN 16) PN16, IS:14846 of rating PN 1.0 (min.). Stem, seat ring and wedge facing ring shall be of stainless-steel construction. Other parts shall be as per IS: 14846 /BS:5163). Flanges shall be designed as per ANSI B 16.5 Cl. 150 (min.) to meet with the piping flanges. Valves shall be of outside screw and rising stem type. Gate valves for sizes below 50 NB and below shall conforms to IS:778 Class-2/ANSI B16.34 straight, rising stem; without side screw.
- 5) Sluice/Isolation gates shall be provided with the following accessories in addition to the standard items:
 - a. Hand wheel
 - b. Manual Gear reduction unit operator for valves 200 NB and above
 - c. Bypass valve for valve of sizes 350 NB and above.
 - d. Draining arrangement wherever required.
 - e. Arrow indicating flow direction.
 - f. Position indicator.
- g. Sluice/Isolation gates shall be provided with back seating bush to facilitate gland renewal during full open condition.
- 6) Design standard for Gates shall be IS: 3042 or Equivalent.

Material of Construction

- a. Frame and Door: Cast Iron IS:210 Gr.260
- b. Spindles, bolts & nuts: M.S. to IS:2062
- c. Face & seat rings: Gun metal (as per IS: 3042).
- 7) All the parts of gates shall be applied with the coats of heavy duty bitumastic paint. Each of the gates shall be provided with hand wheel and a position indicator.
- 8) Sluice valve/knife edge type slide valves shall design by IS 14846. Plug valves shall be used for the application of lime slurry/lime solutions conforming to BS: 5353 Class 150 or Equivalent.
- 9) Valves will be used to start/stop or control flow. Gates will be primarily used for isolation of flow in open channels although these should be capable of throttling the flow too. However, contractor can provide either isolation gates or butterfly valves in various RCC (IN BHEL SCOPE) tanks/pits/sumps such as sludge pit, etc. Sample valves will be used in sample collection lines. Unless otherwise specified all the valves shall be supplied with counter flanges by the Contractor.
- 10) All valves shall be suitable for service conditions i.e. flow, temperature and pressure under which they are required to operate. All the valves shall be of standard pressure rating of the relevant design standard. Nonstandard pressure rating shall not be accepted. The pressure and temperature rating of the valve shall not be less than the maximum expected pressure and temperature plus 5% additional margin of the system in which valves are proposed to be installed. The pressure rating of individual piping system components such as valves, flanges etc. shall however be not less than that specified.

BOQ for receipt of material at Site, Unloading, Inspection, Verification, Storage, up -keeping, Safety & Security, Material Handling. ETC works shall be provided by the equipment supplier.

Indicative BOM of the supplies is attached as below which may be changed during engineering stage.

SN	ITEM DESCRIPTION	Unit	QTY
1	Supply & ETC of Main Lighting Distribution Board (MLDB) (Comprising of 415V, 3-Ph, 4-wire bus and one number 100kVA Lighting transformer, 160A Incomer TPN MCCB (including 160/1A CT, Current & Voltage Transducers, Ammeter & Voltmeter with selector switches etc.); Ongoing feeders 6 Nos. 63A TPN SFU	Nos.	2
2	Supply & ETC of Emergency Lighting Distribution Board (ELDB) (Comprising of 415V, 3-Ph, 4-wire bus and one number 100kVA Lighting transformer, 160A Incomer TPN MCCB (including 160/1A CT, Current & Voltage Transducers, Ammeter & Voltmeter with selector switches etc.); Ongoing feeders 4 Nos. 63A TPN SFU	Nos.	1
3	Supply & ETC of Indoor Lighting Panel - Type LP-1	Nos.	3
4	Supply & ETC of Indoor Lighting Panel - Type LP-2	Nos.	2
5	Supply & ETC of Indoor DC Lighting Panel DCLP	Nos.	1
6	Supply & ETC of Outdoor Lighting Panel - Type LP-1	Nos.	2
7	Supply & ETC of Outdoor Lighting Panel - Type LP-2	Nos.	2
8	Supply & ETC of Switchboard - Type SWB-1	Nos.	20
9	Supply & ETC of Switchboard - Type SWB-2	Nos.	25
10	Supply & ETC of Switchboard - Type SWB-3	Nos.	3
11	Supply & ETC of Switchboard - Type SWB-4	Nos.	1
12	Supply & ETC of Switchboard - Type SWB-5	Nos.	1
13	Supply & ETC of MCB Box (I/C: 415V, 3-PH, 32A TPN MCB; O/G: 5 Nos. 1-PH, 6A MCB)	Nos.	1
14	Supply & ETC of Receptacle - 6/16A (Decorative) RB type	Nos.	10
15	Supply & ETC of Receptacle - 20A (Industrial) RA type	Nos.	10
16	Supply & ETC of Receptacle - 20A (Industrial) RC type - Flameproof	Nos.	2
17	Supply & ETC of Receptacle - 415 V, 63A, 3-PH (Industrial) Indoor Receptacle	Nos.	5
18	Supply & ETC of Receptacle - 63A, 415V, 3-Phase, 4-Pin Interlocked industrial grade rotatry switch socket, Outdoor Receptacle (Necessary arrangement for looping incoming supply cables shall be provided)	Nos.	2
19	Supply & ETC of Receptacle - 415V, 250A. 3-Phase, 4-Pin TPN MCCB Industrial type Outdoor Receptacle with earthing contacts - for Oil filtration machine (Necessary arrangement for looping incoming supply cables shall be provided)	Nos.	1
20	Supply & ETC of Outdoor Junction box	Nos.	3
21	Supply & ETC of Indoor lighting fixtures - LED Decorative recess mounted lighting fixture Type FC30	Nos.	80
22	Supply & ETC of Indoor lighting fixtures - LED Industrial batten surface mounted lighting fixture Type FC06	Nos.	40
23	Supply & ETC of Indoor lighting fixtures - Capsule LED corrosion proof lighting fixture Type FC81	Nos.	5
24	Supply & ETC of Indoor lighting fixtures (GIS Building) - LED High bay lighting fixture Type SB03	Nos.	15
25	Supply & ETC of Emergency DC lighting fixtures - DC Industrial bulkhead lighting fixture for Non-false Ceiling Areas	Nos.	10
26	Supply & ETC of Emergency DC lighting fixtures - DC Downlighter for False Ceiling Areas	Nos.	10
27	Supply & ETC of Street lighting fixtures - LED Street light fixture Type SS63	Nos.	35
28	Supply & ETC of Flood lighting fixtures - LED Flood light fixture Type SF66	Nos.	75
29	Supply & ETC of LED Post Top Lantern fixture - Outdoor type	No.	5
30	Supply & ETC of Marine type luminaires 100W lamp with accessories	No.	1
31	Supply & ETC of Aviation light for High mast	Nos.	5
32	Supply & ETC of Occupancy based Infra Red Sensors	Nos.	10
33	Supply & ETC of Exit Sign Boards	Nos.	5
34	Supply & ETC of Exhaust fans - with metal sheet crawl & bird screen for Toilets	Nos.	3
35	Supply & ETC of Exhaust fans - with metal sheet crawl & bird screen for Pantry	Nos.	1
36	Supply & ETC of Ceiling fans 1200mm sweep with electronic regulator, fan hook, suspension rod etc.	Nos.	3
37	Supply & ETC of Wall mounted fans 400mm sweep	Nos.	10
38	Supply of Free-standing Aluminium Ladder, height adjustable (from 5m to 10m height)	Nos.	1
39	Supply, Civil works & ETC of 30m high Lighting High Mast with Lantern Carriage (Winch type) for Switchyard Lighting along with feeder pillar & junction box	Nos.	2
40	Supply, Civil works & ETC of 8m High Lighting Pole (including JB) for Street Lighting	Nos.	30
41	Supply, Civil works & ETC of 4m high Lighting Pole (including JB) for Post-top Lantern	Nos.	5
42	Supply & ETC of Galvanized rigid conduit of 20mm size with accessories	Mtr.	2000
43	Supply & ETC of Galvanized rigid conduit of 25mm size with accessories	Mtr.	500
44	Supply & ETC of Galvanized heavy duty steel conduit of 25mm size with accessories with additional epoxy coating for corrosive areas	Mtr.	50
45	Supply & ETC of Galvanized rigid conduit of 40mm size with accessories	Mtr.	10

SN	ITEM DESCRIPTION	Unit	QTY
46	Supply & ETC of 20mm Flexible conduits made with bright, cold rolled annealed and electro galvanized mild steel strips and coated with PVC	Mtr.	50
47	Supply & ETC of 1C, 1.5 sqmm PVC insulated stranded Cu. Wire Red/Yellow/Blue/Black/Grey (ISI marked with valid CML number). Colour coded.	Mtr.	1000
48	Supply & ETC of 1C, 2.5 sqmm PVC insulated stranded Cu. Wire Red/Yellow/Blue/Black/Grey (ISI marked with valid CML number). Colour coded.	Mtr.	2500
49	Supply & ETC of 1C, 4 sqmm PVC insulated stranded Cu. Wire Red/Yellow/Blue/Black/Grey (ISI marked with valid CML number). Colour coded.	Mtr.	500
50	Supply & ETC of 2C, 2.5 sqmm PVC insulated stranded Cu. Wire	Mtr.	500
51	Supply & ETC of 1C, 10 sqmm PVC insulated stranded Al. Wire	Mtr.	500
52	Supply & ETC of Earthing Material - 25x6mm GI Flat	Mtr.	100
53	Supply & ETC of Earthing Material - GI wire for Earthing of size 16 SWG	Mtr.	2000
54	Supply & ETC of Portable 24V halogen lamp unit	Nos.	1
55	Supply & ETC of 5A, 24V industrial type sockets	Nos.	1
56	Supply & ETC of Temperature Transducer	Nos.	5
57	Supply & ETC of Telephone points- single outlet telephone socket including cable/wire and accessories	Nos.	10
58	Supply & ETC of Telephone JB suitable for 20 pair Indoor type	Nos.	1
59	Supply & ETC of Supply & ETC of 2 wire telephone cable (ISI marked).	Mtr.	200
60	Supply & ETC of LAN points including accessories	Nos.	5
61	Supply & ETC of LAN Cable	Mtr.	200
62	Supply & ETC of Erection hardwares for indoor like 3 way, G.I., circular J.B.(20mm and 25mm), 4 way, G.I., circular J.B.(20mm and 25mm), 90deg, G.I., Inspection Bend (20mm and 25mm), 90deg, G.I., Normal Bend (20mm and 25mm), Heavy duty, Saddle with base (20mm and 25mm), Heavy duty, Saddle without base (20mm and 25mm), M4X25mm, steel screw with nut and washer, G.I. check nut/lock nut (20mm and 25mm), PVC Rawl plug, 6mm, Wooden screw, 35mm, Earth clip/clamp (20mm and 25mm), Cleat fabrication out of 25x6mm M.S. flat (for hanging conduit in false ceiling areas, Anchor fastner (M10x75mm for cleats, M12x75mm for lighting panels), Rubber bush (20mm and 25mm), 20mm PVC, flexible conduit, 25mm, PVC conduit, Coupling, Swing out bracket, 20mm, Heavy duty, ball socket, Machine screw (for fixing surface mounting fixtures on circular J.B.), PVC closure (20mm and 25mm), Reducer (20mm and 25mm), GI wire/ FRLSH cu wire for earthing, lugs & glands for wires/cables, indoor junction box etc, as required, for completion of switch yard indoor illumination system	Lot	1
63	Supply & ETC of Erection hardwares for outdoor like 20x1.5mm Aluminium flat, M12x40mm, G.I. Bolt with nut and washer for fixing outdoor lighting panels, M6x30mm, G.I. Bolt with nut and washer for fixing control gear boxes, M8x30mm, G.I. Bolt with nut and washer for fixing outdoor J.B.s, SLP, M10x35mm, G.I. Bolt with nut and washer for fixing outdoor lighting fixtures, Earth wire from J.B. to lighting fixtures, Mounting brackets for outdoor lighting fixtures, GI wire for earthing, lugs & glands for wires/cables etc, as required, for completion of switch yard outdoor illumination system	Lot	1
64	Services of Illumination System Design - Lux Level Design Calculations for Indoor & Outdoor area	Lot	1
65	Services of Illumination System Design -Lighting Layout for indoor & Outdoor area	Lot	1
66	Services of Illumination System Design -Conduit Layout for indoor areas	Lot	1
67	Services of Illumination System Design -Cable Schedule, Power Distribution scheme, Control Schemes, any other drawing, document, design, Preparation of BOQ required for complete illumination system	Lot	1
68	Services of Site Test - Lux Level Measurement and demonstration to customer at site including arrangement of necessary test equipment on returnable basis	Lot	1
69	Laying, Testing & Commissioning of 2C, 2.5 sq mm PVC insulated, Armoured Cu. Cable	Mtr.	4000
70	Laying, Testing & Commissioning of 2C, 6 sq mm PVC insulated, Armoured Al. Cable	Mtr.	500
71	Laying, Testing & Commissioning of 4C, 6 sq mm PVC insulated, Armoured Al. Cable	Mtr.	500
72	Laying, Testing & Commissioning of 4C, 16 sq mm PVC insulated, Armoured Al. Cable	Mtr.	3000
73	Laying, Testing & Commissioning of 3.5C, 70 sq mm PVC insulated, Armoured Al. Cable	Mtr.	2000
74	Laying, Testing & Commissioning of 3.5C, 240 sq mm XLPE insulated, Armoured Al. Cable	Mtr.	250
75	Laying of 50 mm GI conduits at a depth of 300 mm including excavation, backfilling, making & repairing of walls in trenches, cutting, threading, fixing of sockets/bends where required etc to complete. Also between pull pit boxes to JB/LP	Mtr.	250
76	Laying of 100 mm GI conduits at a depth of 300 mm including excavation, backfilling, making & repairing of walls in trenches, cutting, threading, fixing of sockets/bends where required etc to complete. Also between pull pit boxes to JB/LP	Mtr.	250

SN	ITEM DESCRIPTION	Unit	QTY
77	Construction of Pull Pit Boxes of sizes 400 mm x 400 mm x 400 mm at the free ends and turning of GI pipes if pipe length exceeds 4M	No.	5
78	Earthing using 50x6 mm GI Flat	Mtr.	250
79	Earthing using 75x12 mm GI Flat	Mtr.	250
80	Earthing using 40mm Dia, 3m long MS Rod	Mtr.	180
81	Type Test of LED Lighting Fixture - High Bay Fixture	Lot	1
82	Type Test of LED Lighting Fixture - Well Glass Fixture	Lot	1
83	Type Test of LED Lighting Fixture - Street Light Fixture	Lot	1
84	Type Test of LED Lighting Fixture - Surface mounted type Fixture	Lot	1
85	Type Test of LED Lighting Fixture - Recessed mounted type Fixture	Lot	1