




An ISO 9001
Company

Bharat Heavy Electricals Limited

(High Pressure Boiler Plant)

Tiruchirappalli – 620014, TAMIL NADU, INDIA

CAPITAL EQUIPMENT / MATERIALS MANAGEMENT

ENQUIRY		Phone: +91 431 257 5443/ 7297	
NOTICE INVITING TENDER		Email : smams@bhel.in, hari.r@bhel.in	
Web : www.bhel.com			
TWO PART BID	Enquiry Number:	Enquiry Date:	Due date for submission of quotation:
Tender to be submitted in two Parts	2742100002	01.02.2021	03.03.2021
You are requested to quote the Enquiry number date and due date in all your correspondence. This is only a request for quotation and not an order. Please note that under any circumstances both delayed offer and late offers will not be considered. Hence vendors are requested to ensure that the offer is reaching physically our office before 14:00 hrs on the Date of tender opening.			
Item	Description		Quantity
10	20 Ton Battery Operated Trolley as per the technical specification & commercial conditions applicable (to be downloaded from web site www.bhel.com or https://eprocure.gov.in/epublish/app)		01 No.
Important points to be taken care during submission of offer			
1. Delivery terms shall be FOR, BHEL Stores, PPPU, Tirumayam, Pudukkottai Dt- 622 507, Tamilnadu. 2. Compliance Form TMM/ IND/ 04A to be filled and enclosed along with the offer failing which, the offer will not be considered for evaluation. 3. Delivery period required is 10 Weeks from the date of Purchase Order. 4. EMD for this Tender will be (INR): 40,000.00 5. Erection and commissioning activities shall be done by the supplier, at BHEL, Tirumayam works. 6. Time period required for Erection and Commissioning activities shall be 3 weeks from the date of intimation by BHEL 7. Procurement of the item through this NIT will be as per Public Procurement (Preference to Make in India), Order 2017 dated 04.06.2020 by DPIIT (DPIIT Order No. P-45021/2/2017-PP (BE-II) dated 04.06.2020), to encourage 'Make in India ' and promote manufacturing and production of goods and services in India. 8. All updates, amendments, corrigenda, etc., (if any), for each tender will be posted only on the above websites from time to time, as and when required, until each tender is opened. There will be no publication of such updates, amendments, corrigenda, etc., through newspapers or any other media.			
BHEL's General guidelines / instructions (refer MM/CE/GENL/001- EMD), compliance form and technical specification can be downloaded from BHEL web site http://www.bhel.com or from https://eprocure.gov.in/epublish/app under Enquiry reference "2742100002".			
Tenders should reach us before 14:00 hours on the due date Tenders will be opened at 14:30 hours on the due date Tenders would be opened in presence of the tenderers who have submitted their offers and who may like to be present		Yours faithfully, For BHARAT HEAVY ELECTRICALS LIMITED  R. HARI Engineer MM / Capital Equipment BHEL, TRICHY - 620 014 Engineer / MM/ Capital Equipment	


Technical Specification Part – A
Battery Operated Material Transfer Trolley

S.No	BHEL Specification	Vendor's Offer
1.0	QUALIFYING CRITERIA	
1.1	The BIDDER / VENDOR (OEM) shall have at least FIVE Years of Experience in the Design, Manufacture & Supply of "Battery Operated Material Transfer Trolley".	
1.2	Only those vendors (OEMs), who have Manufactured, supplied and commissioned at least ONE Battery Operated Material Transfer Trolley, similar to the machine specified under Part B, in the last Five years [as on date of this tender opening(first date)] should quote.	
1.3	Vendor has to submit at least ONE Performance Certificate from their customer, for satisfactory performance of Battery Operated Material Transfer Trolley supplied to them and such equipment is working satisfactorily for a minimum period of one year [as on date of this tender opening (first date)]. For obtaining the Performance certificate, a suggestive format is provided at the end of part-A.	
1.4	BHEL reserves the right to verify the information provided by the Vendor. In case the information provided by vendor is found to be false/ incorrect, the offer shall be rejected.	

2.0	INFORMATION TO BE PROVIDED BY VENDOR	
2.1	Vendor shall provide contact details (phone no & email id) including the address of his Agents / Service Centres in India.	
2.2	Details of Battery Operated Material Transfer Trolley supplied to BHEL units, if any. (Year of commissioning, Application, Type)	
2.3	The BIDDER/VENDOR to furnish Reference List of Customers (max 10 customers) including Contact details (phone no & email id) to whom trolley is supplied within 5 years.	


टी. डी. कार्थिकियन / T.D. KARTHIKEYAN
उप प्रबंधक / Deputy Manager
एम एस एल एच टीडी / M&S & TD
MES Mech. Maint. Planning & Systems
थिरुमयम - पोलीपीयू / BHEL - PPPU
थिरुमयम / Thirumayam - 622 507


पी. जे. सजी / P. J. SAJI
प्रबंधक / Manager
एम एस एल एच टीडी / M&S & TD
थिरुमयम - पोलीपीयू / BHEL - PPPU
थिरुमयम / Thirumayam - 622507


जे. तमिलवानन / J. THAMILVANAN
उप प्रबंधक / Deputy Manager
उत्पादन, टूल इंजीनियरिंग एवं इन्व्स्टीगेशन
Production, Tool Engineering and WTC
थिरुमयम - पोलीपीयू / BHEL - PPPU
थिरुमयम / Thirumayam - 622 507

Suggestive Format of Performance Certificate:

The performance certificate should be produced on **Customer's Letter Head**.

PERFORMANCE CERTIFICATE

- 1 Supplier of the machine
- 2 Make & Model of the M/C
- 3 Month & Year of Commissioning
- 4 Application for which M/C is used
- 5 Weight of the machine
- 6 Performance of the Machine
(Strike off whichever is not applicable) Satisfactory / Not Satisfactory
- 7 After sales service
(Strike off whichever is not applicable) Satisfactory / Not Satisfactory
- 8 Any Other remarks

Performance certificate issued date:


Signature & Seal of the Authority
Issuing the Performance Certificate

Contact details of issuing authority

Name & Designation:

Office No/ Mobile no:


Email ID:



टी. डी. कार्थिकेयन / T.D. KARTHIKEYAN
उप प्रबंधक / Deputy Manager
एम & एस मेकानिकल, मॉनिंग एवं सिस्टम
M&S Mech. Maint. Monitoring & Systems
बीएलपीयू - पीपीपीयू / BHEL - PPPU
तिरुमयम / Thirumayam - 622 607



पी. जे. साजि / P. J. SAJI
प्रबंधक / Manager
एम एंड एस एवं टीडी / M&S & TD
बीएलपीयू - पीपीपीयू / BHEL - PPPU
तिरुमयम / Thirumayam - 622507



जे. तमिलवानन / J. THAMILVANAN
उप प्रबंधक / Deputy Manager
उत्पादन, टूल इंजीनियरिंग एवं डब्ल्यूटीसी
Production, Tool Engineering and WTC
बीएलपीयू - पीपीपीयू / BHEL - PPPU
तिरुमयम / Thirumayam - 622 607

Technical specification for battery powered transfer car
[Carrying Capacity: 20 tons]

Sl. No	PARTICULARS / BHEL SPECIFICATIONS	BIDDER's OFFER
1.0.0	APPLICATION a) The proposed Transfer Car is intended for material handling within a large and heavy fabrication industry, on steel rails embedded in the shop floor. b) The Transfer Car will be put to use for continuous duty [three shifts in a day and for all the 365 days in an year]. c) The shop floor environment will be rough, dust prone, humid, welding fume filled and ambient temperature going upto 50° C. Bidder to note.	
2.0.0	SCOPE OF SUPPLY a. Design and Manufacture as per BHEL Tender Specifications. b. Assembly and Running Test before Despatch, at Supplier's Works. c. Supply in Modules / Sub-Assemblies d. Commissioning and Performance Prove-Out at BHEL Works e. Mechanical & Electrical Spares Bidder to confirm.	
3.0.0	TECHNICAL SPECIFICATIONS	
3.1.0	Pulling Capacity 20,000 kg Bidder to confirm.	
3.2.0	Rail Track Gauge 1676 mm [Broad Gauge] Bidder to confirm.	
3.3.0	Trolley Platform Length 6500 mm Bidder to confirm.	
3.4.0	Trolley Platform Width 2500 mm Bidder to confirm.	
3.5.0	Height from Rail Level 900 mm [Loading Platform Level] Bidder to confirm.	
3.6.0	No of Axles Two Bidder to confirm.	
3.7.0	Distance between Axles Minimum 3500mm Bidder to specify.	
3.8.0	Wheel Tread Diameter 500 mm Bidder to confirm.	
3.9.0	Motor DC SERIES MOTOR 3.5 HP 1700 RPM 36V Bidder to specify.	

Karthikeyan
01/01/2021

टी. डी. कार्थिकियन / T.D. KARTHIKEYAN
उप प्रबंधक / Deputy Manager
एम & एस मशीन, मैनूअल मॉन्निंग & सिस्टम
बीएचईएल - पीपीपीयू / BHEL - PPPU
तिरुमयम / Thirumayam - 622 507

Saji
01/01/21

बी. जे. साजि / B. J. SAJI
प्रबंधक / Manager
एम & एस एस एवं टीडी / M&S & TD
बीएचईएल - पीपीपीयू / BHEL - PPPU
तिरुमयम / Thirumayam - 622507

J. Thamilvanan
01-01-21

जे. तमिलवाणन / J. THAMILVANAN
उप प्रबंधक / Deputy Manager
उत्पादन, टूल इंजीनियरिंग एवं डब्ल्यूटीसी
बीएचईएल - पीपीपीयू / BHEL - PPPU
तिरुमयम / Thirumayam - 622 507

Technical specification for battery powered transfer car
[Carrying Capacity: 20 tons]

Sl. No	PARTICULARS / BHEL SPECIFICATIONS	BIDDER's OFFER
3.10.0	Haulage Speed Upto 30 m / min. Bidder to specify.	
4.0.0	CONFIGURATION & CONSTRUCTION	
4.1.0	Basic Design The transfer car shall be configured to run on BG [Broad Gauge] track with a sturdy steel structure, powered with a suitable DC motor (in conjunction with a gearbox and battery) and provided with controls, operator console, battery charger, etc., as per the details given under the following clauses. Bidder to note.	
4.2.0	TRANSFER CAR CARRIAGE a. The under frame shall be fabricated out of steel rolled beams and sections by welding. b. The top shall be covered with steel chequered plates of adequate thickness (not less than 8 mm) to withstand load capacity of the transfer car. c. The main members shall be adequately reinforced to withstand shock loads encountered in service. Bidder to confirm.	
4.2.1	Raw Material a. Only steel materials, tested and certified for quality by reputed inspection authorities, shall be used. b. Test Certificates to be produced for BHEL verification and form part of the documentation. Bidder to confirm.	
4.2.2	Welding Electrodes a. For all Horizontal Welding E 7018 Electrode only should be used. b. For all Vertical Welding E 7048 Electrode only should be used. Bidder to confirm.	
4.2.3	Welded Joint Testing All Butt Welded Joints (if carried out/though not preferred by BHEL) shall be subjected to 100% X-Ray Testing and X-Ray Films to be produced for BHEL evaluation and form part of the documentation. Bidder to confirm.	
4.2.4	Bottom Clearance The bottom most part of the components mounted under the trolley carriage shall have a minimum ground clearance of 100 mm. Bidder to specify.	

Damish
01/01/2024

टी. डी. कार्थिकेयन / T.D. KARTHIKEYAN
उप प्रबंधक / Deputy Manager
एम & एस मेकिंग प्रणाली योजना एवं सिस्टम
M&S Mech. & Info Planning & Systems
बीएचईएल - पीपीपीयू / BHEL - PPPU
तिरुमयम / Thirumayam - 622 507

Syath
01/01/24

एम एंड एस एच सिस्टम / M&S & I
बीएचईएल - पीपीपीयू / BHEL - PPPU
तिरुमयम / Thirumayam - 622507

J. Thamilvanan
01-01-24

जे. तामिलवानन / J. THAMILVANAN
उप प्रबंधक / Deputy Manager
उत्पादन, टूल इंजीनियरिंग एवं डब्ल्यूटीसी
Production, Tool Engineering and WTC
बीएचईएल - पीपीपीयू / BHEL - PPPU
तिरुमयम / Thirumayam - 622 507

**Technical specification for battery powered transfer car
[Carrying Capacity: 20 tons]**

Sl. No	PARTICULARS / BHEL SPECIFICATIONS	BIDDER's OFFER
4.2.5	Suspension system The transfer car frame shall rest on the axle box through a suspension system with helical coil springs to eliminate shocks being transferred from rail to the under frame during operation. The suspension spring pads and bearing blocks shall not be welded. They should be arranged and fixed for easy maintenance. Bidder to confirm.	
4.2.6	Battery Compartment Battery compartment shall be protected from damage using guard plates Bidder to confirm.	
4.2.7	Attachments The below listed attachments are to be compulsorily provided with the Transfer Car.	
4.2.7.1	Buffers Two each of spring-loaded buffers with rubber pads shall be provided at both ends of the transfer car. Bidder to confirm.	
4.2.7.2	Coupler Hook type couplers are to be provided at both ends, for shunting purposes. Bidder to confirm.	
4.2.7.3	Lifting Hooks Adequate number of lifting hooks shall be provided for transporting / lifting the transfer car by means of overhead cranes Bidder to confirm.	
4.2.7.4	Side Supports 3 Nos. of support pockets with inside dimension of 75mm x 75 mm shall be provided on each side of the trolley to accomodate side-support pipes Bidder to confirm.	
4.2.7.5	Step Ladder One step ladder for climbing to be provided in the front and back. Bidder to confirm.	
4.2.7.6	Front and Rear Guards Front and rear guards shall be provided with additional supports for protection. Bidder to confirm.	
4.3.0	DRIVE SYSTEM - The drive shall consist of DC Series motor coupled to the totally enclosed gearbox and drive the wheel through axle-mounted heavy duty gearbox. - Motor & Gearbox to be mounted on the same frame. - Suitable arrangement may be provided to avoid damage to motor & gearbox assembly due to jerking at start & stop.	

Damini
01/01/2021

टी. डी. कार्तिक्केयन / T.D. KARTHIKEYAN
उप प्रबंधक / Deputy Manager
एन & एस मेकैनिक्स प्रोडक्शन एंड सिस्टम
M&S Mech. I, Prod. Engineering & Systems
वीरचईएल - बीएलपीयू / BHEL - PPPU
तिरुमयम / Thirumayam - 622 507

Sajid
01/01/21

पी. जे. सजिद / P. J. SAJI
प्रबंधक / Manager
एम एंड एस एंड टीडी / M&S & TD
वीरचईएल - बीएलपीयू / BHEL - PPPU
तिरुमयम / Thirumayam - 622 507

J. Thamilvanan
01/01/21

जे. तमिलवानन / J. THAMILVANAN
उप प्रबंधक / Deputy Manager
उत्पादन, टूल इंजीनियरिंग एवं ड्रॉफ्टिंग
Production, Tool Engineering and WTC
वीरचईएल - बीएलपीयू / BHEL - PPPU
तिरुमयम / Thirumayam - 622 507

Technical specification for battery powered transfer car
[Carrying Capacity: 20 tons]

Sl. No	PARTICULARS / BHEL SPECIFICATIONS	BIDDER's OFFER
	d. Motor- Gear box coupling shall be Full Gear coupling. e. The power to the motor shall be supplied from the batteries mounted on the trolley itself. Bidder to confirm and elaborate the details.	
4.3.1	Motor a. DC Series motor of suitable capacity having adequate starting torque shall be used. b. The motor shall be totally enclosed. c. The speed control shall be through armature resistance control. d. Three-step speed in either direction shall be provided. e. DC magnetic brake shall be provided. Bidder to confirm and elaborate the details.	
4.3.2	Traction Motor Make Motor make shall be of reputed make. BIDDER to specify make and rating.	
4.3.3	Track Rail Size ISR 90 Lbs./Yard Bidder to confirm.	
4.3.4	Brake Fail safe electro-magnetic brake shall be provided for instantaneous stopping. Bidder to confirm.	
4.3.5	Gear-Box a. The gearbox casing shall be fabricated out of steel plates. b. The housing shall be stress relieved after fabrication to eliminate the internal stresses developed during welding and also to maintain the dimensional accuracy in service. c. The housing shall be of split design to facilitate easy assembly & maintenance d. The mating joint faces shall be of accurate finish, blue matched & lapped together to ensure leak proof joint. e. The gears shall be made out of alloy steel forging. f. The gear tooth size and face width shall be designed with adequate factor of safety for severe shocks while in service during stall condition of motor as while braking under load. Bidder to confirm and elaborate the details.	

Signature
01/01/2021

टी. जी. कार्थिकेयन / T.D. KARTHIKEYAN
उप प्रबंधक / Deputy Manager
एम. एस. एल. एंड. टी. डि. / M&S & TD
बीएचईएल - पीपीयू / BHEL - PPPU
तिरुमयन / Thirumayam - 622 507

Signature
01/01/21


पी. जे. साजि / P. J. SAJI
प्रबंधक / Manager
एम. एस. एल. एंड. टी. डि. / M&S & TD
बीएचईएल - पीपीयू / B-
तिरुमयन / Thirumayam - 622 507


Signature
01/01/21


जे. तमिलवानन / J. THAMILVANAN
उप प्रबंधक / Deputy Manager
उत्पादन, टूल इंजीनियरिंग एवं जलसूटिसी
Production, Tool Engineering and WTC
बीएचईएल - पीपीयू / BHEL - PPPU
तिरुमयन / Thirumayam - 622 507

Technical specification for battery powered transfer car
[Carrying Capacity: 20 tons]

Sl. No	PARTICULARS / BHEL SPECIFICATIONS	BIDDER's OFFER
4.3.6	Wheel and Axle - Cast steel wheels as per IS 2707 Gr II of defect free and finish machined on running tread, flange and bore shall be provided. - The tread shall be induction hardened to 300 to 350 BHN. - Axles shall be of forged steel. Bidder to confirm	
4.4.0	CONTROL SYSTEM - DC Motor shall be used with resistance for speed and torque control. - The resistance value shall be selected so that the motor delivers required torque while starting and current is kept within the permissible safe limit. - Heavy-duty electromagnetic contactors shall be used to include and remove the resistance in the circuit. - The control shall be by push buttons mounted in the control console. - The driver console shall be provided with cover and lock and key to avoid unauthorized operation. Bidder to confirm and elaborate the details.	
4.4.1	Main Control Master controller with Dead-Man handle mounted at the driver's platform at one end of the trolley. Bidder to confirm	
4.4.2	Remote Control Pendant type hand held Remote Control Unit with 5m long cable with quick-fix end connectors. Bidder to confirm	
4.5.0	BATTERY - Battery shall be accommodated in the transfer car suitably for easy maintenance, charging & replacement. Battery shall be mounted on a trolley type frame which can be moved out for easy maintenance. - Battery shall be Iron clad, heat sealed polypropylene classic motive power battery and assembled in steel trays duly FRP lined, including inter cell connectors, terminal take off, charging socket and harness, complete with all components, conforming to IS:5154 Latest edition. Bidder to confirm	


 टी. डी. कार्थिकियन / T.D. KARTHIKEYAN
 उप प्रबंधक / Deputy Manager
 एन. सी. एस. मॉड्यूल सिस्टम प्रोडक्शन एवं इंजीनियरिंग
 NCS Mod. M. I. E. Production & Systems
 बीएचईएल - धीपीपीयू / BHEL - PPPU
 तिरुमयम / Thirumayam - 622 507


 पी. जे. सजी / P. J. SAJI
 प्रबंधक / Manager
 एम. एंड. एस. एवं टीडी / M&S & TD
 बीएचईएल - धीपीपीयू / BHEL - PPPU
 तिरुमयम / Thirumayam - 622 507


 जे. तमिलवानन / J. THAMILVANAN
 उप प्रबंधक / Deputy Manager
 उत्पादन, टूल इंजीनियरिंग एवं उद्यमशीलता
 Production, Tool Engineering and WTC
 बीएचईएल - धीपीपीयू / BHEL - PPPU
 तिरुमयम / Thirumayam - 622 507

Technical specification for battery powered transfer car
[Carrying Capacity: 20 tons]

Sl. No	PARTICULARS / BHEL SPECIFICATIONS	BIDDER's OFFER
4.5.1	Battery Charging Supplier shall charge the battery at site. Sufficient quantity of electrolyte and suitable Charger shall also be supplied along with the battery. Bidder to confirm	
4.5.2	Battery Power Rating 36V DC, 300 Ah, 5 h rating Storage Type, Traction Duty, lead acid Battery. Bidder to specify	
4.5.3	Battery Make Storage Battery shall be of internationally reputed make only. BIDDER has to specify make & power rating of the Battery.	
4.6.0	BATTERY CHARGER Suitable for 36 V, 300 Ah lead acid battery. Charger shall have the following features: a. Constant current equalizing facility with auto cut-off. b. Protection for reverse battery, over current and short circuit. c. Free standing, self – compensating, and 100% automatic charging. d. Charging current and charging voltage indication. e. On delay start. Bidder to confirm.	
4.6.1	Input Electric Power The battery charger shall be suitable for input electric supply through a 415VAC $\pm$ 10%, 50Hz $\pm$ 3% from 3 Phase, 3 Wire System. [No neutral conductor] Bidder to confirm.	
4.6.2	Power Cable 10 m long charging cable of adequate size, with end connectors, shall be supplied. Bidder to confirm.	
4.7.0	SAFETY PROTECTIONS The following safety protections shall be compulsorily provided: 1. Overload Protection. 2. Short Circuit Protection. 3. Dead Man Control. 4. Key Switch. 5. Hooter. 6. Charger Isolation. 7. Reverse Interlock. 8. Over Speed Protection. 9. Emergency Stop. Bidder to confirm.	


01/01/2024
 टी. डी. कार्थिकियन / T.D. KARTHIKEYAN
 उप प्रबंधक / Deputy Manager
 एम & एस प्रोडक्शन टूल इंजीनियरिंग एवं सिस्टम
 M&S Production Tool Engineering & Systems
 थिरुमयम - पीपीयू / BHEL - PPU
 थिरुमयम / Thirumayam - 622 507


01/01/24
 पी. जे. साजि / P. J. SAJI
 प्रबंधक / Manager
 एम एंड एस एवं टीसी / M&S & TD
 बीएचईएल - पीपीयू / BHEL - PPU
 थिरुमयम / Thirumayam - 622507

01-01-24
 जे. तमिलवाणन / J. THAMILVANAN
 उप प्रबंधक / Deputy Manager
 उत्पादन, टूल इंजीनियरिंग एवं डब्ल्यूटीसी
 Production, Tool Engineering and WTC
 बीएचईएल - पीपीयू / BHEL - PPU
 थिरुमयम / Thirumayam - 622 507

**Technical specification for battery powered transfer car
[Carrying Capacity: 20 tons]**

Sl. No	PARTICULARS / BHEL SPECIFICATIONS	BIDDER's OFFER
4.8.0	SURFACE CLEANING All the fabricated parts shall be de-rusted and degreased (by shot blasting or chemical treatment for surface cleaning), after completion of all operations but prior to painting. Bidder to confirm.	
4.9.0	PAINTING The Steel fabricated parts are to be painted as follows. - One coat of Primer with 25 microns of DFT (Dry Film Thickness) and 48 hours of compulsory curing after painting. - Two coats of Enamel Paint (Colour - Golden Yellow) each with a DFT of 25 microns and intermittent curing of minimum 16 hours. - The front and rear portions shall be painted yellow and black strips. Bidder to confirm.	
5.0.0	SPARES The bidder has to supply the items listed below along with main item - Heavy-duty electromagnetic contactors - 1set - Master controller - 1number - Dead-Man Switch - 1number - Male Female connector for battery charging - 1set - Spare motor- gearbox coupling - 1 set Bidder to confirm. And bidder has to compulsorily list down the Mechanical, Electrical and Electronic Spares with Unit Rate, which are to be procured for three years of continuous operation of the Transfer Car with the Remote Control Unit in addition to the above mentioned 5 items.	
6.0.0	DOCUMENTS/DETAILS for APPROVAL The following documents and details are to be submitted for BHEL Approval, prior to taking up the manufacture of the Transfer Car.	
6.1.0	Drawings and Documents - GA Drawing of the Transfer Car / Trolley. - Trolley Dimensional Drawing. - Sub-Assembly Drawing for Wheel & Axles, Gear Boxes, etc. - Calculations for Selection of Electric Motor and Gear-Box. - Electrical Drawings. - Schematic Drawing of Trolley Controls. - Battery Charger Schematic Drawing. - Total Weight of the Transfer Car including all Electrical Equipment. Bidder to confirm.	


 श्री. ई. कार्थिकेयन / E.D. KARTHIKEYAN
 उप प्रबंधक / Deputy Manager
 एम & एस मीकॅनिकल इंजिनियरिंग एवं सिस्टम
 M&S Mech. & Engrg. & Systems
 बीएचईएल - पीपीपीयू / BHEL - PPPU
 तिरुमयम / Thirumayam - 622 507


 श्री. जे. सजि / J. SAJI
 प्रबंधक / Manager
 एम & एस मीकॅनिकल इंजिनियरिंग एवं सिस्टम
 M&S & TD
 बीएचईएल - पीपीपीयू / BHEL - PPPU
 तिरुमयम / Thirumayam - 622 507


 श्री. तमिलवानन / J. THAMILVANAN
 उप प्रबंधक / Deputy Manager
 उत्पादन, टूल इंजीनियरिंग एवं ड्रॉफ्टिंग
 Production, Tool Engineering and WTC
 बीएचईएल - पीपीपीयू / BHEL - PPPU
 तिरुमयम / Thirumayam - 622 507

Technical specification for battery powered transfer car
[Carrying Capacity: 20 tons]

Sl. No	PARTICULARS / BHEL SPECIFICATIONS	BIDDER's OFFER
7.0.0	O & M MANUALS Each Transfer Car shall be provided with a. Complete set of Tools required for Operational Maintenance, b. 3 Copies of Operation & Maintenance Manual hard copy & one soft b) copy in CD, [containing the following technical details, given under Clause Sl. No. 7.1.0] Bidder to confirm.	
7.1.0	Drawings & Details a. Trolley General Arrangement Drawing b. Assembly Drawing for Wheel & Axle, Gear-Box Assembly, etc. c. Electric Wiring Schematics d. Detailed Wiring Diagram for Sub-Systems / Control Panels e. Battery Charger Schematic Drawing. f. Specifications / Ratings and Data sheets of All Bought-Out Items g. Warranty / Guarantee Card for all the Bought-Out Items h. Trouble Shooting Chart for all Systems i. List of Spares – both Mechanical and Electrical Bidder to confirm.	
8.0.0	INSPECTION Schedule of Inspection at supplier's works: a. Verification of Test Certificate for Raw Materials used for fabrication. b. Verification of X-Ray Report of Butt-Joints and Random Testing of the Welds, by physical examination. c. Verification of Transfer Car Dimensions, Checking of Wheel Alignment, Mechanical Assemblies and Total Alignment. d. Trolley operation without load. e. General checks and verification of technical details mentioned in specification. Schedule of Inspection at BHEL: a. Full / Rated Load Test. b. 10% OVER-LOAD Carrying Ability Check. Bidder to confirm	
9.0.0	ERECTION & COMMISSIONING	
9.1.0	Mechanical Erection /Assembly Erection / Assembly of the Transfer Car has to be done by the Representative of the Supplier, at BHEL Works. Bidder to confirm.	

Dammihw
01/01/2021
टी. डी. कार्थिकियन / T.D. KARTHIKEYAN
उप प्रबंधक / Deputy Manager
एच. डी. एच. सिस्टम / H.D. ECH. SYSTEMS
Mkt. Mgmt. Planning & Systems
बीएचईएल - पीपीपी / BHEL - PPPU
थिरुमयम / Thirumayam - 622 507

Sayid
01/01/21
टी. डी. कार्थिकियन / T.D. KARTHIKEYAN
उप प्रबंधक / Deputy Manager
एच. डी. एच. सिस्टम / H.D. ECH. SYSTEMS
Mkt. Mgmt. Planning & Systems
बीएचईएल - पीपीपी / BHEL - PPPU
थिरुमयम / Thirumayam - 622 507

J. Thamilvanan
01-01-21
Page 8 of 9
जी. तमिलवानन / J. THAMILVANAN
उप प्रबंधक / Deputy Manager
उत्पादन, टूल इंजीनियरिंग एवं डब्ल्यूटीसी
Production, Tool Engineering and WTC
बीएचईएल - पीपीपी / BHEL - PPPU
थिरुमयम / Thirumayam - 622 507

Technical specification for battery powered transfer car
[Carrying Capacity: 20 tons]

SI. No	PARTICULARS / BHEL SPECIFICATIONS	BIDDER's OFFER
9.2.0	Commissioning Commissioning of the Transfer Car and Performance Prove –Out for the Trolley's Capacity and Smooth Running (at BHEL Works) shall be the RESPONSIBILITY of the supplier. Bidder to confirm	
9.3.0	Guarantee Vendor shall provide a guarantee for a period of 12 months from the date of commissioning of the equipment or 18 months from the date of dispatch, whichever is earlier. Bidder to confirm.	

Darshin
 01/01/2024
 टी. डी. कार्तिकेयन / T.D. KARTHIKEYAN
 उप प्रबंधक / Deputy Manager
 एम & एस मॉक, प्लानिंग एवं सिस्टम
 M&S Moch. Main. Planning & Systems
 बीएचईएल - बीपीपीयू / BHEL - PPPU
 तिरुमयम / Thirumayam - 622 507

Saji
 01/01/24
 पी. जे. सजी/P. J. SAJI
 प्रबंधक / Manager
 एम एंड एस एवं टीडी / M&S & TD
 बीएचईएल - बीपीपीयू / BHEL - PPPU
 तिरुमयम / Thirumayam -622507

J. Thamilvanan
 01-01-24
 जे. तमिलवाणन / J. THAMILVANAN
 उप प्रबंधक / Deputy Manager
 उत्पादन, टूल इंजीनियरिंग एवं डब्ल्यूटीसी
 Production, Tool Engineering and WTC
 बीएचईएल - बीपीपीयू / BHEL - PPPU
 तिरुमयम / Thirumayam - 622 507