PROJECT: CONTRACT QUALITY DOC.NO: ##Enquiry No: NTPC Dadri 4 x 490MW REOUIREMENTS (COR) for BAP/OR/G501-G502/ (BHEL W.O no: G 501 and G 502) **ELECTRICALLY OPERATED HOISTS** ## Supplier Name & /Dadri/ EOH 001 used in FGD APPLICATION Address: **CONTRACT NO: Rev NO.: 00** NTPC Dadri 4 x 490MW PAGE: Page 1 of 1 CS-6130-109-9-FC-NOA-6641 ##Offer reference: (BHEL W.O no: G 501 and G 502) DATE: 31.07.2021 PACKAGE: FGD PACKAGE MAIN CONTRACTOR: ##Date: **BHEL - RANIPET** SUB CONTRACTOR & ADDRESS: **Contact Official Name:** Mobile no: (To be filled by VENDOR) Email id: Sl. DESCRIPTION **BHEL/NTPC Requirements** ##Specific NO. confirmations by the vendor ITEM: ELECTRICALLY OPERATED HOISTS Vendor shall confirm to meet the requirement of SOP ref no. SOP OP No. 01 Quality plan Requirement 0000-999-OOM-S-053 Rev 00 dt 05.04.2013 and arrange to submit the SQP duly endorsed (signature and stamp) in all pages along with duly filled in Endorsement sheet for accepting the QAP in totality in the event of Purchase Order. 02 Type test Vendor shall confirm for successful conduction & completion of all the tests & type tests if any as indicated in the attached SQP ref no. SQP QP No. requirements 0000-999-QOM-S-053 Rev 00 dt 05.04.2013. BHEL/BHEL AIA and Ultimate customer NTPC Inspection as per this SOP 03 Inspection Methodology is must before dispatch.

	Methodology	is must before dispatch.	
		No material shall be dispatched without BHEL/Ultimate Customer NTPC, inspection with required CHP/MDCC clearances.	
04	For inspection call	To raise inspection call by BHEL/BHEL AIA inspection including for type test witnessing, vendor is requested to contact Mr R Kesavan, DGM (QC-Proc)., Mobile no: +91 9443006303., Email id: Kesavan@bhel.in and Mr Zeeshan Ali, Sr.Engineer (QC-Proc)., Mobile no: +91 9443149691., Email id: zeeshan@bhel.in for inspection related activities for immediate response / resolution.	
05	Packing	Required Packing & preservation shall also to be ensured as per requirements stipulated in Engg spec / drg / data sheet/PO condition to avoid any damage during transit., handling damages & storage at site.	
06	Painting	Paint color and coating thickness to be ensured as per requirements stipulated in Engg spec / drg / data sheet.	
07	Document package	Specific confirmation for Document Package in the event of an order (2 hard copies + 2 CDs in PDf file) is to be given containing the following with proper linkages (.) (i) Index Sheet (ii) SQP (iii) TCs identified by BHEL/NTPC for record for "CHP" and Verification portion as given in. (iv) Final Inspection Report + all applicable Test Certificates (v) BHEL/BHEL authorized Inspection Agency report + TC (vi) Type test reports conducted/submitted with approval (vii) NTPC CHP/MDCC	

##Supplier signature with seal

Necessarily to be filled up by the vendor at the time of offer itself otherwise their offer may not be considered w.r.t Quality Requirements being customer specific requirements.

ENDORSEMENT SHEET FOR QP REFERENCE / STANDARD / FIELD QUALITY PLAN (RQP / SQP/RFQP/SFQP)

TO BE FILLED IN BY SUPPLIER AT T	IME OF SUBMISSION	एनश्वीती NTPC To be filled in by NTPC
PROJECT NAME	NTPC Dadri 4 x 490MW (BHEL W.O no: G 501 and G 502)	2REVIEW & ENDORSEMENT BY NTPC PROJECT SPECIFIC OP NUMBER ALLOTTED
CONTRACT NO.:	CS-6130-109-9-FC-NOA-6641	Thousand a new particular transfer of the second se
MAIN SUPPLIER	M/S.BHEL, RANIPET , TAMIL NADU., INDIA	QP NO:
MANUFACTURER WORKS & ADDRESS	(TO BE FILLED BY EOH MANUFACTURER)	
ITEM /EQUIPMENT / SYSTEM/	ELECTRICALLY OPERATED WIRE ROPE HOIST FOR FGD	REV. NO.: 00 DT:
SUB-SYSTEM DETAILS i.e. MODEL	APPLICATION	
TYPE/SIZE/RATING etc.		
APPROVED QP NO.: RQP/SQP/RFQP/SFQP	0000-999-QOM-S053 Rev No. 00 dt 05.04.2013	
Confirmation by Main Supplier (TICK WHICHEV	VER APPLICABLE)	(TICK APPLICABLE)
I. That the item/ component is identical to that con	sidered for SQP approval.	The MQP/RQP/SQP is endorsed for this project
II. That there are minor changes in the item/ comp	ponent with respect to that considered for MQP/RQP/SQP approval, however	without any change
the same do not affect the contents of MQP/RQP/S	SQP	
III. That there are minor changes in the item/com	ponent with respect to that considered for MQP/RQP/SQP approval, however	The SQP is endorsed for this project with changes
the same affect the MQP/RQP/SQP slightly, as ind	icated below / in attached sheet.	as indicated.
		DISTRIBUTION OF ENDORSEMENT OF
		A) $MQP/RQP/SQP$:
		1. MAIN SUPPLIER (WITH A COPY OF
		MQP/RQP/SQP)
		2. MANUFACTURER
		3. RIO
		4. CQA-SPL
		5. CQA-O/C B) RFQP/SFQP:
		1. MAIN SUPPLIER (with a copy of MQP/RQP/SQP
		2. MANUFACTURER
		3. NTPC FQA (with a copy of MQP/RQP/SQP
		4. NTPC Erection (with a copy of MQP/RQP/SQP
		5. CQA-SPL
		6. CQA-O/C
	(TO BE FILLED BY EOH MANUFACTURER)	NTPC (Reviewed /Approved by/ Date & Seal)
SIGN.: (Main Supplier) DATE:	SIGN.: (Manufacturer) DATE:	

0
70
RMAT
>
7
Z
O
OS-
432
01
QA
÷
'n
4
10/F
끳
4
Ż

SALN REPRES		MATTER STATE OF STATE		SN CC			A RAI	A1 MSI MEN FAB		A.2 PIPE	Same	A.3 FOR		B. BOUG					B.2 WIR		B.3 MOTOR		B,4 GEA		
	UPTO SWL 15	: 18		OPERATIONS		2	RAW MATERIAL INSPECTION:	MS PLATES FOR STRUCTURAL MEMBERS & FABRICATED ROPE DRUM		(IF SEAM LESS PIPE IS USED)		FORGINGS/ ROLLED BARS FOR GEARS, PINIONS, WHEELS, AND BRAKE DRUM		HOOKS					WIRE ROPES		OR		GEAR BOX		
	OPERATED HOIST	0 -		CHARACTERISTICS		ţ3	N.	CHEMICAL & MECHANICAL PROPERTIES	ULTRASONIC TEST OF PLATES	CHEMICAL, MECHANICAL PROPERTIES & ACID ETCHING	ULTRASONIC TEST FOR		ULTRASONIC TEST	MAKE & IDENTIFICATION	CHEMICAL & MECHANICAL PROPERTIES	PROOF LOAD TEST	INTERNAL DEFECTS BEFORE & AFTER PROOF LOAD TEST	PROCE LOAD TEST	MAKE & IDENTIFICATION	DIMENSION & BREAKING STRENGTH	MAKE TYPE/RATING	ROUTINE TESTS	MAKE! TYPE! RATING	BACKLASH, TOOTH CONTACT & REDUCTION RATIO	NO LOAD RUN TEST (NOISE LEVEL TEMP RISE & OIL LEAKAGE)
	See Assess	9		CLASS		*		MAJOR	MAJOR	MAJOR	MAJOR	MAJOR	MAJOR	MAJOR	MAJOR	MAJOR	CRITICAL	CRITICAL	MAJOR	MAJOR	MAJOR	MAJOR	MAJOR	MAJOR	MAJOR
	IS: 3938			TYPE OF CHECK		Şh		CHEM & MECH	NOT	CHEM & MECH	In	CHEM & MECH	NOT	VISUAL	CHEM & MECH	MECHANICAL	TON	NOT	TANSIA	REVIEW	VISUAL	REVIEW	VISUAL	REVIEW	REVIEW
	10 CO	Sames		QUAN	×				100%	1 SAMPLE	100%	H BATCH	100%	100%	1 SAMPLE	100%	100%	100%	100%	100% (EA	100%	100%	100%	100%	100%
	OE:			QUANTUM OF CHECK	C/N	6.		I SAMPLE/ HEAT	100%	SAMPLE/HEAT/SIZE	100%	D HEATT SIZE	100%	100%	E) HEAT/ HT	100%	100%	100%	100%	100% (EACH BATCH)	100%	100%	100%	100%	100%
REV. NO.	DATE	PAGE	VALID UPTO	DOCUMENT		7.		MATERIAL SPECIFICATION AS PER APPROVED DATA SHEETS DRAWINGS	ASTM A-435	MATERIAL SPECIFICATION AS PER APPROVED DATA SHEETS/ DRAWINGS	ASTM E-213	APPROVED DATA SHEETS /DRAWINGS	ASTM A-388	HOOK TO FROM COMPETANT AUTHORITY	APPROVE	IS:15660/ IS: 5749	ASTM - A 388	ASIM E-185	APPROVED MAKES	IS. 2268 / APPROVED DATA	NTPC APPROVED DRAWING/ DATA SHEET/	NTPC SPECIFICATION / IS	NIPC APPROVED DRAWING/ DATA SHEET!	The second secon	NIPC APPROVED DRAWING! CATA
00	05.04.2013	Page 1 of 4	0 04.04.2016	ACCEPTA NORM		ço		CATION AS PER EETS/ DRAWINGS	ASTM A-435	CATION AS PER EETS/ DRAWINGS.	ASTM E-213	CATION AS PER EETS /DRAWINGS	REFERNOTE - 1	ETANT AUTHORITY/	CATION AS PER IEETS /DRAWINGS	IS 15580/ IS: 5749	REFER NOTE - 1	NO DEFECT	MAKES	ED DATA SHEET	WING/ DATA SHEET/	ATION/IS 325	WING! DATA SHEET!	The state of the state of	WING! DATA SHEET/MTG
	013	of 4	910	Format of RECORD		8.		MTC	20	MTC	R	MIC	70	TC	MIC	Ā	70	R		MIC	R	MTC	50	MTC	MIC
-		-		00		o		4	4	4	2	4	4	4	4	1	A	4	1	4			4	4	4
H S MAURYA HI	SSINGH	M K ASTHANA	RAJEEY GARGY	AGE	3			σ	70	'0	מר	v	TO	D	ס	ъ	ס	70	P	υ	0	<	70	<	<
URYA	THANKS THE	NAHT	LGAR	AGENCY	n	10.		<	<	<	<	<	<	<	<	<	<	<	<	<	٧	<	<	<	<
3	B	Souré V	GVI		Z			₹ 88	× 0 × 0	<	4	< #8₹	V ONL	V RE	<	×	90	4	V BE	<	V RE	<	38	4	<
130	Shortday of	こののが本	N. W.	REMARKS C.,		7.		N THE ABSENCE OF CORRELATED TO CHECK	ONLY FOR THICKNESS 2 25 MM.			OF THE ABSENCE OF CORRELATED TO CHECK TESTING SHALL BE DONE	ONLY FOR DIA 240	REFER ANNEX: FOR MAKE			ONLY PORTION		REFER ANNEX I FOR MAKE		REFER ANNEX L FOR MAKE		REFER ANNEX I FOR MAKE		

.

ENGG, DIV./QA&I

ENG

LEGEND: * RECORDS INDENTIFIED WITH TICK" (*) SHALL BE ESSENTIALLY INCLUDED BY SUPPLIER IN QA DOCUMENTATION ** M: MANUFACTURERSUB-SUPPLIER C: MAIN SUPPLIER N: NTPC P: PERFORM W: WITNESS AND V: VERIFICATION AS APPROPRIATE. CHP: NTPC SHALL IDENTIFY IN COLUM "N' AS W FORMAT NO.: QS-01-QALP-10/F1-R1

Note:# NTPC Inspection Engineer to check, approval date / revision no. of reference documents at the time of Inspection

8.9 B.5 SN LIMIT SWITCH: OVERLOAD
RELAY/SEL/CONTACTOR/
CONTROL TRANSFORMER/
PUSH BUTTON TERMINAL
BLOCK! INDICATING LAMP/ ROPE DRUM, WHEELS, PULLEYS & HOOK SHANK AFTER WACHINING ROLLING & WELDING OF ROPE DRUM (FABRICATED) STATION HOUSING/ BOX WAYED (AS APPLICABLE) CONTROL EPR FLEXIBLE TRAILING BRAKES -EN/ EH SELECTOR SWITCH **OPERATIONS** COMPONENT & NUT ON MACHINED SURFACES WELD JOINTS WPS, POR SWPQ MAKE! TYPE! RATING TREATMENT PREPARATION SHADE! THK (MIN 70 H) MATERIAL & THK, DOOR VISUAL & DIMENSIONAL NOT TEST ON WELD ALIGNMENT, PAINT ACCEPTANCE TESTS MAKE! TYPE! RATING ACCEPTANCE TESTS MAKE! TYPE RATING MAKE! TYPE! RATING ROUTINE TESTS WAKE TYPE/ RATING CHARACTERISTICS WELD HEAT CLASS CRITICAL MAJOR CHECK TYPE OF MEASURE DPT MEASURE VISUAL & REVIEW REVIEW VISUAL **VISUAL** REVIEW VISUAL REVIEW VISUAL REVIEW VISUAL VISUAL PPT 직 100% 100% 100% 5,000 to 100% 100% 100% 100% 100% 100% 100% 100% 100% 100% 100% 100% K QUANTUM OF CHECK 100% 300% 100% 100% 100% 100% 100% 16003 100% 100% 100% 100% 100% 100% 100% 100% CN MANUFACTURING DRAWING APPROVED IR REFERENCE APPROVED WPS ASME SEC-IX NIPC APPROVED DRAWING/NIPC SPECIFICATION/IS:1554/IS:9988/IS:4289/ IS:7088 NTPC APPROVED DRAWING/ NTPC SPECIFICATION APPROVED MAKES ASME SEC - V NTPC APPROVED DRAWING/ NTPC SPECIFICATION APPROVED MAKES ASME-SEC-V ASTM E-185 MANUFACTURER'S DRAWINGS APPROVED DRAWING/ NIPC TECH.
SPECS/ APPROVED MAKES NTPC APPROVED DRAWING/NTPC SPECIFICATION IS 3838 ASME-SEC-VIII DIV 1 (UCS-56) VALID UPTO ASME -SEC VIII R
DIVISION -1, UW 51 & ASME SECTION -NORM ACCEPTANCE For NO DEFECT B REPORT RI FLMS SR 70 MIC 70 MTC RECORD Format of 50 2 4 2 4 4 0 4 RAJEEY GARGA M K ASTHANA T 70 < O TO V 0 < ט Z AGENCY < < ٧ V O V < < × < < < ŧ V < < DURING THE FINAL INSPECTION CHP SR CHART REVIEW BY NTPC DURING FINAL REFER NOTE-2 REFER ANNEX-I FOR MAKE REFER ANNEX FOR MAKE REFER ANNEX-I FOR MAKE NSPECTION REFER ANNEX-I FOR MAKE REFER ANNEX FOR MAKE REMARKS 11

ELECTRIC OPERATED HOIST

CONFORMING TO CODE:

STANDARD QUALITY PLAN

OP NO. REV. NO DATE

0000-998-QOM -S-053

REVIEWED BY:

APPROVED BY

HS MAURYA HT

S SINGHULL

Page 2 of 4 05.04.2013 00

IS: 3938

UPTO SWL 15 TON

ITEM (MATERIAL, CLASS, GRADE, RATING, RANGE, SIZE ETC)

17.5

ENGG. DIV JOASI

0/

ENGG. DIV./QA&I

of

FORMAT NO.: QS-01-QAI-P-10/F1-R1

Note:# NTPC inspection Engineer to check, approval date / revision no. of reference documents at the time inspection

LEGEND: * RECORDS. INDENTIFIED WITH "TICK" (*) SHALL BE ESSENTIALLY INCLUDED BY SUPPLIER IN QA DOCUMENTATION.
** MI: MANUFACTURER/SUB-SUPPLIER G: MAIN SUPPLIER, N: NTPC P: PERFORM W: WITNESS AND V: VERIFICATION AS APPROPRIATE, CHP: NTPC SHALL IDENTIFY IN COLUM "N" AS W ALL CRITICAL DIMENSIONS SHALL BE MEASURED THE CURRENT AND SPEED FOR HOISTING MOTION AND LONG TRAVEL MOTION SHALL BE MEASURED DURING NO LOAD TEST AND SAFE WORKING LOAD (SWL) TEST. ALL INTERLOCKS, BRAKE OPERATION, LIMIT SWITCHES AND SAFETY MEASURES SHALL BE CHECKED.

HY TEST ON CONTROL PANELS WILL BE DONE ISOLATING WAYF DRIVE AND OTHER ELECTRONIC PARTS: HY TEST AT 2 KV FOR POWER & 1.5 KV FOR CONTROL CIRCUIT ACCORDANCE WITH APPROVED DRAWING/ DATA SHEETS

MOTOR POWER RATING LESS THAN 30KW:
ACCEPTANCE OF MOTOR LESS THAN 30KW IS BASED ON COC OF THE MANUFACTURER & THE CONTRACTOR CONFIRMING AS FOLLOWS:
"IT IS HEREBY CONFIRMED THAT THE ABOVE MENTIONED MOTORS WAS WERE MANUFACTURED TAKING CARE OF NTPC SPECIFIC REQUIREMENTS REGARDING AMBIENT TEMP. VOLTAGE & FREQUENCY VARIATION, HOT STARTS, PULL OUT TORQUE, STARTING KVAKW, TEMP. RISE, DISTANCE BETWEEN CENTRE OF STUD & GLAND PLATE AND TESTED IN

PAINTING OF HOIST BACK WALL ECHO SHALL BE SET AT 100% OF FULL SCREEN HEIGHT AT SOUND AREA OF THE BAR USING NORMAL BEAM PROBE OF 2 MHz TO 5 MHz, AT THIS SENSITIVITY LEVEL, ANY DEFECT ECHO EXCEEDING 20% OF FSH IS NOT ACCEPTABLE. IN ADDITION, LOSS OF BACK WALL ECHO MORE THAN 20% OF FSH IS ALSO NOT ACCEPTABLE.

WPS, POR & WELDERS QUALIFIED BY LLOYDS, BYQI, TUV, DNV, NTPC, BHEL, NPCIL ARE ACCEPTABLE. ONLY QUALIFIED WELDRES SHALL BE DEPLOYED FOR WELDING. CONTROL PANE TEST & FULL LOAD OVERLOAD TEST AT 125% TEST BY PAPER INSERTION METHOD HV. IR ADHESION VISUAL DET MEASUREMENT PAINT SHADE ADHESION THICKNESS. VERIFICATION & OPERATION BREAK, LIMIT RELAYS INTERLOCKING OPERATION DRAWN, SPEED DEGREE OF PROTECTION ENCHING Q MAJOR MAJOR MAJOR MAJOR MAJOR MAJOR MAJOR VISUAL MEASURE VISUAL MEASURE MEASURE MEASURE VISUAL & VISUAL VISLIAI 8 100% 100% 100% 100% 100% 100% 100% 100% 100% 100% 100% 100% 100% 100% S IS: 3938/ APPROVED DRAWING IS: 3938/ APPROVED DRAWING IS: 3838/ APPROVED DRAWING IS: 3938/ IS: 3938/ APPROVED DRAWING DATA SHEET
AS PER NTPC SPECIFICATION 3938/ APPROVED DRAWING/ APPROVED DRAWING DATA SHEET DATA SHEET DATA SHEET DATA SHEET Z 70 70 N 8 8 2 14 × S 8 ¥ × THICKNESS> 70 MICRON

1.		N N	1			MIN	
2		OPERATIONS		OFTO SANT 12 TON	ELECTRIC	(ŏã	RANGE, SIZE ETC)
3.		CHARACTERISTICS CLASS		NOI GL	ELECTRIC OPERATED HOIS		RANGE, SIZE ETC)
		CLASS			I	22	ING,
p ₁		CHECK		15: 3938	CONFORM		STANDAR
6.	M C/N	CHECK DOCUMENT			CONFORMING TO CODE		STANDARD QUALITY PLAN
7.		DOCUMENT	VALUE CIPTO	PAGE	DATE	REV. NO.	LAN OP NO.
00		NORM	0 04.04	Page 3	05,04.201	00	0000-999-00
9. D		Format of RECORD	2016	of 4	2013		9-QOM -S-053
10.	M C	AGENCY	RAJEEV GARG	M K ASTHANA	S SINGHA	HSMAURYA	REVIEWED BY: APPR
11.		REMARKS C. N	The second second	- W.	人はある	世代の	APPROVED BY

PUSH BUTTON (AS

COMPLETE ASSEMBLED HOIST VISUAL & DIMENSIONAL ALONG WITH ACTUAL CONTROL PANEL, VVFD &.

MAJOR

MEASURE

100%

100%

IS: 3938/ APPROVED DRAWING

Œ

U

×

¥

REFER NOTE

DATA SHEET

FINAL INSPECTION:

Note:# NTPC Inspection Engineer to check, approval date / revision no. of reference documents at the time of inspection

1/1

FORMAT NO.: QS-01-QAI-P-10/F1-R1

LEGEND: * RECORDS, INDENTIFIED WITH "TICK" (*) SHALL BE ESSENTIALLY INCLUDED BY SUPPLIER IN QA DOCUMENTATION.
*** M: MANUFACTURER/SUB-SUPPLIER C: MAIN SUPPLIER, N: NTPC P: PERFORM W: WITNESS AND V: VERIFICATION, AS APPROPRIATE. CHP: NTPC SHALL IDENTIFY IN COLUM "N" AS W

23 SELECTOR SWITCH	21 INDICATING METER	20 TERMINAL BLOCK	18 BRAKES - DCEM		15 CURRENT TRANSFORMERS	14 TRANSFORMERS (CONTROL)	13 INDICATING LIGHT	12 PUSH BUTTON STATIONS (PENDANT)	11 PUSH BUTTONS	10 BEARING	B FIEVE CONTRACTOR	CONTACTOR&OLR, TIME DELAY RELAY AUX RELAY	6 LIMIT SWITCHES	6 MOTOR	4 GEAR BOX	3 HOOK	2 WIRE ROPE	- OLECT
SUSHEEL STOWAG L&T, KAYCEE	MECO RIGINAL WAGO(FOR CONTROL ONLY)	WMIELECTROMAG	EMCO PETHE MAN BOLL	L&T.ABB.SIEMENS.SCHIENDER, DANFOSS	INDCOIL AE PRAGATI PRECISE VARBA	VASHING	VAISHNO, SIEMENS L&T	VAISHNO, SIEMENS, L&T, TELEMECHANIC	SKF FAG NRB NTN NBC TIMKEN. CORDS, GEMS, HAVELLS. ONLY FOR FIXED CABLE	UNIVERSAL POLYCAB KELNICCO DEL TON' PARAMOLINE CONTRE	SIEMENS L&T GEIL C&S	-	+	ELECON, SHANTI GEAR, NEW ALLENBURRY WORKS PETI BONEIGH OF THE CO.	HERMAN MOHATA, SMRITI FORGING LARACHIWALA Approved up to 15T	USHA MARTIN. BHARAT WIRE ROPE, BOMBAY WIRE ROPE	SAIL, TISCO, RINL, JSW, JISL ESSAR IISCO, WEI SPI IN	

	D. 1501	7 1 10	The State of the S				200			NT PC		
	OF ALL MAJOR BOLK		2			OPERATIONS		UPTO SWL 15 TON	ELECTRIC	RANGE, SIZE ETC)		
	LIGI OF ALL MAJOR BOUGHT OUT ITEMS AND THEIR ACCEPTABLE MAKES ASEL LETER BET ON		3.			CHARACTERISTICS		15 TON	ELECTRIC OPERATED HOIST	RANGE, SIZE ETC)		
	EIR ACCEPT	4.	4		3.	CLASS			ST	ding,		
TO COMPANY OF STREET	ABLE MAKES ASE	ņ			CHECK	TYPE OF		IS: 3938	CONFORM	STANDA		
AACOTED GETCAA	TIOTED DELOW	6.		M C/N	CHECK	DUANTIM OF BETERRED			CONFORMING TO CODE	STANDARD QUALITY PLAN		
		7.		DOCUMEN!		OLAN GI	PAGE	DATE	REV. NO.	LAN QP NO.		
	ţ	20		NORM	PTANCE	04.04.2016	Page 4 of 4	05.04.2013	00	0000-939-Q0		
	8. D			RECORD	CES	2016	of 4	2013		00-999-QOM -S-053		
	10.		N N	-	AGENCY	RAJEEV GARG	MKASTHANA	SSINGHA	H S MAURYA	REVIEWED BY: APPROVE		
	11.			PACES OF SECTION	REMARKS	The state of the s	京大海,	SAN SOLL	一年の本土	APPROVED BY		