

3



PLANT PURCHASE SPECIFICATION (CFFP - HARDWAR)

FF 05057 Rev 02

Page 1 of 3

FERRO VANADIUM (Low Sulphur & Phosphorus)

1. SCOPE

This specification governs the quality of Ferro Vanadium (LSP) with the following requirements.

2. APPLICATION

The material shall be used as alloying addition for manufacturing of alloy steel

3. CONDITION OF DELIVERY

The size should be in the range of 10-50 mm. However oversized material should not exceed 10% by weight and undersize material should not exceed 5% by weight.

4. COMPLIANCE WITH NATIONAL STANDARDS

The specification in general is based on Indian standards specification IS 1466-1985.

5. FREEDOM FROM CONTAMINATION

The material shall be free from extraneous contamination such as slag.

6. CHEMICAL COMPOSTION

The material shall conform to the following chemical composition when it is analyzed in accordance with IS 1559. The sampling shall be done as per IS: 1472.

ELEMENT	% MIN	%MAX
Vanadium	50	55
Carbon	-	0.10
Silicon	-	1.5
Sulphur	-	0.02
Phosphorus	-	0.02
Aluminium	-	1.50

COPYRIGHT AND CONFIDENTIAL
The information on this documents is the property of Bharat Heavy Electrical Limited it must not be used directly or indirectly in any way detrimental to the interest of the company

RMI	S.N.GHOSH	WORKED BY	M.K.SAHU
MPIC	N.K.VERMA	CHECKED BY	RANJAN
CHAIRMAN CPSC	R.PARTHASARATHY	SECRETARY PPSC	Dr.M.S.RAWAT
		APPROVED : PLANT STANDARDS COMMITTEE	
		PREPARED : SMS TECH	ISSUED : Steel Melting Shop
		DATE : 30-07-10	



PLANT PURCHASE SPECIFICATION

(CFFP - HARDWAR)

FF 05057 Rev 02

Page 2 of 3

7. INSPECTION

- CFFP reserves the right to witness the testing of the material at supplier works and therefore the supplier shall notify the readiness of the material in advance.
- CFFP may, at its discretion, test the material after receipt and acceptance of the material will be based on the CFFP's test results.
- For any deviation from this specification prior approval shall be taken by the supplier.
- For result of analysis and properties of material the decision of CFFP shall be final and binding on the supplier.

8. TEST CERTIFICATES

One Original and three copies of Test Certificate from the **Manufacturer** containing the following information **along with test result of clause 3,5 and the chemical composition as per clause 6** should be provided.

Manufacturer's Name
Name of the material
Batch/Lot No.
Quantity.

Note:

- A manufacturer supplying directly to BHEL should include BHEL's P.O. No. and Challan No. also in the TC.
- Any other supplier should provide a covering letter along with original Manufacturer's TC as above mentioning BHEL's P.O. No. and Challan No.

9. PACKING AND MARKING

The material shall be packed in **Tamper proof metallic drum** such as to prevent loss / deterioration in quality during handling, transport and storage. It should be in the manufacturer's packing. Each package should be marked with the following details.

Name of the material
Manufacturer's Name / Trade mark
Batch/Lot No.
Net weight.

10. REFERRED STANDARDS

IS: 1466 -1985, IS : 1559 , IS: 1472 and BHEL Corporate specification: AA 11310

WORKED
BY

M.K.SAHU

30.07.10

CHECKED
BY

RANJAN

30.07.10