

BHARAT HEAVY PLATE & VESSELS LIMITED.,  
(A Subsidiary Bharat Heavy Electricals Limited)  
A Government of India Enterprises  
Visakhapatnam – 530 012 INDIA.  
web site: [www.bhpvl.com](http://www.bhpvl.com)



Phone : +91(0891) 6681309, 494  
+91(0891) 6681396  
Fax : +91(0891) 6681700  
E-Mail : [mm\\_cps@bhpvl.com](mailto:mm_cps@bhpvl.com),  
[mm@bhpvl.com](mailto:mm@bhpvl.com)

**NOTICE INVITING TENDER( NIT)**

**Category of Tender: TWO BID  
(PRICED + UN - PRICED)**

**SUB: Retrofit and Reconditioning of Tilting,  
2 Burner & 3 Burner Furnaces**

Our Ref: **MM/2/10/3031/CAP/W-468/5293**

**DATE: 06.01.2012**

Sealed quotations in duplicate are invited from suppliers on **or before 17.02.2012 SUPERSCRIBING OUR REFERENCE AND CATEGORY OF TENDER** on the cover, for supply of the under mentioned stores within the above due date, otherwise send **REGRET LETTER**, strictly subject to the Terms & Conditions attached herewith.  
**LATE TENDERS ARE NOT ACCEPTABLE.**

ITEM No.	DESCRIPTION / SPECN. / SIZE	QTY
1.	Retrofit and Reconditioning of Tilting, 2 Burner & 3 Burner Furnaces (Estimated Cost of wok is <b>Rs. 45 Lakhs</b> )	<b>3 No 's</b>
	<b>Encl:</b>  <b>1. Qualifying Criteria</b> ..... <b>2 pages</b> <b>2. Technical Specifications</b> ..... <b>12 Pages</b> <b>3. General Terms/ commercial terms and conditions</b> ..... <b>9 pages</b> <b>(INCLUDING CHECK LIST)</b>	

**For BHARAT HEAVY PLATE & VESSELS LIMITED,**

**For Dy. GENERAL MANAGER (MM)**

# RETROFIT AND RECONDITIONING OF TILTING, 2 BURNER & 3 BURNER FURNACES

## BRIEF SCOPE:

Complete retrofit and reconditioning of Tiling, 2 burner and 3 burner furnaces(1 No each) with prove-out of geometrical and job accuracies, complete painting and handing over to Production at BHPV works by the vendor.

## NOTES:

1. Vendor must submit complete information for all the clauses mentioned below. The offer meeting this clause would only be processed.
2. The column "**BIDDER'S OFFER WITH CONFIRMATION & COMPLETE TECHNICAL DETAILS**" of this format shall be filled in by the Vendor and submit along with the offer. Inadequate / incomplete, ambiguous, or unsustainable information against any of the clauses of the specifications / requirements shall be treated as non-compliance and lead to disqualification of the offer without asking queries.
3. The offer and all documents enclosed with offer should be in English language only.
4. Vendors MUST visit BHPV, Visakhapatnam and study the existing furnaces before submission of quotation. The cut-off date for visit to BHPV for inspection of Furnaces, clarification to the vendors to be completed 7 days prior to the tender due date. There will be no further extension of due date.
5. Reconditioning of all the three Furnaces must be completed with in 4 Months from the date of Release of PO. Vendor to mobilize resources accordingly to complete the job in 4 Months respects. The furnaces will be given for retrofit one after the other and each furnace should be completed with in 1 Month.
6. Vendors must indicate makes of all components that are being supplied as a part of this tender clearly indicated in a separate sheet.

<b>ADDRESS OF THE SUPPLIER :</b>	<b>ADDRESS OF THE INDIAN AGENTS :</b>
<b>TELEPHONE NOS.:</b>	<b>TELEPHONE NOS.:</b>
<b>FAX NOS.:</b>	<b>FAX NOS.:</b>
<b>E-MAIL ADDRESS:</b>	<b>E-MAIL ADDRESS :</b>

## RETROFIT AND RECONDITIONING OF TILTING, 2 BURNER & 3 BURNER FURNACES

Page 2 of 2

### QUALIFICATION CRITERIA FOR RECONDITIONING OF THREE FURNACES

SL NO	PRE-QUALIFICATION	Vendor's confirmation YES/NO
<b>A.1.</b>	<p><b>PRE-QUALIFICATION REQUIREMENTS (Proofs to be enclosed for verification)</b> All the following conditions are to be satisfied by the bidder. Documentary proof is to be enclosed with techno-commercial bid satisfying all these conditions. In case the bidder fails to enclose the same, the offer will be liable for rejection.</p>	
	<p>1. The party must be a reputed Manufacturer of LPG/HSD fired stress relieving Furnaces with at least 7 Years experience in this field (by 30.11.2011). The experience reference shall be for a period preceding immediately to the date given above. Party must submit at least one satisfactory certificate issued by customer. Copies of purchase orders/work orders and corresponding completion certificates should be submitted as proof for verification. The dates of the P.O / certificates should be within this period only. Offers without these documents will be rejected. List of the customers along with respective contracting officers addresses (including Phone no. /E-Mail ID) for whom machines were manufactured / rebuilt should be enclosed with the offer.</p>	
	<p>2. The annual turnover during the last three Years ending March 31<sup>st</sup> 2011 should be at least 90 Lakhs (CA certified copy of balance sheet / P&amp;L statements to be enclosed).</p>	
	<p>3. Latest Bankers' solvency (not later than six months from the date tender notice) for an amount of Rs 67 Lakhs from any Nationalized bank.</p>	
	<p>4. Experience of having successfully completed similar works during the last Seven Years (by 30.11.2011) should be either of the following.</p> <p style="padding-left: 40px;">Three similar completed works costing not less than the amount each equal to 40% of the estimated cost.</p> <p style="text-align: center;">or</p> <p style="padding-left: 40px;">Two similar completed works costing not less than the amount each equal to 50% of the estimated cost.</p> <p style="text-align: center;">or</p> <p style="padding-left: 40px;">One similar completed work costing not less than the amount each equal to 80% of the estimated cost.</p>	
<b>A.2</b>	<p><b>Definition of "Similar Works"</b> Manufacturer / Reconditioner of LPG/HSD fired stress relieving Furnaces of the following types.</p> <ol style="list-style-type: none"> <li>1. Manufacturer of LPG/HSD fired stress relieving Furnaces.</li> <li>2. Reconditioning jobs for LPG/HSD fired stress relieving Furnaces.</li> </ol>	

## RETROFIT AND RECONDITIONING OF TILTING, 2 BURNER & 3 BURNER FURNACES

SNO	MAKE	MODEL NO	YEAR OF INSTALLATION	BRIEF SPECS
1.	VULCAN	VULCAN Engineers (P) Ltd Mumbai	1970	Tiltable type 3 burner LPG fired Furnace Size(1000X1000)mm - 3 Burners
2.	VULCAN	VULCAN Engineers (P) Ltd Mumbai	1970	3 burners LPG fired Furnace Size(1500X1000)mm - 3 Burners
3.	VULCAN	VULCAN Engineers (P) Ltd Mumbai	1970	2 Burners LPG fired Furnace 1000X1000 - 2 burners

### Brief description of existing Furnaces:

BHPV is having three numbers of gas fired box type VULCAN make Furnaces supplied By M/s. VULCAN Engineers Pvt. Ltd commissioned during the Year 1970 with the specifications mentioned below. At present the Furnaces are working with frequent breakdowns. The furnace no. 1(3 Burners) is a tiltable top cover LPG fired furnace.

### 1.0 TECHNICAL DETAILS OF ALL THE 3 FURNACES:

Sno	Description	Tiltable type furnace	3 burner furnace	2 burner furnace
1.1	Jobs for the furnace is intended	Used in heating for small forgings, flanges, hot pressings or stampings etc	Used in heating for small forgings, flanges, hot pressings or stampings etc	For heating up jobs before carrying out the pressing and stamping operations
1.2	Inside Length	2500mm	1500mm	1000mm
1.3	Inside width	500mm	1000mm	800mm
1.4	Inside height	1000mm	700mm	600mm
1.5	Max charge weight	2 Tonnes	2 Tonnes	1 Tonne
1.6	Fuel	LPG	LPG	LPG
1.7	No of burners	3	3	2
1.8	Capacity of each burner	8 Nm <sup>3</sup> /hour	5Nm <sup>3</sup> /hour	5Nm <sup>3</sup> /hour
1.9	Max furnace temp	950°C	1150°C	1150°C

## RETROFIT AND RECONDITIONING OF TILTING, 2 BURNER & 3 BURNER FURNACES

### TECHNICAL DETAILS OF 3 BURNER AND 2 BURNER FURNACES:

Sno	Description	Tiltable type furnace	3 burner furnace	2 burner furnace
1.10	Max permissible temp variation	+15°C	+15°C	+15°C
1.11	No of doors	3(tiltable)	1	1
1.12	No of temp control zones	1	1	1
1.13	Temp recording point	3	1	1
1.14	Power supply	415V, 3Phase, 50Hz	415V, 3Phase, 50Hz	415V, 3Phase, 50Hz

### FURNACE NO 1(3 Burners- Tiltable):

This furnace is of LPG fired, tiltable top cover box type furnace. The complete furnace casings are fabricated from mild steel plates of 5mm in thickness reinforced with rolled steel sections.

Complete refractory lining materials for the furnace including the flue duct and chimney are made up of :-

- High grade fire bricks in normal as well as special shape confirming to IS-8 quality and mortar for the same(115mm thick)
- Light fire bricks to back up the above fire bricks and suitable mortar for the same(115mm thick)
- Insulation bricks and suitable mortar for the same to minimize heat losses to bare minimum(115mm thick)
- Hydraulically set light fire ramming mass.
- 3 nos tiltable type furnace top covers fabricated from mild steel plates with sealing arrangement.
- Manually operated individual counter balance type cover lifting arrangement including shaft, lever, bearings, counter weights etc.
- 3 nos high velocity impulse burners with pilot burners, burner block and burner plate, suitable for firing L P G, rated for 8Nm<sup>3</sup>/hour with turn down ration 10:1.
- 1 no 3 HP combustion air blower having a capacity of 450 cfm at 18" WG coupled with TEFC induction motor complete with starter.
- Combustion air ring main for supplying combustion air from blower to the main burners and pilot burners.

## RETROFIT AND RECONDITIONING OF TILTING, 2 BURNER & 3 BURNER FURNACES

Page 3 of 12

### FURNACE NO 1(3 Burners- Tilttable):

- Gas piping from main closing valve on furnace to individual main and pilot burners.
- AUDCO valves are being used for regulating and shutting off gas supply to individual burners.
- Butterfly valves are used for regulating combustion air supply to individual main burners.
- Manually operated damper for furnace pressure control.
- Safety valves incorporated with alarm device with safety switch against air, gas and power failure.
- Self supporting chimney(8mtrs high) lined with fire bricks backed by insulation medium upto 3 mtrs high.
- Induced draught equipment consisting of heat resisting steel nozzle, manually operated butterfly valve and blower complete with motor and starter.

At the time of commissioning, automatic furnace temperature controlling and recording system with the following details was installed (at present it is not working).

- a. Milli Volt type temp controller with selector switch(Range 0 – 1200°C incorporating thermocouple burnout protection suitable for operation on 230V.
- b. Three point strip chart temp recorder (Range 0 – 1200°C) calibrated for Ni.Cr thermocouple and suitable for operation on 230V AC.
- c. Duplex thermocouples.
- d. Solenoid valves in gas line
- e. Butterfly valves in air line
- f. Actuators for operation of above butterfly valves.

### FURNACE NO 2&3(3 & 2 Burners box type):

These furnace casings are fabricated from mild steel plates of 5mm in thickness reinforced with rolled steel sections.

- High grade fire bricks in normal as well as special shape confirming to IS-8 quality and mortar for the same(115mm thick)
- Light fire bricks to back up the above fire bricks and suitable mortar for the same(115mm thick)
- Insulation bricks and suitable mortar for the same to minimize heat losses to bare minimum(115mm thick)
- Hydraulically set light fire ramming mass.

## RETROFIT AND RECONDITIONING OF TILTING, 2 BURNER & 3 BURNER FURNACES

Page 4 of 12

### FURNACE NO 2&3(3 & 2 Burners box type):

- Vertically rise and fall type furnace door fabricated from mild steel plates reinforced with rolled steel sections.
- 3 nos in case furnace no 2 and 2 nos in case of furnace no 3 high velocity impulse burners with pilot burners, burner block and burner plate, suitable for firing LPG rated for 5Nm<sup>3</sup>/hour with turn down ration 10:1.
- Manually operated individual counter balance type cover lifting arrangement including shaft, lever, bearings, counter weights etc.
- 1 no 2 HP combustion air blower having a capacity of 300 cfm at 18" WG coupled with TEFC induction motor complete with starter.
- Combustion air ring main for supplying combustion air from blower to the main burners and pilot burners.
- Gas piping from main closing valve on furnace to individual main and pilot burners.
- AUDCO valves are being used for regulating and shutting off gas supply to individual burners.
- Butterfly valves are used for regulating combustion air supply to individual main burners.
- Manually operated damper for furnace pressure control.
- Safety valves incorporated with alarm device with safety switch against air, gas and power failure.
- Self supporting chimney(8mtrs high for furnace no 2 and 25mtrs for furnace no 3) lined with fire bricks backed by insulation medium upto 3 mtrs high.
- Induced draught equipment consisting of heat resisting steel nozzle, manually operated butterfly valve and blower complete with motor and starter(for furnace no 2 only).
- Gas pressure regulating valve to reduce the line gas pressure required for the burners(for furnace no 3 only).
- Reduce gas pressure for furnace no.2 should be tapped from the pressure reducing valve.

At the time of commissioning, automatic furnace temperature controlling and recording system with the following details was installed (at present it is not working).

- a. Milli Volt type temp controller Range: 0 – 1200°C calibrated for pt-pt R thermocouple and incorporating thermocouple burn out protection suitable for operation on 230V AC, single phase, 50Hz.
- b. Single point strip chart temp recorder (Range 0 – 1200°C) calibrated for pt-pt R thermocouple and suitable for operation on 230V AC, 50Hz.
- c. Duplex thermocouples.
- d. Solenoid valves in gas line
- e. Butterfly valves in air line
- f. Actuators for operation of above butterfly valves.

## RETROFIT AND RECONDITIONING OF TILTING, 2 BURNER & 3 BURNER FURNACES

### FURNACE NO 2&3(3 & 2 Burners box type):

- i. Milli Volt type temperature controller (Range: 0 to 1200°C)
  - ii. Three point strip chart temp recorder(Range 0 to 1200°C)
  - iii. Duplex thermocouples
  - iv. Compensating leads
  - v. Solenoid valves for gas line
  - vi. Butterfly valves for air line.
  - vii. Two position control motor for operation of butterfly valves.
  - viii. Furnace pressure indicator
- Refractory lining of the door is having 1. Light fire castable refractory 2. Insulation bricks and mortar.
  - Complete front plate castings and top and sealing cup manufactured from heat resisting cast iron.
  - Box girder at top for bolting the front plate castings
  - Door locking device
  - Heat resisting steel wall holders for stabilizing the brick walls.

**SCOPE OF WORK:** For the entire work defined, supply, erection and commissioning is included in vendor's scope.

S.No.	PARTICULARS	SPECIFICATION / DESCRIPTION	BIDDER'S OFFER (WITH CONFIRMATION & COMPLETE TECHNICAL DETAILS)
<b>2.0</b>	<b>The following items are to be supplied and commissioned for all the three furnaces.</b>		
2.1	The existing refractory/bricks/insulation inside the furnace and hearth must be replaced and lined with new conventional refractory insulation bricks of IS standards. Where ever the refractory retainer castings are not available, must be replaced with new castings.	Vendor to specify	
2.2	All the burners with allied accessories, control valves etc are to be replaced with new burners. The type, model and specifications of the same are to be furnished by vendor.	Vendor to specify	
2.3	New UV flame failure device and auto ignition system for each burner have to be provided.	Vendor to specify	
2.4	The burners shall be lighted by means of new spark plug igniters with LPG pilot burner system.	Vendor to specify	

## RETROFIT AND RECONDITIONING OF TILTING, 2 BURNER & 3 BURNER FURNACES

S.No.	PARTICULARS	SPECIFICATION / DESCRIPTION	BIDDER'S OFFER (WITH CONFIRMATION & COMPLETE TECHNICAL DETAILS)
2.5	Suitable Electronic control system to be designed for temperature control of the furnace through suitable thermocouples. Suitable quantities of new duplex thermocouples shall be provided.	Vendor to specify	
2.6	Suitable system to be designed and installed for control of furnace pressure.	Vendor to confirm	
2.7	All the furnaces must be provided with new Milli Volt type temperature controller (Range: 0 to 1200°C) and digital three point strip chart temp recorder(Range 0 to 1200°C) with printers for printing temperature graph and one spare temperature recorder shall be provided for each furnace. Makes of temp recorders: Chino Laxsons, Yokogawa,	Vendor to specify	
2.8	New safety interlocks must be provided wherever required particularly whenever the thermocouples fails, burners fails, solenoids open/closes, furnace pressure increases etc. The following interlocks shall be provided in addition to some other interlocks which the vendor can suggest and implement.  <ul style="list-style-type: none"> <li>a. Main gas solenoid valve valves are to be disabled if <ul style="list-style-type: none"> <li>i.air pressure low</li> <li>ii.Gas pressure is low</li> <li>iii.Failure of power</li> <li>iv.Main gas solenoid valve is interlocked with individual zone temperature high so as to disable the flow of gas.</li> <li>v. Gas solenoid valve near each burner are interlocked such that in case of flame failure, the flow of fuel is to be disabled.</li> </ul> </li> </ul>	Vendor to specify	
2.9	New air pressure gauge, air pressure switch, fuel pressure gauge, fuel pressure switch have to provided and installed for all the three furnaces.	Vendor to specify	

## RETROFIT AND RECONDITIONING OF TILTING, 2 BURNER & 3 BURNER FURNACES

S.No.	PARTICULARS	SPECIFICATION / DESCRIPTION	BIDDER'S OFFER (WITH CONFIRMATION & COMPLETE TECHNICAL DETAILS)
2.10	Audio visual alarm annunciator shall be supplied installed on instrument panel. It must operate for the following mal-functions. <ul style="list-style-type: none"> <li>a. Low combustion air pressure</li> <li>b. High gas pressure</li> <li>c. Low gas pressure</li> <li>d. High temp of zone</li> <li>e. Flame failure</li> <li>f. Any unforeseen circumstances other than above</li> </ul>	Vendor to Confirm	
2.11	Where ever the combustion air pipeline is damaged, that must be replaced with new pipeline. All the valves and fittings must be replaced with new.	Vendor to confirm	
2.12	The pressure transmitter and rotary electrical actuator for flue exhaust damper (wherever available) actuation must be replaced with new items.	Vendor to confirm	
2.13	New digital meters for Temperature, voltage, current etc must be provided on the panel.	Vendor to confirm	
2.14	All incoming and outgoing cables shall be through 3mm thick gland plate provided at the bottom of the panel.	Vendor to confirm	
2.15	In case the zonal temperature overshoots the maximum set value, it should shut off the zonal (fuel) valve. At the same time, the system should annunciate an audio visual alarm.	Vendor to specify	
2.16	Orifice type flow meter with pressure transmitter & tubing shall be provided at main line of LPG to measure the flow. Vendor must supply the same and install. Vendor to specify the brand / model.	Vendor to specify	
2.17	Suitable system for recording the consumption of fuel for each cycle shall be provided	Vendor to confirm	
2.18	All power, control, reference cables, including termination material, cable racks, conduits, earthing material shall be replaced with new.	Vendor to specify	
2.19	Any tools and tackles, instruments and materials required for further maintenance of BHPV shall be provided.	Vendor to specify	

## RETROFIT AND RECONDITIONING OF TILTING, 2 BURNER & 3 BURNER FURNACES

Page 8 of 12

S.No.	PARTICULARS	SPECIFICATION / DESCRIPTION	BIDDER'S OFFER (WITH CONFIRMATION & COMPLETE TECHNICAL DETAILS)
2.20	Essential spare items, consumables, spare bricks, insulating material, refractory material must be supplied along with the items of retrofitting the furnace.	Vendor to specify	
2.21	All butterfly valves, AUDCO valves, thermocouples, compensating leads, solenoid valves etc must be replaced with new.	Vendor to specify	
<b>3.0</b>	<b>The following items are to be retrofitted / reconditioned / repaired.</b>		
3.1	The fixed hearth of side wall, under ground flue duct shall be lined with conventional refractory and insulation bricks etc.	Vendor to specify	
3.2	The existing blowers are to be checked and reconditioned.	Vendor to specify	
3.3	The furnace door rise and fall and tilting door shall be checked and reconditioned for smooth lifting and lowering movement. The motor, connections, lifting and lowering arrangement, clamping arrangement, top and bottom sand seal arrangement to avoid leakages of hot gases should be thoroughly checked and reconditioned.	Vendor to specify	
3.4	Under LPG gas train equipment shall be thoroughly checked for replacement/reconditioning	Vendor's scope	
3.5	All valves, gas shut off valves, pumping unit under gas firing shall be replaced with new ones.	Vendor's scope	
<b>4.0</b>	<b>Painting of the Furnaces :</b> Complete Furnace body, bogie, blower and all furnace related items etc., shall be painted with two coats of reputed brand of Premium heat resistant Apple Green color paint. Letters, numerals etc. will have to be painted with a different color as required / as indicated by BHPV at the time of final painting. For electrical panel boxes inside area is to be painted with two coats of white enamel paint. Painting should be carried out according to the standard procedure for painting including cleaning and removing old paint, applying metal primer putty etc. Good finish should be ensured. <b>Overall furnaces aesthetic view should be taken care of.</b>	Vendor to confirm.	

## RETROFIT AND RECONDITIONING OF TILTING, 2 BURNER & 3 BURNER FURNACES

S.No.	PARTICULARS / SPECIFICATION / DESCRIPTION	BIDDER'S OFFER (WITH CONFIRMATION & COMPLETE TECHNICAL DETAILS)
5.0	<p>1. Dismantling of the furnace assemblies and bogie into individual parts, degreasing, chemically cleaning, pre-painting of structural parts, joint inspection to finalize the detailed list of</p> <p style="margin-left: 20px;">a. Spares to be bought out b. Spares to be manufactured</p> <p>The list should be approved by BHPV. Drawings of spares to be manufactured and specifications for bought out items shall be submitted to BHPV by the vendor for approval.</p> <p><b>SPARES :</b> For the above mentioned spare parts (electrical/ mechanical / electronics / Instrumentation) required to be replaced beyond the spares quoted by the vendor along with offer, approved by BHPV after joint inspection, BHPV will supply spares available with them or procuring the spares.</p> <p>2. A separate tender will be floated for these spares (bought out spares and spares to be manufactured). The vendor shall also compulsorily participate in the above tenders quoting for all the spares. The spares will be ordered on the lowest party and the spares will be given to the vendor for assembly into the furnace. No extra cost will be paid for the fitment and assembly of these spares.</p> <p style="margin-left: 20px;">a. Spares required to be replaced other than those agreed to during joint inspection will have to be approved by BHPV before such replacement is affected. Cost of such spares shall be absorbed by the Contractor. BHPV will not pay for these items. b. Prior intimation has to be given to BHPV by the contractor for deputing the team for joint inspection at BHPV / contractor works.</p>	Vendor to confirm
5.1	Operational spares for 2 Years should be quoted separately.	Vendor to confirm
5.2	A spare parts manual should be provided along with the parts list.	Vendor to confirm
<b>6.0</b>	<b>Prove-out test</b>	
6.1	The required temperatures, safety features prove out, calibration of furnace, pressure gauges, temperature recorders, material temperature, furnace temperature etc must be shown to production and maintenance personnel of BHPV. The job trials for sufficient number of jobs must be shown to BHPV personnel. The heat treatment cycle and furnace temperature graphs must be certified by the quality department of BHPV.	

## RETROFIT AND RECONDITIONING OF TILTING, 2 BURNER & 3 BURNER FURNACES

S.No.	PARTICULARS / SPECIFICATION / DESCRIPTION	BIDDER'S OFFER (WITH CONFIRMATION & COMPLETE TECHNICAL DETAILS)
6.2	After successful job tests, the furnace should be handed over to production division for their trail run and regular heat treatment cycle would begin on the furnace. After completely satisfying themselves with regards to the heat treatment cycle, stress relieving jobs, temperature accuracies, loading capacity, complete functioning of furnaces etc., the Production and maintenance personnel would then release the satisfactory performance certificate for the furnace. Only on receipt of such certificate, the work would be deemed as completed.	
7.0	<b>BHPV's Scope of work:</b>	
7.1	Material handling facilities to be given for Mechanical, Electrical and Instrumentation requirements which should come up during retrofitting.	
7.2	Oil, gas, water, compressed air etc required for testing the furnace will be provided by BHPV.	
7.3	All necessary documents, drawings available with BHPV related to Furnace will be given to vendor	
<b>8.0</b>	<b>Miscellaneous</b>	
8.1	The supplier should give a point-by-point reply to the specifications	
8.2	<p>The following manuals should be supplied along with the retrofit of the furnace.</p> <ol style="list-style-type: none"> <li>1. Electrical Circuit diagrams – 3 sets</li> <li>2. Circuit diagrams for all PCBs - 3 Sets</li> <li>3. O&amp;M Manuals (hard copy &amp; Soft Copy) for Electrical, Electronics &amp; Instrumentation system – 3 sets</li> <li>4. Details of all Mechanical, Electrical, instrumentation, Electronics modifications &amp; fittings with drawings – 3 sets</li> <li>5. Spare parts manual – 3 sets</li> <li>6. Complete block diagram with pipelines of furnace after retrofit -3 sets.</li> </ol> <p style="text-align: right;">All the manuals, software, wiring diagram, circuit diagrams etc in CD - 2 sets.</p>	
8.3	The operation manual should contain exhaustive details of the operation of Furnace.	

## RETROFIT AND RECONDITIONING OF TILTING, 2 BURNER & 3 BURNER FURNACES

S.No.	PARTICULARS / SPECIFICATION / DESCRIPTION	BIDDER'S OFFER (WITH CONFIRMATION & COMPLETE TECHNICAL DETAILS)
8.4	The supplier should provide at least 2 days training in operation, programming, interfacing and maintenance at BHPV for production and maintenance personnel for each furnace.	
8.5	The supplier should provide 1 Year warranty from the date of retrofit & reconditioning of the Furnaces.	
8.6	Operational spares for 2 Years should be quoted separately. The spares should include spare bricks, solenoid valves, limit switches, insulating material, relays, pressure gauges, instrumentation items, bogie wheels, A4 size color LaserJet printer and other essential spares.	
8.7	Place of Work: The supplier can execute the complete reconditioning and retro fitment activity at BHPV, Visakhapatnam or at supplier's works. If the furnace / bogie / blower parts are to be taken to the supplier's works, the transportation cost (to & fro, insurance) has to be borne by the supplier.	
8.8	Name plates, instruction plates shall be replaced with new ones. One plate with Furnace specifications in full, name & address of reconditioning party, year of reconditioning etc. should be riveted on front / rear side of furnace.	Vendor to specify
8.9	Oiling points with periodicity, type of oil to be used shall be indicated on the furnace, if any.	Vendor to specify
8.10	Bar chart showing the time required for the following elements to be given covering the period of delivery quoted a) Dismantling of furnace at BHPV works b) Complete cleaning and joint inspection of components at BHPV works to identify parts for replacement and rework. c) Manufacturing, rework/repairing etc. of the components, completion of scraping work and sub-assemblies d) Complete retrofit & reconditioning work e) Re-erection & re-commissioning at BHPV works f) Job trial and prove out	Vendor to confirm
8.11	Any modifications carried out shall not sacrifice original temp ranges, safety features, bogie speed, refractory linings, original function of furnace etc.	Vendor to specify

## RETROFIT AND RECONDITIONING OF TILTING, 2 BURNER & 3 BURNER FURNACES

S.No.	PARTICULARS / SPECIFICATION / DESCRIPTION	BIDDER'S OFFER (WITH CONFIRMATION & COMPLETE TECHNICAL DETAILS)
8.12	<p><b><u>REWORK IN LIEU OF REPLACEMENT :</u></b> Reworks in lieu of replacement on the parts like ( bushes, box nuts, screw rods etc.) preferably chrome plating / welding / machining / grinding etc. identified initially and also during joint inspection shall be in the scope of vendor. BHPV will not pay extra for these works.</p>	Vendor to confirm
8.13	BHPV reserves the right to inspect the progress as well as workmanship at any stage of the work. Decision of BHPV Representative shall be final in the matter of inspection at any stage. Contractor shall extend necessary co-operation to enable such inspection.	Vendor to confirm
8.14	All discarded / replaced parts shall be returned to BHPV.	Vendor to confirm
8.15	Any work (Mechanical, Electrical and Instrumentation) not mentioned in this scope of work to keep the Furnaces in working condition with all features and accuracies are in the scope of the contractor.	Vendor to specify
8.16	The contractor is required to study the furnaces, the scope of supply and certify the completeness of scope in order to execute the work. In case of any discrepancies in the scope of work, the contractor is required to highlight the same to BHPV before submission of the offer.	Vendor to specify
8.17	Lodging & Boarding facilities for the contractor personnel are at Contractor's scope (during dismantling period, re-erection & re-commissioning period and for troubleshooting during performance guarantee period). BHPV is not responsible for this.	Vendor to confirm
8.18	<b>Interpretation:</b> Any dispute of difference of opinion in respect of the interpretation, effect or application of this particular condition of the Contract or of the amount recoverable hereunder from the vendor shall be decided by the Contractee and the decision shall be final and conclusive.	Vendor to confirm
8.19	<b>Subletting:</b> The vendor shall not sublet or assign this work or any part thereof without the written permission of BHPV. In the event of the vendor subletting or assigning this work or any part thereof without such permission, BHPV shall be entitled to cancel the contract and execute the contract elsewhere at the risk and account of the vendor and the vendor shall be liable for any loss or damage which BHPV may sustain in consequence of or arising out of such contract elsewhere.	Vendor to confirm

**COMMERCIAL TERMS AND CONDITIONS FOR SUBMISSION OF OFFER****1.0 QUOTATIONS**

Bidders shall submit the offer in TWO INNER ENVELOPES as indicated below which shall be sealed in one outer envelope.

**Envelope I:** This sealed envelope should contain all the copies of technical bid together with un-priced commercial bid. This envelope should be clearly marked “**Part I – Technical and Un-priced commercial bid**” Indicating Tender No., Due Date and Address & Reference of the Bidder.

**Envelope II:** This sealed envelope should contain price details this envelope should be clearly marked “**Part II - Price bid**” indicating Tender No., Due Date and Address & Reference of the Bidder.

Both the envelopes (Part I & II) shall be put in one cover, duly sealed, super scribing as Part I and Part II of Tender No., due date of opening and the address and reference of the Bidder

The above offer should reach this office on or before the due date by 14.00 Hrs (IST)  
Tender should not be addressed to any Individuals name but only designation to

**Dy. General Manager (MM)**  
**BHARAT HEAVY PLATE & VESSELS LIMITED**  
**VISAKHAPATNAM - 530 012 (A P), INDIA.**

Tenders should be free from CORRECTION AND ERASURES. Corrections if any must be attested. All amounts shall be indicated both in words as well as in figures. Where there is difference between amount quoted in words and figures, amount quoted in words shall prevail.

Offers should be in ENGLISH and accompanied by technical literature catalogue and detailed dimensional drawings in ENGLISH or otherwise the offers will not be considered.

**2.0 PART I (TECHNICAL & UN-PRICED COMMERCIAL BID)****2.1 Technical**

This part shall include / indicate the following:

- 2.1.1. Offer should contain complete scope of supply with all technical details, specifications, delivery and other commercial terms and conditions.
- 2.1.2. Point by point confirmation for the Technical Specification enclosed is to be provided. If there are any deviations the same should be clearly specified. Offers received without conformation to our specification will be rejected.
- 2.1.3. List of customers to whom same or similar equipment have been supplied along with performance certificates to be enclosed.
- 2.1.4. Relevant catalogue to be attached.
- 2.1.5. List of spares parts (with part numbers) for two years operation and maintenance should be attached.

2.1.6. Information on shipping weight and cubage (length, width & height) to be provided

2.1.7. In case of foreign bidder offer, the Principal's technical offer only should be enclosed.

## 2.2 Un-Priced Commercial

This part shall include / indicate the following

2.2.1. Port of shipment / Station of dispatch

2.2.2. Terms of payment

2.2.3. FOB/FCA price along with freight charges up to Chennai port (for foreign bidders) Ex-works/FOR Dispatch Station price along with freight charges up to BHPV Visakhapatnam (for Indian bidders)

2.2.4. Taxes, Service tax & duties including Cess applicable.

2.2.5 Delivery Schedule

2.2.6. Filled-in check list to be enclosed

2.2.7. Offer validity

2.2.8. Country of origin

2.2.9. Percentage of agency commission if any along with a copy of Agency agreement The FOB/FCA/CFR Prices quoted shall include the agency commission.

2.2.10. A copy of "Un-Priced Part II 'i.e., a copy of the Price Bid without the price details to be enclosed.

2.2.11 BHPV is eligible for availing CENVAT / VAT credit on both inputs and capital inputs. The suppliers invoice should separately indicate the amount of duty / taxes and should invariably mention the following details:

1. The Central excise registration number, range division and commission rate of the supplier's jurisdiction.
2. The rate of duty and 8 digit central excise tariff heading of the item supplied.
3. The TIN, VAT, CST registration number of the supplier.

The duplicate copy of the invoice is required for availing CENVAT credit and original copy for availing VAT credit, if purchased within the state.

In case of foreign bidders the duplicate copy of the electronic Bill of Entry along with TR6 challan should be made available for availing CENVAT credit on CVD, Cess (S) and SAD.

## 3.0 **PART II (PRICE –BID)**

This part should contain the schedule of price particulars and to be co-related to the technical details provided in Part-I

## 4.0 **OPENING OF TENDERS**

The Part I – Technical & un-priced commercial bid alone would be opened on the Tender opening date.

The Part II – Price bid of technically suitable Bidders alone would be opened. The Technically suitable Bidders would be informed about the Price Bid opening date. Clarifications if any required by BHPV FOR Technical evaluation / commercial evaluation would be sought from Bidders before opening of Part II – price bid.

### GENERAL

5.1 Incomplete offers will not be considered.

5.2 **Fixed priced:** Prices quoted by the bidder shall be fixed and not subject to any escalation whatsoever during the period of bid validity and execution of the Purchase Order A bid submitted with an adjustable price will be treated as non- responsive and rejected Prices shall be written in words and figures. In the event of difference, the price in words shall be valid and binding. Unit prices shall be considered correct in the event of any discrepancy with regards to total price.

5.3 **Bid currency:** Indian bidders should submit the prices only in Indian Rupees. Foreign bidders may submit their bid in their home currency, which should be clearly indicated in the un-priced commercial bid as well as in the price bid.

- 5.4 **Terms of Delivery:** Bidders are required to quote their best delivery period. Foreign Bidders should submit their offer for net FOB/ FCA – Nearest Sea Port / Air Port as well as CFR / Chennai Seaport/ Airport. Freight charges up to Chennai port to be indicated separately. Indian Bidders should submit their offer for Dispatching station as well as FOR BHPV Visakhapatnam basis. Freight charges from works to BHPV Visakhapatnam to be indicated separately. Delivery from the date of Letter of Intent to be mentioned in the offer.
- 5.5 **Taxes and Duties:** All Taxes and Duties payable as extra to the quoted price should be specifically stated in offers along with CST & TIN No/ Tariff No. etc, failing which the purchaser will not be liable for payment of such Taxes and Duties (Our TIN No.28280189432, APGST No. VSP/04/1/1023 dated 24.08.1968. CST No.VSP/04/1/1012 dated 24.08.1968 & BHPV ECC No AAA CB 7076 N-XM001. Assessment circle Visakhapatnam.)
- 5.6 **Validity:** The offers for main equipment and spares shall be kept open for acceptance for a period of 120 days (one hundred and twenty days) from the dates of opening of the tender (part I)
- 5.7 **Terms of Payment:**
- 5.7.1 **Indian Bidders:**
- 5.7.1.1 90% payment (90% of basic price + 100% Taxes) will be made within 45 days of receipt of material and balance 10% will be made after acceptance of material/commissioning of the equipment at BHPV, Visakhapatnam and on submission of Performance Bank Guarantee.
- 5.7.2 **Foreign Bidders**  
An Irrevocable letter of Credit shall be established for 80% of FOB/FCA/CFR/ (excluding Indian Agent's commission) 2 months prior to shipment and valid for 3 months for negotiation against shipment Letter of Credit shall be opened through a branch of State Bank of India in the country where order shall be placed. In case, in the country where order is placed, State Bank of India is not there, Letter of Credit will be confirmed by foreign banker. Balance 20% of FOB/FCA/CFR value shall be paid through sight draft on Commissioning & acceptance of the equipment at BHPV Visakhapatnam, against submission of 10% performance bank guarantee. All Bank charges outside India are to supplier's account. Lump sum erection and commissioning charges if any, shall be payable after satisfactory erection & commissioning of the equipment by sight draft against certificate issued by the competent authority.
- 5.7.3 **Common to both India & Foreign Bidders.**  
Erection & Commissioning (E&C) charges will be released after deduction of Income Taxes as per the Govt. of India rules. The TDS certificate will be issued by BHPV. Applicable service tax on E&C charges will be payable extra. The liability of depositing the same to the Govt. will be of the supplier.
- 5.7.4 **Loading criteria common to both Indian and foreign bidders:** Vendor should accept the payment terms specified above. However for any deviation to the payment terms offered with reference to the above criterion will be loaded with prime lending rate of SBI prevailing on date of opening of price bid + 2%, which shall be computed for the differential period between BHPV terms of payment and the offered basic price.
- 5.8 DUNS number (allotted by M/s. DUN & Bradstreet) shall be mentioned in your offer.
- 5.9 **Guarantee:** The equipment shall be guaranteed for a period of 18 months from the date of supply or 12 months from the date of commissioning and acceptance whichever is earlier.  
**Offers from vendors not accepting to the requested guarantee period will be rejected.**

5.10 **Contract Execution Bank Guarantee (CEBG):** The successful tenderer shall furnish a Bank Guarantee from any Nationalized Bank for 5% of Purchase Order value (FOR Dispatching station value – Excluding taxes, duties, freight & insurance – for Indian bidders) & (FOB/FCA value – excluding freight & insurance – for foreign bidders) confirming that the order will be executed as per the terms and conditions and this should be valid till final dispatch date (LR/GR/BL/AWB) with additional 2 months claim period. Letter of Credit will be processed only after receipt of CEBG. The CEBG is to be furnished within 3 weeks from the date of Purchase order.

**Offers from vendors not accepting to submit CEBG will be rejected.**

5.11 **Performance Bank Guarantee (PBG):** The supplier shall furnish a Bank guarantee from any Indian Nationalized Bank approved by BHPV in the format, given by BHPV along with purchase order for 10% of the Purchase Order value (FOR Dispatching station value – Excluding taxes, duties, freight & insurance – for Indian bidders) & (FOB/FCA value – excluding freight & insurance – for foreign bidders) valid for period of guarantee with additional claim period of 2 months.

**Offers from vendors not accepting to submit PBG will be rejected.**

The CEBG & PBG shall be obtained from any Indian Nationalized Bank

5.12 **Liquidated damages:** Delivery of the goods specified in the purchase order should be made within the time prescribed. Failure to dispatch the materials in the time as per the delivery quoted in our Purchase Order would make the supplier liable to an un-conditional penalty at the rate of ½% of the value of goods for each week of delay subject to a maximum of 10% of the Purchase Order value.

5.12.1 **Loading Criteria for Liquidated Damages:** Any deviation from above LD Clause to the extent for which LD is not agreed by the vendor i.e., differential % value will be loaded on basic price, e.g. If some vendor agrees for say maximum of 6% LD then his price will be loaded by 4% (10 – 6) of his quoted basic price.

5.13 **Risk purchase:** If the supplier fails to deliver the goods within the delivery specified in the Purchase Order, BHPV will be entitled to terminate the contract and to purchase elsewhere at the risk and cost of the seller either the whole of the goods or any part which the supplier has failed to deliver or dispatch within the delivery period mentioned in the Purchase Order.

**Offers from vendors not accepting the above Risk Purchase terms will be rejected.**

5.14 **Indian Agent & Agency commission:** An Indian Agent can represent only one Foreign Manufacturer against a particular Tender. The FOB/FCA/CFR price quoted by the Foreign bidder shall include the agency commission. However, the agency commission component payable to their Indian Agents shall be shown separately in the offer. This will be paid by BHPV in India Rupees, on satisfactory commissioning & acceptance of the equipment. Copies of current Agency Agreement / Authorization Letter in respect of Agency Commission shall be furnished along with offer. For calculation of Rupee equivalent of Agency Commission exchange rate as prevailing on the date of Purchase Order will be taken.

5.15 **Short shipment / Warranty replacement:** In case of any short shipment in the main equipment / spares, customs duty levied on such supplies, shall be borne by the supplier. Any warranty replacement during the warrantee period shall be on FOR, BHPV - Visakhapatnam, basis.

- 5.16 **Inspection & Testing:** All goods shall be subject to inspection by BHPV or its authorized representatives at supplier's works or at BHPV stores. The supplier will not charge for the facilities provided for inspection of goods. In case of machine tools the machine would be inspected and proved at supplier's works prior to dispatch however, final inspection and acceptance of the machine will be carried after installation of the machine at BHPV, Visakhapatnam.
- 5.17 **Operating and Maintenance manuals:** The Bidders shall clearly mention in their offer that Operating Maintenance Manuals as called for in the Technical Specification in the required number of copies will be provided.
- 5.18 **Cenvat & VAT credit. (for Indian Bidders only):** The quotation must indicate Tariff item number and rate of Excise Duty applicable. The original Excise Duty Gate Pass will be required to be furnished in case charges to us. If the bidder is availing Cenvat credit for his input materials, the effect of proforma credit should be passed on to the purchaser.
- 5.19 **Packing:** The Supplier shall arrange for packing suitably in all respects considering the peculiarity of the material involves for normal transport by sea / air / rail road and suitably protected against effect of tropical salt laden atmosphere in the event of shipment being delayed at ports.
- 5.20 **Salient Points of HSE** (Health, Safety & Environment) that are to be considered while submissions of offer are:
- 5.20.1 Consumption benchmarks related to output shall be provided wherever applicable for key input resources (energy/fuels/chemicals)
- 5.20.2 Competency requirements for operation, maintenance and calibration, if any, shall be communicated
- 5.20.3 If any Hazardous chemicals as per MSIHC (Manufacturing, Storage and import of Hazardous Chemicals) Rules 1989/94/2000 are used, the MSDS shall be provided, along with on site & OFF site emergency plan (as applicable).
- 5.20.4 The noise level at operator level shall be within 90 Dba
- 5.20.5 OH&S (Occupational Health and Safety) control measures for safe working of machine as applicable shall be specified
- 5.20.6 The machine/equipment shall be fitted with guard for rolling and moving parts and shall comply with applicable OH&S legislations and Factories Act 1948
- 5.20.7 The supplier shall submit the layout drawing of operating controls, displays etc and operating instructions to enable ergonomics evaluation and approval
- 5.20.8 The recommended PPE (Personal Protective Equipment) for the equipment shall be furnished
- 5.20.9 Alarm System (both visual and audible) and Automatic switch off of the equipment shall be provided for any intrusion, overloading, short circuiting or any malfunctioning of the equipment.
- 5.20.10 Details of all hazardous / harmful substances discharges as by-products / wastes during operations of the machine / equipment, such as fumes, gases, dust particles, aerosols UV./IR (Ultra violet / Infra red) radiations, etc shall be furnished, along with their concentrations and their TLV, (Threshold Limit Value)

- 5.20.11 Appropriate pollution control measures shall be proposed to keep the emissions from the machinery / processes within the prescribed limit as stated in Environment Protection Rules 1986.
- 5.20.12 All furnaces, process units, DG sets, paint booths, shot blasting chambers, etc shall be provided with stack(s) of sufficient height as per guidelines laid down in the Environment Protection Rules 1986.
- 5.20.13 wherever industry specific standards are not available for control of pollutants, general emission standards shall be used
- 5.20.14 Chemicals banned due to their negative impact on the environment shall not be used on the process
- 5.20.15 Fuels with sulphur content less than 0.05% shall be proposed.
- 5.20.16 Details regarding nature of waste generated and appropriate disposal practices available shall be provided, along with the operation procedure of the plant / process.
- 5.20.17 Hazardous chemicals and flammable substances shall be transported only through authorized transporters and all safety practices as laid down in applicable legislative requirements such as Central Motor Vehicle Rules, Manufacture, Storage and Import of Hazardous Chemical 1989, etc. shall be followed.
- 5.20.18 Primary materials used in the equipment shall be specified and they shall be eco - friendly.
- 5.21 Evaluation of offers shall be on the basis of delivered cost (Net cash outflow to BHPV).
- 5.22 BHPV also reserves its right to allow to the Public Sector Enterprises ordering and price preference facilities as admissible under the existing policy.
- 5.23 BHPV reserves its right to reject a tender due to unsatisfactory past performance in the execution of a contract at another project / unit.
- 5.24 BHPV shall be at liberty to reject or accept any tender, part or in full, at their own discretion and any such action is not liable for any question or claim against BHPV.
- 5.25 BHPV reserves the right to go for a Reverse Auction (RA) instead of opening the submitted sealed bid, which will be decided after technical evaluation. Information and general terms and conditions governing RA are given below.

### **GENERAL TERMS AND CONDITIONS OF RA (REVERSE AUCTION)**

Against this enquiry for the subject item/system with detailed scope of supply as per enquiry specifications. BHPV may resort to "REVERSE AUCTION PROCEDURE" i.e., ON LINE BIDDING ON INTERNET.

1. For the proposed reverse auction, technically and commercially acceptable bidders only shall be eligible to participate.
2. BHPV will engage the services of a service provider who will provide all necessary training and assistance before commencement of on line bidding on internet.
3. BHPV will inform the vendor in writing in case of reverse auction, the details of service provider to enable them to contact & get trained.

4. Business rules like event date, time, start price, bid decrement, extensions etc. also will be communicated through service provider for compliance.
  5. Vendors have to fax the Compliance form in the prescribed format (provided by Service provider) before start of Reverse auction. Without this, the vendor will not be eligible to participate in the event.
  6. BHPV will provide the calculation sheet (e.g., EXCEL sheet) which will help to arrive at “Total Cost to BHPV like Packing & Forwarding charges, taxes and Duties, Freight charges, Insurance, Service Tax for Services and loading factors (for non-compliance to BHPV standard Commercial terms & conditions) for each of the vendor to enable them to fill-in the price and keep it ready for keying in during the Auction.
  7. Reverse auction will be conducted on scheduled date & time.
  8. At the end of Reverse Auction event, the lowest bidder value will be known on the network.
  9. The lowest bidder has to Fax the duly signed Filled-in prescribed format as provided on case-to-case basis to BHPV through Service provider within 24 hours of Auction without fail.
  10. Any variation between the on-line bid value and the signed document will be considered as sabotaging the tender process and will invite disqualification of vendor to conduct business with BHPV as per prevailing procedure.
  11. In case BHPV decides not to go for Reverse Auction procedure for this tender enquiry, the Price bids and price impacts, if any, already submitted and available with BHPV shall be opened as per BHPV’s standard practice.
- 5.26 **Force Majeure clause:** If at the time during the continuance of this contract the performance in whole or in part by either party of any obligations under this contract shall be prevented or delayed by reason, of any war, hostilities, acts of the public enemy, civil commotion, sabotage, fires, explosions epidemics, quarantine, restrictions or acts of GOD (hereinafter referred to as events) then provided notice of happening of any such events is given by either party to other within twenty one days from the date of occurrence thereof neither party shall reason of such events be entitled to terminate this contract nor shall either party have any such non performance and delay is resumed as soon as practicable after such events has come to an end or ceased to exist, if the performance in whole or part of any obligation under this contract is prevented or delayed by reason or any such event claims for extension of time shall be granted for period considered reasonable by the purchaser subject to prompt notification by the seller to the purchaser of the particulars of the events and supply to the purchaser if required of any supporting evidence. Any waiver of time in respect of partial installment shall not be deemed to be a waiver of time in respect of remaining deliveries.

**CHECK LIST**

Bidder's acceptance to BHPV's Standard Commercial Terms &amp; Conditions.

**Applicable for Indian bidders**

(To be submitted along with the offer – please do not change the format)

<b>BHPV Tender No: &amp; Date:</b>	Bidders Confirmation / response
Technical Confirmation to BHPV's Specification	Furnished /Not Furnished
Prices have been quoted on "FIRM PRICE" basis only.	Yes / No
Prices have been quoted on "F.O.R BHPV" basis only.	Yes / No
Validity of offer (we require a minimum period of 120 days from the date of Tender Opening – <b>please Specify</b> )	
Sales Tax ( <b>please Specify</b> )	
Excise Duty ( <b>please Specify</b> )	
Delivery period from the date of Purchase Order ( <b>please Specify</b> ). A loading @ ½ % of the Purchase Order value per week will be done for the grace period requested. For evaluation 4 weeks will be considered as one month. Vendors quoting a delivery period beyond the 'the requested delivery plus the allowed grace period' is liable for rejection.	
Liquidated damages as per clause 5.12 (we require acceptance to @ ½% per week subject to a maximum of 10%).	
Risk Purchase as per clause 5.13 <b>(Offers from vendors not accepting the Risk Purchase terms will be rejected)</b>	Yes / No
Payment terms : 90% payment will be made within 45 days of receipt of material and balance 10% will be made after acceptance of material/commissioning of the equipment at BHPV Visakhapatnam and on submission of Performance Bank Guarantee.	
Contract Execution Bank Guarantee (CEBG) as per Clause 5.10 ( <b>Offers from vendors not accepting to submit CEBG will be rejected</b> )	Yes / No
Performance Bank Guarantee (PBG) as per Clause 5.11 ( <b>Offers from vendors not accepting to submit PBG will be rejected</b> )	Yes / No
Guarantee as per clause 5.9 (The equipment shall be guaranteed for a period of 18 months from the date of supply or 12 months from the date of commissioning and acceptance whichever is earlier). <b>(Offers from vendors not accepting to the requested guarantee period will be rejected)</b>	Yes / No
Approximate Net Weight of the total Consignment	
Approximate Gross Weight of the total Consignment	

**Signature & Office Seal of the bidder**

**CHECK LIST**

Bidder's acceptance to BHPV's Standard Commercial Terms &amp; Conditions.

**Applicable for foreign bidders** (To be submitted along with the offer – please do not change the format)

<b>BHPV Tender No: &amp; Date:</b>	Bidders Confirmation / response
Technical Confirmation to BHPV's Specification	Furnished / Not Furnished
Prices have been quoted on "FIRM PRICE" basis only.	Yes / No
Prices have been quoted on "F.O.R BHPV" basis only.	Yes / No
Validity of offer (we require a minimum period of 120 days from the date of Tender Opening – <b>please Specify</b> )	
Currency in which quoted ( <b>please Specify</b> )	
Port of loading ( <b>please Specify</b> )	
Country of Origin ( <b>please Specify</b> )	
Sales Tax ( <b>please Specify</b> )	
Excise Tax ( <b>please Specify</b> )	
Delivery period from the date of Letter of Intent ( <b>please Specify</b> )	
Liquidated damages as per clause 5.12 (we require acceptance to @ ½% per week subject to a maximum of 10%)	
Risk Purchase as per clause 5.13 ( <b>Offers from vendors not accepting the Risk Purchase terms will be rejected</b> )	Yes / No
Payment terms (An irrevocable Letter of Credit shall be established for 80% of FOB/FCA/CFR (excluding Indian Agent's Commission) 2 months prior to shipment and valid for 3 months for negotiation against shipment. Letter of Credit shall be Opened through a branch of State Bank of India in the country where Order shall be Placed. In case, in the Country where order is placed State Bank of India is not there, Letter of credit will be opened through our bankers or as permitted by Government of India. Letter of Credit will not be confirmed by foreign banker. Balance 20% of FOB/FCA/CFR value shall be paid through sight draft on Commissioning. & acceptance of the equipment at BHPV, Visakhapatnam against submission of 10% performance Bank Guarantee. All Bank charges outside India are to Supplier's account. Lump sum erection and Commissioning charges, if any shall be payable after satisfactory erection and Commissioning of the Equipment by sight draft against Certificate issued by the competent authority as per clause 5.7.2)	
Agency commission (refer clause 5.14)	Acceptable / Not acceptable
Contract Execution Bank Guarantee (CEPG) as per Clause 5.10 ( <b>Offers from vendors not accepting to submit CEBG will be rejected</b> )	Yes / No
Performance Bank Guarantee (PBG) as per Clause 5.11 ( <b>Offers from vendors not accepting to submit PBG will be rejected</b> )	Yes / No
Guarantee as per clause 5.9 (The equipment shall be guaranteed for a period of 18 months from the date of supply or 12 months from the date of commissioning and acceptance whichever is earlier). ( <b>Offers from vendors not accepting to the requested guarantee period will be rejected</b> )	Yes / No
Approximate Net Weight of the total Consignment	
Approximate Gross Weight of the total Consignment	

Signature &amp; Office Seal of the bidder