

	TECHNICAL SPECIFICATION FOR MASONRY & ALLIED WORKS	SPECIFICATION NO. PE-TS-999-600-C008	
		VOLUME - II B	
		SECTION - D	SUB-SECTION – C8
		REV.NO. 00	
		SHEET 1	OF 7


VOLUME – II B
CIVIL, STRUCTURAL & ARCHITECTURAL WORKS

SPECIFICATION NO. PE-TS-999-600-C008

SECTION - D

GENERAL TECHNICAL SPECIFICATION

MASONRY & ALLIED WORKS



Bharat Heavy Electricals Limited
Project Engineering Management
PPEI Building, Power Sector,
Plot No. 25, Sector 16A,
Noida (U.P.)-201301

	TECHNICAL SPECIFICATION FOR MASONRY & ALLIED WORKS	SPECIFICATION NO. PE-TS-999-600-C008	
		VOLUME - II B	
		SECTION - D	SUB-SECTION - C8
		REV.NO. 00	

SHEET 2 OF 7

TABLE OF CONTENT

CLAUSE NO.	DESCRIPTION	PAGE NO.
1.00.00	SCOPE	3
2.00.00	INSTALLATION	3
3.00.00	I.S. CODES	7

	TECHNICAL SPECIFICATION FOR MASONRY & ALLIED WORKS	SPECIFICATION NO. PE-TS-999-600-C008	
		VOLUME - II B	
		SECTION - D	SUB-SECTION - C8
		REV.NO.	00
		SHEET	3 OF 7

**TECHNICAL SPECIFICATION
FOR
MASONRY & ALLIED WORKS**

1.0.0 SCOPE

This specification covers furnishing, installation, repairing, finishing, curing, protection, maintenance and handing over of masonry and allied works for use in structures and locations covered under the scope of the Contract.

2.0.0 INSTALLATION

2.1.0 Soling

2.1.1 Brick Soling

The ground shall be dressed, consolidated by ramming or by light rolling and a 12 mm thick cushion of sand laid. On the sand cushion the bricks shall be laid with fine joints and placed firmly in position by hammering with wooden mallet. The surface shall be free from undulations. The 'frog' side shall be on the underside. The joints shall be broken the in all direction and bricks cut as required. Orientation shall be as desired by the Engineer. After laying of each layer of bricks sand shall be spread over and worked into the joints to pack the bricks tight.


2.1.2 Stone Soling

The stones for soling shall be selected on the basis of thickness of soling as shown as the drawings. The larger stones shall be laid and the gaps filled by smaller stones. The interstices shall then be firmly packed with sand by flooding with water.

2.2.0 Brick Edging

Excavation shall be done close to the brick dimensions and in perfect alignment. Bricks shall be firmly placed by hammering with wooden mallets and sides and joints packed firmly with earth so that the edging is not disturbed easily. Alignment and level shall be acceptable to the Engineer.

	TECHNICAL SPECIFICATION FOR MASONRY & ALLIED WORKS	SPECIFICATION NO. PE-TS-999-600-C008	
		VOLUME - II B	
		SECTION - D SUB-SECTION - C8	
		REV.NO. 00	
		SHEET 4	OF 7
2.3.0	Masonry		
2.3.1	General	<p>All masonry work shall be true to lines and levels as shown on drawings. All masonry shall be tightly built against structural members and bonded with dowels, inserts etc. as shown on drawings.</p>	
2.3.2	Mortar	<p>Mix for mortar shall be specified in the Schedule of Items.</p> <p>When lime is used hydrated lime shall be mixed with water to form a putty and stored with care to prevent evaporation for at least 24 hours before use. Quick lime shall be slaked with enough water to make a cream, passed through a No. 10 sieve and stored avoiding evaporation for seven days before use.</p> <p>Lime putty and sand in proper proportion shall be mixed on a water-tight platform with necessary addition of water and thoroughly ground in a mortar mill. This mix shall be transferred to a mechanical mix, required quantity of cement added and the content mixed for at least 3 minutes. Mixtures of lime putty and sand may be stored avoiding drying out. For cement sand mortar cement and sand in requisite proportions shall be mixed dry in a mechanical mixer and then water added and mixed further. Minimum quantity of water shall be added to achieve working consistency.</p> <p>Surplus mortar droppings from masonry, if received on surface free from dirt may be mixed with fresh mortar if permitted by the Engineer who may direct addition of additional cement. No mortar which has stood for more than half an hour shall be used.</p>	
2.3.3	Brick Masonry	<p>Bricks shall be soaked by submergence in clean water for at least two hours in approved vats before use. Bricks shall be laid in English bond unless specified otherwise. Broken bricks shall not be used. Cut bricks shall be used if necessary to complete bond or as closers. Bricks shall be laid with frogs upwards over full mortar beds. Bricks shall be pressed into mortar and tapped into final position so as to embed fully in mortar. Inside faces shall be buttered with mortar before the next bricks is placed and pressed against it. Thus all joints between bricks shall be fully filled with mortar.</p> <p>Mortar joints shall be kept uniformly 10 mm thick. All joints on face shall be raked to minimum 10 mm depth using raking tool while the mortar is still green to provide bond for plaster or pointing. Where plaster or pointing is not provided, the joints shall be struck flush and finished immediately. Brickworks two bricks thick or more shall have both faces in true plane. Brickwork of lesser thickness shall have one selected face in true plane.</p>	

	TECHNICAL SPECIFICATION FOR MASONRY & ALLIED WORKS	SPECIFICATION NO. PE-TS-999-600-C008	
		VOLUME - II B	
		SECTION - D	SUB-SECTION - C8
		REV.NO. 00	
		SHEET 5	OF 7

2.3.4 **Exposed Brickwork**

Brickwork in superstructures which is not covered by plaster shall be as shown on drawing and executed by specially skilled mason. Courses shall be truly horizontal and vertical joints truly vertical. Wooden straight edges with brick course graduations and position of window sills and lintels shall be used to control uniformity of brick courses. Masons must check workmanship frequently with plumb, spirit level, rule and string. All brick-work shall be cleaned at the end of days work. If face bricks are specified in the drawings, the brickwork shall be in composite bricks, with face bricks on the exposed face and balance in routine bricks, but maintaining the bond fully. Where face bricks are not specified, bricks for the exposed face shall be specially selected from routine bricks. All exposed brickwork on completion of work shall be rubbed down, washed clean and pointed as specified. Where face bricks are used carborandum stone shall be used for rubbing down.

2.3.5 **Reinforced Brickworks**

Reinforcements shall be as specified in the drawings. All reinforcements shall be thoroughly cleaned and fully embedded in mortar. Where M.S. bars are used as reinforcement, these shall be laped with dowels if left in R.C. columns or welded to steel stanchions.

2.3.6 **Stone Masonry**

Stones shall be thoroughly soaked before laying. Stones shall be laid on their natural quarry beds. Individual stones shall be fitted with mallet and properly wedged to reduce thickness of mortar joints. Thickness of joint shall be not less than 8 mm and not greater than 25 mm. At least two stones shall run the full width of the wall for every square meter of surface area.

2.3.7 **Exposed Stonework**

Stonework which is to be kept exposed shall be as shown on drawing or described in the Schedule of Items. It shall be executed by specially skilled mason. Stones used for exposed face shall be specially selected. All exposed stone faces shall be kept clean and free from mortar and pointed up neatly as the work proceeds in a manner called for in the drawings or instructions. A sample wall, 10 sq.m. in area shall be built and approved by the Engineer and all works shall match with this sample.

2.3.8 **Composite Masonry**

Where stonework facing with brick masonry backing is specified the bond between them shall be achieved by bond stones of dimensions and frequency as desired by the Engineer.

	TECHNICAL SPECIFICATION FOR MASONRY & ALLIED WORKS	SPECIFICATION NO. PE-TS-999-600-C008	
		VOLUME - II B	
		SECTION - D SUB-SECTION - C8	
		REV.NO. 00	
		SHEET 6	OF 7
2.3.9	Expansion & Separation Joints	<p>Location of joints shall strictly be as shown on drawings or as instructed by the Engineer. Expansion joints shall be as shown on drawings. Expansion joint filler boards and sealing strips shall have minimum transverse joints. Transverse joints shall meet the approval of the Engineer.</p> <p>Separation joints shall be with standard water proof paper or with alkathene sheets about 1 mm in thickness. Length and sealing of laps shall be to the satisfaction of the Engineer.</p>	
2.3.10	Mouldings, Cornices, Drip Course	<p>These shall be made as shown in drawings. Bricks or stone shall be cut and dressed as required. If no subsequent finish is envisaged, these shall be rubbed to correct profile with carborandum stone.</p>	
2.3.11	Curing	<p>Masonry shall be cured by keeping it wet for seven days from the date of laying. In dry weather at the end of days work top surface of masonry shall be kept wet by ponding.</p>	
2.3.12	Embedding of fixtures	<p>All fixtures shall generally be embedded in mortar and masonry units shall be cut as required.</p>	
2.3.13	Encasing of Structural Steel	<p>This shall be done by building masonry work round flanges, webs etc. and filling the gap between steel and masonry by minimum 12 mm thick mortar. Encased members shall be wrapped with chicken wire mesh when shown on drawings or instructed by the Engineer. The minimum lap in chicken wire mesh shall be 50 mm.</p>	
2.4.0	Damp Proof Course	<p>Unless otherwise specified Damp-proof course shall be 40 mm or as per schedule thick 'artificial stone' in proportion 1:1-1/2:3 cement sand stone-chips (10 mm down) with admixture of a waterproofing compound as approved by the Engineer. The percentage of admixture shall be as per manufacturer's specifications but not less than 2% by weight of cement. The top surface shall be double chequered and cured by ponding for seven days.</p>	
2.5.0	Damp Proof Membrane		

	TECHNICAL SPECIFICATION FOR MASONRY & ALLIED WORKS	SPECIFICATION NO. PE-TS-999-600-C008	
		VOLUME - II B	
		SECTION - D	SUB-SECTION - C8
		REV.NO. 00	
		SHEET 7	OF 7

Damp proof treatment using fibre or hessian base bitumen felt shall be 6, 8 or 10 course treatment as specified in IS:1609. The number of courses shall be as mentioned. Sequence of work shall be as directed by the Engineer. Extreme care shall be taken to prevent damage to felt during and after laying. The Contractor shall be obliged to rectify any leakage appearing within 5 years of installation by removing and renewing the coats at the point of leakage.

Where shown on drawing, damp proof membrane with one layer bitumen paper or one layer alkathene sheet shall be laid with minimum 150 mm lap under slabs on grade.

3.0.0 I.S. CODES

Some of the important relevant codes for this section are :

- IS:1127 : Recommendations for dimensions and workmanship of natural building stones for masonry work.
- IS:1597 : Code of Practice for Construction of stone Masonry.
- IS:1609 : Code of Practice for laying Damp-proof treatment using bitumen felts.
- IS:2212 : Code of Practice for Brickwork.
- IS:2250 : Code of Practice for preparation and use of Masonry Mortar.
- IS:5134 : Bitumen Impregnated Paper & Board.