

Schedule 1:

Pressure Sensor, 0 - 400 bar

Pressure Sensor with 2 outputs

Output 1: Switching Output or IO-Link mode

Output 2: Analog or switching output

Range: 0 to 400 bar

Model: PS510-400-01-LI2UPN8-H1141

Make: Turck

Schedule 2:

Inductive proximity sensor Sn 15mm

Inductive proximity sensor Sn 15mm

Model: BI15-CP40-VP4X2/S100

Make: M/s Turck India

Schedule 3:

INDUCTIVE PROXI. SWITCH (NON-FLUSH TYPE)

INDUCTIVE PROXIMITY SWITCH (NON-FLUSH TYPE)

MAKE: TURCK

TYPE: N150U-CP40-VP4X2

DESCRIPTION:-Inductive sensor Rectangular, Height 40mm, Variable orientation of active face in 9 directions, Plastic, PBT-GF30-V0, High Luminance corner LEDs, Optimum view on supply voltage and Switching State from any position 4-wire DC, 10 TO 65 VDC, Changeover contact.

Schedule 4:

PROXIMITY SENSOR 10-30VDC, 50mm SENSING

INDUCTIVE PROXIMITY SENSOR

VOLTAGE: 10-30V DC

SENSING DISTANCE: 50mm

TYPE: PNP NO/NC TYPE

MOUNTING: NON-FLUSH

MODEL: N150U-CK40-VP4X2-H1141

MAKE: M/s TURCK INDIA

Schedule 5:

PROTECTIVE HOUSING FOR PROXIMITY SENSORS

PROTECTIVE FRAME FOR CP40 INDUCTIVE PROXIMITY SENSORS

TYPE: SG40/2 (ULTEM)TEMP. RESISTANT: UPTO + 170 DEG.C

INGRESS PROTECTION: IP 68

Schedule 6:

VALVE CONNECTOR TYPE A-PUR CABLE - 5M

VALVE CONNECTOR CABLE WITH TYPE A CONNECTOR AT ONE END

SHEATH MATERIAL: PUR CONNECTOR: 18MM DIN TYPE A VALVE CONNECTOR

LENGTH: 5 METRES

MODEL: VAS22-S80E-5/TXL

MAKE: M/S TURCK INDIA

Schedule 7:

M12 connector 5 pin 10 m cable

Sensor cable with connector

Sheath material: PVC

Connector: 5 Pin M12

Length: 10 metres

Model: RKC4.5T-10/TEL

Make: M/s Turck India

Schedule 8:

Ultrasonic Level Control Sensor - 1300mm

Ultrasonic Level Sensor with 2 outputs

Output 1: Switching output or IO-link mode

Output 2: Analog output

Range: 130 to 1300 mm

Model: LUS211-130-51-LI2UPN8-H1141

Make: Turck

Schedule 9:

Sensor Test Box

Sensor Test Box

Connection: Push button type terminals or via M12 connectors

Supply: 2 nos 9V battery

Model: TB3-CP80

Make: Turck

Schedule 10:

IO-Link Master with Integrated USB Port

USB-B Type Compatible IO-link master

Function: Commissioning/Parameterization of IO-link devices

Power supply: USB or external power supply unit

IO-link connection: M12

Model: USB-2-IOL-0002

Make: Turck

Schedule 11:
Double Ended 4 Pin M12 Connector Actuator or Sensor Cable - PUR Connector A: Female, M12, Straight, 4-pin Connector B: Female, M12, Straight, 4-pin Cable Length: 2m Model: RKC4.4T-2-RSC4.4T/TXL Make: Turck

Note to Supplier:

1. Any deviation against specification shall be specified without fail.
2. Delivery shall be within 3 months from the date of P.O.
3. Relevant data sheets shall be submitted along with the offer.