

Annexure-C
Technical Specifications

Item wise Technical Specifications			
Enq. Item SL.No	Technical Specifications	Qty (in M ²)	Bidder Confirmation
10	CERAMIC FIBRE BLANKETS ARE TO BE SUPPLIED AS PER THE FOLLOWING SPECIFICATIONS: DENSITY: 128Kg/m³, Size Dimensions (mm): 7300 - 7620(L) x 610(W), Thickness (mm): 25, Max Temperature Degree C: 1425, GRADE: ZIRCONIA (HTZ), Al₂O₃ (%) MIN: 33-36, ZrO₂ (%): 14-18, Shot Content (ASTM)%: 10-15, Thermal conductivity (w/mk): 0.11-0.15, Specification properties confirming to ASTM-C-892-93/LATEST. NOTE: (1) TEST CERTIFICATE FOR MATERIAL CONFIRMITY FROM GOVT. APPROVED/SANCTIONED LAB OR ISO CERTIFIED LAB/COMPANY MUST BE PRODUCED DURING PRE-DESPATCH INSPECTION. (2) MATERIALS SHOULD BE SUPPLIED ALONG WITH ORIGINAL TEST CERTIFICATES AND MATERIAL SAFETY DATA SHEET(MSDS). (3) ITEMS HAVE TO BE OFFERED TO BHEL ENGINEER FOR PRE-DESPATCH INSPECTION AT VENDOR'S WORKS. (4) PREFERABLE DELIVERY PERIOD TO BE WITHIN 2 MONTHS FROM THE DATE OF PURCHASE ORDER. (5) SPECIFIC NOTE - UNLOADING THE MATERIALS AT BHEL TRICHY SHALL BE UNDER THE SCOPE OF THE VENDOR.	800	

Vendor Seal & Sign