

**Annexure-C
Technical Specifications**

Item wise Technical Specifications		
Enq. Item SL.No	Item Description and Technical Specifications	Qty (Nos)
10	<p>Teflon flat gasket -240X210X3mm</p> <p>Specification: Flat Teflon gasket Size 240x210x3mm Tolerance +/-1mm Application: Used as sealant across flanges. Should provide leak proof joint when hot water at 80degC is passed through at flow rate 400m3/hr</p>	30
20	<p>Teflon flat gasket -160X120X3mm</p> <p>Specification: Flat Teflon gasket Size 160X120X3mm Tolerance +/-1mm Application: Used as sealant across flanges. Should provide leak proof joint when hot water at 80degC is passed through at flow rate 400m3/hr</p>	30
30	<p>Teflon flat gasket -140X120X3mm</p> <p>Specification: Flat Teflon gasket Size 140X120X3mm Tolerance +/-1mm Application: Used as sealant across flanges. Should provide leak proof joint when hot water at 80degC is passed through at flow rate 400m3/hr</p>	40
40	<p>Teflon flat gasket -130X80X3mm</p> <p>Specification: Flat Teflon gasket Size 130X80X3mm Tolerance +/-1mm Application: Used as sealant across flanges. Should provide leak proof joint when hot water at 80degC is passed through at flow rate 400m3/hr</p>	40
50	<p>Teflon flat gasket -125X60X3mm</p> <p>Specification: Flat Teflon gasket Size 125X60X3mm Tolerance +/-1mm Application: Used as sealant across flanges. Should provide leak proof joint when hot water at 80degC is passed through at flow rate 400m3/hr</p>	50
60	<p>Teflon flat gasket -120X90X3mm</p> <p>Specification: Flat Teflon gasket Size 120X90X3mm Tolerance +/-1mm Application: Used as sealant across flanges. Should provide leak proof joint when hot water at 80degC is passed through at flow rate 400m3/hr</p>	30

70	<p>Teflon flat gasket -110X70X3mm</p> <p>Specification: Flat Teflon gasket Size 110X70X3mm Tolerance +/-1mm Application: Used as sealant across flanges. Should provide leak proof joint when hot water at 80degC is passed through at flow rate 400m3/hr</p>	30
80	<p>Teflon flat gasket -65X33X3mm</p> <p>Specification: Flat Teflon gasket Size 65X33X3mm Tolerance +/-1mm Application: Used as sealant across flanges. Should provide leak proof joint when hot water at 80degC is passed through at flow rate 400m3/hr</p>	40
90	<p>Teflon flat gasket -50X30X3mm</p> <p>Specification: Flat Teflon gasket Size 50X30X3mm Tolerance +/-1mm Application: Used as sealant across flanges. Should provide leak proof joint when hot water at 80degC is passed through at flow rate 400m3/hr</p>	80
100	<p>Teflon flat gasket -37X32X3mm</p> <p>Specification: Flat Teflon gasket Size 37X32X3mm Tolerance +/-1mm Application: Used as sealant across flanges. Should provide leak proof joint when hot water at 80degC is passed through at flow rate 400m3/hr</p>	40
110	<p>Teflon flat gasket -280X215X3mm</p> <p>Specification: Flat Teflon gasket Size 280X215X3mm Tolerance +/-1mm Application: Used as sealant across flanges. Should provide leak proof joint when hot water at 80degC is passed through at flow rate 400m3/hr</p>	80