

**Annexure-C
Technical Specifications**

Item wise Technical Specifications			
Enq. Item SL.No	Item Description and Technical Specifications	Qty (Nos)	Supplier's Confirmation
10	<p>METAL COUPLINGS</p> <p>METAL BELLOWS/DISK COUPLING WITH PILOT BORE. TORQUE: 130 - 150 NM OD OF COUPLING: 80-85 MM LENGTH OF COUPLING: 90-100 MM TYPE: CLAMPING TYPE WITH STRAIGHT HUB PILOT BORE SIZE: VENDOR TO SPECIFY HUB MATERIAL: VENDOR TO SPECIFY BELLOWS MATERIAL: VENDOR TO SPECIFY</p> <p>MODEL EXAMPLE: NES1300W WITH STRAIGHT HUB(TSUBAKI),KB4150(KBK)</p>	4	
20	<p>METAL COUPLINGS</p> <p>METAL BELLOWS/DISK COUPLING WITH PILOT BORE. TORQUE: 180 - 200 NM OD OF COUPLING: 90-95 MM LENGTH OF COUPLING: 95-105 MM TYPE: CLAMPING TYPE WITH STRAIGHT HUB PILOT BORE SIZE: VENDOR TO SPECIFY HUB MATERIAL: VENDOR TO SPECIFY BELLOWS MATERIAL: VENDOR TO SPECIFY</p> <p>MODEL EXAMPLE: NES2000W WITH STRAIGHT HUB(TSUBAKI),KB4200(KBK)</p>	3	
30	<p>HIGH PRECISION LOCKNUT</p> <p>HIGH PRECISION LOCKNUT WITH AXIAL LOCKING SCREWS. SIZE: M40X1.5P OD OF THE LOCKNUT: 60 MM (MAX) WIDTH:25 MM (MAX) HARDNESS: 28 - 32 HRC</p>	10	
<p>COMMON NOTE: CATALOGUE/TECHNICAL DATA SHEET TO BE ENCLOSED ALONG WITH OFFER FOR TECHNICAL EVALUATION. OFFER WITHOUT DATA SHEET IS LIABLE FOR REJECTION.</p>			

Supplier's Signature and Seal