

ANNEXURE-1

SNO	MATCODE	MDESC	QUANTITY	UNIT
1	HW8444140040	1N4004 RECTIFIER DIODE. MAXIMUM REPETITIVE PEAK REVERSE VOLTAGE = 400V, MAXIMUM AVERAGE FORWARD RECTIFIED CURRENT = 1.0 A, PACKAGE: DO-41 (DO-204AL)	50	NO
2	HW8444140058	1N4005 RECTIFIER DIODE. MAXIMUM REPETITIVE PEAK REVERSE VOLTAGE = 600V, MAXIMUM AVERAGE FORWARD RECTIFIED CURRENT = 1.0 A, PACKAGE: DO-41 (DO-204AL)	50	NO
3	HW8444154016	1N5401 DIODE. MAXIMUM REPETITIVE PEAK REVERSE VOLTAGE (VRRM)100V, MAXIMUM AVERAGE FORWARD RECTIFIED CURRENT IF 3.0A. CASE: DO-201AD	50	NO
4	HW8444154040	1N5404 DIODE. MAXIMUM REPETITIVE PEAK REVERSE VOLTAGE (VRRM) 400V, MAXIMUM AVERAGE FORWARD RECTIFIED CURRENT IF 3.0A. CASE: DO-201AD	50	NO
5	HW8444154067	1N5406 DIODE. MAXIMUM REPETITIVE PEAK REVERSE VOLTAGE (VRRM) 600V, MAXIMUM AVERAGE FORWARD RECTIFIED CURRENT IF 3.0A. CASE: DO-201AD	50	NO
6	HW8444154083	1N5408 DIODE. MAXIMUM REPETITIVE PEAK REVERSE VOLTAGE (VRRM) 1000V, MAXIMUM AVERAGE FORWARD RECTIFIED CURRENT IF 3.0A. CASE: DO-201AD	50	NO
7	HW8444154091	DRG: NA REV: -- 10A02 DIODE. MAXIMUM REPETITIVE PEAK REVERSE VOLTAGE (VRRM) 100V, MAXIMUM AVERAGE FORWARD RECTIFIED CURRENT 10A. CASE: R-6	50	NO

8	HW8444154105	DRG: NA REV: -- 10A04 DIODE. MAXIMUM REPETITIVE PEAK REVERSE VOLTAGE (VRRM) 400V, MAXIMUM AVERAGE FORWARD RECTIFIED CURRENT 10A. CASE: R-6	50	NO
9	HW8444154113	DRG: NA REV: -- 10A07 DIODE. MAXIMUM REPETITIVE PEAK REVERSE VOLTAGE (VRRM) 1000V, MAXIMUM AVERAGE FORWARD RECTIFIED CURRENT 10A. CASE: R-6	50	NO
10	HW8444154121	DRG: NA REV: -- 1N4448WS SURFACE MOUNT DIODE. MAXIMUM REPETITIVE PEAK REVERSE VOLTAGE (VRRM) 100V, MAXIMUM AVERAGE FORWARD RECTIFIED CURRENT 150MA OR MORE. CASE: SOD-323	50	NO
11	HW8444154130	DRG: NA REV: -- MCL4148 SURFACE MOUNT DIODE. MAXIMUM REPETITIVE PEAK REVERSE VOLTAGE (VRRM) 100V, MAXIMUM AVERAGE FORWARD RECTIFIED CURRENT 150MA OR MORE. CASE: MICRO MELF	50	NO
12	HW8444154148	DRG: NA REV: -- LL4148 SURFACE MOUNT DIODE. MAXIMUM REPETITIVE PEAK REVERSE VOLTAGE (VRRM) 100V, MAXIMUM AVERAGE FORWARD RECTIFIED CURRENT 150MA OR MORE. CASE: SOD-80/MINI MELF	50	NO
13	HW8444154156	DRG: NA REV: -- BAV19WS SURFACE MOUNT DIODE. MAXIMUM REPETITIVE PEAK REVERSE VOLTAGE (VRRM) 120V, MAXIMUM AVERAGE FORWARD RECTIFIED CURRENT 150MA OR MORE. CASE: SOD-323	50	NO

14	HW8444154164	DRG: NA REV: -- BAV20WS SURFACE MOUNT DIODE. MAXIMUM REPETITIVE PEAK REVERSE VOLTAGE (VRRM) 200V, MAXIMUM AVERAGE FORWARD RECTIFIED CURRENT 150MA OR MORE. CASE: SOD-323	50	NO
15	HW8444154172	DRG: NA REV: -- BAV21WS SURFACE MOUNT DIODE. MAXIMUM REPETITIVE PEAK REVERSE VOLTAGE (VRRM) 250V, MAXIMUM AVERAGE FORWARD RECTIFIED CURRENT 150MA OR MORE. CASE: SOD-323	50	NO
16	HW8444154180	DRG: NA REV: -- BYG20D SURFACE MOUNT DIODE. MAXIMUM REPETITIVE PEAK REVERSE VOLTAGE (VRRM) 200V, MAXIMUM AVERAGE FORWARD RECTIFIED CURRENT 1.5 A OR MORE. CASE: DO-214AC	50	NO
17	HW8444154199	DRG: NA REV: -- BYG20G SURFACE MOUNT DIODE. MAXIMUM REPETITIVE PEAK REVERSE VOLTAGE (VRRM) 400V, MAXIMUM AVERAGE FORWARD RECTIFIED CURRENT 1.5 A OR MORE. CASE: DO-214AC	50	NO
18	HW8444154202	DRG: NA REV: -- BYG20J SURFACE MOUNT DIODE. MAXIMUM REPETITIVE PEAK REVERSE VOLTAGE (VRRM) 600V, MAXIMUM AVERAGE FORWARD RECTIFIED CURRENT 1.5 A OR MORE. CASE: DO-214AC	50	NO
19	HW8444154210	DRG: NA REV: -- BAV99 DUAL SURFACE MOUNT DIODE. MAXIMUM REPETITIVE PEAK REVERSE VOLTAGE (VRRM) 70V OR MORE, MAXIMUM AVERAGE FORWARD RECTIFIED CURRENT 200 MA OR MORE. CASE: SOT-23	50	NO

20	HW8444154229	DRG: NA REV: -- EGF1B DUAL SURFACE MOUNT DIODE. MAXIMUM REPETITIVE PEAK REVERSE VOLTAGE (VRRM) 100V, MAXIMUM AVERAGE FORWARD RECTIFIED CURRENT 1 A. CASE: DO-214AC	50	NO
21	HW8444154237	DRG: NA REV: -- EGF1B DUAL SURFACE MOUNT DIODE. MAXIMUM REPETITIVE PEAK REVERSE VOLTAGE (VRRM) 200V, MAXIMUM AVERAGE FORWARD RECTIFIED CURRENT 1 A. CASE: DO-214AC	50	NO
22	HW8444154245	DRG: NA REV: -- GF1B DUAL SURFACE MOUNT DIODE. MAXIMUM REPETITIVE PEAK REVERSE VOLTAGE (VRRM) 100V, MAXIMUM AVERAGE FORWARD RECTIFIED CURRENT 1 A. CASE: DO-214	50	NO
23	HW8444154253	DRG: NA REV: -- GF1D DUAL SURFACE MOUNT DIODE. MAXIMUM REPETITIVE PEAK REVERSE VOLTAGE (VRRM) 200V, MAXIMUM AVERAGE FORWARD RECTIFIED CURRENT 1 A. CASE: DO-214	50	NO
24	HW8444154261	DRG: NA REV: -- GF1G DUAL SURFACE MOUNT DIODE. MAXIMUM REPETITIVE PEAK REVERSE VOLTAGE (VRRM) 400V, MAXIMUM AVERAGE FORWARD RECTIFIED CURRENT 1 A. CASE: DO-214	50	NO
25	HW8444154270	DRG: NA REV: -- GF1J DUAL SURFACE MOUNT DIODE. MAXIMUM REPETITIVE PEAK REVERSE VOLTAGE (VRRM) 600V, MAXIMUM AVERAGE FORWARD RECTIFIED CURRENT 1 A. CASE: DO-214	50	NO

26	HW8444154288	DRG: NA REV: -- GF1M DUAL SURFACE MOUNT DIODE. MAXIMUM REPETITIVE PEAK REVERSE VOLTAGE (VRRM) 1000V, MAXIMUM AVERAGE FORWARD RECTIFIED CURRENT 1 A. CASE: DO-214	50	NO
----	--------------	--	----	----