

ANNEXURE- HRC FUSE/2022

| Sl. No. | Material Code | Material description | QTY | Vendor to confirm | Deviation if any | Make & Model no./Product Id/catalogue No. |
|---------|---------------|---|-----|-------------------|------------------|---|
| 1 | HW8431310090 | BOLTED TYPE HRC FUSE LINK RATING:20A,415V AC,OFFSET TAG, 2 HOLE FIXING SIZE:A1 BREAKING CAPACITY:80KA, UTILISATION CATEGORY:GG, CONFORMING TO IS:13703/IEC: 60269 | 40 | | | |
| 2 | HW8431310103 | BOLTED TYPE HRC FUSE LINK RATING:32A,415V AC,OFFSET TAG, 2 HOLE FIXING SIZE:A2 BREAKING CAPACITY:80KA, UTILISATION CATEGORY:GG, CONFORMING TO IS:13703/IEC: 60269 | 102 | | | |
| 3 | HW8431300779 | BOLTED TYPE HRC FUSE LINK RATING:50A,415V AC,OFFSET TAG SIZE:A3 BREAKING CAPACITY: 80KA,UTILISATION CATEGORY: GG, CONFORMING TO IS:13703/IEC:60269 | 82 | | | |
| 4 | HW8431310057 | BOLTED TYPE HRC FUSE LINK RATING 63A,415V AC, OFFSET TAG2 HOLE FIXING SIZE:A3, BREAKING CAPACITY:80KA, UTILISATION CATEGORY:GG, CONFORM TO IS NO:13703/IEC:60269 | 181 | | | |
| 5 | HW8431301090 | BOLTED TYPE HRC FUSE LINK RATING 80A,415V AC, CENTER TAG 2 HOLE FIXING SIZE:B1, BREAKING CAPACITY:80KA, UTILISATION CATEGORY:GG, CONFORM TO IS NO: 13703/IEC:60269 | 38 | | | |
| 6 | HW8431310065 | BOLTED TYPE HRC FUSE LINK RATING 100A,415V AC,OFFSET TAG2 HOLE FIXING SIZE:A4, BREAKINGCAPACITY=80KA, UTILISATION CATEGORY:GG,CONFORM TO IS NO: 13703/IEC:60269 | 65 | | | |
| 7 | HW8431301112 | BOLTED TYPE CERAMIC HRC FUSE LINK RATING:125A,415V AC, CENTRAL TAG,2 HOLE FIXING,SIZE:B1,BREAKING CAPACITY:80KA, UTILISATION CATEGORY:GG CONFORMING TO IS:13703/IEC: 60269 | 44 | | | |
| 8 | HW8431301074 | BOLTED TYPE CERAMIC HRC FUSE LINK RATING:160A,415V AC, OFFSET TAG,2 HOLE FIXING,SIZE :A4,BREAKING CAPACITY:80KA, UTILISATION CATEGORY:GG, CONFORMING TO IS:13703/IEC: 60269 | 40 | | | |

| | | | | | | |
|----|--------------|--|----|--|--|--|
| 9 | HW8431323353 | BOLTED TYPE CERAMIC HRC FUSE LINK RATING: 160A,415V AC, CENTRAL TAG ,2 HOLE FIXING ,SIZE :B2, BREAKING CAPACITY:80KA, UTILISATION CATEGORY:GG, CONFORMING TO IS:13703/IEC: 60269 | 17 | | | |
| 10 | HW8431322373 | BOLTED TYPE HRC FUSE LINK RATING:200A,415VAC,CENTRAL TAG2 HOLE FIXING,SIZE:B2,BREAKINGCAPACITY:80KA, UTILISATION CATEGORY:GG,CONFORM TO IS NO: 13703/IEC:60269 | 45 | | | |
| 11 | HW8431322390 | BOLTED TYPE HRC FUSE LINK RATING:315A,415VAC,CENTRAL TAG2 HOLE FIXING,SIZE:B3,BREAKINGCAPACITY:80KA, UTILISATION CATEGORY:GG,CONFORM TO IS NO: 13703/IEC:60269 | 42 | | | |
| 12 | HW8431323361 | BOLTED TYPE CERAMIC HRC FUSE LINK, RATING:400A,415VAC, CENTER TAG,2 HOLE FIXING, SIZE:B4,BREAKING CAPACITY: 80KA, UTILISATION CATEGORY: GG, CONFORMING TO IS:13703/IEC: | 8 | | | |
| 13 | HW8431302437 | BLADE CONTACT DIN TYPE HRC FUSE LINK RATING 63A, 415V AC,SIZE 000,BREAKING CAPACITY: 80KA,UTILISATION CATEGORY=GG, FUSE BLOWN INDICATION IS: 13703/IEC:60269 | 76 | | | |
| 14 | HW8431302470 | BLADE CONTACT DIN TYPE HRC FUSE LINK RATING 80A, 415V AC SIZE:0,BREAKING CAPACITY: 80KA,UTILISATION CATEGORY=GG, FUSE BLOWN INDICATION IS: 13703/IEC:60269 | 70 | | | |
| 15 | HW8431300132 | BLADE CONTACT DIN TYPE CERAMICHRC FUSE LINK RATING:100A,415VAC,SIZE:000,BREAKING CAPACITY 80KA AC,UTILISATION CATEGORY: GG,FUSE BLOWN INDICATION, CONFORMING TO IS:13703/IEC: 60269 | 68 | | | |
| 16 | HW8431302496 | BLADE CONTACT DIN TYPE HRC FUSE LINK RATING 125A,415V AC,SIZE:0,BREAKING CAPACITY: 80KA,UTILISATION CATEGORY=GG, FUSE BLOWN INDICATION. IS:13703/IEC:60269 | 84 | | | |
| 17 | HW8431323370 | BLADE CONTACT DIN TYPE CERAMIC HRC FUSE LINK 125A, 415V AC,SIZE-000, BREAKING CAPACITY: 80KA,UTILISATION CATEGORY=GG, FUSE BLOWN INDICATION. ,CONFORMING TO IS:13703/IEC: 60269 | 56 | | | |

| | | | | | | |
|----|--------------|--|----|--|--|--|
| 18 | HW8431302534 | BLADE CONTACT DIN TYPE HRC FUSE LINK RATING 160A,415V AC SIZE:1,BREAKING CAPACITY:80KA,UTILISATION CATEGORY=GG,FUSE BLOWN INDICATION.IS:13703/IEC:60269 | 48 | | | |
| 19 | HW8431300272 | DIN TYPE HRC FUSE LINK(BLADE CONTACT)160A,415V AC,SIZE:00, BREAKING CAPACITY 80KA AC,IS: 13703/IEC:60269 | 57 | | | |
| 20 | HW8431300329 | DIN TYPE HRC FUSE LINK(BLADE CONTACT)200A,415V AC,SIZE:0, BREAKING CAPACITY 80KA AC,IS: 13703/IEC60269 | 38 | | | |
| 21 | HW8431302542 | BLADE CONTACT DIN TYPE HRC FUSE LINK RATING 200A,415V AC SIZE:1,BREAKING CAPACITY 80 KAUTILISATION CATEGORY=GG,FUSE BLOWN INDICATION.IS:13703/IEC:60269 | 38 | | | |
| 22 | HW8431300418 | DIN TYPE HRC/HBC FUSE LINK (BLADE CONTACT)250A,415V,SIZE:1,BREAKING CAPACITY 80KA AC,IS:13703/IEC:60269 | 57 | | | |
| 23 | HW8431300426 | DIN TYPE HRC FUSE LINK(BLADE CONTACT)315A,415V AC,SIZE:1, BREAKING CAPACITY 80 KA AC,IS:13703/IEC:60269 | 59 | | | |
| 24 | HW8431302801 | BLADE CONTACT DIN TYPE HRC FUSE LINK RATING 400A,415V AC,SIZE:2,BREAKING CAPACITY:80KA UTILISATION CATEGORY:GG,FUSE BLOWN INDICATION,CONFORM TO IS:13703/IEC:60269. | 59 | | | |
| 25 | HW8431300515 | BLADE CONTACT DIN TYPE CERAMIC HRC FUSE,RATING:500A,415V AC, SIZE:3,BREAKING CAPACITY:80KA,UTILISATION CATEGORY:GG,FUSE BLOWN INDICATION,CONFORMING TO IS:13703/IEC: 60269 | 12 | | | |
| 26 | HW8431301902 | CYLINDRICAL CAP TYPE HRC FUSE 20A,415 VAC,SIZE: DIA=14,L=51 MM, BREAKING CAPACITY:80KA, CONFORM TO IS:13703/IEC:60269 | 27 | | | |
| 27 | HW8431301929 | CYLINDRICAL CAP TYPE HRC FUSE 32A,415VAC,SIZE: DIA=14,L=51 MM, BREAKING CAPACITY:80KA CONFORM TO IS:13703/IEC:60269 | 31 | | | |
| 28 | HW8431301953 | CYLINDRICAL CAP TYPE HRC FUSE 63A,415VAC,SIZE:DIA=14,L=51MM BREAKING CAPACITY:80KA,CONFORM TO IS:13703/IEC:60269 | 66 | | | |

| | | | | | | |
|----|--------------|--|-----|--|--|--|
| 29 | HW8431300612 | COMPACT FUSE LINKS,CERAMIC HRCFUSE,RATING:4A,415VAC, STAGGERED TAG,SIZE:F1,BREAKINGCAPACITY:80KA,UTILISATION CATEGORY:GG,CONFORMING TO IS: 13703/IEC:60269 | 82 | | | |
| 30 | HW8431300620 | COMPACT FUSE LINKS,CERAMIC HRCFUSE,RATING:6A,415VAC, STAGGERED TAG,SIZE:F1,BREAKINGCAPACITY:80KA,UTILISATION CATEGORY:GG,CONFORMING TO IS: IS:13703/IEC:60269 | 68 | | | |
| 31 | HW8431300639 | COMPACT FUSE LINKS,CERAMIC HRCFUSE,RATING:10A,415VAC, STAGGERED TAG,SIZE:F1, BREAKINGCAPACITY:80KA,UTILISATION CATEGORY:GG,CONFORMING TO IS: 13703/IEC:60269 | 87 | | | |
| 32 | HW8431300647 | COMPACT FUSE LINKS, CERAMIC HRCFUSE,RATING:16A, 415 VAC, STAGGERED TAG,SIZE:F1, BREAKINGCAPACITY:80KA, UTILISATION CATEGORY:GG,CONFORMING TO IS: 13703/IEC:60269 | 110 | | | |
| 33 | HW8431300655 | COMPACT FUSE LINKS,CERAMIC HRCFUSE,RATING:20A,415 VAC,STAGGERED TAG,SIZE:F1, BREAKINGCAPACITY:80KA, UTILISATION CATEGORY:GG,CONFORMING TO IS: 13703/IEC:60269 | 38 | | | |
| 34 | HW8431300752 | COMPACT FUSE LINKS,CERAMIC HRCFUSE,RATING:32A,415 VAC, STAGGERED TAG,SIZE:F1,BREAKINGCAPACITY:80KA, UTILISATION CATEGORY:GG,CONFORMING TO IS: 13703/IEC:60269 | 50 | | | |
| 35 | HW8431322543 | FUSE HOLDERS & FUSE BASES FOR 63AMP.,415V AC BOLTED TYPE,OFFSET TAG2,SIZE= A3 | 49 | | | |
| 36 | HW8431300434 | BLADE CONTACT DIN TYPE CERAMICHRC FUSE,RATING:200A,415V AC SIZE:2,BREAKING CAPACITY:80KA,UTILISATION CATEGORY:GG,FUSE BLOWN INDICATION,CONFORMING TOIS:13703/IEC:60269 | 18 | | | |

| S.No. | Special Instructions | Remarks | Accepted | Deviation |
|-------|---|------------------------------|----------|-----------|
| | | | (Yes/No) | |
| 1 | Technical data sheet and catalogue for each quoted item along with the offer. | Bidder to comply and provide | | |
| 2 | the date of receipt of material at BHEL Store. | Bidder to comply | | |

M. S. / 8/7/22