

Annexure B

Pre-Qualification Criteria, Vendor Confirmation to Technical Specifications & Vendor's Details

A. Pre-Qualification Criteria		
SL.No	Pre-Qualification Criteria	Vendor's Confirmation /Acceptance
Only those vendors who satisfy the following conditions will get qualified to participate in the tender		
1.	The manufacturer or their authorized dealers should only submit the offer. The vendor should submit a copy of the valid dealership certificate along with technical offer. The offers without dealership certificate will not be considered for evaluation	
2.	The manufacturer or their authorized dealers should provide the pneumatic tool catalogues of above product with model No., full specifications, dimensions, capacity, weight, free speed rpm, body material, noise level, vibration etc. Along with the offer otherwise offer will not be considered for technical evaluation	
3.	The manufacturer/supplier should have minimum past 2 years of experience in supplying these items from the date of enquiry/tender. To evidence that previous PO copy for supplying similar products (pneumatic grinders) to BHEL and/or any-other organization should be submitted along with offer. Otherwise offer will not be considered for evaluation.	
4.	Company profile details has to be provided along with offer.	
B. Technical Specifications		
SL. No	Description and Technical Specification of the item	Vendor's Confirmation/Acceptance
1.	<p>PNEUMATIC ANGLE GRINDER - 7 INCH</p> <p>PNEUMATIC ANGLE GRINDER WITH WHEEL GUARD ASSEMBLY, HOSE ADAPTOR AND WHEEL MOUNT PIN SPANNER.</p> <p>FREE SPEED - 6000 RPM. WHEEL CAPACITY - 7", APPROX WEIGHT - 6 KG MAX. OVERALL LENGHT - 350 MM MAX. AIR INLET - 3/8" OR 1/2 "" BSP. WITH NIPPLE SPINDLE THREAD - 5/8"" -11 TPI BSW or M16 AIR PRESSURE - 4 to 6 Kg/sq.cm (Max).</p>	
2.	<p>PNEUMATIC H.D ST.TYPE STEEL CLAD GRINDER</p> <p>"PNEUMATIC HEAVY-DUTY STRAIGHT TYPE STEEL CLAD GRINDER" (ROLLER) WITH WHEEL SAFETY GUARD AND HOSE ADAPTER WITH NIPPLE AND WHEEL MOUNT PIN SPANNER.</p> <p>FREE SPEED - 6000 RPM WHEEL SIZE - 6" LENGTH - 580 MM MAX. WEIGHT - 5KG. MAX. AIR INLET - 3/8 " BSP. SPINDLE - 5/8" BSW or UNF. AIR PRESSURE - 4 to 6 Kg/sq.cm (Max).</p>	

Vendor Signature & Seal

3.	<p>PNEUMATIC DIE GRINDER ST. TYPE(PENCIL)</p> <p>"PNEUMATIC DIE GRINDER (PENCIL) STRAIGHT TYPE WITH HOSE ADAPTOR AND NUT ASSEMBLY AND WHEEL GUARD AND WHEEL MOUNT PIN SPANNER.</p> <p>FREE SPEED RPM - 14500 TO 18000 SPINDLE THREAD - 3/8" UNF or BSW WITH 6MM COLLET MOUNTED ON 3/8" SPINDLE APPROX WEIGHT - 2.5 KG. MAX. LENGTH - 250 TO 320 MM. BODY - STEEL AIR INLET - 1/4" BSP. WITH NIPPLE AIR PRESSURE - 4 to 6 Kg/sq.cm" (Max)</p>	
4.	<p>PNEUMATIC DIE GRINDER STRAIGHT - (BABY)</p> <p>PNEUMATIC DIE GRINDER (BABY) STRAIGHT TYPE WITH 6 MM COLLET NUT, HOSE ASSEMBLY AND WHEEL MOUNT PIN SPANNER.</p> <p>FREE SPEED RPM - 22000 - 35000 THROTTLE - LEVER TYPE. WEIGHT - 0.5KG TO 1KG. OVERALL LENGTH - 125 TO 175 MM. BODY - STEEL. AIR INLET - 1/4" BSP, WITH NIPPLE AIR PRESSURE - 4 to 6 Kg/sq.cm.(Max)</p>	
5.	<p>PNEUMATIC DIE GRINDER ST.TYPE (LONG)</p> <p>PNEUMATIC DIE GRINDER (LONG) STRAIGHT TYPE WITH HOSE ADAPTOR AND NUT ASSEMBLY AND WHEEL GUARD AND WHEEL MOUNT PIN SPANNER.</p> <p>FREE SPEED RPM - 14500 TO 15000 SPINDLE THREAD - 3/8" UNF or BSW WITH 6MM COLLET MOUNTED ON 3/8" SPINDLE EXTENDED LENGTH TYPE OF 450 MM LENGTH. APPROX WEIGHT - 2.5 KG. MAX. AIR INLET - 1/4" BSP. WITH NIPPLE AIR PRESSURE - 4 to 6 Kg/sq.cm.</p>	
6.	<p>PNEUMATIC PISTOL TYPE DRILL - 10 MM</p> <p>"PNEUMATIC PISTOL TYPE DRILL WITH CHUCK, KEY AND HOSE ADAPTER WITH NIPPLE</p> <p>DRILL CAPACITY - 10MM RPM - 2000 TO 2900. AIR INLET - 1/4" BSP. AIR PRESSURE - 4 to 6 Kg/sq.cm (Max).</p>	
C. GENERAL TERMS AND CONDITIONS		
1.	The vendor may visit the site for any technical assessment and clarification before quoting.	
2.	The supplier should offer for inspection at supplier's work before despatch and arrange for load test at their works.	
3.	The supply products have to confirm/comply with industrial safety norms / standards.	

Vendor Signature & Seal

4.	BHEL reserves the right to visit the vendor's works for verifying the manufacturing facilities and any other credential furnished by the vendor. In case the information furnished with the offers found to be false /incorrect at the later stage, the offer shall be rejected.	
5.	Vendor should offer minimum 12 months guarantee/warrantee for its products. Vendor to confirm.	
6.	Equipment assembly drawing and spares/parts drawing shall be provided along with supply.	
7.	O&M manuals in hard copy's / soft copy's shall be submitted by vendor	

D. Supplier/Vendor details

	Supplier Name & Address	
	Contact Person Name, email id and Mobile Number	
	HSN code for the quoted items	
	GST% included in the quoted price	

Vendor Signature & Seal