

Annexure B

Pre-Qualification Criteria, Vendor Confirmation to Technical Specifications & Vendor's Details

A. Pre-Qualification Criteria		
SL.No	Pre-Qualification Criteria	Vendor's Confirmation /Acceptance
	The BIDDER has to compulsorily meet all the following requirements and supporting documents should be furnished without which the offer will not be considered for technical evaluation.	
1.	Vendor should have supplied ELECTRICAL items to industries. Vendor shall necessarily furnish purchase order copies of customers to whom similar items have been supplied within five years of offer submitted date.	
B. Technical Specifications		
SL. No	Description and Technical Specification of the item	Vendor's Confirmation/Acceptance
1.	SWITCH FUSE 32AMPS 415VOLT TPN HRC TYPE Sheet steel enclosed fully shrouded TPN switch fuse unit rated for 32amps and 32 amps HBC Fuse provided the unit, with side handle operation, quick make and break mechanism. All current carrying parts are hard silver plated /nickel plated contacts and interlock arrangements, with ON/OFF indication, two external earthing terminals and cable entry holes at top and bottom to be provided, kit-kat in porcelain powder coated grey paint with seven tank system. Rated operating voltage 415 at 50 HZ, AC supply. As per IS/IEC 60947: Part 3: 2012 (Reaffirmed 2018).	
2.	SWITCH FUSE 100AMPS 415V TPN HRC TYPE Sheet steel enclosed fully shrouded TPN switch fuse unit rated for 100Amps, with side handle operation, quick make and break mechanism. All current carrying parts are hard silver plated/nickel plated contacts and interlock arrangements, with ON/OFF indication, two external earthing terminals and with 100Amps HBC fuse links. Cable entry holes at top and bottom to be provided, kitkat in porcelain, powder coated grey paint with seven tank system. Rated operating voltage 415 at 50 HZ., AC supply. As per IS/IEC 60947: Part 3: 2012 (Reaffirmed 2018).	
3.	TPN SWIT.FUSE 125A 415V Sheet Steel enclosure TPN fuse switch unit, rated for 125 Amps at 415 / 500 Volt, 50Hz, AC Supply. Quick make and break mechanism and all current carrying parts are hard silver plated //nickel plated and inter locks arrangements, with ON / OFF indication, two external earthing terminal and with HBC fuse links, confirming to IS/IEC 60947: Part 3: 2012 (Reaffirmed 2018)	
4.	ISOLATOR 32 AMPS 415 VOLT TPN 3 PHASE Sheet steel enclosed fully shrouded TPN Isolator rated for 32 amps with side handle operation, quick make and break mechanism. All current carrying parts are hard silver plated contacts/Nickel plated contacts and inter locks arrangements, with ON/OFF indication, two external earthing terminals. Cable entry holes at top and bottom to be provided, kit-kat in porcelain, powder coated grey paint with seven tank system. Rated operating voltage 415/500 at 50 HZ. AC supply. As per IS/IEC 60947: Part 1: 2007 (Reaffirmed 2017).	

Vendor Signature & Seal

5.	<p>ISOLATOR 63 AMPS 415 VOLT TPN 3 PHASE Sheet steel enclosed fully shrouded TPN Isolator rated for 63 amps with side handle operation, quick make and break mechanism. All current carrying parts are hard silver plated contacts/Nickel plated contacts and inter locks arrangements, with ON/OFF indication, two external earthing terminals. Cable entry holes at top and bottom to be provided, kit-kat in porcelain, powder coated grey paint with seven tank system. Rated operating voltage 415/500 at 50 HZ., AC supply. As per IS/IEC 60947: Part 1: 2007 (Reaffirmed 2017).</p>	
6.	<p>ISOLATOR 100 AMPS 415 VOLT TPN 3 PHASE Sheet steel enclosed fully shrouded TPN Isolator rated for 100 amps with side handle operation, quick make and break mechanism. All current carrying parts are hard silver plated contacts/Nickel plated contacts and inter locks arrangements, with ON/OFF indication, two external earthing terminals. Cable entry holes at top and bottom to be provided, kit-kat in porcelain, powder coated grey paint with seven tank system. Rated operating voltage 415/500 at 50 HZ., AC supply. As per IS/IEC 60947: Part 1: 2007 (Reaffirmed 2017).</p>	

C. Supplier/Vendor details		
	Supplier Name & Address	
	Contact Person Name, email id and Mobile Number	
	HSN code for the quoted items	
	GST% included in the quoted price	