

**BHARAT HEAVY ELECTRICALS LIMITED IVP
GOINDWAL SAHIB
MM DEPARTMENT**

Date: 26.02.2018

Corrigendum

Reference: **Tender Enquiry no. 1718-119 dated 07.02.2018 for supply and commissioning of P6 LED DISPLAY BOARD**

1. Due date of submission of quotations of above referred tender enquiry has been extended upto 15.03.2018 at 1500 Hrs. Tender will be opened on 15.03.2018 at 1530 Hrs.
2. Technical specification sheet Annexure-I Page 4 of tender document is withdrawn. Revised technical Specification Sheet Annexure-IA is attached. Total sr. nos. on technical specification sheet will be 24 instead of 33. From Now onwards, technical specification sheet Annexure-IA will be considered. Technical Specification sheet Annexure- IA is attached.
3. P6 LED DIPLAY BOARD Title of tender document is replaced with P6 OUTDOOR LED DISPLAY BOARD. From Now onwards wherever word "P6" comes in tender documents it shall be read as "P6 Outdoor".

ANNEXURE - IA

TECHNICAL SPECIFICATION SHEET

S.No.	Item	Specification
1	Size	6 feet X 4 feet (24 Sq. feet)
2	Type	P6 Outdoor
3	Pixel Pitch	6mm
4	Chip of LED	SMD Lamp
5	LED per pixel	(SMD 3 in 1)
6	Cabinet Material	Aluminum Diecasting
7	Best View Distancing	6-100 m
8	Vertical Viewing Angle	110° (Standard LEDs Viewing Angle)
9	Horizontal Viewing Angle	140° (Standard LEDs Viewing Angle)
10	Brightness	$\geq 5000 \text{cd/m}^2$
11	Brightness Adjustment	Manual, Auto
12	Operating Temperature	$-30^{\circ}\text{C} \sim +60^{\circ}\text{C}$ 10%~95%RH
13	LEDs Lifetime	>100,000 Hours(over 11 years lifetime)
14	Input Voltage	AC110V/220V/380V $\pm 10\%$
15	Input Power Frequency	50/60Hz
16	Refresh Rate	1800 - 2400 Hz
17	Frame Rate	> 60 frames/sec
18	Data Transfer Method	RJ45, USB
19	Humidity	0--90%
20	Water proof	>IP65
21	Control Method	Synchronized with computer monitor
22	Color Temperature	6500K ± 500
23	Color	Full Color
24	Warranty	1 Year