

# **Bharat Heavy Electricals Limited**

(A Govt. of India Undertaking)
Transmission Business Group
Materials Management, 5th Floor, Plot No.25,
Sector-16A, Noida, Uttar Pradesh, PIN No: 201301
Phone: 0120-6748541, Email: gaurav.agarwal@bhel.in

### **CORRIGENDUM - 01 TO NIT NO-72528**

Dated 31.03.2023

Subject: Corrigendum-01 to Tender enquiry for Supply & Services of 400 kV GIS FOR NTPC Talcher PROJECT.

Project : NTPC Talcher Project

Equipment / Item : SUPPLY & SERVICES OF 400kV GIS. Enquiry No/Date : Enquiry No\_61G2300308 Dated 10-03-2023

BHEL NIT NO : 72528

Original Tender due date : 31.03.2023

This Corrigendum is issued by BHEL-TBG against above mentioned NIT/ enquiry for:

- 1) Issuance of technical clarifications to pre-bid technical queries (enclosed).
- 2) extension of due date of tender submission/opening to 14-04-2023.

All other terms and conditions for this tender enquiry shall remain unchanged.

Bidder to ensure submission of offer on or before due.

Note: Tender ID in CPP Portal is 2023\_BHEL\_23119\_1.

Thanking you

Gaurav Agarwal BHEL TBG, NOIDA

# CLARIFICATIONS TO TECHNICAL PRE-BID QUERIES Annexure-I

20	10 9	0			O1		ω	N		U
1	Section-1 (Annexure-A, C1 to C5 & D1 to D4)  Section-1 (Annexure-A,	A15 & A16)	-	Section-1 (1 11, Pg 18)	Section-1 (1.8. Pg. 15), Section-2 (1.06.01, Pg. 4 of 40)	13. Pg. 7	Section-1:	12 Pg. 5	11, Pg. 3	
	Mandatory maintenance & monitoring equipment	Mandatory maintenance & monitoring equipment		Section-1 (1 11, Pg. 18) Training at manufacturers works and at Site	c. In case the Bidder has conducted such specified type test(s) according to the relevant standard and/ or specification not earlier than Ten (10) years prior to 06-June-years are acceptable. Please confirm. 2022, he may submit the type test reports to the Customer for waiver of conductance of such type test(s).	b. Site Installation, Testing and commissioning. HV test kit shall be brought at site multiple times as per site requirements, for reasons not attributable to BHEL/NTPC. GIS bays may be commissioned at different point of time depending on the site conditions and as per L2 schedule for the project, and hence deployment of the resources at multiple times at site by bidder in line with actual requirement is envisaged and payment for the same shall be made to bidder, for the reasons not attributable to bidder.	In addition to this, packing of GIS & its accessories shall be suitable for long term storage without any deterioration in quality and performance (min 2 years).	B) Any change in bay pitch (distance between bays): In a case where shifting of GIS bays shall be called by BHEL (during contract stage) due to layout requirement/cost optimization/ revision/ change in civil architectural requirement or due to expansion joint requirement in the GIS building. Bidder to incorporate the same with full compliance of technical requirement.	The 400 KV GIS shall have three single phase constructions, one and half breaker arrangement (I-Type) having the following bays:	
SF6 gas analyzer (item no. C3) can be used to measure dew point of SF6 gas. Hence no need to have dew point meter separately. Please clarify.	We request you to confirm make & model of each of these items listed in Bid Price Schedule	As the quantity of SF6 gas & structure material would vary from one GIS design Bidder to quote as per Tender BOQ. to the other, we request you to amend the quantity! unit of such items as 1 Lot & let the manufacturer estimate the same & quote accordingly.	Request for CAD layout or clear pdf layouts as given layout drawings are not legible.	To & Fro, local transport, Boarding and lodging charges for trainees shall be excluded from GIS supplier's scope of supply. It shall remain in BHEL's scope. Request to confirm.	As per latest CEA guidelines (enclosed), type test reports not older than 15 years are acceptable. Please confirm.	GIS bays shall be installed in one shot and testing and commissioning of the same shall be done after installation. Charging of lines, trafos can be at different point of time once GIS bays are on-line.  Request to clarify the "multiple times" as we have only two GT bays in this project.	Packing of GIS & its accessories shall be suitable for 6 months storage subject. Bidder to follow TS to Buyer following Seller's storage instructions.	Request for CAD layout drawing with column and beams marked to make precise offer without any assumptions.	In GIS, there is no difference in layout arrangement for 1.5 CB scheme wheth it is i-type or D-type. Please confirm.	Bidder's Query
Bdder to quote as per Tender BOQ.	Bidder to offer equipments meeting the technical requirements mentioned in the TS, Also, the offered equipments shall be suitable for maintenance/ monitoring of the supplied GIS system.	n Bidder to quote as per Tender BOQ.	Enclosed	Bidder to follow TS	In line with TS, Type Test Report validity period shall be as per latest CEA guidelines.	Bidder to follow TS (Refer Price Schedule Sl. No G1 to G6)	et Bidder to follow TS	Enclosed	layout arrangement for 1.5 CB scheme whether Noted, Bidder to offer as per OEM Type Tested	BHEL Reply

1 of 7

-	19 G			17 S	1 to		6		4	1	ώ ω	12	=======================================	
	General	Section-2 (6.06.00, Pg. 28 of 40)	23 of 40)	(5 02 02, Pg.	Section-2 (3 03 02, Pg. 17 of 40)		Section-2 (2.21, Pg. 13 of 40)		Section-2 (2.21, Pg 13 of 40)	of 40)	7 of 40) Section-2 (2.15 Pg. 13	Section-2 (2.01.01, Pg.	SLD	Clause No
	SLD & layout	Current for pressure relief test – 63kArms	the secondary circuits, which are connected to the local control cubicle				(h) Calibration/checking of SF6 gas pressure / density switches.	203 high voltage tests at site with lightning impulse and switching impulse voltages are reports shall be submitted.	Commissioning Tests:	ine leads to the tank heaters shall be enclosed in a conduit	dismantling  The leads to the l	to commercial settlement.	Notes: CSD for the tie bay & additional GIS CT cores	pescription as per Bid Document
drawings. From the given SLD and BOQ, there is no PIR for any Circui breaker. Please confirm.		Not applicable to GIS Surge arresters as per IFC	Terminal box shall be provided for CTs.	of GIS, no relays shall be provided.	Trip circuit supervision relay shall be not of relay population	switches can be calibrated at factory	Checking of Density suitch functionity	IEC Lightning and switching impulse tests are type tests for which type test reports shall be submitted.	There are no tank heaters provided.  We perform only Power from the control of th	Thermostats shall be provided only in LCC operating mechanism	We understand that no extension provision is to be given as there is a indication of future bays in SLD or in layout drawings. Please confirm	Annexure-3 of Section-2.	Quantity of CSD shall be as per BOQ and CTs. CT processhall be asset	Bidder's Query
<ul> <li>i) Autocad drawing enclosed.</li> <li>ii) All the CBs are without PIR, however bidder to quote unit rate for the CB with PIR as per Tender BOQ.</li> </ul>	Requirement of pressure relief test shall be as per latest IEC guidelines.		Noted	I'np circuit supervision relays are not to be provided in GIS LCC.		Noted.		Noted, Bidder to follow TS.	Noted Bidder to offer as per OEM Type Tested design.		Bidder to follow TS, Future Bays may be added in future by M/s NTPC.	Noted any change in qty of CSD & no of CT cores shall be adjusted based on unit rates quoted for the respective items. However, CT secondary parameters shall be as per Annexure-3 of Section-2	Direct Kepiy	Buri Dosk

A Mindhear

SOC   Set gas quarter, 20 M	H 2	Clause No BOQ 114(ITEM NO 14)
2. BOQ 1.15(ITEM NO 15) Support Structure for GIS equipment - 55MT support structure for GIS equipment. 1.16(ITEM NO 16) Support Structure for GIS equipment - 55MT support structure for GIS equipment. 1.16(ITEM NO 16) Support Structure for GIS equipment - 55MT support structure for GIS equipment. 1.17(ITEM NO 17)  Support Structure for GIS equipment - 55MT support structure for GIS equipment. 1.17(ITEM NO 17)  Support Structure for GIS equipment - 55MT support structure for GIS equipment. 1.17(ITEM NO 17)  Support Structure for GIS equipment - 55MT support structure for GIS equipment. 1.17(ITEM NO 17)  Support Structure for GIS equipment - 55MT support structure for GIS equipment. 1.17(ITEM NO 17)  Support Structure for GIS equipment - 55MT support structure for GIS equipment. 1.17(ITEM NO 17)  Support Structure for GIS equipment - 55MT support structure for GIS equipment. 1.17(ITEM NO 17)  Support Structure for GIS equipment - 55MT support structure for GIS equipment. 1.17(ITEM NO 17)  Support Structure for GIS equipment - 55MT support structure for GIS equipment. 1.17(ITEM NO 17)  Support Structure for GIS equipment - 55MT support structure for GIS equipment. 1.17(ITEM NO 17)  Support Structure for GIS equipment - 55MT support structure for GIS equipment. 1.17(ITEM NO 17)  Support Support Structure for GIS equipment - 55MT support structure for GIS equipment. 1.17(ITEM NO 17)  Support Support Structure for GIS equipment - 55MT support structure for GIS equipment. 1.17(ITEM NO 17)  Support Su		
3 BOQ 1.16(ITEM NO 16) Support Structure for GIS equipment -65MT support structure for GIS equipment.  BOQ 1.17(ITEM NO 17) Earthing Material for GIS including High Frequency Earthing.  BOQ 2.05(ITEM NO 22) Spare gas of 20% SF6 gas in 4 MT 2.05(ITEM NO 22)  Fraining in Site and Factory E8 & E9 Page No. 36 Training in Site and Factory F0 A 3.09(ITEM NO 25)  Portable PDM system & Online PDM system.  Portable PDM system & Online PDM system.	2	1 15(ITEM NO 15)
3 BOQ 1.16(ITEM NO 16) Support Structure for GIS equipment. 65MT support structure for GIS equipment.  BOQ 1.17(ITEM NO 17)  Earthing Material for GIS including High Frequency Earthing.  BOQ 2.05(ITEM NO 22) Spare gas of 20% SF6 gas in 4 MT 2.05(ITEM NO 22)  Spare gas of 20% SF6 gas in 4 MT 2.12(ITEM NO 29)  Vindoscope/ Observinf Window for CB  ITraining in Site and Factory  RE & E9 Page No. 36  Fortable PDM system & Online PDM system.  BOQ 307 & 3.09(ITEM NO 99 & 61)  Portable PDM system & Online PDM system.		
Support Structure for GIS equipment55MT support structure for GIS equipment.  BOQ 1.17(ITEM NO 17) Earthing Material for GIS moluding High Frequency Earthing.  Spare gas of 20% SF6 gas in 4 MT 2.05(ITEM NO 22) Spare gas of 20% SF6 gas in 4 MT 2.12(ITEM NO 22) Windoscope/ Observinf Window for CB 2.12(ITEM NO 29) Windoscope/ Observinf Window for CB  Windoscope/ Observinf Window for CB  Training in Site and Factory  BOQ 3.07 & 3.09(ITEM NO 9.8 & E9 Page No: 36  Portable PDM system & Online PDM system.	T	
BOQ IT NO_72528 E8 & E9 Page No. 36 BOQ 307 & 3.09(ITEM NO 59 & 61)  Earthing Material for GIS including High Frequency Earthing.  Earthing Material for GIS including High Frequency Earthing.  Fortable PDM system & Online PDM system.	ω	1.16(ITEM NO 16)
BOQ Spare gas of 20% SF6 gas in 4 MT  Spare gas of 20% SF6 gas in 4 MT  Spare gas of 20% SF6 gas in 4 MT  2.12(ITEM NO 22)  Windoscope/ Observinf Window for CB  NIT NO_72528 E8 & E9 Page No: 36 BOQ 3.07 & 3.09(ITEM NO 59 & 61)  Portable PDM system & Online PDM system.		
Spare gas of 20% SF6 gas in 4 MT  Spare gas of 20% SF6 gas in 4 MT  BOQ 2.12(ITEM NO 29)  Windoscope/ Observinf Window for CB  ITaining in Site and Factory  BOQ 3.07 & 3.09(ITEM NO 59 & 61)  Portable PDM system & Online PDM system.	4	BOQ 1.17(ITEM NO 17)
Spare gas of 20% SF6 gas in 4 MT  2.05(ITEM NO 22)  Windoscope/ Observinf Window for CB  VIT NO. 72528 E8 & E9 Page No: 36  BOQ 3.07 & 3.09(ITEM NO 59 & 61)  Portable PDM system & Online PDM system.		
BOQ NIT NO_72528 E8 & E9 Page No: 36 BOQ 3.07 & 3.09(ITEM NO 59 & 61) Windoscope/ Observinf Window for CB Training in Site and Factory  Portable PDM system & Online PDM system.		2.05(ITEM NO 22)
2.12(ITEM NO 29)  Training in Site and Factory  IT NO_72528  E8 & E9 Page No: 36  Portable PDM system & Online PDM system.  Postable PDM system.	100	BOQ
NIT NO_72528 E8 & E9 Page No. 36 Training in Site and Factory  BOQ 3.07 & 3.09(ITEM NO 59 & 61)  Portable PDM system & Online PDM system.		2.12(ITEM NO 29)
NIT NO_72528 E8 & E9 Page No. 36  BOQ BOQ 3.07 & 3.09(ITEM NO 59 & 61)  Portable PDM system & Online PDM system.		
E8 & E9 Page No. 36  Faining in Site and Factory  BOQ 3.07 & 3.09(ITEM NO 59 & 61)  Portable PDM system & Online PDM system.		SCECT ON TIM
BOQ 3.07 & 3.09(ITEM NO  Portable PDM system & Online PDM system.  Please accept the same.  We need your clarification for them.  Please clarify the same.		E8 & E9 Page No. 36
Whether we need to consider them.  Please clarify the same.		30Q 3.07 & 3.09(ITEM NO
Please clarify the same	-	9 00 01)
	-	

( In low

3 of 7

-	15	14	13	12	1	10	9	US Z
	TEM NO 5.01		General	2 General	1 BOQ 3 01 & 3 02(ITEM NO 52 & 53)	The same of the sa	4 02(ITEM NO 63)	
	SERVICES- GIS: INSULATION CO-ORDINATION STUDIES FOR GIS SYSTEM	TYPE TESTING: In case the Bidder has conducted such specified type test(s) according to the relevant standard and / or specification not earlier than Ten (10) years the Type test Report validity for EHV GIS till next 15 Year from the issuance of prior to 08-June-2022, he may submit the type test reports to the Customer for waiver of conductance of such type test(s).  Kindly accept the validity duration till 15 Years inplace of 10 Years.	Gas Monitoring System	GIS Building Layout	SH5 gas Handling Plant	CT with enclosure	GIS spare CB with PIR	Description as per Bid Document
	Insulation Co-Ordination Studies is under scope of bidder, however BHEL should confirm to release the study input details along with GIS layout approval to successful bidder, Otherwise, Manufacturer can not commence manufacturing activity until in insulation cordination study shall not be completed.  Kindly confirm to provide the inputs as per above requested timeline.		We need calification by you for SF6 gas monitor system, you need seperated online SF6 gas monitor system or Gas pressure sensing device(without transmitter).  Please clarify the same.	We would like to inform you that as per received layout diagram GIS structure for GIB is getting foul,  Please revise the beam location in civil diagram.  We will propose GIS layout for your references.	We would like to inform you that our proposed SF6 gas handling plant will compile your requirement of Gas filling, Evacuation, Filtering, Drying, Storage and Recycling work.  Please accept the same.	We would like to inform you that, we are using differeent CT ratios for different Bays  Please clarify which bay CT required in spare.	We would like to inform you that as per present scope CB with PIR is not using in any Bay, so this type CB is not required for this project incase of consideration of PIR requirement, the entire 400kV GIS model will be different. Hence kindly elimate the requirement of CB with PIR as spare item. Please accept the same.	Bidder's Query
	Technical inputs shall be provided to successful bidder based on data provided by NTPC. Manufacturing shall be done by vendor in line with provisions for TS.	In line with TS, Type Test Report validity period shall be as per latest CEA guidelines.	Bidder to follow Tender BOQ.	Refer Note "COLUMN SPACING OF GIS BUILDING SHALL BE AS PER THIS  DRAWING. BIDDER TO OFFER GIS SYSTEM  COMPATIBLE WITH THIS COLUMN SPACING  & BUILDING DIMENSIONS." mentioned in  Conceptual GIS Building layout drawing No.  4540-001-230-PVE-F-023B attached with TS,  Bidder to quote accordingly.	Bidder to follow Tender BOQ.	Bidder to follow BOQ mentioned in Annexure-A of Section-1 of TS (Refer SI: No A4: Spare Bay CT shall be same as Line Bay)	Bidder to follow Tender BOQ	BHEL Reply

( Imakraph

, c			- Table 1	· ·	4	ω	N	J	_	
TBG_ENGG 8. Modular Design	1341798/2023/TBG- TBG_ENGG SLD	TBG_ENGG Noted 4	1341798/2023/TBG- TBG_ENGG 2.17	TBG_ENGG 1.3	TBG_ENGG 1.9. d	1341798/2023/TBG- TBG_ENGG 1.18 PACKING AND DISPATCH	TBG_ENGG 1.8 TYPE TESTING		1341798/2023/TBG-	Clause No
I he bus enclosure shall be sectionalized in a manner that maintenance work on any Noted, however, entire bus shall bus disconnector (when bus and bus disconnector are enclosed in a single enclosure) acceptable. can be carried out by isolating and evacuating the small effected section and not the entire bus.	Notes:  1) CT & VT core details given in single line diagram/TS are tentative and may change document. In case at contract stage. Changes to be incorporated by bidder without any cost and delivery price as required implication to BHEL/ NTPC.	Bidder shall conduct insulation co-ordination & very fast transient overvoltage (VFTO) studies in line with IEC 60071 for establishing suitability of surge arrester rating, and any other technical requirement for successful operation of GIS. Prices for VFTO study shall be included in the price quoted for Insulation Co-ordination study.		Service continuity requirements of GIS	Type test for VT and Surge Arrestor	4 The equipment may be stored outdoors for long periods before installation. The packing shall be completely suitable for outdoor storage in areas with heavy rains and high ambient temperature. Hence, packing of the equipment shall be suitable for long storage (minimum 2 years).	to be supplied under this contract  We understand that the offered product should be type tested as per IEC 6227+203 from the manufacturing works from where the product is being offered and the type testing shall have to be completed before delivery of Pls confirm.  Further regarding validity of type test, we understand type test report will accepted if it been performed before within 10 years from date of signing contract.	otherwise specified, minimum mass of zinc coating for Galvanizing shall be 610 gm/square meter.		rescription as per big Document
be taken out of service. Hope the same is	shall be as per CT/VT parameters mentioned in the tender ie of change in parameters, the same shall be compensated in	We shall offer the Surge arresters as per the BOQ. In case of additional requirement of surge arrester is envisaged after conducting VFTO studies during execution, the same shall be at additional time and price implication.	Confirmed, however any change in length of busduct and bus bar shall be compensated as per unit rate defined in respective line item in Price Bid.	Access from front side to ciruit breaker is possible only in design of circuit breakers that are horizontally oriented.  For vertical circuit breakers, the access to interrupters is from top (to remove/repair interrupter), hence we understand that the requirement for 400 kV GIS in this project is with horizontal circuit breakers only. Pis confirm.	For the surge arrestor and $VT$ , type tests of the vendors shall be submitted for approval. We do not envisage to repeat the type test.	In case the material is to be stored for longer periods, we request BHEL to store the material in Indoor Store only and in line with OEM storage guidelines.	We understand that the offered product should be type tested as per IEC 62271-203 from the manufacturing works from where the product is being offered and the type testing shall have to be completed before delivery of GIS Pis confirm.  Further regarding validity of type test, we understand type test report will be accepted if it been performed before within 10 years from date of signing of contract.	We would like to inform that structures are hot dip galvanized according to EN ISO 1461[2]. The coating thickness is at-least 85 µm. We shall offer structure suitable for highly corrosive, highly humid and more prone to fungli environment.	Annexure-III	Bidder's Query
Bidder to offer as per OEM Type Tested design.	Any change in qty of no. of CT cores shall be adjusted based on unit rates quoted for the respective items; However, CT secondary parameters shall be as per Annexure-3 of Section-2.	Unit rates shall be operated in case of any addition/deletion of equipment. No time implication shall be allowed.	For Bus Ducts, Bidder to quote as per Tender BOQ.	Bidder to offer as per OEM Type Tested design.	Bidder to follow TS.	Noted	Pl. follow TS. Also, in line with TS, Type Test Report validity period shall be as per latest CEA guidelines.	Bidder to follow minimum requirements mentioned in TS.		BHEL Reply

Of Mulhard


21		t		17	A CONTRACTOR OF THE PARTY OF TH		15	14		12		1	10
11.05.00 (f) 11.06.00 (e)	Sub Section -B-17 11.01.00	4.04.00 (l)	3.03.02 Sub Section -B-17	2.21.00	Sub Section -B-17 2.15.00	2 13.02	Sub Section -B-17	2.03.21	Notes for Switch yard	BOQ-tr	100	Notes 10  BOQ-F2	Clause No 1341798/2023/TBG-
Capacitance and tan delta measurement at minimum 10kV	alties of the items as per oyer without any extra cost	mechanical position indication shall be provided locally at each switch along with remote indication at each bay module control cabinet & in the power house control room.	trip	Commissioning Tests On completion of the erection and installation, following commissioning tests shall be performed as per IEC 62271-203, CIGRE working Group 23.03, 1975-Electra No.42, 7-29:	The leads to the tank heaters shall be enclosed in a conduit.	of the monitoring device can be performed without draining the main gas system. Each gas section shall be fitted with a suitable valve for routine gas sampling	Gas pressure monitoring devices shall be filled with tool with	Adequate number of gas leak detectors shall be installed at various locations at the base of the GIS structure to detect presence of gas which may be harmful for human. The detector shall send alarm signal locally as well as at remote stations.	GIS CT for metering purpose	Final successful Testing of GIS including HV test and its accessories		chemical anchor bolts and hardware etc. required for fixing and erection of GIS and bus duct shall be in bidder scope.  Circuit breaker with PIR	All supporting structures including foundation boths! fixture boths! contradict that
As per OEM recommendation, the subject tests is not applicable for GIS.	Site testing shall be done in line to IEC and as per OEM standards. Kindly accept.	We would like to inform that, As per manufacturer's product specific design mechanical position indication shall be provided with operating mechanism. LED position indication shall be provided in local control cubicle.	We would like to inform that, Trip circuit supervision relay shall be part of relay panel. In Local control cubicle of GIS, no relays shall be provided.	We would like to inform that, Site routine test shall be performed as per IEC only.	Tank heaters is not applicable for GIS, and offered GIS is type tested in line with IEC.	We would like to inform that, functional check /comparative check/calibration/replacement of gas density switch can be done by isolating the device from the GIS system, without de-energizing the primary equipment and without reducing pressure in gas compartments.	leak detectors, local alarm and remote alarm is not considered in scope.		We have considered CTs in line with the BCQ. Scope of supply documents	Noted, however, we have considered supervision of erection, testing and commissioning in one mobilization only.	Please note that the circuit breakers are without PIR. We understand that CSD is required in the breakers mentioned in the bay description and SLD. Request clarify on these clauses where PIR is mentioned.	Embedded Items, Rails and/ or other items structural items specific to GIS shall be as per OEM design, hence request you to consider accordingly in BOQ as lot item included in respective GIS Bay/GIB price	Bidder's Query
Bidder to follow TS.	Bidder to follow TS.	Noted	Trip circuit supervision relays are not to be provided in GIS LCC.	Bidder to follow TS	Noted; Bidder to offer as per OEM Type Tested design.	Noted		Bidder to follow TS	Bidder to follow TS	Bidder to follow TS	All the CBs are without PIR, however bidder to quote unit rate for the CB with PIR as per Tender BOQ.	Bidder to quote as per Tender BOQ.	BHEL Reply


at maken

28	27	26	25	24	23	22	S
General	General	Sub Section -B-17 3 20.3	Sub Section -B-17	Sub Section -B-17 2 15 00	SAS	Sub Section -B-17 11 07 00 (e)	Clause No
Make and Model of the equipment	DING SHALL BE AS PER THE DRAWING ON ER TO OFFER GIS SYSTEM COMPATIBLE WITH DING DIMENSIONS	BAY MARSHALLING BOX	Type fast	HEATERS:	Merging Units / Bay control units / Switchgear control units	SURGE ARRESTER  a) Grading leakage current b) Resistance of ground connection c) Resistive current drawn at rated voltage after energisation.	Description as per Bid Document
We request to provide the approved vendor list, make/model of the equipment to be supplied under this tender	We request to provide the AutoCAD drawing for the layout to examine the feasibility of installation.	Please note that the bay marshalling box is not in our scope, we have considered Local control cubicles for the control and wiring termination of GIS.	We understand that the offered product should be type tested as per IEC 62271-203 from the manufacturing works from where the product is being offered and the type testing shall have to be completed before delivery of GIS PIs confirm.  Further regarding validity of type test, we understand type test report will be accepted if it been performed before within 10 years from date of signing of contract.	We wish to inform that offered drive in CB/DS/ES is having continuous heater design and does not required any kind of thermostat. Same is as per type tested design.	We have offered conventional LCC along with conventional CT & VT in GIS Cables shall be considered from GIS to LCC as per conventional practice with tentative distance marked in Layout. MIU/BCU/SCU or any associated cables are not considered in bidders scope.	As per OEM recommendation, the subject tests shall not be performed at site	Bidder's Query
Bidder to offer equipments meeting the technical requirements mentioned in the TS. Also, the offered equipments shall be suitable for maintenance/ monitoring of the supplied GIS system.	Enclosed	Noted	In line with TS, Type Test Report validity shall be as per latest CEA guidelines.	Noted; Bidder to offer as per OEM Type Tested design.	Noted	Bidder to follow TS.	BHEL Reply

CHACK LECONDRA

Whitek KAPIL 23.3.23





# 400kV OUTDOOR EQUIPMENT

S.NO.	DESCRIPTION	SYMBOL	BAY NO./LOCATION	UNIT	QUANTITY
1	3X1PH, 3X275 MVA, 420/SQRT(3)/21kV GENERATOR TRANSFORMER		404, 410	NOS.	2
2	144* MVA, 400/11.5/11.5 kV STATION TRANSFORMER		401, 407	NOS.	2
3	125 MVAr, 400kV SHUNT REACTOR - 3PH	<b>)</b>	412 BR	NOS.	1
4	336 kV LIGHTNING ARRESTER - 1PH	ţ	401 LA, 403 LA, 404 LA, 406 LA, 407 LA, 410 LA, 412LA, 413 LA, 415 LA	NOS.	27
5	400kV, 8800pF LINE CAPACITIVE VOLTAGE TRANSFORMER - 1PH.	<del> </del>	403 CVT, 406 CVT, 413 CVT, 415 CVT	NOS.	12
6	400kV, 4400pF CAPACITIVE VOLTAGE TRANSFORMER FOR GT BAYS - 1PH	<u>.</u>	404 CVT, 410 CVT	NOS.	6
7	400kV, 3150A 0.5mH PEDESTAL MOUNTED WAVE TRAP - 1PH		403 WT, 406 WT, 413 WT, 415 WT	NOS.	8

# 400kV INDOOR GIS

S.NO.	DESCRIPTION	SYMBOL	BAY NO./LOCATION	UNIT	QUANTITY
1	400kV, 3150 A, 63kA FOR 1 SEC, CIRCUIT BREAKER WITH CONTROLLED SWITCHING - 3PH	<b>◆</b> * * •	401-52, 402-52, 407-52, 408-52, 411-52, 412-52	SETS	6
2	400kV, 3150 A, 63kA FOR 1 SEC, CIRCUIT BREAKER WITHOUT CONTROLLED SWITCHING - 3PH	•— <b>′</b> ×—•	403-52, 404-52, 405-52, 406-52, 409-52, 410-52, 413-52, 414-52, 415-52	SETS	9
3	400kV, 3150 A, 63kA FOR 1 SEC, DISCONNECTOR WITH ONE EARTH SWITCH - 3PH	1	401-89A, 401-89B, 401-89T, 403-89A, 403-89B, 404-89A, 404-89B, 404-89T, 406-89A, 406-89B, 407-89A, 407-89B, 407-89T, 409-89A, 409-89B, 410-89A, 410-89B, 410-89T, 412-89B, 412-89BR, 413-89A, 413-89B, 415-89A	SETS	25
4	400kV, 3150 A, 63kA FOR 1 SEC, DISCONNECTOR WITH TWO EARTH SWITCHES - 3PH	1 6 1	402-89A, 402-89B, 405-89A, 405-89B, 408-89A, 408-89B, 411-89A, 411-89B, 414-89A, 414-89B	SETS	10
5	400kV, 3150 A, 63kA FOR 1 SEC, DISCONNECTOR WITH ONE HIGH SPEED EARTH SWITCHES -3PH	;	403-89L, 406-89L, 409-89L, 413-89L, 415-89L	SETS	5
6	400kV, 3000A, 63kA FOR 1 SEC, CURRENT TRANSFORMER - 1PH	φ.	401-CTA, 401-CTB, 402-CTA1, 402-CTA2, 403-CTA, 403-CTB, 403-CTL, 404-CTA, 404-CTB, 405-CTA1, 405-CTA2, 406-CTA, 406-CTB, 406-CTL, 407-CTA, 407-CTB, 408-CTA1, 408-CTA2, 409-CTA, 409-CTB, 409-CTL, 410-CTA, 410-CTB, 411-CTA1, 411-CTA2, 412-CTA, 412-CTB, 413-CTA, 413-CTB, 413-CTL, 414-CTA1, 414-CTA2, 415-CTA, 415-CTB, 415-CTL	NOS.	105
7	400kV, 3000A, 63kA FOR 1 SEC, METERING CURRENT TRANSFORMER - 1PH	φ-	401-CTM, 404-CTM, 407-CTM, 410-CTM, 412-CTBR	NOS.	15
8	400kV BUS VOLTAGE TRANSFORMER - 1PH		4BUSI VT, 4BUSII VT	NOS.	6
9	400kV, 3150 A, 63kA FOR 1 SEC, DISCONNECTOR FOR BUS VT WITH TWO EARTH SWITCHES - 3PH		4BUSI 89, 4BUSII 89	SETS	2
10	BUS SURGE ARRESTER - 1PH	ţ	4BUSI LA, 4BUSII LA	NOS.	6
11	400kV SF6 TO AIR BUSHING - 1PH	•	401-X, 403-X, 404-X, 406-X, 407-X, 409-X 410-X, 412-X, 413-X, 415-X	NOS.	30

## NOTES:

- WAVETRAPS SHALL BE PROVIDED IN TWO PHASES.
- RATING OF LA SHALL BE DECIDED BASED ON INSULATION COORDINATION AND TOV RESULTS.
- ST RATING IS SUBJECT TO APPROVED SIZING CALCULATION
- EARTHING SWITCHES MARKED WITH # ARE HIGH SPEED EARTHING SWITCHES.
- CIRCUIT BREAKERS WITH \* ARE BREAKERS HAVING CONTROLLED SWITCHING FACILITY.
- GT STANDS FOR GENERATOR TRANSFORMER.
  - ST STANDS FOR STATION TRANSFORMER.
- NOMENCLATURE MAY CHANGE AFTER FINALIZATION OF VENDOR.

### MAIN SYSTEM PARAMETERS

1. NOMINAL VOLTAGE	-	400kV
2. HIGHEST SYSTEM VOLTAGE	-	420kV

3. RATED FREQUENCY 50 HZ

4. RATED SHORT TIME CURRENT 63kA FOR 1 SEC

5. POWER FREQUENCY WITHSTAND VOLTAGE 650 kVrms

± 1425 kVpeak 6. LIGHTNING IMPULSE WITHSTAND VOLTAGE

7. SWITCHING IMPULSE WITHSTAND VOLTAGE ± 1050 kVpeak

LINE DIAGRAM

8. CREEPAGE 31mm/kV (13020 MM)

CA NO.								
ADDITIONAL INFORMATION W.O.No.	ग्राहक/परियोग	তাৰা কা ৰাফ						/ER
STATUS OF DRAWING	NAME OF CUSTON	MER/PROJECT	PROJEC	CT PHAS	E-III (	(2x660 MV	V)	
DISTRIBUTION OF PRINTS	<i>बीएचईएत्त</i>	भारत हेवी	इलेबिट्कल्स	लिमिटेड	बनाया	नाम /NAME	हस्ता ./sign.	दि./DATE

DATE ALTERED	REV.	DATE	ALTERED	REV.	DATE	ALTERED REV	DATE	ALTERED	REV.	DATE	ALTERED	REV.	DAT	TE ALTERED	REV.	DATE	ALTERED RE	. DATI		REV.	DATE	ALTERED	PC
CHECKED			CHECKED	I		CHECKED		CHECKED			CHECKED			CHECKED APPROVED	]		CHECKED		CHECKED	] 01	12 12 2	2 CHECKED APPROVED	RD
APPROVED			APPROVED			APPROVED		APPROVED			APPROVED			APPROVED			APPROVED		APPROVED	101	12.12.2	APPROVED	VK
	ZONE			ZONE		ZON	E		ZONE			ZONE			ZONE		ZO	Æ.		ZONE	ADDI:		NCORPORATE CSD AS PER ENTS.

अनुपात / SCALE कार्ड को ह 400kV GIS SWITCHYARD SINGLE