

	BHARAT HEAVY ELECTRICAL LIMITED			Enquiry No. :	
	UNIT'S ADDRESS: Fabrication Plant <u>Bharat Heavy Electricals Limited</u> <u>Industrial Area jagdishpur, District: Sultanpur</u> <u>Uttar Pradesh-227817 (India)</u> Ph: -+91-5361-271378 Fax: +91-5361-271382			Due Date :	
CONTACT PERSON'S NAME/DESIGN./PHONE NO./E-MAIL (FROM PURCHASE DEPTT.)				Supplier Qtn. No.:	
<u>SPECIFICATION CUM COMPLIANCE CERTIFICATE OF FLOOR TYPE CNC HORIZONTAL BORING MACHINE</u>					
NOTE:-					
1. Vendor (OEM) must submit complete information against clause no. 25 (Qualifying condition). The offer meeting this clause would only be processed (OEM : Original Equipment Manufacturer).					
2. The following format must be completely filled and deviations mentioned in the appropriate columns. Inadequate /incomplete, ambiguous, or unsustainable information against any of the clauses of the specifications/requirements shall be treated as non-compliance.					
3. The offer and all documents enclosed with offer should be in English language only.					
NAME & ADDRESS OF THE SUPPLIER :					
TELEPHONE NOS.:					
FAX NOS.:					
E-MAIL ADDRESS :					

SCOPE: SUPPLY, ERECTION & COMMISSIONING OF FLOOR TYPE CNC HORIZONTAL BORING MACHINE COMPLYING WITH SPECIFICATIONS AS BELOW					
SNO	DESCRIPTION FOR BHEL REQUIREMENT	CONFIRMED BY	OFFERED	DEVIATIONS	REMARKS
1.0	PURPOSE & WORKPIECE MATERIAL				
1.1	Purpose : The machine is required for machining of Water Box, water Chambers and other components of Condensers, turbines and Generators of various ratings. The Machine should be suitable for heavy duty Milling, heavy Drilling, Boring, Threading-Metric & Buttress Threads, Reverse Counter Boring, Core Drilling, Reaming, etc. on high alloy steel castings.	Vendor to confirm			
1.2	Work Piece Material: The machine should be capable of machining components of Ferrous and non Ferrous metals like Caron Steel, alloy Steel, cast Iron, copper, Alminium etc. and other similar metals.	Vendor to confirm			
2.0	SPECIFICATIONS:				
2.1	MACHINE CONFIGURATION: The Machine shall be Floor Type CNC Horizontal Boring Machine with a Rotary Table. Looking from spindle side, AAC is to be on Right side of Rotary Table. Linear movement of Table is to be perpendicular to X-axis. Vendor to supply layout of machine showing size and depth of pit, alongwith the offer.				
2.2	HEAD STOCK				
2.2.1	Boring spindle diameter	200MM			
2.2.2	Milling spindle diameter	vendor to inform			
2.2.3	Ram Cross section (LxB)	450 mm x 450 mm (min.)			
2.2.4	Spindle drive power - AC (Continuous Rating - S1)	100 KW (or more)			
2.2.5	Spindle speed (Infinitely variable) (RPM)	3 to 1500 (or more)			
2.2.6	Max torque on the boring spindle (N-m)	4000Nm min.			
2.2.7	Max torque on the milling spindle (N-m)	4000Nm min.			
2.2.8	Spindle taper	ISO - 60			
2.2.9	Machine to be supplied with a Conversion Sleeve of taper ISO-60 / BT-50 fitted in the spindle of the machine. This Sleeve is to remain fitted in spindle during the normal operation of the machine. One no. additional Conversion Sleeve to be supplied as spare. All toolings to be mounted on machine spindle should have a shank taper of BT-50.	Vendor to submit / confirm			
2.2.10	Torque-Power-Speed characteristics of the spindle system to be submitted by the vendor.	Vendor to submit			
2.2.11	Spindle Cooling System (Details to be submitted)	Vendor to offer			
2.3	COLUMN:				
2.3.1	Column longitudinal travel (X-Axis)	8500 mm			
2.3.2	X-axis feed rate (Infinitely variable)	1 to 10000 mm / Min. (or more)			
2.3.3	X-axis rapid traverse rate	10 M/ Min. (or more)			
2.3.4	Axis Resolution	0.001			
2.4	HEADSTOCK TRAVERSE ON COLUMN:				
2.4.1	Headstock vertical travel (Y-Axis)	5000 mm			
2.4.2	Traverse Range (w.r.t. Table top)	0-5000 mm			
2.4.3	Y-axis feed rate (Infinitely variable)	1 to 10000 mm / Min. (or more)			

SNO	DESCRIPTION FOR BHEL REQUIREMENT	CONFIRMED BY	OFFERED	DEVIATIONS	REMARKS
2.4.4	Y-axis rapid traverse rate	10 M/ Min. (or more)			
2.4.5	Axis Resolution	0.001			
2.5	RAM/ SPINDLE TRAVERSE:				
2.5.1	Boring spindle axial travel (W-Axis)	1100 mm (or more)			
2.5.2	Ram axial travel (Z-Axis)	1300 mm (or more)			
2.5.3	Spindle + Ram travel (W+Z)	2400 mm (or more)			
2.5.4	Lowest spindle position from machine bed plate (200mm or less)	Vendor to confirm and submit details			
2.5.5	Boring Spindle axis feed rate (Infinitely variable)	1 to 5000 mm / Min. (or more)			
2.5.6	Boring Spindle axis rapid traverse rate	5 M/ Min. (or more)			
2.5.7	Ram axis feed rate (Infinitely variable)	1 to 5000 mm / Min. (or more)			
2.5.8	Ram axis rapid traverse rate	5 M/ Min. (or more)			
2.5.9	Axis Resolution	0.001			
2.5.10	Spindle & Ram Axes should be independently programmable with Independent Drives and Feed back system.	Vendor to offer			
2.6	FEED AND DRIVE SYSTEM:				
2.6.1	Feed drives/ motors for X,Y,Z & W axes [AC servo motors] shall be digital type of either Siemens or Fanuc make (Details of model, make, type etc. to be submitted)	Vendor to offer			
2.6.2	Maximum feed force for all axes	Vendor to inform			
2.6.3	Feed back system for X, Y & Ram (Z) axes: Heidenhain linear scales with pressurised compressed air cleaning (Details to be submitted by the vendor)	Vendor to offer			
2.6.4	Feed back system for Spindle (W) Axis: Heidenhain Rotary/Linear Encoders (Details to be submitted by the vendor)	Vendor to offer			
2.6.5	Type of power transmission: 1. Pre-loaded backlash free double pinion & rack drive for X-axis. 2. Backlash free re-circulating ball screw with Pre-loaded double nut for all other axes. (Complete description of the aforesaid including diameter of Ball Screw for each axis, to be submitted with the offer)	Vendor to offer			
2.6.6	Mechanism for locking X, Y & Z axis	Vendor to offer			
2.6.7	Maximum thrust rating of all axes.	Vendor to offer			
2.7	MACHINE GUIDEWAYS:				
2.7.1	Width of bed guideways, X-axis	Vendor to inform			
2.7.2	Width of column guideways, Y-axis	Vendor to inform			
2.7.3	Details of Guide ways for Ram axis and bearing details of Spindle axis are to be submitted with offer.	Vendor to inform			
2.7.4	Guide ways for X-axis, Y-axis & Z-axis: Hydrostatic (Details to be submitted). Details of lubrication system provided on Spindle axis are also to be submitted with the offer.	Vendor to inform			
2.7.5	Hardness of guideways	Vendor to inform			
2.7.6	Metallic Telescopic Covers of rust resistant material to be provided with wipers for X & Y axes guide ways. Joints of telescopic covers should be so sealed to avoid mixing of coolant & hydrostatic oil is to be provided.	Vendor to inform			
2.8	ROTARY TABLE :				
2.8.1	Table size (LxB) in mm	2000x2500			
2.8.2	Maximum load carrying capacity (Tons)	25			
2.8.3	Table rotation	360 degrees			
2.8.4	Hight of table above floor	900mm			

SNO	DESCRIPTION FOR BHEL REQUIREMENT	CONFIRMED BY	OFFERED	DEVIATIONS	REMARKS
2.8.5	Length of Bed	3500mm (Aprox.)			
2.8.6	Table travel on bed	1200 mm			
2.8.7	Longitudinal and circular feed	infinitely variable			
2.8.8	Fine feeds within	0.75 to 75 mm/min			
2.8.9	Working feeds within	5 to 500 mm/min			
2.8.10	Rapid feeds within	10 to 1000 mm/min			
2.8.11	Rating of feed motor	7.5 KW			
2.8.12	Accuracy of Table indexing	+/- 5 minutes (min.)			
2.8.13	Size of Longitudinal Slot and T-slot pitch over table	28 mm (to suit M24 Bolts) and 250 mm respectively			
2.8.14	Feed back devices :				
2.8.15	a) Rotary encoder, preferably Heidenhain make	Vendor to confirm			
2.8.16	b) Linear Scale, preferably Heidenhain make	Vendor to confirm			
2.8.17	c) DRO , preferably Heidenhain make	Vendor to confirm			
2.8.18	Feed drives : Fanuc/ Siemens digital AC Servo drives.	Vendor to confirm			
2.8.19	Bearings, preferably SKF/FAG make	Vendor to confirm			
2.8.20	Rotary table shall be fitted with telescopic cover and wipers to remove chips & dust	Vendor to confirm			
2.8.21	One set of tool kit for operation and maintenance of table shall be provided.	Vendor to confirm			
2.8.22	Recommended spares including oil seals, bearings etc. shall be provided	Vendor to confirm			
2.8.23	Location of the Table: Table shall be detachable type and can be mounted anywhere on the floor plate as per the requirement	vendor to confirm			
2.8.24	Centralised lubrication for lubrication of table and floor plate shall be provided	vendor to confirm			
2.8.25	Following documentation shall be sent along with the rotary table: 3 sets of O&M manuals consisting of:- • Operating & maintenance instructions. • Kinematic diagrams of drive & gear mechanism & operation of rotary table. • Electrical/Electronic circuit diagrams. • Drawings/ details of PCBs etc. • Lubrication charts for table, drive, gear box, saddle, slide way etc. • Table for comparable oil/grease with reference to recommended lubricants. • List of bearings/ sealing/devices for electrical items. • System for limiting play in table movements.	vendor to submit			
2.9	FLOOR PLATES: Cast Iron Floor Plates having T-slots of size 42 mm suitable for Clamping Bolts of size M36 for clamping of job.	Vendor to offer			
2.9.1	Dimensions of Floor Plates (Length X Width)	8000 mm X 8000 mm			
2.9.2	Floor Plates should have T-slots of size 42 mm suitable for Clamping Bolts of size M36 for clamping of job.	Vendor to confirm			
2.9.3	Anchoring Material for fixing the Floor Plates on the foundation	Vendor to offer			
2.10	CONSTRUCTION				
2.10.1	Vendor to furnish details of material , hardness and constructional details including explanatory drawings of various components / assemblies like column, Bed, Head stock, Ram, Spindle, Rotary table etc.	Vendor to submit.			

SNO	DESCRIPTION FOR BHEL REQUIREMENT	CONFIRMED BY	OFFERED	DEVIATIONS	REMARKS
2.10.2	Video images on CD including hard copy explaining the technical features / literature with photograph, drawings should be enclosed with the offer.	Vendor to submit.			
2.10.3	Automatic deflection compensation for ram and column effective at any extension of the ram plus spindle is to be provided taking into consideration weight of all possible cutters/ attachments offered. Details of the offered system should be submitted with offer.	Vendor to submit.			
2.10.4	Head Stock and Column Counterbalancing System.	Vendor to submit.			
2.11	OPERATOR'S PLATFORM:				
2.11.1	Operator's platform of sufficient load carrying capacity to be provided. with Independent Motorised Vertical Movement for total Vertical Traverse as well as forward stroke of sufficient length . Push Button switches are to be provided on the Operator's Platform at suitable location for motorised movement. A 15 Amp. Plug Point with ON/ OFF switch is also to be provided on the Platform.	Vendor to offer			
2.11.2	Horizontal movement of complete Platform.	Vendor to inform			
2.11.3	Weight carrying Capacity of the Platform should be Min. 300 Kg..	Vendor to inform			
2.11.4	Minimum Height of Platform from Shop Floor.	Vendor to inform			
2.11.5	Splash / Chip guards on operator platform for protection of operator, operator's panel and to avoid spillage of coolant & chips on operator's platform.	Vendor to offer			
2.12	OPERATION AND CONTROL SYSTEM:				
2.12.1	OPERATOR'S PANEL:				
2.12.1.1	Swiveling type operator's panel having complete CNC and machine control system with CRT/TFT of required configuration shall be provided on the operators platform. All switches on the Operator's panel including that for table rotation should be within reach of operator of average height (Indian, 5'6" approx.) for convenient, efficient & safe operation. All displays/indications should also be conveniently placed accordingly. Layout showing complete details of the panel should be submitted.	Vendor to offer			
2.12.2	CNC SYSTEM & FEATURES :				
2.12.2.1	Make : Fanuc / Siemens.	Vendor to confirm			
2.12.2.2	Type : PC based latest version	Vendor to confirm			
2.12.2.3	Model: Sinumerik 840D with PC Version PCU 50, NCU 573.5 or higher with Intel Pentium III, 1GHz, 512 MB SDRAM (or higher), Windows XP Operating System or equivalent Fanuc system. (Latest version, as available at the time of ordering, should be supplied).	Vendor to offer and submit details			
2.12.2.4	The system should, preferably, have OP 15 Operator's Panel with TFT colour display (15 inch or more), 19 Inch Machine Control Panel , Full CNC Keyboard with Qwerty keys and Mouse/Trackball or equivalent for Fanuc system, RS232-C interface for I/O devices, COM1(V.24), COM (V.24), LPT1 Parallel Interface for Printer, VGA, MPI interface & USB, 2 Channels and Expansion slots. The operator Panel configuration will be as per Rittal VIP6000 or equivalent. The CNC System shall also have Electronic hand wheels selectable for all axes, USB Port with 1 GB Pen drive (for each machine) for data input/output, Hard disk of 10 GB or higher (Largest size available at the time of order shall be supplied), Graphic Simulation, COM port for telediagnosics, Network ready with LAN and preinstalled system software & other required softwares etc. (Details should be submitted by Vendor)	Vendor to offer and submit details			

SNO	DESCRIPTION FOR BHEL REQUIREMENT	CONFIRMED BY	OFFERED	DEVIATIONS	REMARKS
2.12.2.5	The CNC System should necessarily have the following features: Access locks on the operator panel, Coordinate System Rotation, Coordinate System Transformation, Look Ahead of Minimum 70 blocks, Helical Interpolation, Scaling, Programmable mirror image machining, Process oriented Canned Cycles for Drilling, Milling & Turning operations, Rigid Tapping and Tool Management. The system shall also have SITOP Power, DC-UPS Module 15 with AKKU module to ensure automatic unattended shutdown of the system in case of power failure or even in normal machine shutdown, Display of PLC ladder on 840D monitor & Simatic S-7 loaded on the hard disk and Display of servo-waveforms on 840D monitor or equivalent features in Fanuc system.	Vendor to offer and confirm			
2.12.2.6	Details of Standard features. List to be submitted.	Vendor to specify			
2.12.2.7	Features of CNC System required for identified jobs or foreseen by the vendor as required.	Vendor to specify			
2.12.3	MANUAL CONTROL :				
	Complete manual control of machine with required switches / keys should be provided on operator's panel for selection of required axis, axis direction, cutting feed, spindle rpm, Direction of Spindle Rotation, i.e. CW/ CCW, cutting feed and spindle rpm on/off, display of axis position values etc, for manual operation without using CNC program or MDI mode. Diagram/ Sketches for switches/ keys provided on operators pendant to be submitted.	Vendor to confirm. Layout of panel showing requisite switches to be submitted.			
2.12.4	HAND HELD UNIT:				
	Hand Held unit, Type B-MPI of Siemens make or equivalent alongwith sufficient length of interfacing cable is to be offered with complete details.	Vendor to offer			
2.12.5	UPS FOR CNC SYSTEM:				
	UPS of 30 minutes for CNC system with inbuilt cooling and charge status display. (Battery charging /discharging time should be specified by vendor)	Vendor to offer			
2.12.6	PORTABLE FLOPPY DRIVE UNIT (I/O DEVICE):				
2.12.6.1	Portable Floppy Drive Unit or its equivalent (Note Book PC with pen drive) for bi-directional transfer of program and data between the offered unit and supplied CNC system as well as any standard PC shall be supplied with all required interfaces, cables and software.	Vendor to offer and submit details			
2.13	MACHINE LIGHTS:	Vendor to offer and submit details			
2.13.1	Machine Lights for sufficient illumination of complete working area on both sides of operator's platform should be provided for clear visibility.	Vendor to offer and submit details			
2.13.2	A magnetic base portable spot light with sufficiently long cable should also be provided.	Vendor to offer and submit details			
2.13.3	Any lights required in the foundation/ pit area shall also be foreseen and supplied by the vendor.	Vendor to offer and submit details			
2.13.4	All light fittings, consumables, adapters/receptacles should have compatibility with Indian equivalents	Vendor to offer and submit details			
2.13.5	Flashing / rotary type End of Cutting and Program Stop Light.	Vendor to offer and submit details			
2.14	AIR CONDITIONERS:				
2.14 .1	Air Conditioners with Dehumidifiers of suitable / sufficient capacity to be provided for all Electrical / Electronic Panels / Cabinets including Operator's Panel considering specified ambient conditions. Detailed specifications of the same are to be submitted.	Vendor to offer			

SNO	DESCRIPTION FOR BHEL REQUIREMENT	CONFIRMED BY	OFFERED	DEVIATIONS	REMARKS
2.14.2	In case of order, vendor shall confirm to supply the following information about Air Conditioners and Chiller Unit (s) used in the machine: Type of Refrigeration/ Chiller unit. Capacity of the chiller unit. Type of compressor with complete specifications. Type of Thermostatic Expansion Valve with complete specifications. Fan size and flow in CFM (cubic feet meter) of the Condenser unit. Specifications of the Evaporator Unit (Width Plate type/ Coil type) Functional requirement of temperature of Cooling Oil to be maintained between range T1 to T2. Type of temperature indicator/ controller used in the chiller unit with complete specifications.	Vendor to confirm			
2.15	HYDRAULIC SYSTEM : Details should be Submitted by the Vendor				
2.15.1	The Hydraulic System shall be of Re-circulating Type. Hydraulic Tank should be preferably placed at shop floor.	Vendor to offer and confirm			
2.15.2	Pumps, Valves, Switches (Pressure & Flow) should be of Make : Rexroth / Vickers / Parker / Hawe.	Vendor to offer and confirm			
2.15.3	Filtration System: Sufficient no. of filters (with electric clogging indicator and alarm on PLC) should be used to avoid frequent clogging of the filters and other maintenance related problems. Filter elements should be of Make: EPE / Hydac.	Vendor to offer and confirm			
2.15.4	Failure indication	Vendor to offer			
2.15.5	Automatic shut off provision, Details should be submitted.	Vendor to offer			
2.15.6	Refrigerated type cooling and electric heating (Electric heating, only if required) system of sufficient capacity to maintain complete Hydraulic System, including lubrication oil, hydrostatic oil and gearbox oil, etc. keeping in view the specified ambient conditions to be offered with complete details. The temperature of Hydraulic Oil should not go beyond 40 deg. C.	Vendor to offer & submit			
2.15.7	Hydraulic pump capacity (flow/ pressure) to be intimated.	Vendor to inform			
2.15.8	No Tandem pumps should be used. Maximum desired permissible pressure is 100 Kg/sqcm. If anywhere, more than 100 Kg/sqcm pressure is used, then one set of such hose pipes and seal kit of such Hydraulic cylinder should be supplied in spare in addition to other spares.	Vendor to confirm & offer			
2.15.9	First filling of all required Oils & Grease etc. to be supplied by vendor. Indigenous (Indian) source or Indian equivalent and specifications of oils / greases are also to be provided by the vendor.	Vendor to offer & submit			
2.16	COOLANT SYSTEM :				
2.16.1	Coolant System with all accessories for following variants shall be provided. Selection of all the variants shall be through program and push buttons provided on the Operator's panel as well.	Vendor to offer and submit details			
	a) Recirculating Type Flood Coolant System with nozzles around spindle.	Vendor to offer and submit details			
	b) Air coolant system	Vendor to offer and submit details			
	c) High Pressure Coolant thru Spindle	Vendor to offer and submit details			
2.16.2	All offered attachments, tool holders, boring bars, cassettes, adapters etc. shall have the provision so that coolant is available directly at the tool-cutting tip.	Vendor to offer and submit details			
2.16.3	Coolant collection and recirculation system should be leakproof & perfect to avoid any spillage on shop floor, trenches for cables & foundation pit of the machine etc.	Vendor to offer and submit details			
2.16.4	Coolant Filtration System: Recirculating type coolant system with Vacuum Rotary drum type System.	Vendor to confirm and submit details.			
2.16.5	Coolant Flow Diagram showing filters, pumps, valves, tanks etc. to be submitted with the offer.	Vendor to offer and submit details			

SNO	DESCRIPTION FOR BHEL REQUIREMENT	CONFIRMED BY	OFFERED	DEVIATIONS	REMARKS
2.16.6	Pressure & rate of flow of coolant for different variants should be furnished in the offer. The Pressure should be sufficient for the coolant to reach the tool tip at full pressure.	Vendor to offer and submit details			
2.16.7	Coolant Tank Capacity (Any specific requirement, like Deep Hole Drilling etc. to be specified by indentor)	Vendor to offer and submit details			
2.16.8	For finer control of Pressure and Coolant Flow Rate, after its activation through program or switches, Rotary/ potentiometer switches shall be provided on the Operator's Panel.	Vendor to offer and submit details			
2.16.9	Coolant pump & motor details for all variants of coolant system are to be submitted with the offer.	Vendor to offer and submit details			
2.16.10	The coolant tank should be fitted with skimmer for regular cleaning of coolant from contamination with tramp oil.	Vendor to offer and submit details			
2.17	ELECTRICAL SYSTEM :				
2.17.1	415V with + 10% / -10% fluctuation, 50HZ with fluctuation of +/-3 HZ, 3 Phase AC (3 wire system with out neutral) Power Supply Source will be provided by BHEL at a single point near the machine, as per layout recommended by Vendor. All types of cables, connections, circuit breakers etc. required for connecting BHEL's power supply point to different parts of the machine/control cabinets, shall be the responsibility of vendor. Requirement of grounding/earthing with required material details is to be informed by vendor well in advance so that same could be incorporated during construction of foundation.	Vendor to comply			
2.17.2	Tropicalisation: All electrical / electronic equipment shall be tropicalized	Vendor to comply			
2.17.3	All electrical & electronic control cabinets & panels should be dust and vermin proof	Vendor to comply			
2.17.4	All electrical components in the cabinets should be mounted on DIN Rail	Vendor to comply			
2.17.5	All electrical and electronic panels including operator's panel should be provided with fluorescent lamps for sufficient illumination and power receptacles of 220Volts, 5/15 Amp AC. All adapters/receptacles should have compatibility with Indian equivalents.	Vendor to comply			
2.17.6	Motors shall conform to IEC or Indian Standards	Vendor to comply			
2.17.7	All cables moving with traversing axes should be installed in Caterpillar/ Drag chain mounted horizontally/vertically. Additionally, all the cable trays required for laying of cables should be included in the offer.	Vendor to confirm			
2.17.8	Vendor should ensure the proper earthing for the machine and its peripherals.	Vendor to comply			
2.17.9	In-cycle hour counter with reset facility is to be included in the offer.	Vendor to comply			
2.18	SAFETY ARRANGEMENTS:	Vendor			
	Following safety features in addition to other standard safety features should be provided on the machine:	Vendor to comply			
	1.Machine should have adequate and reliable safety interlocks / devices to avoid damage to the machine, workpiece and the operator due to the malfunctioning or mistakes. Machine functions should be continuously monitored and alarm / warning indications through lights/ alarm number with messages (on CNC display and panels) should be available.	Vendor to comply			
	2. A detailed list of all alarms / indications provided on machine should be submitted by the supplier.	Vendor to comply			
	3. All the pipes, cables etc. on the machine should be well supported and protected.	Vendor to comply			
	4. All the rotating parts used on machine should be statically & dynamically balanced to avoid undue vibrations.	Vendor to comply			
	5. Emergency Switches at suitable locations as per International Norms are to be provided.	Vendor to comply			
	6. Oil & water pipe lines should not run with electrical cable in the same tray / trench.	Vendor to comply			
	7. Safety Lights at both ends of moving column (preferably Flashing during X-travel).	Vendor to comply			

SNO	DESCRIPTION FOR BHEL REQUIREMENT	CONFIRMED BY	OFFERED	DEVIATIONS	REMARKS
2.19	ENVIRONMENTAL PERFORMANCE OF THE MACHINE :				
	The Machine shall conform to following factors related to environment :	Vendor to comply			
	(a) Maximum noise level shall be 85 dB(A) at normal load condition, 1 M away from the machine with correction factor for back ground noise, if necessary. This will be measured as per international standards like DIN 45635-16. Supplier to demonstrate compliance to noise level, if so required.	Vendor to comply			
	(b) There shall not be any emissions from the machine except fumes of cutting fluid during machining.	Vendor to comply			
	(c) There should not be any effluent from the machine. In case there are any effluents from the machine, requisite effluent treatment plant or pollution control device should be built into the machine by the supplier.	Vendor to comply			
	(d) No hazardous chemicals shall be required to be used in the machine.	Vendor to comply			
	(e) If any safety / environmental protection enclosure is required it should be built in the machine by the vendor.	Vendor to comply			
	(f) Paint of the machine should be oil / coolant resistant and should not peel off and mix up with coolant.	Vendor to comply			
3.0	CHIP CONVEYOR :				
3.1	A chip conveyor to carry both short and curly chips efficiently and effectively to the chip bin to be provided on one end of the machine . Two Chips bins of appropriate size of Indian make, with wheels & handle for movement, should also be supplied.	Vendor to confirm			
3.2	Type of chip conveyor	Slat type Vendor to confirm			
3.3	Width of conveyor	Vendor to inform			
3.4	Elevation of chip conveyor for chip bin	Vendor to inform			
3.5	Material of chip conveyor (to be rust resistant)	Vendor to inform			
3.6	Provision for smooth flow of chips to the conveyor.	Vendor to inform			
3.7	Operation of chip conveyor (forward & reverse) through push buttons on operator's panel and at Chip Conveyor	Vendor to inform			
3.8	Layout showing location of chip conveyor to be submitted.	Vendor to inform			
4.0	SERVO VOLTAGE STABILIZER:				
4.1	Indian make Oil/ Air Cooled servo Controlled Voltage Stabilizer suitable for complete machine, its drives, controls, PLC etc. with no undesirable Harmonics in the stabiliser output.	Vendor to offer with details			
4.2	Make	NEEL, Aplab or Auto Electric			
4.3	Model & Rating	Vendor to specify			
4.4	Spares Package for the Voltage Stabiliser for 2 years trouble free working should also be offered with item wise list ss under 1. Control Cards, 01Set. 2. Monitoring PCB, 01 No. 3. Control motor, 01 No. 4. Carbon Brushes, 01 set	Vendor to confirm			
4.5	Catalogue of the Voltage Stabiliser shall be submitted with the offer.	Vendor to submit			
5.0	ULTRA ISOLATION TRANSFORMER				
5.1	Indian make Ultra Isolation Transformer suitable for complete machine , its drives, controls, PLC etc. shall be offered with complete details.	Vendor to offer			
5.2	Make	NEEL, Aplab or Auto Electric			
5.3	Model and Rating	Vendor to specify			
5.4	Catalogue of the Isolation Transformer shall be submitted with the offer.	Vendor to submit			

SNO	DESCRIPTION FOR BHEL REQUIREMENT	CONFIRMED BY	OFFERED	DEVIATIONS	REMARKS
6.0	PNEUMATIC SYSTEM:				
6.1	AIR COMPRESSOR:				
6.1.1	Independent Air Compressor (of reputed Indian make Elgi, Chicago Pneumatic or Ingersol Rand) with refrigerated type Dryer & Filter of suitable capacity for the total compressed air requirements of the machine & accessories and to suit required air quality should be supplied. The system should be so designed to have additional provision and required accessories before Refrigerated type Air Dryer so that BHEL compressed air supply having pressure 5 Kg/sq.cm with high moisture could be used as and when required. The compressor unit should be suitable for continuous duty operation.	Vendor to offer with details.			
6.1.2	Make & Model of Air Compressor and Refrigerator type Dryer.	Vendor to specify			
6.1.3	Capacity (Flow, Pressure & KW)	Vendor to specify			
6.1.4	Spares Package for the compressor for 2 years trouble free working should also be offered as under 1. Air Filter element, 6 nos. 2. Oil filter, 15 nos. 3. Air oil separator, 6 nos. 4. Flexible hose pack kit, 1 set 5. Oil, 50 litres 6. Belts, 04 Nos.	Vendor to confirm			
6.2	COMPRESSED AIR POINTS:				
6.2.1	Compressed Air Point with manual ON/ OFF Valve and flexible pipe of suitable length for work piece cleaning.	Vendor to offer			
7.0	TOOLINGS:				
7.1	Complete Description of offered Tooling System	Vendor to offer			
7.2	All cutting tools, tool holders, arbors, boring bars, clamping elements etc., recommended for machining of proveout component shall be offered by the vendor. Consummables for offered Tools, like inserts,screws etc., should be quoted for machining of 2 more components in addition to the prove-out component.	Vendor to offer			
7.3	Vendor shall be responsible, financially or otherwise, for any deviation/ rejection in proveout component due to wrong machining or malfunctioning of the machine during proveout machining and also for the delay in machining due to improper recommended tooling etc..	Vendor to comply			
8.0	MEASURING SYSTEMS:				
8.1	Automatic job measuring system with measuring cycles, calibration system and all types of probes / styli required for measuring dimensions of the prove-out components. Vendor to furnish detailed description of the system along with offer. The measurement system shall be customised so that the measured result file shall be generated in the CNC System only and shall contain all relevant information such as nominal values, measured values, tolerances along with project details of measured component as per sample format at Annexure-I. Further , all the measurements done on the component shall appear in a single file in the above sample format. The selected probing results output file shall be printable from the CNC screen of the machine on a printer through a single key command/soft Key. All necessary hardware & software including Printer, all types of cables, communication software, CNC features required for above mentioned setup shall be provided by the party.	Vendor to offer with details.			
8.1.1	Spares Package for the Measuring system for 2 years trouble free working should also be offered as under.The spares should include Tool Probes, Interface Unit & Special Tips if any. 1. Renishaw probes, 01 set 2. Electronic Control Unit,01 set	Vendor to offer			

SNO	DESCRIPTION FOR BHEL REQUIREMENT	CONFIRMED BY	OFFERED	DEVIATIONS	REMARKS
8.2	Automatic Tool Offset measuring system with measuring cycles, calibration system etc suitable for all types of tools recommended for prove-out components. The system shall be capable of measuring tool length ,tool radius and loading these values into tool offset memory of the machine. The system shall be such that the measurement should be with an accuracy of 10 microns or less. In addition, the system shall be capable of monitoring of runout of tools.Vendor to furnish detailed description of the system along with offer.	Vendor to offer with details.			
8.2.1	Spares Package for the Automatic Tool Offset Measuring system for 2 years trouble free working should also be offered as under. 1. Complete BLUM Laser System unit , 01 set	Vendor to offer			
9.0	DIAGNOSTIC SYSTEM:				
9.1	FAULT DIAGNOSTIC SYSTEM:				
9.1.1	Supplier's own diagnostic system with required Software and Hardware installed on the CNC system, which shows detailed cause and remedy for the fault on the CNC system display with full video diagnostics indicating the element /device causing the fault. Vendor should also offer a PC note book along with Simatic S7 software (licensed copy), necessary cables, PCMCIA card / Adaptor (for Communication with MPI port) for diagnostic purpose. The Note Book PC should be loaded with complete Electrical Schemes, Mechanical Assembly drawings, Hydraulic Circuit Diagrams, Operation and Maintenance Manuals, Machine Alarm list along with Help text wiring diagram, On-Line display of PLC user should be available on the note book PC.	Vendor to offer & submit			
9.1.2	Provision of OEM Screen with soft keys enabling the service personnel to bring back the tool carriers of the ATC/AAC to its initial/nearest position in case of interruption of tool carrier's positioning cycle due to alarm on the machine or power failure. With this OEM screen, service personnel should be able to perform individual steps of Tool carriers positioning cycle manually. Separate Hand Held Pendant should also be provided to retrieve the tool carrier to it's initial position.	Vendor to offer			
9.1.3	Machine should have provision to switchover from position feedback system -2 (direct) to Position feed back system-1 (Motor encoder) through PLC program (for service personnel only).	Vendor to offer			
9.1.4	Help guide should be provided to use both diagnostic systems shall be provided.	Vendor to confirm			
10.0	LEVELING & ANCHORING SYSTEM	Required.			
10.1	Complete anchoring system including foundation bolts, anchoring materials, fixators, leveling shoes etc shall be supplied for the Machine including Floor Plates and Rotary Table.	Vendor to offer and submit details.			
11.0	TOOLS FOR ERECTION, OPERATION & MAINTENANCE :				
11.1	Special tools and equipment required for erection of the machine shall be brought by the vendor. Necessary tools like Torque Wrench, Spanners, Keys, grease guns etc.for operation and maintenance of the machine should be supplied. List of such tools should be submitted with offer	Vendor to offer			
11.2	Test mandrel for checking spindle run-out & alignment should be supplied	Vendor to offer			
12.0	ACCESSORIES:				
12.1	AUTOMATIC TOOL CHANGER & TOOL MAGAZINE :				
12.1.1	Type	Vendor to specify			
12.1.2	No. of storage locations	40 or more			
12.1.3	Tool shank	BT50			
12.1.4	Max tool diameter (all pockets filled)	140mm or more			
12.1.5	Max tool diameter (adjacent pockets empty)	Vendor to specify			
12.1.6	Max tool length	500mm			
12.1.7	Tool change time (tool-to-tool)	Vendor to specify			
12.1.8	Tool change time (chip-to-chip)	Vendor to specify			
12.1.9	Tool selection method: Random with shortest path	Vendor to confirm			
12.1.10	The machine shall have manual Tool loading/ unloading through push button provided on machine head stock/ Auxilliary Hand pendant.	Vendor to confirm			

SNO	DESCRIPTION FOR BHEL REQUIREMENT	CONFIRMED BY	OFFERED	DEVIATIONS	REMARKS
12.1.11	The spindle taper and tool pocket at changer station will have the provision of cleaning by compressed air blow during ATC cycle. The spindle taper will also have the provision of compressed air blow through push button provided on machine head stock/ Auxilliary Hand pendant during manual tool change.	Vendor to confirm			
12.1.12	Auxiliary Control, with suitable interlocks, for manual insertion / withdrawal of tool from the tool magazine.	Vendor to confirm			
12.1.13	Suitable arrangement, Software based customised screens and manual key based, should be provided to extract a tool trapped in the ATC cycle. Details of both the system to be provided along with the offer.	Vendor to submit			
12.1.14	Tool changing position should be at a convenient height from floor, which will be mutually agreed, so that it remains at an approachable position in order to work manually in case of emergency.	Vendor to confirm			
12.1.15	Maximum Tool Overhang out of different Holders.	Vendor to specify			
12.1.16	Maximum Permissible Weight on each Pocket. (It should not be less than 35 Kg.)	Vendor to specify			
12.1.17	Maximum Permissible Weight on Complete ATC.	Vendor to specify			
12.1.18	The Machine operation should be possible with or without referencing ATC.	Vendor to confirm			
12.1.19	One set of tool holder retention stud equal to Tool Magazine capacity shall be provided as standard item with the machine. Drawing of Pull Stud should also be supplied.	Vendor to confirm & submit			
12.1.20	Tool Changer arm working should be explained in details. Full ATC catalogue should be submitted with the offer.	Vendor to confirm & submit			
12.2	AUTOMATIC ATTACHMENT CHANGER (AAC):				
12.2.1	All attachments shall be suitable for loading / unloading through AAC	Vendor to offer			
12.2.2	No. of storage positions	Vendor to inform			
12.2.3	Location of the attachment changer	On RHS of X-Traverse.			
12.2.4	Mounting plates as required for attachments should be supplied	Vendor to offer and submit			
12.2.5	Maximum Permissible Weight on each Position.	Vendor to offer and submit			
12.2.6	Maximum Permissible Weight on Complete AAC.	Vendor to offer and submit			
12.2.7	Additional Longitudinal Traverse of X-axis required to accommodate and use of AAC beyond the specified X-axis traverse shall be separately offered by the vendor.	Vendor to offer and submit			
12.2.8	Suitable Software based and manual key based arrangement should be provided to extract an Attachment trapped in the AAC cycle. Details of both the system to be provided along with the offer.	Vendor to offer and submit			
12.3	ATTACHMENTS FOR :				
12.3.1	PROGRAMMABLE UNIVERSAL MILLING HEAD:				
12.3.1.1	Power	40 KW or more			
12.3.1.2	Max torque	Vendor to inform			
12.3.1.3	Speed Range	Vendor to inform			
12.3.1.4	Speed ratio	Same as spindle			
12.3.1.5	Spindle taper	BT50			
12.3.1.6	Traverse Range of A-axis in deg.	(+/-) 95			
12.3.1.7	Resolution of A-axis	0.001 deg.			
12.3.1.8	Rotation of C-axis (Any number of rotation)	360 deg			
12.3.1.9	Resolution of C-axis	0.001 deg.			
12.3.1.10	Torque-Power-Speed characteristic diagram to be submitted.	Vendor to submit			
12.3.1.11	Weight of the head	Vendor to inform			
12.3.1.12	Coolant system: Internal (thru spindle) & External coolant with requisite flexible pipes on its snout is to be provided.	Vendor to offer.			
12.3.1.13	Pull Stud for mounting the Head and for mounting the Tools in the taper of the Head shall be supplied by the vendor.	Vendor to offer.			
12.3.2	CNC ANGULAR HEAD/RIGHT ANGLE MILLING HEAD:				
12.3.2.1	Power	40 KW (or more)			
12.3.2.2	Max torque	Vendor to inform			

SNO	DESCRIPTION FOR BHEL REQUIREMENT	CONFIRMED BY	OFFERED	DEVIATIONS	REMARKS
12.3.2.3	Speed Range (Infinitely Variable)	1-2000rpm or more			
12.3.2.4	Speed ratio (1:1 between spindles of Machine and Head)	Vendor to confirm			
12.3.2.5	Spindle taper	BT50			
12.3.2.6	Traverse Range of C-axis	360 deg.			
12.3.2.7	Resolution of C-axis	1 deg.			
12.3.2.8	Power-Torque-Speed characteristic diagram to be submitted	Vendor to submit			
12.3.2.9	Wt. of the head	Vendor to inform			
12.3.2.10	Coolant system: Internal (thru spindle) & External coolant with requisite flexible pipes on its snout is to be provided.	Vendor to confirm			
12.3.2.11	Pull Stud for mounting the Head and for mounting the Tools in the taper of the Head shall be supplied by the vendor.	Vendor to offer and submit			
13.0	SPARES:				
13.1	Itemwise breakup of mechanical, hydraulic, electrical and electronic spares used on the machine in sufficient quantity as per recommendation of Vendor for 2 years of trouble free operation on three shifts continuous running basis should be offered by vendor. The list to include following, in addition to other recommended spares: (Unit Price of each item of spare should be offered)	Vendor to confirm			
13.1.1	Mechanical & Hydraulic Spares: The following spares are to be included.				
13.1.1.1	Pumps used on machine i.e Hydraulic / Hydrostatic, lubrication, coolant and oil cooling - recirculating system (1 no. each type).	Vendor to offer			
13.1.1.2	Pressure control valves, Pressure reducing valves, Flow control valves & Direction control valves used in Hyd / Lub / Pneumatic/ coolant circuit. (1 no. of each type)	Vendor to offer			
13.1.1.3	Pressure switches, flow switches used in Hyd / Lub / Pneumatic/ coolant circuit. (1 No. of each type)	Vendor to offer			
13.1.1.4	All types of regenerative type filter inserts (10 No. of each type)	Vendor to offer			
13.1.1.5	All types of Disposable type filter inserts (30 nos. of each type)	Vendor to offer			
13.1.1.6	All types of Accumulators with charging kit (1 no. of each type)	Vendor to offer			
13.1.1.7	One set of belts (including timing belt) used in the machine.	Vendor to offer			
13.1.1.8	One set of seal kits used in different hydraulic & pneumatic cylinders in the machine.	Vendor to offer			
13.1.1.9	One set of hose pipe with end connection used in the machine.	Vendor to offer			
13.1.1.10	All types of couplings used with different pumps (1 no. of each type) & pressure sleeves used in machine.	Vendor to offer			
13.1.1.11	All types of shaft seals (2 no. of each type), O-rings & Piston Rings (5 nos. of each type) used in the	Vendor to offer			
13.1.1.12	One set of pneumatic filtration / condensate drain system.	Vendor to offer			
13.1.2	Electrical /Electronic / CNC Spares : Following Spares are to be offered.	Vendor to offer			
13.1.2.1	Limit Switches/ Micro Switches (2 Nos each type)	Vendor to offer			
13.1.2.2	Relays (2 Nos each type)	Vendor to offer			
13.1.2.3	Contactors (2 Nos each type)	Vendor to offer			
13.1.2.4	RTD temperature transmitter (1 No each type)	Vendor to offer			
13.1.2.5	Proximity Switches (5 Nos each type)	Vendor to offer			
13.1.2.6	Push Buttons (5 Nos each type)	Vendor to offer			
13.1.2.7	Indicating Lamps (10 Nos each type)	Vendor to offer			
13.1.2.8	Semiconductor Fuses (5 Nos each type)	Vendor to offer			
13.1.2.9	Special Fuses (5 Nos each type)	Vendor to offer			
13.1.2.10	Circuit Breakers (1 No each type)	Vendor to offer			
13.1.2.11	Main Power Switch (1 No each type)	Vendor to offer			

SNO	DESCRIPTION FOR BHEL REQUIREMENT	CONFIRMED BY	OFFERED	DEVIATIONS	REMARKS
13.1.2.12	Encoders (1 No each type)	Vendor to offer			
13.1.2.13	Scanning Heads for Linear Scales (1 No each type)	Vendor to offer			
13.1.2.14	Wave shape unit/ EXE unit (1 No each type)	Vendor to offer			
13.1.2.15	PCU module (Hard disk loaded with Ghost of the machine after final commissioning)	Vendor to offer			
13.1.2.16	NCU module	Vendor to offer			
13.1.2.17	Operator's panel with Display Unit	Vendor to offer			
13.1.2.18	I/O Cards for PLC (1 No each type)	Vendor to offer			
13.1.2.19	Servo Motors for Feed Drives (1 No each type)	Vendor to offer			
13.1.2.20	Power Module & Control Cards for Main Drive as well as Feed Drives (1 Nos each type)	Vendor to offer			
13.1.2.21	One each of the following items : CNC Power Supply, I/R Module, NCU BOX, Machine Control Panel, Hand Held Unit/ B-MPI, Any other auxiliary drive , if used, Complete Proportional Valve Controller, if used.	Vendor to offer			
13.2	All types of spares for total machine and accessories should be available for atleast ten years after supply of the machine. If machine or control is likely to become obsolete in this period, the vendor should inform BHEL sufficiently in advance and provide drawings of parts / details of spares & suppliers to enable BHEL to procure these in advance, if required.	Vendor to offer			
13.3	Recommended set of spares for all attachments, viz.; Angular Milling Head, and Boring Heads are to be offered with details. The spares are to include Motors, Set of Gears, Encoders, Limit/ Cam Switch Connectors with item wise details.	Vendor to offer			
13.4	Recommended set of spares for Job and Tool Measuring Systems are to be offered with details.	Vendor to offer			
13.5	Vendor to confirm that complete list of spares for machine and accessories, along with specification/ type/ model, and name & address of the spare supplier shall be furnished along with documentation to be supplied with the machine.	Vendor to confirm			
14.0	DOCUMENTATION : Three sets of following documents (Hard copies with Soft Copies wherever specified) in English language should be supplied along with the machine	Vendor to offer			
14.1	Operating manuals of Machine & CNC system	Vendor to offer			
14.2	Programming Manuals of Machine & CNC system	Vendor to offer			
14.3	Detailed Maintenance manual of machine and supplied systems.	Vendor to offer			
14.4	Maintenance, Interface & commissioning manuals, PLC programming manual for CNC system, Interface & commissioning manuals for spindle ,feed drives and auxiliary drive.	Vendor to offer			
14.5	Manufacturing drawings for all supplied clamping elements, cutting tools, tool holders, arbors, boring bars, coolant connections, adapters, sleeves, fixtures etc.	Vendor to offer			
14.6	Catalogues, Operation & Maintenance Manuals of all bought out items including drawings, wherever applicable.	Vendor to offer			
14.7	Detailed specification of all rubber items and hydraulic/lube fittings	Vendor to offer			
14.8	Operating Manuals, Maintenance Manuals & Catalogues for supplied accessories viz. Voltage Stabilizer,	Vendor to offer			
14.9	User Program print-outs (hard copy) with comments in English for PLC of main machine and auxiliary systems (if used) alongwith cross reference list and Input/Output list.	Vendor to offer			
14.1	PLC program, NC data & PLC data on CD.	Vendor to offer			
14.1	Complete back-up of PCU-50 or equivalent (in case of Fanuc) hard disk on GHOST CD and clearly written Instructions to take back-up and reloading on a new hard disk.	Vendor to offer			
14.1	Complete list of parts/items(Bill of materials) used in the machine in English language.	Vendor to offer			
14.1	Electrical Schematic Diagrams, Wiring Diagrams, Junction Box Layouts, Connector Diagrams and Cable Layouts of the machine in English.	Vendor to offer			

SNO	DESCRIPTION FOR BHEL REQUIREMENT	CONFIRMED BY	OFFERED	DEVIATIONS	REMARKS
14.1	Drawings of machine assemblies/sub-assemblies/parts including Pneumatic/ Coolant / Hydraulic circuit diagrams. All Assembly/ Sub Assembly Drawings shall be supplied with the part list marked on it in English.	Vendor to offer			
14.2	One additional set of all the above documentation on CD ROM, wherever possible.	Vendor to offer			
15.0	TRAINING:				
15.1	Four BHEL Persons should be trained at vendor's works for each machine for the area & period given below: (a) CNC Part Programming for the machine, application of all CNC Features, Programming for Measuring Systems & supplied accessories etc. (Period 3 Weeks) (b) Electrical, Electronic & CNC maintenance for machine & other supplied equipments (Period 2 weeks) (c) Mechanical & Hydraulic maintenance of the machine & other supplied equipments (Period 2 weeks) (d) Operation of the machine & other supplied equipments (Period 2 weeks) Pre-dispatch inspection (ref. SI.No. 22.1) of the machine shall also be carried out by the team during their stay at vendor's works for the training. Vendor may specify days required for pre-dispatch inspection. BHEL reserves the right to choose no. of persons, field & period of training, out of above, while deputing their engineers for training.	Vendor to offer			
15.2	Air-fare, boarding & lodging for the trainees shall be borne by BHEL.	Vendor to confirm			
15.3	Competent, English speaking experts shall be arranged by the vendor during training for satisfactory & effective training of BHEL personnel.	Vendor to confirm			
15.4	Vendor to quote for training on per man week basis	Vendor to quote			
15.5	Vendor should commit to organize and quote for training of Electronics Engineer and Programmer at the CNC System Manufacturer's works for advanced features and specialised training if so required by BHEL.	Vendor to confirm			
16.0	FOUNDATION:				
16.1	Vendor shall submit the layout drawing showing layout of the machine and load points within two month from the date of Letter of Intent (LOI)/ P.O., whichever is earlier indicating details like Static/ Dynamic load details etc. and final Layout Drawings shall be submitted by the supplier within three The Layout should consist of all requirements pertaining to complete machine and all accessories, including space requirement for Voltage Stabiliser, Isolation Transformer, Air Compressor, Chip Bin & any other accessory. Layout should also show size of Pit in which whole machine alongwith Floor Plate to be installed below ground level. Vendor to supply layout of machine showing size and depth of pit. Foundation of the machine shall be designed by BHEL and to be concurred by the vendor. BHEL shall construct complete foundation for the machine under supervision of supplier and at supplier's responsibility. Vendor should arrange equipment required for the testing of foundation, if required by the vendor. The vendor shall also indicate detailed specifications of grouting compound and grouting procedure etc. for grouting of foundation bolts of the machine	Vendor to confirm			
17.0	ERECTION & COMMISSIONING				
17.1	Supplier to take full responsibility for carrying out the erection, start up, testing of machine, it's control system & all types of other supplied equipment, machining of test pieces etc. Service requirement like power, air & water shall be provided by BHEL at only one point to be indicated by supplier in their foundation/layout drawings. Other requirements like crane and helping personnel shall also be provided by BHEL. Details of these requirements should be informed by vendor in advance. The available crane capacity at the proposed location of the machine will be Ton. The vendor will ensure to make requisite arrangement for lifting of heavier consignment/ items/ assembly of the machine not getting covered by this capacity.	Vendor to confirm			

SNO	DESCRIPTION FOR BHEL REQUIREMENT	CONFIRMED BY	OFFERED	DEVIATIONS	REMARKS
17.2	Erection & Commissioning of Voltage stabilizer, Isolation Transformer & Air Compressor shall also be responsibility of the vendor.	Vendor toffer and submit details			
17.3	Successful proving of BHEL components by the supplier shall be considered as part of commissioning. All tests, as mentioned at clause 21 (Machine Acceptance) shall form part of the commissioning activity.	Vendor toffer and submit details			
17.4	Test mandrel for checking run-out/taper & alignment should be supplied	Vendor toffer and submit details			
17.5	Tools, Tackles, Test Mandrels, instruments and other necessary equipment including Laser equipment required to carry out all above activities should be brought by the supplier.	Vendor toffer and submit details			
17.6	Commissioning spares, required for commissioning of the machine within stipulated time, shall be brought by the supplier on returnable basis.	Vendor toffer and submit details			
17.7	All Cover Plates required for the machine and its peripherals including pits, if any, shall be supplied and installed by the vendor.	Vendor toffer and submit details			
17.8	Portion, if any, of the machine, accessories and other supplied items where paint has rubbed off or peeled during transit or erection should be repainted and merged with the original surrounding paint by the vendor.	Vendor toffer and submit details			
17.9	Schedule of Erection and Commissioning shall be submitted with the offer.	Vendor toffer and submit details			
17.10	Charges, duration, terms & conditions for E&C should be furnished in detail separately by vendor along with offer.	Vendor toffer and submit details			
17.11	The vendor shall supply sufficient quantity of paint of the machine and carry out touching wherever the paint is damaged during transit or erection of the machine.	Vendor to confirm			
17.12	BHEL will provide one no. EOT of 50 Tonnes capacity, for the erection of the machine . Any additional Crane (Mobile), if required for the erection of the machine shall be arranged by the vendor on returnable basis. Any high rise Lift require for the erection of the machine shall also be arranged by the vendor on returnable basis.	Vendor to confirm			
18.0	ACCURACY TESTS:				
18.1	GEOMETRICAL ACCURACIES :				
18.1.1	Geometrical Accuracy Tests shall be in accordance with ISO 3070 standard or equivalent applicable standard. Detailed Test Charts for the same, clearly showing the accuracies to be achieved on the machine, shall also be submitted with the offer.	Vendor to offer and submit details			
18.1.2	All the above accuracies to be demonstrated to BHEL engineers during pre-acceptance tests at Suppliers works and during Erection & Commissioning at BHEL Works.	vendor to demonstrate			
18.2	MACHINE POSITIONING ACCURACIES & REPEATABILITY: Should be measured as per VDI/DGQ 3441 (Latest Revision) using LASER INTERFEROMETER.				
18.2.1	Positioning uncertainty (Pa per 1000mm) for X,Y,Z,W axes	0.015 mm			
18.2.2	Positional scatter (Ps per 1000mm) for X,Y,Z axes=	0.008 mm			
	Positional scatter (Ps per 1000mm) for W axes=	0.012 mm			
18.2.5	Total positioning error P for entire travel for X,Y,Z,W & V axes	Vendor to specify			
18.2.7	All the above accuracies to be demonstrated to BHEL engineers during pre-acceptance at Suppliers works and during Erection & Commissioning at BHEL Works.	Vendor to confirm			
19.0	OPERATING CONDITIONS & THERMAL STABILITY :				
19.1	Power Supply (AC): Voltage = 415V +10% / -10% of fluctuations , Frequency= 50Hz +3 / -3 , No. of phases = 3 phase with neutral. Ambient Operating Conditions: Temperature = 5 to 45 degree Celsius , Relative Humidity = 95% max.	Vendor to accept & confirm			

SNO	DESCRIPTION FOR BHEL REQUIREMENT	CONFIRMED BY	OFFERED	DEVIATIONS	REMARKS
19.2	Weather conditions are tropical, Atmosphere may be dust laden during some part of the year. Machine shall be kept in the normal shop floor condition. Max. temperature variation is up to 20 deg Celsius in 24 hours. (Vendor to confirm that machine is suitable for above and details of provisions on the machine for the same are to be furnished by Vendor)	Vendor to accept & confirm			
19.2	Thermal Stability of the complete machine keeping in view specified Ambient Conditions and accuracy requirements of BHEL components and trouble free operation of the machine should be ensured by vendor. (Vendor to confirm that machine is suitable for above and details of provisions on the machine for the same should be furnished by Vendor)	Vendor to accept & confirm			
19.3	The machine, including attachments and accessories, should be suitable for 24 hrs. continuous operation to its full capacity for 24 hour a day and 7 days a week throughout. Vendor to ensure and confirm the same.	Vendor to accept & confirm			
20.0	PROVEOUT OF BHEL COMPONENTS :				
20.1	"Front Water Box (L.S.)" Drawing No. 0-160-31-70039 of 500 MW will be likely proveout component. <i>Job setting plan, Machining process plan & Requirement of Tools etc. for machining of proveout components shall be discussed and mutually agreed with vendor (Final proveout component drawing no. may change, however, the machining features of the changed components shall be in line with the original component drawing).</i> Complete machining of prove out components shall be done by Vendor at BHEL works to the specified design accuracy and surface finish, using cutting tools and CNC programs to be provided by the vendor to prove the machine after complete erection, tests & test piece machining etc. Material for the proveout components shall be provided by BHEL. <i>Vendor shall submit final job setting plan, machining process plan, tool layout & list with complete description, time study etc. for the proveout machining within two months of placement of order.</i>	Vendor to accept and offer.			
20.2	Vendor shall submit CNC programs prior to start of erection of Machine at BHEL works. Vendor shall be fully responsible for machining of proveout components as per drawing and other requirements specified by BHEL to the full satisfaction of BHEL. Clarifications, if any required by vendor, regarding accuracy requirements of the proveout components, whether specified or not, should be discussed and cleared by vendor during initial technical discussions.	Vendor to confirm			
20.3	During proveout, all tools should be preset by using supplied Tool offset Measuring System and measurement of machined dimensions of the job shall be done by supplied Job Measuring System. Vendor shall be responsible, financially or otherwise, for any deviation/ rejection in proveout component to the extent of cost of Casting/Forging, due to wrong machining or malfunctioning of the machine during proveout machining and also for the delay in machining due to improper recommended tooling etc..The cost of such deviation / rejection, if any, shall be refunded by the vendor to BHEL.	Vendor to confirm			
21.0	MACHINE ACCEPTANCE: (Tests/Activities TO be Performed by Vendor)	Should be accepted & confirmed by Vendor			
21.1	Tests/Activities should be carried out at supplier's works on the machine before dispatch :				
21.1.1	Geometrical Accuracy Tests as per test chart.	Vendor to offer and submit details			
21.1.2	Positioning Accuracy Tests as per VDI-DGQ/3441	Vendor to offer and submit details			
21.1.3	The machine should be tested for continuous running of 48 hrs. If any break down occurs during this test, the test should be repeated for 48 hrs from that time.	Vendor to offer and submit details			
21.1.4	Demonstration of all features of the machine, CNC system and all Accessories.	Vendor to offer and submit details			
21.1.5	Machining of NAS Test Piece . Vendor to supply test piece and tooling for it's machining.	Vendor to offer and submit details			
21.2	Test to be carried out at BHEL works while commissioning the machine :				

SNO	DESCRIPTION FOR BHEL REQUIREMENT	CONFIRMED BY	OFFERED	DEVIATIONS	REMARKS
21.2.1	Geometrical Accuracy Tests as per test chart.	Vendor to offer and submit details			
21.2.2	Positioning Accuracy Tests as per VDI-DGQ/3441	Vendor to offer and submit details			
21.2.3	Full load test to demonstrate the maximum power & cutting capacity of the machine.	Vendor to offer and submit details			
21.2.4	The machine should be tested for continuous running of 48 hrs. If any break down occurs during this test, the test should be repeated for 48 hrs from that time.	Vendor to offer and submit details			
21.2.5	Demonstration of all features of the machine, CNC system & all accessories to the satisfaction of BHEL for their efficient and effective use.	Vendor to offer and submit details			
21.2.6	Demonstration by actual use of all supplied attachments and accessories to their full capacity.	Vendor to offer and submit details			
21.2.7	Machining of NAS Test Piece . Vendor to supply test piece and tooling for it's machining.	Vendor to offer and submit details			
21.2.8	Job prove out.	Vendor to offer and submit details			
21.2.9	Two weeks supervision of independent operation of machine by BHEL after job proveout.	Vendor to offer and submit details			
21.2.10	Training of BHEL machine operators in operation of complete machine & accessories etc by the supplier's experts / engineers during their stay at BHEL works	Vendor to offer and submit details			
22.0	PACKING:				
22.1	Sea worthy & rigid packing for all items of complete machine, CNC System, all Accessories and other supplied items to avoid any damage/loss in transit. When machine is despatched in containers, all small loose items shall be suitably packed in boxes	Vendor to confirm			
23.0	GUARANTEE :				
23.1	24 months from the date of acceptance of the machine.	Vendor to confirm			
24.0	GENERAL : The vendor should submit the following information:				
24.1	Machine Model	Vendor to inform			
24.2	Total connected load (KVA):	Vendor to inform			
24.3	Floor area required (Length, Width, Height) for complete machine & accessories. The Layout of the machine may be planned so that the Rotary Table shall be at the Left Hand side of the X-Traverse while looking from the Spindle.	Vendor to inform			
24.4	Painting of Machine/ Electrical Panels: RAL 6011 Apple Green (Polyurethane Paint)	Vendor to inform			
24.5	Total weight of the machine	Vendor to inform			
24.6	Weight of heaviest part of machine	Vendor to inform			
24.7	Weight of the heaviest assembly/ subassembly of the Machine	Vendor to inform			
24.8	Dimensions of largest part/ subassembly/ assembly of the machine	Vendor to inform			
24.9	Vendor to submit, along with offer, the reference list of customers where similar machines have been supplied mentioning the customer, Machine Model, major specifications of the supplied machine, CNC System, Year of Supply etc.	Vendor to submit			
24.10	Detailed catalogues , sketch/ photographs of the m/c and accessories/ attachments should be submitted with the offer.	Vendor to submit			
24.11	Hydraulic, Pneumatic & oil pipings should be preferably metallic except places where flexible pipings are essential.All the pipes required for the same shall be included in the standard scope of the machine.	Vendor to submit			
24.12	Ladder is to be provided to access the machine elements located at the top of the column.	Vendor to offer & confirm			
25.0	QUALIFYING CONDITIONS :				
25.1	Only those vendors (OEMs) should quote who have supplied and commissioned at least one number CNC	Vendor to accept & confirm			

SNO	DESCRIPTION FOR BHEL REQUIREMENT	CONFIRMED BY	OFFERED	DEVIATIONS	REMARKS
	HORIZONTAL BORING MACHINE of (Spindle Diameter 160 mm, Ram+Spindle Traverse: 1500 mm) or higher sizes, for similar applications in the past ten years (on the date of opening of Tender) other than the Country of Origin or in India and referred machine is presently working satisfactorily for more than one year after commissioning (on the date of opening of Tender). The following information is to be submitted by the vendor about the companies where similar machines have been supplied. This is required from all the vendors for qualification of their offer.				
25.2	Name of the customer/ company where referred machine is installed.	Vendor to inform			
25.3	Complete postal address of the customer.	Vendor to inform			
25.4	Month & Year of commissioning.	Vendor to inform			
25.5	Parameters of machine(s) supplied (Spindle Diameter, X- Axis and Y-axis travel, Ram+Spindle Travel with features etc. and application for which the machine is supplied.	Vendor to inform			
25.6	Name and designation of the contact person of the customer.	Vendor to inform			
25.7	Phone, FAX no. and e-mail address of the contact person of the customer.	Vendor to inform			
25.8	Performance certificate from the customers regarding satisfactory performance of machine supplied to them (Original Certificate or Through E-mail directly from the customer). The original performance certificate may be returned after verification by BHEL, if required.	Vendor to submit			
25.9	BHEL reserves the right to verify information submitted by vendor. In case the information is found to be false/incorrect, the offer shall be rejected.	Vendor to accept & confirm			
26.0	OTHER FEATURES:	Vendor to confirm			
26.1	NETWORKING:				
	Machine control should have necessary hardware and software for interfacing with gigabit Ethernet Local Area Network with 100 MB/sec through UTP cables for NC program and other related data transfer. This network to be connected to wide area network/Internet. The networking should have following capabilities.	Vendor to confirm			
	a) The machine shall appear as a node in the Entire Network. (Network Neighborhood)	Vendor to confirm			
	b) The program transfer shall be by simple copy and paste method provided sharing access is allowed between any PC and the machine across the network.	Vendor to confirm			
	c) The program transfer between CNC system and network should also be possible in CNC Mode.	Vendor to confirm			
26.2	MACHINE MONITORING SYSTEM (MMS) SIGNALS				
	Following MMS signals would be made available on a specifically earmarked terminal strip. These MMS signals would be sourced from a SIMATIC S-7 PLC output card separately.				
	a) Control ON	Vendor to offer			
	b) Cycle ON				
	c) Spindle Running				
	d) Feed Active (Any of the axes moving)				
	e) M30 (Program Stop)				
26.3	Cable Trays and Brackets for laying of Cables and Hose Pipes and all types of covers required to cover Cable Trenches and different type of openings are to be supplied by the vendor alongwith the machine.	Vendor to confirm			



<div> <div> <div>5</div><div>16</div><div>55</div><div>40</div><div>40</div><div>20</div><div>12</div><div>20</div><div>20</div><div>20</div><div>12</div><div>12</div><div>12</div><div>10</div><div>10</div><div>10</div><div>10</div><div>8</div><div>8</div> </div> <div>WELD SIZE & SYMBOL</div> </div>																		<div> <div>QMS NO./GR.SP.NO.</div> <div>O-160-31-70039</div> </div> <div> <div>STATUS OF DRG.</div> <div>DATE</div> </div>				<div> <div>TYPE OF PRODUCT</div> <div>4X500MW TALCHER TPP</div> </div> <div> <div>OR</div> <div>NAME OF CUSTOMER/PROJECT</div> </div>			
<div> <div>1.70</div><div>28.26</div><div>0.44</div><div>36.61</div><div>2.15</div><div>14.6</div><div>21.4</div><div>15.6</div><div>17.0</div><div>19.2</div><div>1.70</div><div>18.18</div><div>3.0</div><div>4.10</div><div>0.30</div><div>2.40</div><div>0.15</div><div>14.86</div><div>16.2</div><div>3.30</div> </div> <div>SEAM LENGTH IN M.</div>																		<div> <div>GRADE OF UNTOL DIM. ---</div> <div>M / CG - C / M / E AA 0230208</div> </div> <div> <div>WELDING - A/B/C/D - AA 0621104</div> <div>GAS CUTTING- 'T3' AA 0621101</div> </div>				<div> <div>TYPE OF DEPOSITED METAL</div> <div>WT.</div> </div>			
<div> <div>0.23</div><div>36.73</div><div>10.0</div><div>222.6</div><div>13.5</div><div>64.5</div><div>38.5</div><div>68.3</div><div>43.0</div><div>37.20</div><div>1.20</div><div>13.54</div><div>2.25</div><div>6.50</div><div>0.15</div><div>1.17</div><div>0.16</div><div>8.02</div><div>10.90</div><div>1.11</div> </div> <div>WT. OF DEPOSITED METAL</div>																		<div> <div>TYPE OF ELECTRODE</div> <div>REV.</div><div>DATE</div><div>ALTERED</div><div>CHECKED</div> </div>				<div> <div>REV.</div><div>DATE</div><div>ALTERED</div><div>CHECKED</div> </div>			
<div> <div>E-7018</div> <div>E-7018</div> </div>																		<div> <div>REV.</div><div>DATE</div><div>ALTERED</div><div>CHECKED</div> </div>				<div> <div>REV.</div><div>DATE</div><div>ALTERED</div><div>CHECKED</div> </div>			
<div> <div>ZONE</div> <div>8</div> </div>																		<div> <div>ZONE</div> <div>7</div> </div>				<div> <div>ZONE</div> <div></div> </div>			
<div> <div>DEPT</div><div>HVE</div> <div>CODE</div><div>4222</div> </div>																		<div> <div>SCALE</div><div>1.25</div> <div>WEIGHT (KG)</div><div>2790.00</div> </div>				<div> <div>REF. TO ASSY DRG.</div> <div>ITEM NO.</div><div>NO OF ITEM</div> </div>			
<div> <div>TITLE</div> <div>FRONT WATER BOX (R.S.)</div> </div>																		<div> <div>CARD CODE</div> <div>DRAWING NO.</div><div>O-160-31-70039</div> <div>SHEET NO.</div><div>01</div><div>NO OF SHEETS</div><div></div> </div>				<div> <div>REV.</div> </div>			