

GRI	DATA ACQUISITION PCB CARDS, DATA ACQUISITION COMPUTER AND ACCESSORIES	GRI NO.: GRI/27/07/08-09 DATE : 09.03.2009 PAGE : 1 OF 5
-----	---	--

INDENT NO.: C/T/4100/20089406

DATED: 09.03.2009

DATA ACQUISITION PCB CARDS, DATA ACQUISITION COMPUTER AND ACCESSORIES

I. PCI BUS HIGH PERFORMANCE DATA ACQUISITION PCB CARDS:

These cards are required for PC based data acquisition system on PCI bus. These should comprise of signal-conditioning boards along with software drivers & interfacing cables, connector assembly etc. The cards quoted should be of PCI compatible and of latest generation/ architecture. Other specification requirements are:

Item listed in Annexure-1 for a total requirement of one set.

Number of each of cards required: Indicated against each card

1.1 High Resolution PCI A/D Card

01 Nos.

Specifications:

ANALOG INPUT:

Number of channels	: 32 differential analog inputs (Software selectable) (Although 32 differential input channels in one single card is preferred, but two or more cards making 32 channels will also be considered)
Resolution	: 12 bit preferably 16 bit
Sampling rate for A/D conversion	: 100 KS/s or more
Conversion time	: Less than 10 μ S
Input Signal Ranges	: Unipolar /bipolar from 1.25V to 10 V or better (Selectable) for each channel
Max. Input Over Voltage	: ± 20 V
Over Voltage Protection	: 25V (Pk – Pk)
Data Transfer Modes	: Software and DMA or Interrupts, bus mastering
Accuracy (DC)	: 0.05 % of FS of the selected range or better ± 1 LSB
Linearity error	: ± 1 LSB
Input Impedance	: At least 10M Ω

DIGITAL I/O: Provision of this feature will be preferred (if this facility ,is not available in A/D card, provision of same in relay card or separate digital I/O and shall also be considered)

Number of channels: TTL/CMOS compatible minimum 12 inputs/output

Data transfers: Programmed I/O

TIMING I/O: 32 bit user configurable timer counter (By cascading two 16 bit counters).

TIME Base Clock frequency Min. 1 MHz

TRIGGER FACILITY: Software, Pacer, ext. Trigger modes be available.

Prepared by	D. S. More Mgr. (GRI)	
Checked & Approved by	P. J. BAGAWADE SDGM(GRI)	

GRI	DATA ACQUISITION PCB CARDS, DATA ACQUISITION COMPUTER AND ACCESSORIES	GRI NO.: GRI/27/07/08-09 DATE : 09.03.2009 PAGE : 2 OF 5
-----	---	--

I/O CONNECTOR: Provision of suitable I/O Connectors providing very good noise reduction. Also it is preferable to have BNC connector sockets based analog input terminal board for analog input signals with inter connection between BNC board to DAS board via shielded D-connector. Ribbon cable connector may also be provided for testing of cards etc.

SIGNAL SHIELDING & NIOSE IMMUNITY: In case of driver cards there should be proper protective covers for modules/ sensitive part of circuit/ Connectors to provide signal shielding and noise immunity.

1. 2 D/A OUTPUT CARD

01Nos.

a) This should be card with isolated multi-channel analog output card for PCI bus.

Specifications:

NALOG OUTPUT:

No. of channels	:	Minimum 12 (Although 12 channels or more (upto 32 no. of channels) in one single card is preferred two or more cards making 12 or more channels output will also be considered)
Resolution	:	12 bits or better
Output ranges	:	- 10 V to + 10 V
Current loop (sink)	:	0 – 20 mA or 4– 20 mA
Throughput (speed)	:	15 kHz or better
Settling time	:	less than 1 msec.
Accuracy	:	± 5 LSB or better
Offset error	:	less than ± 4 LSB
Output Impedance	:	Max. 0.15 Ω
Output protection	:	Short to ground
Isolation	:	At least 1000 V DC
Reset	:	Should retain output values on reset

I/O CONNECTOR: Provision of suitable I/O Connectors providing very good noise reduction like shielded D-connector. Ribbon cable connector may also be provided for testing of cards.

1. 3 RELAY OUTPUT CARD :

01 No.

Specifications:

This should be a multichannel relay output board which can be **driven directly from digital output or analog output from above indicated PC cards through compatible connectors**. There should be provision to protect its relay contact points from the surge voltage of inductive loads. Each relay should have LED indication for its on/off status. All output contacts should be accessible through screw terminals.

To avoid overloading of PC power supply the card should have a provision so that driving voltages are jumper selectable to +5V, 12 V or external D.C. Power supply and screw terminal for it.

No. of channels: Minimum 6 relay channels

Prepared by	D. S. More Mgr. (GRI)	
Checked & Approved by	P. J. BAGAWADE SDGM(GRI)	

GRI	DATA ACQUISITION PCB CARDS, DATA ACQUISITION COMPUTER AND ACCESSORIES	GRI NO.: GRI/27/07/08-09 DATE : 09.03.2009 PAGE : 3 OF 5
-----	---	--

Relay :

The relays can be power relays or photo coupler isolated solid state relays.

Relay type : Power relay / Solid state relay with NO/NC output contacts.
Contact rating : AC 250 V , Min. 1A
Turn on/turn off time : Max. 800 msec.
Blocking voltage : Higher than 550 Volts.

If card doesn't include relays installed on it then relays be quoted separately.

1.4 SOFTWARE:

Party should indicate various software driver packages included as basic scope of supply in above cards. In addition following driver software packages if not covered by std. Scope may be quoted separately.

DOS DRIVERS:

Driver S/W for Microsoft BASIC and Quick BASIC, Microsoft C++, Borland/Turbo C++ 4.5, Labview

WINDOWS DRIVER – DLL:

Dynamic Link Library driver for Microsoft Windows and Windows NT of latest versions with Visual Basic, Microsoft C++, Visual C++, Borland C++. Complete source code listing be provided for these driver software packages and demo programs.

OPERATING CONDITIONS :

The cards should be able to perform satisfactorily under following operating environmental conditions.

- | | |
|------------------|-------------|
| a) Ambient Temp. | 0 to 50 ° C |
| b) Humidity | 0 to 90 % |

POWER SUPPLY :

These cards(except relay card) will be installed in PCI slots of the PC motherboard and hence will draw power from PC in-built +5 v and ±12V DC power supply.

II. END USER APPLICATION /OPERATION SOFTWARE :

01 No.

Party to provide customer specific software in WINDOWS VC++ or Labview environment, demonstrating integrated performance of operation of all the above cards in addition to data acquisition, data processing (exact requirement of processing will be provided at the time of software development), data display in tabular and bar graph format), data storage / retrieval (Creating files for data storage/saving & reading data from these files), data printing, Graphical waveform display/plotting(Plotting – Using Deskjet colour printer and Laser printer), for analog signal at overall, 50 Hz 100 Hz frequency generator by suitably sampling of incoming analog signal, simultaneously on all 32 channels, Online data processing to be in both time and frequency mode. Integration of online signal to be in both time and frequency mode. Operation of software should be Window's icon based menus. Data to be stored for each channel for 512 data sets for on-line process. Provision of shiftwise data output related to channelwise max value of data, even records-alarms/warnings during the shift etc. Extensive post processing/ statistical analysis facility. Provision of digital data interface for communicating with central digital data controller/ processor mimic display/animation of generator stator overhang & its vibration.

Prepared by	D. S. More Mgr.. (GRI)	
Checked & Approved by	P. J. BAGAWADE SDGM(GRI)	

GRI	DATA ACQUISITION PCB CARDS, DATA ACQUISITION COMPUTER AND ACCESSORIES	GRI NO.: GRI/27/07/08-09 DATE : 09.03.2009 PAGE : 4 OF 5
-----	---	--

III. PC INTEL PENTIUM-IV FOR DATA ACQUISITION SYSTEM

01 Nos.

The main computers installed at site be suitable to be used as data acquisition system for electrical parameters monitoring in control rooms. The computer should have PCI slots. **The computer should be commercial computer only and not industrial computer. The computer should be of HP make.**
These are broad Spec./ features .However if any other features are required to meet above requirement , may please be quoted.

3.0 **HARDWARE CONFIGURATION: -**

- CPU INTEL PENTIUM-IV PROCESSOR (4 GHZ OR MORE)
- 512KB / 1MB L2 CACHE (INTEL 865 CHIPSET 400/533/800 FSB)
- 1 GB DDR RAM UPGRADABLE
- LOCAL BUS ARCHITECTURE PCI COMPATIBLE
- 1.44 MB 3.5 " FDD
- 160 (OR MORE) GB IDE HDD
- 8X DVD ROM READ / WRITER
- INTEGRATED ONBOARD AC 97 AUDIO
- ON BOARD 10/100 MBPS ETHERNET CONTROLLER CARD
- 56 Kbps INTERNAL PCI MODEM
- AGP (128 MB or MORE) GRAPHICS CARD WITH RESOLUTION 1600 X 1280
- MATCHING -LOW-EMISSION NON-INTERLACED 17" LCD MONITOR
SUITABLE FOR PIXEL RESOLUTION UPTO 1600 X 1280, DISPLAY SHOULD BE STABLE AND FLICKER FREE
- OPTICAL MOUSE
- STANDARD 104/105 KEYS KEYBOARD .
- PCI I/O EXPANSION SLOTS FOR INSTALLING ADD-ON CARDS MENTION NO. AND TYPE OF AVAILABLE EXPANSION SLOTS **minimum 02** PCI slots
- OVER ALL HEIGHT OF PC CABINET SHALL BE NOT MORE THAN 400mm
- RTC WITH BATTERY BACK UP
- LATEST ANTI-VIRUS PROTECTION HARDWARE/ SOFTWARE
- LATEST VERSION A4 SIZE HP LASER COLOUR PRINTER (Quote Type & model No.)
- PORTS 1 PARALLEL,1 SERIAL ,MINIMUM 4 USB PORT (2 FRONT & 2 BACK)

OPERATING CONDITIONS :

The system should be able to perform satisfactorily under following operating environmental conditions.

- a) Ambient Temp. 0 to 50 ° C
- b) Humidity 0 to 90 %

POWER SUPPLY :

It should be operable from Mains of 220 V \pm 20 % at 50 \pm 10 % Hz

3.1 **SOFTWARE - Operating System :**

01 Set

Windows XP with original CD and Hard copy of documentation and compatible for operation with offered PCI cards, viz : A/D cards, D/A cards etc. One set for two PC's

Prepared by	D. S. More Mgr. (GRI)	
Checked & Approved by	P. J. BAGAWADE SDGM(GRI)	

GRI	DATA ACQUISITION PCB CARDS, DATA ACQUISITION COMPUTER AND ACCESSORIES	GRI NO.: GRI/27/07/08-09 DATE : 09.03.2009 PAGE : 5 OF 5
-----	---	--

3.2 ACCESSORIES/ SPARES/ CONSUMABLES :

01 Set

Each set comprising of following -

- 1 KVA UPS (HP/APC MAKE(SMART RS 1000 or equivalent): 02 No.
(UPS should be able to operate under another centralised UPS at power house)
- Spare Printer cartridge for laser colour printer : 01 Set (Black & Colour)
- 1.44 MB (3.5 ") Floppies : 10 Nos.
- Blank CD : 10 Nos.

IV. OTHER REQUIREMENTS FOR PC & CARDS: TEST/CALIBRATION CERTIFICATES :

The party will give test certificate/ detail calibration certificate traceable to national / International standards indicating the validity period and periodicity of calibration recommended for this system.

SPECIAL TESTS :

Party to indicate various tests carried out on cards/PC to ensure its reliability like Burn in test at max. ambient temperatures and humidity conditions indicated in operating conditions above. Test certificates in support of these tests will also be required.

PREDISPATCH INSPECTION AND TRAINING :

Party shall offer the system for pre-dispatch inspection & performance testing and at the same time impart training on various aspects of system

COMMISSIONING : Party will carry out commissioning of the system at BHEL Haridwar.

GUARANTEE/WARRANTEE: The PC/ Cards be guaranteed/warranted for the performance of at least 24 months period from the date of commissioning.

ANNUAL MAINTENANCE CONTRACT : Party should quote for Annual Maintenance Contract charges for period beyond expiry of the guarantee period.

GENERAL:

- Prices should be quoted for individual items separately. However all the items shall be procured from same party only in view of consideration of technical compatibility of these items.
- Other Hardware/ miscellaneous items like connector block and cables/ribbon cables, bus extenders etc. may also be quoted.
- Computer quoted should be of a leading brand. Party should mention make, model no. & send technical details of the computer parts & peripherals like Printer, Graphics Adapter Card, Monitor, Hard Disk Drive etc. which have been quoted. Please also send details of software quoted.
- Party should indicate any other operating/ environmental requirement for safe and trouble-free operation of system and also any specific requirements of the system for continuous operation over prolonged periods as may be required in process monitoring/control applications.
- Five sets (Hard copies and on CDs) of detailed operation/ maintenance manual including circuit diagrams for main system (motherboard, Graphics Adapter Card, Monitor, Hard Disk Controller)& driver cards be supplied.
- Party to write the software and demonstrate the performance of cards for their (i.e. A/D Card, D/A Card and Relay Card) simultaneous operation during pre-dispatch inspection of the system. Party to provide complete source code of the programs.
- Pre-Qualifying Requirement: The equipment offered (mainly PCI –A/D, D/A & Relay cards) shall be of proven design. Party should send reference list of customers (last 5 years) to whom they have supplied such items.

Prepared by	D. S. More Mgr. (GRI)	
Checked & Approved by	P. J. BAGAWADE SDGM(GRI)	

INDENT NO.: C/4100/20089406/T

DATED: 08.03.2009

DATA ACQUISITION PCB CARDS, DATA ACQUISITION COMPUTER AND CESSORIES

LIST OF ITEMS REQUIRED

SL. No.	ITEM DESCRIPTION	QUANTITY
I	PCI BUS HIGH PERFORMANCE DATA ACQUISITION PCB CARDS	
	High Resolution PCI A/D Card ANALOG INPUT: Number of channels : 32 differential analog	01 No.
	D/A OUTPUT CARD	01 No.
	RELAY OUTPUT CARD	01 No.
II	END USER APPLICATION /OPERATION SOFTWARE	01 No.
III	DATA ACQUISITION COMPUTER AND ACCESSORIES	
	PC INTEL PENTIUM-IV FOR DATA ACQUISITION SYSTEM	01No.
	SOFTWARES - DOS drivers	01 Set
	- Windows drivers - Windows XP with original CD and Hard copy (Operating System)	
3	ACCESSORIES/ SPARES/ CONSUMABLES Ref. 3.2	01 Set