

Data sheet for GEM/NIT

Minimum Technical Qualifications Required for supplying

Sl. No.	Technical Requirement
1	ZINC PLATED HEX. HEAD STEEL BOLT M10X30-8.8 AS PER SPECIFICATION AA7121123 REV. 07
2	ZINC PLATED HEX. HEAD STEEL BOLT M10X50-8.8 AS PER SPECIFICATION AA7121123 REV.07
3	ZINC PLATED HEX. HEAD STEEL BOLT M12X30-8.8 AS PER SPECIFICATION AA7121123 REV.07
*	Test Requirement :- As per TC/COC. & SPECIFICATION AA7121123 REV.07



CORPORATE STANDARD

AA 712 11 23

Rev. No. 07

PAGE 1 OF 3

SCREWS, HEXAGON HEAD, PRODUCT GRADE 'A' COARSE PITCH, STEEL, PROPERTY CLASS 8.8 (M6 - M24)

1.0 DESIGNATION:

A product Gr. A hexagon head, steel screws of thread M8, length 50mm, coarse pitch and conforming to property class 8.8 shall be designated as:

1.1 On drawings:

- i) Material specification column : AA 712 11 23
- ii) Description column : SCRU HEX A M8X50 - 8.8.

1.2 On indents:

Screws Hex A M8 X 50 - 8.8 ; AA 712 11 23.

1.3 For issuing enquiries and on purchase orders:

While issuing enquiries and purchase orders, delete BHEL standard number from the above description and add the information given under clause 2.0.

2.0 COMPLIANCE WITH STANDARDS:

2.1 Dimensions, tolerances & general Requirements:

As per IS:1364, Part 2 - 2002.

2.2 Mechanical Properties:

To conform to property class 8.8 as specified in Table - 3 of IS:1367, Part.3-2002.
Permissible hardness 238-350 HB for sizes M6-M10.

2.3 Threads:

Pitch-coarse to IS:4218, Part 2.
Tolerance quality - Medium.
Tolerance class - 6g.

2.4 Identification Marking:

As stated in Cl.9.2.1 of IS:1367, Part.3.

2.5 Surface Discontinuity: As per IS:1367, Part.9.

2.6 Finish: Plated as specified in BHEL order

Revisions :
Cl. 25.7.11 of MOM of WG-F

APPROVED :
INTERPLANT
STANDARDIZATION COMMITTEE (WG-F)

Rev. No. 07

Amd.No.

Prepared

Issued

Dt. of 1st Issue

Dt:01.10.2004

Dt :

Year :

HARDWAR

Corp. R&D

January, 1977

**3.0 NOTE:**

- 3.1 Length and diameter combination (refer Table 1 on page 3 of 3) between the bold lines should only be used.
- 3.2 For screw threads, general (Metric) refer to BHEL standard AA 023 18 00.
- 3.3 For tolerance grade, position and class refer to BHEL standard AA 023 02 01.
- 3.4 Screws to this standard would be unplated, divisions wishing to have plated bolts would have to get them plated.
- 3.5 Weights given in this standard are for general reference only and are not for commercial transactions.
- 3.6 When fasteners are to be tested with in BHEL, the sampling and acceptance plan shall be as per IS:1367, part 17.

4.0 REFERRED STANDARDS (Latest publications including amendment):

- 1) IS: 1364, Pt.2 2) IS:1367 Pt.3, 9&17 3) IS: 4218, Pt.2 4) AA 023 02 01
5) AA 023 18 00 6) AA 023 18 50

EXPLANATORY NOTE:**The following changes have been made in the revision:**

- New clause 2.5 Surface Discontinuity is added.
- Existing clause 2.5 is renumbered as 2.6.
- In Cl.2.2, year of IS is modified as 2002.
- Clause 9 of IS:1367 is included in Cl 4.0

