








 TME/2015	PRODUCT STANDARD TME DIVISION, BHOPAL		TM10478																
			Rev 01																
			PAGE 01 OF 02																
<p align="center"><u>SPECIFICATION FOR "THREAD INSERT KIT" FOR 3-PHASE TRACTION MOTOR TYPE 6FRA6068 & 6FXA7059.</u></p>																			
<p>1.0 Forward:</p> <p>This specification covers the requirement of "Thread Insert Kit" for manufacturing of 3-Phase Traction Motor.</p>																			
<p>2.0 Requirement:</p> <p>Requirement per set in the "KITS" form are indicated here under : Supplier shall quote their rates per set in "KITS" form taking all items together, otherwise their offer are liable to be summarily rejected.</p>																			
<table border="1"> <thead> <tr> <th>Sl. No.</th> <th>Description & Drg. / Specn. No.</th> <th>Qty./ TM (nos)</th> </tr> </thead> <tbody> <tr> <td>01</td> <td>Thread Insert H.C. M20X1.5D (coarse), (Material-stainless steel)</td> <td>10</td> </tr> <tr> <td>02</td> <td>Thread Insert H.C. M20X1.5D (coarse), (Material-stainless steel)</td> <td>10</td> </tr> <tr> <td>03</td> <td>Thread Insert H.C. M30X1.5D (coarse), (Material-stainless steel)</td> <td>16</td> </tr> <tr> <td colspan="2">Total Qty.</td> <td>36</td> </tr> </tbody> </table>					Sl. No.	Description & Drg. / Specn. No.	Qty./ TM (nos)	01	Thread Insert H.C. M20X1.5D (coarse), (Material-stainless steel)	10	02	Thread Insert H.C. M20X1.5D (coarse), (Material-stainless steel)	10	03	Thread Insert H.C. M30X1.5D (coarse), (Material-stainless steel)	16	Total Qty.		36
Sl. No.	Description & Drg. / Specn. No.	Qty./ TM (nos)																	
01	Thread Insert H.C. M20X1.5D (coarse), (Material-stainless steel)	10																	
02	Thread Insert H.C. M20X1.5D (coarse), (Material-stainless steel)	10																	
03	Thread Insert H.C. M30X1.5D (coarse), (Material-stainless steel)	16																	
Total Qty.		36																	
<p>Note: Qty./TM of "Thread Insert Kit (6FRA)" = 01 set (36 Nos.)</p>																			
<table border="1"> <thead> <tr> <th>Sl. No.</th> <th>Description & Drg. / Specn. No.</th> <th>Qty./ TM (nos)</th> </tr> </thead> <tbody> <tr> <td>01</td> <td>Thread Insert H.C. M20X1.5D (coarse), (Material-stainless steel)</td> <td>10</td> </tr> <tr> <td>02</td> <td>Thread Insert H.C. M20X1.5D (coarse), (Material-stainless steel)</td> <td>10</td> </tr> <tr> <td>03</td> <td>Thread Insert H.C. M24X1.5D (coarse), (Material-stainless steel)</td> <td>04</td> </tr> <tr> <td colspan="2">Total Qty.</td> <td>24</td> </tr> </tbody> </table>					Sl. No.	Description & Drg. / Specn. No.	Qty./ TM (nos)	01	Thread Insert H.C. M20X1.5D (coarse), (Material-stainless steel)	10	02	Thread Insert H.C. M20X1.5D (coarse), (Material-stainless steel)	10	03	Thread Insert H.C. M24X1.5D (coarse), (Material-stainless steel)	04	Total Qty.		24
Sl. No.	Description & Drg. / Specn. No.	Qty./ TM (nos)																	
01	Thread Insert H.C. M20X1.5D (coarse), (Material-stainless steel)	10																	
02	Thread Insert H.C. M20X1.5D (coarse), (Material-stainless steel)	10																	
03	Thread Insert H.C. M24X1.5D (coarse), (Material-stainless steel)	04																	
Total Qty.		24																	
<p>Note: Qty./TM of "Thread Insert Kit (6FXA)" = 01 set (24 Nos.)</p>																			
<table border="1"> <tr> <td rowspan="2"> Revision : 01 Date: 11.08.2020 </td> <td>Distribution</td> <td>Qty.</td> <td colspan="2"> Approved :  (M. Verma) </td> </tr> <tr> <td> TXM QTM TME TSD </td> <td> 1 1 1 1 </td> <td> Prepared  (A. Shukla) </td> <td> Checked:  (A. Jain) </td> <td> Date: 11.08.2020 </td> </tr> </table>					Revision : 01 Date: 11.08.2020	Distribution	Qty.	Approved :  (M. Verma)		TXM QTM TME TSD	1 1 1 1	Prepared  (A. Shukla)	Checked:  (A. Jain)	Date: 11.08.2020					
Revision : 01 Date: 11.08.2020	Distribution	Qty.	Approved :  (M. Verma)																
	TXM QTM TME TSD	1 1 1 1	Prepared  (A. Shukla)	Checked:  (A. Jain)	Date: 11.08.2020														

TME/2015

**PRODUCT STANDARD
TME DIVISION, BHOPAL**

TM10478

Rev 01

PAGE 02 OF 02

3.0 Specification

Material of Thread Insert shall comply to AISI-304.

4.0 Dimension

The dimensional tolerance of Thread Insert shall comply to DIN 8140, Part-1, Type-A.

5.0 Special Condition

Supplies will be acceptable with manufacturer's guarantee & test certificate.

6.0 Marking & Packing

Manufacture's identification mark/ colour code shall be provided on each item. One set of KIT shall be properly packed in box of suitable material to avoid damage during handling and transportation. All the item should be first kept in durable polythene packet, each type is separate packet and then finally kept in box. Two cards indicating description of the material of individual item including quantity duly signed by BHEL's inspector shall be tagged one inside and other outside the box.

7.0 Inspection

- a) Few thread insert of each size shall be selected at random.
- b) Thread insert shall be tested at NABL certified lab to confirm the material as said above.

8.0 This specification is equivalent to CLW's specification no. 4TMS.096.076.

COPYRIGHT AND CONFIDENTIAL
The information on this document is the property of **BHARAT HEAVY ELECTRICALS LIMITED**
It must not be used directly or indirectly in any way detrimental to the interest of the company