

745883/2022/HEP-TXM20500

TXM DIVISION
ITEM ACCEPTANCE PLAN CUM QAP for Tooling Items

Indent no	:	820510055		
	Sl. No.	Description		
1	1	QUICK RELEASE COUPLING WITH NIPPLE, FEMALE THREAD WITH 60 DEGREE SEALING CONE M16X1.5. MAX WORKING PRESSURE 300.0 MPA (3000 BAR/43500 PSI), MIN. BURST PRESSURE 600.0 MPA, LENGTH 64 MM, DIAMETER 30MM, HEXAGON 22MM.		
2	2	SS SEAMLESS HYDRAULIC HIGH PRESSURE PIPE, LENGTH = 3000 MM, OD = 6 MM, BOTH END SWIVEL CONNECTOR, ONE SIDE 1/4" BSP & OTHER SIDE M16x1.5. SAFE WORKING PRESSURE = 3000 BAR. ONE SET CONSIST Of ONE FEMALE CCOUPLER & ONE MALE COUPLER		
Check List	:	FOR ITEM SL. NO. #01 TO 2	1	TC & GC to be check
			2	Visual inspection of item
			3	Fittment of item with existing pinion extraction sytem & performance to be check at BHEL shop

Ravindra Kumar Gupta
Dy.Mgr/TXM