

ANNEXURE -A CUM PQC PI 820510055

item no.	MAT CODE	Description	VENDOR TO CONFIRM	
1	TM7790102010	QUICK RELEASE COUPLING SET (WITH NIPPLE), FEMALE THREAD WITH 60 DEGREE SEALING CONE M16X1.5. MAX WORKING PRESSURE 300.0 MPA (3000 BAR/43500 PSI), MIN. BURST PRESSURE 600.0 MPA, LENGTH 64 MM, DIAMETER 30MM, HEXAGON 22MM. ONE SET CONSISTS OF ONE FEMALE COUPLER & ONE MALE COUPLER	YES/NO	VENDOR TO NOTE & CONFIRM
2	TM7790101056	SS SEAMLESS HYDRAULIC HIGH PRESSURE PIPE, LENGTH = 3000 MM, OD = 6 MM, BOTH END SWIVEL CONNECTOR, ONE SIDE 1/4" BSP & OTHER SIDE M16X1.5. SAFE WORKING PRESSURE = 3000 BAR.	YES/NO	VENDOR TO NOTE & CONFIRM
3		TEST CERTIFICATE	VENDOR TO SUBMIT TEST CERTIFICATE DURING SUPPLY	VENDOR TO NOTE
4		STANDARD GUARANTEE/WARRANTY TERMS	YES/NO	VENDOR TO NOTE

PQC/PQR REQUIREMENTS

1	Only OEM or authorized agent/dealer/channel partner of the OEM should quote	Yes/No	Submit : Proof of establishment/declaration in case of OEM & in case of authorized agent/dealer/channel partner of the OEM Valid authorization certificate from OEM is required.
2	Experience of supplying similar items i.e. QUICK RELEASE COUPLING MAX WORKING PRESSURE 300.0 MPA (3000 BAR/43500 PSI) or HYDRAULIC HIGH PRESSURE PIPE SAFE WORKING PRESSURE = 3000 BAR. OF ANY SIZE to any GOVT. OR PRIVATE ORGANISATION in the last five years from date of opening of enquiry (TOD) should quote.	Yes/No	Submit : Proof of Experience : PO copy , Proof of Supply : Invoice / delivery chalan copy

Notes:

- In absence of compliance above PQC/PQR, supplier offer is liable to be rejected.