भारत हेवी इलेक्ट्रिकल्स लिमिटेड पावर सेक्टर- पश्चिमी क्षेत्र श्रीमोहिनी काम्पलेक्स, 345 - किंग्सवे नागपुर- 440 001



Bharat Heavy Electricals Limited Power Sector-Western Region Shreemohini complex, 345 - Kingsway Nagpur-440 001

फोन / Phone 0712- 3048600 TO 604 फैक्स FAX: 0712- 3048698- 699/ 3048605 www.bhelpswr.co.in

PUR-F 31/01 Page 1 OF 9

PURCHASE ENQUIRY

	Our E-mail : smb@bhelpswr.co.in	
M/s	ENQUIRY No.	XI014 E
	ENQ.DATE	22.07.11
	DUE DATE	12.08.11

Dear sir,

Kindly submit your sealed quotation by Speed Post / Registered Post / Courier / Air Mail in two bids viz.

(1) Technical cum Commercial Bid & (2) Price Bid for the material indicated below confirming acceptance to the terms and conditions enclosed ,so as to reach our office on or before 3.00 PM on the due date. Quotation may be sent by Fax only if asked so by BHEL / with prior permission of BHEL.

S Description of Material Unit Qty Delivery Schedule (Destination) SUPPLY OF PORTA CABINS WITH CHAIRS Within 01	
	ired at
SLIPPLY OF PORTA CARINS WITH CHAIRS Within 01	
AND ALL FITTINGS INCLUDING PAINTING AS PER SPECIFICATION & SKETCH ENCLOSED. NOS NOS Month from the date of approval of drawings by BHEL. REF.ANNEXI FOR DETAIL	

A) GENERAL TERMS AND CONDITIONS OF CONTRACT

CI. No.	DESCRIPTION
01	Each tender should be sent in a double cover, inner cover should be sealed with tenderer's distinctive seal. The outer cover should bear the address of this office and superscribed with correct Enquiry No. and Due Date. Tender should be free from CORRECTION AND ERASURES. Corrections, if any must be attested. All amounts shall be indicated both in words as well as in figures. Where there is difference between amount in figures and words, amount quoted in words shall prevail.
02	Technical cum Commercial bid will be opened at 4.00 PM on Due Date. The Technical cum Commercial bid should accompany copy of documents like authorized dealership certificate, earlier supply order details of similar equipment and their performance feedback from customers, company profile and present status, product catalogue of the models offered, technical specifications of the product, commercial Terms & Conditions and other relevant documents etc.
03	Price bid of technically accepted bidders only will be opened. No revision of prices will be entertained after Tenders are opened, unless mentioned in our enquiry / asked so by BHEL.
04	Manufacturer's name, Trade Mark or Patent No. if any, shall be specified in the Technical cum Commercial Bid
05	Please mention the relevant national / international standard code of the product quoted for in the Technical cum Commercial bid.
06	The purchaser shall be under no obligation to accept the lowest or any other tender and shall be entitled to accept or reject any tender in part or full without assigning any reason whatsoever.
07	Late tenders (received after Due Date & time) shall not be accepted in any circumstances.
08	Price quoted shall be valid for 90 days from the date of opening
09	Price shall be quoted as per enclosed 'Price Format' only. Quotations not accompanying filled in 'Price Format' are likely to be rejected. Please fill in all the columns of all formats

PUR-F31/01 Page 2 OF 9 DUE DATE: 12.08.11

FN	Page 2 OF 9 QUIRY NO. XI014 E DT.22.07.11 DUE DATE: 12.08.11
	The price quoted should be as applicable to DGS & D (Govt. of India) and other Govt. Organizations. In
10	case DGS & D rate / Running Contract is not existing, but a contract is in vogue with any BHEL Unit,
	reference of the same shall be furnished and same may be applicable to this contract.
11	SECURITY DEPOSIT: The supplier shall have to furnish Security Deposit (Cash/DD/Bank Guarantee
	from a Scheduled Bank) if so specified in the tender under Special Terms & Conditions.
12	PACKING AND MARKING: The supplier shall arrange for secure protective packing of the goods suitable for tropical conditions to avoid loss, damage, atmospheric action during handling and transit. The packing standards will comply with relevant national standard/carrier's conditions of packing or established practice. If any damage is sustained and the carrier or underwriter attributes it to improper packing, the seller shall be liable to replace the material or reimburse the value of the loss notwithstanding any transit insurance arranged by him or not. The following marking shall be made on each package in black bold letters. NAME & ADDRESS OF CONSIGNEE, DIMENSION OF
	PACKAGE, WEIGHT DETAILS: GROSS, TARE & NETT These markings should be stenciled or written in bold letters on the package. Should the package be small, suitable cards/metal tags giving these details may be tagged or nailed
13	INSPECTION: Final inspection will be carried out the destination/site/Purchaser's works by the authorized inspecting Officer, if so specified in the tender under Special Terms & Conditions. Whenever preliminary or stage inspection is to be carried out at supplier's works the same is subject to final acceptance after receipt of the material at the destination/Purchasers works and the decision of the purchaser shall be final. The propriety of goods shall not pass until final acceptance by the purchaser
14	REJECTION: The seller shall intimate the purchaser in writing within 15 days (after being intimated about rejection of goods) regarding disposal action of the rejected material. If no advice is received within this time the purchaser shall be at liberty to return the material at the cost and risk of the seller after receiving the cost if any paid by the Purchaser including inward freight and other incidental charges. The Purchaser will not be responsible for the rejected material thereafter and no claim will rest on him.
15	Delivery: Purchaser shall not be liable to receive and pay for any supply made after delivery date stipulated in the order unless the delivery date is formally extended by the purchaser. Wherever the terms of delivery of the order is other than F.O.R. destination, delivery date will be reckoned as the date of dispatch or the date of readiness after inspection of the material where the Purchaser has agreed for inspection or collection.
16	Test certificate: The seller shall carry out such tests as prescribed by the purchaser / as required in accordance to the relevant national or international standards, in his works and/or and other places as stipulated in the order. Necessary test certificate shall be submitted with delivery of materials. The seller shall also provide at no extra cost the required number of catalogues, drawing and other manuals related to materials under this order.
17	TERMS OF PAYMENT: Payment will normally be made within a month of receipt of material in good condition at destination. Any other payment terms have to be mutually agreed. The seller shall send dispatch documents, invoice etc. in such quantum and a manner as provided in the order. (I) It is expressly understood that in the event of rejection of the materials for which payment has been made against document's through bank the Purchaser reserves the right to claim from the seller the amount paid and the incidental charged incurred in the same manner i.e. negotiating return dispatch documents, through Bank and the Seller shall honour such claim and retire the documents from the Bank. (ii) Bank charges for any payment claimed through Bank shall be borne by the seller and the seller shall also agree to bear any demurrage or other charges arising out of any delay in retirements or documents from Bank due to delayed, insufficient incorrect information furnished. (iii) The seller shall also ensure that the Carriers do not delay dispatch of the consignment once the carrier's receipt is obtained.
18	GUARANTEE WARRANTY: The materials shall be warranted for design material and workmanship and also for performance warranty as specially stipulated by the purchaser in the order in its annexure.
19	INSURANCE: Wherever specifically agreed to and directed, the supplier will insure the goods for all transit risks upto delivery of the goods at the final destination. In all other cases supplier must furnish particulars of dispatch for each consignment immediately after the dispatch of goods. Failure to do this will make the supplier responsible for making good any loss, which otherwise might have been recovered from underwriters.

PUR-F31/01 Page 3 OF 9

DT.22.07.11 **ENQUIRY NO.XI014 E** DUE DATE: 12.08.11 DELIVERY FAILURE, TERMINATION & LIQUIDATED DAMAGE: The parties hereto agree that the timely dispatch/delivery and completion of the other schedules as stipulated in order/contract shall be the essence of the Order/Contract. If the seller/contractor fails to complete the dispatch/ delivery and other schedules within the time period stipulated in the order/contract, or within any extension of time granted by the purchaser, it shall be lawful for the purchaser to recover damages for the breach of order/contract without prejudice to any other rights and/or remedies provided for, in order/contract and hereunder. The purchaser reserves the right to recover from the Seller/Contractor, as agreed liquidated damages and not by way of penalty, a sum equivalent to half percent {1/2% of the total contract price per week part thereof, subject to a 20 maximum of ten percent @ 10%} of the total contract price excluding elements of taxes, duties and freight, if seller/contractor has failed to deliver any part of the goods within the period stipulated in the Order/Contract. The purchaser reserves the right to purchase from elsewhere on account of and at the risk and cost of the seller /contractor without notice to the seller /contractor of goods not so delivered or their equivalent, without canceling the order/contract in respect of the goods not yet due for delivery. The purchaser reserves the right to cancel the order/contract or a portion thereof for the goods not so delivered at the risk and cost of the seller/contractor and the seller/contractor shall be liable to the purchaser for any excess costs thereof. RISK PURCHASE: In the event the supplier has failed to deliver or dispatch whole of the goods or any part within the time stipulated or if the same were not available in his stock, the best and the nearest available substitute thereof may be purchased/arranged by purchaser from elsewhere at the risk and 21 the cost of the seller. The purchaser at his option will be entitled to terminate the contract and seller shall be liable for any loss which the purchaser may sustain by reason of such risk purchases in addition to penalty at the rate mentioned in clause 20 above. PREFERENTIAL DELIVERY: It should be noted that if an Order is placed on a higher tenderer as a result of this invitation to tender, in preference to the lowest acceptable offer in consideration of the earlier delivery, the seller will be liable to pay the purchaser the difference between the contract rate 22 and that of the lowest acceptable tender on the basis of final price F.O.R. destination including all elements of freight, sales tax, duties and other incidentals in case of failure to complete supplies in terms of such contract within the date of delivery specified in the tender and contract. Purchaser reserves its right to the Public Enterprises price preference facilities as admissible under the 23 Govt. of India policy from time to time. 24 This order or any part thereof shall not be sub-contracted without the purchaser's consent. 25 METRIC SYSTEM: Supplier is requested to indicate metric system measurements in all documents. INDEMNITY: The Seller shall indemnify the Purchaser against any claim due to any breach of patent, 26 negligence, defective material or injury to seller or his agent. In the event of any reduction in the price, due to change of Govt. duties after award to the work and 27 before delivery commencement, purchaser is entitled to such reduction and may negotiate fresh price at its discretion. GENERAL: The purchaser reserves the right to split up the tender and place orders for individual item 28 on different suppliers and also increase or decrease the quantity. DISPUTES & ARBITRATION: All cases of disputes will be resolved according to the Indian Arbitration 29 Act 1940 FORCE MAJEUR: Acts of God, Acts of Government, War, Sabotage, Riots, Civil commotion, Police action, Revolution, Natural Calamities, Epidemic and other similar causes over which the supplier has 30 no control, will amount to Force Majeur. Delay attributable to Force Majeur will be condoned; however the onus of establishing the reason of delay lies with the Supplier. **Please Note:** a) Tender Specification documents with complete details are hosted in web page (www.bhel.com). Bidders can directly download the same and use for submission of offer. Tender Document charges (Rs 2,000/-) shall be paid to BHEL positively along with or before submission of Offer. b) Interested bidders may alternately collect hard copy of Tender documents from this Office on all working days within the sale period on payment of Tender Document charges of Rs 2,000/either by DD (in favour of BHEL payable at Nagpur) or cash. Courier charges will be Rs. 500/-31 extra if T.S. documents are requested through courier. c) BHEL takes no responsibility for any delay/loss of documents or correspondences sent by courier/post. d) BHEL reserves the right to accept or reject any or all tenders without assigning any reasons whatsoever. e) Dates of Price Bid opening will be intimated to Techno Commercially Qualified Bidders later.

PUR-F31/01 Page 4 OF 9

ENOL	וםע אור).XI014 E	DT.22.07.11	Page 4 OF 9 DUE DATE: 12.08.11	
LINGU	f)		addenda, amendments and clarifications		
	'/		ssion Dates; etc will be hosted in the web		
			View Corrigendum) and NOT in the newspa		
	updated on all such updates.				
	g)		the right to reject any tender on the basis of		
		•	ongoing job or any similar job in the last s	seven years or for furnishing false	
			laration in the offer.		
	a)		Documents: Tender Specification documents will		
			AM to 4:00 PM on all working days within the period	od specified in the NII.	
	b)	Holidays:			
			ler Documents shall not take place on National Hol		
			vernments, Sundays, second and last Saturdays	and nolidays of BHEL PSWR Nagpur	
	۵)	HQ.	ione on Tondor Cresification.		
	c)	•	ions on Tender Specification:	and had the hidden on on to make this	
			s on the Tender Specifications, if any, may be sou	agnit by the bidders so as to reach this	
	۹/		st seven days before the Due Date for submission.		
	d)	Supporting Docur	nerits. Il submit documents in support of possessing "Q	usolifying Paguiromente" og under duly	
			and stamped by the authorized signatory.	dalifying Requirements as under duly	
32			s of Work Orders issued by the Customer containing	ng dotails of Pill of Quantities/Schodule	
32		of Rates.	s of work Orders issued by the Customer containing	ing details of bill of Quantities/Schedule	
			s of Completion Certificate issued by Customer or	Owner of Project	
		•	s of completion certificate issued by customer of the solution	•	
		for Turnove	•	is, accompanied by relevant schedules	
			DER: Tender received after the specified time of	submission shall not be considered in	
		any circum		Submission shall not be considered in	
			t be submitted without any deviation		
			ived with any deviation or without relevant informat	tion as described above are liable to be	
			ice bids received in the form other than specified		
		rejected.	ico bido roccivod in the form dator than opocinic	a in rait ii (i nee Bia) are nable to be	
		-	t sign & stamp all pages of this tender specification	as an acceptance of tender conditions	
			nclose this tender specification with their offer.	. ac an acceptance of tonder conditions	
22	In cas		adictions between General and special terms	s and conditions, the provisions in	
33			litions will prevail.	, ·	

Yours faithfully, For BHARAT HEAVY ELECTRICALS LTD.

DGM (PURCHASE)

ENQUIRY NO.XI014 E DT.22.07.11

B) SPECIAL TERMS AND CONDITIONS OF CONTRACT Clause | Item Description No 01 **QUALIFICATION REQUIREMENT:** Bidder must fulfill all the Qualifying Requirements (i.e. a, b, c, d) as under in order to be considered as technically qualified for this Tendering process: a) Bidder must have, in last seven years as on 30/06/2011, executed any one of the following (i.e. a1or a2): a.1) Supplied Porta Cabins to any Unit of BHEL for a value not less than 20 Lakhs, in a Single Order a.2) Supplied Porta Cabins to any Government, Semi Government/ or any other Customer for a quantity of not less than 10 numbers in any one Purchase Order. AND b) Bidders must have achieved an Average annual financial turnover of Rs. 7.50 Lakhs or more over last three Financial Years i.e. 2008-09, 2009-10 & 2010-11 OR 2007-08, 2008-09 & 2009-10 if account for FY 10-11 has not been audited. c) Net worth of bidder based on Audited Accounts of 2010-11 (OR 2009-10 incase accounts for FY 10-11 has not been audited) should be higher than 50% of the Paid-up Capital in case of Companies. AND d) Bidder must have earned cash profit in any one of the three Financial Years as applicable in case of 'c' above based on latest Audited Accounts. ______ Explanatory Notes for QR 'a' 1. The word 'executed' means the bidder should have achieved the criteria specified in the QR even if the total contract has not been completed or closed 2. Porta Cabins means "Self contained, furnished, ready to use Portable cabins" of steel fabricated framework. 02 **Fulfillment of Qualifying Requirements:** A bidder must satisfy all the Qualifying Requirements stipulated under 'a', 'b', 'c' and 'd' of this Specification, concurrently in order to get qualified. 03 **Earnest Money Deposit (EMD)**: Refundable, Non-interest bearing EMD of Rs 60,000/- (Rupees Sixty Thousand) is applicable for this Tender. EMD shall be paid ONLY by Account Payee Demand Draft in favour of "Bharat Heavy Electricals Limited" payable at Nagpur. 04 The bidder shall submit all documents as called for in the Technical specifications. 05 Bidder should furnish an undertaking for the product support along with uninterrupted and timely supply of fittings for at least 3 years for the quoted item. 06 The offer of the bidder indicating/disclosing prices in techno-commercial (un-priced bid) or at any stage before opening of price-bid shall be straightaway rejected.

PUR-F31/01 Page 5 OF 9 DUE DATE:12.08.11

PUR-F31/01 Page 6 OF 9

ENQUI	RY NO.XI014 E	DT.22.07.11	DUE DATE:12.08.11
07	EVALUATION: - Offers	will be evaluated based on total pric	e of all the porta cabin required at a
	site and also by considering the input credit of ED offered by the vendor.(i.e. total landed		
	cost of all the porta cabin of a particular site including taxes, duties and freight minus ED		
	paid for the same).		
08	Bidder must confirm v	hether Excise Invoice shall be given	or not. In case bidder confirms that
	excise invoice shall be	given, then the evaluation of bid s	shall be on the basis landed cost to
	BHEL excluding Excise	Duty.	
09	Security Deposit is not applicable for this Enquiry		
10	Payment Terms :		
	a) 80% of basic -	- 100% taxes, duties and freight sh	nall be payable for the Porta cabin
	supplied at Site	e in good physical condition.	
	b) 10% within 30	days of acceptance of installation at	Site
	c) 10% after com	oletion of warranty period of 1 year	
11	Incomplete offer shall	not be considered for evaluation and	d shall be rejected.
12	Bidder should submit	the Drawings for approval within	10 days from the date of Purchase
	Order. Delivery period	will commence once the drawings a	re approved by BHEL.
13	Bidder should submit	the complete set of our Enquiry d	uly signed and stamped along with
	their offer as an accep	tance of terms & conditions.	

Thanking you,

Yours faithfully, For BHARAT HEAVY ELECTRICALS LTD.

DGM (PURCHASE)

CERTIFICATE OF NO DEVIATION

TENDER SPECIFICATION No.: XI014 E

HEREBY CERTIFY THAT NOT WITHSTANDING ANY CONTRARY INDICATIONS / CONDITIONS ELSEWHERE IN OUR OFFER DOCUMENTS, I/WE HAVE NEITHER SET ANY TERMS AND CONDITIONS NOR THERE IS ANY DEVIATION TAKEN FROM THE CONDITIONS OF BHEL'S TENDER SPECIFICATIONS, EITHER TECHNICAL OR COMMERCIAL, AND I/WE AGREE TO ALL THE TERMS AND CONDITIONS MENTIONED IN BHEL'S TENDER SPECIFICATION WITH ASSOCIATED AMENDMENTS & CLARIFICATIONS.

SIGNATURE OF THE TENDERER

DATE:

PUR-F31/01 Page 8 of 9

TECHNO-COMMERCIAL TERMS & CONDITIONS: (PART OF TECHNICAL CUM COMMERCIAL BID) ENQUIRY NO.XI014 E DT.22.07.2011 DUE DATE: 12.08.2011

SN	DESCRIPTION OF T & C	TERMS & CONDITIONS AS QUOTED IN THIS TENDER
01	DELIVERY TERMS	F.O.R.DESTINATION
02	PLACE OF DELIVERY	REFER ANNEXURE-II
03	DELIVERY PERIOD FROM THE DATE	01 MONTH
	OF ORDER	
04	CURRENCY OF PAYMENT	INR
05	PACKING & FORWARDING CHARGES	INCLUDED@% / EXTRA @% / NOT INCLUDED
06	EXCISE DUTY (% RATE)	INCLUSIVE@% / EXTRA @% / N.A.
07	EXCISE DUTY INVOICE (FOR CENVAT BENFIT)	SHALL BE PROVIDED/ NOT PROVIDED
08	VAT/CST WITHOUT C OR D FORM	FOR Chattisgarh-Included @% (or) Extra@% (or) Not Applicable FOR Maharashtra -Included @% (or) Extra@%.(or) Not Applicable NO "C" OR "D" FORM WILL BE ISSUED BY BHEL
09	OCTROI / ENTRY TAX AT DESTINATION	EXTRA, IF APPLICABLE SHALL BE PAID BY BHEL ON PRODUCTION OF ORIGINAL OCTROI RECEIPT.
10	FREIGHT CHARGES UP TO DESTINATION	QUOTED EXTRA@% / INCLUDED IN COMPOSITE PRICE BIDDER TO INDICATE APPLICABLE PERCENTAGE/PRICE IN THE PRICE BID CLEARLY.
11	TRANSIT INSURANCE CHARGES	BY BHEL. SUPPLIER HAS TO INTIMATE THE DISPATCH DETAILS TO BHEL'S UNDERWRITERS AS SOON AS THE MATERIAL DISPATCHED.
12	ANY OTHER CHARGES (please specify here the nature of charge)	(AMOUNT TO BE SPECIFIED IN THE PRICE FORMAT)
13	PAYMENT TERMS (Specify scope of Banker's Charges at both ends / Demand Draft Charges)	REFER SPECIAL TERMS & CONDITIONS
14	MODE OF DISPATCH	BY ROAD
15	NAME OF THE GOODS MANUFACTURER / PRINCIPALS	
16	TRADE NAME / MODEL NUMBER OF GOODS	
17	AUTHORIZED DEALERSHIP CERTIFICATE	CERTIFICATE OF MANUFACTURER/PRINCIPALS: ENCLOSED / NOT ENCLOSED
18	WARRANTY / GUARANTEE CONDITIONS	SHALL BE AS SPECIFIED UNDER WARRANTY CLAUSE IN TECHNICAL SPECIFICATION.
19	PRODUCT CATALOGUE / WRITE UP	ENCLOSED / NOT ENCLOSED.
20	CONTACT PERSON'S NAME TEL/MOB No. e-mail id	

SIGNATURE & SEAL OF TENDERER

PRICE FORMAT

BHARAT HEAVY ELECTRICALS LIMITED POWER SECTOR: WESTERN REGION: NAGPUR

NAME OF	THE TENDERER:		
SELLER'S	REF. No	DATE :	
ENQUIRY	No.: XI014 E DATED	: 22.07.2011	DUE DATE: 12.08.201
S.N.	DESCRIPTION		TYPE A
Α	ITEM DESCRIPTION AS PER ENQUIRY (PLEASE QUOTE THE ENUMBER)	RAND NAME AND MODEL	
В	QTY OFFERED		
С	UNIT RATE		
D	CURRENCY		
E	DISCOUNT (%AGE & AMOUNT)		
F	DISCOUNTED UNIT RATE		
G	DISCOUNTED BASIC PRICE (G = B x F)		
Н	PACKING & FORWARDING CHARGES		
1	EXCISE DUTY (PERCENTAGE AND AMOUNT)		
J	IMPORT DUTY (PERCENTAGE & AMOUNT)		
K	VAT/CST WITHOUT C-FORM		
L	FREIGHT UPTO DESTINATION		
M	TRANSIT INSURANCE		BY BHEL
N	OCTROI CHARGES / ENTRY TAX AT DESTINATION		EXTRA, IF APPLICABLE ON PRODUCTION OF ORIGINAL OCTROI RECEIPT.
0	TOTAL PRICE AT DESTINATION (SUM of 'G' to 'O')		

NOTES:

- 1. PLEASE USE ADDITIONAL SHEETS IF NECESSARY
- 2. FURNISH FURTHER BREAK UP OF PRICE, IF NECESSARY

ANNEXURE-I

TECHNICAL SPECIFICATION

Scope of work:

Design, Engineering, Supply, Transportation and Installation over the foundation/platform (provided by BHEL) in all respects including fittings, fixtures, accessories, electrification, sanitary, plumbing etc. at various construction sites (in the state of Maharashtra & Chhattisgarh)

Sr. No.	Component	Description (old)	Remarks	
Main Load Bearing members				
1	Base Frame (Outer frame)	150mm especially Pressed formed profile of appropriate geometry made of MS sheet (IS 10748 or equivalent) 2.5mm Thick.	Ref. drawings	
2	Stiffeners for base frame	75mm x 40mm Pressed formed rectangular hollow Section made of MS sheet(IS 10748) 2.5mm Thick (Min. 3 rows in longitudinal side & 4 rows transverse side)	Ref. drawings	
3	Roof top frame (Main outer frame)	150mm especially Pressed formed profile of appropriate geometry made of MS sheet (IS 10748 or equivalent) 2.5mm Thick.	Ref. drawings	
4	Stiffeners (for Top frame)	50 x 25 x2.5mm (transverse direction min. 4 rows) & 32 x 32x 2mm (longitudinal direction min. 3 rows) Pressed formed hollow section made of MS sheet (IS 10748)	Ref. drawings	
5	Corner Posts	Pressed formed square hallow section of 3.15mm thick M.S sheet of section 91 X 91 X 31.5 mm.	Ref. drawings	
6	Side/vertical intermediate Post & horizontal stiffeners	Especially Pressed formed profile of appropriate geometry made of 2.0 mm thick M.S sheet for holding wall paneling (compressed sandwich panel) ,all fitting & fixtures including AC and Over Head cabinets etc.		
7	Lifting Hooks & Base Plates	Necessary lifting hooks for loading, unloading shall be provided. All the corner post shall have min. 16mm thick base plate of size 250mmx250mm on both top and bottom.		
8	Painting	The All Exposed Structural frame shall be painted with one coat primer and two coat enamel paint. With dark blue color. Primer coat shall be red oxide 35 micron DFT and synthetic enamel paint shall be 50 micron DFT of two coats of Asian/Burger make. Total dry film thickness (DFT) of finished paint should not be less than 135 micron including primer.		
		Paneling		
1	Main Wall paneling	The interior shall be aesthetically finished to give custom built appearance with good workmanship. Main Wall Paneling shall be of CONTIUOUS SANDWITCHED PANEL (CSP) with PUF (Polyurethane Foam) insulation of density 40±2 Kg/M³ and overall thickness 60mm with 0.5mm thick PPGI (pre painted galvanized iron) sheet of approved color (preferably light gray color) on both sides. An additional off-white colored wall paneling of 8mm thick hallow extruded polymeric section (syntax or Equivalent) with tongue and grove arrangement on inner surface of CSF panel to be fixed with suitable anti-corrosive frame grid arrangements. All electrical wiring shall be concealed with PVC conduit between CSF and Inner polymeric panel.	PPGI sheet make shall be ISPAT INDIA LIMITED/ JSW or Approved Equivalent.	
2	Roof	Roofing shall be of 50mm thick PUF insulation of density 40±2 Kg/M³ with 0.5mm thick PPGI (pre painted galvanized iron) sheet of approved color (preferably light gray color) on both sides.	PPGI sheet make shall be ISPAT INDIA LIMITED/ JSW or Approved Equivalent.	
3	False ceiling	The false ceiling shall be made out of anti corrosive painted 19mm square hollow section design to fix to the roof frame with suitable hangers. The clear height of ceiling shall be		

ENQUIRY NO.XI014 E DT. 22.07.2011 DUE DATE: 12.08.2011

8 ft. from the finished floor level. Cut out should be made properly wherever necessary for fixing electrical filting. False ceiling shall be done with 8mm thick hallow extruded polyments section section (syntax or Equivalent) with tongue and grove arrangement. The color of Ceiling should match with innet well planels. 4 Partition Partition frame to be made out of anticornosive painted 25 mm hollows equare section of 16 SWG thicknesses as per continuous must be section of 18 SWG thicknesses as per continuous must be section of 18 SWG thicknesses as per continuous must be section of 18 SWG thicknesses as per continuous must be section of 18 SWG thicknesses as per continuous must be section of 18 SWG thicknesses as per continuous must be section of 18 SWG thicknesses as per continuous must be section of 18 SWG thicknesses as per continuous must be section of 18 SWG thicknesses as per continuous must be section of 18 SWG thicknesses as per continuous must be section of 18 SWG thicknesses as per continuous must be section of 18 SWG thicknesses as per continuous must be section of 18 SWG thicknesses as per continuous must be section of 18 SWG thicknesses as per continuous must be section of 18 SWG thicknesses as per continuous must be section of 18 SWG thicknesses as per continuous must be section of 18 SWG thicknesses as per continuous must be section of 18 SWG thicknesses as per continuous must be section of 18 SWG thicknesses as per continuous must be section of 18 SWG thicknesses as per continuous must be section of 18 SWG thicknesses as per continuous must be section of 18 SWG thicknesses as per continuous must be section of 18 SWG thicknesses as per continuous must be section of 18 SWG thicknesses as per continuous must be section of 18 SWG thicknesses as per continuous must be section of 18 SWG thicknesses as per continuous must be section of 18 SWG thicknesses as per continuous must be section of 18 SWG thicknesses as per continuous must be section of 18 SWG thicknesses as per continuous must be section of				
False ceiling shall be done with 8mm thick hallow extruded polymeric section (syntax or Equivalent) with tongue and grove arrangement. The color of Ceiling should match with inner wall panels. Partition Partition frame to be made out of anticorrosive painted 25 mm hollow square section of 16 SWC thicknesses as per IS-4923 and double side paneling with polymeric section of minimum thickness of mm. These panels are to be joined together by tongue and groove using self tapping screws. The color of PVC partition of helghrid Feet (wherever required) should be polymeric fully open able air light doors with process of the polymeric fully open able air light doors with process of the polymeric fully open able air light doors with process of the polymeric fully open able air light doors with process of the polymeric fully open able air light doors with process of the polymeric fully open able air light and the process with process of the polymeric fully open able air light partition with PVC doors and vision panels. The floor shall consists of min. 0.80mm thick PPGI (pre painted galvanized iron) sheet as outleng arrangement etc. BulkITED/JSW or painted galvanized iron) sheet as outleng arrangement with process of approved Texture and color. The floor shall be finally covered with mm thick Vinyl sheet of approved Texture and color. Especially Pressed formed profile of appropriate geometry made of 2.0 mm thick Ms. sheet for Rain water gutter with having min 65mm dia GI rain water down comer connected with L bow. External Doors and Wilndows External Doors and Wilndows Wilndows shall be filed with Amm thick Timbed Class with proper locking arrangement. Safety and the provided in all windows. Window will shall be decided as per the height of work station. All Windows shall be filted with Rain-shee (canopy) made from 1.0 mm thick color coated sheet. Canopy shall be folding type with proper holding and locking arrangement and shall be used as a protective cover to the glazzed window at the time of transportation. All				
polymeric section (syntax or Equivalent) with tongue and grove arrangement. The color of Celling should match with inner wall panels. Partition frame to be made out of anticorrosive painted 25 mm hollow square section of 16 SWG thicknesses as per IS-4923 and double side paneling with polymeric section of minimum thickness 6 mm. These panels are to be joined together by tongue and grovoe using self tapping screws. The color of PVC partition should match with wall panels. Doors for partition of height 6 feet (wherever required) should be polymeric fully open able air tight doors with proper accessories, and locking arrangement etc. Bunk house Cabin Type –A shall have full partition with PVC doors and vision panels. Bottom flooring The floor shall consists of min. 0.80mm thick PPGI (prepainted galvanized iron) sheet as outer most Skin followed by 25mm thick marine plywood conforming to IS: 710. The plywood shall be finally covered with mm thick Timm thick Winyl sheet as outer most Skin followed by 25mm thick marine plywood conforming to IS: 710. The plywood shall be finally covered with mm thick Timm thick Winyl sheet as outer most Skin followed by 25mm thick marine plywood conforming to IS: 710. The plywood shall be finally covered with mm thick Timm thick Winyl sheet as outer most Skin followed by 25mm thick MS sheet for Rain water gutter with having min 65mm die GI rain water down comer connected with L bow. External Doors and Windows 1 Windows Glazed sliding type windows of required dimension as per drawing shall be made out of PVC extruded sections with horizontal two track sliding. Windows shall be fitted with 4mm thick. Titted Glass with proper locking arrangements. Safety aluminum Grills' guard bars of suitable sections shall be provided in all windows. Window will shall be decided as per the height of work station. All Windows shall be fitted with Rain-sheed (canopy) made from 1.0 mm thick Coor coated sheet. Canopy shall be folding type with proper holding and locking arrangement and shall be used as				
grove arrangement. The color of Celling should match with inner wall panels. Partition Partition frame to be made out of anticorrosive painted 25 mm hollow square section of 16 SWC thicknesses as per IS-4923 and double side paneling with polymeric section of minimum thickness of mm. These panels are to be joined together by tongue and groove using self tapping screws. The color of PVC partition should match with wall panels. Doors for partition of height 6 feet (wherever required) should be polymeric fully open able air tight doors with proper accessories, and locking arrangement etc. Bunk house Cabin Type - A shall have full partition with PVC doors and vision panels. The floor shall consists of min. 0.80mm thick PPGI (prepainted galvanized iron) sheet as outer most Skin followed by 25mm thick marine phywood conforming to IS: 710. BLIMITED/JSW or Approved Fauture and color. Rain water gutter Especially Pressed formed profile of appropriate geometry made of 2.0 mm thick M.S. sheet for Rain water gutter with having min 65mm die GIr ain water down comer connected with L bow. External Doors and Wilndows Windows Glazed sliding type windows of required dimension as per drawing shall be made out of PVC extruded sections with horizontal two track sliding. Windows shall be fitted with right of the provided in all windows. Windows shall be fitted with Rain-shed (canopy) made from 1.0 mm thick color coated sheet. Canopy shall be folding they give hip proper holding and locking arrangement and shall be used as a protective cover to the glazed window at the time of transportation. All Main electric supply (Normal 3 Ph 4 wire supply) were accessories shall be made of suitable M.S. Frame covered with 0.5mm thick PPGI sheet both side with PUF insulation (density 40±22 Kg/M²) so as to match with wall panel. High Quality Mortice Lock, Aldrop, Stopper, Handle & other accessories shall be red from with paneling shall be adored or concealed type (refer wall paneling details) for wining. The wiring of Air Conditioner (AC)			•	
Partition Partition frame to be made out of anticorrosive painted 25 mb holow square section of 16 \$Wort bicknesses as per IS-4923 and double side paneling with polymeric section of minimum thickness of mm. These panels are to be joined together by tongue and groove using self tapping screws. The color of PVC partition should match with wall panels. Doors for partition of height 6 feet (wherever required) should be polymeric fully open able air light doors with proper accessories, and locking arrangement etc. Bunk house Cabin Type - A shall have full partition with PVC doors and vision panels.				
mm hollow square section of 16 SWG thicknesses as per IS-4923 and double side paneling with polymeric section of minimum thickness 6 mm. These panels are to be joined together by tongue and groove using self tapping screws. The color of PVC partition should match with wall panels. Doors for partition of height 6 feet (wherever required) should be polymeric fully open able air tight doors with proper accessories, and locking arrangement tet. Bunk house Cabin Type -A shall have full partition with PVC doors and vision panels. The floor shall consists of min. 0.80mm thick PPGI (prepainted galvanized iron) sheet as outer most Skin followed by 25mm thick marine plywood conforming to IS: 710. The plywood shall be finally covered with 1 mm thick Vinyl sheet of approved Texture and color. Rain water gutter Especially Pressed formed profile of appropriate geometry made of 2.0 mm thick M.S sheet for Rain water gutter with having min 65mm dia GI rain water down comer connected with L bow. External Doors and Windows Statemal Doors and Windows Vindows Glazed sliding type windows of required dimension as per drawing shall be made out of PVC extruded sections with horizontal two track sliding. Windows shall be fitted with 4 mm thick Tinted Glass with proper locking arrangement. Safety aluminum Grills/ guard bars of suitable sections shall be provided in all windows. Window sil shall be decided as per the height of work station. All Windows shall be fitted with Rain-shed (canopy) made from 1.0 mm thick color coated sheet. Canopy shall be folding type with proper holding and locking arrangement and shall be used as a protective cover to the glazed window at the time of transportation. M.S. frame shall be made from pressed steel using CR (corrosion resistant) Steel of 1.5mm thick. Door sharps 40 yallow and because of the provided made of concealed type (refer wall paneling details) for wiring. The wiring of Air Conditioner (AC) should be provided in each callo with PUE insulation (density 40±2 Kg/M²) so as to match with				
IS-4923 and double side paneling with polymeric section of minimum thickness 6 mm. These panels are to be joined together by tongue and groove using self tapping screws. The color of PVC portition should match with wall panels.	4	Partition		Ref. drawings
minimum thickness 6 mm. These panels are to be joined together by tongue and groove using self tapping screws. The color of PVC partition should match with wall panels. Doors for partition of height 6 feet (wherever required) should be polymeric fully open able air tight doors with proper accessories, and locking granagement etc. Bunk house Cabin Type —A shall have full partition with PVC doors and vision panels. The floor shall consists of min. 0.80mm thick PPGI (pre painted galvanized iron) sheet as outer most Skin followed by 25mm thick marine plywood conforming to Its. 710. The plywood shall be finally covered with 1mm thick Vinyl sheet of approved Texture and color. Rain water gutter Especially Pressed formed profile of appropriate geometry made of 2.0 mm thick M.S sheet for Rain water gutter with having min 65mm dia GI rain water down comer connected with 1.50w. Especially Pressed formed profile of appropriate geometry made of 2.0 mm thick M.S sheet for Rain water gutter with having min 65mm dia GI rain water down comer connected with 1.50w. Especially Pressed formed profile of appropriate geometry made of 2.0 mm thick M.S sheet for Rain water gutter with having min 65mm dia GI rain water down comer connected with 1.50w. Especially Pressed formed profile of appropriate geometry made of 2.0 mm thick M.S sheet for Rain water gutter with having min 65mm dia GI rain water down comer connected with 1.50w. Taken and the provided in all windows. Windows shall be fitted with 4mm thick Tinted Glass with proper locking arrangement. Safety aluminum Grills' guard bars of suitable sections shall be provided in all windows. Windows will shall be decided as per the height of work station. All Windows shall be fitted with Rain-shed (canopy) made from 1.0 mm thick color coated sheet. Canopy shall be made from pressed steel using CR (corrosion resistant) Steel of 1.5mm thick. Door shutter shall be made from pressed steel using CR (corrosion resistant) Steel of 1.5mm thick. Door shutter shall be made from pressed st			·	
together by tongue and groove using self tapping screws. The color of PVC partition should match with wall panels. Doors for partition of height 6 feet (wherever required) should be polymeric fully open able air light doors with proper accessories, and locking arrangement etc. Bunk house Cabin Type —A shall have full partition with PVC doors and vision panels. The floor shall consists of min. 0.80mm thick PPGI (pre painted galvanized iron) sheet as outer most Skin followed by 25mm thick marine plywood conforming to IS: 710. The plywood shall be finally covered with 1 mm thick Vinyl sheet of approved Fexture and color. Rain water gutter Especially Pressed formed profile of appropriate geometry made of 2.0 mm thick M.S sheet for Rain water gutter with having min 65mm dia GI rain water down comer connected with 1. bow. External Doors and Windows Statemal Doors and Windows 1 Windows Glazed sliding type windows of required dimension as per drawing shall be made out of PVC extruded sections with horizontal two track sliding. Windows shall be fitted with 4mm thick Tinted Glass with proper locking arrangement. Safety aluminum Grills/ guard bars of suitable sections shall be provided in all windows. Window sill shall be decided as per the height of work station. All Windows shall be fitted with Rain-shed (canopy) made from 1.0 mm thick color coated sheet. Canopy shall be folding type with proper holding and locking arrangement and shall be used as a protective cover to the glazed window at the time of transportation. M.S. Frame shall be made from pressed steel using CR (corrosion resistant) Steel of 1.5mm thick. Door shutter shall be made from spressed steel using CR (corrosion resistant) Steel of 1.5mm thick. Door shutter shall be made from spressed steel using CR (corrosion resistant) Steel of 1.5mm thick. Door shutter shall be made from Shall be as per the drawings. Estertical Installation, Telephone and Data cabling: A) Main electrica supply (Normal 3 Ph 4 wire supply) and the composition band of Shall be				
The color of PVC partition should match with wall panels. Doors for partition of height 6 feet (wherever required) should be polymeric fully open able air tight doors with proper accessories, and locking arrangement let. Bunk house Cabin Type —A shall have full partition with PVC doors and vision panels. The floor shall consists of min. 0.80mm thick PPGI (pre painted galvanized iron) sheet as outer most Skin followed by 25mm thick marine phywood conforming to 15: 710. The phywood shall be finally covered with 1mm thick Vinyl sheet of approved Texture and color. Rain water gutter Especially Pressed formed profile of appropriate geometry made of 2.0 mm thick Ms S sheet for Rain water gutter with having min 65mm dia GI rain water down comer connected with L bow. Especially Pressed formed profile of appropriate geometry made of 2.0 mm thick Ms S sheet for Rain water gutter with having min 65mm dia GI rain water down comer connected with L bow. Esternal Doors and Windows 1 Windows Glazed sliding type windows of required dimension as per drawing shall be made out of PVC extruded sections with horizontal two track sliding. Windows shall be fitted with 4mm thick Tinted Glass with proper locking arrangement. Safety aluminum Grills/ guard bars of suitable sections shall be provided in all windows. Window sill shall be decided as per the height of work station. All Windows shall be fitted with Rain-shed (canopy) made from 1.0 mm thick color coated sheet. Canopy shall be fidding type with proper holding and locking arrangement and shall be used as a protective cover to the glazed window at the time of transportation. 2 M.S. Doors M.S. Fame shall be made from pressed steel using CR (corrosion resistant) Steel of 1.5mm thick. Door shutter shall be made from pressed steel using CR (corrosion resistant) Steel of 1.5mm thick. Door shutter shall be made from pressed steel using CR (corrosion resistant) Steel of 1.5mm thick. Door shutter shall be made from the covered with 0.5mm thick provided. Electrical Installation,				
Doors for partition of height 6 feet (wherever required) should be polymeric fully open able air tight doors with proper accessories, and locking arrangement etc. Bunk house Cabin Type - A shall have full partition with PVC doors and vision panels. Septiment of the properties of the properties of the properties of approved the polywood shall be finally covered with 1mm thick PPGI (pre per per partition) provided in all with proper of the provided in each cabin water gutter of approved Texture and color. Rain water gutter				
proper accessories, and locking arrangement etc. Bunk house Cabin Type – A shall have full partition with PVC doors and vision panels. 5 Bottom flooring The floor shall consists of min. 0.80mm thick PPGI (pre painted galvanized iron) sheet as outer most Skin followed by 25mm thick marine phywood conforming to IS: 710. The plywood shall be finally covered with 1mm thick Vinyl sheet of approved Texture and color. 6 Rain water gutter Especially Pressed formed profile of appropriate geometry made of 2.0 mm thick M.S sheet for Rain water gutter with having min 65mm dia GI rain water down comer connected with L bow. External Doors and Windows I Windows Glazed sliding type windows of required dimension as per drawing shall be made out of PVC extruded sections with horizontal two track sliding. Windows shall be fitted with 4mm thick Tinted Glass with proper locking arrangement. Safety aluminum Grills' guard bars of suitable sections shall be provided in all windows. Windows shall be fitted with Rain-shed (canopy) made from 1.0 mm thick color coated sheet. Canopy shall be folded uppe with proper holding and locking arrangement and shall be used as a protective cover to the glazed window at the time of transportation. 2 M.S. Doors M.S. frame shall be made from pressed steel using CR (corrosion resistant) Steel of 1.5mm thick. Door shutter shall be made of suitable M.S. Frame covered with 0.5mm thick. PPGI sheet both side with PUF insulation (density 40±2 Kg/M³) so as to match with wall panel. High Quality Mortice Lock, Aldrop, Stopper, Handle & other accessories shall be Provided. Electrical Installation, Telephone and Data cabiling: A) Main electric supply (Normal 3 Ph 4 wire supply). Main electrical inlet shall be through Cutter, Hammer make IP-55 certified 5 Pin welding socket (63Amp). All wiring shall be row of a recover of the provided in each cabin with 1 No. ELCB along with 63Amps 3 pole MCB and individual MCBs for light, fans and AC. All MCBs shall be housed in metal enclosure. UPS power supply. Main w				
Bottom flooring				
Bottom flooring				
The floor shall consists of min. 0.80mm thick PPE(I (pre painted galvanized iron) sheet as outer most Skin followed by 25mm thick marine plywood conforming to IS: 710. The plywood shall be finally covered with 1 min thick Vinyl sheet of approved Texture and color. Rain water gutter				
painted galvanized iron) sheet as outer most Skin followed by 25mm thick marine plywood conforming to IS: 710. The plywood shall be finally covered with 1mm thick Vinyl sheet of approved Texture and color. Especially Pressed formed profile of appropriate geometry made of 2.0 mm thick M.S sheet for Rain water gutter with having min 65mm dia GI rain water down comer connected with L bow. External Doors and Windows Elazed sliding type windows of required dimension as per drawing shall be made out of PVC extruded sections with horizontal two track sliding. Windows shall be fitted with 4mm thick Tinted Glass with proper locking arrangement. Safety aluminum Grills/ guard bars of suitable sections shall be provided in all windows. Windows shall be fitted with Rain-shed (canopy) made from 1.0 mm thick color coated sheet. Canopy shall be folding type with proper holding and locking arrangement and shall be used as a protective cover to the glazed window at the time of transportation. 2 M.S Doors M.S. Frame shall be made from pressed steel using CR (corrosion resistant) Steel of 1.5mm thick. Door shutter shall be made of suitable M.S. Frame covered with 0.5mm thick. PPGI sheet both side with PUF insulation (density 40±2 Kg/M²) so as to match with wall panel. High Quality Mortice Lock, Aldrop, Stopper, Handle & other accessories shall be Provided. Electrical Installation, Telephone and Data cabling: A) Main electrics supply (Main electrical inlet shall be through Cutler, Hammer make Provided. Electrical Installation, Telephone and Data cabling: Main electrical installation, Telephone and Data cabling: Main electrical installation, Telephone and Data cabling: a) A) Main electric supply (Main with CRS for light, first and account opper wire and cable of concealed type (refer wall paneling details) for wiring. The wiring of Air Conditioner (AC) should be provided in each cabin with 1 No. ELCB along with 63Amps 3 pole MCB and individual MCBs for light, wire should be provided in each cabin wire entry should be from	5	Bottom flooring		PPGL sheet make
by 25mm thick marine plywood conforming to 18: 710. The plywood shall be finally covered with 1mm thick Vinyl sheet of approved Texture and color. Rain water gutter Especially Pressed formed profile of appropriate geometry made of 2.0 mm thick Mr. Sheet for Rain water gutter with having min 65mm dia ofl rain water down comer connected with L bow. External Doors and Windows Glazed sliding type windows of required dimension as per drawing shall be made out of PVC extuded sections with horizontal two track sliding. Windows shall be fitted with 4mm thick Tritled Glass with proper locking arrangement. Safety aluminum Gnills' guard bars of suitable sections shall be provided in all windows. Window slil shall be decided as per the height of work station. All Windows shall be fitted with Rain-shed (canopy) made from 1.0 mm thick color coated sheet. Canopy shall be folding type with proper holding and locking arrangement and shall be used as a protective cover to the glazed window at the time of transportation. M.S. frame shall be made from pressed steel using CR (corrosion resistant) Steel of 1.5mm thick. Door shutter shall be made of suitable M.S. Frame covered with 0.5mm thick. PPGI sheet both side with PUF insulation (density 40½ Kg/M³) so as to match with wall panel. High Quality Mortice Lock. Aldrop, Stopper, Handle & other accessories shall be Provided. A) Main electric supply (Normal 3 Ph 4 wire supply) (Normal 3 Ph 4 wire supply) A) Main electrical inset shall be through Cutler, Hammer make provided in each cabin with 1 No. ELCB along with 63Amps 3 pole MCB and individual MCBs for light, fans and AC. All MCBs shall be housed in metal enclosure. UPS power supply. Main wire entry should be from the opposite side of the Entrance/Door. B) UPS power supply Windows divided be through Cutler, Hammer make IP-55 certified 5 Pin welding socket (63Amp). These sockets should be mounted on outside wall of the cabin and further		Bottom neoring		
6 Rain water gutter Especially Pressed formed profile of appropriate geometry made of 2.0 mm thick M.S sheet for Rain water gutter with having min 65mm dia GI rain water down comer connected with L bow. External Doors and Windows Glazed sliding type windows of required dimension as per drawing shall be made out of PVC extruded sections with horizontal two track sliding. Windows shall be fitted with 4mm thick Tinted Glass with proper locking arrangement. Safety aluminum Grills/ guard bars of suitable sections shall be provided in all windows. Window shall be fitted with Rain-shed (canopy) made from 1.0 mm thick color coated sheet. Canopy shall be folding type with proper holding and locking arrangement and shall be used as a protective cover to the glazed window at the time of transportation. 2 M.S Doors M.S. frame shall be made from pressed steel using CR (corrosion resistant) Steel of 1.5mm thick. Door shutter shall be made of suitable M.S. Frame covered with 0.5mm thick PPGI sheet both side with PUF insulation (density 40±2 Kg/M³) so as to match with wall panel. High Quality Mortice Lock, Aldrop, Stopper, Handle & other accessories shall be Provided. Electrical Installation, Telephone and Data cabling: A) Main electric supply (Normal 3 Ph 4 wire supply) Main electrical inlet shall be through Cutler, Hammer make provided in each cabin with 1 No ELCB along with 63Amps 3 pole MCB and individual MCBs for light, fans and AC. All MCBs shall be housed in metal enclosure. UPS power supply. Main wire entry should be form the opposite side of the Entrance/Door. 2 B) UPS power supply UPS inlets supply shall be through Cutler, Hammer make IP-55 certified 5 Pin welding socket (63Amp). These sockets should be end further various Electrical items shall be read from the capinal further. 55 certified 5 Pin welding socket (63Amp). These sockets should be mounted on outside wall of the cabin and further items shall be read items shall be read items shall be read items shall be read items.				LIMITED/JSW or
Ref. drawings Ref. drawinson Ref. drawinson Ref. drawings Ref. drawings Ref. drawings Ref.				Approved Equivalent.
geometry made of 2.0 mm thick M.S. sheet for Rain water gutter with having min 65mm dia GI rain water down comer connected with L. bow. External Doors and Windows Glazed sliding type windows of required dimension as per drawing shall be made out of PVC extruded sections with horizontal two track sliding. Windows shall be fitted with 4mm thick Tinted Glass with proper locking arrangement. Safety aluminum Grills' guard bars of suitable sections shall be provided in all windows. Windows shall be fitted with Rain-shed (canopy) made from 1.0 mm thick color coated sheet. Canopy shall be folding type with proper holding and locking arrangement and shall be used as a protective cover to the glazed window at the time of transportation. M.S. frame shall be made from pressed steel using CR (corrosion resistant) Steel of 1.5mm thick. Door shutter shall be made of suitable M.S. Frame covered with 0.5mm thick PPGI sheet both side with PUF insulation (density 40±2 Kg/M²) so as to match with wall panel. High Quality Mortice Lock, Aldrop, Stopper, Handle & other accessories shall be Provided. Electrical Installation, Telephone and Data cabling: A) Main electric supply Main electrica supply Main electrica inlet shall be through Cutler, Hammer make IP-55 certified 5 Pin welding socket (63Amp). All wiring shall be done with Finolex / Anchor Make FRLS multi-strand copper wire and cable of concealed type (refer wall paneling details) for wiring. The wiring of Air Conditioner (AC) should be 6 Sqmm and for lighting/Fans should be 4Sqmm. One main incomer distribution board (3Ph-4 wire) should be provided in each cabin with 1 No. ELC. Balong with 63Amps 3 pole MCB and individual MCBs for light, fans and AC. All MCBs shall be housed in metal enclosure. UPS power supply. Main wire entry should be from the opposite side of the Entrance/Door. B) UPS power supply UPS inlets supply shall be through Cutler, Hammer make IP-55 certified 5 Pin welding socket (63Amp). These sockets would be 45 carried of 5 Pin welding socket (63Amp). Thes			of approved Texture and color.	
geometry made of 2.0 mm thick M.S sheet for Rain water gutter with having min 65mm dia Gl rain water down comer connected with L bow. External Doors and Windows Glazed sliding type windows of required dimension as per drawing shall be made out of PVC extruded sections with horizontal two track sliding. Windows shall be fitted with 4mm thick Tinted Glass with proper locking arrangement. Safety aluminum Grills/ guard bars of suitable sections shall be provided in all windows. Windows shall be fitted with Rain-shed (canopy) made from 1.0 mm thick color coated sheet. Canopy shall be folding type with proper holding and locking arrangement and shall be used as a protective cover to the glazed window at the time of transportation. 2 M.S Doors M.S. frame shall be made from pressed steel using CR (corrosion resistant) Steel of 1.5mm thick. Door shutter shall be made of suitable M.S. Frame covered with 0.5mm thick PGI sheet both side with PUF insulation (density 40±2 Kg/M³) so as to match with wall panel. High Quality Mortice Lock, Aldrop, Stopper, Handle & other accessories shall be Provided. Electrical Installation, Telephone and Data cabling: 1 A) Main electric supply (Normal 3 Ph 4 wire supply) Main electrical inlet shall be through Cutter, Hammer make IP-55 certified 5 Pin welding socket (63Amp). All wiring shall be done with Finolex / Anchor Make FRLS multi-strand copper wire and cable of concealed type (refer wall paneling which is a provided in each cabin with 1 No. ELC Balong with 63Amps 3 pole MCB and individual MCBs for light, fans and AC. All MCBs shall be housed in metal enclosure. UPS power supply. Main wire entry should be from the opposite side of the Entrance/Door. 2 B) UPS power supply UPS inlets supply shall be through Cutter, Hammer make IP-55 certified 5 Pin welding socket (63Amp). These sockets should be mounted on outside wall of the cabin and further was hall be read	6	Rain water gutter	Especially Pressed formed profile of appropriate	Ref. drawings
Section Sect				
Windows Glazed sliding type windows of required dimension as per drawing shall be made out of PVC extruded sections with horizontal two track sliding. Windows shall be fitted with 4mm thick Tinted Glass with proper locking arrangement. Safety aluminum Grills' guard bars of suitable sections shall be provided in all windows. Windows shall be fitted with Rain-shed (canopy) made from 1.0 mm thick color coated sheet. Canopy shall be folding type with proper holding and locking arrangement and shall be used as a protective cover to the glazed window at the time of transportation. M.S. frame shall be made from pressed steel using CR (corrosion resistant) Steel of 1.5mm thick. Door shutter shall be made of suitable M.S. Frame covered with 0.5mm thick PCG sheet both side with PUF insulation (density 40±2 Kg/M³) so as to match with wall panel. High Quality Mortice Lock, Aldrop, Stopper, Handle & other accessories shall be Provided. Described Spin welding socket (63Amp). All wring shall be done with Finolex / Anchor Make FRLS multi-strand copper wire and cable of concealed type (refer wall paneling details) for wiring. The wiring of Air Conditioner (AC) should be 6 Sqmm and for lighting/Fans should be 4Sqmm. One main incomer distribution board (3Ph-4 wire) should be provided in each cabin with 1 No. ELCB along with 63Amps 3 pole MCB and individual MCBs for light, fans and AC. All MCBs shall be housed in metal enclosure. UPS power supply. Main wire entry should be from the opposite side of the Entrance/Door. Post certified 5 Pin welding socket (63Amp). These sockets various Electrical items shall be read from the opposite side of the Entrance/Door.				
Windows Glazed sliding type windows of required dimension as per drawing shall be made out of PVC extruded sections with horizontal two track sliding. Windows shall be fitted with 4mm thick Tinted Glass with proper locking arrangement. Safety aluminum Grills' guard bars of suitable sections shall be provided in all windows. Window slil shall be decided as per the height of work station. All Windows shall be fitted with Rain-shed (canopy) made from 1.0 mm thick color coated sheet. Canopy shall be folding type with proper holding and locking arrangement and shall be used as a protective cover to the glazed window at the time of transportation. Windows M.S. frame shall be made from pressed steel using CR (corrosion resistant) Steel of 1.5mm thick. Door shutter shall be made of suitable M.S. Frame covered with 0.5mm thick PPGI sheet both side with PUF insulation (density 40±2 Kg/M³) so as to match with wall panel. High Quality Mortice Lock, Aldrop, Stopper, Handle & other accessories shall be Provided. Description Main electrical inlet shall be through Cutter, Hammer make P-55 certified 5 Pin welding socket (63Amp). All wiring shall be done with Finolex / Anchor Make FRLS multi-strand copper wire and cable of concealed type (refer wall paneling details) for wiring. The wiring of Air Conditioner (AC) should be 6 Sqmm and for lighting/Fans should be 4Sqmm. One main incomer distribution board (39Ph-4 wire) should be provided in each cabin with 1 No. ELCB along with 63Amps 3 pole MCB and individual MCBs for light, fans and AC. All MCBs shall be housed in metal enclosure. UPS power supply. Main wire entry should be from the opposite side of the Entrance/Door. Description PyS inlets supply shall be through Cutter, Hammer make IP-55 certified 5 Pin welding socket (63Amp). These sockets should be mounted on outside wall of the cabin and further litems shall be read				
drawing shall be made out of PVC extruded sections with horizontal two track sliding. Windows shall be fitted with 4mm thick Tinted Glass with proper locking arrangement. Safety aluminum Grills/ guard bars of suitable sections shall be provided in all windows. Window sill shall be decided as per the height of work station. All Windows shall be fitted with Rain-shed (canopy) made from 1.0 mm thick color coated sheet. Canopy shall be folding type with proper holding and locking arrangement and shall be used as a protective cover to the glazed window at the time of transportation. M.S. frame shall be made from pressed steel using CR (corrosion resistant) Steel of 1.5mm thick. Door shutter shall be made of suitable M.S. Frame covered with 0.5mm thick PPGI sheet both side with PUF insulation (density 40±2 Kg/M³) so as to match with wall panel. High Quality Mortice Lock, Aldrop, Stopper, Handle & other accessories shall be Provided. Electrical Installation, Telephone and Data cabling: A) Main electric supply (Normal 3 Ph 4 wire supply) Main electrical inlet shall be through Cutler, Hammer make lP-55 certified 5 Pin welding socket (63Amp). All wiring shall copper wire and cable of concealed type (refe wall paneling details) for wiring. The wiring of Air Conditioner (AC) should be 6 Sqmm and for lighting/Fans should be 4Sqmm. One main incomer distribution board (3Ph-4 wire) should be provided in each cabin with 1 No. ELCB along with 63Amps 3 pole MCB and individual MCBs for light, fans and AC. All MCBs shall be housed in metal enclosure. UPS power supply. Main wire entry should be from the opposite side of the Entrance/Door. B) UPS power supply UPS inlets supply shall be through Cutler, Hammer make IP-55 certified 5 Pin welding socket (63Amp). These sockets should be mounted on outside wall of the cabin and further items shall be read	1	Windows		
horizontal two track sliding, Windows shall be fitted with 4mm thick Tinted Glass with proper locking arrangement. Safety aluminum Grills/ guard bars of suitable sections shall be provided in all windows. Window sill shall be decided as per the height of work station. All Windows shall be fitted with Rain-shed (canopy) made from 1.0 mm thick color coated sheet. Canopy shall be folding type with proper holding and locking arrangement and shall be used as a protective cover to the glazed window at the time of transportation. 2 M.S Doors M.S. frame shall be made from pressed steel using CR (corrosion resistant) Steel of 1.5mm thick. Doors shutter shall be made of suitable M.S. Frame covered with 0.5mm thick PPGI sheet both side with PUF insulation (density 40±2 Kg/M³) so as to match with wall panel. High Quality Mortice Lock, Aldrop, Stopper, Handle & other accessories shall be Provided. 2 A) Main electric supply (Normal 3 Ph 4 wire supply) A) Main electrical inlet shall be through Cutler, Hammer make IP-55 certified 5 Pin welding socket (63Amp). All wiring shall be done with Finolex / Anchor Make FRLS multi-strand copper wire and cable of concealed type (refer wall paneling details) for wiring. The wiring of Air Conditioner (AC) should be 6 Sqmm and for lighting/Fans should be 4Sqmm. One main incomer distribution board (3Ph-4 wire) should be provided in each cabin with 1 No. ELCB along with 63Amps 3 pole MCB and individual MCBs for light, fans and AC. All MCBs shall be housed in metal enclosure. UPS power supply. Main wire entry should be from the opposite side of the Entrance/Door. 2 B) UPS power supply UPS inlets supply shall be through Cutler, Hammer make IP-55 certified 5 Pin welding socket (63Amp). These sockets should be mounted on outside wall of the cabin and further in the shall be read in the shall be read in the cabin and further in the cabin and further in the shall be read in the shall be read in the cabin and further in	'	VVIIIdows		
thick Tinted Glass with proper locking arrangement. Safety aluminum Grills/ guard bars of suitable sections shall be provided in all windows. Window sill shall be decided as per the height of work station. All Windows shall be fitted with Rain-shed (canopy) made from 1.0 mm thick color coated sheet. Canopy shall be folding type with proper holding and locking arrangement and shall be used as a protective cover to the glazed window at the time of transportation. 2 M.S. Doors M.S. frame shall be made from pressed steel using CR (corrosion resistant) Steel of 1.5mm thick. Door shutter shall be made of suitable M.S. Frame covered with 0.5mm thick PPGI sheet both side with PUF insulation (density 40±2 Kg/M³) so as to match with wall panel. High Quality Mortice Lock, Aldrop, Stopper, Handle & other accessories shall be Provided. Electrical Installation, Telephone and Data cabling: A) Main electrics supply (Normal 3 Ph 4 wire supply) Wain electrical inlet shall be through Cutter, Hammer make IP-55 certified 5 Pin welding socket (63Amp). All wiring shall be done with Finolex / Anchor Make FRLS multi-strand copper wire and cable of concealed type (refer wall paneling details) for wiring. The wiring of Air Conditioner (AC) should be 6 Sqmm and for lighting/Fans should be 4Sqmm. One main incomer distribution board (3Ph-4 wire) should be provided in each cabin with 1 No. ELCB along with 63Amps 3 pole MCB and individual MCBs for light, fans and AC. All MCBs shall be housed in metal enclosure. UPS power supply. Main wire entry should be from the opposite side of the Entrance/Door. 2 B) UPS power supply UPS inlets supply shall be through Cutler, Hammer make IP-55 certified 5 Pin welding socket (63Amp). These sockets should be mounted on outside wall of the cabin and further litems shall be read				
provided in all windows. Window sill shall be decided as per the height of work station. All Windows shall be fitted with Rain-shed (canopy) made from 1.0 mm thick color coated sheet. Canopy shall be folding type with proper holding and locking arrangement and shall be used as a protective cover to the glazed window at the time of transportation. 2 M.S Doors M.S. frame shall be made from pressed steel using CR (corrosion resistant) Steel of 1.5mm thick. Door shutter shall be made of suitable M.S. Frame covered with 0.5mm thick PPGI sheet both side with PUF insulation (density 40±2 Kg/M²) so as to match with wall panel. High Quality Mortice Lock, Aldrop, Stopper, Handle & other accessories shall be Provided. Electrical Installation, Telephone and Data cabling: A) Main electrics supply (Normal 3 Ph 4 wire supply) Main electrical inlet shall be through Cutler, Hammer make of various Electrical intension of various from Annexure-A copper wire and cable of concealed type (refer wall paneling details) for wiring. The wiring of Air Conditioner (AC) should be 6 Sqmm and for lighting/Fans should be 4Sqmm. One main incomer distribution board (3Ph-4 wire) should be provided in each cabin with 1 No. ELCB along with 63Amps 3 pole MCB and individual MCBs for light, fans and AC. All MCBs shall be housed in metal enclosure. UPS power supply. Main wire entry should be from the opposite side of the Entrance/Door. 2 B) UPS power supply UPS inlets supply shall be through Cutler, Hammer make IP-55 certified 5 Pin welding socket (63Amp). These sockets should be mounted on outside wall of the cabin and further items shall be read			thick Tinted Glass with proper locking arrangement. Safety	,
the height of work station. All Windows shall be fitted with Rain-shed (canopy) made from 1.0 mm thick color coated sheet. Canopy shall be folding type with proper holding and locking arrangement and shall be used as a protective cover to the glazed window at the time of transportation. 2 M.S Doors M.S. frame shall be made from pressed steel using CR (corrosion resistant) Steel of 1.5mm thick. Door shutter shall be made of suitable M.S. Frame covered with 0.5mm thick PPGI sheet both side with PUF insulation (density 40±2 Kg/M³) so as to match with wall panel. High Quality Mortice Lock, Aldrop, Stopper, Handle & other accessories shall be Provided. Electrical Installation, Telephone and Data cabling: 1 A) Main electric supply (Normal 3 Ph 4 wire supply) (Normal 3 Ph 4 wire				
Rain-shed (canopy) made from 1.0 mm thick color coated sheet. Canopy shall be folding type with proper holding and locking arrangement and shall be used as a protective cover to the glazed window at the time of transportation. 2 M.S Doors M.S. frame shall be made from pressed steel using CR (corrosion resistant) Steel of 1.5mm thick. Door shutter shall be made of suitable M.S. Frame covered with 0.5mm thick PPGI sheet both side with PUF insulation (density 40±2 Kg/M³) so as to match with wall panel. High Quality Mortice Lock, Aldrop, Stopper, Handle & other accessories shall be Provided. Electrical Installation, Telephone and Data cabling: Main electrical inlet shall be through Cutler, Hammer make IP-55 certified 5 Pin welding socket (63Amp). All wiring shall be done with Finolex / Anchor Make FRLS multi-strand copper wire and cable of concealed type (refer wall paneling details) for wiring. The wiring of Air Conditioner (AC) should be 6 Sqmm and for lighting/Fans should be 4Sqmm. One main incomer distribution board (3Ph-4 wire) should be provided in each cabin with 1 No. ELCB along with 63Amps 3 pole MCB and individual MCBs for light, fans and AC. All MCBs shall be housed in metal enclosure. UPS power supply. Main wire entry should be from the opposite side of the Entrance/Door. 2 B) UPS power supply UPS inlets supply shall be through Cutler, Hammer make IP-55 certified 5 Pin welding socket (63Amp). These sockets should be mounted on outside wall of the cabin and further			· ·	
sheet. Canopy shall be folding type with proper holding and locking arrangement and shall be used as a protective cover to the glazed window at the time of transportation. 2 M.S Doors M.S. frame shall be made from pressed steel using CR (corrosion resistant) Steel of 1.5mm thick. Door shutter shall be made of suitable M.S. Frame covered with 0.5mm thick PPGI sheet both side with PUF insulation (density 40±2 Kg/M³) so as to match with wall panel. High Quality Mortice Lock, Aldrop, Stopper, Handle & other accessories shall be Provided. Electrical Installation, Telephone and Data cabling: A) Main electric supply (Normal 3 Ph 4 wire supply) A) Main electrical inlet shall be through Cutter, Hammer make IP-55 certified 5 Pin welding socket (63Amp). All wiring shall be done with Finolex / Anchor Make FRLS multi-strand copper wire and cable of concealed type (refer wall paneling details) for wiring. The wiring of Air Conditioner (AC) should be 6 Sqmm and for lighting/Fans should be 4Sqmm. One main incomer distribution board (3Ph-4 wire) should be provided in each cabin with 1 No. ELCB along with 63Amps 3 pole MCB and individual MCBs for light, fans and AC. All MCBs shall be housed in metal enclosure. UPS power supply. Main wire entry should be from the opposite side of the Entrance/Door. B) UPS power supply UPS inlets supply shall be through Cutler, Hammer make IP-55 certified 5 Pin welding socket (63Amp). These sockets should be mounted on outside wall of the cabin and further items shall be read item				
locking arrangement and shall be used as a protective cover to the glazed window at the time of transportation. M.S. frame shall be made from pressed steel using CR (corrosion resistant) Steel of 1.5mm thick. Door shutter shall be made of suitable M.S. Frame covered with 0.5mm thick PPGI sheet both side with PUF insulation (density 40±2 Kg/M³) so as to match with wall panel. High Quality Mortice Lock, Aldrop, Stopper, Handle & other accessories shall be Provided. Electrical Installation, Telephone and Data cabling: Main electrical inlet shall be through Cutler, Hammer make IP-55 certified 5 Pin welding socket (63Amp). All wiring shall be done with Finolex / Anchor Make FRLS multi-strand copper wire and cable of concealed type (refer wall paneling details) for wiring. The wiring of Air Conditioner (AC) should be 6 Sqmm and for lighting/Fans should be 4Sqmm. One main incomer distribution board (3Ph-4 wire) should be provided in each cabin with 1 No. ELCB along with 63Amps 3 pole MCB and individual MCBs for light, fans and AC. All MCBs shall be housed in metal enclosure. UPS power supply. Main wire entry should be from the opposite side of the Entrance/Door. B) UPS power supply UPS inlets supply shall be through Cutler, Hammer make IP-55 certified 5 Pin welding socket (63Amp). These sockets should be mounted on outside wall of the cabin and further items shall be read from shall be read to all the shall be read to all the shall be read from the opposite side of the Entrance/Door.				
M.S. frame shall be made from pressed steel using CR (corrosion resistant) Steel of 1.5mm thick. Door shutter shall be made of suitable M.S. Frame covered with 0.5mm thick PPGI sheet both side with PUF insulation (density 40±2 Kg/M³) so as to match with wall panel. High Quality Mortice Lock, Aldrop, Stopper, Handle & other accessories shall be Provided. A) Main electric supply (Normal 3 Ph 4 wire supply) Main electrical inlet shall be through Cutler, Hammer make be done with Finolex / Anchor Make FRLS multi-strand copper wire and cable of concealed type (refer wall paneling details) for wiring. The wiring of Air Conditioner (AC) should be 6 Sqmm and for lighting/Fans should be 4Sqmm. One main incomer distribution board (3Ph-4 wire) should be provided in each cabin with 1 No. ELCB along with 63Amps 3 pole MCB and individual MCBs for light, fans and AC. All MCBs shall be housed in metal enclosure. UPS power supply. Main wire entry should be from the opposite side of the Entrance/Door. B) UPS power supply UPS inlets supply shall be through Cutler, Hammer make IP-55 certified 5 Pin welding socket (63Amp). These sockets should be mounted on outside wall of the cabin and further items shall be read item				
(corrosion resistant) Steel of 1.5mm thick. Door shutter shall be made of suitable M.S. Frame covered with 0.5mm thick PPGI sheet both side with PUF insulation (density 40±2 Kg/M³) so as to match with wall panel. High Quality Mortice Lock, Aldrop, Stopper, Handle & other accessories shall be Provided. A) Main electric supply (Normal 3 Ph 4 wire supply) Main electrical inlet shall be through Cutler, Hammer make IP-55 certified 5 Pin welding socket (63Amp). All wiring shall be done with Finolex / Anchor Make FRLS multi-strand copper wire and cable of concealed type (refer wall panelling details) for wiring. The wiring of Air Conditioner (AC) should be 6 Sqmm and for lighting/Fans should be 4Sqmm. One main incomer distribution board (3Ph-4 wire) should be provided in each cabin with 1 No. ELCB along with 63Amps 3 pole MCB and individual MCBs for light, fans and AC. All MCBs shall be housed in metal enclosure. UPS power supply. Main wire entry should be from the opposite side of the Entrance/Door. B) UPS power supply UPS inlets supply shall be through Cutler, Hammer make IP-55 certified 5 Pin welding socket (63Amp). These sockets should be mounted on outside wall of the cabin and further litems shall be read items shall				
be made of suitable M.S. Frame covered with 0.5mm thick PPGI sheet both side with PUF insulation (density 40±2 Kg/M³) so as to match with wall panel. High Quality Mortice Lock, Aldrop, Stopper, Handle & other accessories shall be Provided. Condition	2	M.S Doors		
PPGI sheet both side with PUF insulation (density 40±2 Kg/M³) so as to match with wall panel. High Quality Mortice Lock, Aldrop, Stopper, Handle & other accessories shall be Provided. Electrical Installation, Telephone and Data cabling: A) Main electric supply (Normal 3 Ph 4 wire supply) Main electrical inlet shall be through Cutler, Hammer make IP-55 certified 5 Pin welding socket (63Amp). All wiring shall be done with Finolex / Anchor Make FRLS multi-strand copper wire and cable of concealed type (refer wall paneling details) for wiring. The wiring of Air Conditioner (AC) should be 6 Sqmm and for lighting/Fans should be 4Sqmm. One main incomer distribution board (3Ph-4 wire) should be provided in each cabin with 1 No. ELCB along with 63Amps 3 pole MCB and individual MCBs for light, fans and AC. All MCBs shall be housed in metal enclosure. UPS power supply. Main wire entry should be from the opposite side of the Entrance/Door. 2 B) UPS power supply UPS inlets supply shall be through Cutler, Hammer make IP-55 certified 5 Pin welding socket (63Amp). These sockets should be mounted on outside wall of the cabin and further				'
Kg/M³) so as to match with wall panel. High Quality Mortice Lock, Aldrop, Stopper, Handle & other accessories shall be Provided. Electrical Installation, Telephone and Data cabling: A) Main electric supply (Normal 3 Ph 4 wire supply) Main electrical inlet shall be through Cutler, Hammer make leading supply) P-55 certified 5 Pin welding socket (63Amp). All wiring shall be done with Finolex / Anchor Make FRLS multi-strand copper wire and cable of concealed type (refer wall paneling details) for wiring. The wiring of Air Conditioner (AC) should be 6 Sqmm and for lighting/Fans should be 4Sqmm. One main incomer distribution board (3Ph-4 wire) should be provided in each cabin with 1 No. ELCB along with 63Amps 3 pole MCB and individual MCBs for light, fans and AC. All MCBs shall be housed in metal enclosure. UPS power supply. Main wire entry should be from the opposite side of the Entrance/Door. B) UPS power supply UPS inlets supply shall be through Cutler, Hammer make IP-55 certified 5 Pin welding socket (63Amp). These sockets should be mounted on outside wall of the cabin and further litems shall be read items shall be read items.				
Electrical Installation, Telephone and Data cabling: A) Main electric supply (Normal 3 Ph 4 wire supply) Be done with Finolex / Anchor Make FRLS multi-strand copper wire and cable of concealed type (refer wall paneling details) for wiring. The wiring of Air Conditioner (AC) should be 6 Sqmm and for lighting/Fans should be 4Sqmm. One main incomer distribution board (3Ph-4 wire) should be provided in each cabin with 1 No. ELCB along with 63Amps 3 pole MCB and individual MCBs for light, fans and AC. All MCBs shall be housed in metal enclosure. UPS power supply. Main wire entry should be from the opposite side of the Entrance/Door. B) UPS power supply UPS inlets supply shall be through Cutler, Hammer make IP-55 certified 5 Pin welding socket (63Amp). These sockets should be mounted on outside wall of the cabin and further			· · ·	
A) Main electric supply (Normal 3 Ph 4 wire supply) A) Main electrical inlet shall be through Cutler, Hammer make led one with Finolex / Anchor Make FRLS multi-strand copper wire and cable of concealed type (refer wall paneling details) for wiring. The wiring of Air Conditioner (AC) should be 6 Sqmm and for lighting/Fans should be 4Sqmm. One main incomer distribution board (3Ph-4 wire) should be provided in each cabin with 1 No. ELCB along with 63Amps 3 pole MCB and individual MCBs for light, fans and AC. All MCBs shall be housed in metal enclosure. UPS power supply. Main wire entry should be from the opposite side of the Entrance/Door. B) UPS power supply UPS inlets supply shall be through Cutler, Hammer make IP-55 certified 5 Pin welding socket (63Amp). These sockets should be mounted on outside wall of the cabin and further			Lock, Aldrop, Stopper, Handle & other accessories shall be	
A) Main electric supply (Normal 3 Ph 4 wire supply) Main electrical inlet shall be through Cutler, Hammer make IP-55 certified 5 Pin welding socket (63Amp). All wiring shall be done with Finolex / Anchor Make FRLS multi-strand copper wire and cable of concealed type (refer wall paneling details) for wiring. The wiring of Air Conditioner (AC) should be 6 Sqmm and for lighting/Fans should be 4Sqmm. One main incomer distribution board (3Ph-4 wire) should be provided in each cabin with 1 No. ELCB along with 63Amps 3 pole MCB and individual MCBs for light, fans and AC. All MCBs shall be housed in metal enclosure. UPS power supply. Main wire entry should be from the opposite side of the Entrance/Door. B) UPS power supply UPS inlets supply shall be through Cutler, Hammer make IP-55 certified 5 Pin welding socket (63Amp). These sockets should be mounted on outside wall of the cabin and further		PI.		
(Normal 3 Ph 4 wire supply) IP-55 certified 5 Pin welding socket (63Amp). All wiring shall be done with Finolex / Anchor Make FRLS multi-strand copper wire and cable of concealed type (refer wall paneling details) for wiring. The wiring of Air Conditioner (AC) should be 6 Sqmm and for lighting/Fans should be 4Sqmm. One main incomer distribution board (3Ph-4 wire) should be provided in each cabin with 1 No. ELCB along with 63Amps 3 pole MCB and individual MCBs for light, fans and AC. All MCBs shall be housed in metal enclosure. UPS power supply. Main wire entry should be from the opposite side of the Entrance/Door. 2 B) UPS power supply UPS inlets supply shall be through Cutler, Hammer make IP-55 certified 5 Pin welding socket (63Amp). These sockets should be mounted on outside wall of the cabin and further items shall be read	1			Quantities of
be done with Finolex / Anchor Make FRLS multi-strand copper wire and cable of concealed type (refer wall paneling details) for wiring. The wiring of Air Conditioner (AC) should be 6 Sqmm and for lighting/Fans should be 4Sqmm. One main incomer distribution board (3Ph-4 wire) should be provided in each cabin with 1 No. ELCB along with 63Amps 3 pole MCB and individual MCBs for light, fans and AC. All MCBs shall be housed in metal enclosure. UPS power supply. Main wire entry should be from the opposite side of the Entrance/Door. 2 B) UPS power supply UPS inlets supply shall be through Cutler, Hammer make IP-55 certified 5 Pin welding socket (63Amp). These sockets should be mounted on outside wall of the cabin and further items shall be read	'			
copper wire and cable of concealed type (refer wall paneling details) for wiring. The wiring of Air Conditioner (AC) should be 6 Sqmm and for lighting/Fans should be 4Sqmm. One main incomer distribution board (3Ph-4 wire) should be provided in each cabin with 1 No. ELCB along with 63Amps 3 pole MCB and individual MCBs for light, fans and AC. All MCBs shall be housed in metal enclosure. UPS power supply. Main wire entry should be from the opposite side of the Entrance/Door. 2 B) UPS power supply UPS inlets supply shall be through Cutler, Hammer make IP-55 certified 5 Pin welding socket (63Amp). These sockets should be mounted on outside wall of the cabin and further items shall be read				
be 6 Sqmm and for lighting/Fans should be 4Sqmm. One main incomer distribution board (3Ph-4 wire) should be provided in each cabin with 1 No. ELCB along with 63Amps 3 pole MCB and individual MCBs for light, fans and AC. All MCBs shall be housed in metal enclosure. UPS power supply. Main wire entry should be from the opposite side of the Entrance/Door. 2 B) UPS power supply UPS inlets supply shall be through Cutler, Hammer make IP-55 certified 5 Pin welding socket (63Amp). These sockets should be mounted on outside wall of the cabin and further items shall be read		1,	copper wire and cable of concealed type (refer wall paneling	from Annexure-A
main incomer distribution board (3Ph-4 wire) should be provided in each cabin with 1 No. ELCB along with 63Amps 3 pole MCB and individual MCBs for light, fans and AC. All MCBs shall be housed in metal enclosure. UPS power supply. Main wire entry should be from the opposite side of the Entrance/Door. 2 B) UPS power supply UPS inlets supply shall be through Cutler, Hammer make IP-55 certified 5 Pin welding socket (63Amp). These sockets should be mounted on outside wall of the cabin and further items shall be read				
provided in each cabin with 1 No. ELCB along with 63Amps 3 pole MCB and individual MCBs for light, fans and AC. All MCBs shall be housed in metal enclosure. UPS power supply. Main wire entry should be from the opposite side of the Entrance/Door. B) UPS power supply UPS inlets supply shall be through Cutler, Hammer make IP-55 certified 5 Pin welding socket (63Amp). These sockets should be mounted on outside wall of the cabin and further items shall be read				
3 pole MCB and individual MCBs for light, fans and AC. All MCBs shall be housed in metal enclosure. UPS power supply. Main wire entry should be from the opposite side of the Entrance/Door. B) UPS power supply UPS inlets supply shall be through Cutler, Hammer make IP-55 certified 5 Pin welding socket (63Amp). These sockets should be mounted on outside wall of the cabin and further items shall be read				
MCBs shall be housed in metal enclosure. UPS power supply. Main wire entry should be from the opposite side of the Entrance/Door. 2 B) UPS power supply UPS inlets supply shall be through Cutler, Hammer make IP-55 certified 5 Pin welding socket (63Amp). These sockets should be mounted on outside wall of the cabin and further items shall be read				
the Entrance/Door. 2 B) UPS power supply UPS inlets supply shall be through Cutler, Hammer make IP- 55 certified 5 Pin welding socket (63Amp). These sockets should be mounted on outside wall of the cabin and further items shall be read				
2 B) UPS power supply UPS inlets supply shall be through Cutler, Hammer make IP- 55 certified 5 Pin welding socket (63Amp). These sockets should be mounted on outside wall of the cabin and further items shall be read				f
55 certified 5 Pin welding socket (63Amp). These sockets should be mounted on outside wall of the cabin and further items shall be read			the Entrance/Door.	
55 certified 5 Pin welding socket (63Amp). These sockets should be mounted on outside wall of the cabin and further items shall be read	2	B) UPS nower supply	LIPS inlets supply shall be through Cutler. Hammer make ID-	Quantities of
should be mounted on outside wall of the cabin and further items shall be read		D) Of O power suppry		
connected to Main distribution board inside the cabin having from Annexure-A			should be mounted on outside wall of the cabin and further	items shall be read
			connected to Main distribution board inside the cabin having	from Annexure-A

ENQUIRY NO.XI014 E DT. 22.07.2011 DUE DATE: 12.08.2011

		<u> </u>			
3	C)Telephone and Network cabling	provision of incoming MCB 32Amps, 2 Pole and MCB at each sitting arrangement including internal wiring from Main Board up to the switch socket for further distribution. All wiring shall be done with Finolex/Anchor Make FRLS multistrand copper wire 2.5mm square cable of open type with using proper channel (PVC - C section channel) closer for wiring. One (1) No. Junction Box with Lock and Key should be mounted outside the Cabin for connecting to external telephone lines and network data cables. The junction Box should have provision for connecting at least four telephone lines and for connecting external network cabling type CAT-6. The cable should be terminated on Krone connectors and should be wired to the Telephone, outlets inside the cable. One (1) No. 8 port D-Link switch should be mounted inside the cabin and further internal cabling shall be done with CAT-6 cables. Cabling from D-Link switch to users nodes is within the scope of work.	Quantities of various Electrical items shall be read from Annexure-A		
4	Electrical fittings	Same as old description shall be followed, only fridge and their fitting and fixtures are deleted from Bidder's scope.	Quantities of various Electrical items shall be read from Annexure-A		
	Furniture for work station				
1	(A) Tables	Layout and dimensions shall be as per drawings. Materials shall be extruded polymeric panel (PVC) as per IS 10151/1982 of 25mm thick with proper supporting legs and clamping arrangement with wall frame			
	(B) Godrej Chairs, Sofa, Centre Table	1) Regency Model 7001 D-1 No. 2) Serena Model 9002 A-1 No. 3) Regency Model PCH 7003D-06 Nos. 4) Sofa Petal Series F33 - 1 No.	Quantity mentioned for each Porta Cabin		
2	Overhead cabinets	As per Drg. Materials shall be extruded polymeric panel (PVC) as per IS 10151/1982 of 25mm thick with proper locking and fixing arrangement with wall frame. It should be strange enough to take load of files. Safety appliances			
1					
'		1 No. Portable Fire Extinguisher shall be in each cabin at appropriate location with all fitting and fixtures. The pressure capacity of Fire Extinguisher shall be 2.5 Kgf.			

A tentative BOQ for various electrical items against different types of bunk houses as follows. It is the responsibility of the bidder to enumerate the required quantity as per their electrical design.

Annexure-A

Sl.no	Item Name	Unit	Bunk House type A
1	Air conditioner -1.5T capacity	Nos	2
2	Tube light CFL type	Nos	3
3	Fan	Nos	2
4	Main power distribution board.	Nos	1
5	UPS power distribution board.	Nos	1
6	Main power inlet 5 pin socket.	Nos	2
7	Telephone and network crone box	Nos	1
8	Bulk head fitting CFL type.	Nos	1
9	24 port D-Link switch for networking.	Nos	1
10	Computer, UPS, telephone and networking point	Nos	2

DUE DATE: 12.08.2011 **ENQUIRY NO.XI014 E** DT. 22.07.2011

Shop Inspection:

Periodical inspection of process at least at three stages – 1st during welding process of main frame for inspection of materials & welding quality & 2nd at internal & external paneling & insulation and 3rd at Furnishing, electrocutions & finish paint. Minor modifications, if any, required to be carried out which will be specified during the stage of inspection/manufacturing process. Rates quoted should consider this aspect also.

Testing of CSP Panel

Successful bidder (after award of tender) shall submit the test certificates like Fire test & Impact test for CSP panels from recognized Govt institution / CBRI (Central Building Research Institute, Roorkee). The mentioned tests are indicative only. Any additional tests relevant to this product shall be submitted. The certificates shall be submitted during manufacturing of CSP panels.

Marking:

Each Unit shall be marked externally with: Name & address of Manufacturer Type and Serial No. Max. Permissible distributed floor loads Max. External size Max. Weight of unit for lifting Position of lifting & anchoring points

BHEL Logo: The Main Door should carry a logo of BHEL made of stainless embossed.

Warrantv:

Suitability of stacking

- 1 year for workmanship & defective materials
- 3 years for painting as per European scale of rusting RE3 (10% of total surface). However normal wear & tear and damage by external impact etc. are not covered.

First installation at site and after sale service:

During the first installation(for each cabin) at site, manufacturers shall depute their technician to check placement of cabins over the pedestal, all fittings, fixtures and electrical installation ,AC etc. and to ensure successful operation of Bunk House at site. Minor wear and tear occurred during transit which involves denting and painting shall be done by Manufacture free of

Warranty/Guarantee for electrical installation/Equipments like Air conditioner (AC), Fans, Lighting shall either be extended in the name of BHEL from original supplier of Equipment or to be taken care by the supplier of the Bunk House as a part of Warranty.

Note:

The specifications provided herein are only indicative and, manufacturer shall be overall responsible for detail Design, Engineering, drawings, finishing, internal furnishing, electrification & fixtures and proper functioning of the Bunk houses.


ANNEXURE-II


Sl.No.	CONSIGNEE ADDRESS	
	BHEL SITE OFFICE	
01	2X600 MW DBPL (DAINIK BASKAR POWER LTD)	
01	NEAR VILL.BARADARSHA,	
	DIST.JANJGIR – CHAMPA (CHATTISGARH)	
	BHEL SITE OFFICE	
02	2X500 MW STPS, NTPC LIMITED	
02	TEHSIL-MAUDA, DIST-NAGPUR	
	MAHARASHTRA-441104	
	BHEL SITE OFFICE	
	PLOT NO. A-1, MIDC	
03	MUSALGAON, SINNAR,	
	NASIK.	
	MAHARASTRA	
	BHEL SITE OFFICE	
04	PLOT NO. D2, ADDITIONAL INDUSTRIAL AREA,	
04	NANDGAONPETH, DISTT: AMRAVATI,	
	MAHARASHTRA- 444 901	

DGM/PUR

ENQUIRY NO.XI014 E DT. 22.07.2011 DUE DATE: 12.08.2011

ANNEXURE-III





BHARAT HEAVY ELECTRICALS LIMITED PSWR-NAGPUR-440001 DT. 22.07.2011

ENQUIRY NO.XI014 E

