



भारत हेवी इलेक्ट्रिकल्स लिमिटेड

(भारत सरकार का उपक्रम)

BHARAT HEAVY ELECTRICALS LIMITED

(A Govt. of India Undertaking)

TCN - 01

Ref: PSER:SCT:SPT-F2420:TCN-01

Date: 11-03-2026

Sub	Tender Change Notice (TCN) - 01.	
Job	PROVIDING 1 NO. HLHR (HEAVY LIFT HIGH REACH) HYDRAULIC CRAWLER CRANE HAVING LATTICE BOOM & LUFFING JIB WITH CRITICAL LOAD LIFTING CAPACITY OF 203MT (MINIMUM) BELOW HOOK AT AROUND 18M (MINIMUM) RADIUS WITH MAIN BOOM AND TO OBTAIN CLEAR HEIGHT BELOW HOOK OF 115M (MINIMUM) ABOVE GROUND LEVEL ON MONTHLY RENTAL BASIS AT BHEL-PSER, 1X800 MW NTPC SIPAT STPP STAGE-III PROJECT, PO- UJJWAL NAGAR, SIPAT, DIST - BILASPUR, CHHATTISGARH, PIN - 495555.	
Ref	1.0	Tender no. PSER:SCT:SPT-F2420:26
	2.0	BHEL's NIT, vide reference no. PSER:SCT:SPT-F2420:11402 Date: 04-03-2026
	3.0	All other pertinent issues till date.

With reference to above, following points/documents, relevant to tender, may please be noted and complied with while submitting the offer.

1. The clarifications to bidder's queries are attached as Annexure-A1 to this TCN.
2. Revised 'No deviation certificate' is attached. Bidder to submit 'No deviation certificate' as per attached format only.
3. All other terms & conditions shall remain unchanged.

Thanking you,

Yours faithfully,
for BHARAT HEAVY ELECTRICALS LTD.

Manager / SCT

Encl.: As Above

पावर सेक्टर पूर्वी क्षेत्र (मुख्यालय)

POWER SECTOR EASTERN REGION, DJ-9/1, SALT LAKE CITY, KOLKATA - 700 091

फैक्स/Fax : (033) 23211960

फोन/Phone : बोर्ड/EPABX : (033) 2339 8000

FORMAT FOR NO DEVIATION CERTIFICATE
(To be submitted in the bidder's letter head)

BHARAT HEAVY ELECTRICALS LIMITED,
Power Sector - Eastern Region,
Plot no 9/1, DJ Block, Sector – II, Salt Lake City,
Kolkata – 700 091

Sub	No Deviation Certificate.	
Job	PROVIDING 1 NO. HLHR (HEAVY LIFT HIGH REACH) HYDRAULIC CRAWLER CRANE HAVING LATTICE BOOM & LUFFING JIB WITH CRITICAL LOAD LIFTING CAPACITY OF 203MT (MINIMUM) BELOW HOOK AT AROUND 18M (MINIMUM) RADIUS WITH MAIN BOOM AND TO OBTAIN CLEAR HEIGHT BELOW HOOK OF 115M (MINIMUM) ABOVE GROUND LEVEL ON MONTHLY RENTAL BASIS AT BHEL-PSER, 1X800 MW NTPC SIPAT STPP STAGE-III PROJECT, PO- UJJWAL NAGAR, SIPAT, DIST – BILASPUR, CHHATTISGARH, PIN - 495555.	
Ref	1.0	Tender no. PSER:SCT:SPT-F2420:26
	2.0	BHEL's NIT, vide reference no. PSER:SCT:SPT-F2420:11402 Date: 04-03-2026
	3.0	BHEL's TCN-01, vide reference no. PSER:SCT:SPT-F2420:TCN-01 Date: 11-03-2026.
	4.0	All other pertinent issues till date.

Dear Sir/Madam,

With reference to above, this is to confirm that as per tender conditions, we have visited site before submission of our offer and noted the job content & site conditions etc. We also confirm that we have not changed/ modified the tender documents as appeared in the website/ issued by you and in case of such observance at any stage, it shall be treated as null and void.

We hereby confirm that we have not taken any deviation from tender clauses together with other references as enumerated in the above referred NIT. We hereby confirm our unqualified acceptance to all terms & conditions, unqualified compliance to technical specification, integrity pact (if applicable) and acceptance to reverse auctioning process.

In the event of observance of any deviation in any part of our offer at a later date whether implicit or explicit, the deviations shall stand null & void.

We confirm to have submitted/uploaded offer/documents in accordance with tender instructions with acceptance of the terms & conditions of the tender by us and as per aforesaid references.

Thanking you,

Yours faithfully,

(Signature, date & seal of authorized
representative of the bidder)

Job: PROVIDING 1 NO. HLHR (HEAVY LIFT HIGH REACH) HYDRAULIC CRAWLER CRANE HAVING LATTICE BOOM & LUFFING JIB WITH CRITICAL LOAD LIFTING CAPACITY OF 203MT (MINIMUM) BELOW HOOK AT AROUND 18M (MINIMUM) RADIUS WITH MAIN BOOM AND TO OBTAIN CLEAR HEIGHT BELOW HOOK OF 115M (MINIMUM) ABOVE GROUND LEVEL ON MONTHLY RENTAL BASIS AT BHEL-PSER, 1X800 MW NTPC SIPAT STPP STAGE-III PROJECT, PO- UJJWAL NAGAR, SIPAT, DIST – BILASPUR, CHHATTISGARH, PIN - 495555

Tender No.: PSER:SCT:SPT-F2420:26

Revision/ Clarification of Tender Clause(s)

ANNEXURE-A1 TO TCN-01

Sl. No	Reference Clause of Tender Document	Existing Provision	Bidder's query	BHEL's Clarification																		
1	NOTICE INVITING TENDER / PSER:SCT:SPT-F2420:26 / Page 2 of 30	<p>DUE DATE & TIME OF OFFER SUBMISSION</p> <p><i>Date: 16-03-2026, Time: 11-00 Hrs. IST</i> <i>The bidder should respond by submitting their offer online in our e-Procurement platform at https://eprocurebhel.co.in only. Offers are invited in two-parts only. Hard copy bid or bids through email/fax shall not be accepted.</i></p>	<p>We have downloaded the tender documents and currently reviewing the technical and commercial requirements for the purpose of submitting most competitive offer to you.</p> <p>We request you to kindly extend the bid submission date by atleast one week, shall be very thankful to you.</p>	No change in tender submission due date.																		
2	SPECIAL CONDITIONS OF CONTRACT (SERVICE) AND TECHNICAL SPECIFICATION / VOLUME-ID & II/ Page 11 of 16	<table border="1"> <thead> <tr> <th>1.2</th> <th>CRANE DETAILS</th> <th>CRANE TECHNICAL SPECIFICATIONS AND COMPLIANCE MUST BE SUBMITTED ALONG WITH OFFER.</th> </tr> </thead> <tbody> <tr> <td>1.2.1</td> <td>LIFTING CAPACITY</td> <td>HEAVY LIFT HIGH REACH (HLHR) HYDRAULIC CRAWLER CRANE HAVING LATTICE BOOM & LUFFING JIB WITH CRITICAL LOAD LIFTING CAPACITY OF 203MT (MINIMUM) BELOW HOOK AT AROUND 18M (MINIMUM) RADIUS WITH MAIN BOOM AND TO OBTAIN CLEAR HEIGHT BELOW HOOK OF 115M (MINIMUM) ABOVE GROUND LEVEL WITH 85% CAPACITY OF RATED SAFE WORK LOAD AT LIFT RADIUS OF THE CRANE.</td> </tr> <tr> <td>1.2.2</td> <td>MAIN BOOM LENGTH REQUIREMENT (MINIMUM)</td> <td>126M (MIN)</td> </tr> <tr> <td>1.2.3</td> <td>LUFFING JIB LENGTH REQUIREMENT (MINIMUM)</td> <td>48M (MIN)</td> </tr> <tr> <td>1.2.4</td> <td>COMBINATION OF BOOM & JIB (M + M) (MAIN BOOM + JIB) (MINIMUM 48 M LUFFING JIB SHALL BE FITTED AT MINIMUM 99 M LENGTH OF THE MAIN BOOM)</td> <td>147M (MIN)</td> </tr> <tr> <td>1.2.5</td> <td colspan="2">THE END TO END CRAWLER WIDTH OF THE CRANE SHALL BE WITHIN 12M.</td> </tr> </tbody> </table>	1.2	CRANE DETAILS	CRANE TECHNICAL SPECIFICATIONS AND COMPLIANCE MUST BE SUBMITTED ALONG WITH OFFER.	1.2.1	LIFTING CAPACITY	HEAVY LIFT HIGH REACH (HLHR) HYDRAULIC CRAWLER CRANE HAVING LATTICE BOOM & LUFFING JIB WITH CRITICAL LOAD LIFTING CAPACITY OF 203MT (MINIMUM) BELOW HOOK AT AROUND 18M (MINIMUM) RADIUS WITH MAIN BOOM AND TO OBTAIN CLEAR HEIGHT BELOW HOOK OF 115M (MINIMUM) ABOVE GROUND LEVEL WITH 85% CAPACITY OF RATED SAFE WORK LOAD AT LIFT RADIUS OF THE CRANE.	1.2.2	MAIN BOOM LENGTH REQUIREMENT (MINIMUM)	126M (MIN)	1.2.3	LUFFING JIB LENGTH REQUIREMENT (MINIMUM)	48M (MIN)	1.2.4	COMBINATION OF BOOM & JIB (M + M) (MAIN BOOM + JIB) (MINIMUM 48 M LUFFING JIB SHALL BE FITTED AT MINIMUM 99 M LENGTH OF THE MAIN BOOM)	147M (MIN)	1.2.5	THE END TO END CRAWLER WIDTH OF THE CRANE SHALL BE WITHIN 12M.		<p>With reference to the technical specification of crane, we had checked the feasibility with our crane LR1800.</p> <p>The crane meets the required lifting capacity of 271 MT at 20 m radius and achieves the minimum hook height of 115 m (Load chart and feasibility sketch attached for your kind reference)</p> <p>However, there are two deviations from the specified parameters:</p> <p>Point No. 1.2.4 - The luffing jib is required to be connected with a minimum of 99 m main boom, whereas in our crane the maximum possible connection is at 91m main boom.</p> <p>Point No. 1.2.5 - The crawler track width of the crane is 12.3 m, while the specified limit is within 12 m.</p> <p>Kindly confirm if the above configuration is acceptable and we can submit the bid with LR1800 Crane.</p>	The critical load lifting capacity shall be with the main boom only, as per Clause No. 1.2.1 of Tender Document, Volume ID & II (SCC & TS). Hence, BHEL's Terms and Conditions remain unchanged, as stipulated in Clause Nos. 1.2.1, 1.2.2, 1.2.3, 1.2.4, and 1.2.5 of the Tender Document.
1.2	CRANE DETAILS	CRANE TECHNICAL SPECIFICATIONS AND COMPLIANCE MUST BE SUBMITTED ALONG WITH OFFER.																				
1.2.1	LIFTING CAPACITY	HEAVY LIFT HIGH REACH (HLHR) HYDRAULIC CRAWLER CRANE HAVING LATTICE BOOM & LUFFING JIB WITH CRITICAL LOAD LIFTING CAPACITY OF 203MT (MINIMUM) BELOW HOOK AT AROUND 18M (MINIMUM) RADIUS WITH MAIN BOOM AND TO OBTAIN CLEAR HEIGHT BELOW HOOK OF 115M (MINIMUM) ABOVE GROUND LEVEL WITH 85% CAPACITY OF RATED SAFE WORK LOAD AT LIFT RADIUS OF THE CRANE.																				
1.2.2	MAIN BOOM LENGTH REQUIREMENT (MINIMUM)	126M (MIN)																				
1.2.3	LUFFING JIB LENGTH REQUIREMENT (MINIMUM)	48M (MIN)																				
1.2.4	COMBINATION OF BOOM & JIB (M + M) (MAIN BOOM + JIB) (MINIMUM 48 M LUFFING JIB SHALL BE FITTED AT MINIMUM 99 M LENGTH OF THE MAIN BOOM)	147M (MIN)																				
1.2.5	THE END TO END CRAWLER WIDTH OF THE CRANE SHALL BE WITHIN 12M.																					