

PSGSG/12 -13/005	<b>Product Specifications For (DELRIN) Rings</b>	Drg. No.	:
		Date	12.02.2021
		Product	<b>GSM</b>
<b>1.0</b>	<b>Application</b> : SWITCHGEAR		
<b>2.0</b>	<b>Configuration</b> : POLY ACETAL (DELRIN )Rings shall be machined as per Dimensions		
<b>3.0</b>	<b>Color</b> : Natural (White)		
<b>4.0</b>	<b>Specifications:</b>  1. <b>Chemical name</b> : POLY ACETAL  2. <b>Properties :</b> Density : 1.1-1.4 gm/cc Tensile strength at yield : 60-80 MPa Melting point : 160 – 180 °C Dielectric constant : 3.0 – 4.0		
<b>5.0</b>	<b>Packing :</b> The contacts shall be packed in high density cardboard boxes, with a primary wrapped in polyethylene and packed individually in dust free boxes after degreasing. The component shall be guaranteed against all material and manufacturing defects for at least one year.		
<b>6.0</b>	<b>General :</b> 1. Surface finish of the components shall be at least RA 1.6. 2. The component shall be free from dirt, grease and loose particles.		
<b>7.0</b>	In case of doubts in specifications the supplier shall contact BHEL for clarifications.		
1/1	PSGSG/12-13/005.doc		<b>Signature</b>