

Bharat Heavy Electricals Limited

(High Pressure Boiler Plant)
Tiruchirappalli – 620014, TAMIL NADU, INDIA
CAPITAL EQUIPMENT / MATERIALS MANAGEMENT

ENQUIRY

Phone: +91 431 257 79 38

Fax : +91 431 252 07 19 Email : tvenkat@bheltry.co.in

NOTICE INVITING TENDER

Web : www.bhel.com

TWO PART BID	Enquiry Number:	Enquiry Date:	Due date for submission of quotation:
Tender to be submitted in two Parts	2620900159	29.08.2009	13.10.2009

You are requested to quote the Enquiry number date and due date in all your correspondence. This is only a request for quotation and not an order.

Please note that under any circumstances both delayed offer and late offers will not be considered. Hence vendors are requested to ensure that the offer is reaching physically our office before 14.00 hrs on the Date of tender opening.

Item	Description	Quantity
10	500 Amps General Purpose Welding Power	
	Source as per the technical specification &	42 Nos.
	commercial conditions applicable (to be	
	downloaded from web site www.bhel.com or	
	http://tenders.gov.in)	

Important points to be taken care during submission of offer

- 1. Delivery required 6 months from the date of purchase order.
- 2. Grace period of 2 months beyond the above delivery period will be considered.
- 3. Checklist to be filled and enclosed along with the offer failing which, the offer will not be considered for evaluation.

BHEL's General guidelines / instructions (refer MM/CE/GT/001) including bank guarantee formats and list of consortium banks, commercial terms check-list can be downloaded from BHEL web site http://www.bhel.com or from the Government tender website http://tenders.gov.in (public sector units > Bharat Heavy Electricals Limited page) under Enquiry reference "2620900159".

Tenders should reach us before 14:00 hours on the due date Tenders will be opened at 14:30 hours on the due date Tenders would be opened in presence of the tenderers who have submitted their offers and who may like to be present

Yours faithfully,
For BHARAT HEAVY ELECTRICALS LIMITED

Manager / Capital Equipment / MM

PART A

QUALIFYING CRITERIA FOR THE SUPPLY OF INVERTER CONTROLLED MANUAL ARC WELDING POWERSOURCES - 500 Amps. [60% Duty Cycle]

SECTION - I

The BIDDER is expected to give complete details against each clause in the table given below and wherever necessary an additional sheet may be attached (giving clear reference number) to cover the required details.

S. No.	PARTICULARS	VENDOR'S RESPONSE
1.0	Number of Years of Experience of the BIDDER (Original Equipment Supplier) in the field of design, manufacture and supply of 'INVERTER CONTROLLED MANUAL ARC WELDING MACHINES' for Radiographic Quality SMAW Welding Applications for Pressure Parts Fabrication	
2.0	YEAR of LAUNCH of the MODEL quoted against this ENQUIRY	
3.0	Number of 'Inverter Controlled Manual Arc Welding Machines' supplied, till date in the QUOTED MODEL	
4.0	Number of 'Inverter Controlled SMAW Welding Machines – 500 Amps. Rating with 60 % Duty Cycle' supplied and commissioned till date for the following category of CUSTOMERS a) High Pressure Boiler Industries b) Ship Building Applications c) Heat Exchangers / Pressure Vessels	
5.0	Details on International Standards followed in Design and Testing of Welding Machines	
6.0	Comprehensive Details, on Performance Testing of Welding Machines carried out at the Factory, to be furnished with the Technical Offer.	
7.0	Details on SERVICE-AFTER-SALES Set-Up in India including the Addresses of Agents / Service Centres in India, to be furnished compulsorily.	
8.0	BIDDER to indicate the Country of Origin for the supply of welding machines. Machines manufactured in Countries like TAIWAN/CHINA/KOREA are not preferred.	

SECTION - II

The BIDDER has to compulsorily meet the following requirements to get qualified for submitting an offer for the Inverter Controlled SMAW Welding Powersources.

S. No.	REQUIREMENTS	VENDOR'S COMMENTS
9.0	The BIDDER shall have a minimum of TEN Years of Continuous Experience in the Design, Manufacture & Supply of Inverter Controlled SMAW Welding Machines.	
10.0	The BIDDER should have supplied a minimum of 50 number of Inverter Controlled SMAW Welding Machines with rating 500 Amps. (@ 60 % Duty Cycle) and above to Customers in India. Indicate the number of such welding machines sold in India.	
11.0	Reference List of Customers and Performance Certificate from minimum THREE CUSTOMERS [Heavy Engineering Companies] with full contact details of CONTACT PERSON, who are the End Users of the MODEL (given under Clause No.10.0) of Inverter Controlled SMAW Welding Machines.	

SECTION - III

The BIDDER has to comply with the following, for accepting the Technical Offer for scrutiny by the Purchaser :

S.No.	REQUIREMENTS	VENDOR'S COMPLIANCE
12.0	The BIDDER shall submit the offer in	
	TWO PARTS - Technical [with PART A &	
	PART B] & Commercial and Price Bid.	
	The Offer shall contain a comparative	
13.0	statement of Technical Specifications	
	given by BHEL and the Offer Details	
	submitted by the Bidder, against each	
	clause. A just 'CONFIRMED' or	
	'COMPLIES' or 'YES' or 'NO-DEVIATION'	
	or similar words in the technical	
	comparative statement may lead to	
	disqualification of the Technical Offer.	

S.No.	REQUIREMENTS	VENDOR'S COMPLIANCE
14.0	The BIDDER shall assure a continuous	
	support for SPARES and SERVICE for TEN	
	Years, from the date of commissioning of	
	the equipment at BHEL Works.	
15.0	The Technical Offer shall be supported by	
	Product Catalogue and Data Sheets in	
	ORIGINAL and complete technical details	
	/ literature on the QUOTED MODELS of	
4/0	Welding Powersources	
16.0	The Commercial Offer (given with the	
	Technical Offer) shall contain the Scope	
	of Supply and the Un-Priced Part of the	
	Price-Bid, for confirmation for the scope	
17.0	of supply.	
17.0	Earlier performance & field experience (service support) with BHEL (if any) will	
	be a reckoning factor for the technical	
	qualification of the OFFER.	
18.0	The expected delivery period (including	
10.0	the time for Pre-Dispatch Inspection	
	clearance by BHEL) for the welding	
	machines is not more than six months	
	from the date of issue of BHEL Purchase	
	Order. In case the quoted delivery period	
	extends beyond six months, an additional	
	grace period of two months is permitted,	
	but with a loading for arriving at the	
	PRICE COMPETITIVENESS of the Offer	
	(if the OFFER is technically acceptable	
	on all accounts). Details are given in the	
	commercial terms of the this tender	

PART B

TECHNICAL SPECIFICATIONS FOR INVERTER CONTROLLED GENERAL PURPOSE WELDING POWERSOURCES [500 AMPS.]

AA.	APPLICATION:		
SI.No.	FEATURES /BHEL SPECIFICATION	OFFER BY BIDDER	DEVIATIONS
1.1.0	The proposed Welding Machine is intended for use with Manual Arc		
	Welding Process for Radiographic Quality Welds like Butt Joints, Fillet		
	Welds, and Double Groove Welds coming in High Pressure Vessels using		
	φ 2.5 mm to φ 6.3 mm basic coated stick electrodes .		
1.2.0	The Offered Welding Machine shall be PORTABLE in Nature and a		
	CONSTANT CURRENT DC Powersource.		
BB.	MACHINE CONFIGURATION: [The scope of supply shall co	nsist of the following,	for each machine]
SI.No.	FEATURES /BHEL SPECIFICATION	OFFER BY BIDDER	DEVIATIONS
2.1.0	Welding Powersource with Transport Trolley and Wheels		
2.2.0	Control Unit Integrated with Powersource		
	(for Hot Start & Arc Dynamics Control)		
2.3.0	Hand Operated Remote Control Unit for Current Variation		
2.4.0	Set of Inter-Connecting Cables, Adapters, etc.		
2.5.0	Welding Cable and Welding Holder (multiples of 5 mtrs. in length)		
2.6.0	Return Current Cable with Screw Type Earth Clamp.		
2.7.0	Electrical & Mechanical Spares for Powersource & Control Unit		
2.8.0	Operation & Maintenance Manuals – Three Copies per Machine		
2.9.0	Commissioning of Equipment and Performance Prove-out of the offered		
	equipment at BHEL Works, by Supplier's Representative, free of cost.		

CC. E	QUIPMENT SPECIF	ICATION : POWERSOURCE FEATURES		
SI.No.	FEATURES	BHEL SPECIFICATION	OFFER BY BIDDER	DEVIATIONS
3.1.0	Туре	Powersource shall be Inverter Controlled with IGBT and capable of delivering a smooth Constant Direct Current (in DCEP mode), even with a fluctuation of ±10 % in the Input Voltage		
3.2.0	Switching Frequency	BIDDER has to indicate the Switching Frequency of the Inverter Circuit and the make of IGBT used		
3.3.0	Current Rating	500 Amps. @ 60 % Duty Cycle OR Around 375 Amps. at 100% Duty Cycle.		
3.4.0	Operating Range for Welding Current	25 Amps. to 500 Amps. (with stepless variation)		
3.5.0	Open Circuit Voltage	BIDDER to mention the Open Circuit Voltage for the offered Powersource [Preferred OCV is above 75 V]		
3.6.0	Current Setting	The variation in the set value of the welding current to the actual value, shall not exceed 1 %.		
3.7.0	Current Control	Preferred through a local variator [with the help of a 3 inch diameter KNOB] provided in the Front Panel of Powersource and the Remote Control Unit.		
3.8.0	Power Input	415 ± 10% V AC, 3 Phase, 50 ± 2% Hz, through a 3 Wire System [4 th wire for EARTHING] – No Neutral Conductor		
3.9.0	Input Power Cable	A 10 metre long electric input power cable with protective sheathing to be provided with the powersource.		
3.10.0	Control Panel Switches	Power ON/OFF, Remote ON/OFF, Voltage & Ampere Control, Hot Start Control, Arc Dynamics Control		
3.11.0	Voltmeter & Ammeter	Factory Installed Ammeter & Voltmeter on the front panel with easy removal and replacement (i.e., without lifting the top cover of the Welding Powersource) for periodic instrument calibration		
3.12.0	Arc Strike	Selection for Instantaneous Arc Strike with HOT START for SMAW Process.		

CC. E	QUIPMENT SPECIF	ICATION : POWERSOURCE FEATURES	[conto	[k
SI.No.	FEATURES	BHEL SPECIFICATION	OFFER BY BIDDER	DEVIATIONS
3.14.0	Arc Dynamics Control - Electronic Inductance Variable Control Insulation Machine Protection	To minimise spatter and optimise weld-bead wetting action, during welding of materials special materials like Stainless Steel, T 91/P 91, Inconel, in addition to Carbon and Low Alloy Steels. Class "H" – to suit Tropical Working Conditions IP 23 – Degree of Protection		
	Machine Cooling	The Powersource shall feature a 'state of art' forced air cooling system that ensures adequate cooling of the components while preventing dust and metal particles from being drawn in.		
3.17.0	Functional / Elemental Design Protection	 a) Inbuilt protection for the IGBT/Powersource against Thermal / Overload / Short-Circuit / Single or Two Phase Power Input Conditions. b) All PCBs shall be sprayed with mould coating to prevent damage from dust and grinding particles. c) Machine Design to ensure proper earthing for the machine and its peripherals 	[BIDDER has to specifically furnish technical details on how these protective measures are addressed in the Machine Design]	
3.18.0	EMI Suppression	 a) Powersource shall be equipped with a suitable Filter Network connected to the INPUT Power Line, to prevent propagation of EMI either into or out of the Powersource. b) All metal enclosures and internal shields shall prevent radiated EMI. c) BIDDER has to elaborate the DESIGN FEATURES to meet the above requirements. 		
	Portability	Under-Carriage with hard rubber lined wheels for portability of the powersource by manual pushing		
3.20.0	Ambient Conditions	Temperature upto + 50 ° C; Humidity upto 90 % but both upper limits do not occur simultaneously.		

CC. E	QUIPMENT SPECIFI	CATION : POWERSOURCE FEATURES		[contd.]
SI.No.	FEATURES	BHEL SPECIFICATION	OFFER BY	BIDDER	DEVIATIONS
3.21.0	Load Compensation	Output variation due to line voltage fluctuation,			
		cable heating or drift due to the use of long cable,			
		[20 metres long welding cable] to be eliminated.			
3.22.0	Electrode Holder &	Heavy Duty rugged LUG type terminals to connect			
	Return Current	50 mm ² Welding Cable for SMAW Electrode Holder			
	Connection	and Return Current Cable for SMAW Process			
3.23.0	Welding Current	SMAW Welding (current) Cable, 20 mtrs. in length,			
	Cable	with one end connected to the Powersource and the			
		free end provided with a FEMALE Connector to			
		connect a MALE Connector with 50 mm ² Cable of			
		the Manual Welding Electrode Holder.			
3.24.0	Return Current Cable	Welding Current RETURN Cable, 20 mtrs. in length,			
		with one end connected to the Powersource and the			
		other end provided with a Screw Type Earth Clamp			
3.25.0	Power Rating	BIDDER to indicate the Maximum Power Rating			
		[in kVA] of the Powersource and the NO-LOAD			
		Power Consumption in Watts.			
3.26.0	Power Source Model	To Specify the Model of Powersource Offered			
DD	COLUDATALE COFOLE	OATLON DEMOTE CONTROL UNIT FEATURES			
		CATION: REMOTE CONTROL UNIT FEATURES	OFFED D	/ DIDDED	DEVIATIONS
SI.No.	FEATURES	BHEL SPECIFICATION	OFFER BY	BIDDEK	DEVIATIONS
4.1.0	Application	For welding current variation from a distant work			
		place, in addition to that provided in the front panel			
4.0.0	<u> </u>	of the welding powersource.			
4.2.0	Туре	Hand Operated with 10 mtrs. long control cable			
		with end quick-fix end connectors			
4.3.0	Current Control	Stepless Variation of Welding Current			
4.4.0	OPTIONAL REMOTE	To quote for a suitable Remote Control Unit ,			
	CONTROL UNIT	which operates on Wire-Less (Cord Less) mode.			

EE.	SPARES :			
S.No.	ITEMS	BHEL SPECIFICATION	OFFER BY BIDDER	DEVIATIONS
	Power Source	All type of Spare Parts including the following items: a. IGBT Kit b. All Types of Fuses c. Control – Transformers d. Printed Circuit Boards / PCBs – All Types e. Rectifiers, Thermistors, Capacitors f. Switches and Knobs g. Cooling Fan Motor h. Ammeter & Voltmeter i. Potentiometer j. Relays & Timers k. Receptacles l. Control Cable with End Connectors n. Filters o. Welding & Return Cable Connectors are to be COMPULSORILY QUOTED (with Unit Rate) for one powersource required for 2 years of operation on THREE shift basis for 365 Days in an year.	OTTER BY BIBBER	DEVIATIONS
5.2.0	Remote Control Unit	Complete Set of Remote Control Unit and its Spares like Knob, Potentiometer, etc. to be OFFERED		
FF.	O&M MANUALS:			
S.No.		BHEL SPECIFICATION	OFFER BY BIDDER	DEVIATIONS
6.1.0	No. of Copies 3	3 (Three) for Each Machine		
	•	English		
	Soft Copy C	One SOFT COPY in DC-ROM is to be given for each nachine, containing the details mentioned under Clause SI. No. FF./6.4.0		

FF. (O&M MANUALS	:	[contd]		
S.No.	PARTICULARS	BHEL SPECIFICATION	OFFER BY BIDDER	DEVIATIONS	
6.4.0	Manual Details :	 Manual shall contain all instructions for machine installation and welding trial testing, in sequence. 			
		b. Manual to give general circuit diagrams, showing the interconnection of various elements and also details on PCBs [Printed Circuit Board] like tapping voltages, main electronic elements' specifications and ratings, etc.			
		c. Manual to give other details like trouble shooting chart, weld parameters selection for various base metals, etc.			
		d. Master List of Parts & Spares used in the machine with Make, Model, Rating, etc.			
	GENERAL POINTS		OFFER BY BIRDER	DEVIATIONS	
S.No.	PARTICULARS	BHEL SPECIFICATION	OFFER BY BIDDER	DEVIATIONS	
7.1.0	Inspection	 a. The welding machines shall be offered for inspection by BHEL Engineers at supplier's works for performance evaluation prior to despatch. b. Welding Trials are to be taken on 20 mm thick Plate Butt Joints with φ 2.5, 3.15, 4.0 			
		and 5.0 mm SMAW Electrodes of Class E 7018-1 and E-9018-B3.			
	Commissioning	The equipment shall be commissioned, free of cost by the supplier's representative at BHEL Works.			
7.3.0	Training	The Supplier's SERVICE ENGINEER shall give training in the Operation and Maintenance (mainly on electric/electronic troubleshooting) of the Machine for BHEL Staff, after the successful commissioning of the Welding Machines			

GG.	. GENERAL POINTS :		[contd]	
S.No.	PARTICULARS	BHEL SPECIFICATION	OFFER BY BIDDER	DEVIATIONS
7.4.0	Guarantee	The machine shall be guaranteed for a minimum of 12 (twelve) months from the date of commissioning & performance prove-out at BHEL.		
7.5.0	Bought-Out Items	a) The Bought-Out Items - like Motors, IGBTs, ICs, Relays, Contactors, Switches, Electronic Elements, etc., used in the Powersource & Control Unit shall be of Internationally Reputed Manufacturers only.		
		b) BIDDER has to furnish the MAKE of Bought-Out Items proposed to be used in the Welding Machine, with the OFFER.		