

TD-106. - 2 Rev. No. : 00 Form No. :		PRODUCT STANDARD HYDERABAD GT ENGINEERING		Prod. Std. No. : GT54207												
				Rev. No. 07												
				Page : 1 of 3												
COPYRIGHT AND CONFIDENTIAL The information on this document is the property of BHARAT HEAVY ELECTRICALS LIMITED. It must not be used directly or indirectly in any way detrimental to the interest of the company. <u>FILTER CARTRIDGE</u> <u>1.0 DESCRIPTION</u> This specification specifies to filter cartridges used in various Gas Turbine systems like Lube oil, HSD & Naptha. The PH series cartridges shall be of high flow design capable of replacing PL series cartridges. <u>2.0 DESIGN DATA</u> 2.1 Materials and Construction 2.1.1 Cartridges designated for application with fuel oil (see Tabulation) must be suitable for long term use with Distillate, Naptha, Crude, and Residual fuel oils at temperatures from 50 F to 260 F. the cartridges are to be constructed of the following materials: <table border="0" style="margin-left: 40px;"> <tr> <td>Center Tube</td> <td>-</td> <td>Nylon/glass OR Metal (Galvalume)</td> </tr> <tr> <td>End Caps</td> <td>-</td> <td>Metal</td> </tr> <tr> <td>Adhesive</td> <td>-</td> <td>Urethane (2parts)</td> </tr> <tr> <td>Gaskets</td> <td>-</td> <td>Lexide (cellulose fiber) OR Cork</td> </tr> </table> 2.1.2 Cartridges designated for application exclusively with tube oil must be constructed of materials suitable for long term use with petroleum based oils and phosphate ester fire resistant fluids at temperatures from 50 F to 170 F. 2.2 The manufacturer shall make no substitutions of materials without the consent of BHEL Gas Turbine Engineering. Any proposed change in materials shall be presented in writing to BHEL. The proposal for change in materials shall include supporting test data evaluating the impact of the changes on cartridge performance, over the full range of environments for which cartridge service is specified. <u>3.0 QUALITY ASSURANCE</u> 3.1 All material will be delivered in a clean, usable condition appropriate to the function of the item. Openings will be securely covered against entry of foreign materials where appropriate. <u>4.0 MARKING AND PACKING FOR SHIPMENT</u> 4.1 Packing shall be accomplished in accordance with acceptable commercial practices (for domestic or foreign shipments) unless otherwise indicated in the purchase order or quotation request. 4.2 All shipping containers shall be identified with Customer Order Number, BHEL PO No's. Each shipping container shall contain three packing lists, listing all contents of the particular container with one copy attached in a secure manner to the outside. Each part will be identified and keyed to the packing list.					Center Tube	-	Nylon/glass OR Metal (Galvalume)	End Caps	-	Metal	Adhesive	-	Urethane (2parts)	Gaskets	-	Lexide (cellulose fiber) OR Cork
Center Tube	-	Nylon/glass OR Metal (Galvalume)														
End Caps	-	Metal														
Adhesive	-	Urethane (2parts)														
Gaskets	-	Lexide (cellulose fiber) OR Cork														
Ref. Doc	342A2581															

TD-106. - 2 Rev. No. : 00 Form No. :		PRODUCT STANDARD HYDERABAD GT ENGINEERING		Prod. Std. No. : GT54207																																											
				Rev. No. 07																																											
				Page : 2 of 3																																											
5.0 VARIANT TABLE																																															
<table border="1"> <thead> <tr> <th>BHEL Var No</th> <th>BHEL Matl code /GE Part No</th> <th>HILLIARD New Part No</th> <th>Wt. (Kg)</th> <th>Length & OD in inches</th> <th>Remarks</th> </tr> </thead> <tbody> <tr> <td>01</td> <td>GT9754207011 342A2581P002</td> <td>PL718-05-GE</td> <td>0.5</td> <td>L = 18 Inch (457.2mm) OD=6 1/4 Inch(158.75mm) ID= 2 9/16 Inch(65.09mm)</td> <td>Fr. 6/9 HSD & All Frs. Lube oil</td> </tr> <tr> <td>02</td> <td>GT9754207020 342A2581P003</td> <td>PL511-05-GE</td> <td>0.5</td> <td>L = 11 Inch (279.4 mm) OD=4 5/16 Inch(109.54mm) ID= 1 3/4 Inch(44.45mm)</td> <td>Fr. 5 HSD & All Frs. Control Oil</td> </tr> <tr> <td>03</td> <td>GT9754207038 342A2581P006</td> <td>PL511-12-CGE</td> <td>0.5</td> <td>L = 11 Inch (279.4 mm) OD=4 11/16 Inch(119.06mm) ID= 1 3/4 Inch(44.45mm)</td> <td>Coupling oil – All Frames</td> </tr> <tr> <td>04</td> <td>GT9754207046 342A2581P023</td> <td>PH511-05-C</td> <td>0.5</td> <td>L = 11 Inch (279.4 mm) OD=4 5/16 Inch(109.54mm) ID= 1 3/4 Inch(44.45mm)</td> <td>Fr-5, Naphtha</td> </tr> <tr> <td>05</td> <td>GT9754207054 342A2581P020</td> <td>PH718-05-CN</td> <td>0.5</td> <td>L = 18 Inch (457.2mm) OD=6 1/4 Inch(158.75mm) ID= 2 9/16 Inch(65.09mm)</td> <td>Fr-6, Fr-9 Naphtha</td> </tr> <tr> <td>06</td> <td>-</td> <td>PH718-05-C</td> <td>0.5</td> <td></td> <td>Fr6F & Fr9F Lube oil</td> </tr> </tbody> </table>						BHEL Var No	BHEL Matl code /GE Part No	HILLIARD New Part No	Wt. (Kg)	Length & OD in inches	Remarks	01	GT9754207011 342A2581P002	PL718-05-GE	0.5	L = 18 Inch (457.2mm) OD=6 1/4 Inch(158.75mm) ID= 2 9/16 Inch(65.09mm)	Fr. 6/9 HSD & All Frs. Lube oil	02	GT9754207020 342A2581P003	PL511-05-GE	0.5	L = 11 Inch (279.4 mm) OD=4 5/16 Inch(109.54mm) ID= 1 3/4 Inch(44.45mm)	Fr. 5 HSD & All Frs. Control Oil	03	GT9754207038 342A2581P006	PL511-12-CGE	0.5	L = 11 Inch (279.4 mm) OD=4 11/16 Inch(119.06mm) ID= 1 3/4 Inch(44.45mm)	Coupling oil – All Frames	04	GT9754207046 342A2581P023	PH511-05-C	0.5	L = 11 Inch (279.4 mm) OD=4 5/16 Inch(109.54mm) ID= 1 3/4 Inch(44.45mm)	Fr-5, Naphtha	05	GT9754207054 342A2581P020	PH718-05-CN	0.5	L = 18 Inch (457.2mm) OD=6 1/4 Inch(158.75mm) ID= 2 9/16 Inch(65.09mm)	Fr-6, Fr-9 Naphtha	06	-	PH718-05-C	0.5		Fr6F & Fr9F Lube oil
BHEL Var No	BHEL Matl code /GE Part No	HILLIARD New Part No	Wt. (Kg)	Length & OD in inches	Remarks																																										
01	GT9754207011 342A2581P002	PL718-05-GE	0.5	L = 18 Inch (457.2mm) OD=6 1/4 Inch(158.75mm) ID= 2 9/16 Inch(65.09mm)	Fr. 6/9 HSD & All Frs. Lube oil																																										
02	GT9754207020 342A2581P003	PL511-05-GE	0.5	L = 11 Inch (279.4 mm) OD=4 5/16 Inch(109.54mm) ID= 1 3/4 Inch(44.45mm)	Fr. 5 HSD & All Frs. Control Oil																																										
03	GT9754207038 342A2581P006	PL511-12-CGE	0.5	L = 11 Inch (279.4 mm) OD=4 11/16 Inch(119.06mm) ID= 1 3/4 Inch(44.45mm)	Coupling oil – All Frames																																										
04	GT9754207046 342A2581P023	PH511-05-C	0.5	L = 11 Inch (279.4 mm) OD=4 5/16 Inch(109.54mm) ID= 1 3/4 Inch(44.45mm)	Fr-5, Naphtha																																										
05	GT9754207054 342A2581P020	PH718-05-CN	0.5	L = 18 Inch (457.2mm) OD=6 1/4 Inch(158.75mm) ID= 2 9/16 Inch(65.09mm)	Fr-6, Fr-9 Naphtha																																										
06	-	PH718-05-C	0.5		Fr6F & Fr9F Lube oil																																										
#DO NOT USE , USE VAR05#																																															
6.0 SHELF LIFE REQUIREMENT:																																															
All packages having any shelf life items as part of it must have clear indication on the package/container and packing list. Any deviation to this requirement must be brought to notice of GT Engineering for specific approval. PL Series (Pleated Cellulose Media) Elements Safe shelf life is two years if stored in original unopened factory packaging. Paper can become brittle with age. Since the resin in the paper continues to post cure, the old paper can become over cured. PH Series – (Pleated Synthetic Media) up to five years if stored in original unopened factory packaging.																																															
7. Inspection at IGI (Incoming Goods Inspection) stage:																																															
A verification check to be done if the product arrived in good condition at warehouse/stores before accepting them in to our stock.																																															
- Verify if the received product model no is as per the order and according to the desired variant. - Check if the boxes are OK and the labels are there in the right place, the quantity is OK, etc. - Visual inspection to be done to ensure that the received goods have no physical damage. - Check the physical dimensions of the supplied elements are as per the specification. - Guaranteed and proved with a measurement test reports from the vendor shall be received. - Shelf life of the elements to be checked and ensure it is in line with the Spec requirement. - Any deviation to this requirement must be brought to notice of GT Engineering for specific approval.																																															
Ref. Doc	342A2581																																														

COPYRIGHT AND CONFIDENTIAL

The information on this document is the property of BHARAT HEAVY ELECTRICALS LIMITED. It must not be used directly or indirectly in any way detrimental to the interest of the company.

TD-106. - 2 Rev. No. : 00 Form No. : 	PRODUCT STANDARD HYDERABAD GT ENGINEERING		Prod. Std. No. : GT54207		
			Rev. No. 07		
			Page : 3 of 3		
COPYRIGHT AND CONFIDENTIAL The information on this document is the property of BHARAT HEAVY ELECTRICALS LIMITED. It must not be used directly or indirectly in any way detrimental to the interest of the company.	RECORD OF REVISIONS				
	Rev. No.	Date	Revision Details	Revised By	Approved By
	00	21/12/1995	First Made	YVRAO	BIB
	01	02/09/1998	IN VAR 05 GEPT NO CHANGED FROM 18 TO 20	YVRAO	BIB
	02	07/01/1999	VAR 06 ADDED	YVRAO	BIB
	03	17/10/2006	IN VAR 04 GE PART NO CHNAGED FROM 14 TO 23	YVRAO	BSN
	04	25/03/2019	GENERALLY REVISED	ART	VSH
	05	25/06/2019	SHELF LIFE REQUIREMENT ADDED	KRANTHI	SANJAY
	06	21/01/2021	Hilliard part no updated for Var-04 OD& Length Updated for all elements. Clause 6 updated.	KRANTHI	SURESH V
	07	02/12/2022	Variant Table Updated with Filter element dimensions	KRANTHI	SURESH V
Ref. Doc	342A2581				