



Particulars General

Specification for 3T EOT crane for Hollow Insulator Grinding Bay

Capacity	3 Metric Tonne
Туре	Double Girder Overhung with 4 wheels, crane with motorised cross travel long travel and hoist as per specification below with control panel
Application	Indoor Loading & Unloading
Area Classification	Safe
Specification & Class	M5 as per IS:3177-1999

Speed

Cross Travel Speed	15 / 5mts/min	
Long Travel Speed	25 / 6.25mts/min	
Main Hoist Speed	Main 4-5mts/min Micro 0.4-0.5mtrs/min	

Dimension

Crane Span	approx. 19 mts (span to match existing girder & rails, supplier to measure the existing dimensions and suitably manufacture)
Lift Height	approx. 8.5mts

Mechanical & Structural

Gear Boxes	Bidders to provide details of Gear Box Construction
Cross Travel & Long Travel	Single flanged taper thread wheels machined out of EN-8 forging, hardended to and mounted on
Wheels	antifriction bearing . (wheel hardness to be lower than that of rail hardness)
Sheaves	Cast Steel as per IS:1030 Gr2
Buffers	Rubber buffers shall be provided for long travel & Cross Travel motions
Platform	2 short platform on drive side to be provided
LT wheels & Total weight	Bidders to provide Total weight of the crane, LT wheel load & LT wheel base

Electrical

Power Supply	415 Volts AC, 3 phase 50 Hz
Control Voltage	230V 1 phase AC (alternatively 110V 1 phase AC)
Motors	Squirrel cage induction motor with IP-55 protection, Class F insulation, Crane Duty 4 pole. Bidders PVC armoured cables with solid copper conductor
Cable Type	PVC armoured cables with solid copper conductor Specify Rayle
Cross Travel Cabling	Through PVC Flexibile trailing cable arrangement running on 'T' track
Variable Frequency Drive	Optional for Cross travel motor & Long travel motor. For hoist only geared train (2 separate motors for macro & micro) to be offered.
DSL system	Already existing, supplier has to supply current collector to match existing bus bar

Hook, Drum, Brake & Rope

Hook Type	Single Shank 'C' type, Hook shall be provided with safety latch as per IS3835	
Wire Rope	Fibre Core, 6 x 36 construction wire rope as per IS 2266. Bidder to indicate technical specification	
Rope Drum	The length of the drum shall be designed such that, while in fully hoisted state, atleast 4 grooves are still open. Similarly, when fully lowered, the drum shall have atleast 4 grooves rope wrapped in	
Brake	Bidders to provide details of braking system	
No of Falls	4	

operation

Operation	 Through independent movable pendent push button station Alternatively Hand held radio remote to be quoted as optional item
Collision	Due to existitance of another crane on the same girder, anti collission system based on limit switch

Others

End Carraiges	Fabricated out of rolled steel chanels
Lubrication	Group lubrication with hand grease gun
Painting	The complete crane structure shall be applied with 2 coats red oxide followed by two coats of synthetic enamel paint, Colour: YELLOW, Bidders to quote with BAL number.

Preferred Makes

Motors	NGEF, Bharat Bijlee, Siemens, Kirloskar, ABB, CGL	
Wire Rope	Usha Martin Black	
Brake	Pethe, EMCO	
Gear Boxes	Elcon, Shanti, Premium	
Bearings	SKF, FAG, NTN	
Limit Switches	Bhartia Cutler hammer, Jai Balaji	
Hook	EEK, FTC. Smriti Forge	

General Requirements

Warranty	12 months from the date of successful commissioning
Service	Bidders to have service backup facility in Bangalore. Bidders to confirm of providing service during
Service	emergency within 24 Hrs.

AN

A.B. SHYAMASUNDAB, DGM/Ins.Prodn. BHEL - EPD, Bangalore-560 012 प्राप्त क्रिक्ट क्रिक क्रिक्ट क्रिक क्रिक क्रिक्ट क्रिक क्र





References	List of clients wherein similar or high and the
Catalouge / Technical	List of clients wherein similar or higher capacity crane supplied in past 2 years to be provided along
n .	To be provided along with technical bid
Company Profile	Brief company profile along with the facilities and product range shall be provided at all the provided at
Erection & Commissioning	technical bid. The financial statement of the company for last 3 years shall also be provided. Scope of supplier. If quoted seperately, to be indicated in the technical bid.

Qualification Criteria

- 1. Only OEM or the authorized dealer/chanel partners are to quote.
- 2. They should have supplied a minimum of 5 similar type & capacity (or higher capacity) cranes in the last 5 years.
- 3. Bidders has to produce successful working certificate of a similar type & capacity cranes(or higher capacity) for a period of last
- 4. Spares and service backup shall be available in Bangalore

ए.ही. ६ त्रमुंदर, च.म.प्र./ए-पु.ज्ला. A.B. SITAMIASUNDAR, DGM/Ins.Prodn. BHEL-EPD, Bangalore-560 012

S. MURALIDHARA, Sr. Engle contreX BHEL - EPD, Bangalore - \$60 012