1) The table given under **ANNEXURE – III** (<u>**LIST OF ITEMS FOR SUPPLY IN EACH SITES :**</u>) of PART C should be read as below:

Two (02) nos. 12 port unmanaged switch may be replaced by one no. 24 port managed switch having following specification.

S.No.	Features	Detailed Specifications
1	No. Of Switches Required	**One no.**
2	Make & Model Offered	
3	Ports	The offered switch should have following ports from day one
	3.1	24 Nos. of 10/100Mbps Ethernet ports
	3.2	2 Nos. of fixed 10/100/1000BASE-T uplink ports
4	Forwarding Bandwidth	8Gbps or more
5	Throughput	5Mpps or More for 64 Bytes Packets
6	Software	The offered switch should come with the latest operating system having full layer 2 features.
7	Dynamic Trunking Protcol (DTP) support	Should support Dynamic Trunking Protocol (DTP) on all switch ports
8	STP support	Should support Spanning Tree Protocol IEEE 802.d , Per VLAN Spanning Tree Protocol (PVST)
9	Standards support	It should support following standards: 802.1Q VLAN tagging· 802.1p Priority· 802.1D Spanning Tree· 802.3u Fast Ethernet· 802.3x Flow Control· 802.3z Gigabit Ethernet.· 802.3ab 1000Base-T (Gigabit Ethernet over Copper)· 802.1x Authentication
10	VTP suport	Should support VLAN Trunking Protocol
11	Security features	Should support IEEE 802.1x for ports & vlans, VLAN ACLs, Port-based ACLs, TACACS+ & RADIUS
12	Manageability	Should be remotely managable through a standard web browser.

The above conditions shall form a part of tender. All other terms and conditions shall remain un-changed.

(Manager – Purchase)