TSX / 304 dated 30.10.2006

SPECIFICATION FOR DIGITAL HAND HELD DP INDICATOR

General: Handheld battery operated digital pressure manometer for measuring differential pressure (of air flow pitot tube) with an accuracy of $\pm 0,25$ % F.S. with bold LCD display of at least 1 cm high.

Technical Specification:

Pressure range: -100 to 100 mbar

Resolution: 0.1 mbar

Accuracy: 0.25% or better

Zero Function: Easy accessible zero adjustment knob

Display Bold LCD Digital around ½"

Indication: Low battery

Process connection: Quick fit connector with suitable dual tubing of 2 metre length to

suit pitot tube pressure connector.

Accessory: Ellipsoidal nosed pitot tube of 1 metre & 1.5 metre length with k

factor of 1 with calibration certificate.

Carrying case Operating manual

Factory calibration certificate

Batteries for instrument initial operation.

PLEASE NOTE:

- 1. The instrument offered can be better than the above specifications
- 2. Should have service facility in India with factory trained engineers to take care of the equipment supplied and to reduce the down time.
- 3. The product catalogue should contain only the product offered in depth preferably highlighting the model offered.
- 4. Two sets of original product catalogue to be enclosed with the offer, without this offer will be rejected totally.
- 5. Vendor should submit the offer with detailed specification of the product offered. The offers given as "as per your specifications" will be rejected.