

<b>1 X 660 MW SAGARDIGHI TPP UNIT#5</b> <b>BOQ - MAIN SUPPLY</b> <b>1.1 kV LT XLPE POWER CABLES</b>				
<b>(1.1)</b> 1.1KV, Al conductor, XLPE insulated, Aluminium round wire armour for single core cables and Galvanised steel round wire armour for twin & multicore cables, INNER SHEATH: PVC conforming to type ST2 of IS: 5831 and IS 7098 Part-I for twin & multicore cable. Single core cables shall have no inner sheath. OUTER SHEATH: FRLS PVC Type ST-2 of IS: 5831 & IS 7098 Part-I				
S. NO.	ITEM CODE	Cable Size (No. of cores - Cross section Area (sq.mm))	Order Quantity (meters)	Drum Length (meters)
1	507-28200-A	1C - 400- AL ROUND WIRE ARMoured	7000	500
2	507-28201-A	1C - 630- AL ROUND WIRE ARMoured	9500	500
3	507-28181-A	2C - 16- AL ROUND WIRE ARMoured	4500	500
4	507-28182-A	2C - 25- AL ROUND WIRE ARMoured	1500	500
5	507-28183-A	2C - 50- AL ROUND WIRE ARMoured	2000	500
6	507-28184-A	2C - 95- AL ROUND WIRE ARMoured	2000	500
7	507-28221-A	2C - 120- AL ROUND WIRE ARMoured	3500	500
8	507-28186-A	3C - 16- AL ROUND WIRE ARMoured	11000	500
9	507-28187-A	3C - 25- AL ROUND WIRE ARMoured	5000	500
10	507-28188-A	3C - 50- AL ROUND WIRE ARMoured	3500	500
11	507-28189-A	3C - 95- AL ROUND WIRE ARMoured	2500	500
12	507-28190-A	3C - 150- AL ROUND WIRE ARMoured	1000	500
13	507-28191-A	3C - 240- AL ROUND WIRE ARMoured	4000	500
14	507-28192-A	3C - 300- AL ROUND WIRE ARMoured	1000	500
15	507-28193-A	3.5C - 25- AL ROUND WIRE ARMoured	8500	500
16	507-28194-A	3.5C - 50- AL ROUND WIRE ARMoured	6000	500
17	507-28195-A	3.5C - 95- AL ROUND WIRE ARMoured	2000	500
18	507-28196-A	3.5C - 185- AL ROUND WIRE ARMoured	1000	500
19	507-28197-A	3.5C - 300- AL ROUND WIRE ARMoured	1000	500
20	507-28198-A	4C - 16- AL ROUND WIRE ARMoured	2500	500

**(1.2)** 1.1KV, Cu conductor, XLPE insulated, Aluminium round wire armour for single core cables and Galvanised steel round wire armour for twin & multicore cables, INNER SHEATH: PVC conforming to type ST2 of IS: 5831 and IS 7098 Part-I for twin & multicore cable. Single core cables shall have no inner sheath. OUTER SHEATH: FRLS PVC Type ST-2 of IS: 5831 & IS 7098 Part-I

S.NO.	ITEM CODE	Cable Size (No. of cores - Cross section Area (sq.mm))	Order Quantity (meters)	Drum Length (meters)
21	507-28001-A	1C-16-CU ARMoured	4000	500
22	507-28130-A	1C-35-CU ARMoured	1000	500
23	507-28015-A	2C - 2.5- CU ARMoured	18000	1000
24	507-28065-A	2C - 6- CU ARMoured	5000	1000
25	507-28043-A	3C - 2.5- CU ARMoured	55000	1000

**NOTES:**

1	The standard drum length shall be 500/1000 meters as indicated above. Tolerance on individual drum length shall be $\pm 5\%$
2	Overall tolerance on total dispatched quantity of each size shall be (-) 2% and (+) 0% except where the total ordered quantity is one single drum length of 500/1000m, in which case it shall be -5% to 0%. Cables consumed for testing and inspection shall be to bidder's account
4	In case of the quantities cleared by BHEL for manufacturing are manufactured and offered for inspection by successful bidder in more than one batch, BHEL reserves the right to witness type testing on all batches without any price implications
5	Unit price of cables quoted by bidder shall be inclusive of type test charges. No separate charges shall be payable for type tests
6	For any clarification please refer technical specification no.PE-TS-445-507-E002(Rev-0)

Annexure I

Sl. No.	Package Co	Package name	DEPTT	BHEL Drawing No	Drawing Title	Primary/Seco ndary	Drg Sch for Vendors	Standard Delivery Terms for Supply Portion
3	507-28000-A	LT XLPE POWER CABLES	ELECT	PE-V0-XXX-507-E113	CROSS SECTION DRGS. - LT XLPE POWER CABLES	Primary	R-0 within 14 days from PO & subsequent revisions within 10 days of comments received from BHEL. BHEL shall furnish comments / approval on each submission within 18 days from receipt.	Within Four (04) months from date of CAT-1 approval of Primary drawing/documents or BHEL manufacturing clearance whichever is later, subjected to drawing/document submission/re-submission schedule as stipulated, in case of any delay in submission/ resubmission of Primary drawing/documents, then same shall be reduced from the given delivery period.
				PE-V0-XXX-507-E913	QUALITY PLAN - LT XLPE POWER CABLES	Primary		
				PE-V0-XXX-507-E111	TECHNICAL DATA SHEET - LT XLPE POWER CABLES	Primary		
				PE-V0-XXX-507-E114	TYPE TEST CERTIFICATES - LT XLPE POWER CABLES	Secondary	Within 1 week after conduction of type test	Additional Qty. (if provided separately under Qty. var. clause of contract): Supply within Four (04) months from the date of Quantity clearance by BHEL.

- Notes
- a. The end period specified is for completion of the deliveries. Deliveries to start progressively so as to meet the completion schedule.
  - b. The delivery conditions specified are for contractual LD purposes, however BHEL may ask for early deliveries without any compensation thereof.
  - c. Wherever schedule of drawings/documents submission / re-submission is stipulated in the Technical Specifications, same shall be superseded by delivery specified in NIT.
  - d. Vendor to start manufacturing activities only after obtaining specific manufacturing clearance from BHEL Purchase group.

# **VOLUME-II**

**1X660MW SAGARDIGHI TPP UNIT#5**

**TECHNICAL SPECIFICATION**

**FOR**

**LT XLPE POWER CABLE**

**SPECIFICATION NO: *PE-TS-445-507-E002***

***REVISION: 0***



**BHARAT HEAVY ELECTRICALS LIMITED**

**POWER SECTOR**

**PROJECT ENGINEERING MANAGEMENT**

**NOIDA, UP (INDIA) – 201301**

1035432/2022/PS-PEM-EL



# TECHNICAL SPECIFICATION FOR LT XLPE POWER CABLES

1X660MW SAGARDIGHI TPP UNIT#5

SPECIFICATION NO. PE-TS-445-507-E002

VOLUME II

SECTION

REVISION 0

DATE: 7.7.2022

SHEET 1 OF 1

## CONTENTS

<u>S. NO.</u>	<u>DESCRIPTION</u>	<u>NO. OF SHEETS</u>
1.	CONTENTS	01
2.	SECTION – I	01
	COMPLIANCE CERTIFICATE	01
	SPECIFIC TECHNICAL REQUIREMENTS	01
	DATA SHEET-A	03
	DATA SHEET-C	03
3.	SECTION – II	01
	STANDARD TECHNICAL SPECIFICATION	02
	QUALITY PLAN (ALONGWITH ANNEXURE A TO QP)	15
	TYPICAL DRAWING OF CABLE DRUM PACKING	01
	TOTAL NO. OF SHEETS=	30
	(INCLUDING COVER/ SEPARATOR SHEETS)	



# TECHNICAL SPECIFICATION FOR LT XLPE POWER CABLES

1X660MW SAGARDIGHI TPP UNIT#5

SPECIFICATION NO. PE-TS-445-507-E002

VOLUME II

SECTION I

REVISION 00

DATE: 7.7.2022

SHEET 1 of 1

## **COMPLIANCE CERTIFICATE**

The bidder shall confirm compliance to the following by signing/ stamping this compliance certificate and furnishing same with the offer.

1. The scope of supply, technical details, construction features, design parameters etc. shall be as per technical specification & there are no exclusion/ deviation with regard to same.
2. There is no deviation with respect to specification other than those furnished in the 'schedule of deviations'.
3. Only those technical submittals which are specifically asked for in NIT to be submitted at tender stage shall be considered as part of offer. Any other submission, even if made, shall not be considered as part of offer.
4. Any comments/ clarifications on technical/ inspection requirements furnished as part of bidder's covering letter shall not be considered by BHEL, and bidder's offer shall be construed to be in conformance with the specification.
5. Any changes made by the bidder in the price schedule with respect to the description/ quantities from those given in 'BOQ-Cum-Price schedule' of the specification shall not be considered (i.e., technical description & quantities as per specification shall prevail).

-----  
BIDDER'S STAMP & SIGNATURE

1035432/2022/PS-PEM-EL



# TECHNICAL SPECIFICATION FOR LT XLPE POWER CABLES

1X660 MW SAGARDIGHI TPP UNIT#5

SPECIFICATION NO. PE-TS-445-507-E002

VOLUME II

SECTION I

REVISION 0

DATE: 7.7.2022

## SECTION – I

### SPECIFIC TECHNICAL REQUIREMENTS



# TECHNICAL SPECIFICATION FOR LT XLPE POWER CABLES

1X660 MW SAGARDIGHI TPP UNIT#5

SPECIFICATION NO. PE-TS-445-507-E002

VOLUME II

SECTION I

REVISION 0

DATE: 7.7.2022

SHEET 1 OF 1

## 1.0 SCOPE OF ENQUIRY

- 1.1 Design, Manufacture, Inspection and Testing at Manufacturer's works, proper packing and delivery to site of LT XLPE Power Cable conforming to this specification.
- 1.2 It is not the intent to specify herein all the details of design & manufacture of material. However, the material shall conform in all respects to high standard of design, engineering & workmanship and shall be capable of performing in continuous commercial operation at site condition.
- 1.3 General technical requirements of the LT XLPE Power cables are indicated in Section-II & Datasheet-A. Project specific technical/ quality requirements / changes are listed in Section-I.
- 1.4 The stipulation of Data Sheet-A shall prevail in case of any conflict between the stipulations of Data Sheet-A & Section-II.
- 1.5 The documents shall be in English Language and MKS system of units.

## 2.0 BILL OF QUANTITIES

Quantity requirements shall be as per 'BOQ-cum-price schedule' as part of NIT.

## 3.0 DRAWINGS & DOCUMENTS TO BE SUBMITTED

- 3.1 After placement of order, documents shall be submitted for BHEL & customer's approval as specified in NIT.
- 3.2 Drawings/documents shall be submitted through Document Management System (DMS).



# TECHNICAL SPECIFICATION FOR LT XLPE POWER CABLES

## 1X660 MW SAGARDIGHI TPP UNIT#5

SPECIFICATION NO. PE-TS-445-507-E002

VOLUME II

SECTION I

REVISION 0

DATE: 7.7.2022

SHEET 1 OF 3

### DATA SHEET-A

1.0	Type of Cable	Flame Retardant Low Smoke halogen (FR-LSH)
2.0	Standard applicable in general(Latest amendment to be referred if any)	IS:7098 (Part-1), IS:8130, IS:5831, IS:10810, IS:3975, ASTM:2843, ASTM:2863, IEC-754-1, IEC:60332 (Part-1), IEC:60332-3-23, IEEE:60383
3.0	Voltage Grade	1.1kV
4.0	Number of cores, cross sectional area of conductors and quantities	As per BOQ-Cum-Price Schedule
5.0	<b>FAULT CHARACTERISTICS</b>	
	Fault Level	50kA RMS
	Fault Clearing Time	1.0 sec
6.0	<b>CONDUCTOR</b>	
(a)	Material (Grade and Class)	Stranded compacted plain aluminium conductor of H2 grade / Stranded high conductivity annealed plain copper Class 2
(b)	Standard Applicable	IS: 8130
(c)	Shape	Aluminium / Copper Circular/ Shaped – as per IS
(d)	Min. number and diameter of strands for main and neutral conductor [Neutral conductor cross section w.r.t main conductor shall be as per Table-2 of IS: 7098 (Part-1)]	As per Table-2 of IS: 8130
7.0	<b>INSULATION</b>	
(a)	Material	Cross-Linked Polyethylene(XLPE)
(b)	Standard Applicable	IS: 7098 (Part-1)
(c)	Continuous withstand temperature	90°C
(d)	Short-circuit withstand temperature	250°C
(e)	Method of application	By extrusion; sleeve extrusion not permitted.
(f)	Nominal Thickness of insulation	As per IS: 7098 (Part-1)
8.0	<b>CORE IDENTIFICATION</b>	By color coding as per IS: 7098 - Part -1
9.0	<b>INNER SHEATH</b>	
(a)	Material	Extruded PVC Type ST-2
(b)	Standard Applicable	IS: 7098 (Part-1) & IS: 5831
(c)	Colour	Black
(d)	Whether FR-LSH	No
(e)	Inner sheath applicable for single core cable	No
(f)	Fillers	Acceptable
(g)	Material of fillers (if permitted)	Same as inner sheath (Material of filler to be compatible with that of inner sheath)
(h)	Method of application	



# TECHNICAL SPECIFICATION FOR LT XLPE POWER CABLES

1X660 MW SAGARDIGHI TPP UNIT#5

SPECIFICATION NO. PE-TS-445-507-E002

VOLUME II

SECTION I

REVISION 0

DATE: 7.7.2022

SHEET 2 OF 3

(1)	Multi-core cables:	
(i)	With fillers	Pressure/ Vacuum extruded
(ii)	Without fillers	Pressure extruded
(2)	Single-core cables:	NOT APPLICABLE
10.0	ARMOUR	
(a)	Applicable	Yes (As specified in BOQ cum price schedule)
(b)	Material:	Wherever armouring is applicable
(i)	Single core cables	Non Magnetic Hard drawn Aluminium Round Wire H4 grade to IS: 8130 (as specified in BOQ cum price schedule)
(ii)	Multi-core cables	Galvanised Steel Round Wire conforming to IS 7098 Part-I (as specified in BOQ cum price schedule)
(iii)	Standard Applicable	Dimension as per IS: 7098 (Part-1) Table-6 and tolerance on dimension as per IS:3975
(c)	Minimum Coverage	90%
(d)	Gap between armour wires	Shall not exceed one armour wire space (No cross-over/ over-riding)
(e)	Breaking load of joint	95 % of normal armour
11.0	OUTERSHEATH	
(a)	Material	PVC Type ST2 as per IS: 5831
(b)	Colour	Black
(c)	Whether FR-LSH	Yes
(d)	Method of application	Extruded
(e)	Thickness of outer sheath	As per Table-8 of IS: 7098 (Part-1)
(f)	Marking	<p>Cable size (cross section area and no. of cores), voltage grade and Reference IS @ 1m (by embossing)  Word "XLPE", "FR-LSH" @ 1m (by embossing)  Manufacturer's name and/ or trade mark, year of manufacture @ 1m (by embossing)  'BHEL' and 'CUSTOMER' name @ 1m (by embossing)</p> <p>Progressive sequential marking of length of the cable in metres @ 1m (by embossing/ printing)</p> <p>The embossing shall be progressive, automatic, in line and marking shall be legible and indelible</p>
12.0	FR-LS CHARACTERISTICS	
(a)	Oxygen index	Min 29 (As per IS 7098-I /ASTMD 2863)
(b)	Temperature index	Min. 250°C(As per IS 7098-I /ASTMD 2863)
(c)	Acid gas generation	Max. 20% by weight (As per IS 7098-I /IEC-60754-1)
(d)	Smoke density rating	Max. 60% (As per IS 7098-I /ASTM D 2843)
(e)	Flammability Test	
(i)	Flammability test for single cable	YES As per IEC-60332 Part-1
(ii)	Flammability test for bunched cables	YES As per IEC-60332 Part-3-23, CAT-B
(iii)	Flammability test as per IEEE: 60383	YES



# TECHNICAL SPECIFICATION FOR LT XLPE POWER CABLES

1X660 MW SAGARDIGHI TPP UNIT#5

SPECIFICATION NO. PE-TS-445-507-E002

VOLUME II

SECTION I


REVISION 0

DATE: 7.7.2022

SHEET 3 OF 3

(iv)	As per Swedish Chimney test SEN-SS-424-1475-F3	YES
13.0	Anti-rodent and Termite repulsion Test	YES
15.0	TOLERANCE ON OUTER DIAMETER	± 2mm
16.0	MINIMUM BENDING RADIUS	
(a)	Single core cables	15 x O.D.
(b)	Multi core cables	12 x O.D.
17.0	SAFE PULLING FORCE	
(a)	Aluminium conductor cable	30 N/ sq. mm.
(b)	Copper conductor cable (if applicable)	50 N/ sq. mm
18.0	CABLE DRUMS	
(a)	Type of Drum	Wooden (heavy construction) as per IS 10418
(b)	Standard drum length	500m (±) 5% / 1000m (±) 5%. (as specified in BOQ-Cum- Priced Schedule)
(c)	Painting	Entire surface to be painted
(d)	Outermost Layer	To be covered with waterproof polyethylene
(e)	Construction details	Clause no 4.2 of Section-II of this technical specification
(f)	Particular details on Drum	<p>The cable drums shall carry the following details in printed form:</p> <ul style="list-style-type: none"> <li>a) Manufacturer's name or trade make</li> <li>b) Type of cable and voltage grade</li> <li>c) Year of manufacture</li> <li>d) Type of insulation</li> <li>e) No. of core and sizes of cables</li> <li>f) Cable code</li> <li>g) Length of cable on drum</li> <li>h) No. of length on drum if more than one</li> <li>i) Direction of rotation by arrow</li> <li>j) Approx. gross mass</li> <li>k) IS number and ISI mark</li> </ul> <p>The surface of the drum and the outer most cable layer shall be covered with water proof cover. Both the ends of the cables shall be properly sealed with heat shrinkable PVC/ rubber caps secured by 'U' nails so as to eliminate ingress of water during transportation, storage and erection. Wood preservative anti-termite treatment shall be applied to the entire drum. Wooden drums shall comply with IS: 10418</p>
(g)	Cable packing	Please refer Clause no 4.2 of Section-II of this technical specification. It may be noted that the outer most cable layer shall be covered with water proof cover polythene followed by complete drum covering with wooden plank of suitable thickness across flanges. (Refer typical drawing of cable drum packing, attached in section -II)
19.0	Sea Worthy packing	No

1035432/2022/PS-PEM-EL

<div>32/2022/PS-PEM-EL</div> <div></div>	<div>TECHNICAL SPECIFICATION FOR LT XLPE POWER CABLES</div> <div>1X660 MW SAGARDIGHI TPP UNIT#5</div>	SPECIFICATION NO. PE-TS-445-507-E002		
		VOLUME II		
		SECTION I		
		REV NO. 0    DATE 7.7.2022		
		SHEET    1                      OF    3		

DATASHEET C

**GUARANTEED TECHNICAL PARTICULARS  
(TO BE SUBMITTED BY SUCCESSFUL BIDDER)**

S.No.		Unit	Description
<b>A</b>	<b>GENERAL</b>	-	
1	Name of manufacturer	-	
2	Place of Manufacture	-	
3	Current rating of cables conforms to	-	
4	Short circuit rating conforms to	-	
5	Formula for calculating short circuit current for different duration	-	
6	Permissible conductor temperature		
	(a) Maximum continuous rating	deg. C	
	(b) Short circuit rating	deg. C	
7	(a) Installation Conditions at site		
	i) Ambient air temperature	deg. C	
	ii) Ground temperature	deg. C	
	iii) Depth of laying of cables buried in ground	cm	
8	CHARACTERISTICS OF FRLS SHEATH		
	(a) Oxygen index	%	
	(b) Temperature index	deg. C	
	(c) Acid gas generation	%	
	(d) Smoke density rating	%	
9	CABLE DRUMS		
	(a) Type & construction	-	
	(b) Standard drum length	Mtr	
	(c) Tolerance on drum length	%	
<b>B</b>	<b>INFORMATION TO BE FILLED IN FOR EACH SIZE CABLE IN THE FORM OF TABLE</b>		
1	No. of cores x size	No. x sq.mm	
2	Voltage grade (Uo/U)	kV	
3	Base current ratings (*) based on Sl. (A) 7.0		
	(a) In air	Amp	
	(b) In ground	Amp	
	(c) ducts	Amp	

NAME OF VENDOR			SEAL	REV.	
NAME	SIGNATURE	DATE			

1035432/2022/PS-PEM-EL



# TECHNICAL SPECIFICATION FOR LT XLPE POWER CABLES

1X660 MW SAGARDIGHI TPP UNIT#5

SPECIFICATION NO. PE-TS-445-507-E002

VOLUME II

SECTION I

REV NO. 0 DATE 7.7.2022

SHEET 2 OF 3

4	Short circuit rating for 1 sec duration	kA	
5	(a) D.C. resistance of conductor at 20 deg C (main / neutral)	ohm/km	
	(b) A.C. resistance of conductor at 90 deg. C (main / neutral)	ohm/km	
	(c) Reactance of cable at Normal frequency	ohm/km	
	(d) Electrostatic capacitance of cable at normal frequency	μF/km	
6	CONDUCTOR		
	(a) Material type	-	
	(b) Grade	-	
	(c) No & dia of wires in each core before stranding	no x mm	
	(d) Shape	-	
7	INSULATION		
	(a) Material	-	
	(b) Nominal thickness (main / neutral)	mm	
	(c) Minimum thickness (main / neutral)	mm	
	(d) Minimum volume resistivity at 27 deg. C	Ohm-cm	
	(e) Minimum volume resistivity at 90 deg. C	Ohm-cm	
8	INNERSHEATH		
	(a) Material	-	
	(b) Whether FRLS	-	
	(c) Thickness (min.)	mm	
	(d) Method of application for multi-core cables	-	
	(e) Type and shape of fillers (if used)	-	
	(f) Colour	-	
9	ARMOUR		
	(a) Material	-	
	(b) Type of armour	-	
	(c) Size/ dimensions (Nominal dia of wire)	mm	
	(d) Minimum no. of round / formed wires	No.	
	(e) Minimum coverage	%	
	(f) Gap between armour wire/strip	-	
	(g) Breaking load of joint	-	
	(h) Maximum resistivity of GS formed / Round wire	Ohm-cm	
	(i) Maximum resistivity of Aluminium round wire	Ohm-cm	
10	OUTERSHEATH		
	(a) Material	-	
	(b) Whether FRLS	-	
	(c) Minimum thickness	mm	

NAME OF VENDOR			SEAL	REV.	
NAME	SIGNATURE	DATE			

1035432/2022/PS-PEM-EL



# TECHNICAL SPECIFICATION FOR LT XLPE POWER CABLES

1X660 MW SAGARDIGHI TPP UNIT#5

SPECIFICATION NO. PE-TS-445-507-E002

VOLUME II

SECTION I

REV NO. 0 DATE 7.7.2022

SHEET 3 OF 3

	(d) Colour	-	
	(e) Method of application	-	
11	DIAMETERS		
	(a) Diameter of insulated conductor	mm	
	(b) Cable diameter under armour	mm	
	(c) Cable diameter over armour	mm	
	(d) Overall diameter of cable	mm	
	(e) Tolerance on overall diameter	(±) mm	
12	Ovality	mm	
13	Minimum bending radius	x O.D	
14	Safe Pulling Force	N/mm <sup>2</sup>	
15	Weight of cable	kg./km	
16	Dimension of drum	mm	
17	Shipping weight (approx.)	kg	
18	Cable marking on outer sheath	-	
19	Marking on drum	-	

(\*) For single core cables, the continuous current rating shall be furnished separately for armour earthed at one end and at both ends.

NAME OF VENDOR			SEAL	REV.	
NAME	SIGNATURE	DATE			

1035432/2022/PS-PEM-EL



# TECHNICAL SPECIFICATION FOR LT XLPE POWER CABLES

1X660 MW SAGARDIGHI TPP UNIT#5

SPECIFICATION NO. PE-TS-445-507-E002

VOLUME II

SECTION II

REVISION 0

DATE: 7.7.2022

## SECTION-II

### STANDARD TECHNICAL REQUIREMENTS



## TECHNICAL SPECIFICATION FOR LT XLPE Power Cable

1X660 MW SAGARDIGHI TPP UNIT#5

SPECIFICATION NO. PE-TS-445-507-E002

VOLUME II

SECTION II

REVISION 0

DATE: 7.7.2022

Sheet 1 of 2

### 1.0 CODES AND STANDARDS

- 1.1 The material shall comply with all currently applicable safety codes and statutory regulations of India as well as of the locality where the material is to be installed.
- 1.2 The design, material, construction, manufacture, inspection and testing of LT XLPE POWER Cable shall conform to the latest revision of relevant standards as per Data Sheet-A.
- 1.3 In case of conflict between the applicable reference standard and this specification, this specification shall govern.

### 2.0 TECHNICAL REQUIREMENTS

- 2.1 LT XLPE POWER Cable shall be supplied as per technical particulars specified in Data Sheet – A.

### 3.0 QUALITY ASSURANCE, TESTING & INSPECTION

- 3.1 Bidder shall confirm compliance with the BHEL Standard Quality Plan (PE-QP-999-507-E002, Rev-02) as attached with the specification without any deviations. At contract stage (project specific), the successful bidder shall submit the same QP for BHEL/ ultimate customer's approval. In case bidder has reference QP agreed with ultimate customer, same can be submitted for specific project after award of contract for BHEL/ultimate customer's approval. There shall be no commercial implication to BHEL on account of minor changes in QP during contract stage.
- 3.2 All materials shall be procured, manufactured, inspected and tested by vendor/ sub-vendor as per approved quality plan.
- 3.3 Type testing, routine / acceptance testing and special testing requirements shall be as per Annexure –A to QAP. Charges for all these tests for all the equipments & components shall be deemed to be included in the bid price (except UV Radiation & Hydraulic Stability test).
- 3.4 The charges of UV Radiation test & Hydrolytic Stability test (if applicable) shall be reimbursed extra at actual against original money receipt of Govt. Lab. (CPRI/ ERDA etc).
- 3.5 Cost of cables consumed for testing shall be to bidder's account.

### 4.0 PACKING

- 4.1 Cables shall be supplied in non-returnable drums. Material of cable drums shall be wooden.
- 4.2 For wooden drums, all wooden parts shall be manufactured from seasoned wood treated with copper naphthenates / zinc naphthenates (refer IS: 401) and anti-termite. The surface of the drum and the outer most cable layer shall be covered with water proof cover. Both the ends of the cables shall be properly sealed with heat shrinkable PVC/ rubber caps secured by 'U' nails so as to eliminate ingress of water during transportation, storage and erection. Dimensions of wooden drums shall be as per IS 10418. All ferrous parts shall be treated with suitable rust protective



**TECHNICAL SPECIFICATION FOR  
LT XLPE Power Cable**

**1X660 MW SAGARDIGHI TPP UNIT#5**

SPECIFICATION NO. PE-TS-445-507-E002

VOLUME II

SECTION II


REVISION 0

DATE: 7.7.2022

Sheet 2 of 2

finish or coating to avoid rusting during transit and storage. BIS certification mark shall be stamped on each cable drum.

- 4.3 Each drum shall carry manufacturer's name, purchaser's name, address and contract no., item no. & type, size & length of cable and net gross weight stencilled on both sides of drum. A tag containing same information shall be attached to the leading end of the cable. An arrow & suitable accompanying wording shall be marked on one end of the reel indicating the direction in which it should be rolled.

	<b>MANUFACTURER/ BIDDER/ SUPPLIER NAME &amp; ADDRESS</b>	<b>STANDARD QUALITY PLAN</b>		<b>SPEC. NO :</b>	<b>DATE: 22</b>
		<b>CUSTOMER :</b>		<b>QP NO.: PE-QP-999-507-E002, REV 02.</b>	
		<b>PROJECT:</b>		<b>PO NO.:</b>	
		<b>ITEM: LT XLPE POWER CABLE</b>	<b>SYSTEM: CABLE</b>	<b>SECTION: II</b>	<b>SHEET 1 OF 12</b>

Sl. No.	COMPONENTS & OPERATIONS	CHARACTERISTICS	CLASS	TYPE OF CHECK	QUANTUM OF CHECK	REFERENCE DOCUMENT	ACCEPTANCE NORMS	FORMAT OF RECORD	AGENCY	REMARKS
1	2	3	4	5	6	7	8	9	* D	** M C N
					M C/N					

**1.0 RAW MATERIALS**

**1.1 Aluminium /Copper Rods** **GENERAL :**

	<b>(Conductor/ Armour Wire)</b>	1. Physical properties	MA	Physical Tests	Sample/ Batch	Sample / Batch	IS:8130 (Al), IS:613 (Cu)	IS:8130 (Al), IS:613 (Cu)	Test Cert.	✓	P/V	V	-	
		2. Elec. Properties	MA	Electrical Tests	Sample/ Batch	Sample / Batch	-do-	-do-	-do-	✓	P/V	V	-	

**SPECIFIC CHECKS:**

	a) Make	MA	Verify	100%	100%	Manufacturer approved source	Manufacturer approved source	Test Cert.	✓	P	V	-	
	b) Grade	MA	-do-	-do-	-do-	IS:8130 (Al), IS:613 (Cu)	IS:8130 (Al), IS:613 (Cu)	-do-	✓	P	V	-	
	c) Resistivity	MA	Electrical Tests	Manufacturer std.	Manufacturer std.	IS:613 (Cu), IS:5082 (Al)	IS:613 (Cu), IS:5082 (Al)	-do-	✓	P	V	-	


**1.2 XLPE Compound for insulation** **GENERAL :**

	1. Physical properties	MA	Physical Tests	Sample/ Batch	Sample / Batch	IS 7098-I	IS 7098-I	Test Cert.	✓	P	V	-	
--	------------------------	----	----------------	---------------	----------------	-----------	-----------	------------	---	---	---	---	--

BHEL					
ENGINEERING			QUALITY		
	Sign & Date	Name		Sign & Date	Name
Prepared by:	<i>[Signature]</i> 18.03.2020	VIKAS KUMAR SINGH	Checked by:	<i>[Signature]</i> 19/03/20	KUNAL GANDHI
Reviewed by:	<i>[Signature]</i> 18/03/20	MANISH SHUKLA	Reviewed by:	<i>[Signature]</i> 19/03/20	RITESH KUMAR JAISWAL

BIDDER/ SUPPLIER	
Sign & Date	
Seal	


FOR CUSTOMER REVIEW & APPROVAL			
Doc No:			
	Sign & Date	Name	Seal
Reviewed by:			
Approved by:			

	MANUFACTURER/ BIDDER/	STANDARD QUALITY PLAN		SPEC. NO :	DATE: 23
	SUPPLIER NAME & ADDRESS	CUSTOMER :		QP NO.: PE-QP-999-507-E002, REV 02.	103
		PROJECT:		PO NO.:	
		ITEM: LT XLPE POWER CABLE	SYSTEM: CABLE	SECTION: II	SHEET 2 OF 12

Sl. No.	COMPONENTS & OPERATIONS	CHARACTERSTICS	CLAS S	TYPE OF CHECK	QUANTUM OF CHECK	REFERENCE DOCUMENT	ACCEPTANC E NORMS	FORMAT OF RECORD	AGENCY	REMARKS				
1	2	3	4	5	6	7	8	9	* D	**				
					M					C/N		M	C	N

		2. Elec. Properties	MA	Electrical Tests	Sample/ Batch	Sample / Batch	-do-	-do-	-do-	✓	P	V	-	
		<b><u>SPECIFIC CHECKS:</u></b>												
		a) Make	MA	Verify	100%	100%	Manufacturer approved source	Manufacturer approved source	Test Cert.	✓	P/V	V	-	
		b) Type/ Grade	MA	-do-	-do-	-do-	-do-	-do-	-do-	✓	P/V	V	-	
		c) Shelf life/ Storage condition	MA	-do-	-do-	-do-	-do-	-do-	-do-	✓	P/V	V	-	
1.3	PVC Compound (for sheath)	<b><u>GENERAL:</u></b>												
		1. Physical properties	MA	Physical Tests	Sample/ Batch	Sample / Batch	IS 5831	IS 5831	Test Cert.	✓	P/V	V	-	
		2. Elec. Properties	MA	Electrical Tests	Sample/ Batch	Sample / Batch	-do-	-do-	-do-	✓	P/V	V	-	
		3. FRLS Properties (as applicable)	CR	Chemical/ Environ.	Sample/ Batch	Sample / Batch	Approved datasheet	Approved datasheet	-do-	✓	P/V	V	-	
		<b><u>SPECIFIC CHECKS:</u></b>												

BHEL						BIDDER/ SUPPLIER		FOR CUSTOMER REVIEW & APPROVAL			
ENGINEERING			QUALITY			Sign & Date		Doc No:			
	Sign & Date	Name		Sign & Date	Name	Seal			Sign & Date	Name	Seal
Prepared by:	<i>Vikas</i> 8/03/2020	VIKAS KUMAR SINGH	Checked by:	<i>Kunal</i> 19/3/20	KUNAL GANDHI			Reviewed by:			
Reviewed by:	<i>Manish</i> 18/03/20	MANISH SHUKLA	Reviewed by:	<i>Ritesh</i> 19/3/2020	RITESH KUMAR JAISWAL			Approved by:			

	<b>MANUFACTURER/ BIDDER/ SUPPLIER NAME &amp; ADDRESS</b>	<b>STANDARD QUALITY PLAN</b>		<b>SPEC. NO :</b>	<b>DATE: 24</b>
		<b>CUSTOMER :</b>		<b>QP NO.:</b> PE-QP-999-507-E002, REV 02.	
		<b>PROJECT:</b>		<b>PO NO.:</b>	
<b>ITEM:</b> LT XLPE POWER CABLE		<b>SYSTEM:</b> CABLE	<b>SECTION:</b> II	<b>SHEET 3 OF 12</b>	


Sl. No.	COMPONENTS & OPERATIONS	CHARACTERSTICS	CLAS S	TYPE OF CHECK	QUANTUM OF CHECK		REFERENCE DOCUMENT	ACCEPTANC E NORMS	FORMAT OF RECORD		AGENCY			REMARKS
1	2	3	4	5	6		7	8	9	*	**			
					M	C/N				D	M	C	N	

		a) Make	MA	Verify	100%	100%	Manufactur er approved source	Manufactur er approved source	Test Cert.	✓	P	V	-	
		b) Type/ Grade	MA	-do-	-do-	-do-	Approved datasheet	Approved datasheet	-do-	✓	P	V	-	
		c) Shelf life/ Storage condition	MA	-do-	-do-	-do-	Compound Manufactur er std.	Compound Manufactur er std.	-do-	✓	P	V	-	
1.4	Fillers (as applicable)	1. Make	MA	Verify	100%	100%	Manufactur er approved source	Manufactur er approved source	Test Cert.	✓	P	V	-	Fillers material chosen shall be compatible with the temperatur e rating of the cable and shall have no deleterious effect on any other

BHEL					
ENGINEERING			QUALITY		
	Sign & Date	Name		Sign & Date	Name
Prepared by:	<i>Vikas</i> 18/03/2020	VIKAS KUMAR SINGH	Checked by:	<i>Kunal Gandhi</i> 19/3/20	KUNAL GANDHI
Reviewed by:	<i>Manish</i> 18/03/20	MANISH SHUKLA	Reviewed by:	<i>Ritesh Kumar</i> 19/3/2020	RITESH KUMAR JAISWAL

BIDDER/ SUPPLIER	
Sign & Date	
Seal	

FOR CUSTOMER REVIEW & APPROVAL			
Doc No:			
	Sign & Date	Name	Seal
Reviewed by:			
Approved by:			

	<b>MANUFACTURER/ BIDDER/ SUPPLIER NAME &amp; ADDRESS</b>		<b>STANDARD QUALITY PLAN</b>				<b>SPEC. NO :</b>		<b>DATE: 25</b>	
			<b>CUSTOMER :</b>				<b>QP NO.: PE-QP-999-507-E002, REV 02.</b>			
			<b>PROJECT:</b>				<b>PO NO.:</b>			
			<b>ITEM: LT XLPE POWER CABLE</b>		<b>SYSTEM: CABLE</b>		<b>SECTION: II</b>		<b>SHEET 4 OF 12</b>	

Sl. No.	COMPONENTS & OPERATIONS	CHARACTERSTICS	CLAS S	TYPE OF CHECK	QUANTUM OF CHECK	REFERENCE DOCUMENT	ACCEPTANC E NORMS	FORMAT OF RECORD	AGENCY	REMARKS
1	2	3	4	5	6	7	8	9	* D	** M C N
					M C/N					

														component of cable)
		2. Type/ Grade	MA	-do-	-do-	-do-	Appd. Data Sheet	Appd. Data Sheet	-do-	✓	P/V	V	-	
1.5	Galvanised steel wire/strip for Armour (as applicable)	GENERAL:												
		1. Make	MA	Verify	Manufac turer std.	Manufa cturer std.	Manufactur er approved source	Manufactur er approved source	Test Cert.	✓	P	V	-	
		2. Dimension	MA	Measurem ent	-do-	-do-	Appd. Data Sheet	Appd. Data Sheet	-do-		P/V	-	-	
		3. Phy. and Elec. Properties	MA	Physical & Electrical Tests	Sample*	Sample *	-do-	-do-	-do-	✓	P/V	V	-	
		4. Galvanization Quality	MA	Galv. Tests	-do-	-do-	IS 3975	IS 3975	-do-		P/V	-	-	
1.6	Wooden Drum	1. Phy. & Constructional checks	MA		Mfr's Plant Std.	Mfr's Plant Std.	IS 10418	IS 10418	Test Cert.	✓	P	V	-	


<b>BHEL</b>						<b>BIDDER/ SUPPLIER</b>		<b>FOR CUSTOMER REVIEW &amp; APPROVAL</b>			
<b>ENGINEERING</b>			<b>QUALITY</b>			Sign & Date		Doc No:			
	Sign & Date	Name		Sign & Date	Name	Seal			Sign & Date	Name	Seal
Prepared by:	<i>Vikas</i> 18/03/2020	VIKAS KUMAR SINGH	Checked by:	<i>Kunal</i> 19/03/20	KUNAL GANDHI			Reviewed by:			
Reviewed by:	<i>Manish</i> 18/03/20	MANISH SHUKLA	Reviewed by:	<i>Ritesh</i> 19/03/20	RITESH KUMAR JAISWAL			Approved by:			

	<b>MANUFACTURER/ BIDDER/</b>	<b>STANDARD QUALITY PLAN</b>				<b>SPEC. NO :</b>			<b>DATE: 26</b>		
	<b>SUPPLIER NAME &amp; ADDRESS</b>	<b>CUSTOMER :</b>					<b>QP NO.: PE-QP-999-507-E002, REV 02.</b>				
		<b>PROJECT:</b>					<b>PO NO.:</b>				
		<b>ITEM: LT XLPE POWER CABLE</b>			<b>SYSTEM: CABLE</b>		<b>SECTION: II</b>			<b>SHEET 5 OF 12</b>	

Sl. No.	COMPONENTS & OPERATIONS	CHARACTERSTICS	CLAS S	TYPE OF CHECK	QUANTUM OF CHECK		REFERENCE DOCUMENT	ACCEPTANC E NORMS	FORMAT OF RECORD		AGENCY			REMARKS
1	2	3	4	5	6		7	8	9	*	**			
					M	C/N				D	M	C	N	

		2. Anti termite treatment	MA	Chem.	Mfr's Plant Std.	Mfr's Plant Std.	Mfr's Plant Std.	Mfr's Plant Std.	-do-	✓	P	V	-	
1.7	Steel Drum #	1. Dimension	MA	Meas.	Mfr's Plant Std.	Mfr's Plant Std.	Approved drg	Approved drg	Test Cert.	✓	P	V	-	# If required, as per spec.
		2. Surface finish	MA	Visual	-do-	-do-	-	Surface shall be smooth	-do-	✓	P	V	-	
2.0	IN PROCESS													
2.1	Wire Drawing	1. Size	MA	Dimension al	Plant Mfg. Std.	Plant Mfg. Std.	Approved datasheet	Approved datasheet	Inspe ction Repor t/ Test report	✓	P	V	-	
		2. Surface finish	MA	Visual	-do-	-do-	Surface shall be smooth	Surface shall be smooth	-do-	✓	P	V	-	


<b>BHEL</b>						<b>BIDDER/ SUPPLIER</b>		<b>FOR CUSTOMER REVIEW &amp; APPROVAL</b>			
<b>ENGINEERING</b>			<b>QUALITY</b>			Sign & Date		Doc No:			
	Sign & Date	Name		Sign & Date	Name	Seal			Sign & Date	Name	Seal
Prepared by:	<i>Vikas</i> 18/03/2020	VIKAS KUMAR SINGH	Checked by:	<i>Kunal</i> 19/3/20	KUNAL GANDHI			Reviewed by:			
Reviewed by:	<i>Manish</i> 18/03/20	MANISH SHUKLA	Reviewed by:	<i>Ritesh</i> 19/3/20	RITESH KUMAR JAISWAL			Approved by:			

	<b>MANUFACTURER/ BIDDER/</b>	<b>STANDARD QUALITY PLAN</b>				<b>SPEC. NO :</b>			<b>DATE: 27</b>	
	<b>SUPPLIER NAME &amp; ADDRESS</b>	<b>CUSTOMER :</b>				<b>QP NO.: PE-QP-999-507-E002, REV 02.</b>				
		<b>PROJECT:</b>				<b>PO NO.:</b>				
		<b>ITEM: LT XLPE POWER CABLE</b>		<b>SYSTEM: CABLE</b>		<b>SECTION: II</b>			<b>SHEET 6 OF 12</b>	

Sl. No.	COMPONENTS & OPERATIONS	CHARACTERISTICS	CLASS	TYPE OF CHECK	QUANTUM OF CHECK		REFERENCE DOCUMENT	ACCEPTANCE NORMS	FORMAT OF RECORD		AGENCY			REMARKS
1	2	3	4	5	6		7	8	9	*	**			
					M	C/N				D	M	C	N	

		3. % of Elongation	MA	Mechanical	-do-	-do-	IS 8130	IS 8130	-do-	✓	P	V	-	
2.2	Stranding of wires	1. No. of wires	MA	Counting	Plant Mfg. Std.	Plant Mfg. Std.	Appd. Datasheet	Appd. Datasheet	Inspection Report/ Test report	✓	P	V	-	
		2. Resistance	CR	Electrical	-do-	-	-do-	-do-	-do-	-do-	P	-	-	
		3. Sequence, lay length & Direction	MA	Visual, Meas.	One Sample of each size/ lot	-	Mfrs Std.	Mfrs Std.	-do-		P	-	-	
		4. Surface Finish	MA	Visual	100%	-	Surface shall be smooth	Surface shall be smooth	-do-		P	-	-	
		5. Dimension	MA	Measurement	One Sample of each size/ lot	-	Appd. Datasheet	Appd. Datasheet	-do-		P	-	-	
2.3	Core Insulation (XLPE) (No repair permitted)													

BHEL						BIDDER/ SUPPLIER		FOR CUSTOMER REVIEW & APPROVAL			
ENGINEERING			QUALITY			Sign & Date		Doc No:			
	Sign & Date	Name		Sign & Date	Name	Seal			Sign & Date	Name	Seal
Prepared by:	<i>Vikas</i> 20.03.2020	VIKAS KUMAR SINGH	Checked by:	<i>Kunal</i> 19/3/20	KUNAL GANDHI			Reviewed by:			
Reviewed by:	<i>Manish</i> 18/03/20	MANISH SHUKLA	Reviewed by:	<i>Ritesh</i> 19/3/20	RITESH KUMAR JAISWAL			Approved by:			

	<b>MANUFACTURER/ BIDDER/</b>	<b>STANDARD QUALITY PLAN</b>			<b>SPEC. NO :</b>			<b>DATE:</b> 28	
	<b>SUPPLIER NAME &amp; ADDRESS</b>	<b>CUSTOMER :</b>			<b>QP NO.:</b> PE-QP-999-507-E002, REV 02.				
		<b>PROJECT:</b>			<b>PO NO.:</b>				
		<b>ITEM:</b> LT XLPE POWER CABLE		<b>SYSTEM:</b> CABLE		<b>SECTION:</b> II		<b>SHEET 7 OF 12</b>	

Sl. No.	COMPONENTS & OPERATIONS	CHARACTERISTICS	CLASS	TYPE OF CHECK	QUANTUM OF CHECK		REFERENCE DOCUMENT	ACCEPTANCE NORMS	FORMAT OF RECORD		AGENCY			REMARKS
1	2	3	4	5	6		7	8	9	*	**			
					M	C/N				D	M	C	N	

		1. Surface finish	MA	Visual	100%	100%	Free from bulging, burnt particles, lumps, cuts & scratches	Free from bulging, burnt particles, lumps, cuts & scratches	Inspection Report/ Test report	✓	P	V	-	
		2. Eccentricity & Ovality #	CR	Measurement	One Sample of each size/ lot	One Sample of each size/ lot	Mnfr's Std	Mnfr's Std	-do-	✓	P	V	-	
		3. Insulation Thickness	CR	Measurement	-do-	-	Appd. Datasheet	Appd. Datasheet	-do-		P	-	-	
		4. Dia over insulation	MA	Measurement	-do-	-	-do-	-do-	-do-		P	-	-	
		5. Tensile Strength & % Elongation	MA	Mechanical	100%	-	IS:1554-I, IS:5831	IS:1554-I, IS:5831	-do-		P	-	-	
		6. Spark Test or Water immersion test	CR	Electrical	100%	-	Mnfr's Std	Mnfr's Std	-do-	Mnfr's Std	P	-	-	
2.4	Core Laying	1. Dia over laid up core	MA	Measurement	One Sample of each size/ lot	-	Appd. Datasheet	Appd. Datasheet	Inspection Report/ Test report		P	-	-	

BHEL					
ENGINEERING			QUALITY		
	Sign & Date	Name		Sign & Date	Name
Prepared by:	<i>Manish</i> 18.03.2020	VIKAS KUMAR SINGH	Checked by:	<i>Kunal Gandhi</i> 19/3/20	KUNAL GANDHI
Reviewed by:	<i>Manish</i> 19/03/20	MANISH SHUKLA	Reviewed by:	<i>Ritesh Kumar</i> 19/3/2020	RITESH KUMAR JAISWAL

BIDDER/ SUPPLIER	
Sign & Date	
Seal	


FOR CUSTOMER REVIEW & APPROVAL			
Doc No:			
	Sign & Date	Name	Seal
Reviewed by:			
Approved by:			

	<b>MANUFACTURER/ BIDDER/</b>	<b>STANDARD QUALITY PLAN</b>				<b>SPEC. NO :</b>			<b>DATE: 29</b>		
	<b>BHEL</b>	<b>SUPPLIER NAME &amp; ADDRESS</b>	<b>CUSTOMER :</b>				<b>QP NO.: PE-QP-999-507-E002, REV 02.</b>				
			<b>PROJECT:</b>				<b>PO NO.:</b>				
			<b>ITEM: LT XLPE POWER CABLE</b>		<b>SYSTEM: CABLE</b>		<b>SECTION: II</b>			<b>SHEET 8 OF 12</b>	

Sl. No.	COMPONENTS & OPERATIONS	CHARACTERISTICS	CLASS	TYPE OF CHECK	QUANTUM OF CHECK	REFERENCE DOCUMENT	ACCEPTANCE NORMS	FORMAT OF RECORD	AGENCY	REMARKS
1	2	3	4	5	6	7	8	9	* D	** M C N
					M C/N					

		2. Sequence of lay & direction	MA	Visual & Meas.	-do-	-	IS 7098-I & Mfr. Std.	IS 7098-I & Mfr. Std.	-do-		P	-	-	
						-								
2.5	Inner Sheath Extrusion (as applicable)	1. Surface finish	MA	Visual	100%	-	Surface shall be smooth	Surface shall be smooth	Inspection Report/ Test report		P	-	-	
		2. Thickness	CR	Measurement	One Sample of each size/ lot	-	Appd. Datasheet	Appd. Datasheet	-do-		P	-	-	
		3. Dia over inner sheath	MA	-do-	-do-	-	-do-	-do-	-do-		P	-	-	
2.6	Armour( as applicable)	1. No.of wires/Strips	MA	Counting	At the start of the process	-	Mnfr's Std	Mnfr's Std	Inspection Report/ Test report		P	-	-	
		2. Lay length / Direction	MA	Visual & Meas.	-do-	-	Mfr. Std.	Mfr. Std.	-do-		P	-	-	
		3. Dia over armouring	MA	Measurement	-do-	-	Appd. Datasheet	Appd. Datasheet	-do-		P	-	-	

<b>BHEL</b>						<b>BIDDER/ SUPPLIER</b>		<b>FOR CUSTOMER REVIEW &amp; APPROVAL</b>			
<b>ENGINEERING</b>			<b>QUALITY</b>			Sign & Date		Doc No:			
	Sign & Date	Name		Sign & Date	Name	Seal			Sign & Date	Name	Seal
Prepared by:	<i>Vikas</i> 18/03/2020	VIKAS KUMAR SINGH	Checked by:	<i>Kunal</i> 19/03/2020	KUNAL GANDHI			Reviewed by:			
Reviewed by:	<i>Manish</i> 18/03/2020	MANISH SHUKLA	Reviewed by:	<i>Ritesh</i> 19/03/2020	RITESH KUMAR JAISWAL			Approved by:			

	<b>MANUFACTURER/ BIDDER/ SUPPLIER NAME &amp; ADDRESS</b>	<b>STANDARD QUALITY PLAN</b>		<b>SPEC. NO :</b>		<b>DATE:</b> 30	
		<b>CUSTOMER :</b>		QP NO.: PE-QP-999-507-E002, REV 02.			
		<b>PROJECT:</b>		PO NO.:			
		<b>ITEM: LT XLPE POWER CABLE</b>		<b>SYSTEM: CABLE</b>		<b>SECTION: II</b>	
						<b>SHEET 9 OF 12</b>	


Sl. No.	COMPONENTS & OPERATIONS	CHARACTERISTICS	CLASS	TYPE OF CHECK	QUANTUM OF CHECK	REFERENCE DOCUMENT	ACCEPTANCE NORMS	FORMAT OF RECORD	AGENCY	REMARKS
1	2	3	4	5	6	7	8	9	* D	** M C N
					M C/N					

		4. Coverage	MA	Measurement	-do-	-	-do-	-do-	-do-		P	-	-	
2.7	Outer Sheath Extrusion (No repair permitted)	1. Surface finish	MA	Visual	100%	-	Surface shall be smooth	Surface shall be smooth	Inspection Report/ Test report		P	-	-	
		2. Sheath Thickness	CR	Measurement	One Sample of each size/ lot	-	Appd. Datasheet	Appd. Datasheet	-do-		P	-	-	
		3. Dia over outer sheath	MA	-do-	-do-	-	-do-	-do-	-do-		P	-	-	
		4. Embossing/ Sequential Marking	MA	Visual	100%	-	Approved data sheet	Approved data sheet	-do-		P	-	-	
3.0	Final Inspection (INTERNAL)	1. Routine Test (Refer Note-H)	CR	Electrical Tests & Measurement	100%	100%	#	#	-do-	✓	P	V	V	#: Refer Annexure-A to QP

BHEL					
ENGINEERING			QUALITY		
	Sign & Date	Name		Sign & Date	Name
Prepared by:	<i>Kunal</i> 18-03-2020	VIKAS KUMAR SINGH	Checked by:	<i>Kunal</i> 19/3/20	KUNAL GANDHI
Reviewed by:	<i>Manish</i> 18/03/20	MANISH SHUKLA	Reviewed by:	<i>Ritesh</i> 19/3/20	RITESH KUMAR JAISWAL

BIDDER/ SUPPLIER	
Sign & Date	
Seal	

FOR CUSTOMER REVIEW & APPROVAL			
Doc No:			
	Sign & Date	Name	Seal
Reviewed by:			
Approved by:			

	<b>MANUFACTURER/ BIDDER/ SUPPLIER NAME &amp; ADDRESS</b>	<b>STANDARD QUALITY PLAN</b>		<b>SPEC. NO :</b>	<b>DATE:</b>
		<b>CUSTOMER :</b>		<b>QP NO.:</b> PE-QP-999-507-E002, REV 02.	
		<b>PROJECT:</b>		<b>PO NO.:</b>	
		<b>ITEM:</b> LT XLPE POWER CABLE	<b>SYSTEM:</b> CABLE	<b>SECTION:</b> II	<b>SHEET 10 OF 12</b>


Sl. No.	COMPONENTS & OPERATIONS	CHARACTERSTICS	CLAS S	TYPE OF CHECK	QUANTUM OF CHECK	REFERENCE DOCUMENT	ACCEPTANC E NORMS	FORMAT OF RECORD	AGENCY	REMARKS
1	2	3	4	5	6	7	8	9	* D	** M C N
					M C/N					

4.0	Final Inspection (EXTERNAL)	1. Finish & Length (Cable & cable drum)	MA	Visual	One drum in each Lot	One drum in each Lot	Appd. Datasheet	Free from Porosity, Bulging, Burnt particles, lumps, cuts & scratches	Inspe ction Repor t/ Test report	✓	P	W	W	
		2. Dimension	MA	-do-	IS 7098-I	IS 7098-I	Appd. Datasheet	Appd. Datasheet	-do-	✓	P	W	W	
		3. Armouring - Coverage & No.of Wires/Strips	MA	Visual & Meas.	-do-	-do-	-do-	-do-	-do-	✓	P	W	W	
		4. Marking & Colour Coding	MA	Visual	-do-	-do-	-do-	-do-	-do-	✓	P	W	W	
		5. Acceptance Tests (Refer Note-H)	CR	Phy, Elect. Tests & FRLS Tests	Sample #	Sample #	#	-do-	-do-	✓	P	W	W	
		6. Type Tests (Refer Note-H)	CR	Physical & Electrical Tests	Sample #	Sample #	-do-	-do-	-do-	✓	P	W	W	

BHEL					
ENGINEERING			QUALITY		
	Sign & Date	Name		Sign & Date	Name
Prepared by:	<i>[Signature]</i> 18-03-2020	VIKAS KUMAR SINGH	Checked by:	<i>[Signature]</i> 19/3/20	KUNAL GANDHI
Reviewed by:	<i>[Signature]</i> 18/03/20	MANISH SHUKLA	Reviewed by:	<i>[Signature]</i> 19/3/20	RITESH KUMAR JAISWAL

BIDDER/ SUPPLIER	
Sign & Date	
Seal	

FOR CUSTOMER REVIEW & APPROVAL			
Doc No:			
	Sign & Date	Name	Seal
Reviewed by:			
Approved by:			

	<b>MANUFACTURER/ BIDDER/ SUPPLIER NAME &amp; ADDRESS</b>	<b>STANDARD QUALITY PLAN</b>		<b>SPEC. NO :</b>	<b>DATE:</b> 32
		<b>CUSTOMER :</b>		<b>QP NO.:</b> PE-QP-999-507-E002, REV 02.	103
		<b>PROJECT:</b>		<b>PO NO.:</b>	
<b>ITEM:</b> LT XLPE POWER CABLE		<b>SYSTEM:</b> CABLE	<b>SECTION:</b> II	<b>SHEET 11 OF 12</b>	

Sl. No.	COMPONENTS & OPERATIONS	CHARACTERSTICS	CLAS S	TYPE OF CHECK	QUANTUM OF CHECK	REFERENCE DOCUMENT	ACCEPTANC E NORMS	FORMAT OF RECORD	AGENCY	REMARKS
1	2	3	4	5	6	7	8	9	* D	** M C N
					M C/N					


5.0	Packing	End sealing / Polythene wrapping	MA	Visual	100%	100%	Appd. Datasheet	Appd. Datasheet	-do-	✓	P	W	
-----	---------	----------------------------------	----	--------	------	------	-----------------	-----------------	------	---	---	---	--

#### NOTES:

- Joints in conductors & armour shall be as permitted by IS:8130 & IS:7098-I respectively.
- No repair of core insulation permitted.
- Cable ends shall be sealed.
- Record of raw material, process & all stages shall be certified by Vendors QC and are liable to audit check by purchaser.
- Fillers/dummy cores etc. Shall be as per BHEL specification.
- Wherever extent of check for stage is mentioned as 'sample' & not defined in QP, the same shall be as per vendors sampling plan agreed by purchaser.
- Vendor shall furnish compliance certificate to the inspection agency confirming the packing as per IS/ BHEL specification.
- For lists of routine tests, acceptance tests & type tests refer annexure to QAP.
- Cable manufacturer to maintain records to show co-relation of raw materials to finished cables i.e. raw material batch/ lot no. should be traceable to the final cable drum number or batch no.
- Cable manufacturer to maintain all quality records identified as per all QP stages enumerated below whether it is identified for BHEL verification or witness or not.
- BHEL reserves the right to perform repeat test, if required.
- Photographs of cable to be despatched shall be sent to BHEL purchase group for review prior to issue of mdcc.
- Project specific QP to be prepared in line with this standard QP.
- In case of export jobs, sea worthy packing as per BHEL technical specification shall be carried out.

#### LEGENDS:

BHEL						BIDDER/ SUPPLIER		FOR CUSTOMER REVIEW & APPROVAL			
ENGINEERING			QUALITY			Sign & Date		Doc No:			
	Sign & Date	Name		Sign & Date	Name	Seal			Sign & Date	Name	Seal
Prepared by:	<i>Manish</i> 18-03-2020	VIKAS KUMAR SINGH	Checked by:	<i>Kunal Gandhi</i> 18/3/20	KUNAL GANDHI						
Reviewed by:	<i>Manish</i> 18/03/20	MANISH SHUKLA	Reviewed by:	<i>Ritesh Kumar</i> 18/3/20	RITESH KUMAR JAISWAL			Reviewed by:			
								Approved by:			

	<b>MANUFACTURER/ BIDDER/ SUPPLIER NAME &amp; ADDRESS</b>		<b>STANDARD QUALITY PLAN</b>				<b>SPEC. NO :</b>		<b>DATE:</b> 33			
			<b>CUSTOMER :</b>				QP NO.: PE-QP-999-507-E002, REV 02.					
			<b>PROJECT:</b>				PO NO.:					
			<b>ITEM: LT XLPE POWER CABLE</b>		<b>SYSTEM: CABLE</b>		<b>SECTION: II</b>		<b>SHEET 12 OF 12</b>			
<b>SI. No.</b>	<b>COMPONENTS &amp; OPERATIONS</b>	<b>CHARACTERSTICS</b>	<b>CLAS S</b>	<b>TYPE OF CHECK</b>	<b>QUANTUM OF CHECK</b>		<b>REFERENCE DOCUMENT</b>	<b>ACCEPTANC E NORMS</b>	<b>FORMAT OF RECORD</b>		<b>AGENCY</b>	<b>REMARKS</b>
1	2	3	4	5	6		7	8	9	*	**	
					M	C/N				D	M	C N

\*RECORDS, IDENTIFIED WITH "TICK"(✓) SHALL BE ESSENTIALLY INCLUDED BY SUPPLIER IN QA DOCUMENTATION,

\*\* M: SUPPLIER/ MANUFACTURER/ SUB-SUPPLIER, B: MAIN SUPPLIER/ BHEL/ THIRD PARTY INSPECTION AGENCY, C: CUSTOMER,

P: PERFORM, W: WITNESS, V: VERIFICATION, AS APPROPRIATE

MA: MAJOR, MI: MINOR, CR: CRITICAL

D: DOCUMENTATION

BHEL					
ENGINEERING			QUALITY		
	Sign & Date	Name		Sign & Date	Name
Prepared by:	<i>Manish</i> 18.03.2020	VIKAS KUMAR SINGH	Checked by:	<i>Ritesh</i> 19/3/20	KUNAL GANDHI
Reviewed by:	<i>Manish</i> 18/03/20	MANISH SHUKLA	Reviewed by:	<i>Ritesh</i> 19/3/20	RITESH KUMAR JAISWAL

BIDDER/ SUPPLIER	
Sign & Date	
Seal	

FOR CUSTOMER REVIEW & APPROVAL			
Doc No:			
	Sign & Date	Name	Seal
Reviewed by:			
Approved by:			

**ANNEXURE-A TO QAP**  
**TYPE/ ACCEPTANCE/ ROUTINE TEST REQUIREMENTS FOR LT XLPE POWER CABLES**

**TYPE/ ACCEPTANCE/ ROUTINE TEST REQUIREMENTS**

**A. Type Test Conduction:**

1. Tests for which "T" is indicated in the 'Test Conduction Required As' column below shall be conducted as Type Test.
2. Sampling:
  - a) Type test to be conducted on each type & size of cable on one drum out of every 10 drums for every lot (CU/AL conductor)
  - b) Flammability Test to be conducted only on one sample/ lot.

**B. Acceptance Test Conduction:**

1. Tests for which "A" is indicated in the 'Test Conduction Required As' column below shall be conducted as Acceptance tests.
2. Sampling:  
Acceptance tests to be conducted on one drum out of every 10 drums/ lot for every size & type.
3. Flammability Test to be conducted only on one sample/ lot (Project specific sampling plan shall be informed later)

**C. Routine Test Conduction:**

1. Tests for which "R" is indicated in the 'Test Conduction Required As' column below shall be conducted as Routine tests.
2. Routine test shall be conducted on 100% drum

**D. Tests listed in S.No-7.0 & 8.0 shall be conducted only on one sample / lot.**

**Note:** LOT shall be considered as per IS: 7098 Part-I, appendix-B.

<u>S. No.</u>	<u>TEST</u>	<u>APPLICABLE FOR</u>	<u>TEST CONDUCTION REQUIRED AS</u>	<u>REFERENCE STANDARD</u>	<u>REMARKS</u>
<b>1.0</b>	<b>Tests for Conductor</b>				
I.	Annealing test	For copper conductor only	<b>T, A</b>	IS 10810 Pt 1	<u>Internal in process Test Report to be furnished for acceptance test</u>
II.	Tensile test	For aluminium conductor only (Not applicable for compacted circular or shaped conductor)	<b>T, A</b>	IS 10810 Pt 2	
III.	Wrapping test	For aluminium conductor only (Not applicable for compacted circular or shaped conductor)	<b>T, A</b>	IS 10810 Pt 3	
IV.	Resistance test	For Al/Cu	<b>T, A, R</b>	IS 10810 Pt 5	


<u>S. No.</u>	<u>TEST</u>	<u>APPLICABLE FOR</u>	<u>TEST CONDUCTION REQUIRED AS</u>	<u>REFERENCE STANDARD</u>	<u>REMARKS</u>
<b>2.0</b>	<b><u>Tests for Armour Wires/Strips</u></b>				
I.	Measurement of dimensions	Applicable for Aluminium wire & GS wire/Strip	<b>T, A</b>	IS 10810 Pt 36	
II.	Tensile test	Applicable for Aluminium wire & GS wire/Strip	<b>T, A</b>	IS 10810 Pt 37	
III.	Elongation at break test	Applicable for GS wire/Strip only	<b>T, A</b>	IS 10810 Pt 37	
IV.	Torsion test	For GS round wire only	<b>T, A</b>	IS 10810 Pt 38	
V.	Winding / Adhesion Test	For GS strip only	<b>T, A</b>	IS 10810 Pt 39	
VI.	Resistivity test	Applicable for Aluminium wire & GS wire	<b>T, A</b>	IS 10810 Pt 42	
VII.	Uniformity of Zinc coating test	For G. S. wires/Strip only	<b>T, A</b>	IS 10810 Pt 40	
VIII.	Mass of Zinc coating test	For G. S. wires/Strip only	<b>T, A</b>	IS 10810 Pt 41	
IX.	Wrapping Test	Applicable for Aluminium wire & GS wire	<b>A</b>	IS 10810 Pt 3	
<b>3.0</b>	<b><u>Physical Tests for XLPE Insulation &amp; PVC sheath</u></b>				
I.	Test for thickness	Applicable for XLPE insulation, PVC inner sheath & PVC outer sheath	<b>T, A</b>	IS 10810 Pt 6	
II.	Tensile strength and elongation test at break	Applicable for XLPE insulation & PVC outer sheath			
(a)	Before ageing		<b>T, A</b>	IS 10810 Pt 7	
(b)	After ageing		<b>T, A</b>	IS 10810 Pt 7	
III.	Ageing in air oven	Applicable for XLPE insulation & PVC outer sheath	<b>T</b>	IS 10810 Pt 11	
IV.	Loss of mass in air oven test	For PVC outer sheath only	<b>T</b>	IS 10810 Pt 10	
V.	Hot deformation test	For PVC outer sheath only	<b>T</b>	IS 10810 Pt 15	
VI.	Heat shock test	For PVC outer sheath only	<b>T</b>	IS 10810 Pt 14	
VII.	Shrinkage test	For XLPE insulation & PVC outer sheath only	<b>T</b>	IS 10810 Pt 12	
VIII.	Thermal stability test	For PVC outer sheath only	<b>T</b>	IS 10810 Pt 60	
IX.	Cold Impact test	For PVC outer sheath only	<b>T</b>	IS 5831/1984	
X.	Bleeding and Blooming test	For PVC outer sheath only	<b>T</b>	IS 5831/1984	
XI.	Hot set test	For XLPE insulation only	<b>T, A</b>	IS 10810 Pt 30	
XII.	Water absorption (gravimetric) test	For XLPE insulation only	<b>T</b>	IS 10810 Pt 33	
<b>4.0</b>	<b><u>Improved Fire performance (FR-LSH) Tests</u></b>				

<u>S. No.</u>	<u>TEST</u>	<u>APPLICABLE FOR</u>	<u>TEST CONDUCTION REQUIRED AS</u>	<u>REFERENCE STANDARD</u>	<u>REMARKS</u>
I.	Oxygen index test	For PVC outer sheath only	T, A	IS 10810 Pt 58 / ASTMD 2863/ NES 715-I	<b><u>Applicable for Inner Sheath also, if the same is indicated in Datasheet-A</u></b>
II.	Smoke density test	For PVC outer sheath only	T, A	IS 10810 Pt 63 / ASTMD 2843	
III.	Acid gas generation test	For PVC outer sheath only	T, A	IS 10810 Pt 59 / IEC-754-1	
IV.	Temperature Index Test	For PVC outer sheath only	T, A	IS 10810 Pt 64 / ASTMD 2863	
<b>5.0</b>	<b><u>Flammability Tests</u></b>				
I.	Flammability test for bunched cables	For complete cable	T	IS 10810 Pt 62/ IEC-60332 (Part-3-23-Cat-B)	<b><u>Test &amp; Category applicable as indicated in Datasheet-A</u></b>
II.	Flammability test for single cable	For complete cable	T,A	IS: 10810 Pt 61 / IEC:60332 Part-1	
III.	Swedish chimney test	For complete cable	A	SEN SS 424 1475 (Class F3)	
IV.	Flammability test	For complete cable	A	IEEE: 60383	
<b>6.0</b>	<b><u>Electrical Tests</u></b>				
I.	High Voltage Test	For complete cable	T, A, R	IS 10810 Pt 45	
II.	Insulation Resistance Test (Volume resistivity method)	For complete cable	T, A	IS 10810 Pt 43	
<b>7.0</b>	<b><u>Anti-rodent and Termite Repulsion test</u></b>	For PVC outer sheath only	A	Refer Note	

Note: A few chipping of the PVC compound is slowly ignited on a porcelain dish or cubicle in a muffle furnace at about 60-degree C. The resulting ignited ash is boiled with a little ammonium acetate solution (10%). Place a drop of aqueous sodium sulphide solution on a thick filter paper and allow soaking. Touch the spot with a drop of above extract. A black spot indicates the presence of lead, the anti-termite and rodent compound.



1035432/2022/PS-PEM-EL

	1x660 MW SAGARDIGHI TPP PH-III, EXTN. UNIT#5	PE-PQ-445-507-E002
	PRE-QUALIFICATION REQUIREMENTS FOR LT XLPE POWER CABLES	REVISION NO. 1 DATE 6.9.2022
		SHEET NO. 1 OF 1





ITEMS: LT XLPE Power Cable

SCOPE: Supply : YES; Erection &amp; Commissioning : NO

1	Bidder should be a manufacturer of LT Power cables
2	Availability of test reports of tests on LT XLPE FRLS power cables to establish in-house capability to carry out all routine, type & acceptance tests as per relevant IS/ International Standards (except UV radiation & hydrolytic stability test which can be conducted at Govt. Lab/ Govt. approved Independent lab)
3	Capacity of manufacturing 100 km of LT power cables per month
4	Manufactured and supplied at least one (1) km of FRLS cables as on 01.07.2020
5a	Manufactured and supplied LT power cable sizes of minimum 240 sq. mm for 3/3.5 core
5b	Manufactured and supplied 1.1kV or higher grade power cable of minimum 630sq.mm. conductor size as on 01.07.2020
6a	Manufactured and supplied at least 100 km of aluminium conductor, XLPE insulated, PVC sheathed power cables of 1.1 kV or higher grade in one single contract as on 01.07.2020
6b	Manufactured and supplied at least 100 km of aluminium conductor, PVC insulated, PVC sheathed power cables of 1.1 kV or higher grade in one single contract as on 01.07.2020
7	Minimum two (2) nos. purchase orders for LT XLPE Power cables shall be submitted which should not be more than five (5) years old from the date of techno- commercial bid opening

**Notes (General points):**

1. Consideration of offer shall be subject to customer's approval of bidders, if applicable.
2. Bidder to submit all supporting documents in English. If documents submitted by bidder are in language other than English, a self-attested English translated document should also be submitted.
3. Notwithstanding anything stated above, BHEL reserves the right to assess the capabilities and capacity of the bidder to perform the contract, should the circumstances warrant such assessment in the overall interest of BHEL.
4. After satisfactory fulfillment of all the above criteria/ requirement, offer shall be considered for further evaluation as per NIT and all the other terms of the tender.
5. PQR 4, 5b, 6a and 6b are in line with end customer provenness criteria.

PREPARED BY  NAME: NITISH MANU DESIGNATION: DY. MGR.	CHECKED BY  NAME: KANHAIYA KUMAR DESIGNATION: SR. MGR.	REVIEWED BY  NAME: OMKAR KUMAR DESIGNATION: DGM	APPROVED BY  NAME: DEBASISA RATH DESIGNATION: DH(ELECT)
--	--	--	---

**ANNEXURE I**  
**1 X 660 MW WBPDCS SAGARDIGHI EXTN UNIT V**

**GeM BID NO. -....., Dt:- --**

**Letter head of Company**

Ref.....

Date.....

To,  
Bharat Heavy Electricals Limited  
PEM, PPEI Building, Plot No 25,  
Sector -16A, Noida (U.P)-201301

**Subject: - Certification regarding local content**

Dear Sir,

We hereby certify that items offered by us of Chemical Dosing System for **1 X 660 MW WBPDCS SAGARDIGHI EXTN UNIT V** meets the requirement of minimum local content in line with clause no. -- of NIT and the Public Procurement (Preference to Make in India), Order 2017 dated-15.06.2017, 28.05.2018, 29.05.2019, 04.06.2020 & 16.09.2020. The Percentage (%) of Local content is .....%.

We further confirm that details of location at which the local value addition is made will be our registered works at .....(address of the works)

Yours very truly

..... (authorized signatory of company)

..... (firm name)

authorized signatory  
of company

## **1 X 660 MW WBPDCS SAGARDIGHI EXTN UNIT V**

**GeM BID NO. -....., Dt:-**

### **ANNEXURE -II (INSTRUCTIONS TO PACKING LIST)**

For faster verification of bills, successful bidder to submit detailed Bill of Material (BOM) at the time of drawings/ documents submission after placement of PO. Each item of the BOM to be uniquely identified with item code no. or item Sl. No. Supplier to ensure that all items which will find separate mention in the packing list are covered in this detailed BOM.

Supplier to also give the following undertaking in the BOM:

“The BOM provided herewith completes the scope (in content and intent) of material supply under PO No. .... Dated ..... Any additional material which may become necessary for the intended application of the supplied items/package will be supplied free of cost in most reasonable time.

Packing List must indicate:

- a) Packing size
- b) Gross weight and net weight of each package
- c) Contents of the package with cross reference to BOM item code no. / Sl. No.
- d) Quantity of each items separately.

The packing list must cover all the BOM items.

Supplier to give following undertaking in the packing list:

The Packing list provided herewith is as per BOM approved under PO No. ----

**ANNEXURE III**  
**1 X 660 MW WBPDC SAGARDIGHI EXTN UNIT V**

**GeM BID NO. -....., Dt:-**

**Letter head of Company**

Ref.....

Date.....

To,  
Bharat Heavy Electricals Limited  
PEM, PPEI Building, Plot No 25,  
Sector -16A, Noida (U.P)-201301

**Subject: - Certification regarding Land Border**

Dear Sir,

I have read the clause regarding restrictions of procurement from a bidder of a country which shares a land border with India. I hereby certify that M/s ..... (Organization name) is not from such a country and is eligible to be considered.

**Note :- Bidder is requested to furnish the above undertaking on company letterhead from the highest competent authority at your end (i.e Owner, partner, CMD, Director, company secretariat etc.).**

Yours very truly

..... (authorized signatory of company)

..... (firm name)

authorized signatory  
of company

**INTEGRITY PACT****Between**

Bharat Heavy Electricals Ltd. (BHEL), a company registered under the Companies Act 1956 and having its registered office at "BHEL House", Siri Fort, New Delhi - 110049 (India) hereinafter referred to as "The Principal", which expression unless repugnant to the context or meaning hereof shall include its successors or assigns of the ONE PART

**and**

\_\_\_\_\_, (description of the party along with address), hereinafter referred to as "The Bidder/ Contractor" which expression unless repugnant to the context or meaning hereof shall include its successors or assigns of the OTHER PART

**Preamble**

The Principal intends to award, under laid-down organizational procedures, contract/s for \_\_\_\_\_

\_\_\_\_\_ (hereinafter referred to as "Contract"). The Principal values full compliance with all relevant laws of the land, rules and regulations, and the principles of economic use of resources, and of fairness and transparency in its relations with its Bidder(s)/ Contractor(s).

In order to achieve these goals, the Principal will appoint panel of Independent External Monitor(s) (IEMs), who will monitor the tender process and the execution of the contract for compliance with the principles mentioned above.

**Section 1- Commitments of the Principal**

- 1.1 The Principal commits itself to take all measures necessary to prevent corruption and to observe the following principles: -
  - 1.1.1 No employee of the Principal, personally or through family members, will in connection with the tender for, or the execution of a contract, demand, take a promise for or accept, for self or third person, any material or immaterial benefit which the person is not legally entitled to.
  - 1.1.2 The Principal will, during the tender process treat all Bidder(s) with equity and reason. The Principal will in particular, before and during the tender process, provide to all Bidder(s) the same information and will not provide to any Bidder(s) confidential/ additional information through which the Bidder(s) could obtain an advantage in relation to the tender process or the contract execution.
  - 1.1.3 The Principal will exclude from the process all known prejudiced persons.
- 1.2 If the Principal obtains information on the conduct of any of its employees which is a penal offence under the Indian Penal Code 1860 and Prevention of Corruption Act 1988 or any other statutory penal enactment, or if there be a substantive suspicion in this regard, the Principal will inform its Vigilance Office and in addition can initiate disciplinary actions.

**Section 2 - Commitments of the Bidder(s)/ Contractor(s)**

- 2.1 The Bidder(s)/ Contractor(s) commit himself to take all measures necessary to prevent corruption. The Bidder(s)/ Contractor(s) commits himself to observe the following principles during participation in the tender process and during the contract execution.

- 2.1.1 The Bidder(s)/ Contractor(s) will not, directly or through any other person or firm, offer, promise or give to the Principal or to any of the Principal's employees involved in the tender process or the execution of the contract or to any third person any material, immaterial or any other benefit which he/ she is not legally entitled to, in order to obtain in exchange any advantage of any kind whatsoever during the tender process or during the execution of the contract.
- 2.1.2 The Bidder(s)/ Contractor(s) will not enter with other Bidder(s) into any illegal or undisclosed agreement or understanding, whether formal or informal. This applies in particular to prices, specifications, certifications, subsidiary contracts, submission or non-submission of bids or any other actions to restrict competitiveness or to introduce cartelization in the bidding process.
- 2.1.3 The Bidder(s)/ Contractor(s) will not commit any penal offence under the relevant Indian Penal Code (IPC) and Prevention of Corruption Act; further the Bidder(s)/ Contractor(s) will not use improperly, for purposes of competition or personal gain, or pass on to others, any information or document provided by the Principal as part of the business relationship, regarding plans, technical proposals and business details, including information contained or transmitted electronically.
- 2.1.4 Foreign Bidder(s)/ Contractor(s) shall disclose the name and address of agents and representatives in India and Indian Bidder(s)/ Contractor(s) to disclose their foreign principals or associates. The Bidder(s)/ Contractor(s) will, when presenting his bid, disclose any and all payments he has made, and is committed to or intends to make to agents, brokers or any other intermediaries in connection with the award of the contract.
- 2.2 The Bidder(s)/ Contractor(s) will not instigate third persons to commit offences outlined above or be an accessory to such offences.
- 2.3 The Bidder(s)/ Contractor(s) shall not approach the Courts while representing the matters to IEMs and shall await their decision in the matter.

### **Section 3 - Disqualification from tender process and exclusion from future contracts**

If the Bidder(s)/ Contractor(s), before award or during execution has committed a transgression through a violation of Section 2 above, or acts in any other manner such as to put his reliability or credibility in question, the Principal is entitled to disqualify the Bidder(s)/ Contractor(s) from the tender process, terminate the contract, if already awarded, exclude from future business dealings and/ or take action as per the separate "Guidelines on Banning of Business dealings with Suppliers/ Contractors", framed by the Principal.

### **Section 4 - Compensation for Damages**

- 4.1 If the Principal has disqualified the Bidder (s) from the tender process before award / order acceptance according to Section 3, the Principal is entitled to demand and recover the damages equivalent to Earnest Money Deposit/ Bid Security.
- 4.2 If the Principal is entitled to terminate the Contract according to Section 3, or terminates the Contract in application of Section 3 above, the Bidder(s)/ Contractor (s) transgression through a violation of Section 2 above shall be construed breach of contract and the Principal shall be entitled to demand and recover from the Contractor an amount equal to 5% of the contract value or the amount equivalent to Security Deposit/ Performance Bank Guarantee, whichever is higher, as damages, in addition to and without prejudice to its right to demand and recover compensation for any other loss or damages specified elsewhere in the contract.

**Section 5 - Previous Transgression**

- 5.1 The Bidder declares that no previous transgressions occurred in the last 3 (three) years with any other company in any country conforming to the anti-corruption approach or with any other Public Sector Enterprise in India that could justify his exclusion from the tender process.
- 5.2 If the Bidder makes incorrect statement on this subject, he can be disqualified from the tender process or the contract, if already awarded, can be terminated for such reason or action can be taken as per the separate "Guidelines on Banning of Business dealings with Suppliers/ Contractors", framed by the Principal.

**Section 6 - Equal treatment of all Bidder (s)/ Contractor (s) / Sub-contractor (s)**

- 6.1 The Principal will enter into Integrity Pacts with identical conditions as this Integrity Pact with all Bidders and Contractors.
- 6.2 In case of Sub-contracting, the Principal Contractor shall take the responsibility of the adoption of Integrity Pact by the Sub-contractor(s) and ensure that all Sub-contractors also sign the Integrity Pact.
- 6.3 The Principal will disqualify from the tender process all Bidders who do not sign this Integrity Pact or violate its provisions.

**Section 7 - Criminal Charges against violating Bidders/ Contractors /Subcontractors**

If the Principal obtains knowledge of conduct of a Bidder, Contractor or Subcontractor, or of an employee or a representative or an associate of a Bidder, Contractor or Subcontractor which constitutes corruption, or if the Principal has substantive suspicion in this regard, the Principal will inform the Vigilance Office.

**Section 8 -Independent External Monitor(s)**

- 8.1 The Principal appoints competent and credible panel of Independent External Monitor (s) (IEMs) for this Integrity Pact. The task of the IEMs is to review independently and objectively, whether and to what extent the parties comply with the obligations under this Integrity Pact.
- 8.2 The IEMs are not subject to instructions by the representatives of the parties and performs his functions neutrally and independently. He reports to the CMD, BHEL.
- 8.3 The IEMs shall be provided access to all documents/ records pertaining to the Contract, for which a complaint or issue is raised before them as and when warranted. However, the documents/records/information having National Security implications and those documents which have been classified as Secret/Top Secret are not to be disclosed.
- 8.4 The Principal will provide to the IEMs sufficient information about all meetings among the parties related to the Contract provided such meetings could have an impact on the contractual relations between the Principal and the Contractor. The parties offer to the IEMs the option to participate in such meetings.

- 8.5 The advisory role of IEMs is envisaged as that of a friend, philosopher and guide. The advice of IEMs would not be legally binding and it is restricted to resolving issues raised by a Bidder regarding any aspect of the tender which allegedly restricts competition or bias towards some Bidders. At the same time, it must be understood that IEMs are not consultants to the Management. Their role is independent in nature and the advice once tendered would not be subject to review at the request of the organization.
- 8.6 For ensuring the desired transparency and objectivity in dealing with the complaints arising out of any tendering process or during execution of Contract, the matter should be examined by the full panel of IEMs jointly, who would look into the records, conduct an investigation, and submit their joint recommendations to the Management.
- 8.7 The IEMs would examine all complaints received by them and give their recommendations/ views to the CMD, BHEL at the earliest. They may also send their report directly to the CVO, in case of suspicion of serious irregularities requiring legal/ administrative action. Only in case of very serious issue having a specific, verifiable Vigilance angle, the matter should be reported directly to the Commission. IEMs will tender their advice on the complaints within 30 days.
- 8.8 The CMD, BHEL shall decide the compensation to be paid to the IEMs and its terms and conditions.
- 8.9 IEMs should examine the process integrity, they are not expected to concern themselves with fixing of responsibility of officers. Complaints alleging mala fide on the part of any officer of the Principal should be looked into by the CVO of the Principal.
- 8.10 If the IEMs have reported to the CMD, BHEL, a substantiated suspicion of an offence under relevant Indian Penal Code / Prevention of Corruption Act, and the CMD, BHEL has not, within reasonable time, taken visible action to proceed against such offence or reported it to the Vigilance Office, the IEMs may also transmit this information directly to the Central Vigilance Commissioner, Government of India.
- 8.11 After award of work, the IEMs shall look into any issue relating to execution of Contract, if specifically raised before them. As an illustrative example, if a Contractor who has been awarded the Contract, during the execution of Contract, raises issue of delayed payment etc. before the IEMs, the same shall be examined by the panel of IEMs. Issues like warranty/ guarantee etc. shall be outside the purview of IEMs.
- 8.12 However, the IEMs may suggest systemic improvements to the management of the Principal, if considered necessary, to bring about transparency, equity and fairness in the system of procurement.
- 8.13 The word 'Monitor' would include both singular and plural.

## **Section 9 - Pact Duration**

- 9.1 This Integrity Pact shall be operative from the date this Integrity Pact is signed by both the parties till the final completion of contract for successful Bidder, and for all other Bidders 6 months after the Contract has been awarded. Any violation of the same would entail disqualification of the bidders and exclusion from future business dealings.
- 9.2 If any claim is made/ lodged during currency of this Integrity Pact, the same shall be binding and continue to be valid despite the lapse of this Pact as specified above, unless it is discharged/ determined by the CMD, BHEL.

**Section 10 - Other Provisions**


- 10.1 This Integrity Pact is subject to Indian Laws and exclusive jurisdiction shall be of the competent Courts as indicated in the Tender or Contract, as the case may be.
- 10.2 Changes and supplements as well as termination notices need to be made in writing.
- 10.3 If the Bidder(s)/ Contractor(s) is a partnership or a consortium or a joint venture, this Integrity Pact shall be signed by all partners of the partnership or joint venture or all consortium members.
- 10.4 Should one or several provisions of this Integrity Pact turn out to be invalid, the remainder of this Integrity Pact remains valid. In this case, the parties will strive to come to an agreement to their original intentions.
- 10.5 Only those bidders / contractors who have entered into this Integrity Pact with the Principal would be competent to participate in the bidding. In other words, entering into this Integrity Pact would be a preliminary qualification.
- 10.6 In the event of any dispute between the Principal and Bidder(s)/ Contractor(s) relating to the Contract, in case, both the parties are agreeable, they may try to settle dispute through Mediation before the panel of IEMs in a time bound manner. In case, the dispute remains unresolved even after mediation by the panel of IEMs, either party may take further action as the terms & conditions of the Contract. The fees/expenses on dispute resolution through mediation shall be shared by both the parties. Further, the mediation proceedings shall be confidential in nature and the parties shall keep confidential all matters relating to the mediation proceedings including any settlement agreement arrived at between the parties as outcome of mediation. Any views expressed, suggestions, admissions or proposals etc. made by either party in the course of mediation shall not be relied upon or introduced as evidence in any further arbitral or judicial proceedings, whether or not such proceedings relate to the dispute that is the subject of mediation proceedings. Neither of the parties shall present IEMs as witness in any Alternative Dispute Resolution or judicial proceedings in respect of the dispute that was subject of mediation.

For & On behalf of the Principal  
(Office Seal)  
**Ashutosh Sharma**  
Place \_\_\_\_\_  
Date \_\_\_\_\_

Digitally signed by Ashutosh Sharma  
Principal, BHARAT HEAVY ELECTRICALS LIMITED, ou=BHEL PS PEM, postalCode=201301, st=Uttar Pradesh, 2.5.4.20=4edbc62da83d0774cfb01da6ac79e7722130a9f8e68309a4c30b11ce5b1ed, serialNumber=b30240406e83ce42d5103de3e9313352dbc73bc5041eff90ce0d94aa87e1b9a2, cn=Ashutosh Sharma  
Date: 2022.07.07 17:03:04 +05'30'

For & On behalf of the Bidder/ Contractor  
(Office Seal)

Witness: \_\_\_\_\_

  
अर्जुन श्रीवास्तव / Arjun Srivastava  
एच प्रोजेक्ट (पी.जी.-II) / Dy. Manager (P.G-II)  
भारत हेवी इलेक्ट्रिकल्स लिमिटेड / Bharat Heavy Electricals Ltd.  
पावर सेक्टर-परियोजना अभियंत्रिकी प्रबंधन  
Power Sector-Project Engineering Management  
पीपीईआई भवन, एच.आर.डी.आई. एंड ईएसआई कॉम्प्लेक्स  
PPEI Bldg. H.R.D.I. & ESI Complex,  
प्लॉट नं. 25, सेक्टर 16 ए, नोएडा - 201301  
Plot No. 25, Sec. 16 A, Noida - 201301

Witness: \_\_\_\_\_

(Name & Address) \_\_\_\_\_

## **ANNEXURE R :- RISK & COST PURCHASE**

### **DEFAULT/ BREACH OF CONTRACT, INSOLVENCY AND RISK PURCHASE**

In case of delays (beyond the maximum late delivery period as per LD clause) in supplies, or if there be defective supplies or non-fulfilment of any other terms and conditions of the Contract as enumerated subsequently in this clause, then, without prejudice to its right to recover any expenses, losses or damages to which the Buyer may be put to incur or sustain by reason of the Seller/Contractor's default or breach of Order/Contract or to suspend business dealings with the Seller/Contractor in terms of the Buyers' Guidelines for Suspension of Business Dealings as applicable from time to time, the Buyer shall also be entitled to cancel the Order/ Contract either in whole or portion thereof without compensation to Seller. On the occurrence of any of the acts/omissions mentioned below, the Buyer may if it so desires, procure upon such terms and in such manner as deemed appropriate, plant/ equipment/ stores not so delivered or others of similar description where plant/ equipment/ stores exactly complying with particulars are not, in the opinion of the Buyer (which shall be final), readily procurable, at the risk and cost of the Seller.

The Seller shall be liable to the Buyer for any excess costs incurred thereof and the Seller shall continue the performance of the Order/Contract to the extent not cancelled under the provisions of this clause. The Seller shall on no account be entitled to any gain on such repurchases. If the Bidder does not agree to this Risk Purchase clause, BHEL reserves the right to reject the bid/offer of the Bidder.

The order/contract may be cancelled in whole or part thereof and Risk & Cost Clause in line with terms and conditions of PO/Contract may be invoked by the Buyer in any of the following cases:

- i. If the Seller/Contractor fails to deliver the goods or materials or any installment thereof within the period(s) fixed for such delivery or the Seller's poor progress of the supply/services vis-à-vis delivery/execution timeline as stipulated in the contract, backlog attributable to the Seller including unexecuted portion of supply does not appear to be executable within balance period available;
- ii. delivers goods or materials not of the contracted quality and failing to adhere to the contract specifications/execution methodology;
- iii. withdrawal from or repudiation/abandonment of the supply/services by the Seller before completion as per contract or if the Seller refuses or is unable to supply goods or materials covered by the order/Contract either in whole or in part or otherwise fails to perform the Order/Contract.

- iv. Non supply by the Seller within scheduled completion/delivery period as per contract or as extended from time to time for reasons attributable to the Seller;
- v. Termination of Contract on account of any other reason(s) attributable to the Seller.
- vi. Assignment, transfer, sub-letting of Contract without BHEL's written permission resulting in termination of Contract or part thereof by BHEL.
- vii. If the Seller be an individual or a Sole Proprietorship, in the event of death or insanity of the Seller.
- viii. If the Seller/Contractor being an individual or if a partnership firm thereof, shall at any time be adjudged insolvent or shall have a receiving order for administration of his estate made against him or shall take any proceeding for composition under any Insolvency Act for the time being in force or make any assignment of the order/Contract or enter into any arrangement or composition with his creditors or suspend payment or if the firm dissolved under the Partnership Act;
- ix. If the Seller/Contractor being a Company is wound up voluntarily or by order of a Court or a Receiver, Liquidator or Manager on behalf of the debenture holders and creditors is appointed or circumstances have arisen which entitles the Court of debenture holder and creditors to appoint a receiver, liquidator or manager
- x. Non- Compliance to any contractual condition or any other default attributable to the Seller.

Such defaulting vendor/Seller shall not be eligible to participate in re-tendering conducted on account of risk purchase made due to fault of such vendor/Seller.

BHEL's right to go for Risk and Cost, Calculation of Risk and Cost amount & LD, recovery options to BHEL are given in detail in Annexure-V hereto.

## **ANNEXURE-V**

### **(RISK AND COST CLAUSE)**

1. BHEL reserves the right to terminate the contract or withdraw portion of work and get it done through other agency, at the risk and cost of the contractor *after due notice of a period of 14 days' by BHEL* in any of the following cases:
- i) If the Seller/Contractor fails to deliver the goods or materials or any instalment thereof within the period(s) fixed for such delivery or the Seller's poor progress of the supply/ services vis-a-vis delivery/execution timeline as stipulated in the Contract, backlog attributable to seller including unexecuted portion of supply does not appear to be executable within balance available period;
  - ii) Delivers goods or materials not of the contracted quality and failing to adhere to the contract specifications;
  - iii) Withdrawal from or repudiation/ abandonment of the supply/ services by Seller before completion as per contract or if the Seller refuses or is unable to supply goods or materials covered by the Order/Contract either in whole or in part or otherwise fails to perform the Order/Contract;
  - iv) Non-supply by the Seller within scheduled completion/delivery period as per Contract or as extended from time to time, for the reasons attributable to the Seller;
  - v) Termination of Contract on account of any other reason (s) attributable to Seller.
  - vi) Assignment, transfer, subletting of Contract without BHEL's written permission resulting in termination of Contract or part thereof by BHEL.
  - vii) If the Seller be an individual or a sole proprietorship Firm, in the event of the death or insanity of the Seller;
  - viii) If the Seller/Contractor being an individual or if a firm on a partnership thereof, shall at any time, be adjudged insolvent or shall have a receiving order for administration of his estate made against him or shall take any proceeding for composition under any Insolvency Act for the time being in force or make any assignment of the Order/Contract or enter into any arrangement or composition with his creditors or suspend payment or if the firm dissolved under the Partnership Act;
  - ix) If the Seller/Contractor being a company is wound up voluntarily or by order of a Court or a Receiver, Liquidator or Manager on behalf of the debenture holders and creditors is appointed or circumstances shall have arisen which entitles the Court of debenture holder and creditors to appoint a receiver, liquidator or manager;
  - x) Non-compliance to any contractual condition or any other default attributable to Seller.

#### **1.1 Risk & Cost Amount against Balance Work:**

Risk & Cost amount against balance work shall be calculated as follows:

$$\text{Risk \& Cost Amount} = [(A-B) + (A \times H/100)]$$

Where,

A= Value of Balance scope of Work (\*) as per rates of new contract

B= Value of Balance scope of Work (\*) as per rates of old contract being paid to the contractor at the time of termination of contract i.e. inclusive of PVC & ORC, if any.

H = Overhead Factor to be taken as 5

In case (A-B) is less than 0 (zero), value of (A-B) shall be taken as 0 (zero).

#### **1.2 \* Balance scope of work (in case of termination of contract):**

Difference of Contract Quantities and Executed Quantities as on the date of issue of Letter for 'Termination of Contract', shall be taken as balance scope of Work for calculating risk & cost amount.

Contract quantities are the quantities as per original contract. If, Contract has been amended, quantities as per amended Contract shall be considered as Contract Quantities.

Items for which total quantities to be executed have exceeded the Contract Quantities based on drawings issued to contractor from time to time till issue of Termination letter, then for these items total Quantities as per issued drawings would be deemed to be contract quantities.

Substitute/ extra items whose rates have already been approved would form part of contract quantities for this purpose.

Substitute/ extra items which have been executed but rates have not been approved, would also form part of contract quantities for this purpose and rates of such items shall be determined in line with contractual provisions.

However, increase in quantities on account of additional scope in new tender shall not be considered for this purpose.

NOTE: In case portion of work is being withdrawn at risk & cost of contractor instead of termination of contract, contract quantities pertaining to portion of work withdrawn shall be considered as 'Balance scope of work' for calculating Risk & Cost amount.

### **1.3 LD against delay in executed work in case of Termination of Contract:**

LD against delay in executed work shall be calculated in line with LD clause no. 16 of GCC, for the delay attributable to contractor. For limiting the maximum value of LD, contract value shall be taken as Executed Value of work till termination of contract.

Method for calculation of LD against delay in executed work in case of termination of contract" is given below.

- i. Let the time period from scheduled date of start of work till termination of contract excluding the period of Hold (if any) not attributable to contractor = T1
- ii. Let the value of executed work till the time of termination of contract = X
- iii. Let the Total Executable Value of work for which inputs/fronts were made available to contractor and were planned for execution till termination of contract = Y
- iv. Delay in executed work attributable to contractor i.e.  $T2 = [1 - (X/Y)] \times T1$
- v. LD shall be calculated in line with LD clause (clause 16) of the Contract for the delay attributable to contractor taking "X" as Contract Value and "T2" as period of delay attributable to contractor.

### **2. Recoveries arising out of Risk & Cost and LD or any other recoveries due from Contractor**

Without prejudice to the other means of recovery of such dues from the Seller recoveries from the Seller on whom risk & cost has been invoked shall be made from the following:

- a) Dues available in the form of Bills payable to seller, SD, BGs against the same contract.
- b) Dues payable to seller against other contracts in the same Region/Unit/ Division of BHEL.
- c) Dues payable to seller against other contracts in the different Region/Unit/ division of BHEL.

*In-case recoveries are not possible with any of the above available options, Legal action shall be initiated for recovery against contractor.*

|

## Formula for LT XLPE POWER CABLE

IEEMA table for Price variation cause for various type of cable

## 1. Aluminium conductor cable

S.N o	Cable Type	AIF (Single core unarmoured & Multi core armoured)	AIF (Single core armoured)	CCFAI	XLFAL (Single core)	XLFAL (Multi core)	FeF	FeW	IEEMA Formula
1.	HT XLPE Power cable	ALP	H1	H2	XL3	XL4	H3	H5	$P = P_o + AIF(AL - Alo) + XLFAL(CC - CCo) + CCFAI(PVCC - PVCCo) + FeF(Fe - Feo)$
2.	LT XLPE Power Cable	ALP	P1	L2	XL1	XL1	P3	P3 (Additional)	$P = P_o + AIF(AL - Alo) + XLFAL(CC - CCo) + CCFAI(PVCC - PVCCo) + FeF(Fe - Feo)$
3.	LT XLPE Power Cable	ALP	P1	L2	XL1	XL1	P3	P3 (Additional)	$P = P_o + AIF(AL - Alo) + CCFAI(PVCC - PVCCo) + FeF(Fe - Feo)$
4.	LT HRPVC Power Cable	ALP	P1	P2	-	-	P3	P3 (Additional)	$P = P_o + AIF(AL - Alo) + CCFAI(PVCC - PVCCo) + FeF(Fe - Feo)$

## 2. Copper conductor cable

S no.	Cable type	CuF	AIF (single core armoured)	CCFCu	XLFCU (Single core)	XLFCU (Multi core)	FeF	FeW	IEEMA Formula
1	HT XLPE Power cable	CUP	H4	H2	XL3	XL4	H3	H5	$P = P_o + CuF(Cu - Cuo) + XLFCU(CC - CCo) + CCFCu(PVCC - PVCCo) + FeF(Fe - Feo) + AIF(AL - Alo)$
2	LT XLPE Power Cable	CUP	P4	L2	XL1	XL1	P3	P3 (Additional)	$P = P_o + CuF(Cu - Cuo) + XLFCU(CC - CCo) + CCFCu(PVCC - PVCCo) + FeF(Fe - Feo) + AIF(AL - Alo)$

S. NO	Size	ALF	CUF	CCFAI/CCFCu	XLFAI/XLFCU	FeW/AIF
1	1CX16 SQMM CU ARMOURED	-	0.151	0	0.023	0.084
2	1CX35 SQMM CU ARMOURED	-	0.332	0	0.035	0.108
3	1C X 400 SQMM AL ARMOURED	1.5502	-	0	0.214	0.000
4	1C X 630 SQMM AL ARMOURED	2.365	-	0	0.318	0.000
5	2C X 2.5 SQMM CU ARMOURED	-	0.046	0.175	0.014	0.273
6	2C X 6 SQMM CU ARMOURED	-	0.112	0.234	0.022	0.348
7	2CX16 SQMM AL ARMOURED	0.091	-	0.341	0.034	0.439
8	2C X 25 SQMM AL ARMOURED	0.146	-	0.278	0.048	0.526
9	2C X 50 SQMM AL ARMOURED	0.273	-	0.685	0.075	0.661
10	2C X 95 SQMM AL ARMOURED	0.548	-	0.389	0.110	1.085
11	2C X 120 SQMM AL ARMOURED	0.691	-	0.421	0.138	1.147
12	3C X 2.5 SQMM CU ARMOURED	-	0.069	0.177	0.021	0.289
13	3C X 16 SQMM AL ARMOURED	0.137	-	0.246	0.049	0.523
14	3C X 25 SQMM AL ARMOURED	0.219	-	0.247	0.070	0.625
15	3C X 50 SQMM AL ARMOURED	0.41	-	0.311	0.108	0.790
16	3C X 95 SQMM AL ARMOURED	0.821	-	0.441	0.160	1.286
17	3C X 150 SQMM AL ARMOURED	1.279	-	0.611	0.259	1.526
18	3C X 240 SQMM AL ARMOURED	2.099	-	0.842	0.388	2.397
19	3C X 300 SQMM AL ARMOURED	2.635	-	1.012	0.467	2.642
20	3.5C X 25 SQMM AL ARMOURED	0.262	-	0.264	0.084	0.664
21	3.5C X 50 SQMM AL ARMOURED	0.478	-	0.335	0.130	0.864
22	3.5C X 95 SQMM AL ARMOURED	0.949	-	0.471	0.190	1.376
23	3.5C X 185 SQMM AL ARMOURED	1.861	-	0.756	0.369	2.315
24	3.5C X 300 SQMM AL ARMOURED	3.033	-	1.031	0.540	3.670
25	4C X 16 SQMM AL ARMOURED	0.183	-	0.279	0.065	0.573

**Price Variation Formulae for cables -Annexure-I**

1. Prices shall be variable as per price variation formulae given below (basis IEEMA).  
The price variation shall be limited to + 20% of total ex-works price actually supplied (cable size wise) and -ve price variation shall be unlimited. Rates for working out price variation shall be as per rates published by IEEMA for the factors given in Annexure-II

**2. Base date for prices:**

**Initial Price (As per IEEMA) for- Alo, Cuo, CCo, PVCCo & Feo:**

Base Date shall be- 1<sup>st</sup> working day of the previous month to the date of issue of tender enquiry.

**Final Price (as per IEEMA) for- Al, Cu, Cc, PVCC & Fe:**

1<sup>st</sup> working day of month, one month prior to the date on which cable is notified as being ready for inspection i.e TPIA inspection call raise date on web portal.

3. Variation factor value for ALF, CuF, CCFAL, CCFCu, XLFAL, XLFCu, FeF & FeW as applicable shall be as per Technical Specification.

4. PVC shall be payable within contractual delivery period (including any extension thereto).

**IEEMA table for Price variation cause for various type of cable**

**1. Aluminium conductor cable**

S.No	Cable Type	AIF (Single core unarmoured & Multi core armoured)	AIF (Single core armoured)	CCFAI	XLFAL (Single core)	XLFAL (Multi core)	FeF	FeW	IEEMA Formula
1.	HT XLPE Power cable	ALP	H1	H2	XL3	XL4	H3	H5	$P = P_o + AIF(AL-Alo) + XLFAL(CC-CCo) + CCFAI(PVCC-PVCCo) + FeF(Fe-Feo)$
2.	LT XLPE Power Cable	ALP	P1	L2	XL1	XL1	P3	P3 (Additional)	$P = P_o + AIF(AL-Alo) + XLFAL(CC-CCo) + CCFAI(PVCC-PVCCo) + FeF(Fe-Feo)$
3.	LT PVC Power Cable	ALP	P1	P2	-	-	P3	P3 (Additional)	$P = P_o + AIF(AL-Alo) + CCFAI(PVCC-PVCCo) + FeF(Fe-Feo)$
4.	LT HRPVC Power Cable	ALP	P1	P2	-	-	P3	P3 (Additional)	$P = P_o + AIF(AL-Alo) + CCFAI(PVCC-PVCCo) + FeF(Fe-Feo)$

**2. Copper conductor cable**

S no.	Cable type	CuF	AIF (single core armoured)	CCFCu	XLFCU (Single core)	XLFCU (Multi core)	FeF	FeW	IEEMA Formula
1	HT XLPE Power cable	CUP	H4	H2	XL3	XL4	H3	H5	$P = P_o + CuF(Cu-Cuo) + XLFCU(CC-CCo) + CCFCu(PVCC-PVCCo) + FeF(Fe-Feo) + AIF(AL-Alo)$
2	LT XLPE Power Cable	CUP	P4	L2	XL1	XL1	P3	P3 (Additional)	$P = P_o + CuF(Cu-Cuo) + XLFCU(CC-CCo) + CCFCu(PVCC-PVCCo) + FeF(Fe-Feo) + AIF(AL-Alo)$

S no.	Cable type	CuF	AIF (single core armoured)	CCFCu	XLFCU (Single core)	XLFCU (Multi core)	FeF	FeW	IEEMA Formula
3	LT PVC Power Cable	CUP	P4	P2	--	--	P3	P3 (Addit ional)	$P=Po+CuF(Cu-Cuo) + CCFCu (PVCC-PVCCo) + FeF(Fe-Feo) + AIF(AL-Alo)$
4	LT HRPVC Power Cable	CUP	P4	P2	--	--	P3	P3 (Addit ional)	$P=Po+CuF(Cu-Cuo) + CCFCu (PVCC-PVCCo) + FeF(Fe-Feo) + AIF(AL-Alo)$
5	LT XLPE Control Cable	CUC	--	P5	--	XL2	P6	P6 (Addit ional)	$P=Po+CuF(Cu-Cuo) + XLFCU(CC-CCo) + CCFCu (PVCC-PVCCo) + FeF(Fe-Feo)$
6	LT PVC Control Cable	CUC	--	P5	--	--	P6	P6 (Addit ional)	$P=Po+CuF(Cu-Cuo) + CCFCu (PVCC-PVCCo) + FeF(Fe-Feo)$
7	LT HRPVC Control Cable	CUC	--	P5	--	--	P6	P6 (Addit ional)	$P=Po+CuF(Cu-Cuo) + CCFCu(PVCC-PVCCo) + FeF(Fe-Feo)$
8	LT XLPE Fire Survival Power Cable	CUP	P4	L2	XL1	XL1	P3	P3 (Addit ional)	$P=Po+CuF(Cu-Cuo) + XLFCU(CC-CCo) + CCFCu (PVCC-PVCCo) + FeF(Fe-Feo) + AIF(AL-Alo)$
9	LT XLPE Fire Survival Control	CUC	--	P5	--	XL2	P6	P6 (Addit ional)	$P=Po+CuF(Cu-Cuo) + XLFCU(CC-CCo) + CCFCu (PVCC-PVCCo) + FeF(Fe-Feo)$
10	LT EPR Fire Survival Power Cable	CUP	P4	L2	--	--	P3	P3 (Addit ional)	$P=Po+CuF(Cu-Cuo) + CCFCu (PVCC-PVCCo) + FeF(Fe-Feo) + AIF(AL-Alo)$
11	LT EPR Fire Survival Control cable	CUC	--	P5	--	--	P6	P6 (Addit ional)	$P=Po+CuF(Cu-Cuo) + CCFCu (PVCC-PVCCo) + FeF(Fe-Feo)$
12	Screened control Cable (Overall screen)	Cu POS	--	--	--	--	Fe POS	Fe POS	$P=Po+CuF(Cu-Cuo) + FeF(Fe-Feo)$
13	Screened control Cable (Individual	Cu PIS	--	--	--	--	Fe PIS	Fe PIS	$P=Po+CuF(Cu-Cuo) + FeF(Fe-Feo)$

**IEEMA Table for Price Variation Clause for various types of Cables****Notes:-**

- (i) Cu POS, Cu PIS, Fe POS & Fe PIS tables shall be as per IEEMA circular No. IEEMA (PVC) /Instrumentation Cable/2014 effective from dtd 01.07.2014.
- (ii) All other tables shall be as per IEEMA circular No. 35//DIV/CAB/05/ dated 24.04.2018.

**Terms used in PVC formulae:**

P = Price payable as adjusted in accordance with above appropriate formula (In Rs./Km).  
 Po= Price quoted/confined (in Rs./km).

**1. ALUMINIUM**

ALF Variation factor for aluminium.  
 Al =Price of aluminium.  
 Alo = Price of aluminium.

**2 COPPER**

CuF =Variation factor for copper.  
 Cu = Price of CC copper rods.  
 Cuo = Price of CC copper rods.

**3.PVCc COMPOUND/POLYMER**

PVCc = Price of PVC compound.  
 PVCco= Price of PVC compound.  
 CCFAL= Variation factor for PVC compound/Polymer for aluminium conductor cable.  
 CCFCu =Variation factor for PVC compound/Polymer for copper conductor cable.

**4. XLPE COMPOUND**

Cc = Price of XLPE compound.  
 Cco= Price of XLPE compound.  
 XLFAL= Variation factor for XLPE compound for aluminium conductor cable.  
 XLFCu =Variation factor for XLPE compound for copper conductor cable.

**5.STEEL**

Fe= Price of steel strips/steel wire.  
 Feo= Price of steel strips/steel wire.  
 FeF =Variation factor for steel.  
 FeW=Variation factor for round wire steel armouring.



501, Kakad Chambers  
132, Dr. Annie Besant Road, Worli  
Mumbai 400 018  
India

P: +91 22 2493 0532  
F: +91 22 2493 2705  
E: [mumbai@ieema.org](mailto:mumbai@ieema.org)  
[www.ieema.org](http://www.ieema.org)

## IEEMA (PVC)/Instrumentation Cable/2014

Effective from: 1<sup>st</sup> July 2014

### Material Price Variation Clause For Instrumentation Cables

The Price quoted/confirmed is based on the input cost of raw materials/components as on the date of quotation, and the same is deemed to be related to the prices of raw materials as specified in the price variation clause given below. In case of any variation in these prices, the price payable shall be subject to adjustment up or down in accordance with the formulae provided in this document.

Terms used in price variation formulae:

P Price payable as adjusted in accordance with above appropriate formula (in Rs/Km)

P<sub>0</sub> Price quoted/confirmed (in Rs/Km)

#### COPPER

CuF Variation factor for copper

Cu Price of CC copper rods. This price is as applicable on first working day of the month, one month prior to the date of delivery.

Cu<sub>0</sub> Price of CC copper rods. This price is as applicable on first working day of the month, one month prior to the date of tendering.

#### STEEL

FeF Variation factor for steel

Fe Price of Steel Strips/steel wire. This price is as applicable on the first working day of the month, one month prior to the date of delivery.

Fe<sub>0</sub> Price of steel strips/steel wire. This price is as applicable on first working day of the month, one month prior to the date of tendering.

The above prices and indices are as published by IEEMA vide Circular reference IEEMA(PVC)/CABLE/--/ prevailing as on 1<sup>st</sup> working day of the month i.e. one month prior to the date of tendering.

The date of delivery is the date on which the cable is notified as being ready for inspection/dispatch (in the absence of such notification, the date of manufacturer's dispatch note is to be considered as the date of delivery) or the contracted delivery date (including any agreed extension thereto), whichever is earlier.

Page 1 of 2

New Delhi  
Rishyamook Building, First Floor  
85 A, Panchsukian Road  
New Delhi 110001, India  
P: +91 11 2336 3013/14  
F: +91 11 2336 3015  
E: [delhi@ieema.org](mailto:delhi@ieema.org)

Bangalore  
204, Swiss Complex  
33, Race Course Road  
Bangalore 560001, India  
P: +91 80 2220 1316/18  
F: +91 80 2220 1317  
E: [bangalore@ieema.org](mailto:bangalore@ieema.org)

Kolkata  
503 A, Oswal Chambers  
2, Church Lane  
Kolkata 700001, India  
P: +91 33 6510 7856  
F: +91 33 2213 1326  
E: [kolkata@ieema.org](mailto:kolkata@ieema.org)

Indian Electrical & Electronics Manufacturers' Association

**IEEMA (PVC)/Instrumentation Cable/2014**

**Effective from: 1<sup>st</sup> July 2014**

**Notes**

- (a) All prices of raw materials are exclusive of modvatable excise/CV duty amount and exclusive of any other central, state or local taxes, octroi, etc.
- (b) All Prices are as on first working day of the month.
- (c) The details of prices are as under:
  1. Price of CC copper rods (in Rs/MT) is ex-works price as quoted by the primary producer.
  2. Price of galvanized steel strip / steel wire (in Rs/MT) is ex-works price as quoted by the manufacturer for Round steel Wire and Flat steel strip (the relevant price of steel strip or steel wire is to be selected depending upon the type of armouring of the cable).

**Price variation formula for 'Instrumentation Cables'**

$$P = P_o + CuF (Cu - Cu_o) + FeF (Fe - Fe_o)$$

**1. For Pair Instrumentation Over all Screen Cables**

Tables References:

Cu POS      Copper Factor  
Fe POS      Steel Factor

**2. For Pair Instrumentation Individual and Over all Screen Cables**

Tables References:

Cu PIS      Copper Factor  
Fe PIS      Steel Factor

**3. For Triad Instrumentation Over all Screen Cables**

Tables References:

Cu TOS      Copper Factor  
Fe TOS      Steel Factor

**4. For Triad Instrumentation Individual & Overall Screen Cables**

Tables References:

Cu TIS      Copper Factor  
Fe TIS      Steel Factor

  
**Deputy Director General**  
Page 2 of 2

## Copper Factors for Instrumentation Cables - CuF

### Cu POS

Pair Instrumentation Over all Screen Cables					
No. of Pairs Cable size in sq.mm	0.5 sq.mm	0.75 sq.mm	1.0 sq.mm	1.5 sq.mm	2.5 sq.mm
1	0.0142	0.0185	0.0233	0.0326	0.0500
2	0.0258	0.0345	0.0440	0.0625	0.0978
3	0.0353	0.0484	0.0626	0.0904	0.1433
4	0.0448	0.0623	0.0811	0.1183	0.1888
5	0.0578	0.0800	0.1022	0.1467	0.2356
6	0.0662	0.0926	0.1210	0.1768	0.2829
7	0.0756	0.1067	0.1378	0.2000	0.3245
8	0.0852	0.1204	0.1582	0.2327	0.3741
9	0.0933	0.1334	0.1734	0.2534	0.4134
10	0.1046	0.1485	0.1959	0.2893	0.4665
11	0.1111	0.1600	0.2089	0.3067	0.5023
12	0.1236	0.1764	0.2333	0.3452	0.5580
13	0.1289	0.1867	0.2445	0.3600	0.5912
14	0.1378	0.2000	0.2623	0.3867	0.6356
15	0.1467	0.2134	0.2800	0.4134	0.6801
16	0.1618	0.2322	0.3080	0.4573	0.7409
17	0.1645	0.2400	0.3156	0.4667	0.7690
18	0.1734	0.2534	0.3334	0.4934	0.8134
19	0.1822	0.2667	0.3512	0.5201	0.8579
20	0.1911	0.2800	0.3689	0.5467	0.9023
21	0.2000	0.2934	0.3867	0.5734	0.9468
22	0.2089	0.3067	0.4045	0.6001	0.9912
23	0.2178	0.3200	0.4223	0.6267	1.0357
24	0.2381	0.3437	0.4575	0.6813	1.1068
25	0.2356	0.3467	0.4578	0.6801	1.1246
26	0.2445	0.3600	0.4756	0.7068	1.1690
27	0.2534	0.3734	0.4934	0.7334	1.2135
28	0.2623	0.3867	0.5112	0.7601	1.2579
29	0.2711	0.4001	0.5290	0.7868	1.3024
30	0.2800	0.4134	0.5467	0.8134	1.3468
31	0.2889	0.4267	0.5645	0.8401	1.3913
32	0.2978	0.4401	0.5823	0.8668	1.4357
33	0.3067	0.4534	0.6001	0.8934	1.4802
34	0.3156	0.4667	0.6179	0.9201	1.5246
35	0.3245	0.4801	0.6356	0.9468	1.5691
36	0.3334	0.4934	0.6534	0.9735	1.6135
37	0.3423	0.5067	0.6712	1.0001	1.6580
38	0.3512	0.5201	0.6890	1.0268	1.7024
39	0.3600	0.5334	0.7068	1.0535	1.7469
40	0.3689	0.5467	0.7245	1.0801	1.7913
41	0.3778	0.5601	0.7423	1.1068	1.8358
42	0.3867	0.5734	0.7601	1.1335	1.8802
43	0.3956	0.5867	0.7779	1.1601	1.9247
44	0.4045	0.6001	0.7957	1.1868	1.9691
45	0.4134	0.6134	0.8134	1.2135	2.0136
46	0.4223	0.6267	0.8312	1.2402	2.0580
47	0.4312	0.6401	0.8490	1.2668	2.1025
48	0.4710	0.6759	0.9010	1.3410	2.2009

## Copper Factors for Instrumentation Cables - CuF

### Cu PIS

Pair Instrumentation Individual and Over all Screen Cables					
No. of Pairs Cable size in sq.mm	0.5 sq.mm	0.75 sq.mm	1.0 sq.mm	1.5 sq.mm	2.5 sq.mm
1	0.0133	0.0178	0.0222	0.0311	0.0489
2	0.0349	0.0437	0.0531	0.0717	0.1069
3	0.0490	0.0621	0.0763	0.1041	0.1570
4	0.0630	0.0806	0.0994	0.1389	0.2071
5	0.0800	0.1022	0.1245	0.1689	0.2578
6	0.0937	0.1200	0.1484	0.2042	0.3103
7	0.1067	0.1378	0.1689	0.2311	0.3556
8	0.1218	0.1569	0.1948	0.2692	0.4107
9	0.1334	0.1734	0.2134	0.2934	0.4534
10	0.1503	0.1943	0.2417	0.3349	0.5122
11	0.1600	0.2089	0.2578	0.3556	0.5512
12	0.1785	0.2313	0.2882	0.4001	0.6128
13	0.1867	0.2445	0.3023	0.4178	0.6490
14	0.2000	0.2623	0.3245	0.4489	0.6979
15	0.2134	0.2800	0.3467	0.4801	0.7468
16	0.2350	0.3053	0.3812	0.5305	0.8141
17	0.2400	0.3156	0.3912	0.5423	0.8446
18	0.2534	0.3334	0.4134	0.5734	0.8934
19	0.2667	0.3512	0.4356	0.6045	0.9423
20	0.2800	0.3689	0.4578	0.6356	0.9912
21	0.2934	0.3867	0.4801	0.6668	1.0401
22	0.3067	0.4045	0.5023	0.6979	1.0890
23	0.3200	0.4223	0.5245	0.7290	1.1379
24	0.3479	0.4535	0.5673	0.7911	1.2165
25	0.3467	0.4578	0.5690	0.7912	1.2357
26	0.3600	0.4756	0.5912	0.8223	1.2846
27	0.3734	0.4934	0.6134	0.8534	1.3335
28	0.3867	0.5112	0.6356	0.8846	1.3824
29	0.4001	0.5290	0.6579	0.9157	1.4313
30	0.4134	0.5467	0.6801	0.9468	1.4802
31	0.4267	0.5645	0.7023	0.9779	1.5291
32	0.4401	0.5823	0.7245	1.0090	1.5780
33	0.4534	0.6001	0.7468	1.0401	1.6269
34	0.4667	0.6179	0.7690	1.0712	1.6758
35	0.4801	0.6356	0.7912	1.1024	1.7247
36	0.4934	0.6534	0.8134	1.1335	1.7736
37	0.5067	0.6712	0.8357	1.1646	1.8225
38	0.5201	0.6890	0.8579	1.1957	1.8713
39	0.5334	0.7068	0.8801	1.2268	1.9202
40	0.5467	0.7245	0.9023	1.2579	1.9691
41	0.5601	0.7423	0.9246	1.2891	2.0180
42	0.5734	0.7601	0.9468	1.3202	2.0669
43	0.5867	0.7779	0.9690	1.3513	2.1158
44	0.6001	0.7957	0.9912	1.3824	2.1647
45	0.6134	0.8134	1.0135	1.4135	2.2136
46	0.6267	0.8312	1.0357	1.4446	2.2625
47	0.6401	0.8490	1.0579	1.4757	2.3114
48	0.6887	0.8936	1.1186	1.5587	2.4186

Steel Factors for Instrumentation Cables - FeF					
Fe POS					
Pair Instrumentation Over all Screen Cables					
No. of Pairs Cable size in sq.mm	0.5 sq.mm	0.75 sq.mm	1.0 sq.mm	1.5 sq.mm	2.5 sq.mm
1	0.1490	0.1565	0.1635	0.1735	0.1930
2	0.2190	0.2335	0.2470	0.2665	0.2595
3	0.2360	0.2545	0.2690	0.2900	0.2680
4	0.2390	0.2580	0.2715	0.2945	0.2830
5	0.2630	0.2820	0.2420	0.2805	0.3155
6	0.2840	0.3160	0.2805	0.2995	0.3430
7	0.2840	0.2595	0.2805	0.2995	0.3430
8	0.3235	0.2930	0.3030	0.3315	0.3780
9	0.2805	0.3180	0.3290	0.3590	0.4205
10	0.2970	0.3215	0.3455	0.3755	0.4385
11	0.3005	0.3255	0.3490	0.3805	0.4435
12	0.3055	0.3440	0.3680	0.3880	0.4520
13	0.3265	0.3530	0.3780	0.4105	0.4785
14	0.3265	0.3530	0.3780	0.4105	0.4785
15	0.3490	0.3765	0.4015	0.4365	0.5195
16	0.3490	0.3765	0.4015	0.4365	0.5195
17	0.3590	0.4005	0.4140	0.4635	0.5470
18	0.3590	0.4005	0.4265	0.4635	0.5470
19	0.3590	0.4005	0.4265	0.4635	0.5470
20	0.3830	0.4240	0.4535	0.4920	0.5760
21	0.3830	0.4240	0.4535	0.4920	0.5760
22	0.4065	0.4520	0.4785	0.5310	0.6190
23	0.4065	0.4520	0.4810	0.5310	0.6190
24	0.4305	0.4770	0.5070	0.5595	0.6475
25	0.4305	0.4770	0.5070	0.5595	0.6475
26	0.4305	0.4770	0.5070	0.5595	0.6475
27	0.4355	0.4820	0.5245	0.5660	0.6700
28	0.4570	0.5045	0.5345	0.5895	0.6950
29	0.4570	0.5045	0.5345	0.5895	0.6950
30	0.4570	0.5045	0.5345	0.5895	0.6950
31	0.4795	0.5285	0.5595	0.6150	0.7225
32	0.4820	0.5285	0.5595	0.6150	0.7225
33	0.4820	0.5285	0.5595	0.6150	0.7225
34	0.4920	0.5520	0.5835	0.6410	0.7500
35	0.4920	0.5520	0.5835	0.6410	0.7500
36	0.4920	0.5520	0.5835	0.6410	0.7500
37	0.4920	0.5520	0.5835	0.6410	0.7500
38	0.5145	0.5760	0.6225	0.6550	0.7805
39	0.5145	0.5760	0.6225	0.6550	0.7805
40	0.5145	0.5760	0.6225	0.6550	0.7805
41	0.5395	0.6025	0.6475	0.6975	0.8230
42	0.5395	0.6025	0.6475	0.6975	0.8230
43	0.5395	0.6025	0.6475	0.6975	0.8230
44	0.5635	0.6265	0.6735	0.7250	0.8540
45	0.5635	0.6265	0.6760	0.7250	0.8540
46	0.5635	0.6265	0.6760	0.7250	0.8540
47	0.5635	0.6265	0.6760	0.7250	0.8540
48	0.5635	0.6265	0.6760	0.7375	0.8665

# Steel Factors for Instrumentation Cables - FeF

## Fe PIS

### Pair Instrumentation Individual and Over all Screen Cables

No. of Pairs Cable size in sq.mm	0.5 sq.mm	0.75 sq.mm	1.0 sq.mm	1.5 sq.mm	2.5 sq.mm
1	0.1880	0.1980	0.2070	0.2220	0.2410
2	0.2315	0.2460	0.2595	0.2815	0.2755
3	0.2505	0.2690	0.2820	0.2495	0.2830
4	0.2645	0.2830	0.2420	0.2805	0.3155
5	0.2895	0.2730	0.2805	0.3005	0.3430
6	0.2755	0.2980	0.3005	0.3280	0.3730
7	0.2755	0.2980	0.3005	0.3280	0.3730
8	0.2980	0.3215	0.3455	0.3740	0.4230
9	0.3230	0.3490	0.3730	0.4040	0.4685
10	0.3405	0.3655	0.3765	0.4215	0.4885
11	0.3430	0.3690	0.3815	0.4265	0.4945
12	0.3490	0.3765	0.4015	0.4470	0.5160
13	0.3715	0.3990	0.4255	0.4720	0.5420
14	0.3715	0.3990	0.4255	0.4720	0.5420
15	0.3955	0.4240	0.4510	0.5020	0.5720
16	0.3955	0.4240	0.4510	0.5020	0.5720
17	0.4190	0.4495	0.4795	0.5295	0.6150
18	0.4190	0.4495	0.4795	0.5295	0.6150
19	0.4190	0.4495	0.4795	0.5295	0.6150
20	0.4445	0.4770	0.5060	0.5570	0.6450
21	0.4445	0.4895	0.5060	0.5695	0.6450
22	0.4695	0.5045	0.5345	0.5870	0.6885
23	0.4695	0.5045	0.5345	0.5870	0.6885
24	0.4970	0.5310	0.5620	0.6285	0.7210
25	0.4970	0.5310	0.5620	0.6285	0.7210
26	0.4970	0.5310	0.5620	0.6285	0.7210
27	0.5035	0.5495	0.5810	0.6360	0.7410
28	0.5135	0.5610	0.6050	0.6610	0.7690
29	0.5135	0.5610	0.6050	0.6610	0.7690
30	0.5260	0.5610	0.6050	0.6610	0.7690
31	0.5495	0.5845	0.6300	0.6885	0.7990
32	0.5495	0.5845	0.6300	0.6885	0.7990
33	0.5495	0.5845	0.6300	0.6885	0.7990
34	0.5735	0.6225	0.6585	0.7285	0.8405
35	0.5735	0.6225	0.6585	0.7285	0.8405
36	0.5735	0.6225	0.6585	0.7285	0.8405
37	0.5735	0.6225	0.6585	0.7285	0.8405
38	0.5990	0.6485	0.6850	0.7575	0.8740
39	0.5990	0.6485	0.6850	0.7575	0.8740
40	0.5990	0.6485	0.6850	0.7575	0.8740
41	0.6250	0.6775	0.7135	0.7880	0.9180
42	0.6250	0.6775	0.7135	0.7880	0.9180
43	0.6250	0.6775	0.7135	0.7880	0.9180
44	0.6485	0.7050	0.7410	0.8165	0.9495
45	0.6485	0.7050	0.7410	0.8165	0.9495
46	0.6485	0.7050	0.7410	0.8165	0.9495
47	0.6485	0.7050	0.7410	0.8165	0.9495
48	0.6485	0.7050	0.7535	0.8290	0.9620



Indian Electrical & Electronics Manufacturer's Association  
 501, Kakad Chambers P +91 22 2493 0532  
 132, Dr. A. B. Road, Worli, F +91 22 2493 2705  
 Mumbai - 400 018. E mumbai@ieema.org  
 INDIA. W www.ieema.org

Cir. No. 35/DIV/CAB/05/

24<sup>th</sup> April 2018

To Members of the Cable Division, Utilities, Railways &amp; Listed purchasing organizations

**Sub: Correction in PV formulae of LT XLPE Power Cable and addition of factors for HT XLPE Power Cables**

We have recently published revised Price Variation Clause for LT&HT XLPE Power Cables and made it effective from 1<sup>st</sup> November 2017 vide Cir. No.111/DIV/CAB/05 dated 5<sup>th</sup> December 2017


While replying to a query of a buyer it is observed that the polymer factor for LT XLPE Power Cables (both aluminium and copper) was incorrectly represented by Table P2.

We have now corrected the anomaly by correcting the PV formulae of LT XLPE Aluminium and Copper Insulated Cables (Sl. No. D & E) by representing Polymer factor by Table L2.

We have also worked out factors for XLPE, Copper and Steel for 3 core HT XLPE Power Cables for 500 and 630 sq.mm.

We now enclose complete PV clause of Cable by including all the PV formulae of different types of power cable (Sl. No. A to I), polymer factor Table L2 and updated XL4, H2 and H5 Table of factors for your perusal & record.

We request to replace PV clause of Cable already circulated vide Cir. 111/DIV/CAB/05 dated 5<sup>th</sup> December 2017 with the enclosed PV clause in your records for future use.

  
 Senior Director  
 Encl: as above

prasad partners in implementation



**HEAD OFFICE - DELHI**  
 Rishyamook Building, First Floor, 85 A, Panchsukian Road, New Delhi - 110001, INDIA.  
 P +91 11 2336 3013 / 14 • F +91 11 2336 3015 • E delhi@ieema.org • W www.ieema.org



Indian Electrical & Electronics Manufacturer's Association  
 501, Kakad Chambers P +91 22 2493 0532  
 132, Dr. A. B. Road, Worli, F +91 22 2493 2705  
 Mumbai - 400 018. E mumbai@ieema.org  
 INDIA. W www.ieema.org

**IEEMA (PVC)/CABLE(R-1)/2017****Effective from: 1<sup>st</sup> November 2017****Material Price Variation Clause For PVC And XLPE Insulated Cables**

The Price quoted/confirmed is based on the input cost of raw materials/components as on the date of quotation, and the same is deemed to be related to the prices of raw materials as specified in the price variation clause given below. In case of any variation in these prices, the price payable shall be subject to adjustment up or down in accordance with the formulae provided in this document.

Terms used in price variation formulae:

P Price payable as adjusted in accordance with above appropriate formula (in Rs/Km)

Po Price quoted/confirmed (in Rs/Km)

**ALUMINIUM**

AIF Variation factor for aluminium

AI Price of Aluminium. This price is as applicable of first working day of the month, one month prior to the date of delivery.

Alo Price of aluminium. This price is as applicable on first working day of the month, one month prior to the date of tendering.

**COPPER**

CuF Variation factor for copper

Cu Price of CC copper rods. This price is as applicable on first working day of the month, one month prior to the date of delivery.

Cuo Price of CC copper rods. This price is as applicable on first working day of the month, one month prior to the date of tendering.

**PVC COMPOUND**

PVCc price of PVC compound. This price is as applicable on first working day of the month, one month prior to the date of delivery.

PVCco Price of PVC compound. This price is as applicable on first working day of the month, one month prior to the date of tendering.

CCFAI Variation factor for PVC compound/Polymer for aluminum conductor cable.

CCFCu Variation factor for PVC compound/Polymer for copper conductor cable.

proud partners in implementation



**HEAD OFFICE - DELHI**  
 Rishyamook Building, First Floor, 85 A, Panchsheel Road, New Delhi - 110001, INDIA.  
 P +91 11 2336 3013 / 14 • F +91 11 2336 3015 • E delhi@ieema.org • W www.ieema.org



Indian Electrical & Electronics Manufacturer's Association  
 501, Kakad Chambers  
 132, Dr. A. B. Road, Worli,  
 Mumbai - 400 018.  
 INDIA.  
 P +91 22 2493 0532  
 F +91 22 2493 2705  
 E [mumbai@ieema.org](mailto:mumbai@ieema.org)  
 W [www.ieema.org](http://www.ieema.org)

**IEEMA (PVC)/CABLE(R-1)/2017**  
**XLPE COMPOUND**

**Effective from: 1<sup>st</sup> November 217**

**Cc** price of XLPE compound. This price is as applicable on first working day of the month, one month prior to the date of delivery.

**Cco** Price of XLPE compound. This price is as applicable on first working day of the month, one month prior to the date of tendering.

**XLFAL** Variation factor for XLPE compound for aluminum conductor cable.

**XLFCU** Variation factor for XLPE compound for Copper conductor cable.

**STEEL**

**FeF** Variation factor for steel

**FeW** Variation factor for round wire steel armouring

**Fe** Price of Steel Strips/steel wire. This price is as applicable on the first working day of the month, one month prior to the date of delivery.

**Feo** Price of steel strips/steel wire. This price is as applicable on first working day of the month, one month prior to the date of tendering.

The above prices and indices are as published by IEEMA vide Circular reference IEEMA (PVC)/CABLE R(1)/--/-- prevailing as on 1<sup>st</sup> working day of the month i.e. one month prior to the date of tendering.

The date of delivery is the date on which the cable is notified as being ready for inspection/dispatch (in the absence of such notification, the date of manufacturer's dispatch note is to be considered as the date of delivery) or the contracted delivery date (including any agreed extension thereto), whichever is earlier.

**Notes**

- (a) All prices of raw materials are exclusive of GST amount.
- (b) All prices excluding Aluminium & Copper are as on first working day of the month.
- (c) The details of prices are as under:

1. Price of Aluminium is LME average Cash SELLER Settlement price of Primary Aluminium in US\$ per MT as published by London Metal Bulletin (LME) including Premium for Aluminium Ingot in US\$ per MT is converted in Indian Rs./MT.
2. Price of PVC Compound (in Rs/MT) is the ex-works price, as quoted by the manufacturer.
3. Price of XLPE Compound (in Rs/MT) is the ex-works price, as quoted by the manufacturer
4. Price of CC copper rods (in Rs/MT) is ex-works price as quoted by the primary producer.
5. Price of galvanized steel strip / steel wire (in Rs/MT) is ex-works price as quoted by the manufacturer for Round steel Wire and Flat steel strip (the relevant price of steel strip or steel wire is to be selected depending upon the type of armouring of the cable).

prc& partners in implementation



**HEAD OFFICE - DELHI**

Rishyamook Building, First Floor, 85 A, Panchkuian Road, New Delhi - 110001, INDIA.

P +91 11 2336 3013 / 14 • F +91 11 2336 3015 • E [delhi@ieema.org](mailto:delhi@ieema.org) • W [www.ieema.org](http://www.ieema.org)



Indian Electrical & Electronics Manufacturer's Association  
 501, Kakad Chambers  
 132, Dr. A. B. Road, Worli,  
 Mumbai - 400 018.  
 INDIA.  
 P +91 22 2493 0532  
 F +91 22 2493 2705  
 E mumbai@ieema.org  
 W www.ieema.org

## IEEMA (PVC)/CABLE(R-1)/2017

Effective from: 1<sup>st</sup> November 217

## Price variation formulae for 'Power Cables'

## A. Aluminum conductor PVC insulated 1.1 kV power cables

$$P = P_o + AIF (AL - ALo) + CCFAI (PVCc - PVCco) + FeF (Fe - Feo)$$

For unarmoured multicore cables (without steel armour);  $FeF = 0$ Table References:

ALP	Aluminium conductor in single core unarmoured & multicore cables
P1	Aluminium conductor aluminium armour in single core armoured cables
P2	PVC compound
P3	Steel armour

## B. Copper conductor PVC insulated 1.1 kV power cables

$$P = P_o + CuF (Cu - Cuo) + CCFCu (PVCc - PVCco) + FeF (Fe - Feo) + AIF (Al - ALo)$$

For steel armoured cables;  $AIF = 0$  For aluminium armoured cables;  $FeF = 0$ For unarmoured cables;  $FeF, AIF = 0$ Tables References:

CUP	Copper conductor
P2	PVC compound
P3	Steel armour
P4	Aluminium armour

## C. Copper conductor PVC insulated 1.1 kV control cables

$$P = P_o + CuF (Cu - Cuo) + CCFCu (PVCc - PVCco) + FeF (Fe - Feo)$$

For unarmoured cables;  $FeF = 0$ Tables References:

CUC	Copper conductor
P5	PVC compound
P6	Steel armour

## D. Aluminum conductor XLPE insulated 1.1 kV power cables

$$P = P_o + AIF (AL - ALo) + XLFAL (CC - Cco) + CCFAI (PVCc - PVCco) + FeF (Fe - Feo)$$

For unarmoured multicore cables (without steel armour);  $FeF = 0$ Table References:

ALP	Aluminium conductor in single core unarmoured & multicore cables
P1	Aluminium conductor aluminium armour in single core armoured cables
L2	Polymer (CCFAI)
P3	Steel armour
XL1	XLPE Compound (XLFAL)

## E. Copper conductor XLPE insulated 1.1 kV power cables

$$P = P_o + CuF (Cu - Cuo) + XLFCU (CC - Cco) + CCFCu (PVCc - PVCco) + FeF (Fe - Feo) + AIF (Al - ALo)$$

proud partners in implementation

For steel armoured cables;  $AIF = 0$  For aluminium armoured cables;  $FeF = 0$ 

## HEAD OFFICE - DELHI

Rishyamook Building, First Floor, 85 A, Panchsukian Road, New Delhi - 110001, INDIA.

P +91 11 2336 3013 / 14 • F +91 11 2336 3015 • E delhi@ieema.org • W www.ieema.org

**IEEMA (PVC)/CABLE(R-1)/2017**Effective from: 1<sup>st</sup> November 217

For unarmoured cables; FeF, AIF = 0

Tables References:

CUP	Copper conductor
L2	Polymer (CCFCu)
P3	Steel armour
P4	Aluminium armour
XL1	XLPE Compound (XLFCu)

**F. Copper conductor XLPE insulated 1.1 kV control cables**

$$P = P_o + CuF (Cu - Cu_o) + XLFCU (CC-Cco) + CCFCu (PVCc-PVCco) + FeF (Fe-Fe_o)$$

For unarmoured cables; FeF = 0

Tables References:

CUC	Copper conductor
P5	PVC compound
P6	Steel armour
XL2	XLPE Compound

**G. For Aluminium conductor XLPE insulated 3.3 to 33 kV power cables**

$$P = P_o + AIF (Al - Al_o) + XLFAL (CC-Cco) + CCFAI (PVCc - PVCco) + FeF (Fe - Fe_o)$$

For unarmoured multicore cables (without steel armour); FeF = 0

Table References:

ALP	Aluminium conductor in single core unarmoured & multicore cables
H1	Aluminium conductor + aluminium armour in single core armoured cables
H2	Polymer
H3/H5	Steel armour (Flat/Round)
XL3/XL4	XLPE Compound (Single core /Multicore)

**H. Copper conductor XLPE Insulated 3.3 to 33 kV power cables**

$$P = P_o + CuF (Cu - Cu_o) + XLFCU (CC-Cco) + CCFCu (PVCc - PVCco) + FeF (Fe - Fe_o) + AIF (Al - Al_o)$$

For steel armoured cables; AIF = 0 For aluminium armoured cables; FeF = 0

For unarmoured cables; FeF, AIF = 0

Table References:

CUP	Copper conductor
H2	Polymer
H3/H5	Steel armour (Flat/Round)
H4	Aluminium armour
XL3/XL4	XLPE Compound (Single core /Multicore)

**I. Copper conductor XLPE insulated 1.0 and 1.5 kV Solar PV DC cables**

$$P = P_o + CuF (Cu - Cu_o)$$

Table CUscd Copper Conductor

proud partners in implementation


 MISSION PLAN  
 2012-2022

HEAD OFFICE - DELHI

Rishyamook Building, First Floor, 85 A, Panchsukian Road, New Delhi - 110001, INDIA.

P +91 11 2336 3013 / 14 • F +91 11 2336 3015 • E delhi@ieema.org • W www.ieema.org

  
 Authorized Signatory

IEEMA (PVC)/CABLE(R-1)/2017

Effective from: 1<sup>st</sup> November 217

TABLE ALP

VARIATION FACTOR FOR ALUMINIUM (AIF)  
POWER CABLES WITH ALUMINIUM CONDUCTOR  
(EXCLUDING SINGLE CORE ARMoured CABLES)

Nominal Cross Sectional Area (in Sq. mm.)	1 core	2 core	3 core	3.5 core	4 core
2.5	0.007	0.014	0.021	-	0.028
4	0.011	0.023	0.034	-	0.046
6	0.017	0.034	0.052	-	0.069
10	0.029	0.053	0.087	-	0.116
16	0.046	0.091	0.137	-	0.183
25/16	0.073	0.146	0.219	0.262	0.292
35/16	0.101	0.202	0.302	0.345	0.404
50/25	0.137	0.273	0.410	0.478	0.547
70/35	0.197	0.395	0.593	0.687	0.791
95/50	0.274	0.548	0.821	0.949	1.095
120/70	0.346	0.691	1.035	1.221	1.382
150/70	0.425	0.853	1.279	1.464	1.706
185/95	0.533	1.070	1.605	1.861	2.140
225/120	0.655	1.310	1.965	2.287	2.620
240/120	0.703	1.400	2.099	2.421	2.799
300/150	0.879	1.757	2.635	3.033	3.514
400/185	1.126	2.249	3.374	3.873	4.498
500	1.418	2.838	4.256	-	5.675
630	1.828	3.663	5.494	-	7.326
800	2.340	4.679	7.018	-	9.357
1000	2.951	5.890	8.834	-	11.779

IEEMA (PVC)/CABLE(R-1)/2017

Effective from: 1<sup>st</sup> November 217

TABLE CUP

**VARIATION FACTOR FOR COPPER CONDUCTOR (CUF)**  
**POWER CABLES WITH COPPER CONDUCTOR**

Nominal Cross Sectional Area (in Sq. mm.)	1 core	2 core	3 core	3.5 core	4 core
2.5	0.023	0.046	0.069	-	0.092
4	0.036	0.076	0.112	-	0.151
6	0.056	0.112	0.171	-	0.227
10	0.095	0.174	0.286	-	0.382
16	0.151	0.299	0.451	-	0.602
25/16	0.240	0.480	0.720	0.862	0.960
35/16	0.332	0.664	0.993	1.135	1.329
50/25	0.451	0.898	1.348	1.572	1.799
70/35	0.648	1.299	1.950	2.260	2.602
95/50	0.901	1.802	2.700	3.121	3.601
120/70	1.138	2.273	3.407	4.016	4.545
150/70	1.398	2.806	4.207	4.815	5.611
185/95	1.753	3.519	5.279	6.121	7.038
225/120	2.154	4.309	6.463	7.522	8.617
240/120	2.312	4.605	6.904	7.963	9.206
300/150	2.891	5.779	8.667	9.976	11.558
400/185	3.703	7.397	11.097	12.738	14.794
500	4.664	9.334	13.998	-	18.665
630	6.012	12.048	18.070	-	24.095
800	7.696	15.389	23.082	-	30.775
1000	9.706	19.372	29.055	-	38.741

TABLE CU<sub>sd</sub>c

**VARIATION FACTOR FOR COPPER CONDUCTOR (CUF)**  
**1.0 & 1.5KV Solar PV DC Cables with Copper Conductor**

Cable Size in sq.mm.	Copper content in MT/km
2.5	0.023
4	0.038
6	0.058
10	0.090

IEEMA (PVC)/CABLE(R-1)/2017

Effective from: 1<sup>st</sup> November 217

TABLE CUC

**VARIATION FACTOR FOR COPPER CONDUCTOR (CUF)  
CONTROL CABLES WITH COPPER CONDUCTOR**

No of Cores	Core size 1.5 sq mm	Core size 2.5 sq mm
2	0.026	0.047
3	0.039	0.070
4	0.052	0.094
5	0.065	0.117
6	0.078	0.141
7	0.091	0.164
8	0.110	0.182
9	0.117	0.205
10	0.130	0.235
12	0.157	0.282
14	0.183	0.329
16	0.209	0.376
18	0.246	0.410
19	0.248	0.446
20	0.260	0.456
24	0.313	0.563
27	0.352	0.634
30	0.391	0.704
37	0.483	0.869
44	0.573	1.033
52	0.678	1.221
61	0.796	1.432

IEEMA (PVC)/CABLE(R-1)/2017

Effective from: 1<sup>st</sup> November 217

TABLE P1

**VARIATION FACTOR FOR ALUMINIUM (AIF)**  
**ALUMINIUM ARMoured SINGLE CORE PVC INSULATED 1.1 KV CABLES**

Nominal cross sectional area (in Sq.mm)	Aluminium factor for Aluminium armoured cable with aluminium conductor
4	0.0685
6	0.0795
10	0.1017
16	0.1303
25	0.1693
35	0.2090
50	0.2597
70	0.3360
95	0.4567
120	0.5443
150	0.6427
185	0.7743
240	0.9737
300	1.2582
400	1.5502
500	1.8958
630	2.3650
800	2.9306
1000	3.7666

IEEMA (PVC)/CABLE(R-1)/2017

Effective from: 1<sup>st</sup> November 217

TABLE P2

VARIATION FACTOR FOR PVC COMPOUND (CCFAI/CCFCu)  
PVC INSULATED 1.1 KV POWER CABLES WITH COPPER/ALUMINIUM CONDUCTOR

Nominal cross Sectional Area (in Sq. mm)	1 core	2 core		3 core		3.5 core		4 core	
	Unarm	Unarm	arm	Unarm	arm	Unarm	arm	Unarm	arm
2.5	0.079	0.125	0.139	0.141	0.157	-	-	0.161	0.179
4	0.094	0.140	0.156	0.164	0.182	-	-	0.188	0.209
6	0.101	0.154	0.171	0.179	0.199	-	-	0.198	0.220
10	0.114	0.194	0.216	0.214	0.238	-	-	0.249	0.277
16	0.142	0.234	0.246	0.279	0.290	-	-	0.328	0.345
25	0.171	0.288	0.303	0.364	0.383	0.422	0.444	0.443	0.466
35	0.189	0.321	0.338	0.403	0.429	0.489	0.515	0.498	0.524
50	0.211	0.411	0.433	0.508	0.535	0.613	0.645	0.647	0.681
70	0.241	-	-	0.613	0.645	0.707	0.744	-	-
95	0.284	-	-	0.795	0.811	0.908	0.927	-	-
120	0.339	-	-	0.866	0.884	1.024	1.045	-	-
150	0.388	-	-	1.070	1.092	1.289	1.315	-	-
185	0.450	-	-	1.310	1.337	1.499	1.530	-	-
225	0.521	-	-	1.586	1.618	1.840	1.878	-	-
240	0.534	-	-	1.649	1.683	1.990	2.031	-	-
300	0.653	-	-	2.007	2.048	2.361	2.409	-	-
400	0.770	-	-	2.437	2.487	2.616	2.669	-	-
500	0.936	-	-	3.117	3.181	3.687	3.762	-	-
630	1.175	-	-	-	-	-	-	-	-
800	1.433	-	-	-	-	-	-	-	-
1000	1.642	-	-	-	-	-	-	-	-

IEEMA (PVC)/CABLE(R-1)/2017

Effective from: 1<sup>st</sup> November 2017

TABLE P3

**VARIATION FACTOR FOR STEEL (FeF)**  
PVC INSULATED 1.1 KV POWER CABLES WITH COPPER/ALUMINIUM CONDUCTOR

Nominal Cross sectional Area (in Sq. mm)	2 core	Shape	3 core	Shape	3 ½ core	Shape	4 core	Shape
4	0.305	W	0.335	W	-	-	0.363	W
6	0.348	W	0.363	W	-	-	0.407	W
10	0.392	W	0.407	W	-	-	0.293	F
16	0.235	F	0.293	F	-	-	0.323	F
25	0.293	F	0.352	F	0.382	F	0.382	F
35	0.323	F	0.382	F	0.411	F	0.440	F
50	0.382	F	0.440	F	0.469	F	0.499	F
70	0.411	F	0.499	F	-	F	0.587	F
95	0.499	F	0.587	F	0.616	F	0.645	F
120	0.528	F	0.616	F	0.675	F	0.731	F
150	0.587	F	0.675	F	0.731	F	0.790	F
185	0.645	F	0.761	F	0.820	F	0.879	F
240	0.731	F	0.879	F	0.937	F	0.996	F
300	0.820	F	0.966	F	1.055	F	1.113	F
400	0.937	F	1.083	F	1.172	F	1.231	F
500	1.055	F	1.231	F	1.348	F	1.406	F
630	1.172	F	-	-	-	-	-	-

IEEMA (PVC)/CABLE(R-1)/2017  
TABLE P3 (Additional)

Effective from: 1<sup>st</sup> November 217

VARIATION FACTOR FOR ROUND WIRE 'W' STEEL (FeF)  
PVC INSULATED 1.1 KV POWER CABLES WITH COPPER/ALUMINIUM CONDUCTOR

Nominal Cross Sectional Area (in sq. mm)	2 Core	3 Core	3.5 Core	4 Core
1.5	0.247	0.259		0.288
2.5	0.273	0.289		0.329
4	0.305	0.335		0.363
6	0.348	0.363		0.407
10	0.392	0.407		0.533
16	0.439	0.523	0.014	0.573
25	0.526	0.625	0.664	0.685
35	0.591	0.685	0.729	0.761
50	0.661	0.790	0.864	1.108
70	0.745	1.122	1.200	1.256
95	1.085	1.286	1.376	1.443
120	1.147	1.386	1.479	1.562
150	1.267	1.526	1.684	2.173
185	1.403	2.090	2.315	2.421
240	1.994	2.397	2.641	2.722
300	2.180	2.642	3.670	3.842
400	2.987	3.728	4.126	4.292
500	3.517	4.226	5.958	6.301
630	4.774	6.018	6.737	7.141

IEEMA (PVC)/CABLE(R-1)/2017

Effective from: 1<sup>st</sup> November 217

TABLE P4

**VARIATION FACTOR FOR ALUMINIUM (AIF)**  
**PVC INSULATED 1.1 KV POWER CABLES WITH COPPER CONDUCTOR**

Nominal Cross Sectional Area (in Sq. mm)	Aluminium Factor for Aluminium armoured cable with copper conductor
4	0.058
6	0.063
10	0.073
16	0.084
25	0.096
35	0.108
50	0.123
70	0.139
95	0.183
120	0.198
150	0.218
185	0.241
240	0.271
300	0.379
400	0.424
500	0.478
630	0.537
800	0.591
1000	0.816

IEEMA (PVC)/CABLE(R-1)/2017

Effective from: 1<sup>st</sup> November 2017

TABLE P5

VARIATION FACTOR FOR PVC COMPOUND (CCFCu)  
PVC INSULATED CONTROL CABLES WITH COPPER CONDUCTOR

No of cores	Core size 1.5 sq mm		Core size 2.5 sq mm	
	Unarm	Arm	Unarm	Arm
2	0.118	0.121	0.125	0.139
3	0.121	0.131	0.141	0.157
4	0.137	0.152	0.161	0.179
5	0.157	0.174	0.187	0.206
6	0.179	0.199	0.234	0.260
7	0.179	0.199	0.234	0.260
8	0.193	0.215	0.292	0.325
9	0.216	0.241	0.300	0.335
10	0.236	0.262	0.303	0.337
12	0.249	0.277	0.334	0.371
14	0.311	0.327	0.389	0.409
16	0.344	0.362	0.435	0.458
18	0.352	0.371	0.474	0.500
19	0.375	0.395	0.476	0.501
20	0.391	0.412	0.519	0.546
24	0.457	0.481	0.584	0.615
27	0.491	0.517	0.631	0.664
30	0.529	0.557	0.706	0.743
37	0.615	0.647	0.835	0.879
44	0.739	0.778	1.019	1.026
52	0.845	0.889	1.100	1.158
61	0.952	1.002	1.246	1.312

IEEMA (PVC)/CABLE(R-1)/2017  
TABLE P6

Effective from: 1<sup>st</sup> November 2017

VARIATION FACTOR FOR STEEL (FeF)  
PVC INSULATED CONTROL CABLES WITH COPPER CONDUCTOR

No of cores	Core size 1.5 sq mm	Shape of armour	Core size 2.5 sq mm	Shape of armour
2	0.243	W	0.277	W
3	0.257	W	0.289	W
4	0.277	W	0.314	W
5	0.303	W	0.342	W
6	0.329	W	0.379	W
7	0.329	W	0.379	W
8	0.341	W	0.456	W
9	0.383	W	0.275	F
10	0.408	W	0.325	F
12	0.289	F	0.342	F
14	0.306	F	0.360	F
16	0.317	F	0.372	F
18	0.332	F	0.350	F
19	0.343	F	0.397	F
20	0.368	F	0.400	F
24	0.398	F	0.475	F
27	0.414	F	0.478	F
30	0.425	F	0.503	F
37	0.461	F	0.548	F
44	0.507	F	0.601	F
52	0.556	F	0.641	F
61	0.585	F	0.685	F

IEEMA (PVC)/CABLE(R-1)/2017  
TABLE P6 (Additional)

Effective from: 1<sup>st</sup> November 217

**VARIATION FACTOR FOR ROUND WIRE 'W' STEEL (FeF)**  
**PVC INSULATED CONTROL CABLES WITH COPPER CONDUCTOR**

No. of Cores	Core size 1.5 sq mm	Core size 2.5 sq mm
2	0.243	0.273
3	0.257	0.289
4	0.277	0.314
5	0.303	0.342
6	0.329	0.379
7	0.329	0.379
8	0.341	0.456
9	0.383	0.508
10	0.408	0.535
12	0.510	0.572
14	0.546	0.625
16	0.581	0.660
19	0.608	0.696
24	0.714	0.819
25	0.679	0.798
27	0.732	0.837
28	0.696	0.815
30	0.758	0.881
33	0.747	0.883
37	0.820	1.217
44	0.926	1.355
48	1.122	1.308
50	1.122	1.308
52	1.149	1.361
56	1.202	1.388
61	1.299	1.520

IEEMA (PVC)/CABLE(R-1)/2017

Effective from: 1<sup>st</sup> November 217

TABLE L2

VARIATION FACTOR FOR POLYMER (CCFAI / CCFCu)  
XLPE INSULATED 1.1 KV POWER CABLES WITH COPPER / ALUMINIUM CONDUCTOR

Nominal Cross Sectional Area (in Sq. mm)	1 core	2 core		3 core		3.5 core		4 core	
	Unarm	Unarm	Arm	Unarm	Arm	Unarm	Arm	Unarm	Arm
2.5	0.055	0.163	0.175	0.166	0.177	-	-	0.177	0.188
4	0.075	0.201	0.204	0.205	0.213	-	-	0.218	0.213
6	0.085	0.213	0.234	0.205	0.230	-	-	0.242	0.232
10	0.082	0.252	0.280	0.217	0.251	-	-	0.285	0.298
16	0.089	0.278	0.341	0.289	0.246	-	-	0.300	0.279
25	0.101	0.307	0.278	0.276	0.247	0.295	0.264	0.331	0.290
35	0.109	0.330	0.319	0.305	0.270	0.328	0.292	0.368	0.319
50	0.124	0.482	0.685	0.348	0.311	0.372	0.335	0.422	0.394
70	0.146	0.354	0.335	0.469	0.397	0.489	0.420	0.528	0.464
95	0.163	0.436	0.389	0.504	0.441	0.544	0.471	0.591	0.523
120	0.176	0.475	0.421	0.556	0.498	0.599	0.538	0.722	0.656
150	0.217	0.510	0.490	0.690	0.611	0.717	0.633	0.840	0.762
185	0.236	0.631	0.608	0.836	0.738	0.854	0.756	1.007	0.899
240	0.273	0.750	0.726	1.002	0.842	1.079	0.952	1.238	1.119
300	0.303	0.919	0.887	1.161	1.012	1.170	1.031	1.457	1.414
400	0.372	1.093	1.040	1.376	1.283	1.545	1.379	1.778	1.626
500	0.413	1.342	-	1.568	1.400	1.806	1.456	-	-
630	0.469	1.546	-	-	-	-	-	-	-
800	0.569	-	-	-	-	-	-	-	-
1000	0.667	-	-	-	-	-	-	-	-

IEEMA (PVC)/CABLE(R-1)/2017

Effective from: 1<sup>st</sup> November 217

TABLE XL1  
VARIATION FACTOR FOR XLPE COMPOUND ( XLFAL/XLFUCU)  
XLPE INSULATED 1.1 KV POWER CABLES WITH COPPER/ALUMINIUM CONDUCTOR

Nominal cross Sectional Area (in Sq. mm)	1 core		2 core		3 core		3.5 core		4 core	
	Unarm	Arm	Unarm	Arm	Unarm	arm	Unarm	Arm	Unarm	arm
2.5	0.007	0.010	0.014	0.014	0.021	0.021			0.028	0.028
4	0.009	0.012	0.018	0.018	0.027	0.027			0.036	0.036
6	0.010	0.015	0.022	0.022	0.033	0.033			0.043	0.043
10	0.013	0.018	0.025	0.025	0.039	0.039			0.053	0.053
16	0.016	0.023	0.034	0.034	0.049	0.049			0.065	0.065
25	0.021	0.030	0.048	0.048	0.070	0.070	0.084	0.084	0.093	0.093
35	0.025	0.035	0.059	0.059	0.084	0.084	0.099	0.099	0.112	0.112
50	0.033	0.044	0.075	0.075	0.108	0.108	0.130	0.130	0.144	0.144
70	0.042	0.054	0.095	0.095	0.137	0.137	0.160	0.160	0.179	0.179
95	0.048	0.062	0.110	0.110	0.160	0.160	0.190	0.190	0.211	0.211
120	0.060	0.076	0.138	0.138	0.200	0.200	0.239	0.239	0.266	0.266
150	0.078	0.095	0.180	0.180	0.259	0.259	0.296	0.296	0.344	0.344
185	0.097	0.116	0.224	0.224	0.324	0.324	0.369	0.369	0.430	0.430
240	0.116	0.137	0.266	0.266	0.388	0.388	0.446	0.446	0.518	0.518
300	0.138	0.164	0.325	0.325	0.467	0.467	0.540	0.540	0.620	0.620
400	0.175	0.214	0.357	0.357	0.536	0.536	0.619	0.619	0.714	0.714
500	0.217	0.260	0.440	0.440	0.660	0.660	0.769	0.769	0.880	0.880
630	0.265	0.318	0.542	0.542	0.814	0.814	0.941	0.941	1.085	1.085
800	0.323	0.389								
1000	0.375	0.444								

IEEMA (PVC)/CABLE(R-1)/2017

Effective from: 1<sup>st</sup> November 217

TABLE XL2  
VARIATION FACTOR FOR XLPE COMPOUND (XLFCU)  
XLPE INSULATED CONTROL CABLES WITH COPPER CONDUCTOR

No of cores	Core size 1.5 sq mm		Core size 2.5 sq mm	
	Unarm	Arm	Unarm	Arm
2	0.010	0.010	0.012	0.012
3	0.016	0.016	0.018	0.018
4	0.021	0.021	0.025	0.025
5	0.026	0.026	0.031	0.031
6	0.031	0.031	0.037	0.037
7	0.036	0.036	0.043	0.043
8	0.036	0.036	0.043	0.043
9	0.042	0.042	0.049	0.049
10	0.052	0.052	0.061	0.061
12	0.062	0.062	0.074	0.074
14	0.073	0.073	0.086	0.086
16	0.083	0.083	0.098	0.098
18	0.094	0.094	0.110	0.110
19	0.099	0.099	0.116	0.116
20	0.104	0.104	0.123	0.123
24	0.125	0.125	0.147	0.147
27	0.140	0.140	0.165	0.165
30	0.156	0.156	0.184	0.184
37	0.192	0.192	0.227	0.227
44	0.229	0.229	0.270	0.270
52	0.270	0.270	0.319	0.319
61	0.317	0.317	0.374	0.374

IEEMA (PVC)/CABLE(R-1)/2017

Effective from: 1<sup>st</sup> November 217

TABLE XL3

VARIATION FACTOR FOR XLPE( XLFAL/XLFUCU)

SINGLE CORE ARMoured /UNARMoured XLPE INSULATED 3.3 to 33 KV POWER CABLES WITH  
CU / AL CONDUCTOR

Nominal Cross Sectional Area (in Sq. mm.)	XLPE Factor for Armoured/ Unarmoured Cable with AL /CU Conductor					
	3.3 KV	6.6 KV (E)	11 KV (E)/ 6.6 KV (UE)	11 KV (UE)	22 KV (E)	33 KV (E)
25	0.110	0.131	0.170	0.279		
35	0.122	0.137	0.175	0.284	0.317	0.522
50	0.135	0.151	0.191	0.307	0.341	0.563
70	0.155	0.172	0.215	0.342	0.379	0.615
95	0.174	0.193	0.241	0.377	0.417	0.670
120	0.192	0.212	0.262	0.407	0.449	0.713
150	0.209	0.229	0.283	0.437	0.481	0.757
185	0.228	0.250	0.308	0.471	0.518	0.809
240	0.255	0.279	0.343	0.519	0.569	0.883
300	0.280	0.322	0.372	0.560	0.613	0.943
400	0.326	0.392	0.420	0.625	0.683	1.041
500	0.388	0.461	0.469	0.694	0.757	1.142
630	0.467	0.520	0.529	0.777	0.845	1.265
800	0.567	0.593	0.602	0.874	0.949	1.407
1000	0.656	0.665	0.660	0.955	1.036	1.525

Note : XLPE factors include Semicons for Conductor & Insulation screen

TABLE - XL4

VARIATION FACTOR FOR XLPE (CCF1A/ / CCF1Cu)

3 CORE XLPE INSULATED 3.3 to 33 KV POWER CABLES WITH COPPER / ALUMINIUM CONDUCTOR

Nominal Cross Sectional Area (in Sq. mm)	3.3 KV ARM	6.6 KV (E) ARM	6.6 KV (UE) / 11 KV (E) ARM	11 KV (UE) ARM	22 KV (E) ARM	33 KV (E) ARM
25	0.315	0.394	0.511	0.838		
35	0.339	0.427	0.545	0.880	0.982	1.638
50	0.378	0.474	0.600	0.957	1.065	1.751
70	0.435	0.541	0.679	1.067	1.183	1.916
95	0.489	0.604	0.755	1.171	1.295	2.071
120	0.537	0.661	0.822	1.265	1.396	2.210
150	0.585	0.719	0.890	1.359	1.497	2.350
185	0.642	0.784	0.968	1.468	1.614	2.513
240	0.717	0.873	1.074	1.615	1.773	2.732
300	0.781	1.006	1.167	1.744	1.928	2.919
400	0.886	1.227	1.314	1.948	2.130	3.229
500	0.956	1.421	1.446	2.148	2.381	3.538
630	1.129	1.582	1.609	2.382	2.630	3.940

Note : XLPE factors include Semicons for Conductor & Insulation screen

IEEMA (PVC)/CABLE(R-1)/2017

Effective from: 1<sup>st</sup> November 217

**TABLE H1**  
**VARIATION FACTOR FOR ALUMINIUM (AIF)**  
**ALUMINIUM ARMoured SINGLE CORE XLPE INSULATED 3.3 TO 33 KV CABLES**

Nominal Cross Sectional Area (in Sq. mm.)	Aluminium Factor for Aluminium Armoured Cable with Aluminium Conductor					
	3.3 KV	6.6 KV (E)	11 KV (E)/ 6.6 KV (UE)	11 KV (UE)	22 KV (E)	33 KV (E)
35	0.251	0.284	0.301	0.344	0.358	0.473
50	0.312	0.336	0.352	0.397	0.408	0.672
70	0.385	0.409	0.423	0.469	0.501	0.723
95	0.476	0.500	0.518	0.637	0.656	0.856
120	0.561	0.586	0.601	0.726	0.744	0.949
150	0.653	0.678	0.696	0.823	0.842	1.050
185	0.773	0.797	0.893	0.949	0.965	1.183
240	0.997	1.063	1.083	1.139	1.154	1.387
300	1.209	1.271	1.283	1.333	1.307	1.753
400	1.438	1.556	1.565	1.620	1.636	2.046
500	1.873	1.901	1.910	2.110	2.128	2.484
630	2.337	2.361	2.369	2.580	2.595	2.978
800	3.007	3.071	3.080	3.145	3.163	3.588
1000	3.737	3.741	3.749	3.804	3.822	4.565

**TABLE H2**  
**VARIATION FACTOR FOR POLYMER (CCFAI / CCFCu)**  
**3 CORE XLPE INSULATED 3.3 to 33 KV POWER CABLES WITH COPPER / ALUMINIUM CONDUCTOR**

Nominal Cross Sectional Area (in Sq. mm)	3.3 KV ARM	6.6 KV (E) ARM	6.6 KV (UE) / 11 KV (E) ARM	11 KV (UE) ARM	22 KV (E) ARM	33 KV (E) ARM
35	0.374	0.990	1.142	1.604	1.782	-
50	0.445	1.119	1.260	1.834	2.046	2.864
70	0.547	1.290	1.396	2.011	2.284	3.219
95	0.594	1.440	1.647	2.269	2.428	3.367
120	0.732	1.692	1.877	2.498	2.715	3.646
150	0.812	1.906	2.061	2.767	2.931	3.927
185	0.960	2.086	2.406	3.028	3.180	4.166
240	1.130	2.484	2.744	3.398	3.580	4.589
300	1.219	2.912	3.161	3.840	4.016	5.029
400	1.313	3.530	3.664	4.353	4.666	5.736
500	1.652	3.925	3.971	4.621	4.878	5.913
630	1.949	4.487	4.982	5.225	5.477	6.696

Fillers added in PVC consumption

IEEMA (PVC)/CABLE(R-1)/2017

Effective from: 1<sup>st</sup> November 217

TABLE H3  
VARIATION FACTOR FOR STEEL (FeF)  
XLPE INSULATED 3.3 TO 33 KV POWER CABLES WITH COPPER / ALUMINIUM CONDUCTOR

Nominal Cross Sectional Area Sq. mm.	3.3 KV	6.6 KV (E)	11 KV (E) / 6.6 KV (UE)	11 KV (UE)	22 KV (E)	33 KV (E)
25	0.551	0.604	0.656	0.814		
35	0.645	0.645	0.731	0.879	0.937	-
50	0.675	0.703	0.761	0.937	0.966	1.181
70	0.761	0.761	0.849	0.996	1.055	1.289
95	0.820	0.849	0.907	1.083	1.113	1.348
120	0.879	0.907	0.966	1.142	1.172	1.406
150	0.966	0.966	1.055	1.201	1.259	1.494
185	1.025	1.055	1.113	1.259	1.318	1.553
240	1.142	1.142	1.231	1.377	1.406	1.641
300	1.231	1.259	1.318	1.465	1.524	1.758
400	1.348	1.406	1.435	1.582	1.641	1.876

**TABLE H4**  
**VARIATION FACTOR FOR ALUMINIUM (AIF)**  
**XLPE INSULATED SINGLE CORE 3.3 TO 33 KV POWER CABLES WITH COPPER CONDUCTOR**

Nominal Cross Sectional Area (in Sq. mm.)	Aluminium Factor for Aluminium Armoured Cable with Copper Conductor					
	3.3 KV	6.6 KV (E)	11 KV (E)/ 6.6 KV (UE)	11 KV (UE)	22 KV (E)	33 KV (E)
35	0.153	0.187	0.204	0.247	0.258	0.372
50	0.179	0.203	0.220	0.262	0.275	0.425
70	0.196	0.219	0.233	0.278	0.311	0.444
95	0.213	0.237	0.254	0.373	0.392	0.470
120	0.228	0.253	0.268	0.393	0.410	0.488
150	0.243	0.269	0.287	0.414	0.432	0.504
185	0.261	0.285	0.381	0.437	0.455	0.526
240	0.324	0.389	0.410	0.465	0.480	0.556
300	0.365	0.428	0.440	0.490	0.510	0.737
400	0.432	0.471	0.480	0.536	0.552	0.783
500	0.489	0.517	0.526	0.726	0.744	0.844
630	0.544	0.568	0.572	0.787	0.801	0.902
800	0.706	0.787	0.797	0.862	0.880	0.982
1000	0.824	0.865	0.867	0.923	0.940	1.324

**TABLE - H5**  
**VARIATION FACTOR FOR STEEL (FeW)**  
**XLPE INSULATED 3.3KV TO 33 KV POWER CABLES WITH COPPER / ALUMINIUM CONDUCTOR**

Nominal Cross Sectional Area in Sq. mm	3.3/3.3 KV	3.3/6.6 KV	11 KV (E) / 6.6 KV (UE)	11 KV (UE)	22 KV (E)	33 KV (E)
25	1.258	1.457	1.612	2.509	1.503	--
35	1.361	1.569	1.853	2.644	2.797	2.517
50	1.682	1.687	2.321	2.800	2.921	4.569
70	2.033	1.979	2.503	3.219	3.347	4.809
95	2.202	2.507	2.718	4.019	4.200	5.437
120	2.371	2.675	2.882	4.241	4.416	6.713
150	2.870	2.847	3.265	4.447	4.621	6.976
185	3.121	3.309	4.148	4.726	5.289	7.356
240	3.758	4.227	4.442	5.442	6.651	7.718
300	4.099	5.024	5.182	6.894	7.084	8.187
400	5.750	6.572	6.658	7.433	7.657	8.760
500	6.716	6.777	6.861	7.588	7.797	8.830
630	7.492	7.465	7.477	8.209	8.386	9.413