

# BHARAT HEAVY ELECT CALS LIMITED Heavy Power Equipment Plant, Ramachandrapuram,

Hyderabad - 502 032. INDIA. Phones: 23182581 / 23182052


Enquiry No.:	
Due Date :	
Supplier Qtn. No.:	
Date :	



### SPECIFICATION FOR COMBINATION TYPE PEDESTAL GRINDER QTY: 2 NOS

SS OF THE SUPPLIER:			
HONE NOS.:			
PS.:			
ADDRESS:			
Description for BHEL Requirement	Offered	Deviations	Remarks
Abrasive belt assembly on RH side & Grinding wheel on LH side			
Motor rating: 2 HP (Minimum)			
Shaft speed : Specify			
Center height: 900 to 950 mm			
Grinding wheel size: φ250 mm x 25 mm			
Abrasive belt size: 50 mm x 2000 mm			
Serrated rubber wheel (for belt): φ250 x 50 mm			
Standard Accessories:			
Grinding wheels (1 No coarse & 1 No fine) for LH side	Way Yes	18000	
Abrasive belt (1 No) for RH side			
Serrated rubber wheel (for belt) : 1 No			
	HONE NOS.:  Description for BHEL Requirement TYPE:Multi-purpose combination type i.e., where both wheel grinding & belt grinding jobs can be ground  Abrasive belt assembly on RH side & Grinding wheel on LH side Motor rating: 2 HP (Minimum)  Shaft speed: Specify Center height: 900 to 950 mm  Grinding wheel size: \$\phi 250 \text{ mm} \text{ x 250 mm}  Abrasive belt size: 50 mm x 2000 mm	ADDRESS:  Description for BHEL Requirement  TYPE:Multi-purpose combination type i.e., where both wheel grinding & belt grinding jobs can be ground  Abrasive belt assembly on RH side & Grinding wheel on LH side  Motor rating: 2 HP (Minimum)  Shaft speed: Specify  Center height: 900 to 950 mm  Grinding wheel size: \$\phi 250 \text{ mm} \times 25 \text{ mm}  Abrasive belt size: 50 mm \times 2000 mm  Serrated rubber wheel (for belt): \$\phi 250 \times 50 \text{ mm}\$  Standard Accessories:  Grinding wheels (1 No coarse & 1 No fine) for LH side  Abrasive belt (1 No) for RH side	ADDRESS:  Description for BHEL Requirement  TYPE:Multi-purpose combination type i.e., where both wheel grinding & belt grinding jobs can be ground  Abrasive belt assembly on RH side & Grinding wheel on LH side  Motor rating: 2 HP (Minimum)  Shaft speed: Specify  Center height: 900 to 950 mm  Grinding wheel size: \$\phi_250 \text{ mm} \times 250 mm \times 250 mm  Abrasive belt size: 50 mm x 2000 mm  Serrated rubber wheel (for belt): \$\phi_250 \times 50 mm  Standard Accessories:  Grinding wheels (1 No coarse & 1 No fine) for LH side  Abrasive belt (1 No) for RH side

Sl. No.	Description for Bi Requirement	Offered	Deviations	Remarks
2.4	Adjustable tool rest on both sides	3		
2.5	Wheel guard & belt guard if applicable		Date	
2.6	Eye shield			
2.7	D.O.L Starter			
2.8	A small container for holding water to be provided adjacent to the grinding wheel head for cooling the tools during grinding operation	(sq rvpp reco		
3.0	Electricals 415 V /3 phase / 50 Hz A/C power supply.			
4.0	Ambient conditions: 10°C To 45 deg.C and 95% RH			
5.0	Spares: Mechanical, Electrical & Electronic spares package for 2 years trouble free operation. In addition 2 Nos of Eye shields and 2 Nos of work rests shall be quoted.		H-Street	Banaga
6.0	Warranty : 12 Months from the date of Commissioning.		11	
7.0	Documentation: 3 sets of Operation & Maintenance manuals in english to be supplied along with the equipment.			



Hyderabad - 502 032. INDIA. Phones: 23182581 / 23182052

Enquiry No.:	
Due Date :	
Supplier Qtn. No.:	
Date :	

## SPECIFICATION FOR PEDESTAL GRINDER WITH COOLANT TANK QUANTITY: 7 Nos (2)

ADDRE	SS OF THE SUPPLIER:	+:		86
TELEPI	HONE NOS.:		74	
FAX NO	OS.:			
E-MAIL	ADDRESS:			
Sl. No.	Description for BHEL Requirement	Offered	Deviations	Remarks
1.0	TYPE:Double ended wheel type i.e., coarse wheel on one side & fine wheel on other side			
1.1	Coarse wheel on RH side & Medium wheel on LH side		L. M.	
1.2	Motor rating: 2 HP (Minimum)			
1.3	Shaft speed : Specify			
1.4	Center height: 900 to 950 mm			
1.5	Grinding wheel size: φ 300 x 40 mm			
1.6	Wheel center distance : Specify			
2.0	Standard Accessories:			
2.1	Grinding wheels (1 No coarse & 1 No Medium)			
2.2	Adjustable tool rest on both sides			
2.3	Wheel guard & belt guard if applicable			
2.4	Eye shield			
2.5	LK/LT Starter			

l. No.	Description for Blan Requirement	Offered	Deviations	Remarks
2.6	Coolant pump, Coolant tray, Coolant tank & Coolant fittings [Coolant tank to be external to the machine]			
3.0	Electricals 415 V /3 phase / 50 Hz A/C power supply.			
4.0	Spares: Mechanical, Electrical & Electronic spares package for 2 years trouble free operation. In addition 2 Nos of eye shields & 2 Nos of work rests shall be quoted as spares			
5.0	Warranty : 12 Months from the date of Commissioning.			
6.0	Documentation: 3 sets of Operation & Maintenance manuals in english to be supplied along with the equipment.			



BHARAT HEAVY ELECTRICALS LIMITED
Heavy Power Equipment Plant Demock

Hyderabad - 502 032. INDIA. Phones: 23182581 / 23182052

Enquiry No.	:
Due Date	:
Supplier Qtn. No	.:
Date	:

## SPECIFICATION FOR PEDESTAL GRINDER WITHOUT COOLANT TANK **QUANTITY: 8 Nos**

ADDRE	SS OF THE SUPPLIER:			
TELEPI	HONE NOS.:			
FAX NO	PS.:			
E-MAIL	ADDRESS:			
Sl. No.	Description for BHEL Requirement	Offered	Deviations	Remarks
1.0	TYPE:Double ended wheel type i.e., coarse wheel on one side & fine wheel on other side			
1.1	Coarse wheel on RH side & Medium wheel on LH side			
1.2	Motor rating: 2 HP (Minimum)			
1.3	Shaft speed : Specify			
1.4	Center height: 900 to 950 mm			
1.5	Grinding wheel size: φ 300 x 40 mm			
1.6	Wheel center distance : Specify			
2.0	Standard Accessories:			
2.1	Grinding wheels (1 No coarse & 1 No Medium)			
2.2	Adjustable tool rest on both sides			
2.3	Wheel guard & belt guard if applicable			
2.4	Eye shield	4		
2.5	LK/LT Starter			

Sl. No.	Description for BHEC Requirement	Offered	Deviations	Remarks
2.6	A small container for holding water to be provided adjacent to the grinding wheel head for cooling the tools during grinding operation			
3.0	Electricals 415 V /3 phase / 50 Hz A/C power supply.			
4.0	Spares: Mechanical, Electrical & Electronic spares package for 2 years trouble free operation. In addition 2 Nos of eye shields & 2 Nos of work rests shall be quoted as spares			
	Marranty , 12 Months from the date of			
5.0	Warranty : 12 Months from the date of Commissioning.			