

**Note: This PQC is for Item no. 40, 50 & 60**

Sl. No.	Pre –Qualification Criteria	Bidder remarks
1	<p>Bidder shall be a manufacturer of Welding Consumables / an authorized dealer of Welding Consumables.</p> <p>* If the offer is quoted by agent, letter of authorization and agreement duly signed by the manufacturer is required to consider the offer.</p>	Manufacturer / Agent *
2	<p>If the Bidder is Category-1 approved vendor of NTPL, Tuticorin then the Bidder need not submit this document, else below documents to be submitted.</p> <p>a. The Firm should have executed orders for the supply of electrodes (ENiCrMo-4) for an order value not less than Rs. 3 lakhs in a calendar year for any or all sizes of the subject elect rode (ENiCrMo-4) within last three (3) years as on the Original schedule date of tender opening.</p> <p>b. Original Tender opening date may be read as 07.05.2019.</p>	
3	<p>Quoted Welding Consumables brand name and its catalogue shall be provided along with offer</p>	
4	<p>Manufacturing plant address shall be provided along with offer.</p>	
5	<p>Suppliers shall submit manufacturing process flow chart (Raw material to finished product ) along with offer.</p>	
6	<p>Suppliers shall submit a valid ISO 9001 certificate or Quality management system certificate or Writ ten down procedure.</p>	

7	Shall confirm to WCPI 261/ 00	
8	Guarantee Certificate to be provide along with the supply mentioning the Purchase order no., Purchase order date and batch wise quantity against each batch no.	

Signature and Seal



**WELDING CONSUMABLE PURCHASE INSTRUCTION FOR**  
**SMAW ELECTRODE ENiCrMo-4**

**1.0 GENERAL:**

- 1.1 The electrodes shall comply with requirements specified in the Latest Edition and Addenda (Applicable on the date of Issue of Purchase Order) of ASME Sec.II.C.SFA-5.11, ENiCrMo-4. All tests, acceptance criteria shall be in accordance with this. Additional requirements specified in this document shall also be complied.
- 1.2 The Electrodes shall be supplied in sizes and quantities as specified in the purchase order.
- 1.3 The electrodes are intended for use in radiographic quality butt welded joints in Hastealloy (UNS-N10276) plates & Pipes. The electrode shall be suitable for joining dissimilar materials such as Hastealloy to Steel.
- 1.4 Every batch of electrodes shall be inspected & test certificates countersigned by Inspecting authority approved.
- 1.5 The electrode shall be of Non-Synthetic type with an alloyed core wire that nearly matches with weld metal chemistry.

**2.0 Chemical Composition:**

The chemical composition of the undiluted weld metal shall confirm to ASME SECII.C SFA-5.11, ENiCrMo-4.

**3.0 MECHANICAL PROPERTIES:**

The tension test and bend test shall meet the requirements of ASME SECII.C SFA-5.11 ENiCrMo-4.

**4.0 RADIOGRAPHIC SOUNDNESS:**

The radiographic test shall meet the requirements of ASME SECII.C SFA-5.11 ENiCrMo-4.

**5.0 SIZE:**

The electrodes shall be supplied in diameters and lengths as specified in the purchase order. The tolerance on diameter and length shall be as per clause 3.1 of SFA-5.02.

Prepared:

  
Jijo Johnson  
Manager / WTC

Reviewed & Approved:

  
R Arivazhagan  
Sr Manager /WTC



**6.0 CORE WIRE & COVERING:**

The electrodes shall meet the requirements of clause 3.2 of SFA-5.02.

**7.0 EXPOSED CORE:**

The electrodes shall meet the requirements of clause 3.3 of SFA-5.02.

**8.0 IDENTIFICATION:**

All electrodes shall be identified as per of clause 3.4 of SFA-5.02.

**9.0 PACKAGING:**

9.1 Electrodes in standard quantity shall be wrapped tightly in a corrugated paper and then packed in moisture proof polythene bags and sealed. These shall be further packed either in hermetically sealed containers or in cardboard packets and then packed in polythene bags and sealed. The number of electrodes per packet shall be such that the net weight of each packet does not exceed 5Kg. Packets shall be further packed in cardboard cartons each weighing not more than 25kg. The Cartons shall be packed in waterproof boxes with crates so as to ensure no damage during shipment and normal storage conditions.

9.2 Weight of each crate shall not exceed 1000kg.

9.3 Markings of packages shall be as per clause 3.6 of SFA-5.02.

**10.0 TESTING & CERTIFICATION:**

10.1 Each consignment of electrodes supplied shall be from one batch only.

10.2 Batch /Lot classification shall be Class C1 as per SFA-5.01 Filler metal procurement guidelines of ASME Sec.II.C. (Latest Edition and Addenda)

10.3 The Level of Testing shall be Schedule J as per SFA-5.01 Filler metal procurement guidelines of ASME Sec.II.C. (Latest Edition and Addenda)


10.4 Three copies of Original Test certificates in English countersigned by Inspecting Authority in compliance with this Purchase Instruction and ASME Sec.II.C, SFA-5.11, ENiCrMo-4 shall be sent.

10.5 The Testing Authority shall certify that supplies made against the batch conform to the requirements of the Latest Edition & Addenda (Applicable on the date of issue of Purchase Order) of ASME Sec.II.C.SFA-5.11, ENiCrMo-4.

Prepared:

  
Jijo Johnson  
Manager / WTC

Reviewed and Accepted:

  
R Arivazhagan  
Sr Manager / WTC