

BHARAT HEAVY ELECTRICALS LIMITED
RAMACHANDRAPURAM, HYDERABAD-32
Township Administration Department

SCHEDULE- A

Tender Notice No:
HY/TA/OT-27/2022-23, Dt.14.02.2023

PRICE BID

Name of work:- Annual Maintenance of Road Repair works in Township Area - Rate Contract"

SL.NO	Description	Qty	Unit	Rate	Amount
	Misc civil works				
1	Preparation and consolidation of sub grade with power road roller of 8 to 12 tonnes capacity after excavating earth to an average of 22.5cm depth dressing to camber and consolidating with road roller including making good the undulations etc. and re-rolling the sub grade and disposal of surface earth lead upto 50mtr	1000	Sq.m	117.5625	117562.5
2	Extra for compaction of earth work in embankment under optimum moisture conditions to give at least 95% of the maximum dry density (proctor density)	1	cum	13.65	13.65
3	Supplying and stacking at site				
a	90mm to 45mm size stone aggregate	20	Cu.m	1380.0375	27600.75
b	63mm to 45mm size stone aggregate	100	Cu.m	1151.7375	115173.75
c	53mm to 22.4mm size stone aggregate	100	Cu.m	1312.3125	131231.25
d	Good earth	75	Cu.m	362.925	27219.375
e	moorum	200	Cu.m	624.45	124890
4	Laying spreading and compacting stone aggregate of specified sizes to WBM specifications including spreading in uniform thickness hand picking rolling with 3 wheeled road/ vibratory roller 8-10 tonnes in stages to proper grade and camber applying and brooming requisite type of screening / binding material to fill up interstices of coarse aggregate watering and compacting to the required density.	250	Cu.m	575.4375	143859.375
5	Scarifying metalled (water bound) road surface including disposal of rubbish lead upto 50m and consolidation of the aggregate received from scarifying with power road roller of 8 to 10 tonnes capacity	2	Sq.m	18.4125	36.825
6	Dry stone pitching 22.5cm thick including supply of stones and preparing surface completes	3	Sq.m	547.65	1642.95
7	Cutting road and making good the same including supply of extra quantities of material ie aggregate moorum screening red bajri and labour required			0	0
a	Water bound macadam	1	Cu.m	1706.9625	1706.9625
8	Engraving letters in hard Granite stone	120	per cm ht per letter	6.15	738

9	Providing and fixing precast reinforced cement concrete 1:1.5:3(1cement 1.5 coarse sand 3 graded stone aggregate 20mm nominal size) kilometres stones as per standard design including finishing smooth in 1:3 cement mortar (1cement fine sand) but excluding the cost of earth work concrete in foundation painting and lettering etc. which shall be paid for separately			0	0
a	50x152.5x25cm size	1	Each	3158.4375	3158.4375
10	Cement concrete 1:2:4(1cement 2 coarse sand 4 grade stone aggregate 40mm nominal size) in pavements laid to required slope and camber in panels as required including consolidation finishing and tamping complete	1	Cu.m	5130.6375	5130.6375
13	Painting runway/ taxi track/ apron marking with adequate no of coats to give uniform finish with road marking paint of superior make as approved by the engineer in charge i/c cleaning the surface of all dirt scales oil grease and other foreign material etc., and lining out complete			0	0
a	New work (two or more coats)	1	Sq.m	113.1375	113.1375
b	Old work(one or more coats)	1	Sq.m	72.3	72.3
14	Painting road surface marking with adequate no of coats to give uniform finish with ready mixed road marking paint conforming to IS 164 on bitumious surface in white / yellow/black shade including cleaning the surface of all dirt scales oil grease and foreign material etc. complete			0	0
a	New work (two or more coats)	2	Sq.m	161.9625	323.925
b	Old work(one or more coats)	2	Sq.m	106.275	212.55
15	making bell mouth opening/ entrance of size 100x50x50cm for drainage pipe under footpath including providing cement concrete 1:3:6(1cement 3 coarse sand 6 grade stone aggregate 20mm nominal size) for shape of bell mouth including plastering providing and fixing precast RCC/SFRC slab including plastering with cement mortar 1:3(1 cement 3 fine sand) of 6 mm thickness on exposed surface of the slab and bell mouth including centring shuttering and neat cement punnig inside the bell mouth etc. all complete.	1	Each	1861.2	1861.2

16	<p>Providing and fixing glow studs of size 100x20mm made of heavy duty body shall be moulded ASA (acrylic styrene acryloretrite) or HIP (high impact polystyrene) or ABC having electronically welded micro prismatic lens with abrasion resistant coating as approved by engineer in charge. the cats eye shall support a load of 13635kg tested in accordance with ASTM D 4280. the slope of retro- reflective surface shall be 35 +/-5 degress to base. the reflective panels on both sides with at least 12cm of reflective area up each side. the luminance intensity should be as per the specification and shall be tested as described in ASTM I:809 as recommended in BS 873 part 4 :1973. the studs shall be fixed to the road surface using the adhesive conforming to IS as per procedure recommended by the manufacturer complete and as per direction of engineer in charge</p>	1	Each	234	234
17	<p>Providing and fixing concertina coil fencing with required dia 610mm(having 15nos round per 6metre length) up to 3m height of wall with existing angle iron Y shape placed 2.4m or 3.00m apart and with 9 horizontal RBT stud tied with GI staples and GI clips to retain horizontal including necessary bolts or GI clips to retain horizontal including necessary bolts or GI barbed wire tied to angle iron all complete as per direction of engineer in charge with reinforced barbed tape(RBT) / spring core (2.5mm thick) wire of high tensile strength of 165kg/ sqmm with tape (0.52mm thick) and weight 43.478gm / metre (cost of MS angle CC blocks shall be paid separately)</p>	1	Mts	269.2	269.2
18	<p>Manufacturing supplying and fixing retro reflective sign boards made upof 2mm thick aluminium sheet, face to be fully covered with high intensityencapsulated type heat activated retro reflective sheeting conforming totype - IV of ASTM-D 4956-01 in blue and silver white or other colourcombination including subject matter, message (bi-lingual), symbols andborders etc. as per IRC ; 67:2001, pasted on substrate by an adhesivebacking which shall be activated by applying heat and pressureconforming to class -2 of ASTM-D-4956-01 and fixing the same withsuitable sized aluminium alloy rivets @ 20 cm c/c to back support frameof M.S. angle iron of size 25x25x3 mm along with theft resistantmeasures, mounted and fixed with 2 Nos. M.S. angles of size 35x35x5mm to a vertical post made up to M.S. Tee section ISMT 50x50x6 mmwelded with base plate of size 100x100x5 mm at the bottom end andincluding making holes in pipes, angles flats, providing & fixing M.S.message plate of required size steel work to be painted with two or morecoats of synthetic enamel paint of required</p>			0	0

a	Mandatory / Regulatory sign boards of 900mm diameter with part as length of 3750mm	1	Sq.m	4580.35	4580.35
b	cautionary / warning sign boards of equilateral triangular shape having each side of 900mm with support length of 3650mm	1	Sq.m	3400.3875	3400.3875
19	Manufacturing supplying and fixing retro reflective overhead signage boards made up of 2mm thick aluminium sheet face to be fully covered with high intensity and encapsulated lens type heat activated retro reflective sheeting conforming to type - III of ASTM-D-4956-01 as approved by Engineer-in-charge letters, borders etc. as per IRC : 67-2001 in silver white with blue colour back ground and with high intensity grade, pasted on substrate by pressure sensitive adhesive backing which shall be activated by applying pressure conforming to class II of ASTM-D-4956-01 and fixing the same to the plate of structural frame work by means of suitable sized aluminium alloys, rivets or bolts & nuts @ 300mm centre to centre all along the periphery as well as in two vertical rows along with theft resistant measures including the cost of painting with two or more coats of epoxy paint in grey colour on the back side of aluminium sheet including appropriate priming coat. The rate includes the cost of rounding off the corners, lowering down the structural frame work from the gantry, fixing and erecting the same in position all	1	Sq.m	4516.5	4516.5
20	Providing Retro-reflective regulatory sign board of size 900mm dia meter made out of 2mm thick aluminium sheet, face to be fully covered with high intensity encapsulated lens type retro -reflective sheeting as approved by Engineer-in-charge . Letter, symbols, borders etc. will be as per IRC - 67 with required colour scheme on the boards and with the high intensity grade A. The aluminium sheet to be riveted to M.S. frame of angle iron of size 40x40x4mm. The boards will be fixed to 1 No. 50x50mm square post made of M.S. angle 50x50x4mm, 4m long welded to the frame with adequate anti-theft arrangement .Sheet work to be painted with two or more coats of synthetic enamel paint over an under coat (primer) and back side of aluminium sheet to be painted with two or more coats of epoxy paint including appropriate priming coat complete in all respects as per direction of Engineer-in-charge.	1	Sq.m	5061.65	5061.65

21	Providing and applying 2.5mm thick road marking strips (retro reflective) of specified shade / colour using hot thermoplastic material by fully / semi automatic thermoplastic paint applicator machine fitted with profile shoe glass beads dispenser propane tank heater and profile shoe heater driven by experienced operator on road surface including cost of material labour T& P cleaning the road surface of all dirt seals oil grease and foreign material etc. complete as per direction of engineer in charge and accordance with applicable specification	1	Sq.m	505.8	505.8
22	providing and fixing post delineators (made of ABS body fitted with 2 nos 100mm dia) reflective and reflectors are mounted on MS pipe of 65mm dia dully power coated anti rust and theft steel not to be installed as per direction of engineer in charge	1	Each	562.55	562.55
23	providing and laying 60mm thick factory made cement concrete interlocking paver block of M-30 grade made by block making machine with strong vibratory compaction and of approved size and design / shape laid in required colour and pattern over and including 50mm thick compacted as per the direction of engineer in charge	1	Sq.m	644.5125	644.5125
24	Providing and laying at or near ground level factory made kerb stone of M-25 grade cement in position to the required line level and curvature jointed with cement mortar 1:3(1 cement 3 coarse sand) including making joints with or without grooves (thickness of joints expect at sharp curve shall not to more than 5mm) including making drainage opening wherever required complete etc. as per direction of engineer incharge(lenght of finished kerb edging shall be measured for payment) precast CC kerb stone shall be approved by engineer in charge	1	Cu.m	6282.1125	6282.1125
25	Supplying and stacking of hard stone (for stone pitching) 22.5cm thick at site	1	Cu.m	724.575	724.575
26	Dry stone pitching 22.5mm thick laid in courses and required profile with hammer dressed stones having no side less than 15cm with minimum depth of 20cm including preparing the beding surfaces ect, all complete(payment for stone to be made separately)	1	Sq.m	365.4375	365.4375
27	75mm thick back filling for pitching including supplying of required materials and consolidation etc. complete with			0	0
a	moorum	10	Sq.m	55.425	554.25
b	stone aggregate 20mm nominal size	10	Sq.m	121.6875	1216.875
c	Stone aggregate 40mm nominal size	10	Sq.m	118.6125	1186.125

28	Providing and laying CC pavement of mix M25 with ready mixed concrete from batching plant . The ready mixed concrete shall be laid and finished with screed board vibrator vacuum dewatering process and finally finished by floating brooming with wire brush etc. complete as per specification and directions of engineer in charge (the panel shuttering work shall be paid for separately)	1	Cu.m	6497.2875	6497.2875
29	Deduct for using of M20 grade concrete instead of M25 grade concrete in CC pavement	1	Cu.m	141.225	141.225
30	Scarifying the existing bitumen road surface to a depth of 50mm and disposal of scarified material within all lifts and lead upto 1000mtr (by mechanical means)	1	Sq.m	3.5625	3.5625
31	Providing and laying Bituminous Macadam using crushed stone aggregates of specified grading premixed with bituminous binder and filler,transporting the hot mix to work site by tippers,laying with paver finisher equiped with lectronic sensor to the required grade,level and alignment and rolling with smooth wheeled,vibratory and tandem rollers to achieve the desired compaction and density, as per specifications,complete and as per directions of Engineer in charge. 40/50 mm compacted thickness with bitumen of grade VG-30(60/70 grade)@ 5.5% (Percentage by weight of total mix) and lime filler @ 3% (percentage by weight of aggregate) prepared in batch type Hot mix plant of 100-120 TPH capacity.etc. complete all as directed by Engineer-in-charge.	50	Cu.m	9077.05	453852.5
32	2.5 cm premix carpet surfacing (hot mix plant) with 2.25 cum and 1.12 cum of granite stone chippings of 13.2 mm and 11.2 mm size respectively per 100 sqm. and 52 kgs and 56 kgs of Hot Bitumen per cum of stone chippings of 13.2 mm and 11.2 mm size respectively including a tack coat with hot straight run bitumen including consolidation with road roller of 6 to 9 tonne capacity etc. complete. (tack coat to be paid for separately),with paving asphalt grade VG-10(80/100 grade) heated and then mixed with solvent at the rate of 70 gms per kg of asphalt all as directed by Engineer-in-charge.	4200	Sq.m	164.75	691950
33	Providing and applying tack coat using bitumen emulsion (Rapid setting) conforming with IS 8887-1995, on W.B.M./W.M.M. surface @ 0.40 kg/sqm by using emulsion pressure distributor including preparing the road surface and cleaning with mechanical broom etc., complete all as directed by Engineer-in-charge.	5500	Sq.m	9.4	51700

34	Providing and applying tack coat using hot straight run bitumen of grade VG- 10(80/100 grade), including heating the bitumen , spraying the bitumen with mechanically operated spray unit fitted on bitumen boiler, cleaning and preparing the existing road surface as per specifications. On bituminous surface @0.50 kg/Sqm all as directed by Engineer-in-charge.	750	Sq.m	29	21750
35	Providing,laying,spreading and compacting graded stone aggregate (size range 53 mm to 0.075 mm) to wet mix macadam(WMM) specification including premixing the material with water at OMC in mechanical mix plant,carriage of mixed material by tipper to site,for all leads & lifts,laying in uniform layers with mechanical paver finisher in sub-base/base course on well prepared surface and compacting with vibratory roller of 8 to 10 tonne capacity to achieve the desired density,complete as per specifications and directions of Engineer in charge.	1	Cu.m	1981.05	1981.05
36	Taking out existing kerb stones of all types from footpath/central verge ,including removal of mortar etc,disposal of unserviceable material to the dumping ground ,for which payment shall be made separately and stacking of serviceable material within 50 metre lead and as per direction of Engineer in charge.	1	Rmt	21.0375	21.0375
37	laying at or near ground level old kerb stones of all types in position to the required line,level and curvature,jointing with cement mortar 1:3 (1 cement : 3 coarse aggregate) including making joints with or without grooves (thickness of joints,except at sharp curve,shall not be more than 5 mm) including making drainage opening eherever required etc complete as per direction of Engineer in charge.(Length of finished kerb edging shall be measured for payment).(Old kerb stone shall be supplied by the department free of cost)	1	Rmt	62.2125	62.2125
39	Providing and laying premix bituminous macadam base course with stone aggregate of quality size and grading as specified in CPWD specification and straight run bitumen of grade 80/100 @ 4% by weight of total mix including hot mixing of stone aggregate and bitumen in hot mix plant, transporting mixed material and laying mixed material with paver finisher to the required level and grade, rolling with road roller of 8 to 10 tonne capacity to achieve the required compaction and densit of any thickness etc complete all as directed by Engineer-in-charge.	1	Cu.m	9482.59092	9482.59092

40	Providing and laying seal coat over prepared surface of road with bitumen heated in bitumen boiler fitted with the spray set spraying using 98 kg of bitumen of grade 80/100 and blinding surface with 0.90 cm of stone aggregate of 6.7 mm size (Passing 11.2 mm sieve and retained on 2.36 mm sieve per 100 sqm of road surface including rolling and finishing with power road roller etc complete, all as directed by Engineer-in-charge.	1	Sq.m	65.23748	65.23748
41	Supply and fixing of kerb stones of size 1.00 M x 0.15 m x 0.30 m twice dressed exposed faces and pointing with CM 1:3 including necessary excavation and refilling the gaps etc., complete all as directed by Engineer-in-charge.	1	Rmt	597.35258	597.35258
42	supply of JCB	50	Hrs	1059.0736	52953.68
43	Conveyance by Manual or Mechanical means of Lime, Murram, building Rubbish including loading un-loading with lift of 50 m upto lead mentioned below all complete all as directed by Engineer in charge			0	0
a	1 Km	10	Cu.m	78.705	787.05
b	2 Km	10	Cu.m	89.655	896.55
c	3 Km	10	Cu.m	100.5	1005
44	Providing radium sticker letters and arrow marks of approved colour and design and size. The base board will be supplied by the department and as directed by the Engineer-in-charge.	3	Sq.m	2688.65124	8065.95372
45	Painting with synthetic enamel paint of approved brand and manufacture to give an even shade (Iron work/Plastered surface/Signboards frames/wood work/Road speed breakers etc.)Two or more coats on new work	1400	Sq.m	91.1625	127627.5
46	providing and laying 60mm thick factory made cement concrete interlocking paver block of M-30 grade made by block making machine with strong vibratory compaction and of approved size and design / shape laid in required colour and pattern over and including 50mm thick compacted as per the direction of engineer in charge	10	Sq.m	644.5125	6445.125
47	Providing and laying in position specified grade of reinforced cement concrete excluding the cost of centering shuttering finishing and reinforcement All work up to plinth level			0	0
a	1:1.5:3(1cement 1.5 coarse sand 3 grade stone aggregate 20mm nominal size)	5	Cu.m	5788.6875	28943.4375
b	1:2:4(1cement 2 coarse sand 4 grade stone aggregate 20mm nominal size)	5	Cu.m	5472.2625	27361.3125
48	Reinforcement for RCC work including straightening, cutting bending placing in position and binding all complete.			0	0
a	Cold twisted bars	10	Kgs	62.625	626.25
b	Hot rolled deformed bars	4	Kgs	62.625	250.5
Total (Inclusive of taxes)(Rs)					2225718.31

Tender % on A		
	In Words	In Figures
Excess		
Less		
Estimate		
*	The bidders are required to quote the tender value on percentage (%) basis at excess or less or on par with estimated value in figures and words. Bidders are requested to fill only one row.	
1	Risk Purchase : In case the contractor fails to execute the work within the scheduled time or due to any other reasons, BHEL reserves the right to get the same completed through some other party at the risk & cost of the contractor and any additional expenditure incurred due to the same shall be charged to the contractor.	
2	All the materials are in the Contractor Scope Only .	
3	The rates are Including taxes.	
4	The contract period is Twelve (12) Month and maintenance period is Six(06) Months. The security deposit will be released after satisfactory completion of the work and after getting I.R clearance and payment of final bill.	
5	<p>Penalty terms:</p> <p>a) If the agency fails to commence the work within 15 days from the date of LOI, a penalty of 0.5% per week delay, subject to a maximum of 2% of the gross value of work will be applicable. if such delay extends beyond 4 weeks from the date of LOI, then BHEL reserves the right to take strict action without any prior notice.</p> <p>b) In the event of delay in supply of goods and or services beyond contractual delivery date, penalty of 0.5% per week or part there of shall be levied on the gross value of work done subject to a maximum of 10% of the gross value of the total work executed. Penalty amount so determined along with GST if applicable thereon shall be recovered</p>	
6	Taxes: Bidders shall quote their Basic price Inclusive of taxes.	
7	The tender % age quoted by the contractor shall be Inclusive of all taxes.	
8	IR Clearance is not required for the works less than Rs. 50,000/-.	
9	The agency has to pay the minimum wages to workers with statutory payments like ESI, PF etc., is as per BHEL notification and as per NIT. For USW= ₹ 565.65, SSW= ₹ 602.99, SW = ₹ 638.8 + ESI + PF + PPE's and other statutory if any increase in future DA is to be borne by the agency.	
10	The agency has to bring police clearance certificate for the work force.	
11	All the terms and conditions of the contract with respect to taxes & duties are subject to the new taxation laws introduced from time to time (e.g. GST). The terms and conditions will be modified in accordance with the provisions of new laws (e.g. GST).	
12	Payment shall be made stage wise on approval from engineer in charge	
13	Vendor shall raise GST invoice on BHEL Hyd GSTIN.	
14	If BHEL is unable to avail the input tax credit, the same amount shall be recovered from the vendor bills.	
15	Use of stone dust is not permitted in any civil works.	
	GST CLAUSES	
17	Following points to be complied with :	
18	In case GST credit is delayed/denied to BHEL due to non/delayed receipt of goods and/or tax invoice or expiry of timeline prescribed in GST law for availing such ITC, or any other reasons not attributable to BHEL, GST amount shall be recoverable from vendor along with interest levied/leviable on BHEL.	
19	In case vendor delays declaring such invoice in his return and GST credit availed by BHEL is denied or reversed subsequently as per GST law, GST amount paid by BHEL towards such ITC reversal as per GST law shall be recoverable from vendor/contractor along with interest levied / leviable on BHEL.	
20	The bidder shall arrange to send to BHEL, Hyderabad along with all the required documents as in Purchase Order, Tax Invoice (Original for Recipient) along with his bills.	
21	Vendor to ensure correct applicability of IGST/CGST/SGST/UTGST based on the Inter /Intra state movement Supply of goods and services or both.	
22	Taxes and duties prevalent on the contractual delivery date or the actual delivery date (in case of delay) whichever is lower shall be applicable paid. Composition Scheme to be addressed.	
23	Vendor shall note that the Invoice has to be raised quoting HSN Code of Goods or Accounting Code of Services or both wherever applicable.	
24	Invoice should mention BHEL-HPEP-HYDERABAD GSTIN: 36AAACB4146P1ZG or GSTIN of BHEL Nodal Agency as mentioned in PO.	
25	In case of any short supply of goods or service Vendor has to raise a credit note for short supplied quantity as per GST provisions	
26	Any GST liability arising on BHEL under reverse charge before actual receipt of goods and or services and/or invoice thereof would be subject to recovery of interest leviable for the period between the date of such liability and actual date of eligibility of ITC based on receipt of goods, receipt of invoices and other conditions specified in GST law, as applicable.	

27	Supplier shall mention their GST registration number in all their invoices and invoices shall be in the format as specified/prescribed under GST laws. Invoices shall necessarily contain Invoice number (in case of multiple numbering system is being followed for billing like SAP invoice no, commercial invoice no etc., then the Invoice No which is linked/uploaded in GSTN network shall be clearly indicated), item description as per PO, Quantity, Rate, Value, applicable taxes with nomenclature (like IGST, SGST, CGST & UTGST) separately, HSN/ SAC Code, etc.
28	A declaration to the effect that all tax liability as per GST rules and regulations shall be discharged.