

## SCHEDULE

S.No	TECHNICAL SPECIFICATION	QUANTITY ( NO)	VENDOR COMMENTS
01	<p><b><i>HIGH PRESSURE HYDRAULIC HOSE CONFORMING TO SAE100R2</i></b></p> <p>HOSE SIZE: <b>9.5 mm (3/8")</b>            HOSE LENGTH: <b>1600 mm</b>            FITTINGS: Straight Female End Swivel Fitting with 24 Degree Cone Ring to Suit            24 Degree Flare End On Both Ends of Size <b>M20x1.5</b> For Stand Pipe Dia of <b>12 mm.</b>  <b>Working Pressure: 280 Bar, Testing Pressure: 560 Bar.</b></p>	06	
02	<p><b><i>HIGH PRESSURE HYDRAULIC HOSE CONFORMING TO SAE100R2</i></b></p> <p>HOSE SIZE: <b>9.5 mm (3/8")</b>            HOSE LENGTH: <b>1700 mm</b>            FITTINGS: Straight Female End Swivel Fitting with 24 Degree Cone Ring to Suit            24 Degree Flare End On Both Ends of Size <b>M20x1.5</b> For Stand Pipe Dia of <b>12 mm.</b>  <b>Working Pressure: 280 Bar, Testing Pressure: 560 Bar.</b></p>	06	
03	<p><b><i>HIGH PRESSURE HYDRAULIC HOSE CONFORMING TO SAE100R2</i></b></p> <p>HOSE SIZE: <b>9.5 mm (3/8")</b>            HOSE LENGTH: <b>2500 mm</b>            FITTINGS: Straight Female End Swivel Fitting with 24 Degree Cone Ring to Suit            24 Degree Flare End On Both Ends of Size <b>M20x1.5</b> For Stand Pipe Dia of <b>12 mm.</b>  <b>Working Pressure: 280 Bar, Testing Pressure: 560 Bar.</b></p>	08	
04	<p><b><i>HIGH PRESSURE HYDRAULIC HOSE CONFORMING TO SAE100R2</i></b></p> <p>HOSE SIZE: <b>19 mm (3/4")</b>            HOSE LENGTH: <b>1600 mm</b>            FITTINGS: Straight Female End Swivel Fitting with 24 Degree Cone Ring to Suit            24 Degree Flare End On Both Ends of <b>M30x2</b> for Stand Pipe Dia of <b>20 mm.</b>  <b>Working Pressure: 157 Bar, Testing Pressure: 315 Bar.</b></p>	06	

S.No	TECHNICAL SPECIFICATION	QUANTITY ( NO)	VENDOR COMMENTS
05	<p><b><i>HIGH PRESSURE HYDRAULIC HOSE CONFORMING TO SAE100R2</i></b></p> <p>HOSE SIZE: <b>19 mm (3/4")</b>  HOSE LENGTH: <b>1700 mm</b>  FITTINGS: Straight Female End Swivel Fitting with 24 Degree Cone Ring to Suit  24 Degree Flare End On Both Ends of <b>M30x2</b> for Stand Pipe Dia of <b>20 mm</b>.  <b>Working Pressure: 157 Bar, Testing Pressure: 315 Bar.</b></p>	06	
06	<p><b><i>HIGH PRESSURE HYDRAULIC HOSE CONFORMING TO SAE100R2</i></b></p> <p>HOSE SIZE: <b>19 mm (3/4")</b>  HOSE LENGTH: <b>2500 mm</b>  FITTINGS: Straight Female End Swivel Fitting with 24 Degree Cone Ring to Suit  24 Degree Flare End On Both Ends of <b>M30x2</b> for Stand Pipe Dia of <b>20 mm</b>.  <b>Working Pressure: 157 Bar, Testing Pressure: 315 Bar.</b></p>	12	
07	<p><b><i>HIGH PRESSURE HYDRAULIC HOSE CONFORMING TO SAE100R2</i></b></p> <p>HOSE SIZE: <b>25 mm (1")</b>  LENGTH: <b>2500 mm</b>  FITTINGS: Straight female end swivel fitting with 24 deg. cone ring to suit with  24 Degree flare end on both ends of <b>M36x2</b> for stand pipe Dia <b>25 mm</b> on both sides.  <b>Working Pressure: 157 Bar, Testing Pressure: 315 Bar.</b></p>	06	
08	<p><b><i>HIGH PRESSURE HYDRAULIC HOSE CONFORMING TO SAE100R2</i></b></p> <p>HOSE SIZE: <b>25 mm (1")</b>  LENGTH: <b>2500 mm</b>  FITTINGS: Straight female end swivel fitting with 24 deg. cone ring to suit with  24 Degree flare end on both ends of size <b>M42x2</b> for stand pipe Dia <b>30 mm</b> on both sides.  <b>Working Pressure: 140 Bar, Testing Pressure: 280 Bar.</b></p>	06	