

DESCRIPTION

SPARES FOR HARD CHROME PLATING:

PP-FRP RECTANGULAR TANK WITH FLANGE ON TOP WITHOUT LID USING BISPHENOL /ISOPHTHALIC GRADE POLYESTER RESIN HAVING WALL THICKNESS OF 5 MM PP REINFORCED WITH 10MM THICK FRP OUTSIDE. IN FRP DIMENSIONS: - 880L X650W X1000H MM AS PER BS - 4994 - 1987.

THE ABOVE TANK SHALL BE SUITABLE REINFORCED WITH STRUCTURAL MATERIAL LIKE ANGLES AND CHANNELS FROM ALL THE SIDES INCLUDING BOTTOM AND ALL THE CORNERS INCLUDING FLANGE.

THIS REINFORCEMENT SHALL BE EMBEDDED WITH THE TANKS FROM OUTSIDE.

ADDITIONAL CONDITIONS

- 1) OPEN TENDER AND TWO PART BID SYSTEM SHALL BE FOLLOWED.
 - 2) INSPECTION AT BHEL
 - 3) ONE YEAR GUARANTEE IS REQUIRED
 - 4) DELIVERY WITHIN 6 TO 8 WEEKS FROM ISSUE OF PURCHASE ORDER
 - 5) THESE TANKS ARE REQUIRED FOR ENTIRE HARD CHROME PLATING FACILITIES.
-

PRE-QUALIFICATION CONDITION

1. VENDOR SHALL SUBMIT THE PROOF OF HAVING SUPPLIED THE SIMILAR TYPE OF PP-FRP TANKS. PROOF OF SUPPLY SUCH AS PO COPY, INVOICE, ETC. SHALL BE ENCLOSED.
2. TRADER SHALL SUBMIT THE AUTHORIZATION LETTER FROM THE ORIGINAL MANUFACTURER.
3. TEST/ GUARANTEE CERTIFICATES SHALL BE SUBMITTED ALONG WITH SUPPLY OF MATERIAL.