



CORPORATE PURCHASING SPECIFICATION

AA53303

Rev No.01

PAGE 1 of 3

REFRACTORY BRICKS - HIGH ALUMINA

1.0 GENERAL:

This specification governs the quality requirements of High Alumina Bricks for the roofs of Electric Arc Furnaces and for Lining of ladles in steel melting shop.

2.0 APPLICATION:

Used for making the roof of Electric Arc Furnaces and lining of ladles in steel melting shops.

3.0 CONDITION OF DELIVERY: As per IS: 1387

4.0 COMPLIANCE WITH NATIONAL STANDARDS:

There is no National Standard covering this type of material.

5.0 DIMENSIONS AND TOLERANCES:

5.1 Shape and Size: As per BHEL drawing.

5.2 Tolerances: $\pm 1.5\%$ or 1.5 mm whichever is greater.

6.0 FREEDOM FROM DEFECTS:

The refractories shall be free from cracks and broken corners and edges. They shall be of homogenous texture and shall have good surface finish.

7.0 TEST SAMPLE: As per IS: 1528

8.0 CHEMICAL COMPOSITION

The material, when analysed in accordance with IS: 1335, shall have the following composition.

Al_2O_3	70% minimum
Fe_2O_3	3% maximum

9.0 PROPERTIES:

The material, when tested as per the relevant parts of IS: 1528 shall show the following properties.

Revisions:

Clause No 25.03 of MOM of MRC - FN

APPROVED:

INTERPLANT MATERIAL RATIONALISATION
COMMITTEE - MRC(FN)

Rev No.01	Amd No.	Reaffirmed	Prepared	Issued	Dt. of 1 st Issue
Dt:19-03-2014	Dt:	Year:	CFFP, Haridwar	Corp.R&D	01-05-1994

CORPORATE PURCHASING SPECIFICATION



- | | | | |
|-----|---|---|--------------------------------|
| 9.1 | Pyrometric Cone Equivalent (PCE) (Part 1) | : | 37 Ortons minimum |
| 9.2 | Refractoriness Under Load (Part 2) | : | 1500 ta°C, minimum |
| 9.3 | Cold Crushing strength (Part 4) | : | 40 N/mm ² , minimum |
| 9.4 | Permanent Linear Change At 1600°C for 1 Hour (Part 6) | : | 3.5% maximum |
| 9.5 | Apparent Porosity (Part 8) | : | 23%, maximum |
| 9.6 | Bulk Density (Part 12) | : | 2.6 to 2.8 g/cc |
| 9.7 | Thermal Shock Resistance | : | 25 cycles minimum |

10.0 INSPECTION AT SUPPLIER'S WORKS:

- 10.1 BHEL reserves the right to witness the testing of the material at supplier works and therefore the supplier shall notify the readiness of the material in advance.
- 10.2 BHEL may also opt for third party inspection. If so, BHEL may either specify a third party or else give a list of third party inspection agencies, out of which supplier may select one of his choice.
- 10.3 The supplier shall offer BHEL's representative all reasonable facilities, without charge to satisfy the latter that the material is being furnished in accordance with this specification. The supplier shall prepare and provide necessary test specimens for testing to be carried out at his premises. If facilities are not available at his works, the supplier shall make necessary arrangements for carrying out the prescribed tests elsewhere.
- 10.4 BHEL may, at its discretion, test the material after receipt and acceptance of the material will be based on the BHEL's test results.
- 10.5 Supplier shall ensure that the material is free from extraneous material. The material shall be rejected if it is not free from extraneous material.
- 10.6 For result of analysis and properties of material the decision of BHEL shall be final and binding on the supplier.
- 10.7 If the material received is not found suitable according to the requirements, it shall be replaced free of cost by the supplier.
- 10.8 For any deviation, demanded by the supplier from the specification, prior approval of BHEL must be obtained.

11.0 TEST CERTIFICATES:

Unless and otherwise stated, one original and three copies of certificates from the original manufacturer shall be supplied along with each consignment.

In addition the supplier shall ensure to enclose one copy of test certificate along with the despatch documents to facilitate quick clearance of the material.

Manufacturer supplying material directly to BHEL should include BHEL PO No. in the Test Certificate. Any other supplier should provide a covering letter along with original manufacturer Test Certificate as above mentioning BHEL PO No.

The test certificates shall bear the followings information:

AA53303: REFRACTORY BRICKS - HIGH ALUMINA

BHEL Order No.

Manufacturer's/ Supplier's Name.



CORPORATE PURCHASING SPECIFICATION

AA53303

Rev No.01

PAGE 3 of 3

Batch/ Lot No.

Quantity Supplied.

Date of manufacture

Dimensional inspection as per clause 5.

Test Results of clauses 8 and 9.

12.0 PACKING AND MARKING:

The material shall be suitably packed to avoid damage during transit. Each consignment shall be legibly marked or labelled with the following information.

AA53303: REFRACTORY BRICKS - HIGH ALUMINA

BHEL Order No.

Manufacturer's/ Supplier's Name.

Trade mark, if any.

Batch/ Lot No.

Sizes and Quantity supplied

Date of manufacture

13.0 REJECTION AND REPLACEMENT

If the material does not comply with the requirements of this specification during receipt inspection at BHEL or if any defect is found during further processing of the material, BHEL reserves the right to reject the whole consignment notwithstanding any previous certification of satisfactory testing and/or inspection. The supplier shall undertake to replace the rejected material at his own cost and the rejected material shall be taken back by the supplier after fulfilling all the commercial terms and conditions.

14.0 Referred Standards (Latest publications including amendments):

1) IS: 1387

2) IS: 1528

3) IS: 1335



ISO 9001:2008, 14001:2004,
50001:2011 & OHSAS 18000
MAHARATNA COMPANY

MATERIAL MANAGEMENT (PURCHASE)
CENTRAL FOUNDRY FORGE PLANT, BHEL HARDWAR
RANIPUR, HARIDWAR (INDIA) – 249403
Phone No.+91-1334-281360/285524, FAX No. 225892
e-mail :rajesh.kur@bhel.in; skkwat@bhel.in

PREQUALIFICATION CRITERIA:

- 1) The participated vendor must have **supplied** High Alumina Bricks with min. 70% Alumina content and Minimum Quantity as per following Table **(Table 1)** in one financial year within a period from date 01.04.2015 to the date of opening tender.

Table 1:

S.No.	Item	Minimum Quantity Required to be supplied in one FY within 01.04.2015 to date of Tender Opening
1.	Roof Set Bricks Model 11	Minimum 1800 Nos. of High Alumina Bricks with min. 70% Alumina content.

- 2) As a supporting document to Point (1) following has to be provided:
- a) **Proof of Order**: Copy of Purchase Orders/Purchase Agreement etc.
 - b) **Proof of Supply**: Copy of Invoice/BL Copy/ any other document to confirm supply of material against above Purchase Order.
 - c) **Proof of Quality**: Copy of Test Certificate/Specification etc (Required if, Alumina content is not mentioned on Purchase Order/Invoice copy etc).

Details to be provided in the following table:

Customer Name & address	Customer PO No.	Quantity supplied	Contact person name of customer, Address, Email, Phone No. etc.