

<div data-bbox="198 256 363 390"> </div> <div data-bbox="224 394 341 422">365 - 148</div>	<div data-bbox="461 260 930 357"> <b>PRODUCT ENGINEERING / V&amp;SB</b>  <b>PURCHASE SPECIFICATION FOR</b>  <b>CABLE GLANDS</b> </div>	<div data-bbox="989 281 1172 308">SPEC:SB:0012</div> <div data-bbox="989 342 1172 369">PAGE 01 OF 01</div>	<div data-bbox="1286 281 1380 308">REV:02</div> <div data-bbox="1286 342 1380 369">27.08.11</div>											
<div data-bbox="172 464 1053 491">1.0 Component : Double compression cable glands</div> <div data-bbox="172 529 623 556">2.0 :</div> <table border="1" data-bbox="157 571 1461 911"> <thead> <tr> <th>Type</th> <th>Material codes</th> <th>Material</th> <th>Size</th> </tr> </thead> <tbody> <tr> <td>(i)</td> <td>963535180000</td> <td rowspan="2">Brass body nickel plated</td> <td>Suitable for 3C X 2.5 mm<sup>2</sup> armoured Cable of OD 14.5 mm with nipple entry Size of M20 x 1.5. Ferrule suitable for armoured wire diameter 0.8mm.</td> </tr> <tr> <td>(ii)</td> <td>963535180100</td> <td>Suitable for 3C X 6 mm<sup>2</sup> armoured Cable of OD 20 mm with nipple entry Size of M20 x 1.5. Ferrule suitable for armoured wire diameter 0.8mm.</td> </tr> </tbody> </table> <div data-bbox="172 949 857 976">3.0 Area classification : Non flame proof</div> <div data-bbox="172 1014 932 1079">4.0 Document required for acceptance : Compliance certificate.</div> <div data-bbox="172 1117 1146 1144">5.0 Packing : Suitably packed to avoid thread damages.</div> <div data-bbox="172 1182 954 1278">6.0 Critical check list : 1. Compliance certificate 2. Thread size 3. Cable entry size</div>				Type	Material codes	Material	Size	(i)	963535180000	Brass body nickel plated	Suitable for 3C X 2.5 mm <sup>2</sup> armoured Cable of OD 14.5 mm with nipple entry Size of M20 x 1.5. Ferrule suitable for armoured wire diameter 0.8mm.	(ii)	963535180100	Suitable for 3C X 6 mm <sup>2</sup> armoured Cable of OD 20 mm with nipple entry Size of M20 x 1.5. Ferrule suitable for armoured wire diameter 0.8mm.
Type	Material codes	Material	Size											
(i)	963535180000	Brass body nickel plated	Suitable for 3C X 2.5 mm <sup>2</sup> armoured Cable of OD 14.5 mm with nipple entry Size of M20 x 1.5. Ferrule suitable for armoured wire diameter 0.8mm.											
(ii)	963535180100		Suitable for 3C X 6 mm <sup>2</sup> armoured Cable of OD 20 mm with nipple entry Size of M20 x 1.5. Ferrule suitable for armoured wire diameter 0.8mm.											
REV. 02		Material Code 963531580100 included on 27.08.11												
PREPARED (J. SANKAR)	CHECKED (RAVINDER SINGH)	APPROVED (K. SRIDHARAN)												