

FIRST ANGLE PROJECTION

(ALL DIMENSIONS ARE IN MM)

REV.			DATE			ALTERED			REV.			DATE			ALTERED			REV.			DATE			ALTERED											
CHECKED						CHECKED			CHECKED						CHECKED			CHECKED						CHECKED											
APPROVED						APPROVED			APPROVED						APPROVED			APPROVED						APPROVED											
<p>1. Copper Braid Type: 40/25 Cross Section : 250 mm²</p> <p>2. Insulating Sleeve Type: 25/50 Material: Glass Silk Braided Hose / Silicone Rubber. Working Temp. : -70 To 200° C Nominal Voltage : 2.5 Kv Breaking Voltage : 7.5 Kv Colour : Black</p> <p>3. Cable Tie with Metal Barb Material: Polyamide Dimensions : 140 x 3.6 mm</p> <p>Note: Finish :- Connection Surface Electro Tin Plated to 15 microns.</p>																																			
QTY.		ITEM NO.		DESCRIPTION										DRAWING No.										ITEM		MATERIAL CODE						A		UNIT Wt. (Kgs.)	
																								VAR.		MATERIAL SPECN.						C		QTY.	
SIGN & DATE				BHARAT HEAVY ELECTRICALS LIMITED. ELECTRONICS DIVISION, BANGALORE										DRN		NAME						SIGN.		DATE		No. OF VAR									
														CKD		T K Murthy								28.11.19											
														APPD		Krishna VVNSSRM								29.11.19											
																Shekar R								29.11.19											
INVENTORY NO.		DEPT. TE		FOR UNSPECIFIED TOLERANCES										SCALE		WEIGHT (Kg)		REF. TO ASSY. DRG.						ITEM NO.		No. OF ITEM									
		CODE 445		REFER ED 0230499																															
TITLE		Copper Braided Insulated Cable - 250 mm Sq										DRAWING NO.										REV.													
												4 668 08 00793										00													
		SHEET NO. 01										NO. OF SHEETS 01																							

A4 SIZE