

FIRST ANGLE PROJECTION

(ALL DIMENSIONS ARE IN MM)

REV.			DATE			ALTERED			REV.			DATE			ALTERED			REV.			DATE			ALTERED											
CHECKED						CHECKED			CHECKED						CHECKED			CHECKED						CHECKED											
APPROVED						APPROVED			APPROVED						APPROVED			APPROVED						APPROVED											
<p>1. Copper Braid Type: 40/25 Cross Section : 250 mm²</p> <p>2. Insulating Sleeve Type: 25/50 Material: Glass Silk Braided Hose / Silicone Rubber. Working Temp. : -70 To 200° C Nominal Voltage : 2.5 Kv Breaking Voltage : 7.5 Kv Colour : Black</p> <p>3. Cable Tie with Metal Barb Material: Polyamide Dimensions : 140 x 3.6 mm</p> <p>Note: Finish :- Connection Surface Electro Tin Plated to 15 microns.</p>																																			
3EHP430699 R0002		REF. DRG. NO.		QTY.		ITEM NO.		DESCRIPTION								DRAWING No.								ITEM		MATERIAL CODE				A		UNIT Wt. (Kgs.)			
																								VAR.		MATERIAL SPECN.				C		QTY.			
SIGN & DATE				BHARAT HEAVY ELECTRICALS LIMITED.										ELECTRONICS DIVISION, BANGALORE										DRN		NAME				SIGN.		DATE		No. OF VAR	
																								CKD		Krishna VVNSSRM						29.11.19			
																								APPD		Shekar R						29.11.19			
INVENTORY NO.		DEPT. TE		FOR UNSPECIFIED TOLERANCES								SCALE		WEIGHT (Kg)		REF. TO ASSY. DRG.								ITEM NO.		No. OF ITEM									
CODE 445				REFER ED 0230499																															
TITLE														DRAWING NO.										REV.											
Copper Braided Insulated Cable - 250 mm Sq														4 668 08 00794										00											
SHEET NO. 01														NO. OF SHEETS 01																					

A4 SIZE