Singrauli MPH Structure Erection

VOLUME-IA TECHNICAL CONDITIONS OF CONTRACT (TCC)

Package-A: Erection, Alignment, Bolting/Welding, Roofing & Cladding, BOIs Work including handling of materials at BHEL / Client's Stores / Storage yard and Transportation and Scope of work includes supply of all Material (As per TCC and BOQ), Consumables, labour, tools and plants, Touch-up painting as and where required (including supply of paints) for Unit-1 Main Power House structure & BOIs as per BOQ at 2X800 MW NTPC Singrauli STPP Stage-III, Sonebhadra, UP

Package-B: Erection, Alignment, Bolting/Welding, Roofing & Cladding, BOIs Work including handling of materials at BHEL / Client's Stores / Storage yard and Transportation and Scope of work includes supply of all Material (As per TCC and BOQ), Consumables, labour, tools and plants, Touch-up painting as and where required (including supply of paints) for Unit-2 Main Power House structure, CCR (Common control room) and BOIs as per BOQ at 2X800 MW NTPC Singrauli STPP Stage-III, Sonebhadra, UP

BHARAT HEAVY ELECTRICALS LIMITED



TECHNICAL CONDITIONS OF CONTRACT (TCC) TABLE OF CONTENTS

Sl No	DESCRIPTION	Chapter
Volume-IA	Part-I: Contract specific details	
1	Project Information	Chapter-I
2	Scope of Works	Chapter-II
3	Facilities in the scope of Contractor/BHEL (Scope Matrix)	Chapter-III
4	T&Ps and MMEs to be deployed by Contractor	Chapter-IV
5	T&Ps and MMEs to be deployed by BHEL on sharing basis	Chapter-V
6	Time Schedule	Chapter-VI
7	Terms of Payment	Chapter-VII
8	Taxes & Duties	Chapter-VIII
9	Bill of Quantities (BOQ)	Chapter-IX
10	General	Chapter-X
11	Foundation & Grouting	Chapter-XI
12	Material Handling, Transportation and Site Storage	Chapter-XII
13	Erection	Chapter-XIII
14	Welding, Heat treatment & Radiography and Non-destructive testing	Chapter-XIV
15	Painting	Chapter-XV
16	Preservation & Protection of Components	Chapter-XVI
17	% Weightage of Individual Items	Chapter-XVII
18	Annexures	Chapter-XVIII

TECHNICAL CONDITIONS OF CONTRACT (TCC) Chapter - I: PROJECT INFORMATION

1.0 Project Information:

Sl. No.	Description	Details
1	Project Title	2X800MW Singrauli Super Thermal Power Project, Stage-III
2	Customer	National Thermal Power Corporation Limited (NTPC Limited)
	Location	Singrauli Super Thermal Power Station (Singrauli STPS) is located in Sonebhadra District of Uttar Pradesh. The Project is located at 118 Km towards South of District Head Quarters Robertsganj and is well connected by State Highway SH-5A. Nearest National Highway NH-39 is at a distance of about 5 Km from the Project.
3		Nearest major city is Renukoot, located at a distance of 60 Km to the project. The nearest Railway Station is Shaktinagar at 3 Km. The nearest major town is Robertsganj, which is approximately 118 Km from the project.
		The Sonebhadra District is bounded by the State of Chhattisgarh to the South, Madhya Pradesh to the West & Jharkhand to the East. The nearest airport is Lal Bahadur Shastri International Airport, Varanasi at a distance of about 220 Km from project site.
4	Nearest Airport	Nearest Commercial Airport is Lal Bahadur Shastri International Airport, Varanasi About 220 Km from Singrauli STPP.
5	Nearest Railway link	Nearest Railway Station is Shaktinagar Station which is About 3.0 Km from Singrauli STPP. Other Nearby Important Stations are Renukoot Junction About 60 Km, Mirzapur Station About 198 Km, Mughal Sarai Junction About 196 Km and Varanasi Cantt About 202 Km.
6	Access By Road/Major Cities	Nearest National Highway NH-39 is at a distance of about 5 Km from the Project.
J		Nearest major city is Renukoot, located at a distance of 60 Km to the project.
7	Temperature	Meteorological data from nearest observatory is placed as a Annexure-G (Attached)

TECHNICAL CONDITIONS OF CONTRACT (TCC) Chapter - I: PROJECT INFORMATION

8	Seismic Zone		As per Annexure of NTP VI, part-B (Annexure-G	C Technical Specifications, Section- attcahed).
9	Wind Speed		Meteorological data from Annexure-G (attached)	n nearest observatory is placed as a
2.0				
	INSTRUCTIONS	TO BIDI	DERS	
1.1	The Bidder shall visit project site and acquire full knowledge and information about conditions prevailing at site and in & around the plant premises, together with site conditions, transportation routes, various distances, all the statutory, obligatory, mandatory requirements of various authorities and all information that may be necessary for preparing the bid and entering into the Contract. All costs for and associated with site visits shall be borne by the bidder.			
1.2	Other contractors would be working in this area and their structures are to be protected. The material brought and stacked for construction should not make hindrance to other contractors.			
1.3	The information given herein is for general guidance and shall not be contractually binding on BHEL/Owner. All relevant site data /information as may be necessary shall have to be obtained /collected by the Bidder.			
1.4	The contractor, in the event of this work awarded to him, shall establish an office at site and keep posted an authorized, responsible officer with valid Power of Attorney Attorney for the purpose of the contract. Any order or instructions of the `Engineer' or his duly authorized representative, communicated to the contractor's representative at site office will be deemed to have been communicated to the contractor at his legal address.			
1.5	No claim will be entertained by BHEL on ground of lack of knowledge and the contractor's rates shall be deemed to have taken this into account.			
1.6	Bidders may fix	Bidders may fix up their site visit in consultation with below mentioned contact person:		
	Name:	Mr. Aja	y Singh	Mr. Amrendra Kumar Thakur
	Designation:	AGM		Manager
	Location:	2X800	Singrauli Project	PSNR Noida
	Email: ajaysingh@BHEL.in pmgakthakur@BHEL.i			
	Ph. No.	(+91) 9	650 590 899	(+91) 954 069 0700

2.0	Scope of Works:
2.1	Scope-Erection, Alignment, Bolting/Welding, Roofing & Cladding, BOIs Work of Main Power House (PH#1&2) and CCR (Common Control Room) Structure including handling of materials at BHEL / Client's Stores / Storage yard and Transportation and Scope of work includes supply of all Material (As per TCC and BOQ), Consumables, labour, tools and plants, Touch-up painting as and where required (including supply of paint) for Unit #1 & 2 at 2X800 MW NTPC Singrauli STPP Stage-III, Sonebhadra, UP
	Complete scope of work will be awarded to one agency. However, for ease of operation of the scope of work, in Technical conditions of contract (TCC), complete scope (tonnage) will be bi-furcated into two packages viz. package-A and package-B as following:
	1. Package-A: Complete scope for Erection of Main Power House Unit#1 structure & BOIs as per BOQ at 2X800 MW NTPC Singrauli stage-III Project.
	2. Package-B: Complete scope for Erection of CCR (Common control room) & Main Power House Unit#2 structure and BOIs as per BOQ at 2X800 MW NTPC Singrauli stage-III Project
	Note: Package A & B shall be treated as separate contract. For each item, item rate shall be derived. Payment shall be made on actual execution of work on item rate basis. In case of any dispute in scope of work between the packages, BHEL Site in-charge decision shall be final and binding to the agency.
	Before commencement of any work, the bidders have to check with Civil/Mechanical/Electrical drawings jointly with concerned BHEL Engineers.
2.2	The scope of works includes: - a. Bolted Type Structural steel works (i.e. Pre-Assembly, Erection, Grouting, Alignment, Bolting and touch-up painting (including supply of paints), other allied works of structural Building and Associates structure as mentioned in 2.2.1.
2.2.1	The scope of works covers Bolted Type Structural steel works (i.e. Pre-Assembly, Erection, Grouting, Alignment, Bolting and touch-up painting other allied works) of structural Building and Associates structure as mentioned below. Scope of work includes supply of all Material (As per TCC and BOQ), Consumables, labour, tools and plants. BHEL shall provide structural steel/pre-fabricated structures, BOIs like handrails, gratings, bolts, deck sheet, etc. as per TCC/BOQ for incorporation in the permanent works as free supply. The scope of supply shall be as mentioned in BOQ/Rate schedule. The scope of work is indicative but not limited to the given below.
	a. Erection of structure as per BOQ
	b. Supply & installation of items as per BOQ.

- c. Fixing/erection of BOI Items as mentioned in BOQ
- d. Erection of Miscellaneous Structure in buildings including Monorail, girder, platforms, etc.

List of Buildings for Structure Erection:

SI No	Name of Structural Building/System	Tentative Weight of Structures (In MT)	Remarks
1	Main Power House Unit 1	7291	Package A
2	CCR (Common control room) Building	3900	Package B
3	Main Power House Unit 2	7291	Package B
4	BOIs	2009	Package A & B
	Total	20,491	

Following BOIs will be supplied by BHEL Free of cost and fixing/erection shall be part of contractor scope as mentioned in BOO:

- a. Metal Deck sheet
- b. Side cladding
- c. Roof sheeting
- d. HSFG Bolts/Bolts
- e. Gratings
- f. Handrails

2.3

Note- 1. Above scope is tentative only and may vary

- 2. Site connections are bolted; however, welding connections also come in some areas fall under the scope of this tender (tentative 500 MT). Contractor shall do the welding within the quoted rate for completion of work.
- 3. Erection of TG/miscellaneous platform (BHEL free supply materials) in Power House or Control Room area may come which shall be executed by contractor (tentative 100 MT). Payment of such erection shall be paid as per item rate of structure erection.
- Field connections are Bolted and fabricated structure will be supplied by BHEL free of cost. Erection shall be part of scope of this tender.
 - The work to be carried out at quoted / accepted rates by the Contractor under the scope of these specifications covers the complete work of handling, loading and transporting of materials from project stores sheds / storage yards to site of erection or preassembly yard and unloading at pre-assembly area/erection site, checking, cleaning chipping and levelling of foundations, providing packers and shims/pre-assembling of equipment at the preassembly yard, inspection, minor rectification, preservation, erection, levelling, and

	other adjustments, cutting, edge / surface preparation, bolting, welding (if applicable), grinding, radiography, LPI/MPI/UT/PAUT/CRT testing wherever needed, heat treatment, including inter connection of all the termination points, and handing over of floors, roof etc., completion of structure erection for PH#1&2 and CCR, BOIs.
2.4	The work under this contract shall be carried out as per BOQ Cum Rate Schedule and in compliance of tender conditions including technical specifications and approved drawings/documents.
2.5	GENERAL
2.5.1	Providing all incidental items not shown or specified but reasonably implied or necessary for the successful completion of the work in accordance with contract.
2.5.2	The drawings enclosed with this tender are intended to give the tenderer a general idea of the type and extent of work involved. The drawings are as such only indicative and not to be considered as the exact construction drawings.
2.5.3	Further this is to be noted that the drawings and the documents furnished along with this specification are the sole property of BHEL. It must not be used directly or indirectly in any way detrimental to the interest of the company.
2.5.4	Scope of work includes furnishing all labor, materials, supervision, consumables, construction plans, equipment, supplies, transport, to and fro the site, fuel, compressed air, transit and storage insurance (for contractor T&Ps and items) and all other incidental items and temporary works not shown on specified but reasonably implied or necessary for the proper completion, maintenance and handing over the works in accordance with the stipulations laid down in the contract documents and additional stipulations, as may be provided by the engineer during the course of works, is in the scope of bidder at no extra cost to BHEL.
2.5.5	Void.
2.5.6	The area of work shall be maintained cleared of all vegetation, rubbish and other objectionable matter and materials by contractor. No separate payment for these operations shall be made for such works.
2.5.7	All the works areas shall be adequately illuminated to the satisfaction of the Engineer-in-Charge when the work is in progress.
2.5.8	Drawings showing enough details for the construction as per the specification shall be furnished to the contractor in a phased manner
2.5.9	All necessary arrangement for safety like Hard Barricading with scaffolding pipes and providing of safety net is in bidder's scope.
2.5.10	The Customer may depute their representative for checking and supervision of important stages of work. The contractor shall be required to provide all facilities for inspection of

	Note: Contractor shall augment manpower to meet the project schedule/ milestones. Deployment of manpower shall be progressive to meet the project schedule. Relevant experience is subject to decision of BHEL site in-charge.
2.6.1	Contractor shall deploy and maintain pool of sufficient experienced staff of Technical and administrative manpower for execution of work at site. Experienced manpower like Site In-charge, Project Manager, Engineers, Planning, Billing, Stores, Accounts, Quality, Safety, Operators, Helpers, security guards etc. as staff shall be deployed by contractor in sufficient numbers for execution of each package
2.6	Tentative Technical Staff Requirement for each package:
2.5.16	Any activity which is necessarily required for satisfactory execution of any item of BOQ in line with technical specifications shall be deemed to be included in BOQ item even if it is not described in the item description and no extra payment shall be made against such activity.
2.5.15	The complete works shall be carried out as per BOQ cum Rate schedule. If any work covered in the scope of contract cannot be executed using items available in BOQ, additional / extra items shall be made and rates for such items shall be worked out as per GCC clause 2.15.7. However, contractor shall be bound to execute all the works under the scope of the contract and decision whether an extra item is applicable or not, shall be taken by BHEL Engineer which will be binding on the contractor.
2.5.14	Medical/First aid center/medicine purchased for emergency/Doctor purpose along with ambulance services with fuel and operator (round the clock) shall be arranged by BHEL for handling medical emergencies. Cost against these facilities shall be distributed/shared among the vendors working in the Project site proportionately based on contract value. (Reference HSE plan for Singrauli project-Annexure C).
2.5.13	Arrangement for joint checking (with BHEL / BHEL's Customer / Consultant) of all site construction activities, Preparation of joint protocols for each & every activity and maintaining quality records for audit/inspection as per approved FQP by BHEL.
2.5.12	Carrying out establish levels and coordinates at suitable intervals from existing grid levels and coordinates furnished by the owner established bench marks, setting out the locations and levels of proposed structures, marking of reference pillars and other identification works etc. The contractor shall provide the owner/BHEL such an assistance, instruments, machines, labour and materials as are normally required for examining, measuring and testing any work and the quality, weight or quantity of any material used.
2.5.11	Giving all notices, paying all fees, taxes etc., in accordance with the general conditions of contract, that is required for all works including temporary works shall be in the scope of contractor.
	works at no extra cost to BHEL. Any defect in quality of work or deviations from drawings / specifications pointed out during such inspection shall be made good by the contractor in the same way as if pointed out by the BHEL Engineer, without any cost implication to BHEL.

	T
2.6.2	Deputation of man-power shall be jointly decided at site in line with construction Schedule.
2.6.3	Engineer/ supervisor for required for proper execution are to be provided as per site requirement
2.6.4	Contractor shall deploy experienced manpower for execution of the job. BHEL reserves the right to reject or approve the list of personnel proposed by the contractor. The persons whose bio-data have been approved by BHEL will have to be posted at site and deviation in this regard will not be permitted unless specific & reasonable justification is made.
2.6.5	N.A.
2.6.6	The contractor shall maintain a site organization of adequate strength in respect of manpower, construction machinery and other implements at all times for smooth execution of the contract. This organization shall be reinforced from time to time, as required to make up for slippage from the schedule without any commercial implication to BHEL. The site organization shall be headed by a competent construction manager having sufficient authority to take decisions at site.
2.7	Supervisors / Engineer and Computer for exclusive use of BHEL:
2.7.1	The Contractor shall depute supervisors / Engineers , acceptable to BHEL Site, with sufficient computer knowledge (knowledge of MS office) to whom works (Planning, Billing, reconciliation, documentation etc.) will be assigned in consultation and acceptance of BHEL for original contract and extended period.
2.7.2	Void
2.7.3	The bidder will have to provide One (01) No. of Laptops (X-86 Architecture Based, 64-Bit Supported, Microprocessor with minimum 8 cores, On-board Graphics feature compatible with supplied OS, Minimum 8 GB RAM 2666 MHZ SDRAM upgradeable to 16 GB, 512 GB SSD M.2 Hard Drive or higher, 13" - 14" (both included) high definition anti-glare LED back lit Screen, OEM USB Optical Travel Mouse, Integrated High definition audio with integrated speakers and volume control (Hardware/Software). Single audio jack (single pin) for connecting ear phones and mic, Built-In HD Webcam with Built-In Microphone, integrated 100/1000 Mbps port, Integrated Wi-Fi 6, supporting industry standard IEEE 802.11ax + Bluetooth 5.0 or higher, Minimum 2xUSB 3.1 Ports, 1xType C, Stereo headphone/microphone combo jack,1 x HDMI Port. 1 x RJ – 45, Minimum 3-cell battery capable of providing 6 hours or more backup in standard business environment, ACPI Compliant, OEM AC Adaptor suitable for 230V supply, Should come pre-installed with Windows 11 Professional Edition or latest version with 64bit latest service pack, OEM carry bag to be supplied with OS Certification from Microsoft and required software able to open/edit drawings & documents of BHEL like MS Office, AutoCAD, ADOBE PDF with one laser jet printer compatible for A4 and A3 size printing with power backup at places, as per instruction of BHEL, for original and extended contract period.
2.7.4	These laptops/ printers shall remain contractor's property/ownership for all legal/technical purposes. However, contractor will be allowed to take out the same after completion of the site works on obtaining permission from BHEL. The computer/printer

	shall remain at BHEL offices or at place decided by BHEL Engineer during the contract period/ extended period (if any).
2.7.5	This facility has to be provided as directed by BHEL till completion of site works or as decided by BHEL. If contractor fails to provide computer/ printer as per requirement, for a continuous period of fifteen days or more, BHEL shall have the right to purchase it on behalf of contractor and recover the expenses incurred from the dues payable to contractor. Recoveries shall be actual expenses incurred plus 5% overheads.
2.7.6	Void
2.8	Field Quality Assurance:
2.8.1	The contractor shall be responsible for day-to-day quality checks for works and other building materials in line with approved Field Quality Plan (FQP) and Manufacturing Quality Plan (MQP) during the progress of work. All quality records and log sheets shall be maintained as per the requirement of BHEL/CUSTOMER and as per FQP/MQP approved by BHEL/CUSTOMER.
2.9	Erection Clause:
2.9.1	The work to be carried out at quoted / accepted rates by the Contractor under the scope of these specifications covers the complete work of handling, loading and transporting of materials from project stores sheds / storage yards to site of erection or preassembly yard and unloading at pre-assembly area/erection site, checking, cleaning chipping and levelling of foundations, providing packers and shims/pre-assembling of equipment at the preassembly yard, inspection, minor rectification, preservation, erection, levelling, and other adjustments, cutting, edge / surface preparation, bolting, welding (if applicable), grinding, radiography, LPI/MPI/UT/PAUT/CRT testing wherever needed, heat treatment, including inter connection of all the termination points, and handing over of floors, roof etc., completion of structure erection for PH#1&2 and CCR, BOIs.
2.9.2	The works to be performed under this contract consist of providing all labour, supervision, material, scaffolding, construction equipment's, tools and plants, temporary works, supplies including Consumables, transportation and all incidental items not shown or specified but reasonably implied or necessary for the proper completion of work in all respects. Testing of all materials etc. are included on the rates of items of work. Works shall be carried out only with approved structural erection drawings. The unit rates shall include all resources, consumables, equipment, fixtures, labour, construction plant, temporary works and everything whether of permanent or temporary nature necessary for the completion of job in all respects.
2.9.3	The bidder should fully apprise himself of the prevailing conditions at the proposed site, climatic conditions including monsoon pattern, local conditions, soil strata and site-specific parameters and shall include for all such conditions and contingent measures in the bid, including those which may have not been specifically brought out in the specifications.
2.9.4	The quantities indicated in the tender specification are approximate and are liable for variation at the discretion of BHEL. The work executed shall be measured and priced as per the unit rate arrived at for each work area as mentioned in the relevant clauses. Quantity variation shall be governed as per GCC clause 2.14.

2.9.12	Painting: Touch-up Painting All structures/ components shall be supplied from BHEL units/ workshops with finish coats of paint. Therefore, final painting is not applicable in the scope of contractor for Unit/shop supplied items (<i>until specifically mentioned in the tender</i>). However, touch up painting (wherever required), incidental to the work, shall have to be done. Payment for application of Primer & Paint, including its supply, for touch-up
2.9.11	The storage yard is located in multiple locations. All other materials have to be transported from storage yard to construction area by the contractor at his own cost, using own Pick & Carry Crane (Farrana) , crane and trailer. Bidders are advised to visit site to ascertained all these aspects before quoting.
2.9.10	No member of the already erected structure/ platform, pipes, grills, platform, other component and auxiliaries should be cut without specific approval of BHEL engineer. In case it is necessary to cut, the contractor shall rectify / repair in a manner acceptable to BHEL / Customer without any additional cost.
2.9.9	Considering the area constraint in the subject project, Contractor has to work in close coordination with other erection/Civil agency at site. BHEL engineer will co-ordinate area clearance. In a project of such magnitude, it is possible that the area clearance may be less/more at a particular given time. Activities and erection program have to be planned in such a way that the project milestone events are achieved as per schedule/ plans. Contractor shall arrange & augment the resources accordingly.
2.9.8	The work shall conform to dimensions and tolerances given in various drawings and quality manuals provided by BHEL. If any portion of work is found to be defective in workmanship not conforming to drawings or other stipulations, the contractor shall dismantle and redo the work duly replacing the defective materials at his cost, failing which the job will be carried out by BHEL by engaging other agencies / departmentally and recoveries will be affected from contractor's bill towards expenditure incurred including BHEL's overhead charges (5%).
2.9.7	The terminal points can be inferred from the relevant drawings and any further clarifications can be obtained/decided by BHEL and that is final and binding on the contractor for deciding the scope of work and effecting the payment for the work done up to the terminals. Carrying out work as per the specification between equipments constituting terminal points, whether the terminal equipments fall within the scope of work/specification, contractor shall carry out the terminal joints at either end.
	Time is the essence of contract. Night shift working is envisaged for works not hazardous in nature with due permission of BHEL like- Erection works at low heights, Material shifting, Preassembly works etc.
2.9.6	It shall be specially noted that, the contractor may have to work round the clock (24x7) or may have to deploy additional manpower/resources to achieve the completion schedules / plans / targets during the entire course of erection and commissioning works, which may involve considerable expenses including overtime. Hence contractor's quoted rate shall take into consideration of all expenses that will be incurred for such arrangement of personnel including labours, engineers / supervisors, T&Ps etc.
2.9.5	Supervisors / Engineers, consumables etc., required for the scope of work shall be provided by the contractor. All the expenditure including taxes and incidentals in this connection will have to be borne by agency unless otherwise specified in the relevant clause. The contractor's quoted rates should be inclusive of all such contingencies.

	works in shop fabricated structure shall be paid separately as per BOQ. Scaffolding & other consumables for such works has to be arranged by Contractor within the quoted rates.
2.9.13	During the course of erection, certain rework / modification / rectification / repairs / fabrication etc will be necessary on account of feedback/revision from various relevant sources, and also on account of design discrepancies/ alterations, manufacturing defects, site operations/ maintenance requirements. This will also include modifications / re-works suggested by BHEL / customer / other inspection group. Contractor shall carry out such rework / modification / rectification / fabrication / repairs etc promptly and expeditiously. This shall be dealt as per GCC clause 2.15 of GCC.
2.9.14	The scope of work covered under this specification is of highly sophisticated nature, height work, critical structure for housing sophisticated machines, heavy lifting etc. and hence, requiring the best quality workmanship, engineering and construction management including high standard safety management (as per relevant clause of tender document) and (Project Management, HSE & Quality etc.). Power House and Common Control Room building are most critical structures and required experienced manpower in handling work at height, heavy structures, heavy liftings, scaffolding etc. The contractor should ensure successful and timely completion of the work. The contractor must have adequate quantity of tools, construction aids, equipments etc., in his possession. He must also have on his rolls adequately trained, qualified and experienced supervisory staff and skilled personnel. The manpower deployment identified by contractor shall match with above scope of works. (Refer HSE Manual). Contractor shall execute the work as per sequence and procedure prescribed by BHEL at site. The erection manuals which are available with BHEL site office are to be referred for compliance and guidance before taking up the work. Any failure to comply with the above might lead to rework and the cost for the same shall be borne by the contractor only. BHEL engineer, depending upon the availability of materials, fronts etc., will decide the sequence of erection and methodology. No claims for extra payment from the contractor will be entertained on the grounds of deviation from the method/sequence of erection adopted in erection of similar jobs or for any reason whatsoever.
2.9.15	N.A.
2.9.16	N.A.
2.9.17	Furnishing samples of all materials required by the engineers for testing/inspection and approval for use in the works. The samples may be retained by the engineer for final incorporation in the works.
2.9.18	Furnishing test reports for the products used or intended to be used, if called for the specifications or if so desired by the engineer.
2.9.19	Giving all notices, paying all fees, taxes, statutory clearances/license/Certificates (like T&P load test, etc.), etc., in accordance with the general conditions of contract, that is required for all works including temporary works is in the scope of bidder.
2.9.20	Arranging manufacturer's supervision for items of work done as per manufacturer's specifications when so specified.

2.9.21	The contractor shall provide the owner/BHEL such an assistance, instruments, machines, labour and materials as are normally required for examining, measuring and testing any work and the quality, weight or quantity of any material used.
2.9.22	Providing all incidental items not shown or specified but reasonably implied or necessary for the successful completion of the work in accordance with contract.
2.9.23	Arranging for joint checking (with BHEL / BHEL's Customer / Consultant) of all site construction activities Preparation of joint protocols for each & every activity and maintaining quality records for audit/inspection as per approved FQP by BHEL.
2.9.24	Contractor shall set up suitable guarded storage facilities. Any theft or missing of BHEL material/Tools & Plant from contractor's custody shall be recovered from contractor's dues along with BHEL's applicable overheads.
2.9.25	The drawings/documents enclosed with this tender are intended to give the tenderer a general idea of the type and extent of work involved. The drawings are as such only indicative and not to be considered as the exact construction drawings.
	Further this is to be noted that the drawings and the documents furnished along with this specification are the sole property of BHEL. It must not be used directly or indirectly in any way detrimental to the interest of the company.
2.9.26	The scope of work will also include such other related works although they may not be specifically mentioned above and all such incidental items not specified but reasonably imply and necessary for completion of the job as a whole all as desired and as directed by the engineer.
2.9.27	The detail scope of work covered above is not a comprehensive list of items of work involved. The detail scope of work may vary considerably depending on the actual requirements.
2.9.28	Adequate lighting facilities such as flood lamps, hand lamps and area lighting shall be arranged by the contractor at the site of construction, pre-assembly yard and contractor's material storage area etc. at his cost.
2.9.29	Adequate water less/Bio urinals (at least 1 no. per 100 nos of manpower, at locations identified by BHEL site in-charge) shall be arranged by the contractor within quoted rates, at site of construction at different level and different areas with proper disposal arrangement.
2.9.30	Vendors have to comply requirements of HSE & Statutory requirement in line with BHEL HSE plan, NTPC Safety requirement, State/Central statutory requirement.
2.9.31	Preparation of method statement, HIRA, Job Safety analysis, permit to work, lifting plans, and all supporting documents as required for starting & continuation of work/job is in vendor's scope.
2.9.32	Scaffolding pipes, clamps, safety nets, floor grills for working platforms are to be made of good quality with proper certifications as per IS Codes.
2.10	Consumables

2.10.1	Field connections are bolted. However, all the required electrodes (in Contractor scope) as approved by BHEL shall be arranged by contractor at his cost for carrying out welding
	required as per FQP/drawings for completion of scope of work. It shall be the responsibility
	of the contractor to obtain prior approval of BHEL site, before procurement regarding, suppliers, type of electrodes etc. On receipt of the electrodes at site, it shall be subject to
	inspection and approval by BHEL. The contractor shall inform BHEL details regarding type
2.40.0	of electrodes, batch number and date of expiry etc. The contractor shall provide within finally accepted price / rates, all consumables like
2.10.2	welding electrodes (including alloy steel and stainless steel), all gases (inert, welding, and cutting), soldering material, dye penetrants, radiography films. Other erection consumables such as tapes, jointing compound, grease, mobile oil, M-seal, Araldite, petrol, CTC / other cleaning agents, grinding and cutting wheels are to be provided by the contractor. Steel, H&S, packers, shims, wooden planks, scaffolding and pre-assembly materials
	(structural steel, sleepers, concrete blocks etc) hardware items etc. required for temporary works such as supports, scaffoldings, pre-assembly bed etc. can be issued from
	BHEL on returnable basis subject to availability with BHEL site store. In case of non-availability same has to be arranged by agency.
2.10.3	All the shims, gaskets and packing, which go finally as part of equipment, shall be supplied by BHEL free of cost.
2.10.4	All the required gases like Oxygen / Acetylene / argon / Nitrogen required for work shall be supplied by the Contractor at his cost. It shall be the responsibility of the contractor to plan
	the activities and store sufficient quantity of these gases. Non-availability of gases cannot be considered as reason for not attaining the required progress. BHEL reserves the right to reject the use of any gas in case required purity is not maintained.
2.10.5	The contractor shall submit quarterly statement report regarding consumption of all consumables for cost analysis purposes.
2.10.6	The contractor shall ensure safe keeping of the inflammable cylinder at a separate place away from normal habitat with proper security etc.
2.10.7	Shortage of any of the electrodes or the equivalent suggested by BHEL shall not be quoted as reason for deficiency in progress or for additional rate.
2.10.8	Storage of electrodes shall be done in an air conditioned / controlled humidity room as per requirement, at his own cost by the contractor.
2.10.9	All low hydrogen electrodes shall be baked / dried in the electrode drying oven (range 375 deg. C - 425 deg. C) to the temperature and period specified by the BHEL Engineer before they are used in erection work and each welder should be provided with one portable electrode drying oven at the work spot. Electrode drying oven and portable drying ovens
	shall be provided by contractor at his cost. In case of improper arrangement of procurement of above electrodes BHEL reserves
2.10.10	the right to procure the same from any source and recover the cost from the contractor's subsequent bills at market value plus 5% overheads.
2.10.11	BHEL reserves the right to reject the use of any electrodes at any stage, if found defective because of bad quality, improper storage, date expiry, unapproved type of electrodes etc. It shall be the responsibility of the contractor to replace at his cost without loss of time.
2.10.12	Self-drilling screws / Self taping screws for sheeting works shall be provided by the agency within the quoted price/rates.
2.11	HEIRARCHY:

In case of any conflict/deviations amongst various documents, the order of precedence shall 2.11.1 be as follows: Corrigendum (if any) 1. Items Description in BOQ Cum Rate Schedule. 2. Technical Conditions of Contract (TCC). 3. Technical Specifications for Customer (Section-C). 4. 5. IS Standard. BHEL's Standard Specification (Section-D). 6. Special Condition of Contract/ General Condition of Contract 7.

Sl. No	Description	Scope		Remarks (for details
SI. NO	PART I	BHEL	Bidder	refer relevant clause of tender document)
3.1	Establishment:			
3.1.1	For Construction Purpose:			
a	Open space for office (as per availability within project premises)	Yes		Location will be finalized after joint survey with owner.
b	Open space for storage (as per availability within project premises)	Yes final		Location will be finalized after joint survey with owner.
С	Open space for fabrication(if any)/pre- assembly (as per availability within project premises)	Yes		Location will be finalized after joint survey with owner.
d	Construction of bidder's office, canteen and storage building including supply of materials and other services		Yes	
e	Bidder's all office equipment, office / store / canteen consumables	Yes		
f	Canteen facilities for the bidder's staff, supervisors and engineers etc.		Yes	
g	Firefighting equipment like buckets, extinguishers etc.	s, Yes		
h	Cordoning-off of storage area, office, canteen etc. of the bidder	Yes		
3.1.2	For living purpose of the bidder:			
a	Open space for labour colony		Yes	Contractor has to make his own arrangements for shelter and transportation of labours as per requirement.
b	Labour Colony with internal roads, sanitation, complying with statutory requirements		Yes	Construction Plan shall be approved by BHEL (Refer relevant Annexures in respect of construction of Labour colony)

Sl. No	Description	Scope		Remarks (for details
31. NO	PART I	BHEL	Bidder	refer relevant clause of tender document)
3.2	Electricity:			
3.2.1	Electricity for construction purposes (for Site/Project works only) 3 Phase 415/440 V within project premises			
a	Single point source	Yes		Free of Cost. Shall be provided at adequate points near the site at a distance of approx. 500 meter.
b	Further distribution including all materials, Protection devices and its service		Yes	
С	Duties and deposits including statutory clearances, if applicable	Yes		
3.2.2	Electricity for office, stores, canteen etc. of the bidder (Chargeable) within project premises			
a	Single point source (Chargeable)	Yes		Chargeable at prevailing tariff on project site at One point near the site at a distance of approx. 500 meter.
b	Further distribution including all materials, Energy Meter, Protection devices and its service		Yes	
С	Duties and deposits including statutory clearances, if applicable		Yes	
3.2.3	Electricity for living accommodation of the bidder's staff, engineers, supervisors, labour Hutment etc.			Contractor has to make his own arrangements
a	Single point source		Yes	
b	Further distribution including all materials, Energy Meter, Protection devices and its service		Yes	
С	Payment/Duties and deposits including statutory clearances if applicable		Yes	
3.3	Water Supply:			
3.3.1	For construction purposes:			
3.3.1	roi construction purposes:			

Cl No	Description	Scope		Remarks (for details
Sl. No	PART I	BHEL	Bidder	refer relevant clause of tender document)
a	Making the water available at single point	Yes		Free of cost by BHEL.
b	Further distribution as per the requirement of work including supply of materials and execution			
3.3.2	Water supply for bidder's office, stores, canteen etc.			
a	Making the water available at single point		Yes	
b	Further distribution as per the requirement of work including supply of materials and execution		Yes	
3.3.3				Contractor has to make his own arrangement
a	Making the water available at single point		Yes	
b	Further distribution as per the requirement of work including supply of materials and execution		Yes	
3.4	Lighting			General area lighting through high mast and other fixtures shall be in the scope of BHEL. However, localized area lighting for bidder's construction site/ storage yard/preassembly yard/material handling location, etc. shall be in scope of contractor.
a	For construction work (supply of all the necessary materials) 1. At office/storage area 2. At the preassembly area 3. At the construction site /area		Yes	

Sl. No	Description	Scope		Remarks (for details
51. NO	PART I			refer relevant clause of tender document)
b	For construction work (execution of the lighting work/ arrangements) 1. At office/storage area 2. At the preassembly area 3. At the construction site /area		Yes	
С	Providing the necessary consumables like bulbs, switches, etc. during the course of project work		Yes	
d	Lighting for the living purposes of the bidder at the colony / quarters		Yes	
3.5	Communication facilities for site operations of the bidder			
a	Telephone, fax, internet, intranet, e-mail etc.		Yes	
3.6	Compressed air wherever required for the work			
a	Supply of Compressor and all other equipments required for compressor & compressed air system including pipes, valves, storage systems etc.		Yes	
b	Installation of above system and operation & maintenance of the same		Yes	
С	Supply of the all the consumables for the above system during the contract period		Yes	
3.7.1	Demobilization of all the above facilities		Yes	
3.7.2	Transportation			
Α	For site personnel of the bidder		Yes	
В	For bidder's equipment and consumables (T&P, Consumables etc.)		Yes	
3.7.3	Erection Facilities			
3.7.3.1	Engineering works for construction:			
a	Providing the erection/constructions drawings for all the equipment covered under this scope.	Yes		Shall be provided progressively.
b	Drawings for construction methods	Yes	Yes	In consultation with BHEL

Sl. No	Description Scope		cope	Remarks (for details	
51. NO	PART I	BHEL Bidder		refer relevant clause of tender document)	
С	As-built drawings wherever deviations observed and executed and also based on the decisions taken at site	Yes		Changes are to be marked in drawing & handover to BHEL on completion of work.	
d	Shipping lists etc. for reference and planning the activities	Yes			
e	Preparation of site erection schedules and other input requirements asper Form-14.		Yes	In consultation with BHEL	
f	Review of performance and revision of site erection schedules in order to achieve the end dates and other commitments	Yes	Yes	In consultation with BHEL	
g	Weekly erection schedules based on Sl. No. e		Yes	In consultation with BHEL	
h	Daily erection / work plan based on Sl. No. g	Yes		In consultation with BHEL	
i	Periodic visit of the senior official of the bidder to site to review the progress so that works is completed as per schedule. It is suggested this review by the senior official of the bidder should be done once in every two months.		Yes		
j	Preparation of pre-assembly bay		Yes	Materials required for preassembly shall be in agency scope. However, if available, BHEL may provide such material on free returnable basis, which shall be returned without any damage.	

3.8	Land/Open Space:
3.8.1	Availability of land within plant boundary is very limited and the contractor has to plan and use the existing land considering the use of land by other Civil /mechanical/ electrical contractors and the storage of plant machineries and materials. The existing land shall be shared by all erection's agencies. BHEL shall provide free of charge limited open space for office, storage shed and laydown area as and where made available by Customer. It is the responsibility of the contractor to construct facilities such as sheds, fabrication/Preassembly yard, provide all utilities and dismantle and clear the site after completion of work or as and when required, as a part of his scope of work.
3.9	Labour and Staff Colony:
	Following are in the Bidder's scope of work for labour & staff colony:
3.9.1	Labour colony is to be developed by bidder for all the labours required to be deployed for the works. All labour colony set-up is to be developed as per attached customer drawing (Annexure-B), BHEL's standard guidelines (Annexure-A) for worker's accommodation/establishment and in compliance of statutory requirements.
	Contractor shall construct/arrange Labour Hutment as per minimum specifications mentioned in the attached drawing/guidelines, for which no separate payment shall be made by BHEL. Modifications if any proposed in the Hutment shall be in consent with BHEL/Customer.
	Ownership of the labour hutment shall be of the contractor and contractor shall keep BHEL indemnified from any statutory obligations/ legal compliances w.r.t. labour hutment establishment during as well as after the completion of contract.
3.9.2	In case labour hutment is not completed as per the drawings, BHEL's guidelines and specification and any penalty is imposed by Customer, same shall be recovered from contract's RA Bill.
	Rectification and Corrections in labour hutment as pointed out by BHEL/Customer shall be bidder's responsibility and any cost incurred by BHEL to complete the works, in case of non-compliance of the instructions, same shall be recovered from his RA Bills along with 5% overheads.
3.9.3	Land for labor colony shall be arranged by Contractor at their own cost as per availability outside project area preferably within 5Km, Necessary levelling/dressing of land shall be done by the contractor. All arrangement for electricity and drinking/service water to be arranged by the contractor within his quoted price. All expenses towards installation of transformer, depositing requisite fees etc if required shall be borne by vendor.
3.9.4	Development of Bidder's temporary staff colony and labour colony having adequate no. of Bio Urinals.
3.9.5	All Civil and Structural work associated with drinking and service water for Bidder's labour and other personnel at the work site/colony/offices including pump houses, pipes, overhead tank, tube wells etc.

3.9.6	Providing and maintaining facilities for safety, welfare, drinking water and sanitation, hygiene, health check-up etc. for construction workers at their workplaces as well as at labour & staff colonies.				
3.9.7	Development and maintenance of above facilities for construction workers deployed by the Contractor shall solely rest with the Contractor.				
3.9.8	Contractor shall follow the BHEL's standard guidelines and customer drawings in respect of construction and maintenance of labour colony/accommodation attached with this tender at the direction of BHEL's engineer				
3.10	Installation of necessary amenities- and temporary infrastructure for construction activities at Project site locations.				
	Following are the minimum amenities to be provided by the bidder within the quoted price including removal/disposal of the same in environment friendly manner after its intended use/completion of scope of work:				
	i. Labour rest sheds near work spot.				
	ii. Canteen facility creation.				
	iii. Drinking water facility.				
	iv. Labour Bio toilets near work spot in sufficient nos. with regular cleaning & maintenance arrangement.				
	v. Labour colony should have all hygienic condition, dining hall, toilets, proper sewerage system, good drinking water arrangements.				
	vi. Regular fogging in the work place and labour colony to avoid mosquitoes.				
	vii. Royalty challan (if applicable) and statutory documents shall be submitted along with RA Bills for processing of Bills.				
3.11	Construction Power:				
3.11.1	Construction power (three phase, 415 V/ 440 V) will be provided near the site at a distance of approx. 500M free of cost . Further, distribution shall be arranged by the contractor at his own cost and services.				
	Construction power (three phase, 415 V/ 440 V) for office, stores, canteen etc. within the site premises will be provided on chargeable basis near the site at a distance of approx. 500M. Further, distribution shall be arranged by the contractor at his own cost and services.				

3.11.2	Contractor shall deploy and install required energy meter (wherever applicable), cables, fuses, distribution boards, switchboards, bus bars, earthing arrangements, protection devices and any other installation as specified by statutory authority/act.
	Contractor shall provide at his own cost necessary calibrated energy meters (tamper proof, suitably housed in a weather proof box with lock & key arrangement) at point of power supply along with calibration certificate from authorized/ accredited agency for working out the power consumption. In case of recalibration required for any reason the necessary charges including replacement by calibrated meters is to be borne by the contractor.
	Contractor is advised to maintain the calibrated energy measuring instruments.
3.11.3	Sufficient power factor compensation equipment like capacitor shall be provided by contractor for reactive loads like welding machines etc. In case of any fine/penalty on account of low power factor, same shall be shared by contractor proportionately according to power consumption.
3.11.4	Contractor shall make necessary arrangements for onward distribution of construction power taking due care of surrounding construction activities like movement of cranes & vehicles, civil work, fabrication/construction/assembly/ erection etc. and safety of personnel. It may become necessary to relocate some of the installations to facilitate work by other agencies or by him.
3.11.5	It shall be the responsibility of the Contractor to provide, maintain the complete installation on the load side of the supply with due regard to the safety requirements at site. All cabling and installations shall comply in all respects with the appropriate statutory requirements. The installation and maintenance of this shall be done by licensed and experienced electrician.
3.11.6	While reasonable efforts will be made to ensure continuous electric power supply, interruptions cannot be ruled out and no claim from the Contractor shall be entertained on this account such as idle labour, extension of time etc. The Contractor shall adjust his working shift accordingly and deploy additional manpower, if necessary, so as to achieve the target.
3.11.7	Contractor shall be well equipped with back-up power supply arrangement like DG set and diesel operated welding machine etc. to tackle situations arising due to failure of supplied power, so as to ensure continuity and completion of critical processes that are underway at the time of power failure or important activities planned in immediate future.
3.11.9	BHEL is not responsible for any loss or damage to the Contractor's equipment as a result of variations in voltage or frequency or interruptions in power supply.
3.11.10	The bidder shall be responsible for General illumination system/arrangements during construction right from start of his work. This system will include temporary pole lighting,

	within the quoted price. The illumination should be such that minimum illumination requirement as specified by Indian standards for general illumination is maintained.
3.11.11	VOID
3.11.12	Supply of electricity shall be governed by Indian Electricity Act and Installation Rules and other Rules and Regulation as applicable. The contractor shall ensure usage of electricity in an efficient manner and the same may be audited by BHEL time to time. In case of any major deviation from normally accepted norms is observed, BHEL will reserve the right to impose penalty as deemed fit for such cases.
3.12	Construction Water:
3.12.1	Construction water shall be provided by BHEL on free of cost basis. Bidder has to make arrangement of further distribution of water at his own cost. No extra payment shall be made under this account.
3.12.2	The Contractor should make arrangements for storage of sufficient quantity of water required for construction purposes.
3.12.3	Contractor to satisfy himself that the water drawn by him is fit for construction / consumption purposes.

- **4.0** Tools and Plants: Number of T&Ps to be deployed at site shall be decided w.r.t. monthly plan and review format (F-14) based on site requirement.
- 4.1 **Major T&P:** The following **Major Tools & Plants** (T&P) shall be arranged by the Contractor for execution of work as per Technical Conditions of Contract of this tender within the quoted rate.

For Package A:

S.N.	DESCRIPTION OF MAJOR T&Ps	CAPACITY	QUANTITY	REMARKS
1.	Crawler/Tyre mounted	80 MT	01 Nos.	Crane to be made available as per instruction from BHEL Site in-charge Tentative schedule: from Start of structure Erection till completion

For Package B:

S.N.	DESCRIPTION OF MAJOR T&Ps	CAPACITY	QUANTITY	REMARKS
1.	Crawler/Tyre Mounted	80 MT	01 No.	Crane to be made available as per instruction from BHEL Site in-charge Tentative schedule: from Start of structure Erection till completion

Note for clause 4.1:

- **1.** Contractor shall mobilise aforementioned cranes/T&Ps at site, in case stated capacity crane could not be made available, for any reason what so ever, a higher capacity crane shall be mobilised by the contractor without any extra cost.
- 2. Agency shall Mobilize / de-mobilize/ re-mobilise the Major T&Ps as per BHEL instruction without any extra cost to BHEL.
- 4.2 **Other T&P:** The following **Other Tools & Plants** (T&P) shall be arranged by the Contractor for execution of work **under Package A & B (i.e. for each package)** as per Technical Conditions of Contract of this tender within the quoted rate. Below given Quantities are tentative for planning purposes by the bidder.

S.N.	DESCRIPTION OF OTHER T&Ps	CAPACITY (MINIMUM)	MINIMUM QUANTITY	REMARKS
1	Crawler crane 40 MT	40 MT	Minimum 01/APR	
2	Tyre mounted Crane/Farana	12/14/18/20/22 MT	Minimum 04/APR	Capacity is tentative and same shall be

S.N.	DESCRIPTION OF OTHER T&Ps	CAPACITY (MINIMUM)	MINIMUM QUANTITY	REMARKS	
				decided with BHEL	
				engineer during	
				execution of	
				work	
3	Trailers with pulling unit	40 MT	Minimum 01/APR	APR	
4	Trailers with pulling unit	20 MT	Minimum 01/APR	APR	
5	Tractor Trolley	APR	Minimum 01/APR	APR	
6	DG Set	250 kVA	APR		
7	Power Winches	2/3/5/10/15 MT	Minimum 06/APR	APR	
8	Hand winch	0.5 /1.0 MT	APR	APR	
9	Welding Machine	APR	APR	APR	
10	Baking/Heating Oven	APR	Minimum 01/APR	APR	
11	Portable Oven	APR	APR	APR	
12	Portable grinding machine of various sizes	APR	APR	APR	
13	Calibrated Power driven bolt tightening machines	Desired Sizes	Minimum 5/APR		
14	Manual Torque tightening machine	Desired Sizes	Minimum 05/APR		
15	Torque calibrator	APR	APR	APR	
16	Bolt Tension Calibrator	APR	APR	APR	
17	Impact wrench with socket (Pneumatic)	Desired Sizes	APR	APR	
18	Steel tape/steel ruler/Wrenches	APR	APR		
19	3-phase distribution board with complete set up for drawl of construction power	APR	APR	Required Since start of work	
20	Power cable for drawl of construction power	APR	APR		
21	Self-drilling cum tapping machine for screws	APR	APR	APR	
22	Radiography arrangement with radioactive isotope source	APR	APR	APR	
23	Gas cutting sets	APR	APR		
24	Chain pulley blocks	APR	APR	Of different capacities	

S.N.	DESCRIPTION OF OTHER T&Ps	ESCRIPTION OF OTHER T&PS CAPACITY (MINIMUM) QUAN		REMARKS
25	Scaffolding materials with clamps for cladding fixing, etc works	APR	APR	Sufficient numbers for parallel working/joints
26	Hoisting and pulley devices/pulleys	APR	APR	
27	SPANNERS / EYE BOLTS (OF ALL SIZES)	APR	APR	
28	Wooden/Concrete sleeper 1.5-2.0 Mtr length	APR	APR	
29	Sufficient quantity of steel ladders for approach up to the top of each erected column to be required during erection of columns.	APR	APR	
30	Suspended working platform Size :7mX1mX0.5m, Rated load 800 kg to 1000 Kg,	APR	APR	APR
31	Theodolite of required accuracy	APR	Minimum 02/APR	
32	Air compressor/blower (electric/diesel operated)	210 CFM, 7 KG/CM2	APR	
33	Slings/Special Slings for Erection of Ceiling Beams & other heavy components	APR	APR	
34	Elcometer for paint thickness checking		As required	
35	Various sizes of clamps/ fixtures for assembling		As required	
36	Dewatering pumps(Electrical & Diesel engine operated)	As required	As required	
37	Welding rectifiers (electrical)	As required	As required	
38	Self-drilling cum tapping machine for screws of PH roof & Cladding sheets and Deck Sheet	As required	As required	
39	Radiography film viewer	As required	As required	
40	Safety ladder for sheet laying	As required		
41	Man lifter	As Per Requirement	As Per Requirement	As Per Requirement
42	Painting equipment/sets	As Per Requirement	As Per Requirement	
43	Dewatering pumps	As required	As required	

S.N.	List of suggestive safety Equipments /PPEs to be included in List of minimum T&P:	Remarks
1.	Safety Net (Conforming IS 11057:1984) Safety Net (Net Size: 10m x 5m, Mesh Size: 25 mm, Mesh Rope: 2mm double cord, Border/Tie Cord: 12mm diameter polypropylene rope (tested as per IS: 5175). Two meters length shall be provided at all four corners.	Min-40 Nos
	Fall Arrester 'Rope grab fall arrester' & anchorage line. Anchorage Line: 14mm- 16 mm diameter, three strand twisted Polyamide rope.	Min. 50 nos. of Rope Grab Fall arrester' and Karbiner each.
2.	Rope Grab fall arrester: Openable & Guided type Fall Arrestor (on flexible line) conforming EN 353-2 & works on 14-16 mm diameter polyamide rope. Material: Nickel Chrome plated Steel	Min 25 nos. anchorage line, 30 metre long each,
	Connector: Karbiner conforming to EN 362 (Minimum Strength 22 KN), material: Steel	10 nos. anchorage line, 40 metre long each
	Retractable Fall arrestor Block (Range 6 Mtr to 15 Mtr)	Min50 Nos
3.	Horizontal life line Stainless Steel Wire rope of 8mm diameter. Minimum six nos. of steel U-bolt clips are required for clamping each wire rope to a rigid support (03 nos. of U-bolt clips at each end).	Min 10 nos. of wire rope, each 40 metre long Min 25 nos. of wire rope, each 25 metre long.
4.	Ladders on column The minimum design live load on metallic ladder shall be a single concentrated load of 100 kilo grams. All rungs shall have a minimum diameter of 16mm to 25 mm, and minimum clear length of rungs shall be 40.6 centimetres. The distance between rungs shall not exceed 30.5 centimetres. Each ladder shall have maximum height of 9.0 metre. The ladder shall have proper fastenings for attaching it to a column using positive means such as bolt, weld or other type of fasteners.	As per requirement based on BHEL engineers instructions
5.	Height Rescue Kit and Confined space rescue kit	1 No each
6.	Lux Meter & Breathe Analyser	01 No (if required)
7.	Multi Gas Meter	1 No
8.	ELCB & RCCB Tester	1 No
9.	Earth Resistance meter	1 No
10.	Scaffolding materials as per EN 74 for hard barricading	As per requirement

11.	Oxygen Meter	1 No
12.	Fire Blanket	APR
13.	Fire resistant tarpaulins	APR
14.	Safety Posters as per BHEL Guidelines	As per requirement and instruction of BHEL
15.	Fire Extinguishers: ABC – 6 Kg: 50 Nos, Co2 – 4.5 Kg: 20 Nos, Foam – 9 Kg: 5 Nos Fire Bucket (set of ¾ buckets) with stand – 10 Nos	
16.	Rubber Mat as per IS 15652	Min 200 Sqm
17.	Electrical rubber gloves	As per requirement
18.	Water Sprinkling tanker for dust suppression	As per requirement

- APR - As per requirement

Note- Please refer BHEL Singrauli site HSE plan (Annexure-C) in respect of safety equipment/PPEs. Separate annexure issued to all contractor at the time of execution of work by Safety officer of BHEL with approval of construction manager/ GM/ PD. PPEs Quantity annexure issued by site are final and agency must fulfill the same during execution of work.

4.3	Measuring and Monitoring Equipment (MMEs): To be finalized as per site requirement.		
4.3.1	All above T&Ps are to be deployed by contractor as and when required as per instruction of BHEL engineer. If works gets delayed due to non-availability of above T&Ps, BHEL reserves the right to deploy the same and recover the charges thereof from the contractor as per prevailing market rate/hiring rate/BHEL internal hiring rates + 5% overhead rates.		
4.3.2	Heavy Equipments (cranes, winch etc.) manufactured less than 15 Yrs. from the current Year shall be only allowed to be used at project Site.		
4.3.3	Hydras are not permitted for the scope of work. Contractor shall deploy and use pick & carry crane of TRX/Farana or equivalent type only for the above purpose. Quantity and capacity of Farana/Pick & Carry crane mentioned above under sl no 4.2(1) is tentative and both shall be mutually decided by BHEL Engineer and contractor at site during execution of work as per the requirement.		
4.3.4	Tandem operation towards material handling is also not permitted in the project premises.		
4.3.5	Necessary electrical / water / air connection required for operation of any of the tools & tackles shall be to Contractor's account.		
4.3.6	Contractor has to submit the Calibration certificates of all the precision Equipment to BHEL. BHEL may ask for recalibration of the MMEs /precision equipment for ensuring		

	quality of work. Contractor must re-ascertain/recheck range and accuracy of each IMTE from BHEL Engineer well in advance before arranging calibration/deployment.
4.3.7	All Measuring and Monitoring Devices (MMD) used for the work in scope of these tender specifications shall be calibrated by the accredited agencies that are approved by BHEL or calibration tractability is established upto National Physical Laboratory.
4.3.8	Contractor has to arrange slings of all sizes for completing the works covered under these specifications.
4.3.9	In the event of need of change of type of any of major T&Ps, approval shall be taken from BHEL Engineer in-charge prior to mobilization. The decision of Number of T&P required due to replacing the enlisted T&P as per above table, shall be taken after analysing the
4.3.10	production capacity and suitability of both the T&Ps. The contractor shall submit the valid test certificate/calibration certificates for all the T&Ps before put into actual use at site. The certificates shall be renewed time to time as instructed by BHEL Engineer.
4.3.11	Crane operators deployed by the contractor shall be offered for testing by BHEL before they are allowed to operate the cranes.
4.3.12	The above list as mentioned in S.No. 4.2 (Other than mentioned in S.No. 4.1 Major T&Ps) is only indicative and these T&Ps may not be required for entire contract period but contractor shall ensure the availability of the T&Ps as per work requirement and T&P Deployment schedule. T&P Deployment schedule shall be finalized at site in consultation with BHEL Engineer based on the work fronts/work requirement. BHEL decision shall be final and binding regarding the T&P deployment schedule. Contractor shall mobilize / maintain the T&P's as per the deployment schedule notified time to time by BHEL Engineer.
4.3.13	APR (As per Requirement) - Contractor has to deploy T&P, MMD, IMTE as per requirement of site and as decided by BHEL Engineer.
4.3.14	Apart from above mentioned T&P, any additional item required in addition to above mentioned T&P for proper execution of scope of work, contractor has to arrange such T&P within quoted rate on the instruction of BHEL in writing in a reasonable period within two weeks from the written instruction from BHEL.
4.3.15	If the work related to T & Ps mentioned above is completed then, BHEL can release that T&P during contract period / extended period (if any). However, written permission shall be taken by contractor from BHEL Construction Manager and gate pass formalities shall be followed by the contractor for releasing the T&P.
4.3.16	In the eventuality of contractor not deploying / abnormal down time of T&P/cranes in his scope during the period specified above, and BHEL arranges for the same [BHEL's own cranes], prevailing BHEL Corporate Crane hire charges (which may vary from time to time) shall be recovered from the contractor's running bills. Corresponding pages of Corporate Crane hire charges are enclosed as part of tender document as File titled "Annexure D- BHEL T&P Hire Charges". (Please note that these charges are as valid up to Aug, 2025 and may get revised further). In case BHEL arrange the T&P/Crane through hiring, actual hiring charges with 5% over head shall be recovered from the contractor's running bills.
4.3.17	The loading, unloading and transportation of contractors T&Ps shall be in the scope of contractor. All necessary items such as Trailers, Cranes, Winches, welding generators, slings, jacks, sleepers, rails etc., are to be arranged by the contractor at his own cost.

4.3.18	All the T&Ps required for this scope of work, except the Tools & Plants mentioned in Chapter V of TCC: T&Ps to be provided by BHEL , are to be arranged by the contractor with in the quoted rates.
4.3.19	All operators (for crane, winch etc.) deployed by contractor shall have valid licence from applicable authority (which ever applicable).
4.3.20	The contractor has to furnish a list of Tools and plants including cranes/tractors/trailers/trucks etc. which he has proposed to deploy for this work.
4.4.1	T&Ps shown in the above in S.No. 4.2 mentioned list is suggestive requirement. However, mobilization schedule as mutually agreed at site for T&Ps, have to be adhered to. Numbers/time of requirement will be reviewed from time to time at site and contractor
	will provide required T&Ps/equipment to ensure completion of entire work within schedule/target date of completion without any additional financial implication to BHEL.
4.4.2	Contractor will give advance intimation & certification regarding capacity etc. prior to dispatch of heavy equipment. Also on completion of the respective activity, demobilization of T&Ps in total or in part can be done with the due approval of Engineer-In-Charge. Retaining of the T&Ps during the contract period will be mutually agreed in line with construction requirement.
4.5	The contractor shall arrange operator, diesel, petrol and other consumables including electrical / water / air connections required for the tools and plants, equipment such as crane, winch, temporary Jhoola, etc. Preventive and routine maintenance of T & P are also to be arranged by the contractor at his cost without any delay. Required number of experienced mechanics and helpers for routine maintenance of the above T&Ps shall be provided by the contractor within his quoted rate.
4.6	Required consumables like electrodes, all gases, and other materials for this scope of work are to be arranged by the contractor at their cost.
4.7	Penalty due to T&Ps: In order to meet the site requirement and in line with monthly plan and review format (F-14), Contractor has to mobilise their T&Ps and made available at site for required activities. For Major T&Ps, if contractor fails due to either of the case mentioned hereunder, BHEL
	shall be entitled to impose penalty on Contractor till any alternate arrangement is made by Contractor OR BHEL (on cost recovery basis). Case 1: Contract fails to mobilise the same within the mobilisation period of 30 days from the date of intimation. OR
	Case 2: After mobilisation of T&P at site, the work is getting hampered due to non-availability of T&P for more than 5 days from the date of such intimation,
	Penal rate for Major T&Ps is mentioned hereunder: a. 80 MT Crane – Rs. 2000/day

TECHNICAL CONDITIONS OF CONTRACT (TCC) Chapter – V: T&PS AND MMES TO BE PROVIDED BY BHEL

5.1 LIST OF T&Ps TO BE PROVIDED BY BHEL FREE OF HIRE CHARGES ON SHARING BASIS:

SL NO	DESCRIPTION & CAPACITY OF T&P	QUANTITY	REMARKS
1	Cranes	As decided by BHEL	All cranes (except Contractor scope as mentioned in Clause 4.1), required for mentioned work, will be arranged by BHEL as per requirement.

1 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2
All the T&Ps mentioned in clause 5.1 above shall be given to contractor on sharable basis and the allotment is made by BHEL on need basis. Contractor shall plan activities well in advance and inform BHEL Engineer in charge/ Construction Manager seven (07) days prior to the date of actual use. The decision of BHEL Engineer in-charge/CM on this will be final and binding.
Contractor shall provide assistance to transport from BHEL stores, install, operate, carry out maintenance, dismantle after use and return to BHEL stores all T&Ps mentioned in Sr no 5.1 for his use.
Cranes provided by BHEL are only for erection purpose and shall not be available for transportation purpose. Contractor shall make their own arrangements for material transportation to erection site.
All the distribution boards, connecting cables, hoses etc., and temporary connection work including electrical connections for the BHEL issued T&Ps shall have to be arranged by the contractor at his cost.
The contractor at his cost shall arrange for grouting of anchor points of T&Ps issued to agency. Necessary grout materials are to be arranged by the contractor at his cost.
The day-to-day and routine maintenance including replacement of spares for the BHEL T&Ps will be carried out by the contractor at his own cost. However, BHEL shall supply spare parts free of charges for normal wear and tear only.
Any loss/damage of tools by the contractor shall have to be replaced or otherwise cost thereof shall be recovered from the contractor.
T&Ps provided by BHEL will be on sharing basis with other agencies / contractors of BHEL. The allocation of T&Ps shall be the discretion of BHEL engineer, which shall be binding on the contractor. T&Ps will be deployed at appropriate time as decided by BHEL for suitable duration and intended purpose. Augmentation of BHEL T&P under special circumstances shall be discretion of BHEL.
All the Hydras/Frannas required for execution of work shall be arranged by contractor within quoted rates.
For BHEL Owned or hired Crane:
1. The cranes may be BHEL owned or may be obtained on hiring basis including operating and maintenance crew.
2. Operator and O&M for BHEL owned crane will be provided by BHEL.
3. Contractor shall provide the fuel for BHEL provided cranes (Hired/owned) for his use.

TECHNICAL CONDITIONS OF CONTRACT (TCC) Chapter – V: T&PS AND MMES TO BE PROVIDED BY BHEL

4. Contractor shall make necessary arrangements like laying of special sleeper beds and steel plates (**Plates for BHEL owned/ hired cranes shall be provided by the BHEL**), assembly and dismantling of heavy attachment, boom, jib etc. for movement and operation of the crane. Contractor shall provide necessary manpower assistance for initial and final assembly & dismantling and for subsequent operations of boom extension and reduction during execution of work. Levelled area will be provided by BHEL/customer for the movement of BHEL cranes. Further Consolidation of the ground with hard-crusting of Area required for movement of contractor's crane (including civil work with material) for placing crane for operation shall be facilitated by BHEL. Necessary plates required for marching operation shall be provided by the BHEL only for BHEL owned cranes.

TECHNICAL CONDITIONS OF CONTRACT (TCC) Chapter – VI: TIME SCHEDULE

6.1	Time Schedule and Mobilization:		
	Initial	Mobilization and Time Schedule:	
6.1.1	Constru date of date of mobiliz	ssue of LOA (though Fax/courier/email) the contractor action Manager/Site In-Charge of BHEL at site within Two LOA and make a Kick of meeting (KOM) for mobilization of start of work and detailed completion program etc. Contracted ation plan to start work within 15 days from date of I is by BHEL in writing.	weeks (14 days) from f manpower, T&Ps and or shall submit detailed
	BHEL. T project the enti	ivities for Erection etc. shall be started as per directions of Co The contractor has to subsequently augment his resources in milestones are completed on specified schedules and entire re contract period, as specified in the following clause from to nner required by BHEL to match with the project schedule.	such a manner that the work completed within
	COMMI	ENCEMENT OF CONTRACT PERIOD	
	equipm	n/placement on its designated foundation / location, of the ent / component / column covered in the scope of these speer as decided by BHEL) shall be recognized as " Start of conge.	ecifications, (whichever
	of control	ritems like packer plates, shims, anchors, inserts etc. will no ract period. The date of Start of contract period shall be the name that the work is the contractor and BHEL engineer to start the work. In confidered final.	e mutually agreed date
6.1.2	may ha	on the availability of civil foundations, drawings and material ave to advance the erection activity after getting clearancer, or the erection activity may get delayed due to site condit	nce from Construction
	prepara foundat contrac period.	ntractor shall have to mobilize his resources before the star atory work like taking over of Foundations, drawing & ma cions, blue-matching, grouting of packer plates etc. and star tor shall complete all the works in the scope of this contra Pending points identified by the customer/BHEL during t are to be liquidated during the contract period itself.	terials and chipping of t of pre-assembly. The act within the contract
	Schedu	lle of Completion:	
(4.2	hereun	ntract period for completion of entire work under scope der, from the "START OF CONTRACT PERIOD" as specified entre work in respective Package.	
6.1.3	S.No.	Package	Contractual Schedule (Month)
	1.	Package A: Structure Erection of Main Power House Unit- 1 along with BOIs as per BOQ at 2X800 MW NTPC Singrauli stage-III Project.	14 Months

TECHNICAL CONDITIONS OF CONTRACT (TCC) Chapter – VI: TIME SCHEDULE

	Package B: Structure Erection of CCR (Common Control	
2.	Room) and Main Power House Unit-2 along with BOIs as	18 Months
	per BOQ at 2X800 MW NTPC Singrauli stage-III Project.	

6.2 The schedule of important milestones is as follows:

6.2.1	Package A Activity	Schedule of completion from date of start of work
6.2.1.1	Main Power House Column Erection works	4 th Month
6.2.1.2	Erection of Floor beams at EL(+) 17.00 M Floor	5 th Month
6.2.1.3	EL(+) 17.00 M Floor Structure clearance for floor casting/ Civil Work	5 th to 6 th Month
6.2.1.4	Readiness of Structure for EOT crane installation	7 th Month
6.2.1.5	Cladding along 'A' row	9 th Month
6.2.1.6	Cladding along 'C' row	11 th Month
6.2.1.7	Cladding along Gable end row	12 th Month
6.2.1.8	Completion of balance structural works	14 th Month
6.2.2	Package B Activity	Schedule of completion from date of start of work
6.2.2.1	CCR structure erection start	1 st Month
6.2.2.2	Main Power House Column Erection works	8 th Month
6.2.2.3	Erection of Floor beams at EL(+) 17.00 M Floor	9 th Month
6.2.2.4	EL(+) 17.00 M Floor Structure clearance for floor casting/ Civil Work	9 th to 10 th Month
6.2.2.5	Readiness of Structure for EOT crane installation	11 th Month
6.2.2.6	Cladding along 'A' row	12 th Month
6.2.2.7	Cladding along 'C' row	13 th Month
6.2.2.8	Cladding along Gable end row	16 th Month

TECHNICAL CONDITIONS OF CONTRACT (TCC) Chapter – VI: TIME SCHEDULE

Completion of balance structural works

will be withheld.

will be withheld.

RA bills.

or released as the case may be.

6.6.2

6.6.3

6.6.4

6.6.5

6.2.2.9

0.2.2.9	Completion of balance structura	II WOI KS	10m MOUTH	
6.3	The above schedule is only tentative. The above schedule shall be advanced, if there are requirements to advance the project to meet the project requirement. No extra payment whatsoever shall be paid on this account.			
6.4	In order to meet the above schedule in general, and any other intermediate targets set, to meet customer/ project schedule requirements, Contractor shall arrange & augment all necessary resources from time to time on the instructions of BHEL Engineer w.r.t. monthly plan and review format (F-14).			
6.5	Intermediate milestones:			
6.5.1	Two Major Intermediate Milestones are identified as M1 and M2 above.			
	Milestones for Package A	Schedule of completion from start of work		
M1	Readiness of unit-1 PH Structure for EOT crane installation		7 th Month	
M2	TG hall cladding		12 th Month	
	Milestones for Package B	Schedule of con	npletion from start of work	
M1	Readiness of unit-2 PH Structure for EOT crane installation		11 th Month	
M2	TG hall cladding		16th Month	
	Provision of Penalty in case of slippage of Intermediate Milestones:			
6.6	In case of slippage of Two Major Intermediate Milestones, mentioned as M1 & M2 above, delay Analysis shall be carried out on achievement of each of these two Intermediate Milestones in reference to F-14.			
6.6.1	In case delay in achieving M1 Milestone is solely attributable to the contractor, 0.5% per week of executable contract value*, limited to maximum 2% of executable contract value,			

In case delay in achieving M2 Milestone is solely attributable to the contractor, 0.5% per

week of executable contract value*, limited to maximum 3% of executable contract value,

Amount already withheld, if any against slippage of M1 milestone, shall be released only if

Amount required to be withheld on account of slippage of identified intermediate milestone(s) shall be withheld out of respective milestone payment (corresponding RA Bill)

and balance amount (if any) shall be withheld @10% of RA Bill amount from subsequent

Final deduction towards LD (if applicable), on account of delay attributable to contractor shall be based on final delay analysis on completion/closure of contract. Withheld amount,

if any due to slippage of identified intermediate milestone(s) shall be adjusted against LD

there is no delay attributable to contractor in achievement of M2 Milestone.

18th Month

TECHNICAL CONDITIONS OF CONTRACT (TCC) Chapter – VI: TIME SCHEDULE

6.6.6	In case of termination of contract due to any reason attributable to contractor before completion of work, the amount already withheld against slippage of intermediate milestones shall not be released and be converted into recovery.
6.6.7	Contractor shall make all possible efforts to expedite the activities, in case of delay of any intermediate milestone, to maintain overall project completion schedule.
6.7	COMPLETION OF WORK AND COMMENCEMENT OF GUARANTEE PERIOD
6.7.1	The works shall be completed to the entire satisfaction of the Engineer and in accordance with the completion schedule as specified in the Contract, and all unused stores and materials, tools, plant, equipment, temporary buildings, site office, labor hutments and other things shall be removed and the site and work cleared of rubbish and all waste materials and delivered up clean and tidy to the satisfaction of the Engineer at the Contractor's expenses.
6.7.2	BHEL shall have power to take over from the Contractor from time to time such sections of the work as have been completed to the satisfaction of the Engineer. Such work however shall not be treated as have been completed until the remaining / pending works are executed to the satisfaction of Engineer.
6.7.3	BHEL Engineer shall certify to the contractor the date on which the work is completed and the date thereof for commencement of Guarantee Period. The work shall be deemed to be completed upon completion of work as per contract or As per the Clause no 2.7.8 of GCC, whichever is earlier, minor pending works/punch point liquidation/defects (if any) which are not likely to affect overall performance of the system may be excludes as per the discretion of BHEL Engineer.
6.8	The decision of BHEL Engineer shall be final and binding on the vendor. The contractor shall submit and a detailed area/structure wise L3 schedule within 25 days from date of LOA, in consultation with BHEL, based on the tentative schedule provided as above. The detailed L3 schedule shall be approved by BHEL and same shall be implemented. Bidder shall submit L3 schedule in MS Projects and excel to meet the agreed project schedule covering various mile stone activities and their split up details such as mobilization, procurement of materials & erection activities. This schedule shall also clearly indicate the interface facilities / inputs applicable in each package. Bidders shall submit Resource deployment plan Area wise with detailed program in line with above schedule in the form of Bar Chart/ MS project planner along with their offer.
6.9	The under mentioned Records/ Log-books/ Registers applicable to be maintained. I. Hindrance Register. II. Site Order Book. III. Test Check of measurements. IV. Records of Test reports of Field tests. V. Records of manufacture's test certificates. VI. Records of disposal of scraps generated during and after the work completion.
6.10	Control and monitoring of progress of work
6.10.1	Refer forms F -14 to F-18 of volume I D (Forms & Procedure) of volume - I BCD. Plan and review will be done as per the formats.

TECHNICAL CONDITIONS OF CONTRACT (TCC) Chapter – VI: TIME SCHEDULE

	The progress reports shall indicate the progress achieved against plan, indicating reasons
6.10.2	for delays, if any. The report shall also give remedial actions which the contractor intends to make good the slippage or lost time so that further works can proceed as per the original plan the slippages do not accumulate and affect the overall programme.
6.10.3	It is the responsibility of the contractor to provide all relevant information on a regular basis regarding progress of work, labour availability, equipment deployment, testing, etc.
6.10.4	Contractor is required to draw mutually agreed monthly work programs in consultation with BHEL well in advance. Contractor shall ensure achievement of agreed program and shall also timely arrange additional resources considered necessary at no extra cost to BHEL.
6.10.5	Progress review meetings will be held at site during which actual progress during the week vis-a-vis scheduled program shall be discussed for actions to be taken for achieving targets. Contractor shall also present the program for subsequent week. The contractor shall constantly update / revise his work program to meet the overall requirement. All quality problems shall also be discussed during above review meetings. Necessary preventive and corrective action shall be discussed and decided upon in such review meetings and shall be implemented by the contractor in time bound manner so as to eliminate the cause of nonconformities.
6.10.6	The contractor shall submit quarterly progress reports, manpower reports, cranes availability report and other reports as per Performa considered necessary by the Engineer. The periodicity of the reports will be decided by BHEL Engineer at site.
6.10.7	The contractor shall submit quarterly statement report regarding consumption of all consumables for cost analysis purposes.
6.10.8	The contractor shall submit a report of any damage, shortage, discrepancy etc., every week detailing in this regard. 'Non-submission of report' would be considered as 'no shortage of materials'.
6.10.9	The manpower reports shall clearly indicate the manpower deployed, category wise specifying also the activities in which they are engaged.
6.11	The monthly report as a booklet shall be submitted at the end of every month and shall contain the following details:-
a	Progress photographs in colour.
b	Erection progress in terms of tonnage, bolting/welding joints, radiography, stress relieving, etc., completed as relevant to the respective work areas against planned.
c	Site Organization chart of engineers & supervisors as on the last day of the month with further mobilization plan.
d	Availability report of cranes.
e	Safety implementation report in the format.
f	Pending material and any other inputs required from BHEL for activities planned during the subsequent month.
6.12	Site Data Digitalisation (SDD): Daily Activity Log, M-Book and Subcontracting Billing Module: -
a	Refer Vendor Portal System with links: for ref. https://pshq.bhel.in/sddvp/
b	Login ID and Password shall be provided by respective package manager.
С	Contractor by clicking 'Daily Work Photos', shall upload area wise photos on daily basis.
d	Contractor by clicking 'Daily Activity Log', shall update site activities on daily basis.

TECHNICAL CONDITIONS OF CONTRACT (TCC) Chapter – VI: TIME SCHEDULE

e	Contractor by clicking 'Measurement Book', shall enter Measurement Book in Format and BOQ.
f	Contractor shall raise their RA Bills along with supporting documents (such as Quality and HR Document - Vetted by Customer Etc.) and checklist through SDD portal only.
g	Contractor shall comply the system requirement.
h	Refer Vendor Manual for further details.
i	Note: The contractor shall be required to provide all facilities including manpower for the aforementioned activities, without any cost implications to the BHEL.
6.13	Agency shall extend all support towards inputs for IPMS system/Project Management consultancy for project monitoring and control.

7.0	Towns of Dovernment
7.0	Terms of Payment:
7.1	Progressive Payment/ Final Payment: The payments for works under the scope of this contract for both the packages shall be operated be as per clause no 2.6; 2.22; 2.23 of General Conditions of Contract, Chapter-X of SCC and below mentioned terms
7.1.1	Documents required for RA Bill:
	GST Complied Invoice of the work done as per approved BBU.
	• WAM -6 for RA Bill.
	Jointly signed Measurement sheet.
	Power of Attorney before submission of Bill.
	 Validity of Bank Guarantees as applicable under the contract.
	Monthly HSE Compliance Certificate certified by BHEL- Safety
	Compliance of guidelines for worker's accommodation/establishment of BHEL-project sites
	 Material re-conciliation statement duly approved by BHEL (bi monthly basis)
	HR/IR compliance documents:
	i. Wages payment sheet as per applicable minimum wages.
	ii. Proof of PF contribution submission.
	iii. Proof of ESI/ WC contribution submission
	iv. Proof of Bonus payment as per Bonus Act if applicable.
	v. Proof of EL payment if applicable.
	vi. Any other statutory document if applicable.
7.1.2	Documents required for Final Bill:
	The final bill is drawn as soon as the entire work is completed. From the final amount due, all amounts already claimed up to the previous running account bill will be deducted. It should be ensured that in the final bill the following additional particulars have been provided:
	Final Bill in WAM-7 Format.
	'No claim' certificate from the contractor.
	 Clearance certificates where ever applicable viz. Clearance Certificates from Customer, various Statutory Authorities like Labour department, PF Authorities, Commercial Tax Department etc.
	 Final Material re-conciliation statement duly approved by BHEL.
	Indemnity Bond as per prescribed format.
	Deviation statement showing the difference between the actuals and as per the contract.

• Final Delay Analysis.

7.1.3 Contractor shall raise their RA Bills along with supporting documents and checklist through BHEL's SDD (Site Data Digitalization) portal or as per instructions of BHEL Engineer only.

The payment for running bills will be released after submission of running bill complete in all respects with all documents. It is the responsibility of the contractor to make his own arrangements for making timely payments towards labour wages, statutory payments, outstanding dues etc. and other dues in the meanwhile. No interest shall be payable for the delayed payment (if any).

Few points of consideration are as below:

- i. The measurements sheets of work done in a month shall be submitted in triplicate duly agreed/signed by BHEL Engineer. The contractor shall extend all necessary assistance for verification of measurements of works without any extra cost.
- ii. Material reconciliation shall be complied on monthly basis.
- **iii.** The RA bill payments are interim payments and bills shall be submitted in prescribed formats.
- **iv.** Recoveries on account of electricity, water, statutory deductions etc. shall be made as per terms of contract.
- v. BHEL will release payment through Electronic Fund Transfer (EFT)/RTGS.
- **vi.** Final bill shall be submitted after completion of works and upon material reconciliation along with all prescribed formats.

Quoted Rates are inclusive of all labour, contractor's equipment, temporary works, consumables and all matters and things of whatsoever nature, charges for Safety Aspects/Compliance to Safety Rules including operations and maintenance services (if applicable) etc., and other services, as identified in the tender Documents, as necessary for the proper execution of the subject work.

7.2 a. Terms of Payment for Erection of structure (BHEL supplied materials), mentioned in MT in BOQ/rate schedule, for both the packages

Progressive Payment against monthly running bills will be made up-to $85\,\%$ of the value of the erected tonnage Pro-rata as per following table.

S no	Description	Percentage
7.2.1	On pre-assembly wherever applicable (if not applicable, this	20%
	portion shall be clubbed with placement in position)	
7.2.2	Placement in position	30%
7.2.3	Alignment with Grouting (wherever applicable)	15%
7.2.4	Welding / bolting / fixing	15%
7.2.5	Readiness of floors for concrete pouring as applicable (if not applicable, then this portion to be paid along with welding/bolting / fixing)	5%
7.2.6	TOTAL	85%

In case, any of the description in not applicable, then the allotted percentage shall be added in subsequent description for payment.

Further 15 % payment on pro-rata basis shall be released on achievement of the following stage / milestones events for the tonnage erected.

S no	Description	Percentage
7.2.7	Structure readiness for EOT load test	5%
7.2.8	Readiness of structure with side cladding in AB row. Payment shall be released on (bay wise) pro rata Basis.	5%
7.2.9	Area cleaning, temporary structures cutting/removal and return of	2%
7.2.7	scrap	
7.2.10	Punch List points/pending points liquidation	2%
7.2.11	Material Reconciliation	1%
7.2.12	TOTAL	15%
	Total of 7.2.6 and 7.2.12	100%

b. Payment of BOIs where, supply and fixing, are in contractor scope shall be done as per item rate mentioned in Bill of quantities/rate schedule

After a Milestone is achieved, allotted percentage shall be added in subsequent erection monthly payments.

7.5 SECURED RECOVERABLE ADVANCES:

Interest Free Secured Mobilization Advance as per GCC Clause No. 2.13.1 will be payable under exceptional circumstances on certification of BHEL Construction Manager at Site. Interest Free Mobilization Advance shall be disbursed in specifically mentioned stages of major respective resource mobilization as specified hereunder:

Package A:

- 1. For Mobilization of 01 no. of Crawler/Tyre Mounted Crane of 80 MT capacity 2.0% of Contract value of package.
- 2. For Mobilization of required T&Ps as per F-14 and resources at site to start the work 1.5% of Contract value of package.
- 3. For Installation and Erection of Site Infrastructure by contractor i.e. site office stores, biourinals etc. 1.5% of Contract value of package.

Package B:

- 1. For Mobilization of 01 no. of Crawler/Tyre Mounted Crane of 80 MT capacity 2.0% of Contract value of package.
- 2. For Mobilization of required T&Ps as per F-14 and at site to start the work 1.5% of Contract value of package.
- 3. For Installation and Erection of Site Infrastructure by contractor i.e. site office stores, biourinals etc. 1.5% of Contract value of package.

Note:

- 1. BHEL Site Construction Manager shall be the deciding authority for assessing the admissibility of advance payment to contractor.
- 2. In case contractor do not fulfil the agreed conditions of payment of 1st mobilization advance, BHEL Site Construction Manager will have the authority to not allow the 2nd mobilization advance to contractor.

8.0	TAXES & DUTIES
8.1	The contractor shall pay all (save the specific exclusions as enumerated in this clause) taxes, fees, license, charges, deposits, duties, tools, royalty, commissions, other charges, etc. which may be levied on the input goods & services consumed and output goods & services delivered in course of his operations in executing the contract. In case BHEL is forced to pay any of such taxes/duties, BHEL shall have the right to recover the same from his bills or otherwise as deemed fit.
	However, provisions regarding GST on output supply (goods/service) and TDS/TCS as per Income Tax Act shall be as per following clauses.
8.2	GST (Goods and Services Tax)
8.2.1	GST as applicable on output supply (goods/services) are excluded from contractor's scope; therefore, contractor's price/rates shall be exclusive of GST. Reimbursement of GST is subject to compliance of following terms and conditions. BHEL shall have the right to deny payment of GST and to recover any loss to BHEL on account of tax, interest, penalty etc. for non-compliance of any of the following condition.
8.2.2	The admissibility of GST, taxes and duties referred in this chapter or elsewhere in the contract shall be limited to direct transactions between BHEL & its Contractor. BHEL shall not consider GST on any transaction other than the direct transaction between BHEL & its Contractor.
8.2.3	Contractor shall obtain prior written consent of BHEL before billing the amount towards such taxes. Where the GST laws permit more than one option or methodology for discharging the liability of tax/levy/duty, BHEL shall have the right to adopt the appropriate one considering the amount of tax liability on BHEL/Client as well as procedural simplicity with regard to assessment of the liability. The option chosen by BHEL shall be binding on the Contractor for discharging the obligation of BHEL in respect of the tax liability to the Contractor.
8.2.4	Contractor has to submit GST registration certificate of the concerned state. Contractor also needs to ensure that the submitted GST registration certificate should be in active status during the entire contract period.
8.2.5	Contractor/Vendor has to issue Invoice/Debit Note/Credit Note indicating HSN/SAC code, Description, Value, Rate, applicable tax and other particulars in compliance with the provisions of relevant GST Act and Rules made thereunder.
8.2.6	Vendor has to submit GST compliant invoice within the due date of invoice as per GST Law. In case of delay, BHEL reserves the right of denial of GST payment if there occurs any hardship to BHEL in claiming the input thereof. In case of goods, vendor has to provide scan copy of invoice & GR/LR/RR to BHEL before movement of goods starts to enable BHEL to meet its GST related compliances. Special care should be taken in case of month end transactions.
8.2.7	Vendor has to ensure that invoice in respect of such services which have been provided/completed on or before end of the month should not bear the date later than last working day of the month in which services are performed.

8.2.8	Subject to other provisions of the contract, GST amount claimed in the invoice shall be released on fulfilment of all the following conditions by the Contractor: -
	a. Supply of goods and/or services have been received by BHEL.
	b. Original Tax Invoice has been submitted to BHEL.
	c. Contractor/Vendor has submitted all the documents required for processing of bill as per contract/ purchase order/ work order.
	d. In cases where e-invoicing provision is applicable, vendor/contractor is required to submit invoice in compliance with e-invoicing provisions of GST Act and Rules made thereunder.
	e. Contractor has filed all the relevant GST return (e.g. GSTR-1, GSTR-3B, etc.) pertaining to the invoice submitted and submit the proof of such return along with immediate subsequent invoice. In case of final invoice/ bill, contractor has to submit proof of such return within fifteen days from the due date of relevant return.
	f. Respective invoice has appeared in BHEL's GSTR - 2A for the month corresponding to the month of invoice and in GSTR-2B of the month in which such invoices has been reported by the contractor along with status of ITC availability as "YES" in GSTR-2B. Alternatively, BG of appropriate value may be furnished which shall be valid at least one month beyond the due date of confirmation of relevant payment of GST on GSTN portal or sufficient security is available to adjust the financial impact in case of any default by the contractor.
	g. Contractor has to submit an undertaking confirming the payment of all due GST in respect of invoices pertaining to BHEL.
8.2.9	Any financial loss arises to BHEL on account of failure or delay in submission of any document as per contract/purchase order/work order at the time of submission of Tax invoice to BHEL, shall be deducted from contractor's bill or otherwise as deemed fit.
8.2.10	TDS as applicable under GST law shall be deducted from contractor's bill.
8.2.11	Contractor shall comply with the provisions of e-way bill wherever applicable. Further wherever provisions of GST Act permits, all the e-way bills, road permits etc. required for transportation of goods needs to be arranged by the contractor.
8.2.12	Contractor shall be solely responsible for discharging his GST liability according to the provisions of GST Law and BHEL will not entertain any claim of GST/interest/penalty or any other liability on account of failure of contractor in complying the provisions of GST Law or discharging the GST liability in a manner laid down thereunder.
8.2.13	In case declaration of any invoice is delayed by the vendor in his GST return or any invoice is subsequently amended/altered/deleted on GSTN portal which results in any adverse financial implication on BHEL, the financial impact thereof including interest/penalty shall be recovered from the Contactor's due payment.


8.2.14	Any denial of input credit to BHEL or arising of any tax liability on BHEL due to non-compliance of GST Law by the Contractor in any manner, will be recovered along with liability on account of interest and penalty (if any) from the payments due to the Contactor.
8.2.15	In the event of any ambiguity in GST law with respect to availability of input credit of GST charged on the invoice raised by the contractor or with respect to any other matter having impact on BHEL, BHEL's decision shall be final and binding on the contractor.
8.2.16	Variation in Taxes & Duties:
	Any upward variation in GST shall be considered for reimbursement provided supply of goods and services are made within schedule date stipulated in the contract or approved extended schedule for the reason solely attributable to BHEL. However downward variation shall be subject to adjustment as per actual GST applicability.
	In case the Government imposes any new levy/tax on the output service/goods after price bid opening, the same shall be reimbursed by BHEL at actual. The reimbursement under this clause is restricted to the direct transaction between BHEL and its contactor only and within the contractual delivery period only.
	In case any new tax/levy/duty etc. becomes applicable after the date of Bidder's offer but before opening of the price Bid, the Bidder/Contractor must convey its impact on his price duly substantiated by documentary evidence in support of the same before opening of price bid. Claim for any such impact after opening the price bid will not be considered by BHEL for reimbursement of tax or reassessment of offer.
8.3	Income Tax:
	TDS/TCS as applicable under Income Tax Act, 1961 or rules made thereunder shall be deducted/collected from contractor's bill.

8.4 BOCW Act & Cess Act

8.4.1 BOCW Cess is not to be borne by contractor. Refer Annexure-3 for BOCW Act & Cess Act.

	Annexure-3:
Bidder may please note that the sub-contractor/bidder of BHEL engaging building or construction worker in connection with building or other construction work, are required to follow the procedures enumerated below:	
1.	It shall be the sole responsibility of the contractor as employer to ensure compliance of all the statutory obligations under the Building and other Construction Workers' (Regulation of Employment and Conditions of Service) Act, 1996 and the Building and other Construction Workers' Welfare Cess Act, 1996 and the rules made thereunder.
2.	It shall be sole responsibility of the contractor engaging Building Workers in connection with the building or other construction works in the capacity of employer to apply and obtain registration

	certificate specifying the scope of work under the relevant provisions of the Building and Other Construction Workers' (Regulation of Employment and Conditions of Service) Act, 1996 from the appropriate Authorities.
3.	It shall be responsibility of the contractor to furnish a copy of such Registration Certificate within a period of one month from the date of commencement of Work.
4.	It is responsibility of the contractor to register under the Building and other Construction Workers' Welfare Cess Act, 1996 and deposit the required Cess for the purposes of the Building and other Construction Workers' (Regulation of Employment and Conditions of Service) Act, 1996 at such rate as the Central Government may, by notification in the Official Gazette, from time to time specify. However, before registering and deposit of Cess under the Building and other Construction Workers' Welfare Cess Act, 1996, the contractor will seek written prior approval from the Construction Manager.
5.	It shall be sole responsibility of the contractor as employer to get registered every Building Worker, who is between the age of 18 to 60 years of age and who has been engaged in any building or other construction work for not less than ninety days during the preceding twelve months as Beneficiary under the Building and other Construction Workers' (Regulation of Employment and Conditions of Service) Act, 1996.
6.	It shall be sole responsibility of the contractor as employer to maintain all the registers, records, notices and submit returns under the Building and other Construction Workers' (Regulation of Employment and Conditions of Service) Act, 1996 and the Building and other Construction Workers' Welfare Cess Act, 1996 and the rules made thereunder.
7.	It shall be sole responsibility of the contractor as employer to provide notice of poisoning or occupation notifiable diseases, to report of accident and dangerous occurrences to the concerned authorities under the Building and other Construction Workers' (Regulation of Employment and Conditions of Service) Act, 1996 and the rules made thereunder and to make payment of all statutory payments & compensation under the Employees' Compensation Act, 1923.
8.	It shall be the responsibility of the sub-contractor as employer to make payment/deposit of applicable cess amount on the extent of work involving building or construction workers engaged by the sub-contractor within a period of one month from the receipt of payment. It shall also be responsibility of the Contractor to furnish BHEL on monthly basis, Receipts/ Challans towards Deposit of the Cess under the Building and other Construction Workers' Welfare Cess Act, 1996 and the rules made thereunder along with following statistics:
	 i) Number of Building Workers employed during preceding one month. ii) Number of Building workers registered as Beneficiary during preceding one month. iii) Disbursement of Wages made to the Building Workers for preceding wage month. iv) Remittance of Contribution of Beneficiaries made during the preceding month



9.1	Bill of Quantities (BOQ) as per scope of work is listed as below.
9.2	The weights/Quantities/dimensions mentioned are approximate and are liable to vary as per design consideration. There will be change in weight, description etc. However, payments will be made for the tonnage actually erected as per the quoted rate. Quantity Variation will be dealt as per clause 2.14 of General Conditions of Contract.
9.3	Rate Schedule Identified are based on envisaged material specification. Payment shall be made on the basis of material specification of actual material received and erected at site. BHEL's decision in this regard shall be final.

	2X800MW NTPC SINGRAUL	I STPP STA	GE-III		
	BOQ FOR STEEL STRUCTURE PH-1	&2, CCR AN	ND IT'S BOI	S	
ST NO.	Item Description	Unit	Total Quantity (Pkg- A+Pkg-B)	Quantity Package-A (PH1)	Quantity Package-B (CCR+PH2)
A.	Erection/Installation of items mentioned hereunder (Supply under BHEL Scope)				
2300	STRUCTURAL WORKS: Structural steel Erection works including all labour, material, consumables, T&Ps (unless otherwise specified in BOQ/TCC contract specification), handling etc. at all level as per specification, drawings and as directed by engineer - in - charge.				
A2301	Taking delivery of steel from BHEL stores / store yard, loading, transportation, unloading, preassembly and erection, bolting, welding of shop fabricated Medium and High Tensile structural steel (Grade designation E250/E350, conforming to IS 2062, with rolled section / built up section / combination of both conforming to IS:2062, pipes conforming to IS:1161/ IS:1239, chequered plate conforming to IS:3052, mild steel rounds, monorails, stays, safety chains, ladders, MS grating etc. in columns, beams, gantry girders, bunkers, silos, hoppers, roof trusses, portals, laced purlins, space frames, hangers, struts, monorails, galleries, stiffeners, wall beams, sheeting runners, brackets, stub columns, bracings, cleats, trestles, base plates, splice plates, chequered plate flooring, decking and seal plates, steel frame grid over false ceiling, walkway platforms, ladders, stairs, stringers, toeguard/kick plate, grizzly gratings, treads, landings, hand-rails etc., welding electrodes and other	MT	18,482.0	7,291.0	11,191.0

1		T	ı	T	
	consumables, alignment, erection bolts & nuts (weight of erection bolts, nuts and welds not payable), assembly, edge preparation, erection scheme, protection against damage in transit, stability of structures, installation of temporary structures, setting column bases, surface preparation by means of manual or mechanical power tools as per IS:1477 part 1, rectification, dismantling and removal of all temporary structures (weight of temporary structures not payable)				
2307	Transportation, erection and alignment, fabrication where required of factory made electroforged galvanised grating units with mild steel having minimum galvanisation conforming to IS:2062 in flooring, platforms, drain and trench covers, walkways, passages, staircases with edge binding strips and anti-skid nosing in treads etc. including fixing clamps, fittings, fixtures, all taxes, duties, packing, grinding, drilling, welding, edge preparation, etc. all complete.				
a	Minimum galvanisation of 610 g/sqm	MT	407.0	162.8	244.2
2308	Transportation, erection and alignment, fabrication where required of factory made galvanised welded grating units (minimum 610 g/sqm galvanisation) with mild steel conforming to IS:2062 in flooring, platforms, drain and trench covers, walk-ways, passages, staircases with edge binding strips and anti-skid nosing in treads etc. fixing clamps, fittings, fixtures, all taxes, duties, packing, grinding, drilling, welding, edge preparation, etc. all complete.	MT	0.5	0.3	0.3
2311	Fixing in position of permanent mild steel bolts (class 4.6 as per IS: 1367 and grade `C' as per IS: 1363) and nuts, washers etc. up to and inclusive of 39 mm diameter and upto 300mm long for structural steel work etc all complete.	MT	1.8	0.7	1.1
2312	Fixing in positing of high strength structural bolts (of property class 8.8 and product grade `C' as per IS: 1367) and conforming to IS: 3757 and high strength structural hardened and tempered nuts (of property class `8' as per IS:1367) conforming to IS:6623 with hardened and tempered washers as per IS:6649 etc. up to and inclusive of 39 mm diameter and upto 300 mm long for structural steel work etc all complete.	MT	277.2	110.9	166.3

A2312	Fixing in positing of high strength structural bolts (of	MT	462.1	184.8	277.2
	property class 10.8/10.9 and product grade `C' as				
	per IS: 1367) and conforming to IS: 3757 and high				
	strength structural hardened and tempered nuts (of				
	property class `8' as per IS:1367) conforming to				
	IS:6623 with hardened and tempered washers as per				
	IS:6649 etc. up to and inclusive of 39 mm diameter				
	and upto 300 mm long for structural steel work etc				
	all complete.				
2320	Fabrication and fixing of stainless steel pipe hand	MT	11.0	4.4	6.6
	railing conforming to SS 409 of 32 mm/40 mm dia				
	including transportation, loading/unloading,				
	painting etc. all complete.				
A2322	Fabrication and fixing of galvanised MS pipe hand	MT	30.0	12.0	18.0
	railing (Min. 1000 mm high) of				
	32mm/40mm/50mm dia (Medium Class) including				
	transportation, loading/unloading, painting etc. all				
	complete				
1500	ROOFING / SIDE CLADDING: Roofing / side				
	cladding work including all labour, material,				
	consumables, T&Ps (unless otherwise specified				
	in BOQ/TCC contract specification), equipment,				
	transportation, handling, scaffolding, laps,				
	hooks, washers, corner pieces etc. at all level as				
	per specification, drawings and as directed by				
	engineer - in - charge.				

A1502 M	IETAL DECK SHEET Type-I, Fixing permanently				
co	olor coated galvanised MS troughed metal sheet				
	ecking plate (including preparing erection				
	rawings showing cut outs, fixing details, overlaps of				
	heets etc. and getting it approved from BHEL) of				
	pproved colour over roof purlins for cast-in-situ				
	pof slab as per relevant IS code and Grade as per				
	pecification. Bare metal thickness(BMT) of deck				
	late shall be minimum 0.8mm with minimum				
	rough depth of 44mm (or as per design whiever is				
	igher) of grade G250 as per AS1397/grade SS255				
	s per ASTM A653M/ grade S250GD as per EN 10326				
	vith zinc coating to class Z275 and shall serve as				
	ermanent shuttering to the roof slab 40mm -				
10	00mm thick measured over crest of metal decking				
&	shall have adequate strength to support weight of				
gr	reen concrete and imposed loads of min 100				
-	g/sqm (for two span condition) during				
	onstruction between beams as per manufacturer's				
	ecommendations/ calculations/ test certificates for				
	pproval including fixing of plates to beams, side				
1 -	upping, end lapping etc. all complete for below				
	nentioned spans. The sheet shall be permanently				
	pated with silicon modified polyster(SMP silicon				
	ontent 30%-50%) paint or super polyster paint of				
	ninimum 20 micron DFT on exposed surface (facing				
	perating floor) over primer coat of minimum 5				
	nicron(nominal) and minum 10 micron (nominal)				
	MP or super polyester paint over primer coat of				
	ninum 5 micron (nominal) on other face. SMP and				
	olyster paint system sahll be of idutrial finish of				
	roduct type 4 of AS/NZ2728, including fixing of				
sh	neet to top flange of beam with drawn arc welding				
of	f headed shear anchor studs @ 260mm c/c in the				
tro	ough and stich screws between two adjacent				
sh	neets and sealing with epoxy sealant.The shear				
	nchor studs shall confirm to type B studs specified				
in	n AWS D1.1/D1.1M or equivalent as shear				
	onnector of 16 mm dia & 65 mm length				
	nanufactured from cold drawn round steel bars				
1	onfirming to ASTM A 29 of grade designation 1010				
	nrough 1020 of standard quality with either semi				
	illed or killed welded by drawn arc stud welding				
	nrough metal deck sheet. (Metal Deck Sheet shall				
	•				
	e issued by BHEL free of cost) pan Upto 1800mm	MT	86.9	34.7	52.1
	nan unio tauumm	IVI I	เสก.ฯ	1 14 /	17/1

METAL DECK SHEET Type-II, Fixing permanently color coated galvanised MS troughed metal sheet decking plate (including preparing erection drawings showing cut outs, fixing details, overlaps of sheets etc. and getting it approved from BHEL) of approved colour over roof purlins for cast-in-situ roof slab as per relevant IS code and Grade as per specification. Bare metal thickness(BMT) of deck plate shall be minimum 0.8mm with minimum trough depth of 44 mm (or as per design whiver is higher) of grade G250 as per AS1397/grade SS255 as per ASTM A653M/ grade S250GD as per EN 10326 with zinc coating to class 2275 and shall serve as permanent shuttering to the floor slab 150 mm thick measured over crest of metal decking & shall have adequate strength to support weight of green concrete and imposed loads of min 100 kg/sqm (for two span condition) during construction between beams as per manufacturer's recommendations/ calculations/ test certificates for approval including fixing of plates to beams, side lapping, end lapping etc. all complete for below mentioned spans. The sheet shall be permanently coated with silicon modified polyster(SMP silicon content 30%-50%) paint or super polyster paint of minimum 20 micron (pominal) SMP or super polyester paint over primer coat of minimum 5 micron(nominal) and minum 10 micron (nominal) SMP or super polyester paint over primer coat of minimum 5 micron (nominal) on other face. SMP and polyster paint system shall be of idutrial finish of product type 4 of AS/NZ2728, including fixing of sheet to top flange of beam with drawn arc welding of headed shear anchor studs @ 260mm c/c in the trough and stich screws between two adjacent sheets and sealing with epoxy sealant. The shear anchor studs shall confirm to type B studs specified in AWS D1.1/D1.1M or equivalent as shear connector of 19 mm dia & 100 mm length manufactured from cold drawn round steel bars confirming to ASTM A 29 of grade designation 1010 through 1020 of standard quality with either semi killed or killed welded by drawn a						
decking plate (including preparing erection drawings showing cut outs, fixing details, overlaps of sheets etc. and getting it approved from BHEL) of approved colour over roof purlins for cast-in-situ roof slab as per relevant IS code and Grade as per specification. Bare metal thickness(BMT) of deck plate shall be minimum 0.8mm with minimum trough depth of 44 mm (or as per design whiever is higher) of grade G250 as per AS1397/grade SS255 as per ASTM A653M/ grade S250GD as per EN 10326 with zinc coating to class 2275 and shall serve as permanent shuttering to the floor slab 150 mm thick measured over crest of metal decking & shall have adequate strength to support weight of green concrete and imposed loads of min 100 kg/sqm (for two span condition) during construction between beams as per manufacturer's recommendations/ calculations/ test certificates for approval including fixing of plates to beams, side lapping, end lapping etc. all complete for below mentioned spans. The sheet shall be permanently coated with silicon modified polyster(SMP silicon content 30%-50%) paint or super polyster paint of minimum 20 micron DFT on exposed surface (facing operating floor) over primer coat of minimum 5 micron(nominal) and minum 10 micron (nominal) SMP or super polyster paint over primer coat of minim 5 micron (nominal) and minum 10 micron (nominal) SMP or super polyester paint over primer coat of minum 5 micron (nominal) on other face. SMP and polyster paintsystem shall be of idutrial finish of product type 4 of AS/NZ2728, including fixing of sheet to top flange of beam with drawn arc welding of headed shear anchor stude @ 260mm c/c in the trough and stich screws between two adjacent sheets and sealing with epoxy sealant. The shear anchor stude shall confirm to type B stude specified in AWS D1.1/D1.1M or equivalent as shear connector of 19 mm dia & 100 mm length manufactured from cold drawn round steel bars confirming to ASTM A.29 of grade designation 1010 through 1020 of standard quality with either semi killed or killed	B1502	METAL DECK SHEET Type-II, Fixing permanently				
drawings showing cut outs, fixing details, overlaps of sheets etc. and getting it approved from BHEL) of approved colour over roof purlins for cast-in-situ roof slab as per relevant IS code and Grade as per specification. Bare metal thickness(BMT) of deck plate shall be minimum 0.8mm with minimum trough depth of 44 mm (or as per design whiever is higher) of grade G250 as per AS1397/grade SS255 as per ASTM A653M/ grade S250GD as per EN 10326 with zinc coating to class 2275 and shall serve as permanent shuttering to the floor slab 150 mm thick measured over crest of metal decking & shall have adequate strength to support weight of green concrete and imposed loads of min 100 kg/sqm (for two span condition) during construction between beams as per manufacturer's recommendations/ calculations/ test certificates for approval including fixing of plates to beams, side lapping, end lapping etc. all complete for below mentioned spans. The sheet shall be permanently coated with silicon modified polyster(SMP silicon content 30%-50%) paint or super polyster paint of minimum 20 micron DFT on exposed surface (facing operating floor) over primer coat of minimum 5 micron(nominal) and minum 10 micron (nominal) SMP or super polyester paint over primer coat of minum 5 micron(nominal) on other face. SMP and polyster paint system shall be of idutrial finish of product type 4 of AS/NZ2728, including fixing of sheet to top flange of beam with drawn arc welding of headed shear anchor studs @ 260mm c/c in the trough and stich screws between two adjacent sheets and sealing with epoxy sealant. The shear anchor studs shall confirm to type B studs specified in AWS D1.1/D1.1M or equivalent as shear connector of 19 mm dia & 100 mm length manufactured from cold drawn round steel bars confirming to ASTM A 29 of grade designation 1010 through 1020 of standard quality with either semi killed or killed welded by drawn arc stud welding through metal deck sheet. (Metal Deck Sheet shall be issued by BHEL free of cost)		color coated galvanised MS troughed metal sheet				
drawings showing cut outs, fixing details, overlaps of sheets etc. and getting it approved from BHEL) of approved colour over roof purlins for cast-in-situ roof slab as per relevant IS code and Grade as per specification. Bare metal thickness(BMT) of deck plate shall be minimum 0.8mm with minimum trough depth of 44 mm (or as per design whiever is higher) of grade G250 as per AS1397/grade SS255 as per ASTM A653M/ grade S250GD as per EN 10326 with zinc coating to class 2275 and shall serve as permanent shuttering to the floor slab 150 mm thick measured over crest of metal decking & shall have adequate strength to support weight of green concrete and imposed loads of min 100 kg/sqm (for two span condition) during construction between beams as per manufacturer's recommendations/ calculations/ test certificates for approval including fixing of plates to beams, side lapping, end lapping etc. all complete for below mentioned spans. The sheet shall be permanently coated with silicon modified polyster(SMP silicon content 30%-50%) paint or super polyster paint of minimum 20 micron DFT on exposed surface (facing operating floor) over primer coat of minimum 5 micron(nominal) and minum 10 micron (nominal) SMP or super polyester paint over primer coat of minum 5 micron(nominal) on other face. SMP and polyster paint system shall be of idutrial finish of product type 4 of AS/NZ2728, including fixing of sheet to top flange of beam with drawn arc welding of headed shear anchor studs @ 260mm c/c in the trough and stich screws between two adjacent sheets and sealing with epoxy sealant. The shear anchor studs shall confirm to type B studs specified in AWS D1.1/D1.1M or equivalent as shear connector of 19 mm dia & 100 mm length manufactured from cold drawn round steel bars confirming to ASTM A 29 of grade designation 1010 through 1020 of standard quality with either semi killed or killed welded by drawn arc stud welding through metal deck sheet. (Metal Deck Sheet shall be issued by BHEL free of cost)		decking plate (including preparing erection				
sheets etc. and getting it approved from BHEL) of approved colour over roof purlins for cast-in-situ roof slab as per relevant IS code and Grade as per specification. Bare metal thickness(BMT) of deck plate shall be minimum O.8mm with minimum trough depth of 44 mm (or as per design whiever is higher) of grade G250 as per ASI3A97/grade SS255 as per ASITM AGSAM/ grade S250GD as per R103266 with zinc coating to class Z275 and shall serve as permanent shuttering to the floor slab 150 mm thick measured over crest of metal decking & shall have adequate strength to support weight of green concrete and imposed loads of min 100 kg/sqm (for two span condition) during construction between beams as per manufacturer's recommendations/ calculations/ test certificates for approval including fixing of plates to beams, side lapping, end lapping etc. all complete for below mentioned spans. The sheet shall be permanently coated with silicon modified polyster(SMP silicon content 30%-59%) paint or super polyster paint of minimum 20 micron DFT on exposed surface (facing operating floor) over primer coat of minimum 5 micron(nominal) and minum 10 micron (nominal) SMP or super polyester paint over primer coat of minimum 5 micron (nominal) and minum 10 micron (nominal) SMP or super polyester paint over primer coat of sheet to top flange of beam with drawn are welding of headed shear anchor studs @ 260mm c/c in the trough and stich screws between two adjacent sheets and sealing with epoxy sealant. The shear anchor studs shall confirm to type B studs specified in AWS D1.1/D1.1M or equivalent as shear connector of 19 mm dia & 100 mm length manufactured from cold drawn round steel bars confirming to ASTM A 29 of grade designation 1010 through 1020 of standard quality with either semi killed or killed welded by drawn arc stud welding through metal deck sheet. (Metal Deck Sheet shall be issued by BHEL free of cost)						
approved colour over roof purlins for cast-in-situ roof slab as per relevant IS code and Grade as per specification. Bare metal thickness(BMT) of deck plate shall be minimum 0.8mm with minimum trough depth of 44 mm (or as per design whiever is higher) of grade G250 as per AS1397/grade SS255 as per ASTM A653M/ grade S250GD as per EN 10326 with zinc coating to class Z275 and shall serve as permanent shuttering to the floor slab 150 mm thick measured over crest of metal decking & shall have adequate strength to support weight of green concrete and imposed loads of min 100 kg/sqm (for two span condition) during construction between beams as per manufacturer's recommendations/ calculations/ test certificates for approval including fixing of plates to beams, side lapping, end lapping etc. all complete for below mentioned spans. The sheet shall be permanently coated with silicon modified polyster (SMP silicon content 30%-50%) paint or super polyster paint of minimum 20 micron DFT on exposed surface (facing operating floor) over primer coat of minimum 5 micron(nominal) and minum 10 micron (nominal) SMP or super polyester paint over primer coat of minimum 5 micron (nominal) on other face. SMP and polyster paint system sahll be of idutrial finish of product type 4 of AS/NZ2728, including fixing of sheet to top flange of beam with drawn arc welding of headed shear anchor studs @ 260mm c/c in the trough and stich screws between two adjacent sheets and sealing with epoxy scalant. The shear anchor studs shall confirm to type B studs specified in AWS D1.1/D1.1M or equivalent as shear connector of 19 mm dia & 100 mm length manufactured from cold drawn round steel bars confirming to ASTM A 29 of grade designation 1010 through 1020 of standard quality with either semi killed or killed welded by drawn arc stud welding through metal deck sheet. (Metal Deck Sheet shall be issued by BHEL free of cost)						
roof slab as per relevant IS code and Grade as per specification. Bare metal thickness(BMT) of deck plate shall be minimum 0.8mm with minimum trough depth of 44 mm (or as per design whiever is higher) of grade G250 as per AS1397/grade SS255 as per ASTM A653M/ grade S250GD as per EN 10326 with zinc coating to class Z275 and shall serve as permanent shuttering to the floor slab 150 mm thick measured over crest of metal decking & shall have adequate strength to support weight of green concrete and imposed loads of min 100 kg/sqm (for two span condition) during construction between beams as per manufacturer's recommendations/ calculations/ test certificates for approval including fixing of plates to beams, side lapping, end lapping etc. all complete for below mentioned spans. The sheet shall be permanently coated with silicon modified polyster(SMP silicon content 30%-50%) paint or super polyster paint of minimum 20 micron DFT on exposed surface (facing operating floor) over primer coat of minimum 5 micron(nominal) and minum 10 micron (nominal) SMP or super polyester paint over primer coat of minimum 5 micron(nominal) and minum 10 micron (nominal) SMP or super polyester paint over primer coat of minimum 5 micron (nominal) on other face. SMP and polyster paint system sahll be of idutrial finish of product type 4 of AS/NZ2728, including fixing of sheet to top flange of beam with drawn arc welding of headed shear anchor studs @ 260mm c/c in the trough and stich screws between two adjacent sheets and sealing with epoxy sealant. The shear anchor studs shall confirm to type B studs specified in AWS D1.1/D1.1M or equivalent as shear connector of 19 mm dia & 100 mm length manufactured from cold drawn round steel bars confirming to ASTM A 29 of grade designation 1010 through 1020 of standard quality with either semi killed or killed welded by drawn arc stud welding through metal deck sheet. (Metal Deck Sheet shall be issued by BHEL free of cost)						
specification. Bare metal thickness(BMT) of deck plate shall be minimum 0.8mm with minimum trough depth of 44 mm (or as per design whiever is higher) of grade G250 as per AS1397/grade SS255 as per ASTM A653M/ grade S250GD as per EN 10326 with zinc coating to class Z275 and shall serve as permanent shuttering to the floor slab 150 mm thick measured over crest of metal decking & shall have adequate strength to support weight of green concrete and imposed loads of min 100 kg/sqm (for two span condition) during construction between beams as per manufacturer's recommendations/ calculations/ test certificates for approval including fixing of plates to beams, side lapping, end lapping etc. all complete for below mentioned spans. The sheet shall be permanently coated with silicon modified polyster (SMP silicon content 30%-50%) paint or super polyster paint of minimum 20 micron DFT on exposed surface (facing operating floor) over primer coat of minimum 5 micron (nominal) and minum 10 micron (nominal) SMP or super polyester paint over primer coat of minimum 5 micron (nominal) on other face. SMP and polyster paint system sahll be of idutrial finish of product type 4 of AS/NZZ728, including fixing of sheet to top flange of beam with drawn arc welding of headed shear anchor studs @ 260mm c/c in the trough and stich screws between two adjacent sheets and sealing with epoxy sealant. The shear anchor studs shall confirm to type B studs specified in AWS D1.1/D1.1M or equivalent as shear connector of 19 mm dia & 100 mm length manufactured from cold drawn round steel bars confirming to ASTM A 29 of grade designation 1010 through 1020 of standard quality with either semi killed or killed welded by drawn arc stud welding through metal deck sheet. (Metal Deck Sheet shall be issued by BHEL free of cost)						
plate shall be minimum 0.8mm with minimum trough depth of 44 mm (or as per design whiever is higher) of grade G250 as per AST397/grade SS255 as per ASTM A653M/ grade S250GD as per EN 10326 with zinc coating to class Z275 and shall serve as permanent shuttering to the floor slab 150 mm thick measured over crest of metal decking & shall have adequate strength to support weight of green concrete and imposed loads of min 100 kg/sqm (for two span condition) during construction between beams as per manufacturer's recommendations/ calculations/ test certificates for approval including fixing of plates to beams, side lapping, end lapping etc. all complete for below mentioned spans. The sheet shall be permanently coated with silicon modified polyster(SMP silicon content 30%-50%) paint or super polyster paint of minimum 20 micron DFT on exposed surface (facing operating floor) over primer coat of minimum 5 micron(nominal) and minum 10 micron (nominal) SMP or super polyester paint over primer coat of minimum 5 micron (nominal) and minum 10 micron (nominal) SMP or super polyester paint over primer coat of minum 5 micron (nominal) on other face. SMP and polyster paint system sahll be of idutrial finish of product type 4 of AS/NZ2728, including fixing of sheet to top flange of beam with drawn arc welding of headed shear anchor studs @ 260mm c/c in the trough and stich screws between two adjacent sheets and sealing with epoxy sealant. The shear anchor studs shall confirm to type B studs specified in AWS D1.1/D1.1M or equivalent as shear connector of 19 mm dia & 100 mm length manufactured from cold drawn round steel bars confirming to ASTM A 29 of grade designation 1010 through 1020 of standard quality with either semi killed or killed welded by drawn arc stud welding through metal deck sheet. (Metal Deck Sheet shall be issued by BHEL free of cost)						
trough depth of 44 mm (or as per design whiever is higher) of grade G250 as per AS1397/grade S2555 as per ASTM A653M/ grade S250GD as per EN 10326 with zinc coating to class Z275 and shall serve as permanent shuttering to the floor slab 150 mm thick measured over crest of metal decking & shall have adequate strength to support weight of green concrete and imposed loads of min 100 kg/sgm (for two span condition) during construction between beams as per manufacturer's recommendations/ calculations/ test certificates for approval including fixing of plates to beams, side lapping, end lapping etc. all complete for below mentioned spans. The sheet shall be permanently coated with silicon modified polyster(SMP silicon content 30%-50%) paint or super polyster paint of minimum 20 micron DFT on exposed surface (facing operating floor) over primer coat of minimum 5 micron(nominal) and minum 10 micron (nominal) SMP or super polyester paint over primer coat of minum 5 micron (nominal) on other face. SMP and polyster paint system sahll be of idutrial finish of product type 4 of AS/NZ2728, including fixing of sheet to top flange of beam with drawn arc welding of headed shear anchor studs @ 260mm c/c in the trough and stich screws between two adjacent sheets and sealing with epoxy sealant. The shear anchor studs shall confirm to type B studs specified in AWS D1.1/D1.1M or equivalent as shear connector of 19 mm dia & 100 mm length manufactured from cold drawn round steel bars confirming to ASTM A 29 of grade designation 1010 through 1020 of standard quality with either semi killed or killed welded by drawn arc stud welding through metal deck sheet. (Metal Deck Sheet shall be issued by BHEL free of cost)						
higher) of grade G250 as per AS1397/grade S255 as per ASTM A653M/grade S250GD as per EN 10326 with zinc coating to class Z275 and shall serve as permanent shuttering to the floor slab 150 mm thick measured over crest of metal decking & shall have adequate strength to support weight of green concrete and imposed loads of min 100 kg/sqm (for two span condition) during construction between beams as per manufacturer's recommendations/ calculations/ test certificates for approval including fixing of plates to beams, side lapping, end lapping etc. all complete for below mentioned spans. The sheet shall be permanently coated with silicon modified polyster(SMP silicon content 30%-50%) paint or super polyster paint of minimum 20 micron DFT on exposed surface (facing operating floor) over primer coat of minimum 5 micron(nominal) and minum 10 micron (nominal) SMP or super polyester paint over primer coat of minum 5 micron (nominal) on other face. SMP and polyster paint system sahll be of idutrial finish of product type 4 of AS/NZ2728, including fixing of sheet to top flange of beam with drawn arc welding of headed shear anchor studs @ 260mm c/c in the trough and stich screws between two adjacent sheets and sealing with epoxy sealant. The shear anchor studs shall confirm to type B studs specified in AWS D1.1/D1.1M or equivalent as shear connector of 19 mm dia & 100 mm length manufactured from cold drawn round steel bars confirming to ASTM A 29 of grade designation 1010 through 1020 of standard quality with either semi killed or killed welded by drawn arc stud welding through metal deck sheet. (Metal Deck Sheet shall be issued by BHEL free of cost) a Span Upto 1800mm MT 362.5 145.0 217.5						
as per ASTM A653M/ grade S250GD as per EN 10326 with zinc coating to class Z275 and shall serve as permanent shuttering to the floor slab 150 mm thick measured over crest of metal decking & shall have adequate strength to support weight of green concrete and imposed loads of min 100 kg/sqm (for two span condition) during construction between beams as per manufacturer's recommendations/ calculations/ test certificates for approval including fixing of plates to beams, side lapping, end lapping etc. all complete for below mentioned spans. The sheet shall be permanently coated with silicon modified polyster (SMP silicon content 30%-50%) paint or super polyster paint of minimum 20 micron DFT on exposed surface (facing operating floor) over primer coat of minimum 5 micron (nominal) and minum 10 micron (nominal) SMP or super polyester paint over primer coat of minum 5 micron (nominal) on other face. SMP and polyster paint system sahll be of idutrial finish of product type 4 of AS/NZZ728, including fixing of sheet to top flange of beam with drawn arc welding of headed shear anchor studs @ 260mm c/c in the trough and stich screws between two adjacent sheets and sealing with epoxy sealant. The shear anchor studs shall confirm to type B studs specified in AWS D1.1/D1.1M or equivalent as shear connector of 19 mm dia & 100 mm length manufactured from cold drawn round steel bars confirming to ASTM A 29 of grade designation 1010 through 1020 of standard quality with either semi killed or killed welded by drawn arc stud welding through metal deck sheet. (Metal Deck Sheet shall be issued by BHEL free of cost) a Span Upto 1800mm MT 362.5 145.0 217.5						
with zinc coating to class Z275 and shall serve as permanent shuttering to the floor slab 150 mm thick measured over crest of metal decking & shall have adequate strength to support weight of green concrete and imposed loads of min 100 kg/sqm (for two span condition) during construction between beams as per manufacturer's recommendations/ calculations/ test certificates for approval including fixing of plates to beams, side lapping, end lapping etc. all complete for below mentioned spans. The sheet shall be permanently coated with silicon modified polyster (SMP silicon content 30%-50%) paint or super polyster paint of minimum 20 micron DFT on exposed surface (facing operating floor) over primer coat of minimum 5 micron(nominal) and minum 10 micron (nominal) SMP or super polyester paint over primer coat of minum 5 micron (nominal) on other face. SMP and polyster paint system sahll be of idutrial finish of product type 4 of AS/NZ2728, including fixing of sheet to top flange of beam with drawn arc welding of headed shear anchor studs @ 260mm c/c in the trough and stich screws between two adjacent sheets and sealing with epoxy sealant. The shear anchor studs shall confirm to type B studs specified in AWS D1.1/D1.1M or equivalent as shear connector of 19 mm dia & 100 mm length manufactured from cold drawn round steel bars confirming to ASTM A 29 of grade designation 1010 through 1020 of standard quality with either semi killed or killed welded by drawn arc stud welding through metal deck sheet. (Metal Deck Sheet shall be issued by BHEL free of cost) a Span Upto 1800mm MT 362.5 145.0 217.5						
permanent shuttering to the floor slab 150 mm thick measured over crest of metal decking & shall have adequate strength to support weight of green concrete and imposed loads of min 100 kg/sqm (for two span condition) during construction between beams as per manufacturer's recommendations/ calculations/ test certificates for approval including fixing of plates to beams, side lapping, end lapping etc. all complete for below mentioned spans. The sheet shall be permanently coated with silicon modified polyster (SMP silicon content 30%-50%) paint or super polyster paint of minimum 20 micron DFT on exposed surface (facing operating floor) over primer coat of minimum 5 micron (nominal) and minum 10 micron (nominal) SMP or super polyester paint over primer coat of minum 5 micron (nominal) on other face. SMP and polyster paint system sahll be of idutrial finish of product type 4 of AS/NZ2728, including fixing of sheet to top flange of beam with drawn arc welding of headed shear anchor studs @ 260mm c/c in the trough and stich screws between two adjacent sheets and sealing with epoxy sealant. The shear anchor studs shall confirm to type B studs specified in AWS D1.1/D1.1M or equivalent as shear connector of 19 mm dia & 100 mm length manufactured from cold drawn round steel bars confirming to ASTM A 29 of grade designation 1010 through 1020 of standard quality with either semi killed or killed welded by drawn arc stud welding through metal deck sheet. (Metal Deck Sheet shall be issued by BHEL free of cost) a Span Upto 1800mm MT 362.5 145.0 217.5		, , ,				
measured over crest of metal decking & shall have adequate strength to support weight of green concrete and imposed loads of min 100 kg/sqm (for two span condition) during construction between beams as per manufacturer's recommendations/ calculations/ test certificates for approval including fixing of plates to beams, side lapping, end lapping etc. all complete for below mentioned spans. The sheet shall be permanently coated with silicon modified polyster(SMP silicon content 30%-50%) paint or super polyster paint of minimum 20 micron DFT on exposed surface (facing operating floor) over primer coat of minimum 5 micron(nominal) and minum 10 micron (nominal) SMP or super polyester paint over primer coat of minum 5 micron (nominal) on other face. SMP and polyster paint system sahll be of idutrial finish of product type 4 of AS/NZ2728, including fixing of sheet to top flange of beam with drawn arc welding of headed shear anchor studs @ 260mm c/c in the trough and stich screws between two adjacent sheets and sealing with epoxy sealant. The shear anchor studes shall confirm to type B studs specified in AWS D1.1/D1.1M or equivalent as shear connector of 19 mm dia & 100 mm length manufactured from cold drawn round steel bars confirming to ASTM A 29 of grade designation 1010 through 1020 of standard quality with either semi killed or killed welded by drawn arc stud welding through metal deck sheet. (Metal Deck Sheet shall be issued by BHEL free of cost) a Span Upto 1800mm MT 362.5 145.0 217.5						
adequate strength to support weight of green concrete and imposed loads of min 100 kg/sqm (for two span condition) during construction between beams as per manufacturer's recommendations/calculations/ test certificates for approval including fixing of plates to beams, side lapping, end lapping etc. all complete for below mentioned spans. The sheet shall be permanently coated with silicon modified polyster(SMP silicon content 30%-50%) paint or super polyster paint of minimum 20 micron DFT on exposed surface (facing operating floor) over primer coat of minimum 5 micron(nominal) and minum 10 micron (nominal) SMP or super polyester paint over primer coat of minum 5 micron (nominal) on other face. SMP and polyster paint system sahll be of idutrial finish of product type 4 of AS/NZ2728, including fixing of sheet to top flange of beam with drawn arc welding of headed shear anchor studs @ 260mm c/c in the trough and stich screws between two adjacent sheets and sealing with epoxy sealant.The shear anchor studs shall confirm to type B studs specified in AWS D1.1/D1.1M or equivalent as shear connector of 19 mm dia & 100 mm length manufactured from cold drawn round steel bars confirming to ASTM A 29 of grade designation 1010 through 1020 of standard quality with either semi killed or killed welded by drawn arc stud welding through metal deck sheet. (Metal Deck Sheet shall be issued by BHEL free of cost) a Span Upto 1800mm MT 362.5 145.0 217.5						
concrete and imposed loads of min 100 kg/sqm (for two span condition) during construction between beams as per manufacturer's recommendations/ calculations/ test certificates for approval including fixing of plates to beams, side lapping, end lapping etc. all complete for below mentioned spans. The sheet shall be permanently coated with silicon modified polyster(SMP silicon content 30%-50%) paint or super polyster paint of minimum 20 micron DFT on exposed surface (facing operating floor) over primer coat of minimum 5 micron(nominal) and minum 10 micron (nominal) SMP or super polyester paint over primer coat of minum 5 micron (nominal) on other face. SMP and polyster paint system sahll be of idutrial finish of product type 4 of AS/NZ2728, including fixing of sheet to top flange of beam with drawn arc welding of headed shear anchor studs @ 260mm c/c in the trough and stich screws between two adjacent sheets and sealing with epoxy sealant. The shear anchor studs shall confirm to type B studs specified in AWS D1.1/D1.1M or equivalent as shear connector of 19 mm dia & 100 mm length manufactured from cold drawn round steel bars confirming to ASTM A 29 of grade designation 1010 through 1020 of standard quality with either semi killed or killed welded by drawn arc stud welding through metal deck sheet. (Metal Deck Sheet shall be issued by BHEL free of cost) a Span Upto 1800mm MT 362.5 145.0 217.5		measured over crest of metal decking & shall have				
concrete and imposed loads of min 100 kg/sqm (for two span condition) during construction between beams as per manufacturer's recommendations/ calculations/ test certificates for approval including fixing of plates to beams, side lapping, end lapping etc. all complete for below mentioned spans. The sheet shall be permanently coated with silicon modified polyster(SMP silicon content 30%-50%) paint or super polyster paint of minimum 20 micron DFT on exposed surface (facing operating floor) over primer coat of minimum 5 micron(nominal) and minum 10 micron (nominal) SMP or super polyester paint over primer coat of minum 5 micron (nominal) on other face. SMP and polyster paint system sahll be of idutrial finish of product type 4 of AS/NZ2728, including fixing of sheet to top flange of beam with drawn arc welding of headed shear anchor studs @ 260mm c/c in the trough and stich screws between two adjacent sheets and sealing with epoxy sealant. The shear anchor studs shall confirm to type B studs specified in AWS D1.1/D1.1M or equivalent as shear connector of 19 mm dia & 100 mm length manufactured from cold drawn round steel bars confirming to ASTM A 29 of grade designation 1010 through 1020 of standard quality with either semi killed or killed welded by drawn arc stud welding through metal deck sheet. (Metal Deck Sheet shall be issued by BHEL free of cost) a Span Upto 1800mm MT 362.5 145.0 217.5		adequate strength to support weight of green				
two span condition) during construction between beams as per manufacturer's recommendations/ calculations/ test certificates for approval including fixing of plates to beams, side lapping, end lapping etc. all complete for below mentioned spans. The sheet shall be permanently coated with silicon modified polyster(SMP silicon content 30%-50%) paint or super polyster paint of minimum 20 micron DFT on exposed surface (facing operating floor) over primer coat of minimum 5 micron(nominal) and minum 10 micron (nominal) SMP or super polyester paint over primer coat of minimum 5 micron (nominal) on other face. SMP and polyster paint system sahll be of idutrial finish of product type 4 of AS/NZ2728, including fixing of sheet to top flange of beam with drawn arc welding of headed shear anchor studs @ 260mm c/c in the trough and stich screws between two adjacent sheets and sealing with epoxy sealant. The shear anchor studs shall confirm to type B studs specified in AWS D1.1/D1.1M or equivalent as shear connector of 19 mm dia & 100 mm length manufactured from cold drawn round steel bars confirming to ASTM A 29 of grade designation 1010 through 1020 of standard quality with either semi killed or killed welded by drawn arc stud welding through metal deck sheet. (Metal Deck Sheet shall be issued by BHEL free of cost) a Span Upto 1800mm MT 362.5 145.0 217.5						
beams as per manufacturer's recommendations/ calculations/ test certificates for approval including fixing of plates to beams, side lapping, end lapping etc. all complete for below mentioned spans. The sheet shall be permanently coated with silicon modified polyster(SMP silicon content 30%-50%) paint or super polyster paint of minimum 20 micron DFT on exposed surface (facing operating floor) over primer coat of minimum 5 micron(nominal) and minum 10 micron (nominal) SMP or super polyester paint over primer coat of minum 5 micron (nominal) on other face. SMP and polyster paint system sahll be of idutrial finish of product type 4 of AS/NZ2728, including fixing of sheet to top flange of beam with drawn arc welding of headed shear anchor studs @ 260mm c/c in the trough and stich screws between two adjacent sheets and sealing with epoxy sealant.The shear anchor studs shall confirm to type B studs specified in AWS D1.1/D1.1M or equivalent as shear connector of 19 mm dia & 100 mm length manufactured from cold drawn round steel bars confirming to ASTM A 29 of grade designation 1010 through 1020 of standard quality with either semi killed or killed welded by drawn arc stud welding through metal deck sheet. (Metal Deck Sheet shall be issued by BHEL free of cost) a Span Upto 1800mm MT 362.5 145.0 217.5						
calculations/ test certificates for approval including fixing of plates to beams, side lapping, end lapping etc. all complete for below mentioned spans. The sheet shall be permanently coated with silicon modified polyster (SMP silicon content 30%-50%) paint or super polyster paint of minimum 20 micron DFT on exposed surface (facing operating floor) over primer coat of minimum 5 micron(nominal) and minum 10 micron (nominal) SMP or super polyester paint over primer coat of minum 5 micron (nominal) on other face. SMP and polyster paint system sahll be of idutrial finish of product type 4 of AS/NZ2728, including fixing of sheet to top flange of beam with drawn arc welding of headed shear anchor studs @ 260mm c/c in the trough and stich screws between two adjacent sheets and sealing with epoxy sealant. The shear anchor studs shall confirm to type B studs specified in AWS D1.1/D1.1M or equivalent as shear connector of 19 mm dia & 100 mm length manufactured from cold drawn round steel bars confirming to ASTM A 29 of grade designation 1010 through 1020 of standard quality with either semi killed or killed welded by drawn arc stud welding through metal deck sheet. (Metal Deck Sheet shall be issued by BHEL free of cost) a Span Upto 1800mm MT 362.5 145.0 217.5						
fixing of plates to beams, side lapping, end lapping etc. all complete for below mentioned spans. The sheet shall be permanently coated with silicon modified polyster(SMP silicon content 30%-50%) paint or super polyster paint of minimum 20 micron DFT on exposed surface (facing operating floor) over primer coat of minimum 5 micron(nominal) and minum 10 micron (nominal) SMP or super polyester paint over primer coat of minum 5 micron (nominal) on other face. SMP and polyster paint system sahll be of idutrial finish of product type 4 of AS/NZ2728, including fixing of sheet to top flange of beam with drawn arc welding of headed shear anchor studs @ 260mm c/c in the trough and stich screws between two adjacent sheets and sealing with epoxy sealant. The shear anchor studs shall confirm to type B studs specified in AWS D1.1/D1.1M or equivalent as shear connector of 19 mm dia & 100 mm length manufactured from cold drawn round steel bars confirming to ASTM A 29 of grade designation 1010 through 1020 of standard quality with either semi killed or killed welded by drawn arc stud welding through metal deck sheet. (Metal Deck Sheet shall be issued by BHEL free of cost) a Span Upto 1800mm MT 362.5 145.0 217.5						
etc. all complete for below mentioned spans. The sheet shall be permanently coated with silicon modified polyster(SMP silicon content 30%-50%) paint or super polyster paint of minimum 20 micron DFT on exposed surface (facing operating floor) over primer coat of minimum 5 micron(nominal) and minum 10 micron (nominal) SMP or super polyester paint over primer coat of minum 5 micron (nominal) on other face. SMP and polyster paint system sahll be of idutrial finish of product type 4 of AS/NZ2728, including fixing of sheet to top flange of beam with drawn arc welding of headed shear anchor studs @ 260mm c/c in the trough and stich screws between two adjacent sheets and sealing with epoxy sealant. The shear anchor studs shall confirm to type B studs specified in AWS D1.1/D1.1M or equivalent as shear connector of 19 mm dia & 100 mm length manufactured from cold drawn round steel bars confirming to ASTM A 29 of grade designation 1010 through 1020 of standard quality with either semi killed or killed welded by drawn arc stud welding through metal deck sheet. (Metal Deck Sheet shall be issued by BHEL free of cost) a Span Upto 1800mm MT 362.5 145.0 217.5						
sheet shall be permanently coated with silicon modified polyster(SMP silicon content 30%-50%) paint or super polyster paint of minimum 20 micron DFT on exposed surface (facing operating floor) over primer coat of minimum 5 micron(nominal) and minum 10 micron (nominal) SMP or super polyester paint over primer coat of minum 5 micron (nominal) on other face. SMP and polyster paint system sahll be of idutrial finish of product type 4 of AS/NZ2728, including fixing of sheet to top flange of beam with drawn arc welding of headed shear anchor studs @ 260mm c/c in the trough and stich screws between two adjacent sheets and sealing with epoxy sealant. The shear anchor studs shall confirm to type B studs specified in AWS D1.1/D1.1M or equivalent as shear connector of 19 mm dia & 100 mm length manufactured from cold drawn round steel bars confirming to ASTM A 29 of grade designation 1010 through 1020 of standard quality with either semi killed or killed welded by drawn arc stud welding through metal deck sheet. (Metal Deck Sheet shall be issued by BHEL free of cost) a Span Upto 1800mm MT 362.5 145.0 217.5						
modified polyster(SMP silicon content 30%-50%) paint or super polyster paint of minimum 20 micron DFT on exposed surface (facing operating floor) over primer coat of minimum 5 micron(nominal) and minum 10 micron (nominal) SMP or super polyester paint over primer coat of minum 5 micron (nominal) on other face. SMP and polyster paint system sahll be of idutrial finish of product type 4 of AS/NZ2728, including fixing of sheet to top flange of beam with drawn arc welding of headed shear anchor studs @ 260mm c/c in the trough and stich screws between two adjacent sheets and sealing with epoxy sealant. The shear anchor studs shall confirm to type B studs specified in AWS D1.1/D1.1M or equivalent as shear connector of 19 mm dia & 100 mm length manufactured from cold drawn round steel bars confirming to ASTM A 29 of grade designation 1010 through 1020 of standard quality with either semi killed or killed welded by drawn arc stud welding through metal deck sheet. (Metal Deck Sheet shall be issued by BHEL free of cost) MT 362.5 145.0 217.5						
paint or super polyster paint of minimum 20 micron DFT on exposed surface (facing operating floor) over primer coat of minimum 5 micron(nominal) and minum 10 micron (nominal) SMP or super polyester paint over primer coat of minum 5 micron (nominal) on other face. SMP and polyster paint system sahll be of idutrial finish of product type 4 of AS/NZ2728, including fixing of sheet to top flange of beam with drawn arc welding of headed shear anchor studs @ 260mm c/c in the trough and stich screws between two adjacent sheets and sealing with epoxy sealant. The shear anchor studs shall confirm to type B studs specified in AWS D1.1/D1.1M or equivalent as shear connector of 19 mm dia & 100 mm length manufactured from cold drawn round steel bars confirming to ASTM A 29 of grade designation 1010 through 1020 of standard quality with either semi killed or killed welded by drawn arc stud welding through metal deck sheet. (Metal Deck Sheet shall be issued by BHEL free of cost) a Span Upto 1800mm MT 362.5 145.0 217.5						
DFT on exposed surface (facing operating floor) over primer coat of minimum 5 micron(nominal) and minum 10 micron (nominal) SMP or super polyester paint over primer coat of minum 5 micron (nominal) on other face. SMP and polyster paint system sahll be of idutrial finish of product type 4 of AS/NZ2728, including fixing of sheet to top flange of beam with drawn arc welding of headed shear anchor studs @ 260mm c/c in the trough and stich screws between two adjacent sheets and sealing with epoxy sealant. The shear anchor studs shall confirm to type B studs specified in AWS D1.1/D1.1M or equivalent as shear connector of 19 mm dia & 100 mm length manufactured from cold drawn round steel bars confirming to ASTM A 29 of grade designation 1010 through 1020 of standard quality with either semi killed or killed welded by drawn arc stud welding through metal deck sheet. (Metal Deck Sheet shall be issued by BHEL free of cost) MT 362.5 145.0 217.5						
primer coat of minimum 5 micron(nominal) and minum 10 micron (nominal) SMP or super polyester paint over primer coat of minum 5 micron (nominal) on other face. SMP and polyster paint system sahll be of idutrial finish of product type 4 of AS/NZ2728, including fixing of sheet to top flange of beam with drawn arc welding of headed shear anchor studs @ 260mm c/c in the trough and stich screws between two adjacent sheets and sealing with epoxy sealant. The shear anchor studs shall confirm to type B studs specified in AWS D1.1/D1.1M or equivalent as shear connector of 19 mm dia & 100 mm length manufactured from cold drawn round steel bars confirming to ASTM A 29 of grade designation 1010 through 1020 of standard quality with either semi killed or killed welded by drawn arc stud welding through metal deck sheet. (Metal Deck Sheet shall be issued by BHEL free of cost) MT 362.5 145.0 217.5						
minum 10 micron (nominal) SMP or super polyester paint over primer coat of minum 5 micron (nominal) on other face. SMP and polyster paint system sahll be of idutrial finish of product type 4 of AS/NZ2728, including fixing of sheet to top flange of beam with drawn arc welding of headed shear anchor studs @ 260mm c/c in the trough and stich screws between two adjacent sheets and sealing with epoxy sealant. The shear anchor studs shall confirm to type B studs specified in AWS D1.1/D1.1M or equivalent as shear connector of 19 mm dia & 100 mm length manufactured from cold drawn round steel bars confirming to ASTM A 29 of grade designation 1010 through 1020 of standard quality with either semi killed or killed welded by drawn arc stud welding through metal deck sheet. (Metal Deck Sheet shall be issued by BHEL free of cost) MT 362.5 145.0 217.5						
paint over primer coat of minum 5 micron (nominal) on other face. SMP and polyster paint system sahll be of idutrial finish of product type 4 of AS/NZ2728, including fixing of sheet to top flange of beam with drawn arc welding of headed shear anchor studs @ 260mm c/c in the trough and stich screws between two adjacent sheets and sealing with epoxy sealant. The shear anchor studs shall confirm to type B studs specified in AWS D1.1/D1.1M or equivalent as shear connector of 19 mm dia & 100 mm length manufactured from cold drawn round steel bars confirming to ASTM A 29 of grade designation 1010 through 1020 of standard quality with either semi killed or killed welded by drawn arc stud welding through metal deck sheet. (Metal Deck Sheet shall be issued by BHEL free of cost) MT 362.5 145.0 217.5		-				
on other face. SMP and polyster paint system sahll be of idutrial finish of product type 4 of AS/NZ2728, including fixing of sheet to top flange of beam with drawn arc welding of headed shear anchor studs @ 260mm c/c in the trough and stich screws between two adjacent sheets and sealing with epoxy sealant. The shear anchor studs shall confirm to type B studs specified in AWS D1.1/D1.1M or equivalent as shear connector of 19 mm dia & 100 mm length manufactured from cold drawn round steel bars confirming to ASTM A 29 of grade designation 1010 through 1020 of standard quality with either semi killed or killed welded by drawn arc stud welding through metal deck sheet. (Metal Deck Sheet shall be issued by BHEL free of cost) MT 362.5 145.0 217.5						
of idutrial finish of product type 4 of AS/NZ2728, including fixing of sheet to top flange of beam with drawn arc welding of headed shear anchor studs @ 260mm c/c in the trough and stich screws between two adjacent sheets and sealing with epoxy sealant. The shear anchor studs shall confirm to type B studs specified in AWS D1.1/D1.1M or equivalent as shear connector of 19 mm dia & 100 mm length manufactured from cold drawn round steel bars confirming to ASTM A 29 of grade designation 1010 through 1020 of standard quality with either semi killed or killed welded by drawn arc stud welding through metal deck sheet. (Metal Deck Sheet shall be issued by BHEL free of cost) MT 362.5 145.0 217.5						
including fixing of sheet to top flange of beam with drawn arc welding of headed shear anchor studs @ 260mm c/c in the trough and stich screws between two adjacent sheets and sealing with epoxy sealant. The shear anchor studs shall confirm to type B studs specified in AWS D1.1/D1.1M or equivalent as shear connector of 19 mm dia & 100 mm length manufactured from cold drawn round steel bars confirming to ASTM A 29 of grade designation 1010 through 1020 of standard quality with either semi killed or killed welded by drawn arc stud welding through metal deck sheet. (Metal Deck Sheet shall be issued by BHEL free of cost) MT 362.5 145.0 217.5						
drawn arc welding of headed shear anchor studs @ 260mm c/c in the trough and stich screws between two adjacent sheets and sealing with epoxy sealant. The shear anchor studs shall confirm to type B studs specified in AWS D1.1/D1.1M or equivalent as shear connector of 19 mm dia & 100 mm length manufactured from cold drawn round steel bars confirming to ASTM A 29 of grade designation 1010 through 1020 of standard quality with either semi killed or killed welded by drawn arc stud welding through metal deck sheet. (Metal Deck Sheet shall be issued by BHEL free of cost) A Span Upto 1800mm MT 362.5 145.0 217.5		of idutrial finish of product type 4 of AS/NZ2728,				
260mm c/c in the trough and stich screws between two adjacent sheets and sealing with epoxy sealant. The shear anchor studs shall confirm to type B studs specified in AWS D1.1/D1.1M or equivalent as shear connector of 19 mm dia & 100 mm length manufactured from cold drawn round steel bars confirming to ASTM A 29 of grade designation 1010 through 1020 of standard quality with either semi killed or killed welded by drawn arc stud welding through metal deck sheet. (Metal Deck Sheet shall be issued by BHEL free of cost) MT 362.5 145.0 217.5		including fixing of sheet to top flange of beam with				
two adjacent sheets and sealing with epoxy sealant. The shear anchor studs shall confirm to type B studs specified in AWS D1.1/D1.1M or equivalent as shear connector of 19 mm dia & 100 mm length manufactured from cold drawn round steel bars confirming to ASTM A 29 of grade designation 1010 through 1020 of standard quality with either semi killed or killed welded by drawn arc stud welding through metal deck sheet. (Metal Deck Sheet shall be issued by BHEL free of cost) A Span Upto 1800mm MT 362.5 145.0 217.5		drawn arc welding of headed shear anchor studs @				
sealant.The shear anchor studs shall confirm to type B studs specified in AWS D1.1/D1.1M or equivalent as shear connector of 19 mm dia & 100 mm length manufactured from cold drawn round steel bars confirming to ASTM A 29 of grade designation 1010 through 1020 of standard quality with either semi killed or killed welded by drawn arc stud welding through metal deck sheet. (Metal Deck Sheet shall be issued by BHEL free of cost) MT 362.5 145.0 217.5		260mm c/c in the trough and stich screws between				
B studs specified in AWS D1.1/D1.1M or equivalent as shear connector of 19 mm dia & 100 mm length manufactured from cold drawn round steel bars confirming to ASTM A 29 of grade designation 1010 through 1020 of standard quality with either semi killed or killed welded by drawn arc stud welding through metal deck sheet. (Metal Deck Sheet shall be issued by BHEL free of cost) A Span Upto 1800mm MT 362.5 145.0 217.5		two adjacent sheets and sealing with epoxy				
B studs specified in AWS D1.1/D1.1M or equivalent as shear connector of 19 mm dia & 100 mm length manufactured from cold drawn round steel bars confirming to ASTM A 29 of grade designation 1010 through 1020 of standard quality with either semi killed or killed welded by drawn arc stud welding through metal deck sheet. (Metal Deck Sheet shall be issued by BHEL free of cost) A Span Upto 1800mm MT 362.5 145.0 217.5						
as shear connector of 19 mm dia & 100 mm length manufactured from cold drawn round steel bars confirming to ASTM A 29 of grade designation 1010 through 1020 of standard quality with either semi killed or killed welded by drawn arc stud welding through metal deck sheet. (Metal Deck Sheet shall be issued by BHEL free of cost) A Span Upto 1800mm MT 362.5 145.0 217.5						
manufactured from cold drawn round steel bars confirming to ASTM A 29 of grade designation 1010 through 1020 of standard quality with either semi killed or killed welded by drawn arc stud welding through metal deck sheet. (Metal Deck Sheet shall be issued by BHEL free of cost) a Span Upto 1800mm MT 362.5 145.0 217.5						
confirming to ASTM A 29 of grade designation 1010 through 1020 of standard quality with either semi killed or killed welded by drawn arc stud welding through metal deck sheet. (Metal Deck Sheet shall be issued by BHEL free of cost) A Span Upto 1800mm MT 362.5 145.0 217.5						
through 1020 of standard quality with either semi killed or killed welded by drawn arc stud welding through metal deck sheet. (Metal Deck Sheet shall be issued by BHEL free of cost) a Span Upto 1800mm MT 362.5 145.0 217.5						
killed or killed welded by drawn arc stud welding through metal deck sheet. (Metal Deck Sheet shall be issued by BHEL free of cost) a Span Upto 1800mm MT 362.5 145.0 217.5						
through metal deck sheet. (Metal Deck Sheet shall be issued by BHEL free of cost) a Span Upto 1800mm MT 362.5 145.0 217.5						
be issued by BHEL free of cost) MT 362.5 145.0 217.5						
a Span Upto 1800mm MT 362.5 145.0 217.5						
			NATE:	2625	1450	2455
b Span Exceeding 1800mm and upto 2500 mm MT 87.3 34.9 52.4						
	b	Span Exceeding 1800mm and upto 2500 mm	MT	87.3	34.9	52.4

A1505	Fixing External/ Inner sheet of Permanent colour	MT	207.5	83.0	124.5
	coated metal cladding / roofing with troughed M.S.				
	sheets of minimum 0.5 mm bare metal thickness of				
	min. grade G350 as per AS1397/grade SS340 class 4				
	or as per ASTM A792M/ grade S350 GD as per EN				
	10326 with zinc coating to class Z275 / aluminium				
	zinc alloy coating to class AZ150 on both sides				
	(including preparing erection drawings showing cut				
	outs, fixing details, overlaps of sheets etc. and getting				
	it approved from BHEL) including fixing to supports				
	/ rails by concealed fixing system, corrosion				
	resistant self tapping / self drilling type fasteners				
	with suitable cap, flashing, etc. all complete over				
	columns, beams, bracings etc. at all levels. The				
	exposed face the sheet shall be permanently coated				
	with silicon modified polyester(SMP silicon content				
	30%-50%) paint or super polyester paint of				
	minimum 20 micron DFT on exposed surface over				
	primer coat of minimum 5 micron and minimum 10				
	micron SMP or super polyester paint over primer				
	coat of minimum 5 micron on other face. SMP tc. all				
	complete for below mentioned spans. The sheet shall				
	be permanently coated. Self drilling/self tapping				
	screws/fastners shall be supplied by contractor.				
	(Cladding/roofing sheet shall be issued by BHEL				
	free of cost)				
A1519	Fixing Factory made (Continuous Line)	MT	75.5	30.2	45.3
AIJI	prefabricated sandwiched Permanent colour coated	141 1	75.5	30.2	43.3
	metal cladding comprising top sheet as				
	troughed(minimum depth of trough shall be 30 mm)				
	(including preparing erection drawings showing cut				
	outs, fixing details, overlaps of sheets etc. and getting				
	it approved from BHEL) permanently colour coated				
	sheet & bottom sheet as plain permanently colour				
	coated for covering of exposed metal/concrete / brick surfaces with insulation shall be of				
	Polyurethane type of minimum 50mm thick				
	(excluding trough). The polyurethane shall be				
	Chlorofluorocarbon (CFC) free and self-				
	extinguishing and shall conform to IS 12436: 1988. It				
	shall have Modular Density 40 +/- 2 Kg/m3 and				
	Thermal Conductivity @ 10 Deg.C 0.017 - 0.020 W/M				
	0k, Water absorption (% by vol) 3.1, Critical Oxygen				
	Index 23 and Compressive Strength 1.2 Kg/sq.cm,				
	sandwiched between the two sheets, each sheet shall				
	be high strength tensile steel sheet 0.5mm bare				
	metal thickness (minimum) of YS350 as per IS 15961 /grade G350 as per AS1397 / grade SS340				

	class 4 as per ASTM A792M / grade S350GD as per				
	EN 10326 with zinc coating to class Z 275 /				
	aluminium-zinc alloy coating to class AZ150 on both				
	sides, both sheet shall be permanently coated with				
	silicon modified polyester (SMP with silicon content				
	of 30% to 50%) paint of minimum 20 micron DFT on				
	exposed surface on 5 microns (min.) epoxy				
	primer/phosphate primer coat and 10 micron (min.)				
	SMP on 5 micron (min.) epoxy primer/phosphate				
	primer on other face, SMP paint system shall be of				
	industrial finish of product type 4 of AS/NZS				
	2728,troughed sheet shall be of approved profile,				
	sectional properties, (suitable for the specified				
	loading / deflection and purlins / runner spacing),				
	colour and shade, at all levels, including all labour,				
	materials, equipment, handling, transportation,				
	special coated fastener conforming to corrosion resistant Class 3 of AS3566 and tested for 1000				
	hours salt spray test, fixing insulated sandwiched				
	metal sheet with the structural members below for				
	supporting the sheeting system, scaffolding,				
	equipment, end and side laps, cutting of openings,				
	preparation of working drawings, testing, etc., all				
	complete, as per specifications. Sealant used for				
	cladding shall be butyl based, two parts poly				
	sulphide or equivalent approved, non stainless				
	material and be flexible enough not to interface with				
	fit of the sheets. Coated surface shall be provided				
	with a protected guard film (polyethylene) of about				
	40 microns to avoid any damage to the coating				
	during handling. Overlap shall be min. 100 mm or as				
	specified by manufacturer. Self drilling/self tapping				
	screws/fastners shall be supplied by contractor.				
	(Cladding/roofing sheet shall be issued by BHEL				
	free of cost)				
			20,491	8,095	12,397
B.	Other items mentioned hereunder				
1004	(Supply+Fixing under contractor scope)	COM	150	(0.0	00.0
A904	Providing and fixing single or double steel door	SQM	150	60.0	90.0
	shutters with 35mm (min) thk flush design shutter				
	comprising of two outer sheets of 18 gauge steel				
	sheets rigidly connected and reinforced inside with				
	continuous vertical 20 gauge stiffeners, spot welded				
	in position at not more than 150mm on centres				
	including void filled with mineral wool (density as per specification), all fittings, Godrej or equivalent				

	make mortice lock with handle on both sides, shop and final painting etc all complete.				
A909	Providing and fixing anodised aluminium work of Jindal, Hindalco or other equivalent approved make for door frames, windows, ventillators, partitions, railing etc with extruded standard tubular and other	Kg	15040	6,016.0	9,024.0
	sections(of minimum 2mm wall thickness) including all fittings & fixtures and accessories of approved make conforming to IS733 and IS1285, anodised and electro color dyed to required shade according to IS 1868 (minimum anodic coating of grade AC15), fixed with rawl plugs, expansion fasteners, SS screws or with fixing clips, including necessary filling of gaps at				
	junctions, at top, bottom and sides with required PVC/neoprene felt for bi-metalic protection etc. including preperation of working drawings, aluminium cleat angle, aluminium snap-on-beading for glazing/panelling, stair case tread nosing, with all fittings and fixtures (like tower bolts, handles, door				
	stopper with rubber shoes, 'L' drops, stays, floor springs, hydraulic door closures etc.), CP brass/stailess steel screws, providing and fixing hinges/pivots, and making provision for fixing of fitting wherever required including cost of				
A912	PVC/neoprene gasket, all complete as per drawing, specification and instructions of engineer in charge (Glazing and panelling shall be paid seperately). Weight of aluminium section only shall be measured Providing and fixing pressed steel	Kg	2976	1,190.4	1,785.6
A)12	Providing and fixing pressed steel frames(complying general requirements of IS 4531) fabricated from 1.2 mm thick M.S sheet mortised, reinforced drilled and tapped for hinges and locks bolts strikes, hold fasts adjustable floor anchors, floor tiles/weather bars, paintings etc all complete as per specifications.	Ιζ	2770	1,170.7	1,703.0

A913	Providing and fixing in position rolling shutter of hot rolled double dipped galvanised steel lath section of 18 SWG tested mild steel strips at 75mm rolling centres interlocked together through their entire length and jointed together at the end by end locks mounted on specially designed pipe shaft with brackets, side guides of 75mm wide and 3mm thick(min.) and arrangements for inside and outside locking with push and pull operation including wire springs, top/hood cover 0.9mm thick (min.), factory galvanized, primed & field painted, partly grilled (as required) with approved enamel paint etc, all complete as per IS 6248 and specification of approved make of following types: The bottom lath shall be coupled to a lock plate fabricated from 3mm thick galvanised steel plate and securely rivetted with stiffening angles.(partly coiled and lath/full lath).				
С	Electrically & Mechanically operated	SQM	350	140.0	210.0
915	Providing, fixing and fitting of glazing of first grade class in steel/aluminium/wooden frames, where ever required, cleaning after fixing including hardware, gaskets, clips, beadings etc. all complete.				
h (a)	6 mm thick clear reflective toughened safety glass of Saint Gobain(India) or Asahi (India) or equivalnet make and should have solar factor 25% or less, Maximum U-vlaue 3.3W/SQMK, VLT min 30%, light reflection internal 10 to 15%, light reflection external 10 to 20%, shading coefficient (0.25-0.28) (including supply)	SQM	1,098	439.0	658.6
Ah	6 mm thick clear toughened glass conforming to IS 5437	SQM	1,115	446.0	669.1
AhB	8 mm thick clear toughened glass	SQM	75	30.0	45.0
AhC	8 mm thick clear toughened fire resistant glass	SQM	75	30.0	45.0
A1503	Providing and fixing shear anchor studs for fixing metal deck sheet to floor structural beams conforming to Type-B studs specified in AWS D1.1/D1.1M or equivalent as shear connector of 19mm diameter and 100mm length manufactured from cold drawn round steel bars conforming to the requirement of ASTM A 29, of grade designation 1010 through 1020, of standard quality with either semi-killed or killed, welded by Drawn Arc Stud Welding through metal deck sheet etc all complete as per specification.	QUINTAL	156	62.4	93.6

B1503	Providing and fixing shear anchor studs for fixing metal deck sheet to roof structural purlins conforming to Type-B studs specified in AWS	QUINTAL	26	10.4	15.6
	D1.1/D1.1M or equivalent as shear connector of				
	16mm diameter and 65mm length manufactured from cold drawn round steel bars conforming to the				
	requirement of ASTM A 29, of grade designation				
	1010 through 1020, of standard quality with either semi-killed or killed, welded by Drawn Arc Stud				
	Welding through metal deck sheet etc all complete as				
12210	per specification.				
A2318	Providing and fixing in position PTFE type sliding bearings of reputed manufacturer for required				
	vertical load and end displacement/rotation as per				
	approved construction draiwngs. PTFE bearing shall be sliding against highly polished stainless steel and				
	the coefficient of friction between them shall be less				
	than 0.06 at 55 kg/sq.cm. In order to prevent cold				
	flow in PTFE surface it shall be rigidly bonded by a special high temperature resistance adhesive to the				
	stainless steel substrata. The stainless steel surface				
	that slides against the PTFE is mirror polished. The				
	stainless steel shall be bonded to the top plate by special high strength adhesive. The thickness of				
	stainless steel plate shall be between 1.0 mm to 1.5				
b	mm. 25 Tons	EACH	10	5.0	5.0
С	40 Tons	EACH	8	4.0	4.0
d	50 Tons	EACH	4	2.0	2.0
e	60 Tons	EACH	6	3.0	3.0
f	100 Tons	EACH	4	2.0	2.0
2328	Supply, fixing lightning arrester and air terminal	EACH	10	5.0	5.0
	over roof of power house building, pump house and				
	other structures inluding all materials, labour, electrodes etc complete (all materials to be supplied				
	by the contractor).				
C.	Touch-up Painting				
i	Surface preparation by means of manual or	MT	1000	500.0	500.0
	mechanical power tools as per IS:1477 part 1, Providing and applying two component moisture				
	curing zinc (ethyl) silicate primer coat (having				
	minimum 80% of metallic Zinc content in dry film,				
	solid by volume minimum 60% ±2%) of minimum 70 micron DFT to be applied over surface conforming to				
	Sa 2 ½ finish of SO 8501-1 with surface profile 40-				
	60 Micron. The primer coat shall be applied by				

	airless spray technique. Zinc dust composition and properties shall be Type-II as per ASTM D520-00 all complete (1 MT = 24 Sqm considered for this tender)				
ii	Surface preparation by means of manual or mechanical power tools as per IS:1477 part 1, Providing and applying (with airless spray technique) intermediate coat of two component polyamide cured epoxy with MIO Content (containing lamellar MIO minimum 30% on pigment, solid by volume minimum 80% ±2%) of minimum 100 micron DFT to be applied after an interval of minimum 24 hours (from the application of primer coat by airless spray technique.) and of approved make including protection and cleaning, scoffolding etc. all complete as per specification for all structures (1 MT = 24 Sqm considered for this tender)	MT	1000	500.0	500.0
iii	Surface preparation by means of manual or mechanical power tools as per IS:1477 part 1, Providing and applying Finish coat of two-pack aliphatic Isocyanate cured acrylic finish paint (solid by volume minimum $55\% \pm 2\%$) with Gloss retention (SSPC Paint Spec No 36, ASTM D 4587, D 2244, D 523) of Level 2 (after minimum 1000 hours exposure, Gloss loss less than 30 and colour change less than 2.0 Δ E) and minimum 70 micron DFT shall be applied after an interval of minimum 10 hours (from the application of sealer coat), Colour and shade of the coat shall be as approved by the Employer) over steel sections already having intermediate coats including protection and cleaning, scoffolding etc. all complete as per specification for all structures . (1 MT = 24 Sqm considered for this tender)	MT	1000	500.0	500.0


10.1	Site Visit
	The bidder shall, prior to submitting his tender for the work, visit and examine the site of works and its surroundings at his own expense, and obtain and ascertain for himself on his own responsibility all information that may be necessary for preparing his tender and entering into a contract, and take the same into account in the quoted contract price for the work.
10.2	
10.2	 i) Site conditions including access to the site, existing and required roads and other means of transport/communication for use by him in connection with the work including diverting and re-routing of services. ii) Requirement and availability of land and other facilities for his enabling works, establishment of his nursery, office, stores etc. iii) Ground conditions including those bearing upon transportation, disposal, handling and storage of materials required for the work or obtained there-from. iv) Source and extent of availability of suitable materials, including drinking water etc., and labour (skilled and unskilled) required for work, and laws and regulations governing their use and employment. v) Geological, meteorological, topographical and other general features of the site and its surroundings as are pertaining to and needed for the performance of the work. vi) The type of equipment and facilities needed, for and in the performance of the work. vii) The extent of lead and lift required for the work in complete form over the entire duration of the contract, and all other information pertaining to and needed for the work including information as to the risks, contingencies and other circumstances, which may influence or affect the work or the cost thereof under this contract.
10.3	The contractor is strictly prohibited from using BHEL's regular components like angles, channels, beams, plates, pipe / tubes, and handrails etc. for any temporary supporting or approach platforms or scaffolding works or as bed for pre-assembly works. Contractor shall arrange himself all such materials. The Contractor shall make all fixtures, temporary supports, steel structures required for jigs & fixtures, anchors for load and guide pulleys required for the work. Contractor shall arrange necessary steel (angles, channels, beams, plates etc) for such usage as normal scope of work without any cost implication on BHEL. In case of such misuse of BHEL materials, a sum as determined by BHEL engineer will be recovered from the contractor's bill. The decision of BHEL engineer is final and binding on the contractor. However, if available with BHEL (in form of scrap/good steel), vendor may be allowed to use on returnable basis on discretion of BHEL.
10.4	Contractors shall ensure that all their Staff / Employees are exposed to periodical training programme conducted by qualified agencies / personnel on ISO 9001 – latest Standards.
10.5	Contractor has to clear the front, expeditiously and promptly as instructed by BHEL Engineer for other agencies, like Civil for casting floors, TG- for Turbine & Generator Erection, Boiler, Piping, Cabling, instrumentation, insulation etc., to commence their work from / on the

	equipments coming under this scope. Sometimes, more than one agencies may have to work
	in same location. Sometimes it may be required to re-schedule the activities to enable other
	agencies to commence / continue the work so as to keep the overall project schedule.
10.6	For the purpose of planning, contractor shall furnish the estimated requirement of power
	(month wise) for execution of work in terms of maximum KW demand.
10.7	All necessary certificates and licenses, permits & clearances to carry out this work from the
	respective authorities/statutory/local authorities/etc are to be arranged by the Contractor,
	if required, at his cost in time to ensure smooth progress of work and render all assistance,
	service required in this regard.
10.8	All registration and statutory inspection fees, if any, in respect of his work pursuant to this
	Contract shall be to the account of the Contractor. However, any registration, statutory
	inspection fees lawfully pay-able under the provisions of any other statutory laws and its
	amendments from time to time during erection in respect of the plant equipment ultimately
	to be owned by the customer, shall be to the account of the customer. Should any such
	inspection or registration need to be re-arranged due to the fault of the Contractor, the
	additional fees for such inspection and/or registration shall be borne by the Contractor.
10.9	The contractor must obtain the signature and permission of the security personnel of the
10.9	customer for bringing any of their materials inside the site premises. Without the Entry Gate
1010	Pass these materials will not be allowed to be taken outside.
10.10	During the course of erection, if the progress is found unsatisfactory, or if the target dates
	fixed from time to time for every milestone are to be advanced, or in the opinion of BHEL, if
	it is found that the skilled workmen like fitters, operators, technicians employed are not
	sufficient BHEL will induct required additional workmen to improve the progress and
	recover all charges incurred on this account including all expenses together with BHEL
	overheads from contractor's bills.
10.11	The intent of specification is to provide services according to the most modern and proven
	techniques and codes. The omission of specific reference to any method, equipment or
	material necessary for proper and efficient execution of this work shall not relieve the
	Contractor of the responsibility of providing such facilities to complete the work without any
	extra compensation.
10.12	Contractor shall erect structure as per the sequence & methodology prescribed by BHEL
	depending upon the technical requirements. Availability of materials and fronts will decide
	this. BHEL Engineer's decision regarding correctness of the work and method of working
	shall be final and binding on the Contractor. No claims for extra payment from the Contractor
	will be entertained on the ground of deviation from the methods / sequence adopted in
	erection of similar sets elsewhere.
10.13	The Contractor shall perform any services, tests etc. which may not be specified but
	nevertheless, required for the completion of work within quoted rates.
10.14	The Contractor shall execute the work in the most substantial and workman like manner.
	The stores shall be handled with care and diligence.

10.15	BHEL reserves right to recover from the Contractor any loss which arises out of undue delay
10.10	/ discrepancy / shortage / damage or any other causes due to Contractor's lapse during any
	stage of work. Any loss to BHEL due to Contractor's lapse shall have to be made good by the
	Contractor as per GCC.
10.16	All works such as cleaning, levelling, aligning, trial assembly, dismantling of certain
10.10	equipments / components for checking and cleaning, surface preparation as per general
	engineering practice and as per BHEL Engineer's instructions at site, cutting, gouging, weld
	depositing, grinding, straightening, chamfering, filing, chipping, drilling, reaming, scrapping,
	lapping, fitting up etc. as may be applicable in such erection works and which are treated
	incidental to the erection works and necessary to complete the work satisfactorily, shall be
10.17	carried out by the Contractor as part of the work within the quoted rates.
10.17	The Contractor shall take delivery of the components, equipment, etc. from the BHEL stores/
	storage area after getting the approval of BHEL Engineer on standard indent forms of BHEL.
	Complete and detailed account of the materials and equipment after usage shall be
	submitted to the BHEL and reconciled periodically.
10.18	Plant materials should not be used for any temporary supports / scaffolding/ preparing pre-
	assembly bed etc. The details of equipments to be erected under this contract are generally
	as per the schedule given in relevant appendices. These details are approximate and meant
	only to give a general idea to the tenderer about the magnitude of the work involved. Actual
	quantum and type of equipments will be based on the relevant erection documents which
	will be furnished to the Contractor in due course of erection and the weight and quantity as
	per the relevant engineering documents will only be admissible for the billing purpose.
10.19	In installation of various equipments it may become necessary to install these on temporary
	supports/ hanger due to various reasons including non-availability of suspension materials.
	Contractor shall install such temporary suspensions/hangers and later on shift the relevant
	equipments to their respective permanent hangers/ suspensions/ supports as incidental to
	work. Requisite materials for such temporary arrangements will be provided by BHEL on
	free -returnable basis which shall be returned to BHEL after the use.
10.20	Interconnection/ hookup, if any, with the existing system shall form part of work. Such
	interconnections, hookups may require shut down of running plant and the relevant work
	have to be completed within such planned shutdowns. This may call for working with
	enhanced resources and on extended hours. Contractor's offer shall cover all such
	contingencies.
10.21	Contractor shall regulate flow of material to and from site in such a manner and sequence,
10.21	that material accumulation at site does not lead to congestion at site. In case it is necessary
	to shift and restack the materials kept at work areas / site to enable other agencies to carry
	out their work or further any other reason, it shall be done by the Contractor most
	expeditiously. No claim for extra payment for such work will be entertained.
10.22	It may so happen that certain components may be supplied in loose conditions. They need
10.22	to be assembled as per relevant drawings or as per advice of BHEL engineer prior to erection.
	This forms the part of the scope of work.

10.23	The Contractor shall have total responsibility for all equipment and materials in his custody
	at Contractor's stores, loose, semi-assembled, assembled or erected by him at site. He shall
	effectively protect the finished works from action of weather and from damages or
	defacement and shall also cover the finished parts immediately on completion of work as per
	BHEL engineer's instructions. The component surfaces should be covered.
10.24	BHEL is operating web based computerized E-store system that includes, inter-alia, issue of
	materials, daily progress reporting, Contractor's running monthly billing and material
	reconciliation through a computerized data management system. Contractor shall install
	necessary hardware to hook-up with the BHEL's system and use the same for his scope of
	work.
	In the event the computerized E-store/SOMS is inoperative for any reasons, the Contractor
	shall take delivery of materials from the storage area/sheds of BHEL/customer after getting
	the approval of the engineer/customer on standard indent forms to be specified by
	BHEL/customer. All these records however shall be updated in the E-store/SOMS as and
	when the E-store/SOMS is reactivated/ normalized.
10.25	Gases like argon, oxygen, acetylene etc that are required for erection related activities shall
	be arranged by the Contractor at his cost.
10.26	It is not the intent to specify herein all details of all material. Any item related this work not
	covered by this but necessary to complete the system will be deemed to have been included
	in the scope of the work.
10.27	Site testing wherever required shall be carried out for all items / materials installed by the
	contractor to ensure proper installation and functioning in accordance with drawings,
	specifications and manufacturer's recommendations.
10.28	The work shall be executed under the usual conditions without affecting power plant
	construction / operation and in conjunction with other operations and contracting agencies
	at site. The contractor and his personnel shall co-operate with the personnel of other
	agencies, co-ordinate his work with others and proceed in a manner that shall not delay or
	hinder the progress of work as a whole.
10.29	Contractor shall, transport all materials to site and unload at site / working area for
	inspection and checking. All material handling equipment required shall be arranged by the
	contractor.
10.30	Contractor shall retain all T&P / Testing instrument / Material handling equipment's etc. at
	site as per advice of BHEL engineer and same shall be taken out from site only after getting
	the clearances from engineer in charge. The contractor at his cost shall arrange necessary
	security measures for adequate protection of his machinery, equipment, tools, materials etc.
	BHEL shall not be responsible for any loss or damage to the contractor's construction
	equipment and materials.

10.31	Housekeeping/Area Cleaning
10.51	The contractor has to do area cleaning on every day on daily basis. Non-compliance of the
	above cleaning shall call for penal recovery on each instance and at the same time, cleaning
	of the area shall be done by BHEL at Cost recovery basis with applicable overheads . No
	excuses on this above account shall be entertained by BHEL on whatsoever account.
	The contractor shall ensure that his premises are always kept clean and tidy to the extent possible. Any untidiness noted on the part of the contractor shall be brought to the attention of the contractor's site representative who shall take immediate action to clean the surroundings to the satisfaction of the Engineer in- Charge. Contractor shall engage separate gangs throughout the contract period, exclusively for proper housekeeping of the site. The contractor has to make necessary arrangements for collection and for bringing down the scrap from all locations and taking them away from the erection areas to various locations as indicated by BHEL Engineer. The house keeping must be a routine and continuous activity at various work fronts.
	Contractor shall remove all scrap materials periodically generated from his working area and collect the same at one place earmarked for the same. Load of scraps is to be shifted to a place earmarked by BHEL. Failure to collect the scrap is likely to lead to accidents and as
	such BHEL reserves the right to collect and remove the scrap at Cost recovery basis with 5%
10.32	overheads, if there is any failure on the part of contractor in this respect. Completion of work, all the temporary buildings, structures, pipe lines, cable etc. shall be
10.32	dismantled and levelled and debris shall be removed as per instruction of BHEL by the
	contractor at his cost. In the event of his failure to do so, the expenditure towards clearance
	of the same will be recovered from the contractor with 5% overhead. The decision of BHEL
	Engineer in this regard is final
10.33	The contractor's work shall not hinder other work, either underground or over ground, such
	as electrical, phone lines, water or sewage lines, etc. In areas of overlap, the contractor shall
	work in coordination with other related contractors.
10.34	Any damage to the other contractor's/customer's work will be penalized and contractor
	shall be responsible for cost for such damages
10.35	Contractor at his cost shall carryout all necessary temporary works required for erection
	works.
10.36	SITE INSPECTION
	a) The owner / employer or his authorized agents may inspect various stages of work
	during the currency of the contract awarded to him. The contractor shall make
	necessary arrangements for such inspection and carry out the rectification pointed
	out by the owner / employer without any extra cost to the owner / employer. No cost
	whatsoever such duplication of inspection of work be entertained.
	b) BHEL / Customer will have full power and authority to inspect the works at any time, either on the site or at the contractor's premises. The contractor shall arrange every
	either on the site of at the contractor's premises. The contractor shall arrange every



	2. Structural Steel Including MS Plates, Rolled Sections, SS Plates, Gratings, Hand Rails etc.
	3. Bought Out Items (Deck sheets, Cladding, Gratings, Handrails, Structural Bolts etc.) as per BOQ
	4. Any other as per BOQ/TCC
10.42	All other materials required for proper completion of job shall be provided by the contractor
	and is deemed to be inclusive in the quoted price. BOIs those are under scope of contractor
10.43	for Supply and fixing are mentioned in BOQ and shall be operated accordingly. Recovery of Materials:
10.43	Recovery of Materials.
	1. The recovery of any wastage of Steel material shall be as 1.05 times the actual cost to BHEL
	2. For Bought Out Items (which are in BHEL scope of supply as free of cost as per BOQ Cum Rate Schedule), recovery for excess wastage / consumption beyond the theoretical consumptions as per drawings will be 1.05 times the actual cost to BHEL.
10.44	Void
10.45	Void
10.46	Reconciliation of Materials:
	a) The contractor shall submit a reconciliation statement of steel issued to the
	contractor with RA Bill (bi-monthly basis). b) At the time of submission of bills, the contractor shall properly account for the material issued to him as specified herein to the satisfaction of BHEL certifying that
	the balance material is available in the contractor custody at site.
	c) All materials as specified in relevant BOQ shall be issued free of cost by BHEL for use in the work covered in this contract from BHEL stores/storage yard. The contractor shall collect these materials from BHEL stores/storage yard at specified places at his own cost and store the same at his stores as per standard norms. Materials issued will be used only for construction of permanent works.
	d) The contractor shall in no case be entitled for any compensation (other than explicitly mentioned in the tender conditions) on account of any delay in supply or non-supply thereof for all or any such materials. However, in case of non-availability of any specific section(s) which delays the completion of work, such cases shall be recorded separately in monthly planning format (F 14) and shall be considered for time extension of contract in line with GCC.
	e) Contractor will have to make his own arrangement at his own cost for procurement of any other materials except as mentioned above/ BOQ, as required for the works and of such quality as acceptable to BHEL.
	f) The contractor shall maintain proper store account for all the BHEL issued materials and shall give reconciliation statement of such account showing

		total receipt, consumption and balance at site to the BHEL. BHEL Engineer's certification for the reconciliation of steel shall be final.
	g)	Contractor shall also carryout in complete association with BHEL, the material management functions and execution like day-to-day update of materials, issued to contractor, accounting for surplus/scrap material returned etc. These functions shall also be carried out through computerized system utilizing suitable software. Contractor shall engage experienced software personnel to associate on dedicated basis for efficient discharge of the same in time.
	h)	BHEL issued materials, shall not be under any circumstances whatsoever, and shall be taken out of the project site unless otherwise permitted by BHEL for outside job.
	i)	BHEL reserves the right to recover from the contractor any loss arising out of damage/ theft or any other causes or during verification/stacking or at any time under the custody of the contractor.
	j)	The contractor shall take care of material issued by BHEL and shall protect the same from damage and weathering.
	k)	The contractor shall solely be responsible for the safety & security of material after it is handed over and issued to contractor by the BHEL
	l)	At the time of submission of bills, if it is noticed by BHEL that the wastage is high and calls recovery at the penal rate, then, BHEL will proceed for recovery for the excess wastage as per penal recovery rates as specified.
	m)	If at any point of time, BHEL finds there is a difference in physical and theoretical balance, where the contractor fails to provide necessary reconciliation, the decision of penal recovery/withhold of amount at penal rate by BHEL shall be final and binding to the contractor till proper records are submitted to and verified by BHEL.
	n)	The reference drawings for actual material consumption to be used for the purpose of reconciliation shall be drawings approved/provided by BHEL.
10.47	Void	bridge approved/provided by Bridge
10.48	All rele	evant provisions/responsibilities of contractors as mentioned in any of the chapter of
	_	ecification (same or different chapter) shall also be applicable, mutatis-mutandis, to
	any otł	ner chapter of this specification.

TECHNICAL CONDITIONS OF CONTRACT (TCC) Chapter – XI: FOUNDATION & GROUTING

11	PREPARATION OF FOUNDATIONS, AND GROUTING
11.1	Building foundations and other necessary civil works for supporting structures, equipments
	etc will be provided by BHEL / Customer. The checking of dimensional accuracy, axes,
	elevation, levels etc, with reference to bench marks of foundations and anchor bolt pits have
	to be checked and logged by the Contractor. The permanent benchmark / reference marks
	will have to be transferred to new locations with sufficient care to maintain the accuracy and
	protected / preserved with adequate care (to enable rechecking at later dates) as per BHEL
	instruction.
11.2	Minor adjustment of foundation level, dressing and chipping of foundation surfaces and
	blue-matching (wherever required) for of all equipments as per BHEL Engineers
	instructions, should be done by the Contractor as part of the work. Contractor/BHEL shall
	prepare protocols before taking over the foundations. Dressing and chipping of foundations
	as per instructions of BHEL Engineer for achieving proper levels will be within the scope of
	work/specification.
11.3	It shall be contractor's responsibility to check the various equipment foundations for their
	correctness with respect to level, orientation, dimensions etc., and ascertained dimensions
	shall be measured and submitted to BHEL for approval before erection.
	Foundation pockets are to be cleaned thoroughly before placing the supports / columns /
	equipments. Verticality of foundation bolts to be checked along with correctness of the
	threads and freeness of the nuts movement. If required cleaning of the threads to be done
11.4	with proper dies.
11.4	All temporary foundations and anchor points required for erection of Structure, Supports,
	etc (until otherwise explicitly mentioned in the tender) are in the scope of Contractor. All
	building materials like cement, steel including re-enforcement bars, grits cements etc for
	such temporary foundations shall have to be arranged by the Contractor within the quoted
	rates. All such foundations shall be demolished and normal ground conditions restored after
11.5	the usage. The surface of foundations shall be dressed to bring the surface of the foundations to the
11.3	required level and smoothness prior to placement of equipments / equipments based on the
	foundations including shear lug provisions / openings.
11.6	Complete grouting of Columns, Structures, equipments, including anchor/ foundation bolts,
11.0	beneath base, base hollows, etc, as may be applicable, is included in the scope of Contractor.
	Arranging all labour, building materials including cement, ordinary portland as well as quick
	setting – free flow - non-shrink grout mix (e.g. conbextra GP-1/GP-2/GP-3), form work,
	shuttering, and any other requirements is in the Contractor's scope. Contractor shall obtain
	approval of BHEL for cement (Ordinary Portland as-well-as quick setting – free flow- non-
	shrink grout mix) prior to use. Cleaning of foundation surfaces, pocket holes and anchor bolt
	pits and de-watering and making them free of oil, grease, sand and other foreign materials
	1 F 3 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7

TECHNICAL CONDITIONS OF CONTRACT (TCC) Chapter – XI: FOUNDATION & GROUTING

	by soda washing, water washing, compressed air and other approved methods are within
	the scope of this specification/ work.
11.7	After the grouting has finally set and cured, alignment of equipments involved shall be
	checked again to verify for any disturbance or any other reason. If required, de-coupling of
	equipments has to be done for conducting the verification. In case any disturbance is noticed
	the cause, if any, shall be removed and re-alignment done as part of work.
11.8	The concrete foundation, surfaces shall be properly prepared by chipping, as required to
	bring the top of such foundation to the required level to provide the necessary roughness for
	bondage and to ensure enough bearing strength. All laitance and surface film shall be
	removed and cleaned and the packers placed with suitable mortar prior to erection of the
	equipment. If required, Packer plates should not only be blue matched with foundation but
	also inter-packer contact surfaces between the packers and foundation frame etc., shall also
	be blue matched by Prussian Blue match checks and required percentage contact shall be
	achieved by chipping and scrapping as per BHEL Engineer's instructions.
11.9	All equipment bases and structural steel bases and foundations pockets shall be grouted and
	finished as per these specifications after surface preparation unless otherwise
	recommended by the equipment manufacturers. The surface preparation includes soda
	washing of the foundations to remove oil, grease etc. to ensure proper grouting.
11.10	The certificates of the grout are to be submitted to BHEL. If necessary, test cubes are to be
	made and tested at site to ensure the quality of the grout as per relevant IS standards. In case
	grouting with Portland cement is approved, necessary cement, sand etc. to be arranged by
	the contractor including the fine aggregates.
11.11	All the materials required for grouting including special cements as approved by BHEL and
	other materials like Portland cement, sand chips, gravel etc., are to be arranged by the
	contractor at his cost. It shall be the responsibility of the contractor to obtain prior approval
	of BHEL, regarding suppliers, type of grouting cements before procurement of grouting
	cements.
11.12	Foundation for the equipment to be erected shall be provided by BHEL / clients of BHEL. The
	dimensions of the foundations and anchor bolt pits shall be checked by the contractor for
	their correctness as per drawings. Further, top elevation of foundations shall be checked
	with respect to bench mark etc. All adjustments of foundations surfaces, enlarging the
	pockets in foundations etc. as may be required for the erection of equipment / plants shall
11.12	be carried out by the contractor.
11.13	PROCEDURE FOR GROUTING:
	Contractor has to carry out the grouting as per the work instructions for grouting available
	at site or the grouting is to be carried out as per the supplier's recommendation / IS standard.
	Copy of those recommendations is to be submitted to BHEL for records.

TECHNICAL CONDITIONS OF CONTRACT (TCC) Chapter – XII: MATERIAL HANDLING, TRANSPORTATION AND SITE STORAGE

The scope of the work will comprise of but not limited to the following:

(All the works mentioned hereunder shall be carried out within the accepted rate unless otherwise specified.)

	specified.)		
12.1	Loading at BHEL / Customer stores and storage yard, transport to site, unloading at site /		
	working area of equipment, placement on respective foundation / location, pre-assembly		
	bay or at working area are in the scope of work. The scope includes taking materials /		
	Equipments from customer stores / storage yard also. Contractors Quoted / Accepted rate		
	shall be inclusive of the same. Required cranes, tractors, trailer or trucks/ slings/ tools and		
	tackles / labour including operators, fuel, lubricants, consumables, etc. for loading &		
	unloading of materials will be in the scope of contractor.		
12.2	Transportation of all items including ODC items from BHEL Store/Yard to Erection site shall		
	be in the contractor's scope. However, in some cases, consignments including ODC may be		
	unloaded near erection site as per space availability and site requirements.		
12.3	Loading at storage yard and transporting to site, unloading at site / pre assembly area or at		
	working area, is in the scope of work. Required cranes for loading & unloading of materials,		
	trailer shall be in the scope of contractor. The contractor shall provide any fixtures, concrete		
	blocks & wooden sleepers, sandbags which are required for temporary supporting of the		
	components at site.		
12.4	The equipments / materials from the storage yard shall be moved in sequence to the actual		
	site of erection / location at the appropriate time as per the direction of BHEL Engineer so		
	as to avoid congestion/damage / loss of such equipment at site.		
12.5	The contractor shall satisfy himself of the quality and quantity of the materials at the time of		
	taking delivery from BHEL stores. No claims whatsoever will be entertained by BHEL		
	because of quality or quantity after the materials are taken by the contractor from BHEL		
	stores.		
12.6	Sometimes it may become necessary for the contractor to handle certain unrequired/non-		
	sequential components in order to take out the required materials. The contractor has to		
	take this contingency also into account. No extra payment is payable for such contingencies.		
12.7	Contractor shall plan and transport equipments/components from storage yard to erection		
	site in such a manner and sequence that material accumulation at site does not lead to		
	congestion at site of work. However, in specific cases "as a special case to expedite the job"		
	the consignment received at BHEL stores can directly be diverted to the work site, as decided		
	by BHEL, following issuance procedure of BHEL. Such direct issues shall be as per the		
	Challan/dispatch document/LR received with the consignment.		
12.8	All materials issued by BHEL shall be stacked neatly, preserved, stored in the contractor's		
	shed / work area above ground level by use of concrete or wooden sleepers. No materials		
	shall remain on ground at any time. All concrete or wooden sleepers required for stacking		
	the materials shall be arranged by contractor at his own cost within the quoted rates. In case		
	it is necessary to shift and re-stack the materials kept at work area / site to enable other		
	agencies to carry out their work, same shall be done by the contractor at no extra cost.		
	, - ·		

TECHNICAL CONDITIONS OF CONTRACT (TCC) Chapter – XII: MATERIAL HANDLING, TRANSPORTATION AND SITE STORAGE

12.9	The contractor shall take necessary measures to see that all the machined surfaces are
	preserved and covered. Contractor has to arrange required fire proof tarpaulins to protect
	the machined components / assembled parts drawn from BHEL store before and after
	erection as required at their cost.
12.10	The contractor shall take all such measures as may be reasonably necessary to ensure that
	its arrangements and those of its sub-contractors with respect to the transport of Goods,
	Materials and Labour to the site do not interfere with local traffic in the vicinity of the site
	and where such interference is unavoidable shall make such special arrangements as may
	be reasonably required to minimize the effect of such interference.
12.11	The contractor shall solely be responsible for the safety & security of material after it is
	handed over and issued to contractor by the BHEL. BHEL reserves the right to recover from
	the contractor any loss arising out of damage/ theft or any other causes or during
	verification/stacking or at any time under the custody of the contractor.
12.12	Open land for storage purposes shall be provided by BHEL on free of cost/as available basis
	for storage of materials issued to contractor (if required). Temporary barbed wire fencing
	(if required), as required, of the open storage yard is to be done by the contractor and is
	included under the scope of his work. Contractor shall also remove grass, bushes etc as a
	required off the land provided to agency and shall make proper continuous up keeping of
	the open yard /land by removing grass, bushes trees etc and same is included under the
	scope of his work & No extra payment shall be made to the contractor in this regard. The
	bidder shall make complete arrangement of necessary security personnel's to safeguard all
	such materials in his custody. The contractor shall take care of material issued by BHEL and
	shall protect the same from theft, damage and weathering. In case, loss of any materials for
	whatsoever reasons attributable to the contractor, then cost of such materials shall be
	recovered from the running bill payment with applicable overheads.
12.13	All surplus materials shall be returned to BHEL store. All wastage / scrap (including melting
	scrap, wastage, and unusable scrap) shall be returned to the stores on weighment basis in
	consultation with BHEL Engineer and a receipt obtained for material accounting purposes.
	Scrap materials shall be sorted section-wise and returned separately at a place directed by
	BHEL Engineer within the project area. Return of such materials will not be entitled for any
	handling and incidental charges.
·	

TECHNICAL CONDITIONS OF CONTRACT (TCC) Chapter – XIII: ERECTION

The scope of the work will comprise of but not limited to the following:

(All the works mentioned hereunder shall be carried out within the accepted rate unless otherwise specified.)

13.1	The contractor will have to follow the instructions provided in the technical manuals
13.1	The contractor will have to follow the instructions provided in the technical manuals,
	drawings, and specifications provided by BHEL, to the contractor from time to time. In case
	of ambiguity or deviation, the decision/clarification of BHEL engineer will have to be followed.
13.2	The contractor will be responsible for the safe custody and proper accounting of all materials
15.2	in connection with the work.
13.3	The temporary structures/ items welded to permanent members/pipes are to be cut and
15.5	removed without any damage. Any damage so to permanent members/ pipes to be made
	good by the contractor at his cost.
13.4	Approach road in the vicinity of Powerhouse area only for their scope of work, to be maintain
	by Contractor.
13.5	In the case of structural members, in certain cases, the raw material will be supplied in
	random lengths and the contractor will have to make up the length / prepare the edges to
	suit the matching profiles, weld / bolt connect the joints at no extra cost
13.6	All structural items including bracings, gussets, beams, etc. shall be supplied after
	fabrication. Hence Fit-ups, edge preparation including welding of stubs, if required,, shall be
	included in the contractor's scope. No separate payment will be made for the same.
13.7	All the equipments /material to be taken inside the plant building shall be cleaned
	thoroughly before taking them inside. The contractor shall clean, wherever necessary and
	do touch up paint inside surfaces of the structures and other components as per instruction
10.0	of BHEL Engineer during erection.
13.8	The contractor shall take all reasonable care to protect the materials and equipment during
	erection. Touch up painting required to be done on any equipment or part during the course
12.0	of erection will have to be done by the contractor which shall be payable as per BOQ.
13.9	Preparation of preassembly bed is very much essential for preassembly of truss, supporting
	structures, etc etc. on consolidated ground and to avoid sagging and shrinking the temporary
13.10	supports are to be provided. The column, girder pieces, primary beams, are to be measured individually to check for
13.10	camber, sweep etc. The level markings on the columns to be checked before erection. The
	verticality stickers are to be fixed over individual column pieces on both the flanges (90
	degrees apart in two places). Arranging these stickers shall be done by the contractor.
13.11	Tier by tier erection method is to be followed. Columns are to be tied up with horizontal and
	diagonal bracing in each tier before proceeding to next/adajacent level. Log sheets are to be
	maintained in line with log sheets which are available with BHEL. After grouting the first tier
	columns, second tier erection is to be taken up. Adequate curing of the grout is to be ensured.
	Verticality of the columns is to be ensured by plumb bob & theodolite. The tolerance shall be

TECHNICAL CONDITIONS OF CONTRACT (TCC) Chapter – XIII: ERECTION

	as indicated in BHEL's erection drawings. Care should be taken while erecting the vertical
	and diagonal bracings to maintain the work points as per drawing.
13.12	Measuring and test equipments with proper calibration certificates are to be made available
	by the contractor before taking up the structural erection. Periodic calibration of the
	measuring instruments is to be done once in six months and certificate for the same to be
	submitted to BHEL for records.
13.13	The tightening procedures for MS/HSFG bolts are to be obtained from BHEL at site before
	taking up the work. Normally it is done by turn of nut method. Torque wrenches also can be
	used . The bolted joints will be checked jointly by BHEL/Customer engineers for required
	tightness and retightening is to be done as per requirement. The tightened bolts will be
	marked with colour paints. Facility for random checking by torque wrench will have to be
	done. The required calibrated torque wrench will be provided by the contractor.
13.14	It shall be the responsibility of the contractor to provide ladders on column for initial works
	till such time stairways are completed. For this the ladder should not be welded on the
	column and should be fabricated clamping type ladders. No temporary welding on any
	structural members is permitted except under special circumstances with the approval of
	BHEL. The necessary materials for the ladders are to be arranged by bidder within quoted
	rate.
13.15	Certain adjustments in length/width of steel members may be necessary while erecting
	different structural members, and the contractor should remove the extra lengths to suit
	the final layout after preparing edges afresh and adopting specified heat treatment
	procedures at no extra cost, wherever indicated. Depending upon the type of deviation
	BHEL will consider the reimbursement at man hour rates. If the drawing provides for
	erection allowance, then it becomes part of the work and no compensation is payable.
13.16	In case of any class of work for which there is no such specifications laid down in the
	contract, the work shall be carried out in accordance with instructions and requirements
	of the BHEL engineer at the quoted rates only.
13.17	Additional platforms for approaching different elevations/positions/equipment as per the
	site requirement and to meet O&M requirements, which may not be indicated in drawings,
	shall be fabricated and erected by contractor. However, the contractor shall be paid for this
	work on accepted tonnage rate as per Rate schedule. The steel materials required for these
	works shall be supplied by BHEL free of cost and the contractor will have to install them to
	suit the requirement. Works of major nature not covered under this clause.
13.18	Work such as minor rectification of foundation bolts, reaming/enalarging of holes, drilling,
	matching of bolts and nuts, making new holes, etc. are covered in the scope of work
13.19	In some cases, the structural material will be supplied in random lengths, which have to be
	fabricated to suit the requirement as incidental to work. Also, it may sometimes be necessary
	to remove some of the erected members to facilitate erection of bigger/ pre-assembled
	equipments. In such cases, the removal and re-erection of such members as agreed by the
	BHEL Engineer, will have to be done by the Contractor as incidental to work.

TECHNICAL CONDITIONS OF CONTRACT (TCC) Chapter – XIII: ERECTION

1	
13.20	Contractor shall arrange materials required for temporary cat ladders & working platforms
	during erection of columns, platforms and other structural components. Such arrangements
	shall, as far as possible, be only of clamping & bolting type as welding on columns etc will not
	be permitted. After the completion of work these shall be removed.
13.21	All the hand rails and toe guards shall be provided as per drawings and site requirement.
	hand rails supplied in running lengths shall be suitably cut, edge prepared and welded. Also,
	hand rails/ guards may have to be provided from the safety point of view in certain places
	though not indicated in the erection drawings. The weld joints of hand rails shall be ground
10.00	smooth to flush finish.
13.22	Void
13.23	Void
13.24	All welded joints, if any, should be painted with anticorrosive paint / primer immediately
	after completion of all work (incl radiography and stress relieving works). Necessary paints
	and other consumables for the above work are in the scope of the Contractor.
13.25	Touch up and preservative painting of all components issued to and/or erected by
	Contractor shall form part of scope of work. The Contractor shall arrange consumables, T&P
10.06	and facilities.
13.26	Void
13.27	All materials as specified in relevant BOQ shall be issued free of cost by BHEL for use in the
	work covered in this contract from BHEL stores/storage yard. The contractor shall collect
	these materials from BHEL stores/storage yard at specified places at his own cost and store
	the same at his stores as per standard norms. Materials issued will be used only for construction of permanent works.
13.28	The contractor shall in no case be entitled for any compensation (other than explicitly
13.20	mentioned in the tender conditions) on account of any delay in supply or non-supply thereof
	for all or any such materials. However, in case of non-availability of any specific section(s)
	which delays the completion of work, such cases shall be recorded separately in monthly
	planning format (F 14) and shall be considered for time extension of contract in line with
	GCC.
13.29	Contractor will have to make his own arrangement at his own cost for procurement of any
	other materials except as mentioned above/ BOQ, as required for the works and of such
	quality as acceptable to BHEL.
13.30	The contractor shall maintain proper store account for all the BHEL issued materials and
	shall give Three (03) copies reconciliation statement of such account showing total
	receipt, consumption and balance at site to the BHEL. BHEL Engineer's certification for the
	reconciliation of steel shall be final.
13.31	Any other connected material supply which is not covered in BOM but required to complete
	the system shall be erected by the vendor and payment in this case shall be made as per
	applicable item rate.
13.32	All transport equipment, handling equipment, tools, tackles, fixtures, equipment, manpower,
	supervisors/engineers, consumables etc, except otherwise specified as BHEL scope of free

TECHNICAL CONDITIONS OF CONTRACT (TCC) Chapter – XIII: ERECTION

	issue, required for this scope of work shall be provided by the Contractor. All expenditure including taxes and incidentals in this connection will have to be borne by Contractor unless otherwise specified in the relevant clauses. The Contractor's quoted rates should be inclusive					
	of all such contingencies.					
13.33	Field Quality Assurance Formats:-					
	It is the responsibility of the contractor to collect and fill up the relevant FQA log sheets of					
	BHEL and present the same to BHEL after carrying out the necessary checks as per the log					
	sheets and obtaining the signature of BHEL and customer as token of their acceptance.					
	Payment to the contractor will be linked with the submission of these FQA log sheets.					

TECHNICAL CONDITIONS OF CONTRACT (TCC) Chapter – XIV: WELDING, HEAT TREATMENT & RADIOGRAPHY AND NON-DESTRUCTIVE TESTING

The scope of the work will comprise of but not limited to the following:

(All the works mentioned hereunder shall be carried out within the accepted rate unless otherwise specified.)

14.1	Complete structure of Powerhouse, CCR, Pipe racks, associated structures, etc as per the
	scope shall be pre-fabricated and shall be have bolted field connection. However, any kind of
	Welding, NDT (RT, UT, etc), Heat Treatment, etc if required during course of work, incidental
	to different situation, shall have to be carried out by contractor within the quoted rates.
14.2	Field Quality Plan (FQP):-
	Relevant FQP for Welding, NDT, Heat Treatment, etc. has to be followed as per instruction of
	BHEL engineer.
14.3	Welding sequence shall be adopted in such a way so as to minimize the distortion due to
	welding shrinkage. Contractor shall indicate in his drawing the sequence of welding
	proposed by him, which should meet prior approval of the Engineer.
14.4	All welders shall be BHEL / customer / consultant qualified as per the approved quality plan
	/ field quality plan which will be submitted by the successful bidder during detail
	engineering stage. WPS and PQR shall be submitted by the successful bidder to BHEL /
	customer / consultant for review and approval.
14.5	The method of welding (viz) Arc, TIG or other methods as indicated in the detailed drawing
	or as instructed by BHEL Engineer shall be followed. BHEL Engineer will have the option to
	change the method to suit site conditions. All the prepared / patched edges will have to be
	suitably protected to prevent rusting or foreign material ingression.
14.6	All welders including tack welders, structural and others welders shall be tested and
	approved by BHEL Engineer before they are actually engaged on work even though they may
	possess a valid certificate. BHEL reserves the right to reject any welder if the welder's
	performance is not found to be satisfactory. The contractor shall maintain the records of
	qualification and performance of welders. BHEL Engineer will issue all the welders qualified
	for the work, an identity card. The welder will keep the same with him at work place at all
	times. He may be stopped from work if he is not found in possession of the same.
14.7	All welders shall be tested and approved by BHEL Engineer before they are quality ensured
	on work though they may possess the requisite certificates. BHEL reserves the right to reject
	any welder without assigning any reason. The welder's identification code as approved by
	the BHEL Engineer shall be stamped by the welder on each joint done by them. The
	contractor will be responsible for the periodic renewal, retesting of the welders as
	demanded by BHEL statutory requirements.
14.8	BHEL Engineer is entitled to stop any contractor's welders from his work if his work is
	unsatisfactory for any technical reason or there is a high percentage of rejection of joints
	welded by him which in the opinion of BHEL Engineer, will adversely affect the quality of

TECHNICAL CONDITIONS OF CONTRACT (TCC) Chapter – XIV: WELDING, HEAT TREATMENT & RADIOGRAPHY AND NON-DESTRUCTIVE TESTING

	welding. Even though the welder has earlier passed the tests it does not relieve the				
110	contractor from his contractual obligations, to check the performance of the welders.				
14.9	Faulty welds caused by the poor workmanship shall be cut and re-welded at the contractor's				
	expense. The Engineer prior to any repair being made shall approve the procedure for the				
	repair of defective welds. After the repair has been carried out, the compliance shall be				
	submitted to the quality engineer.				
14.10	Pre -heating, radiography and other NDT tests, post heating and stress relieving after				
	welding, wherever necessary, are part of erection work and shall be carried out by the				
	contractor in accordance with the instructions of the Engineer and as specified in Erection				
	Welding Schedule, Welding, Heat Treatment & NDT manuals and FQP. Contractor at his cost				
	shall arrange all equipment and consumables essential for carrying out the above process.				
14.11	The contractor shall conduct nondestructive tests like radiography dye penetrant tests,				
	magnetic particle test etc., on weld joints and other equipments etc., as per drawing /				
	welding schedule.				
14.12	The Contractor shall maintain a record in the form as prescribed by BHEL for all operations				
	carried out on each weld and maintain a record indicating the number of welds, the name of				
	welders who welded the same, date and time of start and completion, preheat temperature,				
	radiographic results, rejections if any, percentage of rejection, etc., and submit copies of the				
	same to the BHEL Engineer as required.				
14.13	All expenses for testing of contractor's welders (pre-production test) including destructive				
	and Non- destructive tests conducted by BHEL or by the inspecting authority at site or at				
	laboratory shall have to be borne by the contractor only. Necessary pipe material and the				
	welding TIG wire, if any, will be arranged by BHEL and all testing/facilities will have to be				
	arranged by contractor with in the quoted rate.				
14.14	All welded joints shall be subjected to acceptance by BHEL Engineer.				
14.15	The technical particulars, specifications and other general details of work shall be in				
	accordance with ASME / BHEL welding, Heat treatment and NDE manuals or equivalent as				
	decided by BHEL Engineer.				
14.16	The Contractor shall carryout Radiography, if any, as per welding Manual booklet applicable.				
	However, percentage radiography shown in the respective drawings shall be final and				
	binding on the contractors.				
14.17	Low speed high contrast fine grain films (D7 or equivalent) in 10 cm width only should be				
	used for weld joint radiography. Film density shall be between 1.5. to 2.00				
14.18	All radiographs shall be free from mechanical, chemical or process marks to the extent they				
	shall not confuse the radiographic image and noticed.				
14.19	Penetrometer as per ASME / ISO shall be used for all exposures.				
14.20	Lead numbers and letters (generally of 6mm size) are to be used for identification of				
	radiographic contract No., joints identification, sources used, welders identification, SFD				
	used are to be noted down in the paper cover of radiography. Lead intensifying screens for				
	front and back of the film shall be used as per the instructions of BHEL Engineer.				
<u> </u>	1 and such of the first order of documents for the more deciving of bittle highlicer.				

TECHNICAL CONDITIONS OF CONTRACT (TCC) Chapter – XIV: WELDING, HEAT TREATMENT & RADIOGRAPHY AND NON-DESTRUCTIVE TESTING

14.22 The contractor shall be fully equipped with radiography equipments, films, chemicals and other dark room facilities. There must be a number of radiographic personnel with sufficient experience and certified by BARC for field radiographic inspection. Further, the contractor must follow strictly the safety rules laid down by BARC, from time to time, contractor radiographers shall also be registered with BARC for film badge service. 14.23 Void 14.24 If the contractor does not carry out radiography work in time due to non-availability of film chemical etc. BHEL shall get the work done through some other agency and same shall be debited from the contractor with 5% overhead. 14.25 All the radiographs shall be properly preserved in air-conditioned rooms and shall become the property of BHEL. They are to be reconciled with the work done, joints radiographed and submitted to BHEL/customer. 14.26 Radiography of joints shall be so planned after welding that the same is done either on the same day or next day of the welding to assess the performance of welders. If the performance of the welder is unsatisfactory, he shall be replaced immediately. 14.27 The defects as pointed out by the Engineer shall be rectified immediately to the satisfaction of Engineer and Re-radiographed. The decision of Engineer regarding acceptance of otherwise of the joint shall be final and binding on the contractor. 14.28 Wherever radiographs are not accepted on account of poor exposure, joints shall be radiographed and new film submitted for evaluation. Radiographs shall be taken again of joints after carrying out repairs. However, if the defect persists after first repair as peradiograph, carrying out repairs. However, if the defect persists after first repair as peradiograph, carrying out repairs. However, and the contractor's cost. 14.29 carrying out ultrasonic testing of welded joints wherever required is the part of scope. 14.30 The welded surface irrespective of place of welding shall be cleaned of slag and painted at the cent	1421	77 1
other dark room facilities. There must be a number of radiographic personnel with sufficient experience and certified by BARC for field radiographic inspection. Further, the contractor must follow strictly the safety rules laid down by BARC, from time to time, contractor radiographers shall also be registered with BARC for film badge service. 14.23 Void 14.24 If the contractor does not carry out radiography work in time due to non- availability of film chemical etc. BHEL shall get the work done through some other agency and same shall be debited from the contractor with 5% overhead. 14.25 All the radiographs shall be properly preserved in air-conditioned rooms and shall become the property of BHEL. They are to be reconciled with the work done, joints radiographed an submitted to BHEL/customer. 14.26 Radiography of joints shall be so planned after welding that the same is done either on the same day or next day of the welding to assess the performance of welders. If the performance of the welder is unsatisfactory, he shall be replaced immediately. 14.27 The defects as pointed out by the Engineer shall be rectified immediately to the satisfaction of Engineer and Re-radiographed. The decision of Engineer regarding acceptance of otherwise of the joint shall be final and binding on the contractor. 14.28 Wherever radiographs are not accepted on account of poor exposure, joints shall be readiographe, carrying out repairs. However, if the defect persists after first repair as per radiographe, carrying out radiography shall be repeated till the joint is made acceptable. It case the joint is not repairable, the same shall be cut, re-welded and re-radiographed a contractor's cost. 14.29 Carrying out ultrasonic testing of welded joints wherever required is the part of scope. 14.30 The welded surface irrespective of place of welding shall be cleaned of slag and painted at the center with primer paint to prevent corrosion at no extra cost towards this includin supply of Paint for this purpose. All welds shall be pain	14.21	Void-
experience and certified by BARC for field radiographic inspection. Further, the contractor must follow strictly the safety rules laid down by BARC, from time to time, contractor radiographers shall also be registered with BARC for film badge service. 14.23 Void 14.24 If the contractor does not carry out radiography work in time due to non-availability of film chemical etc. BHEL shall get the work done through some other agency and same shall be debited from the contractor with 5% overhead. 14.25 All the radiographs shall be properly preserved in air-conditioned rooms and shall becom the property of BHEL. They are to be reconciled with the work done, joints radiographed an submitted to BHEL/customer. 14.26 Radiography of joints shall be so planned after welding that the same is done either on the same day or next day of the welding to assess the performance of welders. If the performance of the welder is unsatisfactory, he shall be replaced immediately. 14.27 The defects as pointed out by the Engineer shall be rectified immediately to the satisfaction of Engineer and Re-radiographed. The decision of Engineer regarding acceptance of otherwise of the joint shall be final and binding on the contractor. 14.28 Wherever radiographs are not accepted on account of poor exposure, joints shall be reradiographed and new film submitted for evaluation. Radiographs shall be taken again of joints after carrying out repairs. However, if the defect persists after first repair as peradiograph, carrying out repairs. However, if the defect persists after first repair as peradiograph, carrying out repairs. However, if the defect persists after first repair as peradiograph, carrying out repairs. However, if the defect persists after first repair as peradiograph, carrying out repairs however, if the defect persists after first repair as peradiography and stress reliving works are over. 14.29 carrying out ultrasonic testing of welded joints wherever required is the part of scope. 14.31 void 14.32 consumables, filler wires, el	14.22	
must follow strictly the safety rules laid down by BARC, from time to time, contractor radiographers shall also be registered with BARC for film badge service. 14.23 Void 14.24 If the contractor does not carry out radiography work in time due to non- availability of film chemical etc. BHEL shall get the work done through some other agency and same shall be debited from the contractor with 5% overhead. 14.25 All the radiographs shall be properly preserved in air-conditioned rooms and shall become the property of BHEL. They are to be reconciled with the work done, joints radiographed am submitted to BHEL/customer. 14.26 Radiography of joints shall be so planned after welding that the same is done either on the same day or next day of the welding to assess the performance of welders. If the performance of the welder is unsatisfactory, he shall be replaced immediately. 14.27 The defects as pointed out by the Engineer shall be rectified immediately to the satisfaction of Engineer and Re-radiographed. The decision of Engineer regarding acceptance of otherwise of the joint shall be final and binding on the contractor. 14.28 Wherever radiographs are not accepted on account of poor exposure, joints shall be radiographed and new film submitted for evaluation. Radiographs shall be taken again of joints after carrying out repairs. However, if the defect persists after first repair as peradiograph, carrying out radiography shall be repeated till the joint is made acceptable. It case the joint is not repairable, the same shall be cut, re-welded and re-radiographed a contractor's cost. 14.29 carrying out ultrasonic testing of welded joints wherever required is the part of scope. 14.30 The welded surface irrespective of place of welding shall be cleaned of slag and painted at the center with primer paint to prevent corrosion at no extra cost towards this including supply of Paint for this purpose. All welds shall be painted with primer as specified in the painting schedule, once radiography and stress reliving works ar		
radiographers shall also be registered with BARC for film badge service. 14.23 Void 14.24 If the contractor does not carry out radiography work in time due to non-availability of film chemical etc. BHEL shall get the work done through some other agency and same shall be debited from the contractor with 5% overhead. 14.25 All the radiographs shall be properly preserved in air-conditioned rooms and shall become the property of BHEL. They are to be reconciled with the work done, joints radiographed and submitted to BHEL/customer. 14.26 Radiography of joints shall be so planned after welding that the same is done either on the same day or next day of the welding to assess the performance of welders. If the performance of the welder is unsatisfactory, he shall be replaced immediately. 14.27 The defects as pointed out by the Engineer shall be rectified immediately to the satisfaction of Engineer and Re-radiographed. The decision of Engineer regarding acceptance of otherwise of the joint shall be final and binding on the contractor. 14.28 Wherever radiographs are not accepted on account of poor exposure, joints shall be radiographed and new film submitted for evaluation. Radiographs shall be taken again or joints after carrying out repairs. However, if the defect persists after first repair as per radiographed, carrying out radiography shall be repeated till the joint is made acceptable. It case the joint is not repairable, the same shall be cut, re-welded and re-radiographed a contractor's cost. 14.29 carrying out ultrasonic testing of welded joints wherever required is the part of scope. 14.30 The welded surface irrespective of place of welding shall be cleaned of slag and painted at the center with primer paint to prevent corrosion at no extra cost towards this including supply of Paint for this purpose. All welds shall be painted with primer as specified in the painting schedule, once radiography and stress reliving works are over. 14.31 void 14.32 Consumables, filler wires, electrodes, gas etc. are to b		
14.23 Void 14.24 If the contractor does not carry out radiography work in time due to non- availability of film chemical etc. BHEL shall get the work done through some other agency and same shall be debited from the contractor with 5% overhead. 14.25 All the radiographs shall be properly preserved in air-conditioned rooms and shall become the property of BHEL. They are to be reconciled with the work done, joints radiographed and submitted to BHEL/customer. 14.26 Radiography of joints shall be so planned after welding that the same is done either on the same day or next day of the welding to assess the performance of welders. If the performance of the welder is unsatisfactory, he shall be replaced immediately. 14.27 The defects as pointed out by the Engineer shall be rectified immediately to the satisfaction of Engineer and Re-radiographed. The decision of Engineer regarding acceptance of otherwise of the joint shall be final and binding on the contractor. 14.28 Wherever radiographs are not accepted on account of poor exposure, joints shall be reradiographed and new film submitted for evaluation. Radiographs shall be taken again of joints after carrying out repairs. However, if the defect persists after first repair as per radiographed, carrying out radiography shall be repeated till the joint is made acceptable. It case the joint is not repairable, the same shall be cut, re-welded and re-radiographed a contractor's cost. 14.29 carrying out ultrasonic testing of welded joints wherever required is the part of scope. 14.30 The welded surface irrespective of place of welding shall be cleaned of slag and painted at the center with primer paint to prevent corrosion at no extra cost towards this including supply of Paint for this purpose. All welds shall be painted with primer as specified in the painting schedule, once radiography and stress reliving works are over. 14.31 void 14.32 consumables, filler wires, electrodes, gas etc. are to be arranged by the contractor at his cost Weight of above welding consum		
14.24 If the contractor does not carry out radiography work in time due to non-availability of film chemical etc. BHEL shall get the work done through some other agency and same shall be debited from the contractor with 5% overhead. 14.25 All the radiographs shall be properly preserved in air-conditioned rooms and shall become the property of BHEL. They are to be reconciled with the work done, joints radiographed and submitted to BHEL/customer. 14.26 Radiography of joints shall be so planned after welding that the same is done either on the same day or next day of the welding to assess the performance of welders. If the performance of the welder is unsatisfactory, he shall be replaced immediately. 14.27 The defects as pointed out by the Engineer shall be rectified immediately to the satisfaction of Engineer and Re-radiographed. The decision of Engineer regarding acceptance of otherwise of the joint shall be final and binding on the contractor. 14.28 Wherever radiographs are not accepted on account of poor exposure, joints shall be readiographed and new film submitted for evaluation. Radiographs shall be taken again of joints after carrying out repairs. However, if the defect persists after first repair as per radiographed and new film submitted for evaluation. Radiographs shall be taken again of joints after carrying out repairs. However, if the defect persists after first repair as per radiograph, carrying out repairs. However, if the defect persists after first repair as per radiograph, carrying out repairs wherever, if the defect persists after first repair as per radiograph, carrying out repairs wherever, if the defect persists after first repair as per radiograph, carrying out repairs. However, if the defect persists after first repair as per radiograph, carrying out repairs wherever, if the defect persists after first repair as per radiograph, carrying out repairs. However, if the defect persists after first repair as persistent of the joint is made acceptable. In case the joint is not repairable, the		
chemical etc. BHEL shall get the work done through some other agency and same shall be debited from the contractor with 5% overhead. 14.25 All the radiographs shall be properly preserved in air-conditioned rooms and shall become the property of BHEL. They are to be reconciled with the work done, joints radiographed and submitted to BHEL/customer. 14.26 Radiography of joints shall be so planned after welding that the same is done either on the same day or next day of the welding to assess the performance of welders. If the performance of the welder is unsatisfactory, he shall be replaced immediately. 14.27 The defects as pointed out by the Engineer shall be rectified immediately to the satisfaction of Engineer and Re-radiographed. The decision of Engineer regarding acceptance of otherwise of the joint shall be final and binding on the contractor. 14.28 Wherever radiographs are not accepted on account of poor exposure, joints shall be reradiographed and new film submitted for evaluation. Radiographs shall be taken again of joints after carrying out repairs. However, if the defect persists after first repair as peradiograph, carrying out repairs. However, if the defect persists after first repair as peradiograph, carrying out repairs. However, if the defect persists after first repair as peradiograph, carrying out repairs wherever, if the defect persists after first repair as peradiograph, carrying out repairs. However, if the defect persists after first repair as peradiograph, carrying out repairs wherever, if the defect persists after first repair as peradiograph, carrying out repairs wherever, if the defect persists after first repair as peradiograph, carrying out repairs wherever, if the defect persists after first repair as peradiograph, carrying out repairs wherever, if the defect persists after first repair as peradiograph, carrying out repairs wherever, if the defect persists after first repair as peradiograph, carrying out repairs wherever required is the part of scope. 14.29 carrying out ultrasonic	14.23	Void
debited from the contractor with 5% overhead. All the radiographs shall be properly preserved in air-conditioned rooms and shall become the property of BHEL. They are to be reconciled with the work done, joints radiographed and submitted to BHEL/customer. Radiography of joints shall be so planned after welding that the same is done either on the same day or next day of the welding to assess the performance of welders. If the performance of the welder is unsatisfactory, he shall be replaced immediately. The defects as pointed out by the Engineer shall be rectified immediately to the satisfaction of Engineer and Re-radiographed. The decision of Engineer regarding acceptance of otherwise of the joint shall be final and binding on the contractor. Wherever radiographs are not accepted on account of poor exposure, joints shall be reradiographed and new film submitted for evaluation. Radiographs shall be taken again of joints after carrying out readiography shall be repeated till the joint is made acceptable. It case the joint is not repairable, the same shall be cut, re-welded and re-radiographed a contractor's cost. 14.29 carrying out ultrasonic testing of welded joints wherever required is the part of scope. 14.30 The welded surface irrespective of place of welding shall be cleaned of slag and painted at the center with primer paint to prevent corrosion at no extra cost towards this including supply of Paint for this purpose. All welds shall be painted with primer as specified in the painting schedule, once radiography and stress reliving works are over. 14.31 void 14.32 consumables, filler wires, electrodes, gas etc. are to be arranged by the contractor at his cost Weight of above welding consumables will not be considered for any payment. 14.33 void 14.34 Pre-heating / post heating and stress relieving after welding, where ever applicable, are part of erection work and shall be performed by the contractor in accordance with the instructions of BHEL Engineer within the quoted rates. All required heating	14.24	If the contractor does not carry out radiography work in time due to non- availability of film,
14.25 All the radiographs shall be properly preserved in air-conditioned rooms and shall become the property of BHEL. They are to be reconciled with the work done, joints radiographed and submitted to BHEL/customer. 14.26 Radiography of joints shall be so planned after welding that the same is done either on the same day or next day of the welding to assess the performance of welders. If the performance of the welder is unsatisfactory, he shall be replaced immediately. 14.27 The defects as pointed out by the Engineer shall be rectified immediately to the satisfaction of Engineer and Re-radiographed. The decision of Engineer regarding acceptance of otherwise of the joint shall be final and binding on the contractor. 14.28 Wherever radiographs are not accepted on account of poor exposure, joints shall be reradiographed and new film submitted for evaluation. Radiographs shall be taken again of joints after carrying out repairs. However, if the defect persists after first repair as per radiograph, carrying out radiography shall be repeated till the joint is made acceptable. It case the joint is not repairable, the same shall be cut, re-welded and re-radiographed accontractor's cost. 14.29 Carrying out ultrasonic testing of welded joints wherever required is the part of scope. 14.30 The welded surface irrespective of place of welding shall be cleaned of slag and painted at the center with primer paint to prevent corrosion at no extra cost towards this including supply of Paint for this purpose. All welds shall be painted with primer as specified in the painting schedule, once radiography and stress reliving works are over. 14.31 void 14.32 consumables, filler wires, electrodes, gas etc. are to be arranged by the contractor at his cost Weight of above welding consumables will not be considered for any payment. 14.33 void 14.34 Pre-heating / post heating and stress relieving after welding, where ever applicable, are part of erection work and shall be performed by the contractor in accordance with the instruct		chemical etc. BHEL shall get the work done through some other agency and same shall be
the property of BHEL. They are to be reconciled with the work done, joints radiographed and submitted to BHEL/customer. Radiography of joints shall be so planned after welding that the same is done either on the same day or next day of the welding to assess the performance of welders. If the performance of the welder is unsatisfactory, he shall be replaced immediately. The defects as pointed out by the Engineer shall be rectified immediately to the satisfaction of Engineer and Re-radiographed. The decision of Engineer regarding acceptance of otherwise of the joint shall be final and binding on the contractor. Wherever radiographs are not accepted on account of poor exposure, joints shall be readiographed and new film submitted for evaluation. Radiographs shall be taken again of joints after carrying out repairs. However, if the defect persists after first repair as per radiograph, carrying out radiography shall be repeated till the joint is made acceptable. It case the joint is not repairable, the same shall be cut, re-welded and re-radiographed accontractor's cost. 14.29 carrying out ultrasonic testing of welded joints wherever required is the part of scope. 14.30 The welded surface irrespective of place of welding shall be cleaned of slag and painted at the center with primer paint to prevent corrosion at no extra cost towards this including supply of Paint for this purpose. All welds shall be painted with primer as specified in the painting schedule, once radiography and stress reliving works are over. 14.31 void 14.32 consumables, filler wires, electrodes, gas etc. are to be arranged by the contractor at his cost Weight of above welding consumables will not be considered for any payment. 14.33 void 14.34 Pre-heating / post heating and stress relieving after welding, where ever applicable, are part of erection work and shall be performed by the contractor in accordance with the instructions of BHEL Engineer within the quoted rates. All required heating equipment		debited from the contractor with 5% overhead.
submitted to BHEL/customer. Radiography of joints shall be so planned after welding that the same is done either on the same day or next day of the welding to assess the performance of welders. If the performance of the welder is unsatisfactory, he shall be replaced immediately. The defects as pointed out by the Engineer shall be rectified immediately to the satisfaction of Engineer and Re-radiographed. The decision of Engineer regarding acceptance of otherwise of the joint shall be final and binding on the contractor. Wherever radiographs are not accepted on account of poor exposure, joints shall be readiographed and new film submitted for evaluation. Radiographs shall be taken again or joints after carrying out repairs. However, if the defect persists after first repair as per radiograph, carrying out radiography shall be repeated till the joint is made acceptable. In case the joint is not repairable, the same shall be cut, re-welded and re-radiographed accontractor's cost. 14.29 carrying out ultrasonic testing of welded joints wherever required is the part of scope. 14.30 The welded surface irrespective of place of welding shall be cleaned of slag and painted at the center with primer paint to prevent corrosion at no extra cost towards this includin supply of Paint for this purpose. All welds shall be painted with primer as specified in the painting schedule, once radiography and stress reliving works are over. 14.31 void 14.32 consumables, filler wires, electrodes, gas etc. are to be arranged by the contractor at his cost Weight of above welding consumables will not be considered for any payment. 14.33 void 14.34 Pre-heating / post heating and stress relieving after welding, where ever applicable, are part of erection work and shall be performed by the contractor in accordance with the instructions of BHEL Engineer within the quoted rates. All required heating equipment	14.25	All the radiographs shall be properly preserved in air-conditioned rooms and shall become
14.26 Radiography of joints shall be so planned after welding that the same is done either on the same day or next day of the welding to assess the performance of welders. If the performance of the welder is unsatisfactory, he shall be replaced immediately. 14.27 The defects as pointed out by the Engineer shall be rectified immediately to the satisfaction of Engineer and Re-radiographed. The decision of Engineer regarding acceptance of otherwise of the joint shall be final and binding on the contractor. 14.28 Wherever radiographs are not accepted on account of poor exposure, joints shall be readiographed and new film submitted for evaluation. Radiographs shall be taken again of joints after carrying out repairs. However, if the defect persists after first repair as per radiograph, carrying out radiography shall be repeated till the joint is made acceptable. It case the joint is not repairable, the same shall be cut, re-welded and re-radiographed accontractor's cost. 14.29 carrying out ultrasonic testing of welded joints wherever required is the part of scope. 14.30 The welded surface irrespective of place of welding shall be cleaned of slag and painted at the center with primer paint to prevent corrosion at no extra cost towards this including supply of Paint for this purpose. All welds shall be painted with primer as specified in the painting schedule, once radiography and stress reliving works are over. 14.31 void 14.32 consumables, filler wires, electrodes, gas etc. are to be arranged by the contractor at his cost Weight of above welding consumables will not be considered for any payment. 14.33 Void 14.34 Pre-heating / post heating and stress relieving after welding, where ever applicable, are par of erection work and shall be performed by the contractor in accordance with the instructions of BHEL Engineer within the quoted rates. All required heating equipment		the property of BHEL. They are to be reconciled with the work done, joints radiographed and
same day or next day of the welding to assess the performance of welders. If the performance of the welder is unsatisfactory, he shall be replaced immediately. 14.27 The defects as pointed out by the Engineer shall be rectified immediately to the satisfaction of Engineer and Re-radiographed. The decision of Engineer regarding acceptance of otherwise of the joint shall be final and binding on the contractor. 14.28 Wherever radiographs are not accepted on account of poor exposure, joints shall be readiographed and new film submitted for evaluation. Radiographs shall be taken again of joints after carrying out repairs. However, if the defect persists after first repair as per radiograph, carrying out radiography shall be repeated till the joint is made acceptable. In case the joint is not repairable, the same shall be cut, re-welded and re-radiographed a contractor's cost. 14.29 carrying out ultrasonic testing of welded joints wherever required is the part of scope. 14.30 The welded surface irrespective of place of welding shall be cleaned of slag and painted at the center with primer paint to prevent corrosion at no extra cost towards this including supply of Paint for this purpose. All welds shall be painted with primer as specified in the painting schedule, once radiography and stress reliving works are over. 14.31 void 14.32 consumables, filler wires, electrodes, gas etc. are to be arranged by the contractor at his cost Weight of above welding consumables will not be considered for any payment. 14.33 Void 14.34 Pre-heating / post heating and stress relieving after welding, where ever applicable, are part of erection work and shall be performed by the contractor in accordance with the instructions of BHEL Engineer within the quoted rates. All required heating equipment		submitted to BHEL/customer.
of the welder is unsatisfactory, he shall be replaced immediately. 14.27 The defects as pointed out by the Engineer shall be rectified immediately to the satisfaction of Engineer and Re-radiographed. The decision of Engineer regarding acceptance of otherwise of the joint shall be final and binding on the contractor. 14.28 Wherever radiographs are not accepted on account of poor exposure, joints shall be readiographed and new film submitted for evaluation. Radiographs shall be taken again of joints after carrying out repairs. However, if the defect persists after first repair as per radiograph, carrying out radiography shall be repeated till the joint is made acceptable. In case the joint is not repairable, the same shall be cut, re-welded and re-radiographed a contractor's cost. 14.29 carrying out ultrasonic testing of welded joints wherever required is the part of scope. 14.30 The welded surface irrespective of place of welding shall be cleaned of slag and painted at the center with primer paint to prevent corrosion at no extra cost towards this including supply of Paint for this purpose. All welds shall be painted with primer as specified in the painting schedule, once radiography and stress reliving works are over. 14.31 void 14.32 consumables, filler wires, electrodes, gas etc. are to be arranged by the contractor at his cost Weight of above welding consumables will not be considered for any payment. 14.33 Void 14.34 Pre-heating / post heating and stress relieving after welding, where ever applicable, are par of erection work and shall be performed by the contractor in accordance with the instructions of BHEL Engineer within the quoted rates. All required heating equipments	14.26	Radiography of joints shall be so planned after welding that the same is done either on the
 The defects as pointed out by the Engineer shall be rectified immediately to the satisfaction of Engineer and Re-radiographed. The decision of Engineer regarding acceptance of otherwise of the joint shall be final and binding on the contractor. 14.28 Wherever radiographs are not accepted on account of poor exposure, joints shall be readiographed and new film submitted for evaluation. Radiographs shall be taken again of joints after carrying out repairs. However, if the defect persists after first repair as per radiograph, carrying out radiography shall be repeated till the joint is made acceptable. In case the joint is not repairable, the same shall be cut, re-welded and re-radiographed accontractor's cost. 14.29 carrying out ultrasonic testing of welded joints wherever required is the part of scope. 14.30 The welded surface irrespective of place of welding shall be cleaned of slag and painted at the center with primer paint to prevent corrosion at no extra cost towards this including supply of Paint for this purpose. All welds shall be painted with primer as specified in the painting schedule, once radiography and stress reliving works are over. 14.31 void 14.32 consumables, filler wires, electrodes, gas etc. are to be arranged by the contractor at his cost Weight of above welding consumables will not be considered for any payment. 14.33 void 14.34 Pre-heating / post heating and stress relieving after welding, where ever applicable, are par of erection work and shall be performed by the contractor in accordance with the instructions of BHEL Engineer within the quoted rates. All required heating equipment. 		same day or next day of the welding to assess the performance of welders. If the performance
of Engineer and Re-radiographed. The decision of Engineer regarding acceptance of otherwise of the joint shall be final and binding on the contractor. 14.28 Wherever radiographs are not accepted on account of poor exposure, joints shall be readiographed and new film submitted for evaluation. Radiographs shall be taken again of joints after carrying out repairs. However, if the defect persists after first repair as per radiograph, carrying out radiography shall be repeated till the joint is made acceptable. It case the joint is not repairable, the same shall be cut, re-welded and re-radiographed accontractor's cost. 14.29 carrying out ultrasonic testing of welded joints wherever required is the part of scope. 14.30 The welded surface irrespective of place of welding shall be cleaned of slag and painted at the center with primer paint to prevent corrosion at no extra cost towards this including supply of Paint for this purpose. All welds shall be painted with primer as specified in the painting schedule, once radiography and stress reliving works are over. 14.31 void 14.32 consumables, filler wires, electrodes, gas etc. are to be arranged by the contractor at his cost Weight of above welding consumables will not be considered for any payment. 14.33 Void 14.34 Pre-heating / post heating and stress relieving after welding, where ever applicable, are par of erection work and shall be performed by the contractor in accordance with the instructions of BHEL Engineer within the quoted rates. All required heating equipments		of the welder is unsatisfactory, he shall be replaced immediately.
otherwise of the joint shall be final and binding on the contractor. 14.28 Wherever radiographs are not accepted on account of poor exposure, joints shall be readiographed and new film submitted for evaluation. Radiographs shall be taken again of joints after carrying out repairs. However, if the defect persists after first repair as per radiograph, carrying out radiography shall be repeated till the joint is made acceptable. In case the joint is not repairable, the same shall be cut, re-welded and re-radiographed a contractor's cost. 14.29 carrying out ultrasonic testing of welded joints wherever required is the part of scope. 14.30 The welded surface irrespective of place of welding shall be cleaned of slag and painted at the center with primer paint to prevent corrosion at no extra cost towards this including supply of Paint for this purpose. All welds shall be painted with primer as specified in the painting schedule, once radiography and stress reliving works are over. 14.31 void 14.32 consumables, filler wires, electrodes, gas etc. are to be arranged by the contractor at his cost Weight of above welding consumables will not be considered for any payment. 14.33 Void 14.34 Pre-heating / post heating and stress relieving after welding, where ever applicable, are par of erection work and shall be performed by the contractor in accordance with the instructions of BHEL Engineer within the quoted rates. All required heating equipments	14.27	The defects as pointed out by the Engineer shall be rectified immediately to the satisfaction
 Wherever radiographs are not accepted on account of poor exposure, joints shall be readiographed and new film submitted for evaluation. Radiographs shall be taken again or joints after carrying out repairs. However, if the defect persists after first repair as per radiograph, carrying out radiography shall be repeated till the joint is made acceptable. It case the joint is not repairable, the same shall be cut, re-welded and re-radiographed a contractor's cost. 14.29 carrying out ultrasonic testing of welded joints wherever required is the part of scope. 14.30 The welded surface irrespective of place of welding shall be cleaned of slag and painted at the center with primer paint to prevent corrosion at no extra cost towards this including supply of Paint for this purpose. All welds shall be painted with primer as specified in the painting schedule, once radiography and stress reliving works are over. 14.31 void 14.32 consumables, filler wires, electrodes, gas etc. are to be arranged by the contractor at his cost Weight of above welding consumables will not be considered for any payment. 14.33 Void 14.34 Pre-heating / post heating and stress relieving after welding, where ever applicable, are par of erection work and shall be performed by the contractor in accordance with the instructions of BHEL Engineer within the quoted rates. All required heating equipment. 		of Engineer and Re-radiographed. The decision of Engineer regarding acceptance or
radiographed and new film submitted for evaluation. Radiographs shall be taken again or joints after carrying out repairs. However, if the defect persists after first repair as per radiograph, carrying out radiography shall be repeated till the joint is made acceptable. It case the joint is not repairable, the same shall be cut, re-welded and re-radiographed accontractor's cost. 14.29 carrying out ultrasonic testing of welded joints wherever required is the part of scope. 14.30 The welded surface irrespective of place of welding shall be cleaned of slag and painted at the center with primer paint to prevent corrosion at no extra cost towards this including supply of Paint for this purpose. All welds shall be painted with primer as specified in the painting schedule, once radiography and stress reliving works are over. 14.31 void 14.32 consumables, filler wires, electrodes, gas etc. are to be arranged by the contractor at his cost Weight of above welding consumables will not be considered for any payment. 14.33 void 14.34 Pre-heating / post heating and stress relieving after welding, where ever applicable, are par of erection work and shall be performed by the contractor in accordance with the instructions of BHEL Engineer within the quoted rates. All required heating equipments		otherwise of the joint shall be final and binding on the contractor.
joints after carrying out repairs. However, if the defect persists after first repair as per radiograph, carrying out radiography shall be repeated till the joint is made acceptable. In case the joint is not repairable, the same shall be cut, re-welded and re-radiographed a contractor's cost. 14.29 carrying out ultrasonic testing of welded joints wherever required is the part of scope. 14.30 The welded surface irrespective of place of welding shall be cleaned of slag and painted at the center with primer paint to prevent corrosion at no extra cost towards this including supply of Paint for this purpose. All welds shall be painted with primer as specified in the painting schedule, once radiography and stress reliving works are over. 14.31 void 14.32 consumables, filler wires, electrodes, gas etc. are to be arranged by the contractor at his cost Weight of above welding consumables will not be considered for any payment. 14.33 Void 14.34 Pre-heating / post heating and stress relieving after welding, where ever applicable, are par of erection work and shall be performed by the contractor in accordance with the instructions of BHEL Engineer within the quoted rates. All required heating equipments	14.28	Wherever radiographs are not accepted on account of poor exposure, joints shall be re-
radiograph, carrying out radiography shall be repeated till the joint is made acceptable. In case the joint is not repairable, the same shall be cut, re-welded and re-radiographed a contractor's cost. 14.29 carrying out ultrasonic testing of welded joints wherever required is the part of scope. 14.30 The welded surface irrespective of place of welding shall be cleaned of slag and painted at the center with primer paint to prevent corrosion at no extra cost towards this including supply of Paint for this purpose. All welds shall be painted with primer as specified in the painting schedule, once radiography and stress reliving works are over. 14.31 void 14.32 consumables, filler wires, electrodes, gas etc. are to be arranged by the contractor at his cost Weight of above welding consumables will not be considered for any payment. 14.33 Void 14.34 Pre-heating / post heating and stress relieving after welding, where ever applicable, are par of erection work and shall be performed by the contractor in accordance with the instructions of BHEL Engineer within the quoted rates. All required heating equipments		radiographed and new film submitted for evaluation. Radiographs shall be taken again on
case the joint is not repairable, the same shall be cut, re-welded and re-radiographed a contractor's cost. 14.29 carrying out ultrasonic testing of welded joints wherever required is the part of scope. 14.30 The welded surface irrespective of place of welding shall be cleaned of slag and painted a the center with primer paint to prevent corrosion at no extra cost towards this including supply of Paint for this purpose. All welds shall be painted with primer as specified in the painting schedule, once radiography and stress reliving works are over. 14.31 void 14.32 consumables, filler wires, electrodes, gas etc. are to be arranged by the contractor at his cost Weight of above welding consumables will not be considered for any payment. 14.33 Void 14.34 Pre-heating / post heating and stress relieving after welding, where ever applicable, are par of erection work and shall be performed by the contractor in accordance with the instructions of BHEL Engineer within the quoted rates. All required heating equipments		joints after carrying out repairs. However, if the defect persists after first repair as per
contractor's cost. 14.29 carrying out ultrasonic testing of welded joints wherever required is the part of scope. 14.30 The welded surface irrespective of place of welding shall be cleaned of slag and painted at the center with primer paint to prevent corrosion at no extra cost towards this including supply of Paint for this purpose. All welds shall be painted with primer as specified in the painting schedule, once radiography and stress reliving works are over. 14.31 void 14.32 consumables, filler wires, electrodes, gas etc. are to be arranged by the contractor at his cost Weight of above welding consumables will not be considered for any payment. 14.33 void 14.34 Pre-heating / post heating and stress relieving after welding, where ever applicable, are par of erection work and shall be performed by the contractor in accordance with the instructions of BHEL Engineer within the quoted rates. All required heating equipments		radiograph, carrying out radiography shall be repeated till the joint is made acceptable. In
 14.29 carrying out ultrasonic testing of welded joints wherever required is the part of scope. 14.30 The welded surface irrespective of place of welding shall be cleaned of slag and painted at the center with primer paint to prevent corrosion at no extra cost towards this including supply of Paint for this purpose. All welds shall be painted with primer as specified in the painting schedule, once radiography and stress reliving works are over. 14.31 void 14.32 consumables, filler wires, electrodes, gas etc. are to be arranged by the contractor at his cost Weight of above welding consumables will not be considered for any payment. 14.33 Void 14.34 Pre-heating / post heating and stress relieving after welding, where ever applicable, are par of erection work and shall be performed by the contractor in accordance with the instructions of BHEL Engineer within the quoted rates. All required heating equipment 		case the joint is not repairable, the same shall be cut, re-welded and re-radiographed at
14.30 The welded surface irrespective of place of welding shall be cleaned of slag and painted at the center with primer paint to prevent corrosion at no extra cost towards this including supply of Paint for this purpose. All welds shall be painted with primer as specified in the painting schedule, once radiography and stress reliving works are over. 14.31 void 14.32 consumables, filler wires, electrodes, gas etc. are to be arranged by the contractor at his cost Weight of above welding consumables will not be considered for any payment. 14.33 Void 14.34 Pre-heating / post heating and stress relieving after welding, where ever applicable, are par of erection work and shall be performed by the contractor in accordance with the instructions of BHEL Engineer within the quoted rates. All required heating equipments		contractor's cost.
the center with primer paint to prevent corrosion at no extra cost towards this including supply of Paint for this purpose. All welds shall be painted with primer as specified in the painting schedule, once radiography and stress reliving works are over. 14.31 void 14.32 consumables, filler wires, electrodes, gas etc. are to be arranged by the contractor at his cost Weight of above welding consumables will not be considered for any payment. 14.33 void 14.34 Pre-heating / post heating and stress relieving after welding, where ever applicable, are part of erection work and shall be performed by the contractor in accordance with the instructions of BHEL Engineer within the quoted rates. All required heating equipment	14.29	carrying out ultrasonic testing of welded joints wherever required is the part of scope.
supply of Paint for this purpose. All welds shall be painted with primer as specified in the painting schedule, once radiography and stress reliving works are over. 14.31 void 14.32 consumables, filler wires, electrodes, gas etc. are to be arranged by the contractor at his cost Weight of above welding consumables will not be considered for any payment. 14.33 Void 14.34 Pre-heating / post heating and stress relieving after welding, where ever applicable, are part of erection work and shall be performed by the contractor in accordance with the instructions of BHEL Engineer within the quoted rates. All required heating equipment	14.30	The welded surface irrespective of place of welding shall be cleaned of slag and painted at
painting schedule, once radiography and stress reliving works are over. 14.31 void 14.32 consumables, filler wires, electrodes, gas etc. are to be arranged by the contractor at his cost Weight of above welding consumables will not be considered for any payment. 14.33 void 14.34 Pre-heating / post heating and stress relieving after welding, where ever applicable, are par of erection work and shall be performed by the contractor in accordance with the instructions of BHEL Engineer within the quoted rates. All required heating equipment		the center with primer paint to prevent corrosion at no extra cost towards this including
 14.31 void 14.32 consumables, filler wires, electrodes, gas etc. are to be arranged by the contractor at his cost Weight of above welding consumables will not be considered for any payment. 14.33 Void 14.34 Pre-heating / post heating and stress relieving after welding, where ever applicable, are part of erection work and shall be performed by the contractor in accordance with the instructions of BHEL Engineer within the quoted rates. All required heating equipment 		supply of Paint for this purpose. All welds shall be painted with primer as specified in the
 14.32 consumables, filler wires, electrodes, gas etc. are to be arranged by the contractor at his cost Weight of above welding consumables will not be considered for any payment. 14.33 Void 14.34 Pre-heating / post heating and stress relieving after welding, where ever applicable, are par of erection work and shall be performed by the contractor in accordance with the instructions of BHEL Engineer within the quoted rates. All required heating equipments 		painting schedule, once radiography and stress reliving works are over.
Weight of above welding consumables will not be considered for any payment. 14.33 Void 14.34 Pre-heating / post heating and stress relieving after welding, where ever applicable, are part of erection work and shall be performed by the contractor in accordance with the instructions of BHEL Engineer within the quoted rates. All required heating equipments	14.31	void
14.33 Void 14.34 Pre-heating / post heating and stress relieving after welding, where ever applicable, are par of erection work and shall be performed by the contractor in accordance with the instructions of BHEL Engineer within the quoted rates. All required heating equipments	14.32	consumables, filler wires, electrodes, gas etc. are to be arranged by the contractor at his cost.
14.34 Pre-heating / post heating and stress relieving after welding, where ever applicable, are par of erection work and shall be performed by the contractor in accordance with the instructions of BHEL Engineer within the quoted rates. All required heating equipments		Weight of above welding consumables will not be considered for any payment.
of erection work and shall be performed by the contractor in accordance with the instructions of BHEL Engineer within the quoted rates. All required heating equipments	14.33	void
instructions of BHEL Engineer within the quoted rates. All required heating equipment	14.34	Pre-heating / post heating and stress relieving after welding, where ever applicable, are part
		of erection work and shall be performed by the contractor in accordance with the
recording devices, thermocouples, recorders etc. shall be arranged by contractor.		instructions of BHEL Engineer within the quoted rates. All required heating equipment,
		recording devices, thermocouples, recorders etc. shall be arranged by contractor.
14.35 Any discrepancy in process, procedures provided, BHEL engineer decision is final.	14.35	

TECHNICAL CONDITIONS OF CONTRACT (TCC) Chapter – XV: PAINTING

The scope of the work will comprise of but not limited to the following:

(All the works mentioned hereunder shall be carried out within the accepted rate unless otherwise specified.)

15.1	Touch-up Painting:
13.1	Though the final painting is not there in the scope of the contractor, however, in case any
	shop painted structure/component is required to be repainted due to the reasons
	incidental to the work etc, such re-painting/finish painting of the components/structures
	shall have to done by contractor.
	Payment for application of Primer & Paint, including it's supply, for touch-up works in shop
	fabricated structure shall be paid separately as per BOQ. All required consumables &
	deployment of tools e.g wire brush, paint brush, Spray M/c, cleaning agents etc. are in the scope of contractor.
	scope of contractor.
	Contractor shall carry out surface preparation and touch-up painting works as per
	BHEL/Customer specification and instruction of BHEL engineer at site.
15.2	Paints and painting work carried at site shall confirm to the following codes and standards:
	IS:5 – Colour for ready mixed paints and enamels
	IS: 101 Part 1 to 9 - Methods of sampling and test for paints, varnishes and related
	products
	IS: 1477 Part I&II - Code of practice for painting of ferrous metals in building
	IS: 2932 – Specifications for enamel, synthetic and exterior,
	a) Under Coating
	b) Finishing
	Contractor shall satisfy himself, availability of all information in the specifications for
	proper selection of the paints and ensure their applications as per Codes.
15.3	Primer Painting: (wherever applicable incidental to touch-up painting & preventive
	painting)
	a) After surface preparation, two coats of zinc primer shall be applied. Primer shall be
	applied by either spraying or brushing ensuring a continuous film without "holidays".
	Primer coat shall be immediately applied without any time lag after the surface
	preparation.
	p. span attent
	b) All structure shall be carefully examined and where ever the primer coat is damaged
	shall be recoated with primer. However over the field welds, bolts and nuts etc. two primer
	coats as per a) shall be applied.
15.4	Finish Painting (wherever applicable incidental to touch-up painting & preventive
	painting)

TECHNICAL CONDITIONS OF CONTRACT (TCC) Chapter – XV: PAINTING

- a) After the primer coat has dried out, the surface shall be cleaned of dust without scratching or in any way damaging the primer coat. Over this, dry surface finish painting shall be carried out.
- b) Intermediate coat/Finish painting shall be carried out in two coats. Dry film thickness of each coat shall be as per the recommendation of the primer/paint manufacturer/BHEL Engineer. Minimum thickness including primer and paint coating shall be as per specification.
- c) Paint shall be applied either by brushing or spraying. It shall be ensured that brush marks are a minimum and the requirements of workmanship are as specified in IS: 1477 (for site painting works on systems, structures and components).
- d) Paint used shall be stirred frequently to keep the pigment in suspension. Paint shall be of ready mixed type in original sealed containers as packed by the paint manufacturer. Addition of thinners shall not be permitted.
- e) No painting shall be done in frost/foggy weather or when the humidity is high enough to cause condensation on the surface to be painted. Paint shall not be applied when the temperature of the surface to be painted is 5° C or below.

15.5 **Touch-up painting on damaged areas -**

- a) For coatings damaged up to metal surface preparation shall be carried out by manual cleaning. Minimum 6 inches adjoining area with existing coating shall be roughened by wire brushing, emery paper rubbing etc., for best adhesion of patch primer. Primer coat of touch-up primer has to be applied by brush immediately after the surface preparation.
- b) Over this primer coat, intermediate/finish coat and final finish coat shall be applied as covered above by brush within maximum seven (7) days of application of touch up primer.

Payment for application of Primer & Paint, including it's supply, for touch-up works in shop fabricated structure shall be paid separately as per BOQ.

Supply of paint shall also be in the scope of contractor.

Painting of welded areas / painting of areas exposed after removal of temporary supports / touch-up painting on damaged areas of employer's structures, where inter-connection, welding / modification etc. has been carried out by the bidder.

Clean the surface to remove flux spatters and loose rust, loose coatings in the adjoining areas of weld seams by wire brush and emery paper.

Painting procedure to be followed for touch-up painting on damaged areas.

TECHNICAL CONDITIONS OF CONTRACT (TCC) Chapter – XV: PAINTING

15.7	The scope of work includes colour bands, stencilling, marking and signs for direction of						
	flow/rotation, names etc of approved colours as per the standard colour codes and						
	specifications specified in tender specification or as advised by BHEL/Customer engineer						
	at site for the equipments / components covered in these specifications.						
15.8	In certain isolated instances where it is not possible to clean the equipments as explained						
	above, cleaning by grinding might have to be resorted to. No damage to the						
	equipment/components should be caused.						
15.9	Surface to be painted should be free of oil and grease. It should be removed by using						
	suitable cleaning agents including permitted solvents. Surface cleaned by chemical agent,						
	if required, shall be treated further as prescribed in use of such cleaning agents.						
15.10	During the preparation of surface, if the shop coat is damage by chemical or by mechanical						
	means, contractor shall repair the same free of cost.						
15.11	Specified drying time shall be permitted from one to another coat.						
15.12	This work requires working at higher altitudes from ground level. Contractor shall take						
	sufficient precautions to avoid any accident and hazard in all respects. The ropes, ladders,						
	scaffolding materials, clamps etc and climber used should be of standard quality for safe						
	and smooth execution of work.						
15.13	Contractor shall carry out the work in such a way that other erected equipment, structure,						
	civil foundations and other property are not damaged. For damages in any of such cases						
	due to lapses by Contractor, BHEL shall have the right to recover the cost of such damages						
	from the Contractor.						
15.14	Contractor shall take due care to cover/protect the equipment which are already painted						
	while carrying out the painting of other adjacent equipment. If so happens, it shall be						
	cleaned and repainted by the Contractor without any extra charges.						
15.15	Final painting work shall be started after obtaining clearance from BHEL engineers and as						
	per his instructions.						
15.16	Acceptance of Final Painting for required thickness shall be as per the thickness measured						
	by Elcometer by customer/BHEL Engineer. Contractor shall have to carry out painting till						
	the required thickness is achieved.						

TECHNICAL CONDITIONS OF CONTRACT (TCC) Chapter – XVI: PRESERVATION & PROTECTION OF COMPONENTS

The scope of the work will comprise of but not limited to the following:

(All the works mentioned hereunder shall be carried out within the accepted rate unless otherwise specified.)

16.1	At all stages of work, equipments/materials in the custody of Contractor, including those erected, will have to be preserved as per the instructions of BHEL. Necessary preservation agents including the primer & paint, for the above work shall be provided by the Contractor.
16.2	The Contractor shall make suitable security arrangements including employment of security personnel and ensure protection of all materials/ equipment in their custody and installed equipments from theft/fire/pilferage and any other damages and losses.
16.3	The entire surplus, damaged, unused materials, packaging materials / containers, special transporting frames, gunny bags, etc shall be returned to BHEL stores by the Contractor.
16.4	The Contractor shall not waste any materials issued to agency. In case it is observed at any stage that the wastage/excess utilisation of materials is not within the permissible limits, recovery for the excess quantity used or wasted will be effected with departmental charges from the Contractor. Decision of BHEL on this will be final and binding on the Contractor.
16.5	For any class of work for which no specifications have been laid down in these specifications, work shall be executed as per the instructions of BHEL.

<u>Package Description:</u> Erection, Alignment, Bolting/Welding, Roofing & Cladding, BOIs Work of Main Power House (PH#1&2) and CCR (Common Control Room) Structure including handling of materials at BHEL / Client's Stores / Storage yard and Transportation and Scope of work includes supply of all Material (As per TCC and BOQ), Consumables, labour, tools and plants, Touch-up painting as and where required (including supply of paint) for Unit #1 & 2 at 2X800 MW NTPC Singrauli STPP Stage-III, Sonebhadra, UP

Table-20.1

	<u> </u>			
ST NO.	Item Description	Unit	Total Quantity (Pkg- A+Pkg-B)	Weightage
A.	Erection/Installation of items mentioned hereunder (Supply under BHEL Scope)			
2300	STRUCTURAL WORKS: Structural steel Erection works including all labour, material, consumables, T&Ps (unless otherwise specified in BOQ/TCC contract specification), handling etc. at all level as per specification, drawings and as directed by engineer - in - charge.			
A2301	Taking delivery of steel from BHEL stores / store yard, loading, transportation, unloading, pre-assembly and erection, bolting, welding of shop fabricated Medium and High Tensile structural steel (Grade designation E250/E350, conforming to IS 2062, with rolled section / built up section / combination of both conforming to IS:2062, pipes conforming to IS:1161/ IS:1239, chequered plate conforming to IS: 3052, mild steel rounds, monorails, stays, safety chains, ladders, MS grating etc. in columns, beams, gantry girders, bunkers, silos, hoppers, roof trusses, portals, laced purlins, space frames, hangers, struts, monorails, galleries, stiffeners, wall beams, sheeting runners, brackets, stub columns, bracings, cleats, trestles, base plates, splice plates, chequered plate flooring, decking and seal plates, steel frame grid over false ceiling, walkway platforms, ladders, stairs, stringers, toe-guard/kick plate, grizzly gratings, treads, landings, hand-rails etc., welding electrodes and other consumables, alignment, erection bolts & nuts (weight of erection bolts, nuts and welds not payable), assembly, edge preparation, erection scheme, protection against damage in transit, stability of structures, installation of temporary structures, setting column bases, surface preparation by means of manual or mechanical power tools as per IS:1477 part 1,	МТ	18,482.0	0.81147078

	rectification, dismantling and removal of all temporary structures (weight of temporary structures not payable)			
2307	Transportation, erection and alignment, fabrication where required of factory made electroforged galvanised grating units with mild steel having minimum galvanisation conforming to IS:2062 in flooring, platforms, drain and trench covers, walkways, passages, staircases with edge binding strips and anti-skid nosing in treads etc. including fixing clamps, fittings, fixtures, all taxes, duties, packing, grinding, drilling, welding, edge preparation, etc. all complete.			
a	Minimum galvanisation of 610 g/sqm	MT	407.0	0.01786974
2308	Transportation, erection and alignment, fabrication where required of factory made galvanised welded grating units (minimum 610 g/sqm galvanisation) with mild steel conforming to IS:2062 in flooring, platforms, drain and trench covers, walk-ways, passages, staircases with edge binding strips and anti-skid nosing in treads etc. fixing clamps, fittings, fixtures, all taxes, duties, packing, grinding, drilling, welding, edge preparation, etc. all complete.	MT	0.5	0.00002195
2311	Fixing in position of permanent mild steel bolts (class 4.6 as per IS: 1367 and grade `C' as per IS: 1363) and nuts, washers etc. up to and inclusive of 39 mm diameter and upto 300mm long for structural steel work etc all complete.	MT	1.8	0.00008114
2312	Fixing in positing of high strength structural bolts (of property class 8.8 and product grade `C' as per IS: 1367) and conforming to IS: 3757 and high strength structural hardened and tempered nuts (of property class `8' as per IS:1367) conforming to IS:6623 with hardened and tempered washers as per IS:6649 etc. up to and inclusive of 39 mm diameter and upto 300 mm long for structural steel work etc all complete.	MT	277.2	0.01217206
A2312	Fixing in positing of high strength structural bolts (of property class 10.8/10.9 and product grade `C' as per IS: 1367) and conforming to IS: 3757 and high strength structural hardened and tempered nuts (of property class `8' as per IS:1367) conforming to IS:6623 with hardened and tempered washers as per IS:6649 etc. up to and inclusive of 39 mm diameter and upto 300 mm long for structural steel work etc all complete.	MT	462.1	0.02028677
2320	Fabrication and fixing of stainless steel pipe hand railing conforming to SS 409 of 32 mm/40 mm dia including transportation, loading/unloading, painting etc. all complete.	MT	11.0	0.00048297

A2322	Fabrication and fixing of galvanised MS pipe hand railing (Min. 1000 mm high) of 32mm/40mm/50mm dia (Medium Class) including transportation, loading/unloading, painting etc. all complete	MT	30.0	0.00131718
1500	ROOFING / SIDE CLADDING: Roofing / side cladding work including all labour, material, consumables, T&Ps (unless otherwise specified in BOQ/TCC contract specification), equipment, transportation, handling, scaffolding, laps, hooks, washers, corner pieces etc. at all level as per specification, drawings and as directed by engineer - in - charge.			
A1502	METAL DECK SHEET Type-I, Fixing permanently color coated galvanised MS troughed metal sheet decking plate (including preparing erection drawings showing cut outs, fixing details, overlaps of sheets etc. and getting it approved from BHEL) of approved colour over roof purlins for cast-in-situ roof slab as per relevant IS code and Grade as per specification. Bare metal thickness(BMT) of deck plate shall be minimum 0.8mm with minimum trough depth of 44mm (or as per design whiever is higher) of grade G250 as per AS1397/grade SS255 as per ASTM A653M/ grade S250GD as per EN 10326 with zinc coating to class Z275 and shall serve as permanent shuttering to the roof slab 40mm - 100mm thick measured over crest of metal decking & shall have adequate strength to support weight of green concrete and imposed loads of min 100 kg/sqm (for two span condition) during construction between beams as per manufacturer's recommendations/ calculations/ test certificates for approval including fixing of plates to beams, side lapping, end lapping etc. all complete for below mentioned spans. The sheet shall be permanently coated with silicon modified polyster (SMP silicon content 30%-50%) paint or super polyster paint of minimum 20 micron DFT on exposed surface (facing operating floor) over primer coat of minimum 5 micron(nominal) and minum 10 micron (nominal) SMP or super polyester paint over primer coat of minum 5 micron (nominal) on other face. SMP and polyster paint system sahll be of idutrial finish of product type 4 of AS/NZ2728, including fixing of sheet to top flange of beam with drawn arc welding of headed shear anchor studs @ 260mm c/c in the trough and stich screws between two adjacent sheets and sealing with epoxy sealant.The shear anchor studs shall confirm to type B studs specified in AWS D1.1/D1.1M or equivalent as shear connector of 16 mm dia & 65 mm length manufactured from cold drawn round steel bars confirming to ASTM A 29 of grade designation 1010 through 1020 of standard quality with either semi killed or killed welded			

	welding through metal deck sheet. (Metal Deck Sheet shall be issued by BHEL free of cost)			
a	Span Upto 1800mm	МТ	86.9	0.00381368
B1502	METAL DECK SHEET Type-II, Fixing permanently color coated galvanised MS troughed metal sheet decking plate (including preparing erection drawings showing cut outs, fixing details, overlaps of sheets etc. and getting it approved from BHEL) of approved colour over roof purlins for cast-in-situ roof slab as per relevant IS code and Grade as per specification. Bare metal thickness(BMT) of deck plate shall be minimum 0.8mm with minimum trough depth of 44 mm (or as per design whiever is higher) of grade G250 as per AS1397/grade SS255 as per ASTM A653M/ grade S250GD as per EN 10326 with zinc coating to class Z275 and shall serve as permanent shuttering to the floor slab 150 mm thick measured over crest of metal decking & shall have adequate strength to support weight of green concrete and imposed loads of min 100 kg/sqm (for two span condition) during construction between beams as per manufacturer's recommendations/ calculations/ test certificates for approval including fixing of plates to beams, side lapping, end lapping etc. all complete for below mentioned spans. The sheet shall be permanently coated with silicon modified polyster(SMP silicon content 30%-50%) paint or super polyster paint of minimum 20 micron DFT on exposed surface (facing operating floor) over primer coat of minimum 5 micron(nominal) and minum 10 micron (nominal) SMP or super polyester paint over primer coat of minum 5 micron (nominal) and minum 10 micron (nominal) SMP or super polyester paint over primer coat of minum 5 micron (nominal) on other face. SMP and polyster paint system sahll be of idutrial finish of product type 4 of AS/NZ2728, including fixing of sheet to top flange of beam with drawn arc welding of headed shear anchor studs @ 260mm c/c in the trough and stich screws between two adjacent sheets and sealing with epoxy sealant. The shear anchor studs shall confirm to type B studs specified in AWS D1.1/D1.1M or equivalent as shear connector of 19 mm dia & 100 mm length manufactured from cold drawn round steel bars confirming to ASTM A 2			
а	Span Upto 1800mm	MT	362.5	0.01591549
b	Span Exceeding 1800mm and upto 2500 mm	MT	87.3	0.00383256

11707			2077	0.00044555
A1505	Fixing External/ Inner sheet of Permanent colour coated metal cladding / roofing with troughed M.S. sheets of minimum 0.5 mm bare metal thickness of min. grade G350 as per AS1397/grade SS340 class 4 or as per ASTM A792M/ grade S350 GD as per EN 10326 with zinc coating to class Z275 / aluminium zinc alloy coating to class AZ150 on both sides (including preparing erection drawings showing cut outs, fixing details, overlaps of sheets etc. and getting it approved from BHEL) including fixing to supports / rails by concealed fixing system, corrosion resistant self tapping / self drilling type fasteners with suitable cap, flashing, etc. all complete over columns, beams, bracings etc. at all levels. The exposed face the sheet shall be permanently coated with silicon modified polyester(SMP silicon content 30%-50%) paint or super polyester paint of minimum 20 micron DFT on exposed surface over primer coat of minimum 5 micron and minimum 10 micron SMP or super polyester paint over primer coat of minimum 5 micron on other face. SMP tc. all complete for below mentioned spans. The sheet shall be permanently coated. Self drilling/self tapping screws/fastners shall be supplied by contractor. (Cladding/roofing sheet shall be issued by BHEL free of cost)	MT	207.5	0.00911083
A1519	Fixing Factory made (Continuous Line) prefabricated sandwiched Permanent colour coated metal cladding comprising top sheet as troughed(minimum depth of trough shall be 30 mm) (including preparing erection drawings showing cut outs, fixing details, overlaps of sheets etc. and getting it approved from BHEL) permanently colour coated sheet & bottom sheet as plain permanently colour coated for covering of exposed metal/concrete / brick surfaces with insulation shall be of Polyurethane type of minimum 50mm thick (excluding trough). The polyurethane shall be Chlorofluorocarbon (CFC) free and self-extinguishing and shall conform to IS 12436: 1988. It shall have Modular Density 40 +/- 2 Kg/m3 and Thermal Conductivity @ 10 Deg.C 0.017 - 0.020 W/M 0k, Water absorption (% by vol) 3.1, Critical Oxygen Index 23 and Compressive Strength 1.2 Kg/sq.cm, sandwiched between the two sheets, each sheet shall be high strength tensile steel sheet 0.5mm bare metal thickness (minimum) of YS350 as per IS 15961 /grade G350 as per AS1397 / grade SS340 class 4 as per ASTM A792M / grade S350GD as per EN 10326 with zinc coating to class Z 275 / aluminium-zinc alloy coating to class AZ150 on both sides, both sheet shall be permanently coated with silicon modified polyester (SMP with silicon content of 30% to 50%) paint of minimum 20 micron DFT on exposed surface on 5 microns (min.) epoxy primer/phosphate primer coat and 10 micron (min.) SMP on 5 micron (min.) epoxy primer/phosphate primer on other face, SMP paint system shall be of industrial finish of product type 4 of	MT	75.5	0.00331646

	AS/NZS 2728,troughed sheet shall be of approved profile, sectional properties, (suitable for the specified loading / deflection and purlins / runner spacing), colour and shade, at all levels, including all labour, materials, equipment, handling, transportation, special coated fastener conforming to corrosion resistant Class 3 of AS3566 and tested for 1000 hours salt spray test, fixing insulated sandwiched metal sheet with the structural members below for supporting the sheeting system, scaffolding, equipment, end and side laps, cutting of openings, preparation of working drawings, testing, etc., all complete, as per specifications. Sealant used for cladding shall be butyl based, two parts poly sulphide or equivalent approved, non stainless material and be flexible enough not to interface with fit of the sheets. Coated surface shall be provided with a protected guard film (polyethylene) of about 40 microns to avoid any damage to the coating during handling. Overlap shall be min. 100 mm or as specified by manufacturer. Self drilling/self tapping screws/fastners shall be supplied by contractor. (Cladding/roofing sheet shall be issued by BHEL free of cost)			
B1.	Other items mentioned hereunder (Supply+Fixing under contractor scope)			
A904	Providing and fixing single or double steel door shutters with 35mm (min) thk flush design shutter comprising of two outer sheets of 18 gauge steel sheets rigidly connected and reinforced inside with continuous vertical 20 gauge stiffeners, spot welded in position at not more than 150mm on centres including void filled with mineral wool (density as per specification), all fittings, Godrej or equivalent make mortice lock with handle on both sides, shop and final painting etc all complete.	SQM	150	0.00429711
A909	Providing and fixing anodised aluminium work of INDAL, Jindal, Hindalco or other equivalent approved make for door frames, windows, ventillators, partitions, railing etc with extruded standard tubular and other sections(of minimum 2mm wall thickness) including all fittings & fixtures and accessories of approved make conforming to IS733 and IS1285, anodised and electro color dyed to required shade according to IS 1868 (minimum anodic coating of grade AC15), fixed with rawl plugs, expansion fasteners, SS screws or with fixing clips, including necessary filling of gaps at junctions, at top, bottom and sides with required PVC/neoprene felt for bi-metalic protection etc. including preperation of working drawings, aluminium cleat angle, aluminium snap-on-beading for glazing/panelling, stair case tread nosing, with all fittings and fixtures (like tower bolts, handles, door stopper with rubber shoes, 'L' drops, stays, floor springs, hydraulic door closures etc.), CP brass/stailess steel	Kg	15040	0.02448086

	screws, providing and fixing hinges/pivots, and making provision for fixing of fitting wherever required including cost of PVC/neoprene gasket, all complete as per drawing, specification and instructions of engineer in charge (Glazing and panelling shall be paid seperately). Weight of aluminium section only shall be measured			
A912	Providing and fixing pressed steel frames(complying general requirements of IS 4531) fabricated from 1.2 mm thick M.S sheet mortised, reinforced drilled and tapped for hinges and locks bolts strikes, hold fasts adjustable floor anchors, floor tiles/weather bars ,paintings etc all complete as per specifications.	Kg	2976	0.00227578
A913	Providing and fixing in position rolling shutter of hot rolled double dipped galvanised steel lath section of 18 SWG tested mild steel strips at 75mm rolling centres interlocked together through their entire length and jointed together at the end by end locks mounted on specially designed pipe shaft with brackets, side guides of 75mm wide and 3mm thick(min.) and arrangements for inside and outside locking with push and pull operation including wire springs, top/hood cover 0.9mm thick (min.), factory galvanized, primed & field painted, partly grilled (as required) with approved enamel paint etc, all complete as per IS 6248 and specification of approved make of following types: The bottom lath shall be coupled to a lock plate fabricated from 3mm thick galvanised steel plate and securely rivetted with stiffening angles.(partly coiled and lath/full lath).			
С	Electrically & Mechanically operated	SQM	350	0.01147041
915	Providing, fixing and fitting of glazing of first grade class in steel/aluminium/wooden frames, where ever required, cleaning after fixing including hardware, gaskets, clips, beadings etc. all complete.			
h (a)	6 mm thick clear reflective toughened safety glass of Saint Gobain(India) or Asahi (India) or equivalnet make and should have solar factor 25% or less, Maximum U-vlaue 3.3W/SQMK,	SQM	1,098	0.00539587

	VLT min 30%, light reflection internal 10 to 15%, light reflection			
	external 10 to 20%, shading coefficient (0.25-0.28) (including supply)			
Ah	6 mm thick clear toughened glass conforming to IS 5437	SQM	1,115	0.00596783
AhB	8 mm thick clear toughened glass	SQM	75	0.00048979
AhC	8 mm thick clear toughened fire resistant glass	SQM	75	0.00245795
A1503	Providing and fixing shear anchor studs for fixing metal deck sheet to floor structural beams conforming to Type-B studs specified in AWS D1.1/D1.1M or equivalent as shear connector of 19mm diameter and 100mm length manufactured from cold drawn round steel bars conforming to the requirement of ASTM A 29, of grade designation 1010 through 1020, of standard quality with either semi-killed or killed, welded by Drawn Arc Stud Welding through metal deck sheet etc all complete as per specification.	Kg	15600	0.00904141
B1503	Providing and fixing shear anchor studs for fixing metal deck sheet to roof structural purlins conforming to Type-B studs specified in AWS D1.1/D1.1M or equivalent as shear connector of 16mm diameter and 65mm length manufactured from cold drawn round steel bars conforming to the requirement of ASTM A 29, of grade designation 1010 through 1020, of standard quality with either semi-killed or killed, welded by Drawn Arc Stud Welding through metal deck sheet etc all complete as per specification.	Kg	2600	0.00150690
A2318	Providing and fixing in position PTFE type sliding bearings of reputed manufacturer for required vertical load and end displacement/rotation as per approved construction draiwngs. PTFE bearing shall be sliding against highly polished stainless steel and the coefficient of friction between them shall be less than 0.06 at 55 kg/sq.cm. In order to prevent cold flow in PTFE surface it shall be rigidly bonded by a special high temperature resistance adhesive to the stainless steel substrata. The stainless steel surface that slides against the PTFE is mirror polished. The stainless steel shall be bonded to the top plate by special high strength adhesive. The thickness of stainless steel plate shall be between 1.0 mm to 1.5 mm.			
b	25 Tons	EACH	10	0.00053384
С	40 Tons	EACH	8	0.00049631
d	50 Tons	EACH	4	0.00027166

e	60 Tons	EACH	6	0.00046496
f	100 Tons	EACH	4	0.00034957
2328	Supply, fixing lightning arrester and air terminal over roof of power house building, pump house and other structures inluding all materials, labour, electrodes etc complete (all materials to be supplied by the contractor).	EACH	10	0.00010999
B2.	Touch-up Painting			
i	Surface preparation by means of manual or mechanical power tools as per IS:1477 part 1, Providing and applying two component moisture curing zinc (ethyl) silicate primer coat (having minimum 80% of metallic Zinc content in dry film, solid by volume minimum 60% ± 2 %) of minimum 70 micron DFT to be applied over surface conforming to Sa 2 ½ finish of SO 8501-1 with surface profile 40-60 Micron. The primer coat shall be applied by airless spray technique. Zinc dust composition and properties shall be Type-II as per ASTM D520-00 all complete (1 MT = 24 Sqm considered for this tender)	MT	1000	0.00123083
ii	Surface preparation by means of manual or mechanical power tools as per IS:1477 part 1, Providing and applying (with airless spray technique) intermediate coat of two component polyamide cured epoxy with MIO Content (containing lamellar MIO minimum 30% on pigment, solid by volume minimum 80% ±2%) of minimum 100 micron DFT to be applied after an interval of minimum 24 hours (from the application of primer coat by airless spray technique.) and of approved make including protection and cleaning, scoffolding etc. all complete as per specification for all structures . (1 MT = 24 Sqm considered for this tender)	MT	1000	0.01473367
iii	Surface preparation by means of manual or mechanical power tools as per IS:1477 part 1, Providing and applying Finish coat of two-pack aliphatic Isocyanate cured acrylic finish paint (solid by volume minimum 55% $\pm 2\%$) with Gloss retention (SSPC Paint Spec No 36, ASTM D 4587, D 2244, D 523) of Level 2 (after minimum 1000 hours exposure, Gloss loss less than 30 and colour change less than 2.0 Δ E) and minimum 70 micron DFT shall be applied after an interval of minimum 10 hours (from the application of sealer coat), Colour and shade of the coat shall be as approved by the Employer) over steel sections already having intermediate coats including protection and cleaning,	MT	1000	0.01473367

scoffolding etc. all complete as per specification for all structures .(1 MT = 24 Sqm considered for this tender)		

TECHNICAL CONDITIONS OF CONTRACT (TCC)

Chapter-XVIII: ANNEXURES

18.1 THIS TENDER SPECIFICATION CONSISTS OF FOLLWING ANNEXURE:

SI. No	DESCRIPTION
Annexure-A	BHEL's standard guidelines for worker's accommodation/establishment
Annexure-B	Workers accommodation drawings of customer
Annexure-C	HSE Plan for Singrauli site
Annexure-D	T&P Hire Charges
Annexure-E	HSFG Bolt Tightening procedure
Annexure-F NTPC Technical specification part	
Annexure-G	Site Meteorological data

NOTE- ALL THE ABOVE-MENTIONED ANNEXURE ARE UPLOADED ON E-PROCUREMENT PORTAL