

REF.	Comp. Drg.	 Form No. 2038	उत्पाद मानक परिणामित्र शाप/अभि.निर्देश	PRODUCT STANDARD TRANSFORMER SHOP / ENGG. INSTRUCTIONS	TR20169C																																
					1 पृष्ठों में 1	PAGE 1 OF 1																															
TITLE: SPECIFICATION FOR DRY AIR AND DRY AIR CYLINDER																																					
A. DRY AIR CYLINDER																																					
<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <td colspan="2">Water capacity (Liters)</td> <td>46.7</td> </tr> <tr> <td colspan="2">Gas Capacity (m₃)</td> <td>7 at min. pressure of 135 kg/cm²</td> </tr> <tr> <td colspan="2">Maximum working pressure (kg/cm² at 15°C)</td> <td>150</td> </tr> <tr> <td colspan="2">Hydraulic Test Pressure (kg/cm²)</td> <td>250</td> </tr> <tr> <td rowspan="6" style="text-align: center;">Nominal Dia.(approx.)</td> <td rowspan="2" style="text-align: center;">Inside (d)</td> <td>221 Spun Type</td> </tr> <tr> <td>218.0 Solid Drawn</td> </tr> <tr> <td rowspan="4" style="text-align: center;">Outside (D)</td> <td>232 Spun type</td> </tr> <tr> <td>230 Solid Drawn</td> </tr> <tr> <td colspan="2">Minimum wall thickness : t (mm)</td> </tr> <tr> <td colspan="2">5.5 Spun type</td> </tr> <tr> <td colspan="2">6.0 Solid Drawn</td> </tr> <tr> <td colspan="2" rowspan="3">Total length approx. (H) mm. without valve & cap</td> <td>1370 Spun type</td> </tr> <tr> <td>1405 Solid Drawn</td> </tr> <tr> <td>Tare weight excluding valve & cap approx. (kg.)</td> <td>54</td> </tr> </table>							Water capacity (Liters)		46.7	Gas Capacity (m ₃)		7 at min. pressure of 135 kg/cm ²	Maximum working pressure (kg/cm ² at 15°C)		150	Hydraulic Test Pressure (kg/cm ²)		250	Nominal Dia.(approx.)	Inside (d)	221 Spun Type	218.0 Solid Drawn	Outside (D)	232 Spun type	230 Solid Drawn	Minimum wall thickness : t (mm)		5.5 Spun type		6.0 Solid Drawn		Total length approx. (H) mm. without valve & cap		1370 Spun type	1405 Solid Drawn	Tare weight excluding valve & cap approx. (kg.)	54
Water capacity (Liters)		46.7																																			
Gas Capacity (m ₃)		7 at min. pressure of 135 kg/cm ²																																			
Maximum working pressure (kg/cm ² at 15°C)		150																																			
Hydraulic Test Pressure (kg/cm ²)		250																																			
Nominal Dia.(approx.)	Inside (d)	221 Spun Type																																			
		218.0 Solid Drawn																																			
	Outside (D)	232 Spun type																																			
		230 Solid Drawn																																			
		Minimum wall thickness : t (mm)																																			
		5.5 Spun type																																			
6.0 Solid Drawn																																					
Total length approx. (H) mm. without valve & cap		1370 Spun type																																			
		1405 Solid Drawn																																			
		Tare weight excluding valve & cap approx. (kg.)	54																																		
B. DRY AIR																																					
<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <td>O₂</td> <td>21.5+/-2 ppmv</td> </tr> <tr> <td>N₂</td> <td>78.5+/-2 ppmv</td> </tr> <tr> <td>Purity</td> <td>95.95% minimum</td> </tr> <tr> <td colspan="2">Acceptable Impurity level: H₂O ≤ 4ppmv, CO₂ ≤ 2ppmv, THC ≤ 2 ppmv</td> </tr> <tr> <td>Dew Point Temperature (minimum)</td> <td>-60 °C</td> </tr> </table>							O ₂	21.5+/-2 ppmv	N ₂	78.5+/-2 ppmv	Purity	95.95% minimum	Acceptable Impurity level: H ₂ O ≤ 4ppmv, CO ₂ ≤ 2ppmv, THC ≤ 2 ppmv		Dew Point Temperature (minimum)	-60 °C																					
O ₂	21.5+/-2 ppmv																																				
N ₂	78.5+/-2 ppmv																																				
Purity	95.95% minimum																																				
Acceptable Impurity level: H ₂ O ≤ 4ppmv, CO ₂ ≤ 2ppmv, THC ≤ 2 ppmv																																					
Dew Point Temperature (minimum)	-60 °C																																				
NOTES: - Cylinder shall be generally as per IS:7285. - Cylinder shall be fitted with valve to IS:3224. - T.C. for each cylinder and approval letter from chief controller of explosives Nagpur shall be furnished.																																					
TR20169C PAGE 1 OF 1																																					
पुनः Rev. 00		वितरण DISTRIBUTION.		सं.	स्वीकृत किया : APPROVED : sd/ A. DEOTA																																
		TRE/TRM/FTM/ TRX/TTG /QC-TCB/QA-TCB /JHANSI		जारी किया ISSUED टीआरई मानक /TRE/STD तैयार किया:-PREPD. NM	दिनांक: DATE: 23.01.19																																

