



PRODUCT ENGINEERING / V & SB
TECHNICAL DELIVERY CONDITIONS FOR
SUBDELIVERY COMPONENTS OF SOOT BLOWERS

SPEC:SB:0014

Rev. 01

SHEET NO. 1 of 1

1.0 Description:

1. No Slip Belt
2. No Slip Pulley – 32
3. No Slip Pulley – 64
4. No Slip Pulley – 20
5. No Slip Pulley – 72

1.1 Application:

Drive for position indicator in furnace probe.

2.0 TABLE (DETAILS):

SL.No	COMPONENTS	NO SLIP BELT	NO SLIP PULLEY 32	NO SLIP PULLEY 64	NO SLIP PULLEY 20	NO SLIP PULLEY 72
2.01	Material Code	973661530000	973661540000	973661550000	963539490000	963539520000
2.02	Diametrical Pitch (Dp)	32	32	32	32	32
2.03	No. of teeth	158	32	64	20	72
2.04	Pitch Dia. (In Inches)	4.938	1	2	0.625	2.25
2.05	Outside Dia. (In Inches)	5.031	1.0625	2.0625	0.688	2.313
2.06	Bore Dia. (In Inches)	--	3/16	1/4	3/16	1/4
2.07	Colour	Blue	White(Anodised)	White(Anodised)	White(Anodised)	White(Anodised)
2.08	Material	Molded and spliced Polyurethane with Multiple stands of Ducton core.	Aluminium	Aluminium	Aluminium	Aluminium
2.09	Accessories	--	1 Set screw	1 Set screw	1 Set screw	1 Set screw
2.10	Quantity/Probe	1	1	1	1	1
2.11	Special Remarks	PIC. Catalogue No. FA - 158 - 32	PIC. Catalogue No. FC - 4 - 32	PIC. Catalogue No. FC - 6 - 64	PIC. Catalogue No. FC - 4 - 20	PIC. Catalogue No. FC - 6 - 72

Note: PIC Catalogue number is furnished for procurement from M/s PIC.

SUPPLY FROM OTHER VENDORS SHALL BE CLEARED AFTER SAMPLE APPROVAL.

Rev:01 Dt.13/07/2015

Codes 963539490000 & 963539520000 added.

Prepared By(J SANKAR)

Checked By(SHIVAM GUPTA)

Approved By (HIRENDRA RAUT)