

MPR NO : 20161058

DATED : 04/03/2017

ANNEXURE-A

TECHNICAL SPECIFICATIONS

Item Sr. No.	Item Description	Qty.	Remarks
1	COMPLETE SET OF MOTORISED OIL LUBRICATION UNIT & ELECTRONIC LUBRICATION CONTROLLER CONSISTING OF 3-PHASE 415VAC/50HZ/4-POLE PUMP MOTOR, TANK CAPACITY= 3 L, DISCHARGE=1.0-1.5 LPM, PRESSURE SETTING 10-15 BAR FITTED WITH PRESSURE SWITCH & FLOAT SWITCH, PRESSURE GAUGE 0-25 BAR, RELIEF VALVE, OUTPUT PORT=M10X1, OIL LEVEL INDICATION WINDOW, VERTICAL MOUNTING TYPE RESERVOIR WITH MOUNTING BRACKETS, 220VAC/50HZ ELECTRONIC LUBRICATION CONTROLLER, ON TIME=5 SEC, OFF TIME 2-120 MIN (ADJUSTABLE), PRESSURE SWITCH, FLOAT SWITCH INTERFACE, PANEL MOUNT WITH MAINS ON, LUB ON, LUB FAULT, LOW LEVEL INDICATION, FAULT RELAY & OUTPUT RELAY.	10 Set	Vendor to Comply and Inform "Make" & "Model No. of the offered Unit along with the offer.
2	MOTORISED OIL LUBRICATION UNIT CONSISTING OF 3-PHASE 415VAC/50HZ/4-POLE PUMP MOTOR, TANK CAPACITY= 5 L, DISCHARGE=1.0-1.5 LPM, PRESSURE SETTING 15-20 BAR FITTED WITH PRESSURE SWITCH & FLOAT SWITCH, PRESSURE GAUGE 0-25 BAR, RELIEF VALVE, OUTPUT PORT=M10X1, OIL LEVEL INDICATION WINDOW, VERTICAL MOUNTING TYPE RESERVOIR WITH MOUNTING BRACKETS.	5 No.	Vendor to Comply and Inform "Make" & "Model No. of the offered Unit along with the offer.

Hekeent
04.03.17
(Vijayant Kumar)

Om
04/3/17
Tenzin