

SNO	MATERIAL CODE / DESCRIPTION	UNIT	QTY	LOT	QTY	DELY DT
1	IM4550201700 Supply of Pneumatic Angle Grinder (DCD) with wheel guard assembly, hose adaptor and wheel mount pin spanner complying specifications as given below. Wheel capacity - 230mm (9") Free speed - 6000 rpm(min) Spindle thread size - M16 Weight 5.4 Kg Appx without wheel guard Air Inlet -1/2"RC Air pressure- 5-6 Kg/Cm2 Model CP make CP319A or its equivalent	NO	30.000	01	30.000	31/10/2019
2	IM8290108400 Supply of Pneumatic Angle Grinder with wheel guard assembly, hose adaptor and wheel mount pin spanner complying specifications as given below. Wheel capacity -100mm (4") Free speed - 12000 rpm(min) Weight- 2 Kgs Appx without wheel guard Air Inlet-1/4" BSP with nipple Air pressure- 5-6 Kg/Cm2 Model CP make CP3450 or its equivalent.	NO	50.000	01	50.000	31/10/2019
3	IM8290101000 SUPPLY OF PNEUMATIC IMPACT WRENCH. PISTOL GRIP TYPE WITH HOSE DAPTOR AND NIPPLE: SQUIRE DRIVE - 1/2" MAX. WORKING TORQUE - 500Nm WEIGHT - 3 KGS MAX AIR PRESSURE - 5 TO 6 KG/Sq.cm AIR INLET - 1/4" BSP TO BE FURNISHED WITH FULL SPECIFICATION, MAKE, MODEL NO.. AND RELEVANT CATALOGUE	NO	30.000	01	30.000	31/10/2019
4	IM8290101100 SUPPLY OF PNEUMATIC IMPACT WRENCH. PISTOL GRIP TYPE WITH HOSE DAPTOR AND NIPPLE: SQUIRE DRIVE - 3/4" MAX. WORKING TORQUE - 900Nm WEIGHT - 5.5 KGS MAX AIR PRESSURE - 5 TO 6 KG/Sq.cm AIR INLET - 3/8" BSP TO BE FURNISHED WITH FULL SPECIFICATION, MAKE, MODEL NO. AND RELEVANT CATALOGUE	NO	20.000	01	20.000	31/10/2019
5	IM8290106900 SUPPLY OF PNEUMATIC IMPACT WRENCH. PISTOL GRIP TYPE WITH HOSE DAPTOR AND NIPPLE: SQUIRE DRIVE - 1" MAX. WORKING TORQUE - 900Nm WEIGHT - 12 KGS MAX AIR PRESSURE - 5 TO 6 KG/Sq.cm AIR INLET - 1/2" BSP TO BE FURNISHED WITH FULL SPECIFICATION MAKE, MODEL NO.. AND RELEVANT CATALOGUE	NO	5.000	01	5.000	31/10/2019

MANAGER / PURCHASE