

Annexure-M	
	NIT_48574 (8690622E) dt 04.09.2019
Item Categories (Need to be filled Mandatorily) -	Production capacity
Description	Nos/Month
IM4550201700-Supply of Pneumatic Angle Grinder (DCD) with wheel guard assembly,hose adaptor and wheel mount pin spanner complying specifications as given below. Wheel capacity - 230mm (9") Free speed - 6000 rpm(min) Spindle thread size - M16 Weight 5.4 Kg Appx without wheel guard Air Inlet -1/2"RC Air pressure- 5-6 Kg/Cm2 Model CP make CP319A or its equivalent	
IM8290108400-Supply of Pneumatic Angle Grinder with wheel guard assembly,hose adaptor and wheel mount pin spanner complying specifications as given below. Wheel capacity -100mm (4") Free speed - 12000 rpm(min) Weight- 2 Kgs Appx without wheel guard Air Inlet-1/4" BSP with nipple	
IM8290101000-SUPPLY OF PNEUMATIC IMPACT WRENCH. PISTOL GRIP TYPE WITH HOSE DAPTOR AND NIPPLE: SQUIRE DRIVE - 1/2" MAX. WORKING TORQUE - 500Nm WEIGHT - 3 KGS MAX AIR PRESSURE - 5 TO 6 KG/Sq.cm AIR INLET - 1/4" BSP TO BE FURNISHED WITH FULL SPECIFICATION, MAKE,	
IM8290101100-SUPPLY OF PNEUMATIC IMPACT WRENCH. PISTOL GRIP TYPE WITH HOSE DAPTOR AND NIPPLE: SQUIRE DRIVE - 3/4" MAX. WORKING TORQUE - 900Nm WEIGHT - 5.5 KGS MAX AIR PRESSURE - 5 TO 6 KG/Sq.cm AIR INLET - 3/8" BSP TO BE FURNISHED WITH FULL SPECIFICATION, MAKE,	
IM8290106900-SUPPLY OF PNEUMATIC IMPACT WRENCH. PISTOL GRIP TYPE WITH HOSE DAPTOR AND NIPPLE: SQUIRE DRIVE - 1" MAX. WORKING TORQUE - 900Nm WEIGHT - 12 KGS MAX AIR PRESSURE - 5 TO 6 KG/Sq.cmAIR INLET - 1/2" BSP TO BE FURNISHED WITH FULL SPECIFICATION MAKE,	
Signature of Authorised Person with seal	
Date:	