

ANNEXURE 1

SL	SPECIFICATIONS	QTY.
1	OPA4192ID Operational Amplifier, 10 MHz, 4 Amplifier, 20 V/ μ s, 4.5V to 36V, $\pm$ 2.25V to $\pm$ 18V, SOIC, 14 Pins, -40 to +125°C, Manufacturer-Texas Instruments	40
2	LM139AD Analogue Comparator, Rail to Rail, Differential, 4, 300 ns, 2V to 36V, SOIC, 14 Pins, -55 to +125°C, Manufacturer-Texas Instruments	10
3	CD4011BM NAND Gate, 4 Gate, 2 Input, 6.8 mA, 3V to 18V, SOIC-14, -55 to +125°C, Manufacturer-Texas Instruments	25
4	CD4049UBD Buffer/Converter, Inverting, 3V to 18V, SOIC-16, -55 to +125°C, Manufacturer-Texas Instruments	15
5	CD4081BM AND Gate, 4 Gate, 2 Input, 6.8 mA, 3V to 18V, SOIC-14, -55 to +125°C, Manufacturer-Texas Instruments	10
6	CD4082BM96 AND Gate, CMOS, 2 Gate, 4 Input, 3V to 18V, SOIC-14, -55 to +125°C, Manufacturer-Texas Instruments	10
7	CD4072BM OR Gate, CD4072 Series, High Voltage, 4 Input, 6.8 mA, 3V to 18V, SOIC-14, -55 to +125°C, Manufacturer-Texas Instruments	10
8	ULN2004AID Bipolar Transistor Array, NPN, 50 V, 500 mA, SOIC -16, -40 to +105°C, Manufacturer-Texas Instruments	10
9	HCPL-3180-300E OPTOCOUPLER, GATE DRIVE, 3750VRMS, 1 channel, SMD, 8 pin, -40 to +100°C, Manufacturer-BROADCOM LIMITED	30
10	MCT62SD Transistor Output Optocoupler, 2 Channel, Surface Mount DIP, 8 Pins, 60 mA, 5 kV, 100%, Manufacturer-FAIRCHILD SEMICONDUCTOR	20
11	CD4050BD Buffer/Converter, CD4050, 3 V to 18 V, SOIC-16, -55 to +125°C, Manufacturer-Texas Instruments	8

12	UF4001-E3/54 Fast / Ultrafast Diode, 50 V, 1 A, Single, 1 V, 50 ns, 30 A, 150°C, Manufacturer-VISHAY	20
13	SMA6J10CA-TR TVS Diode, Transil SMA6J Series, Bidirectional, 10 V, 15.7 V, SMD, 2 Pins, Manufacturer-STMICROELECTRONICS	20
14	ICTE15-E3/54 TVS DIODE, 1.5KW, 15V, 1.5KE, Unidirectional, Manufacturer-VISHAY	20
15	SLD24-018 TVS Diode, SLD Series, Bidirectional, 24 V, 36 V, P600, 2 Pins, Manufacturer-LITTELFUSE	10
16	CRCW12061K00FKTA SMD Chip Resistor, Thick Film, 1 kohm, 200 V, 1206 [3216 Metric], 250 mW, $\pm 1\%$, CRCW Series, -55 to +125°C, Manufacturer-	500
17	Resistor, Thick Film, 10 kohm, 200 V, 1206 [3216 Metric], 250 mW, $\pm 1\%$, CRCW Series, -55 to +125°C,	500
18	CRCW12064K70FKEA SMD Chip Resistor, Thick Film, 4.7 kohm, 200 V, 1206 [3216 Metric], 250 mW, $\pm 1\%$, CRCW Series, -55 to +125°C, Manufacturer-VISHAY	300
19	CPF2200R00FKE14 METAL FILM RESISTOR, 200 OHM, 2W, 1%, Manufacturer-VISHAY	20
20	3296W-1-103LF POT, TRIMMER, 10KOHM, 25TURN, 500mW, Through Hole, PANEL, Manufacturer-BOURNS	30
21	D3027 RELAY, SIGNAL, DPDT, 250VAC, 220VDC, 2A, PCB, 200MW, 24V, SMD/SMT, DPDT (2 Form C), Manufacturer-TE CONNECTIVITY / AXICOM	15
22	BNX027H01L, Block Type EMI Filter LC Combined, EMI Network Filter, 16V, 15A, 12.1x9.1mm, 40KHz-1GHz:35dB min, SMD/SMT, -55 to +125°C, Manufacturer-Murata	10
23	BNX025H01L, Block Type EMI Filter LC Combined, EMI Network Filter, 25V, 15A, SMD/SMT, -55 to +125°C, Manufacturer-Murata	6
24	TAJA104K035RNJ Surface Mount Tantalum Capacitor, 0.1 μ F, 35 V, TAJ Series, $\pm 10\%$, 1206 [3216 Metric] Manufacturer-AVX	500

Note:- Quotation for all the items in a lot is mandatory. without which the offer may not be considered for evaluation.

Specification for LOT 2

ANNEXURE 2

SL	SPECIFICATION	QTY
1	19710355 PANEL MOUNT INDICATOR, LED, 19MM, GREEN, 24V,1200 mcd, IP67, Manufacturer-CML INNOVATIVE TECHNOLOGIES	15
2	19710350 PANEL MOUNT INDICATOR, LED, 19MM, RED, 24V,1500 mcd, IP67, Manufacturer-CML INNOVATIVE TECHNOLOGIES	40
3	Werma 10701075, Buzzer, Control Panel, Pulse, 80dB, 2.4kHz, 24VDC, 24VAC, 8mA, IP65, 49mm Ext. Depth,Manufacturer-WERMA	4
4	XB4BP31EX Schneider Electric XB4 Push Button, Green, NO, Spring Return,22 mm,600V,panel mount,-25 to +70°C, Manufacturer-Schneider Electric	10
5	Teknic selector actuator 2AS2-2P, 2 Position Selector Stayput, black, 22.5 mm dia,Metallic,Manufacturer-Teknic.	12
6	Teknic 2AML4 Mushroom Actuator, Series Metallic, Latching Type, Color Red, Dia 40mm	10
7	BOURNS 3590S-2-103L, Precision Potentiometers 7/8"WW, 10Kohms, 0.25%, 10turn,Wirewound,Solder lug,Manufacturer-Bourns	4

Note:- Quotation for all the items in a lot is mandatory without which the offer may not be considered for evaluation.