

1		2		3		4		5		6		7		8																																																																																																																																																																																								
DRAWING NO. 2-V-0000-20264												ALL DIMENSIONS ARE IN MILLIMETRES. FOR TOLERANCES OF UNTOLERANCED DIMENSIONS DURING MANUFACTURE REFER RELEVANT QCP / QP																																																																																																																																																																																										
<table><tr><th rowspan="2">SL No.</th><th rowspan="2">DRAWING NUMBER</th><th rowspan="2">FLANGE RATINGS</th><th rowspan="2">END CAP SIZE (mm)</th><th rowspan="2">MATERIAL SPECIFICATION</th><th rowspan="2">MATERIAL CODE</th><th colspan="5">DIMENSIONS (mm)</th><th rowspan="2">Wt / kg</th><th rowspan="2">REMARKS</th></tr><tr><th>øA</th><th>øB</th><th>øC</th><th>D</th><th></th></tr><tr><td>01</td><td>2-V-4124-20264 /0</td><td>2-1/16" - 2M, 3M, 5M, 10M, 15M</td><td>50</td><td rowspan="5">LINEAR LOW DENSITY POLYETHYLENE (COLOUR : BLUE)</td><td>96 469 968 0000</td><td>122</td><td>56</td><td>43.4</td><td>14</td><td></td><td>0.001</td><td></td></tr><tr><td>02</td><td>2-V-4592-20264 /0</td><td>2-9/16" - 2M, 3M, 5M, 10M, 15M</td><td>65</td><td>96 469 969 0000</td><td>144</td><td>69</td><td>62</td><td>16.3</td><td></td><td>0.002</td><td></td></tr><tr><td>03</td><td>2-V-4134-20264 /0</td><td>3-1/8" - 2M, 3M, 5M, 10M, 15M</td><td>80</td><td>96 469 970 0000</td><td>159</td><td>83</td><td>73</td><td>16.5</td><td></td><td>0.003</td><td></td></tr><tr><td>04</td><td>2-V-4778-20264 /0</td><td>4-1/16" - 2M, 3M, 5M, 10M, 15M</td><td>100</td><td>96 469 971 0000</td><td>192.5</td><td>105</td><td>97.6</td><td>15.3</td><td></td><td>0.005</td><td></td></tr><tr><td>05</td><td>2-V-4L14-20264 /0</td><td>5-1/8" - 2M, 3M, 5M, 10M, 15M</td><td>130</td><td>96 469 972 0000</td><td>260</td><td>156</td><td>135</td><td>16</td><td></td><td>0.007</td><td></td></tr><tr><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr><tr><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr><tr><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr><tr><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr><tr><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr><tr><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr><tr><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr><tr><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr></table>												SL No.	DRAWING NUMBER	FLANGE RATINGS	END CAP SIZE (mm)	MATERIAL SPECIFICATION	MATERIAL CODE	DIMENSIONS (mm)					Wt / kg	REMARKS	øA	øB	øC	D		01	2-V-4124-20264 /0	2-1/16" - 2M, 3M, 5M, 10M, 15M	50	LINEAR LOW DENSITY POLYETHYLENE (COLOUR : BLUE)	96 469 968 0000	122	56	43.4	14		0.001		02	2-V-4592-20264 /0	2-9/16" - 2M, 3M, 5M, 10M, 15M	65	96 469 969 0000	144	69	62	16.3		0.002		03	2-V-4134-20264 /0	3-1/8" - 2M, 3M, 5M, 10M, 15M	80	96 469 970 0000	159	83	73	16.5		0.003		04	2-V-4778-20264 /0	4-1/16" - 2M, 3M, 5M, 10M, 15M	100	96 469 971 0000	192.5	105	97.6	15.3		0.005		05	2-V-4L14-20264 /0	5-1/8" - 2M, 3M, 5M, 10M, 15M	130	96 469 972 0000	260	156	135	16		0.007																																																																																																													
SL No.	DRAWING NUMBER	FLANGE RATINGS	END CAP SIZE (mm)	MATERIAL SPECIFICATION	MATERIAL CODE	DIMENSIONS (mm)					Wt / kg							REMARKS																																																																																																																																																																																				
						øA	øB	øC	D																																																																																																																																																																																													
01	2-V-4124-20264 /0	2-1/16" - 2M, 3M, 5M, 10M, 15M	50	LINEAR LOW DENSITY POLYETHYLENE (COLOUR : BLUE)	96 469 968 0000	122	56	43.4	14		0.001																																																																																																																																																																																											
02	2-V-4592-20264 /0	2-9/16" - 2M, 3M, 5M, 10M, 15M	65		96 469 969 0000	144	69	62	16.3		0.002																																																																																																																																																																																											
03	2-V-4134-20264 /0	3-1/8" - 2M, 3M, 5M, 10M, 15M	80		96 469 970 0000	159	83	73	16.5		0.003																																																																																																																																																																																											
04	2-V-4778-20264 /0	4-1/16" - 2M, 3M, 5M, 10M, 15M	100		96 469 971 0000	192.5	105	97.6	15.3		0.005																																																																																																																																																																																											
05	2-V-4L14-20264 /0	5-1/8" - 2M, 3M, 5M, 10M, 15M	130		96 469 972 0000	260	156	135	16		0.007																																																																																																																																																																																											
NOTES: * 1. ALL OTHER DIMENSIONS & DETAILS (ie, THICKNESS, FINSHING, DIMN. E & F, RADIUS AND ANGLE) AS PER SUPPLIER'S SCOPE. 2. TEST CERTIFICATE FOR END COVERS SHOULD BE PROVIDED.												END CAP ASSY DETAILS																																																																																																																																																																																										
MINIMUM REQUIRED PROPERTIES : <table><tr><th>PROPERTY</th><th>TEST METHOD</th><th>UNIT</th><th>TYPICAL VALUE</th></tr><tr><td>DENSITY (23°C)</td><td>ASTM D 1505</td><td>g/cc</td><td>0.926</td></tr><tr><td>MFI (190ø / 2.19kg)</td><td>ASTM D 1238</td><td>g/10 min</td><td>50</td></tr><tr><td>TENSILE YIELD STRENGTH</td><td>ASTM D 638</td><td>MPa</td><td>11.5</td></tr><tr><td>ELONGATION AT BREAK</td><td>ASTM D 638</td><td>%</td><td>600</td></tr><tr><td>FLEXURAL MODULUS</td><td>ASTM D 790</td><td>MPa</td><td>250</td></tr><tr><td>FLEXURAL MODULUS</td><td>ASTM D 1525</td><td>°C</td><td>97</td></tr></table>												PROPERTY	TEST METHOD	UNIT	TYPICAL VALUE	DENSITY (23°C)	ASTM D 1505	g/cc	0.926	MFI (190ø / 2.19kg)	ASTM D 1238	g/10 min	50	TENSILE YIELD STRENGTH	ASTM D 638	MPa	11.5	ELONGATION AT BREAK	ASTM D 638	%	600	FLEXURAL MODULUS	ASTM D 790	MPa	250	FLEXURAL MODULUS	ASTM D 1525	°C	97	APPLICATIONS : END CAPS ARE USED TO PROTECT THE BODY SEALING GROOVE AREA FROM CONTAMINATIONS OF ENVIRONMENT.																																																																																																																																																														
PROPERTY	TEST METHOD	UNIT	TYPICAL VALUE																																																																																																																																																																																																			
DENSITY (23°C)	ASTM D 1505	g/cc	0.926																																																																																																																																																																																																			
MFI (190ø / 2.19kg)	ASTM D 1238	g/10 min	50																																																																																																																																																																																																			
TENSILE YIELD STRENGTH	ASTM D 638	MPa	11.5																																																																																																																																																																																																			
ELONGATION AT BREAK	ASTM D 638	%	600																																																																																																																																																																																																			
FLEXURAL MODULUS	ASTM D 790	MPa	250																																																																																																																																																																																																			
FLEXURAL MODULUS	ASTM D 1525	°C	97																																																																																																																																																																																																			
1		2		3		4		5		6		7		8																																																																																																																																																																																								
<table><tr><td>DCP No.</td><td>ALTERED</td><td>APPD</td></tr><tr><td>REV</td><td>CHD</td><td>DATE</td></tr><tr><td>ZONE</td><td></td><td></td></tr></table>												DCP No.	ALTERED	APPD	REV	CHD	DATE	ZONE			CAUTION: The information on this document is the property of BHARAT HEAVY ELECTRICALS LTD. It must not be used directly or indirectly in any way detrimental to the interest of the company.				<table><tr><td>No OFF</td><td>DESCRIPTION</td><td>MATL CODE</td><td>MATL SPECN</td><td>HEAT TREATMENT</td><td>SCRAP SORT</td><td>NET WT (kg)</td><td>GROSS WT (kg)</td><td>DRAWING No</td><td>ITEM No</td></tr><tr><td colspan="10">TYPE OF PRODUCT OR NAME OF CUSTOMER/PROJECT</td></tr><tr><td colspan="10">FOR OFE FLANGES</td></tr><tr><td colspan="4">BHARAT HEAVY ELECTRICALS LTD., UNIT: HIGH PRESSURE BOILER PLANT. TIRUCHIRAPALLI -620014.</td><td>DRN</td><td>NAME</td><td>SIGN</td><td>DATE</td><td colspan="2">NO.OF VAR.</td></tr><tr><td colspan="4">365-120</td><td>CHD</td><td>R.NATARAJAN</td><td>R.N</td><td>20-08-2016</td><td colspan="2">20-08-2016</td></tr><tr><td colspan="4">DEPT VL</td><td>APPD</td><td>P.ARUNKUMAR</td><td>P.A</td><td>20-08-2016</td><td colspan="2">20-08-2016</td></tr><tr><td colspan="4">CODE 340</td><td colspan="3">REFERENCE INFORMATION</td><td colspan="3">NO. OF ITEMS</td></tr><tr><td colspan="4">TITLE</td><td colspan="3">DRAWING NO.</td><td colspan="3">REV</td></tr><tr><td colspan="4">FLANGE END CAP (PLASTIC)</td><td colspan="3">2-V-0000-20264</td><td colspan="3">0</td></tr></table>				No OFF	DESCRIPTION	MATL CODE	MATL SPECN	HEAT TREATMENT	SCRAP SORT	NET WT (kg)	GROSS WT (kg)	DRAWING No	ITEM No	TYPE OF PRODUCT OR NAME OF CUSTOMER/PROJECT										FOR OFE FLANGES										BHARAT HEAVY ELECTRICALS LTD., UNIT: HIGH PRESSURE BOILER PLANT. TIRUCHIRAPALLI -620014.				DRN	NAME	SIGN	DATE	NO.OF VAR.		365-120				CHD	R.NATARAJAN	R.N	20-08-2016	20-08-2016		DEPT VL				APPD	P.ARUNKUMAR	P.A	20-08-2016	20-08-2016		CODE 340				REFERENCE INFORMATION			NO. OF ITEMS			TITLE				DRAWING NO.			REV			FLANGE END CAP (PLASTIC)				2-V-0000-20264			0																																																																																		
DCP No.	ALTERED	APPD																																																																																																																																																																																																				
REV	CHD	DATE																																																																																																																																																																																																				
ZONE																																																																																																																																																																																																						
No OFF	DESCRIPTION	MATL CODE	MATL SPECN	HEAT TREATMENT	SCRAP SORT	NET WT (kg)	GROSS WT (kg)	DRAWING No	ITEM No																																																																																																																																																																																													
TYPE OF PRODUCT OR NAME OF CUSTOMER/PROJECT																																																																																																																																																																																																						
FOR OFE FLANGES																																																																																																																																																																																																						
BHARAT HEAVY ELECTRICALS LTD., UNIT: HIGH PRESSURE BOILER PLANT. TIRUCHIRAPALLI -620014.				DRN	NAME	SIGN	DATE	NO.OF VAR.																																																																																																																																																																																														
365-120				CHD	R.NATARAJAN	R.N	20-08-2016	20-08-2016																																																																																																																																																																																														
DEPT VL				APPD	P.ARUNKUMAR	P.A	20-08-2016	20-08-2016																																																																																																																																																																																														
CODE 340				REFERENCE INFORMATION			NO. OF ITEMS																																																																																																																																																																																															
TITLE				DRAWING NO.			REV																																																																																																																																																																																															
FLANGE END CAP (PLASTIC)				2-V-0000-20264			0																																																																																																																																																																																															