

A211A04

A-FORM NO REV NO

6130574202474EP-HCM21100 BHARAT HEAVY ELECTRICALS LIMITED - BHOPAL

							REV NO	0	_
cokhar			MIM DEF	DEFARIMENT			A-FORM DATE	E 01-OCT-24	
and bar	ES	FIMATE SHEET	FOR ISSUE OF N	ESTIMATE SHEET FOR ISSUE OF MATERIAL/COMPONENTS FROM BHEL	TENTS FROM	BHEL	DATE		
FORM NO BP-0021			CHE	CHECKLIST			PAGE	: 1/1	
DEPARTMENT: 211	PROJECT	CT	: BARC	PO NO : A2	: A211A04 EN	END PRODUCT:	BAFFLES PLATE		l .
INDENT NO : 221140073		WORK ORDER NO	: 12010S15459	PO DATE:	DI	DELY REQD :	: 15012025		
INDENT DATE: 01102024		MATERIAL ISSUE DIV: 211	7:211	SUPP CODE:	SC	SUPP NAME :			
			DETAI	DETAILS OF FINISHED GOODS	<u>SQO</u>				
	A-	A-SLNO PO IT	PO IT NO PI IT NO	QUANTITY REQUIRED	TINU C	T SHOP NO	DEST CD CC	COST CD H.CELL	
DESCRIPTION OF SUB-ASSEMBLY/ITEM & WEIGHT/VOLUME/AREA	SEMBLY/ITEM	& WEIGHT/VOL	UME/AREA						
			FREE ISSUE MATE	MATERIAL PER UNIT OF FINISHED GOODS	NISHED GOODS	201			
MATL QTY PSL	PSL	RATE PSL	TOTAL MATL	ISSUE PSL/	SMIV/	MATERIAL	TARRIF	MATL	
CODE UNIT	UNI	UNIT UNIT	TO BE ISSUED	UNIT WIP	PPMIV NO	VALUE	HEAD	ISSUE QTY	
DESCRIPTION OF FREE ISSUE MATERIAL AND WEIGHT /VOLUME/AREA	SUE MATERIA	L AND WEIGHT /	VOLUME/AREA						
	1	0	1		30.000 NO	211	211	211	
DRILLING OF BAFFLE PLATE	LATE								
BP9602016060	1.0000 NO	22800.000	30.00	NO WIP		684000.000		1.0000	
DRILLING OF BAFFLE PLATE AS PER DRG NO-11650340920 REV-01 MATERIAL DIA 1642 X 16 TK R.WT EACH 240 KG AND F.WT EACH-160 KG APPROX (SCRAP DUDECTION @	TE AS PER DRG	NO-11650340920 I	REV-01 MATERIAL	DIA 1642 X 16 TK R.WT	EACH 240 KG A	ND F.WT EACH-160	KG APPROX (SCR.	AP DUDECTION @	
35.60 RS PER KG)									
REMARKSNA							AFORM TOTA	AFORM TOTA] 684000.000	
TOTAL NO OF CANCEL ITEM 0	TEM 0								
									1

SIGNATURE OF ASC EXECUTIVE DESIGNATION TELEPHONE NAME एव. सी. एम. विभाग / HCM Division बी.एच.ई.एल.. मोपाल / BHEL. BHOPAL हरिमन मीमा / HARIMAN MEENA SIGNATURE OF INDENTOR NAME DESIGNATION TELEPHONE SUPPLIER FREE ISSUE BASIS 5 INVARIABLY ISSUE WT. TO BE RECORDED ON SMIV/PMIV SUPPLIER 3.EXCISE DUTY ON ISSUE MATL TO BE BORNE BY :-2.TRANSPORT TO BE PROVIDED BY :-1 MATERIAL TO BE ISSUED ON:-4.SCRAP TO BE RETURNED :-

RPT-101

02

Rev No.

05.09.2024

Date

2+9=11

Pages

Procedure for **Tube Sheet** & **Baffle Drilling** of Heavy Water process Heat Exchangers-34MW DHRUVA, TROMBAY

Date:05.09.2024 RevisionNo.:02

SS MADAVI

Approved By

Name of Main	बी एच ई एल	BHARAT HEAVY ELECTRICALS LIMITED, BHOPAL
Supplier	HḤEL	(Govt. of India undertaking)
BARC PO NO.:	DPS/CPU/04/A	3/2622-TPT/PO/252364, DTD: 22.07.2022
QAP Reference	QAX-TH-1601	
Number		
Customer:	A. Hai of Grant	BHABHA ATOMIC RESEARH CENTER
	क्षाप अ कें हैं BARC	(Govt. of India)
PROJECT:	BARC Heavy W	/ater process Heat Exchangers-34 MW, DHRUVA, TROMBAY
Equipment:	Heavy Water	process Heat Exchangers
Document	12010S15459/	2024/HEP/HCM-01
Number:		
Document Title:	Procedure for	Tube Sheet & Baffle Drilling of Heavy Water process Heat
	Exchangers-34	MW DHRUVA, TROMBAY
		10 0 PC 100.

Pankaj Nimje

Checked By

Hariman Meena

Prepared By

Procedure for **Tube Sheet** & **Baffle Drilling** of Heavy Water process Heat Exchangers-34MW DHRUVA, TROMBAY

Date:05.09.2024 RevisionNo.:02

Revision Control Sheet:					
REV. No/ Date	PAGES	Description of Revision	Prepared By	Checked By	Approved By
00/ 15.04.2024	8	Original submission	Hariman Meena	Pankaj Nimje	SS Madavi
01/ 23.07.2024	2+8=10	1 st Revised submission , (with italic font)	Hariman Meena	Pankaj Nimje	SS Madavi
02/ 05/09/2024	2+9=11	2 nd revised submission, (With underlined italic font)	Hariman Meena	Pankaj Nimje	SS Madavi

Hab?

हरिमन मीना / HARIMAN MEENA प्रबंधक / Manager एच.सी.एम. विभाग / HCM Division बी.एच.ई.एल., भोपाल / BHEL, BHOPAL Re

पंकजं निमजं / PANKAJ NIMJE खप महाप्रबंधक / DGM एच. सी. एम. विभाग / HCM Division बी.एच.ई.एल., भोपाल / B.H.E.L., BHOPAL एस एस मडावी / S. S. MADAVI अपर महाप्रबंधक / AGM एच.सी.एम विभाग / H.C.M. Division बी.एच.ई.एल., भोपाल / B.H.E.L., BHOPAL

BHEL Bhopal	
Procedure for Tube Sheet & Baffle Drilling of Heavy	Date:05.09.2024
Water process Heat Exchangers-34MW DHRUVA, TROMBAY	RevisionNo.:02

1. GENERAL

- 1.1 This procedure establishes the requirements for the Procedure qualification & Production drilling of tube sheet and Baffles.
- 1.2 Production drilling shall be taken up only after successful completion of procedure qualification, duly accepted by BHEL & BARC (QA).
- 1.3 Tube sheet drilling shall be done on a CNC deep hole drilling machine while baffle drilling can be done on CNC drilling machine
- 1.4 All measurements shall be recorded in proper formats.

2. PROCEDURE QUALIFICATION OF TUBE SHEET DRILLING (Bottom & Top TS)

2.1 Following are the requirements for the qualification Block

Item	Requirement
Material	Same as tube sheet material, heat treatment condition, NDE examinations.
Thickness	Equal to Tube sheet Thickness
Surface Flatness	Shall be within <u>0.5</u> mm, under clamped condition
<u>Surface finish</u>	<u>Same as tube sheet -material</u>

2.2 Drilling Machine Setting

- **2.2.1** Channel side (front face) shall face the M/C tool (drill) side, so as to start drilling from the Channel side surface.
- **2.2.2** Set the mock block or DOB (Drilling Qualification Block) suitably clamped.

2.3 Drilling

- **2.3.1** Drilling shall be done as per approved test block layout drawing (attached as drg no. 41650340382 on page no.8) and machine shall be programmed accordingly.
- **2.3.2** Drawing of test block with holes' layout, holes identified with respect to machine, spindles, and spindle combinations, in case of multi spindle machine, shall be prepared prior to drilling.

2.4 Nos. of Holes

Minimum 50 holes shall be drilled for Operator and Machine qualification per spindle as per test block tube hole lay out to establish drilling parameters. Drilling parameters shall be recorded. Another 25 holes to be drill to qualify additional single operator on the same machine.







BHEL Bhopal	
Procedure for Tube Sheet & Baffle Drilling of Heavy	Date:05.09.2024
Water process Heat Exchangers-34MW DHRUVA, TROMBAY	RevisionNo.:02

2.5 Examination

Following examinations shall be carried out:

Item	Requirement Measurement of Hole size	Acceptance Standard
Hole Size	100% holes <u>3mm</u> from both faces.	As per drawing of mockup test block
	Go gauge check for full length & NOGO gauge check for all holes from both ends.	Go gauge should enter and No go gauge should not enter the hole
Ligament	100% ligaments shall be checked at front and rear face sides	As per drawing
Drift	100% holes by optical tooling at rear w.r.t. front side.	As per drawing
Visual examination	100% holes by Visual examination	Hole surface shall be cleaned properly
Surface finish of tube hole	100% holes finish by finish tester or comparator	As per drawing requirement
Hole position	100% holes position shall be measured at front face.	As per drawing requirement

Note: Above qualification shall be applicable for both top and Bottom Tube sheets.

3. TUBE-SHEET DRILLING

3.1 Tube Sheet Condition

Just prior to drilling stage, Tube sheet condition shall be as per approved manufacturing procedure / QAP.

3.2 Drilling

- **3.2.1** Drilling shall be carried out on qualified machine by qualified operators.
- **3.2.2** Tube sheet shall be set/clamped on drilling machine Suitably to carryout drilling operations
- **3.2.3** Suitable measures shall be taken to ensure that Tube sheet setting is not disturbed during drilling.
- **3.2.4** Drilling sequence and machine setting parameters shall be as per drilling program established during procedure qualification. CNC machine drilling program/sequence shall be checked/verified before drilling on the job as per sketch 1. However, drilling sequence may change for effective utilization of machine without compromising of quality of work.
- **3.2.5** One hole shall be drilled on the test block set along with the tube sheet before starting the shift and during the event of any change in conditions (i.e. change of drill, change found during in process checks on hole diameter, finish, ligaments by visual examination and go-no-go gauges) and only after ensuring acceptable hole quality, drilling on the production job shall be taken up.

Page **2** of **9**

Val





BHEL Bhopal	
Procedure for Tube Sheet & Baffle Drilling of Heavy	Date:05.09.2024
Water process Heat Exchangers-34MW DHRUVA, TROMBAY	RevisionNo.:02

- **3.2.6** The first hole on the job at the beginning of the shift shall be examined, <u>measured</u> and recorded for acceptable quality parameters limit.
- **3.2.7** In addition, at regular intervals during drilling operation, hole shall be inspected and measurements recorded.
- **3.2.8** Whenever a drill bit is replaced, the first hole shall be checked for compliance. Reground tools can also be used. Record shall be kept on the status of each grinded tool in Log book.
- **3.2.9** <u>Drill bit/Drill shall replace as per drill manufacturer's recommendations or as and when limits</u> for hole dimensions are reached during in the inspection process, whichever falls early.

3.3 Following documents shall be prepared for the tube sheet drilling process

- **3.3.1** Annexure -1 Record of qualification as per clause 2.1
- **3.3.2** Annexure-2 Measurement and record note as per clause 2.5.
- **3.3.3** Annexure-3 Record of drilling sequence, CNC Program no., drilling cutting parameters (Feed, RPM) as per clause 3.2.4.
- **3.3.4** Annexure-4 Record of holes as per clause no. 3.2.5 and clause no.3.2.7.

3.4 Examination

Following examinations shall be carried out on drilled Tube sheet:

Item	Requirement	Acceptance Standard
Hole size	3 % of total holes referred as "Controlled holes/ reference holes" selected at random by BHEL(QA). Shall be recorded by internal micrometer. * In case of nonconformance of controlled/reference holes wrt specified diameter, an additional six percent (6%) of the holes shall be subjected to dimensional verification to ascertain conformance to the specified diameter. If any of the additional inspections yield non-conforming results, a 100% dimensional measurement of all holes using a micrometer may be carried out.	As per approved drawing
Hole gauging	100% holes of Tube sheet shall be checked with GO gauge for full length & NOGO gauge from both ends. 3% control hole size to be recorded	Go gauge should enter and No go gauge should not enter the hole.
Ligament	100% holes to be checked by ligament gauge, 3% control hole size to be recorded	Approved drawing ,
Drift	All reference/controlled holes and all nonconformance holes at rear w.r.t front side.	Approved drawing
Visual examination	100% holes by Visual Examination.	Inspection for any dent, incomplete hole, hole surface cleanliness.
Hole position	3 % of total holes referred as "Controlled holes/ reference holes.	As per drawing requirement







BHEL Bhopal					
	process Heat Exchangers-34MW DHRUVA, TROMBAY	Date:05.09.2024 RevisionNo.:02			
Surface finish measurement	All reference holes by Surface finish tester/comparator method and at front & rear ends of holes.	Approved drawing			

Note:

- a. "Reference holes" to be selected by BHEL(QA), shall in a manner representing total tube sheet drilling.
- b. Required hole size for tube sheet shall be achieved in single step drilling process.

3.5 Special Occurrence

If abnormalities like vibration, loosening of clamping, drill breakage etc. are noticed, drilling shall be stopped and the affected hole(s) shall be evaluated. Drilling shall proceed only after a satisfactory drilling of a hole on the test block and BHEL (QA) clearance.

4. PROCEDURE QUALIFICATION OF BAFFLE DRILLING

4.1 Qualification Block

Following are the requirements for the qualification Block:

Item	Requirement
Material	Same as Baffle material including heat treatment condition, NDE examinations, etc.
Thickness	The number of plates, in a stack, used in procedure qualification, shall be the maximum permitted during production drilling
Surface Flatness	Shall be within 1mm , Under clamped condition.
Surface Finish of hole	Same as baffle (3.2 Micron)

4.2 Drilling Machine Setting

- **4.2.1.** Setting of baffle plates on machine and clamping arrangements shall be done suitably to prevent buckling of the baffle plate before/during drilling.
- 4.2.1 Each of the plates in such a stack shall be punch marked suitably with respect to drill side face and plate sequence number in drilling direction, stack identification number so that baffles, from the same stack can be installed in the same sequence and facing, in the heat exchangers such that tubes can be smoothly inserted in the drilling direction.

4.3 Drilling


Drilling shall be done as per approved sequence and machine shall be programmed accordingly. Drilling area of block should be divided into 4 quadrants and prepare the annexure indicating the direction of drill bit movement in separate sketch. (*Sketch-1*)







BHEL Bhopal	
Procedure for Tube Sheet & Baffle Drilling of Heavy	Date:05.09.2024
Water process Heat Exchangers-34MW DHRUVA, TROMBAY	RevisionNo.:02



SKETCH-I CLAUSE No. 4.3

DRILLING SEQVENCE:-

Ist QUAD ── IIIrd QUAD. ── IInd QUAD. ── IVth QUAD.

Sketch 1. Drilling Direction & sequences

4.4 No of holes

Minimum 50 holes shall be drilled for both Operator and Machine qualification per spindle as per test baffle plate tube hole lay out to establish drilling parameters. Drilling parameters shall be recorded. Another 25 holes *per spindle shall* drill to qualify another single operator on the same machine.

Page **5** of **9**

0-5



1001

BHEL Bhopal	
Procedure for Tube Sheet & Baffle Drilling of Heavy	Date:05.09.2024
Water process Heat Exchangers-34MW DHRUVA, TROMBAY	RevisionNo.:02

4.5 Examination

Following examinations shall be carried out:

Item	Requirement	Acceptance Standard
Hole Size	100% holes	As per drawing
	Go gauge check for full length & NOGO gauge check for all holes from both ends.	Go gauge should enter and No go gauge should not enter the hole
Ligament	100% ligaments shall be checked at front and rear face sides by GO-NOGO- ligament gauge	As per drawing
Hole position	100% holes shall be measured	As per drawing
Visual examination	100% holes	Hole surface shall be cleaned properly
Surface finish	100% hole finished shall measure by Finish tester or c comparator	As per drawing requirement.

5.0 BAFFLE DRILLING

5.1 Condition

Just prior to drilling stage, Baffle condition shall be as per approved manufacturing procedure /QAP.

5.2 Drilling

- 5.2.1 Drilling shall be carried out on a qualified machine by qualified operators.
- 5.2.2 Baffle Stack shall be set in a suitable position on machine. Stacking of baffles shall be done as per the qualification block (Attached as Drawing no. 41650340383 at page no. 9) used in qualification of baffles drilling process. Maximum stack size can be only 10(ten) baffles per stack.
- 5.2.3 Drilling sequence and machine setting parameters shall be as per drilling program established during procedures qualification. CNC machine drilling program/sequence shall be checked and verified for before drilling on the job.
- 5.2.4 The first hole on the job at the beginning of the shift shall be examined, <u>measured and recorded</u> for acceptable quality.
- 5.2.5 In addition, at regular intervals during drilling operation, hole shall be checked, inspected and measurements recorded.
- 5.2.6 Whenever a drill bit is replaced, the first hole shall be checked for compliance. Reground tools can also be used. Record shall be kept on the status of each drill bit in Log book.
- 5.2.7 <u>One hole shall be drilled on the test block set along with the Baffle Stack before/after the shift and during the event of any change in condition (i.e. change of drill, change found during in process</u>

Page 6 of 9







BHEL Bhopal	
Procedure for Tube Sheet & Baffle Drilling of Heavy	Date:05.09.2024
Water process Heat Exchangers-34MW DHRUVA, TROMBAY	RevisionNo.:02

check on the hole diameter, finish ligaments by visual examination and go-no-go gauges) and only after ensuring acceptable hole quality, drilling on the production job shall be taken up.

5.3 Examination

Following examinations shall be carried out on drilled Baffles:

Item	Requirement	Acceptance Standard
Hole Diameter	Diameters of at least 3% of total holes (but not less than 5 holes /baffle) referred as "Controlled holes/ reference holes" shall be measured and recorded. ** In case of nonconformance of controlled/reference holes wrt specified diameter, an additional six percent (6%) of the holes shall be subjected to dimensional verification to ascertain conformance to the specified diameter. If any of the additional inspections yield non-conforming results, a 100% dimensional measurement of all holes using a micrometer may be carried out.	Approved drawing
Gauging	100 % holes shall be checked with GO gauge & NOGO gauge. 3% control hole size to be recorded	Go gauge should enter and No go gauge should not enter the hole
Ligament	100% holes to be checked by GO-NOGO- ligament gauge. 3% control hole size to be recorded	Approved drawing
Visual examination	100% holes	Inspection for any dent, incomplete hole, hole surface cleanliness.
Surface finish	100% hole finished shall measure by Finish tester or comparator	As per drawing requirement.

Note:

- a. "Reference Holes" to be selected by BHEL (QA) in a manner-representing total Baffle drilling.
- b. Required hole size of baffles shall be achieved in single step drilling process.


5.4 Special occurrence


If abnormalities like vibration, loosening of clamping, drill breakage etc. are noticed, drilling shall be stopped and the affected holes shall be evaluated and reported for clearance. Drilling shall proceed only after a satisfactory drilling of a hole on test block and purchaser or his authorized agency's clearance.











Date: 28.09.2024

Points for technical compliance for Drilling of baffles of Heavy Water Heat Exchanger BARC,

PI.....

- Scope of Work: Drilling baffles for tube holes for Heavy Water Heat Exchanger BARC on labor basis as per the drawings (drg no:1-6503-40920 Rev01), Drilling procedure and QAP requirements. Important details of work are given below:
 - a. 8245 nos of tube hole per baffle as per drawings
 - b. 12 nos of tie rod holes per baffle as per drawing,
- 2. Some critical Job Specifications:
 - a. Tube Hole dia. 9.96+0.1 mm.
 - b. Nos. of Hole/ TS: 8245
 - c. Positional Accuracy: 0.1 mm
 - d. Hole finishing: 3.2 Micron
 - e. Baffles thickness: 16 mm
 - f. Baffle plate material: SA516GR70.
 - g. All the tube holes and tie rod holes shall be rounded off to a radius of 1.0-2.0 mm on the both the side.
- 3. MATERIAL: BHEL will free issue the ready to drill material for baffle plates & and mock block to the vendor
- 4. All acceptance norms shall be as per respective baffles drawing, drawing notes and BHEL QAP. All the dimensions shall be maintained as per drawings.
- 5. Quality inspection at vendor's place by BHEL QA /BHEL appointed Third Party Inspection(TPI) agency and documents will be reviewed by BARC QAP
- 6. Drilling procedure and qualification need to be established on Mock block by the bidder as per the drilling procedure document no. 12010S15459/2024/HEP/HCM-01, and the same has to be witness by BHEL QA and review by BARC QA.
- 7. The mock up plates shall be returned to BHEL without tying any commercial value to it.
- 8. Bidder shall fulfill the requirements of PRE-QUALIFICATION REQUIREMENT (PQR) document for baffles plate drilling of Heavy Water Heat exchanger, BARC.
- 9. Scrap generated, shall be retained by the vendor at the BHEL standard scrap rate and the same shall be deducted at supplier bill along with applicable taxes.
- 10. Both ways transportation shall be in vendor's scope.
- 11. Item to be well packed, dust free and with proper identification tags.
- 12. Drawing Revision before executing the order, supplier should confirm the revision status of Drawings.

 QAP and Drilling Procedure from BHEL Bhopal.

28 07 24

हरिमन मीना / HARIMAN MEENA प्रबंधक / Manager एच. सी. एम. विभाग / HCM Division बी.एच.ई.एल., भोपाल / BHEL, BHOPAL checked by

पंकज निमजे / PANKAJ NIMJE उप महाप्रबंधक / DGM एच. सी. एम. विभाग / HCM Division बी.एच.ई.एल., भोपाल / B.H.E.L., BHOPAL एस पूर्व महास्मित के S. MADAVI अपर महाप्रवंधक / AGM एच.सी. एम. विभाग / H. C.M. Division बी.एच.ई.एल., भोपाल / B.H.E.L., BHOPAL

Page 1 |.1

BHARAT HEAVY ELECTRICALS LTD., BHOPAL

REV. NO. 02 34 MW HEAVY-WATER/PROCESS-WATER SHELL & TUBE TYPE HEAT EXCHANGER

(BARC, TROMBAY, MIMBAL) Baffles Drilling Drawing Nos.-11650340920.

DATE: 03 09 2024

	REMARKS 11	
FAGE: 1 OF 3	AGENCY ** 10	M B C
DAIE: 03.09.2024	FORMAT OF RECORD	* 6
DAIE	ACCEPTANCE NORMS	8
IIIIIII DI AWIIII INOS.=11020240720,	REFERENCE DOCUMENT	7
iiig Drawiiig⊺	QUANTUM OF CHECK	9
	TYPE OF CHECK	5
MOMBA	CLASS	4
(DANC, INCINIDAT, MUMBAT) DAILLES DE	CHARACTERISTICS	3
	COMPONENT & OPERATIONS	2
	SL.	1

ABBR	ABBREVIATIONS USED IN OA PLAN		
Cr.	Critical	NDT	Non Destructive Test
Mj.	Major	UT	Ultrasonic Test
Drg.	Drawing	MCD	Magnetic Crack Detection
Mn.	Minor	DPT	Dye Penetrant Test
Mech.	Mechanical Properties	G/D	Strong Dollowing
T	Testing (Lab.) to be done for checks	Y /S	Stress reflecting
Chem.	Chemical Composition	Meas	Measurement
ı	Instrument	TC	Test Certificate
PSI	Pre-Service Inspection		
QCR	Quality Control Record		
SPEC.	specification		
WPS	Welding Procedure Specification		
Mat.	Material		
WQR	Welder's Qualification Records		
PQR	Procedure Qualification Records		

DOCUMENTATION. ** M: BHEL' BHEL'S SUB-SUPPLIER C: BARC/BARC TPIA, B: BHEL/TPIA, P: PERFORM, R: RECORD LEGEND: * RECORDS, IDENTIFIED WITH "TICK" (√) SHALL BE ESSENTIALLY INCLUDED BY SUPPLIER IN QA REVIEW AND W: WITNESS

date/ revision no. of reference document at the Note:# Inspection Engineer to check, approval

time of inspection

Prepared by

की.एच.ई.एल., मोपाल / BHEL. BHOPAL एच. सी. एम. विभाग / HCM Division THE / HARIMAN MEENA प्रबंधक / Manager

Reviewed by

की एचाई एल.. भोपाल / В.Н.Е.L., ВНОРАL GRAS (JITENDRA SINGH क्यू टी एवं / ОТН (ОА & QC) प्रबंधक / Manager

Approved by

एच. सी. एम. विभाग/H.C.M. Division बी.एच.ई.एल., भोपाल/B.H.E.L., BROPAL एस एस मडावी / S. S. MADAVI अपर महाप्रबंधक / AGM

SL.

BHARAT HEAVY ELECTRICALS LTD., BHOPAL

PAGE: 2 OF 3 **REV. NO. 02** 34 MW HEAVY-WATER/PROCESS-WATER SHELL & TUBE TYPE HEAT EXCHANGER OP NO.QAX/TH/111 DATE: 03.09.2024 (BARC, TROMBAY, MUMBAI) Baffles Drilling Drawing Nos.-11650340920,

REMARKS 11 C AGENCY
** 10 8 M **a** * FORMAT OF RECORD 6 ACCEPTANCE NORMS ∞ REFERENCE DOCUMENT QUANTUM OF CHECK 9 TYPE OF CHECK S CLASS 4 CHARACTERISTICS 3 COMPONENT & OPERATIONS (1

1.0	Baffles											
1.1	Material (baffles plates receipt verification & identification	For traceability & co-relation	Major	Visual	100%	As per BHEL forging drawing	Approved Drawing	Inspn. Record	7	R	M	
1.2.0	IN PROCESS											
1.2.1	Drilling Procedure Qualification	Drilling Procedure Qualification by Drilling holes on Test block	Major	Visual & Meas.	100%	Approved Drawing/ Approved Procedure	Approved Drawing/ Approved Procedure	Inspn. Record	7	Ч	≫ R	BHEL shall supplies the Test block
1.2.2	Baffles Plates	a.One hole Drilling Mockup on test block on Operator or tool change or machine restart	Major	Visual & Meas.	100%	Approved Drawing/ Approved Procedure	Approved Drawing/ Approved Procedure	Inspn. Record	7	P	- M	
		b.Dimn. Conformity including hole size (by Go & No-Go gauge), ligament & Surface finish.	Major	Visual & Meas	100%	Approved Drawing	Approved Drawing	Inspn. Record	>	<u>م</u>	**	*Gauging to be done 100% *3% control hole size to be recorded Review/Verificati on of Dimension at any suitable stage will be carried out by BARC.
		c. Tie rod holes	Major	Visual & Meas.	100%	Approved Drawing	Approved Drawing	Inspn. Record	>	Ь	W R	

हरिसन मीजा / HARIMAN MEENA प्रचंदक / Manager एच.सी.एम. विभाग / HCM Division बी.एच.ई.एल.. भोपाल / BHEL, BHOPAL





एस एस मडावी / S. S. MADAVI अपर महाप्रबंधक / AGM एब. सी.एम. विभाग / H.C.M. Division बी.एच.ई.एल., भोपाल / B.H.E.L., Bh.DPAL

SL.

BHARAT HEAVY ELECTRICALS LTD., BHOPAL

PAGE: 3 OF **REV. NO. 02** 34 MW HEAVY-WATER/PROCESS-WATER SHELL & TUBE TYPE HEAT EXCHANGER

(BARC, TROMBAY, MIMBAL) Baffles Drilling Drawing Nos.-11650340920.

DATE: 03 09 2024 (BARC. TROMBAY, MUMBAI) Baffles Drilling Drawing Nos.-11650340920.

	REMARKS 11	
		C
	AGENCY ** 10	В
	AGE! ** 10	M
		Q *
C IC C ICUIT FOR COSC : TIME	FORMAT OF RECORD	6
TIVE	ACCEPTANCE NORMS	8
ming pramagators-recorded to the form	REFERENCE DOCUMENT	7
mig ziamme i	QUANTUM OF CHECK	9
	TYPE OF CHECK	w
	CLASS	4
(Elizabeth) incomes of the control o	CHARACTERISTICS	3
	COMPONENT & OPERATIONS	2
	; 0	

To be done at	BHEL		
ı			
M			
Ь			
>			
Inspn.	Record		
Approved Drawing/	Approved	Procedure	
Approved	Drawing/	Approved	Procedure
100%			
Visual	& Meas		
Major			
Final baffle machining after	shell rolling as per shell	dimension	

- LATEST REVISIONS OF BHEL SPECIFICATIONS SHALL APPLY.
- IN QUANTUM OF CHECK COLUMN, QUANTUM OF CHECK IS SAME FOR M, C, UNLESS OTHERWISE SPECIFIED.
 - ALL MEASURING INSTRUMENT SHOULD BE CALIBRATED.
 - LATEST APPROVED DRAWING SHALL BE FOLLOWED. 3
- IN CASE OF ANY REPAIR, decision for repair shall be taken with prior approval from BARC. 4. v.

जितेन्द्र सिंह / JITENDRA SINGH

एच.सी.एम. विभाग/H.C.M. Division बी.एच.ई.एल.. मोपाल/B.H.E.L., BROPAL एस एस मडावी / S. S. MADAVI अपर महाप्रबंधक / AGM

की एच ई एत.. भोपाल / В.Н.Е.L., BHOPAL

क्यू ते. एव. / ОТН (ОА & QC) प्रबंधक / Manager

¶.एच.ई.एल., भोपाल / BHEL. BHOPAL एच. सी. एम. विभाग / HCM Division प्रबंधक / Manager

613057/2024/HEP-HCM21100 PRE-QUALIFICATION REQUIREMENT(PQR) FOR BAFFLES PLATE DRILLING OF BARC -34MW Heavy Water Heat Exchanger

Date: 28/09/2024

S.No.	DESCRIPTION	Requirement	Bidder's Response
1.	Traders / agents are not allowed to participate	 Manufacturers/vendors who are owners of at least one in house CNC drilling Machine or CNC deep Hole drilling machine facility are allowed to quote. Offers of parties who are traders, authorized dealers and third parties would not be considered. 	YES / NO – Bidder to submit undertaking clearly stating they are not trader.
2.	Details of past experience in Drilling of baffle plates of similar nature including job executed OR under progress, in the last five years from date of issuing enquiry. No exemptions shall be given to MSE /Start up enterprises in technical evaluation of PQR.	PO Copy & Job Completion Certificate/any document mentioning successful completion of Job/mail mentioning Job Completion with Dimension.	Vendor to confirm & provide invoice/ any correlated documents and link PO copy
3.	In house facility of CNC Drilling Machine suitable for Drilling of CS baffle of holes	 Shall produce the job as per attached drg. no. 11650340920, R-01, drilling procedure & QAP. Baffles Hole dia. 9.96^{+0.1} mm and 16 mm depth (min. or higher) & accommodating Job with Outer Tube Limit (OTL) 1587.7 mm. Positional accuracy: ±0.1mm(within) All the holes shall be rounded off to a radius of 1.0-2.0 mm on the both the side. 	Vendor to confirm suitability/capability/assurance of machine as per job requirements.
3.1	Make		Vendor to Specify
3.2	Quantity	Minimum 1 No. Machine Required	Vendor to Specify and confirm
3.3	Capacity X Axis(Horizontal)	Minimum 2500 mm.	Vendor to Specify & Confirm
3.4	Capacity Y Axis(Vertical)	Minimum 1800 mm.	Vendor to Specify & confirm
3.5	Capacity Z Axis(Axial)	Minimum 200 mm.	Vendor to Specify & confirm
3.6	Accuracy (Positional & Repetitive)	Positional accuracy: ±0.1mm(within)	Vendor to furnish latest Calibration report.
4.0	Pre-requisite	a. CNC drilling Machine or CNC deepHole drilling machine.b. Fixture for mounting the job	Vendor to confirm that which machine he will use Vendor to Note
		d. Internal Micrometer for Hole size measurement /dial gauge.	Vendor to confirm
		e. Go-No-Go Gauge	Vendor to confirm
		f. Ligament Gauge	Vendor to confirm

lar,

R

Year.

PRE-QUALIFICATION REQUIREMENT(PQR) FOR BAFFLES PLATE DRILLING OF BARC -34MW Heavy Water Heat Exchanger

Date:28/09/2024

5.0	Certification	All machines and Instruments used	Vendor to confirm
		should have valid calibration certification	
		by NABL accredited agency.	

Note:

- a. After satisfactory, fulfilment of the all the above criteria/requirement, offer shall be considered for further evaluation as per NIT and all other terms of the tender.
- b. All documentary evidences along with this PQR shall be duly signed and stamped by authorized person.
- c. BHEL reserves the right to verify the information submitted by the vendor. In-case any information is found to false or incorrect the offer shall be rejected. Moreover, in later stages after placement of Purchase order if any information given by Vendor found false /incorrect then BHEL may take any action against the vendor as per BHEL policies and guidelines.
- d. After successful qualification against PQR, credentials shall be submitted to BHEL/BARC for approval. Consideration for the placement of order is subject to technical compliance of BARC requirement and BARC approval to vendor.
- e. BHEL will assumed that vendor has understand & have full clarity of all our technical requirement.

Prepared by

हरिमन मीजा / HARIMAN MEENA प्रबंधक / Manager एच.सी.एम. विमाग / HCM Division बी.एच.ई.एल., भोपाल / BHEL, BHOPAL checked by

पंकज निमर्ज / PANKAJ NIMJE उप महाप्रबंधक / DGM एच. सी. एम. विभाग / HCM Division बी.एच.ई.एल., भोपाल / B.H.E.L., BHOPAL Approved by

एस एस मडावी / S. S. MADAVI अपर महाप्रबंधक / AGM एव. सी. एम. विभाग / H.C.M. Division

एच. सी. एम. विभाग/H.C.M. Division बी.एच.ई.एल., भोपाल/B.H.E.L., BHOPAL